


| | |
|-------------------------------|--|
| Sales Region | Worldwide (except Japan) |
| Series | DRB |
| Model | DRB240 |
| Status |  Production |
| Feature | |
| Options | |
| Option Lineup | Please refer to here. |
| Recommended EMC Filter | |
| Accessories | Please refer to here. |
| Brand | TDK-Lambda |



Electrical Characteristics

| | |
|--------------------------|---------------|
| Input | Single-phase |
| Input Voltage Range[AC] | 85 to 264Vac |
| Input Voltage Range[DC] | |
| Efficiency | 92% Typ. |
| Rated Output Voltage[DC] | 48Vdc |
| Output Voltage Range[DC] | 48 to 52.8Vdc |
| Maximum Output Current | 5A |
| Maximum Average Current | |
| Maximum Peak Current | 6A |
| Maximum Output Power | 240W |
| Maximum Average Power | |
| Maximum Peak Power | 288W |

Package Type & Size

| | |
|------------------------|--------------------------|
| Package / Mounting | DIN rail |
| Industry Standard Size | |
| Width(W) | 41mm Nom. (1.61in Nom.) |
| Height(H) | 124mm Nom. (4.88in Nom.) |
| Depth(D) | 125mm Nom. (4.92in Nom.) |
| Weight | 750g Typ. (1.7lbs Typ.) |

Other

| | |
|-----------------------|-------------|
| Operating Temp. Range | -25 to 70°C |
| Cooling | Convection |

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

| | |
|----------------------------|---|
| Safety Standard(Certified) | CSA60950-1 EN60950-1 UL60950-1 UL508 UL1310 Class 2 |
| Safety Standard(Conformed) | |
| Remarks | This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions. |
