

CUSTOMER: \_\_\_\_\_

DATE: \_\_\_\_\_

## APPROVAL SPECIFICATION

PRODUCT NAME: SMD power inductor

YOUR PART NO. :

OUR PART NO. : MPIT6028 Series

VERSION: V2.0

RECEPTION THE SPECIFICATION HAS BEEN ACCEPTED.  DATE:  COMPANY:		
CFMD	CHKD	RCVD

### MANUFACTURING NAME

深圳市麦捷微电子科技股份有限公司  
 SHENZHEN MICROGATE TECHNOLOGY CO., LTD  
 Address: Yuxing road, Golf Street, Guanlan Town  
 Bao' an District Shenzhen P. R. C  
 Postcode :518110  
 TEL: 86-755-28085000  
 FAX: 86-755-28085605

CFMD.	CHKD.	DSGD.
Charles	王玉生	刘维

## 目录 CATALOG

	规格书版本控制 Component SPEC Version Record.....	3
1	适用范围 Scope.....	4
2	品名构成 Product Identification.....	4
3	形状、尺寸和材料 Appearance, Dimensions and Material.....	4
4	测试条件 Testing Conditions.....	4
5	电气特性 Electrical Characteristics And Test Instruments.....	5
6	工作条件 Condition of work.....	5
7	信赖性试验 Reliability and Test Condition.....	6-7
8	焊接条件 Recommended Soldering Conditions.....	8-9
9	包装 Package Information.....	9-10
10	产品外观检查标准 Visual inspection standard of product.....	10
11	存贮条件 Products Storage.....	11

**Component SPEC Version Record**

Rev.	Effective Date	Changed Contents	Change Reasons	Approved By
1.0	Dec. 10.2012	New released	/	Charles
2.0	JUL. 31.2014	Change the Electrical Characteristics	The Electrical Characteristics improved	Charles

## 1. Scope

This specification applies to the MPIT6028 series of SMD power inductor.


## 2. Product Identification

MPIT 6028 – 4R7 M 31– LF  
① ② ③ ④ ⑤ ⑥

- ① Product Symbol (T type SMD power inductor)
- ② Product dimensions (6.0×6.0×2.8mm)
- ③ Inductance Value: (4R7: 4.7uH 100: 10uH; 101: 100uH)
- ④ Inductance Tolerance: (M: ±20% ; N: ±30%)
- ⑤ Process code
- ⑥ Lead free product.

## 3. Appearance, Dimensions and Material

### 3.1 Appearance and dimensions




Recommended Land Pattern

Dimensions in mm								
Model	A	B	C	D	E	f	g	h
MPIT6028	6.0±0.3	6.0±0.3	2.8 Max.	1.5±0.3	3.0±0.3	5.7Typ.	1.6Typ.	4.7 Typ.

### 3.2 Material List

No.	Item	Material
1	Core	Ni-Zn Ferrite
2	Wire	Enameled Copper Wire
3	Terminal Electrode	Ag/Ni/Sn/Cu
4	Magnetic Glue	Epoxy resin and magnetic powder



## 4. Testing Conditions

Unless otherwise specified

Temperature : Ordinary Temperature ( 5 to 35°C)

Humidity : Ordinary Humidity (25 to 85% RH)

Atmospheric Pressure : 86 to 106 kPa

In case of doubt

Temperature : 20±2°C

Humidity : 60 to 75% RH

Atmospheric Pressure : 86 to 106 kPa

深圳市麦捷微电子科技股份有限公司

地址：深圳市宝安区观澜镇高尔夫大道裕新路

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

## 5. Electrical Characteristics And Test Instruments

Microgate Part No.	Customer Part No.	Inductance	DCR	Isat	Irms
		( $\mu$ H)	( $\Omega$ ) $\pm 30\%$	(A)	(A)
MPIT6028-1R0M31-LF		1.0 $\pm 20\%$	0.010	5.75	5.20
MPIT6028-1R5M31-LF		1.5 $\pm 20\%$	0.013	6.00	4.58
MPIT6028-1R8M31-LF		1.8 $\pm 20\%$	0.016	5.50	4.10
MPIT6028-2R2M31-LF		2.2 $\pm 20\%$	0.020	5.10	3.75
MPIT6028-2R7M31-LF		2.7 $\pm 20\%$	0.020	3.80	3.75
MPIT6028-3R3M31-LF		3.3 $\pm 20\%$	0.025	4.15	3.48
MPIT6028-4R7M31-LF		4.7 $\pm 20\%$	0.030	3.00	3.08
MPIT6028-5R1M31-LF		5.1 $\pm 20\%$	0.043	3.20	2.60
MPIT6028-6R2M31-LF		6.2 $\pm 20\%$	0.047	3.05	2.40
MPIT6028-6R8M31-LF		6.8 $\pm 20\%$	0.047	2.60	2.40
MPIT6028-8R2M31-LF		8.2 $\pm 20\%$	0.055	2.30	2.25
MPIT6028-9R1M31-LF		9.1 $\pm 20\%$	0.074	2.55	2.15
MPIT6028-100M31-LF		10 $\pm 20\%$	0.072	2.04	1.95
MPIT6028-120M31-LF		12 $\pm 20\%$	0.080	1.80	1.85
MPIT6028-150M31-LF		15 $\pm 20\%$	0.125	1.75	1.45
MPIT6028-180M31-LF		18 $\pm 20\%$	0.120	1.52	1.45
MPIT6028-220M31-LF		22 $\pm 20\%$	0.140	1.45	1.40
MPIT6028-270M31-LF		27 $\pm 20\%$	0.155	1.50	1.32
MPIT6028-330M31-LF		33 $\pm 20\%$	0.185	1.35	1.22
MPIT6028-360M31-LF		36 $\pm 20\%$	0.215	1.25	1.13
MPIT6028-390M31-LF		39 $\pm 20\%$	0.225	1.25	1.10
MPIT6028-470M31-LF		47 $\pm 20\%$	0.315	1.15	1.06
MPIT6028-680M31-LF		68 $\pm 20\%$	0.360	0.80	0.86
MPIT6028-750M31-LF		75 $\pm 20\%$	0.410	0.90	0.81
MPIT6028-820M31-LF		82 $\pm 20\%$	0.500	0.80	0.70
MPIT6028-101M31-LF		100 $\pm 20\%$	0.500	0.65	0.70

### Test instruments and remarks

\* CHROMA 3302 meter for L and DCR/CHROMA 3302 and 1320 meter for IDC;

\* L test condition: 100KHz & 1V at 20°C ambient;

\* Rated current: Isat or Irms, whichever is smaller:





<sup>1</sup>:Isat: direct current at which the inductance drops approximate 30% from its value without current.



<sup>2</sup>:Irms: direct current when the temperature of the product rise ( $\Delta T = 40^\circ\text{C}$ ) from 20 °C ambient.

## 6. Condition of work

Operating temperature range:  $-25^\circ\text{C} \sim +120^\circ\text{C}$ .(Including self-heating)

### 7. Reliability and Test Condition

Item	Required Characteristics	Test Method/Condition
High temperature resistance		<p>Temperature: <math>125 \pm 2^\circ\text{C}</math>            Time : 1000 hours            Tested not less than 1 hours, nor more than 2 hours at room temperature.</p> 
Low temperature resistance	<ol style="list-style-type: none"> <li>1. No case deformation or change in appearance.</li> <li>2. <math> \Delta L /L \leq 10\%</math></li> </ol>	<p>Temperature : <math>-40 \pm 2^\circ\text{C}</math>            Time : 1000 hours            Tested not less than 1 hour, nor more than 2 hours at room temperature.</p> 
Humidity test		<ol style="list-style-type: none"> <li>1. Exposure : Temperature: <math>60 \pm 2^\circ\text{C}</math>, Humidity : <math>93 \pm 3\%</math> RH Time : 1000 hours.</li> <li>2. Tested while the specimens are still in the chamber.</li> <li>3. Tested not less than 1 hour, nor more than 2 hours at room temperature.</li> </ol> 
Thermal shock test	<ol style="list-style-type: none"> <li>1. No case deformation or change in appearance.</li> <li>2. <math> \Delta L /L \leq 10\%</math></li> </ol>	<p>First <math>-40^\circ\text{C}</math> for T time, last <math>125^\circ\text{C}</math> T time as 1 cycle. Go through 100 cycles.</p> 

Item	Required Characteristics	Test Method/Condition
Solderability test	Terminal area must have 90% min. solder coverage.	Dip pads in flux then dip in solder pot at $245 \pm 5^\circ\text{C}$ for $<5$ second. Solder: lead free Flux: rosin flux.
Heat endurance of reflow soldering		Refer to the next page reflow curve Go through 3 times. The peak temperature: $260+5/-0^\circ\text{C}$
Vibration test	1. No case deformation or change in appearance. 2. $ \Delta L /L \leq 10\%$	Apply frequency 10~55Hz. 1.5mm amplitude in each of perpendicular direction for 2 hours in each 3 mutually perpendicular directions.(total 6 hours) 
Drop test		Packaged & drop down from 1m with $981\text{m/s}^2(100\text{G})$ attitude in 1 angle 1 ridges & 2surfaces orientations.
Terminal strength push test	<b>Pulling test:</b> Define: Solder the products on testing PCB using eutectic solder. Then apply a force in the direction of the arrow. 10N force. Keep time $\geq 5\text{s}$  <b>Bending test:</b> Soldering the products on PCB, after the pulling test and bending test, terminal should not pull off.	Bend the testing PCB at middle point, the deflection shall be 2mm. Pressurizing Speed: 0.5mm/sec, Keep time: $30 \pm 1\text{s}$ , 
Resistance to solvent test	No case deformation or change in appearance, or obliteration of marking	To dip parts into IPA solvent for 50.5Min, then drying them at room temp for 5Min., at last, to brushing marking 10 times.
Loading Under Humidity Heat	1. No case deformation or change in appearance. 2. $ \Delta L /L \leq 10\%$	1. Exposure : Temperature: $60 \pm 2^\circ\text{C}$ , Humidity : $93 \pm 3\%$ RH Time : 1000 hours. Apply rated current 2. Tested while the specimens are still in the chamber. 3. Tested not less than 1 hour, nor more than 2 hours at room temperature.
Loading at High Temperature	1. No case deformation or change in appearance. 2. $ \Delta L /L \leq 10\%$	1. Temperature: $85 \pm 2^\circ\text{C}$ 2. Time : 1000 hours 3. Apply rated current 4. Tested not less than 1 hours, nor more than 2 hours at room temperature.

## 8. Recommended Soldering Conditions

Product can be applied to flow and reflow soldering.

### (1) Flux, Solder


① Use rosin-based flux. Don't use highly acidic flux with halide content exceeding 0.2wt% (chlorine conversion value).

② Use Sn solder.

### (2) Flow soldering conditions


① Pre-heating should be in such a way that the temperature difference between solder and product surface is limited to 150°C max. Cooling into solvent after soldering also should be in such a way that temperature difference is limited to 100°C max. Unwrought pre-heating may cause cracks on the product, resulting in the deterioration of products quality.

② Standard soldering profile.



### (3) Reflow soldering conditions

Reflow curve



Profile Feature		Lead-Free Assembly
Average Ramp-Up Rate (Ts max. to Tp)		3°C /second max.
Preheat	- Temperature Min (Ts min.)	150 °C
	- Temperature Max (Ts max.)	200 °C
	- Time (ts min to ts max.)	60-180 seconds
Time maintained above	- Temperature (TL)	217 °C
	- Time (tL)	60-150 seconds
Peak/Classification Temperature (Tp)		260 °C
Peak/Classification Time (Tp)		3-4 seconds
Time within 5 °C of actual Peak Temperature (Tp)		20-40 seconds
Ramp-Down Rate		6 °C/second max.
Time 25 °C to Peak Temperature		8 minutes max.

Note 1: All temperatures refer to topside of the package, measured on the package body surface.

深圳市麦捷微电子科技股份有限公司

地址: 深圳市宝安区观澜镇高尔夫大道裕新路

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

8/11



(4) The method on Re-work with using the iron:


The following conditions must be strictly followed when using a soldering iron

Pre-heating	150°C, 1 minute
Tip temperature	350°C max
Soldering iron output	80w max
End of soldering iron	φ1mm max
Soldering time	3 seconds max

Product once removes from the circuit board may not be used again.


## 9. Package Information

### 9.1 Dimension of tape (Unit: mm)




W	A0	B0	K0	E	F	P	P0	D0	T
12.0±0.3	6.4±0.1	6.4±0.1	3.2±0.1	1.75±0.1	5.5±0.05	8.0±0.1	4.0±0.1	1.50±0.1	0.35±0.05

### 9.2 Dimension of reel (Unit: mm)



### 9.3 Taping figure and drawing direction



深圳市麦捷微电子科技股份有限公司

地址：深圳市宝安区观澜镇高尔夫大道裕新路

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605


邮编(Postcode): 518110

9/11

9.4 Packaging quantities: 2000PCS/Reel.

9.5 Peeling strength of cover tape:

The peel force of top cover tape shall be between 0.15N to 1.0N



Room Temp. (°C)	Room Humidity (%)	Room aim (hpa)	Peel Speed Mm/min
5-35	45-85	860-1060	300

## 10. Visual inspection standard of product

No.	Defect Item	Graphic	Rejection identification	Acceptance
1	Core defect		$l > L/6$ or $w > W/6$ , NG.	AQL=0.65
2	Missing resin		The area of missing resin more than 1/2single face, NG	AQL=0.65
3	Cold solder		L more than 1 mm, NG.	AQL=0.65
4	Solder uneven		$H > 0.1\text{mm}$ . NG.	AQL=0.65

## 11.Products Storage

### (1) Storage period

Products which inspected in MICROGATE over 6 months ago should be examined and used, which can be confirmed with inspection No. marked on the container. Solderability should be checked if this period is exceeded.

### (2) Storage conditions

Products should be storage in the warehouse on the following conditions:

Temperature: -10 ~+ 40°C

Humidity : Less than 80% relative and humidity

No rapid change on temperature and humidity

- (3) Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solderability.
- (4) Products should be storage on the palette for the prevention of the influence from humidity, dust and so on.
- (5) Products should be storage in the warehouse without heat shock, vibration, direct sunlight and so on.
- (6) Products should be storage under the airtight packaged condition.