



'C' Programmable Application Development Module

MVI46-ADM

The MVI46 Application Development Module is an SLC backplane compatible module that allows user-developed 'C' applications to operate on the SLC platform. A great way to speed up custom ASCII data communications or to protect a proprietary algorithm, the ADM is a powerful tool for the SLC platform.

Features and Benefits

Powerful platform for developing and running 'C' applications on Rockwell Automation's SLC processors. The MVI46-ADM module is a single slot, backplane compatible solution for the Rockwell Automation SLC platform. This module is a powerful and programmable solution supporting two fully isolated serial ports allowing the many serial field devices to be integrated into the SLC platform.

The MVI46-ADM module has three serial ports, two of which are isolated for field interfaces:

- CFG: Debug/configuration RS-232
- PRT1: Application RS-232, RS-422 or RS-485
- PRT2: Application RS-232, RS-422 or RS-485

PRT1 and PRT2 are jumper configured for direct or Multi-drop field communication. The application program can be written to control the two application ports independently, allowing maximum flexibility in the design.

General Specifications

- Single Slot – 1746 backplane compatible (Local or extended I/O rack only. Remote rack not supported)
- The module is recognized as an Input/Output module and has access to processor memory for data transfer between processor and module using M0/M1 files
- Ladder Logic is used for data transfer between module and processor
- Configuration data obtained through user-defined ladder. Sample ladder file included

'C' Programmable Application Development Module

MVI46-ADM

The MVI46-ADM module is the ideal solution for many applications where serial connectivity must be added to a SLC platform. Applications using the MVI46-ADM module:

- Bar code scanner interface
- Legacy ASCII protocol connections
- Terminal port emulation
- Printer driver (alarm/status printer)
- Customized protocol implementations

How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English

Hardware Specifications

Specification	Description
Backplane Current Load	800 ma @ 5V (from backplane)
Operating Temperature	0 to 60°C (32 to 140°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Shock	30g operational, 50g non-operational
Relative Humidity	5 to 95% (non-condensing)
Vibration	5 g from 10150 Hz
LED indicators	Module status, Backplane transfer status, Application status, Serial activity and error LED status
Debug/Configuration port (CFG)	
CFG Port (CFG)	RJ45 (DB-9M with supplied cable) RS-232 only
Configuration Connector	RJ45 RS-232 Connector (RJ45 to DB-9 cable shipped with unit)
Application Ports	
Application Serial port (PRT1, PRT2) (Serial Modules)	(2) RJ45 RS-232/422/485 Application ports

Functional Specifications

Development Environment

- Operating system: General software DOS 6-XL
- Compatible compiler (16-bit DOS target)
 - Digital Mars C++ V8.49 (included)
 - Borland C++ V5.02

Application Programming Interfaces (API)

- Serial Port API: serial port functions
- Backplane API: low level backplane functions
- ADM API debug port functions: debug port functions, database functions timer functions, high level backplane transfer functions, LED functions, flash read functions

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Compatible products in the inRAX product line also include:

Generic Serial ASCII Interface Module (MVI46-GSC)

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

To order this product, please use the following:

MVI46-ADM 'C' Programmable Application Development Module

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

Distributors:

Place your order by email or fax to:

North American / Latin American / Asia Pacific

orders@prosoft-technology.com,
fax to +1 661.716.5101

Europe

europe@prosoft-technology.com,
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.
January 23, 2007