# Product data sheet
## Characteristics

# QO260C
## Mini CB, QO, 60 A, 2P, 120/240 V, 10 kA, Plug in

Product availability : Stock - Normally stocked in distribution facility

Price** : 67.00 USD




## Main

| | |
|---|---|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 60 A |
| Voltage Rating | 120/240 V AC<br>120 V AC<br>48 V DC |
| Mounting Type | Plug-in |
| Number of Poles | 2P |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Box lugs |
| Type of packing | Clam packaging |

## Complementary

| | |
|---|---|
| Inturrupt Rating | 10 kA 120/240 V AC 50/60 Hz<br>10 kA 120 V AC 50/60 Hz<br>5 kA 48 V DC |
| Number of Panel Spaces | 2 |
| Wire Size | AWG 8...AWG 2 copper or aluminium |
| Tightening torque | 40.71 lbf.in (4.6 N.m) |
| Height | 79.25 mm (3.12 in) |
| Depth | 73.91 mm (2.91 in) |
| Width | 38.10 mm (1.5 in) |

## Environment

| | |
|---|---|
| Certifications | UL listed<br>CSA |
| Ambient Rating | 104 °F (40 °C) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Ordering and shipping details

| | |
|---|---|
| Category | 01342 - QO 2 POLE CARDED BRKRS. |
| Discount Schedule | CPQ |
| GTIN | 00047569522215 |
| Package weight(Lbs) | 0.29 kg (0.63 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant<br>EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| Halogen content performance | Halogen free product |