



8		7	
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION	
© COPYRIGHT 20		20	
BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.			
ATLANTIC VERSION TERMINATOR INTERFACE ADAPTER	PART NUMBER	REVISION	DESCRIPTION
	2150383-1	A	FINE CRIMP HEIGHT ADJUST
	2150383-2	B	FINE CRIMP HEIGHT ADJUST
	2150383-5	A	FINE CRIMP HEIGHT ADJUST
	2150383-6	A	NON-CRIMP HEIGHT ADJUST
	2150383-7	A	FINE CRIMP HEIGHT ADJUST
	7-2150383-7	A	CRIMP TOOLING KIT

APPLICATOR DATA		
CRIMP	SIZE	TYPE
WIRE	.055 [1.40 mm]	F
INSUL	.140 [3.56 mm]	F
APPL INSTRUCTIONS 408-10390		

TERMINAL DATA: TE TERMINAL		TE CRIMP SPECIFICATION	
TERMINAL NAME: RECEPTACLE, FASTON, .187 SERIES			
WIRE STRIP LENGTH .153-.168 IN [3.87-4.25 mm]			INSULATION DIAMETER RANGE Ø.060-.110 IN [1.52-2.79 mm]
TERMINAL APPLICATION SPECIFICATION	114-2036	-	-
TERMINALS APPLIED			
TE TERMINAL	TE TERMINAL	TE TERMINAL	TE TERMINAL
1217129-1	63372-1	62138-1	62138-2
62138-3			

WIRE SIZE		CRIMP HEIGHT mm [INCH]		CRIMP HEIGHT REFERENCE SETTING
20 AWG OR 0.52mm2		1.22+/-0.000 [.048+/- .000]		4.8
22 AWG OR 0.32mm2		1.09+/-0.000 [.043+/- .000]		6.1
24 AWG OR 0.25mm2		1.02+/-0.000 [.040+/- .000]		6.8




- 1 RECOMMENDED SPARE PARTS
- 2 GREASE BEARING SURFACES LIGHTLY
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.
- 4 APPLICATOR SPECIFIC DATA TO BE ENTERED INTO BLANK MEMORY CHIP AT ASSEMBLY. SEE BELOW FOR PART NUMBER:
MECHANICAL FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150383-4
PNEUMATIC FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150383-4
SERVO FEED WITH "FINE CRIMP HEIGHT ADJUST": 8-2150383-5
SERVO FEED WITH "NON-CRIMP HEIGHT ADJUST": 8-2150383-6
5. ADJUSTMENT OF THE STRIPPER MAY BE REQUIRED WHEN MOVING THE APPLICATOR BETWEEN BENCH AND LEADMAKER APPLICATIONS.
- 6 APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEM 50 & 62.
APPLY PART NUMBER 2-23419-6 LOCTITE TO THREADS OF ITEM 242.
FOR -6 ONLY APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEM 37.
- 7 GREASE THREADS, GROOVE AND O-RING ON ITEMS 35 & 252.
- 8 MAGNET, ITEM 166 MUST BE ORIENTED CORRECTLY IN ORDER TO PROPERLY ACTUATE THE COUNTER.
- 9 CRIMP HEIGHT REFERENCE SETTING WAS THE SETTING USED WHEN THE APPLICATOR WAS QUALIFIED AT THE FACTORY. ADJUSTMENT MAY BE NECESSARY WHEN RUNNING APPLICATOR IN THE FIELD.
- 10 SPARE FEED CAM STORAGE LOCATION REFER TO INSTRUCTION SHEET FOR ADDITIONAL INFORMATION.
- 11 THE RECOMMENDED SET-UP FOR END FEED APPLICATORS IS POST-FEED WITH ITEM 2119653-1. THE APPLICATOR CAN BE CONFIGURED FOR PRE-FEED WITH ITEM 2119652-1 BUT MAY ENCOUNTER PROBLEMS WITH SOME APPLICATIONS. FEED ISSUES OR TERMINAL JAMMING MAY OCCUR IN THE PRE-FEED CONFIGURATION.
- 12 WHEN ASSEMBLING -6 NON-CRIMP HEIGHT ADJUST APPLICATOR USE SHIM PACK 2119957-2 TO ALIGN APPLICATOR'S MAXIMUM WIRE CRIMP HEIGHT AT NORMAL TERMINATOR SHUT HEIGHT


2	-	-	1	-	-	-	2119957-2	APPLICATOR SHIM PACK	260
7	-	1	-	1	1	1	8-21084-0	O-RING, .676 ID, .070 DIA. MAT.	252
	-	-	-	-	1	-	2119640-1	PUSH ROD, AIR FEED	250
	-	-	-	-	1	-	2079988-1	BUSHING, LCH5-12, MISUMI	249
	-	-	-	-	1	-	2119641-1	FEED CAM, AIR FEED	248
	-	1	-	1	1	1	2119798-1	DETENT PIN	247
	-	1	-	1	1	1	1-22279-3	SPRING, COMPRESSION	246
	-	-	1	-	-	-	2119759-1	RAM, AMP STYLE, END FEED, NON-ADJUST	245
	-	1	1	1	1	1	2119082-9	CAM, SNAIL, INSULATION ADJUSTMENT	244
-77	-7	-6	-5	-2	-1		PART NO	DESCRIPTION	ITEM NO

*WARNING
ON INSTALLATION, SET WIRE DISC, ITEM 40 TO LARGEST WIRE SIZE SETTING. USE OF SETTINGS BELOW MINIMUM REQUIRED CRIMP HEIGHT SETTING WILL CAUSE DAMAGE TO CRIMP TOOLING.


SET UP GAUGE 2119599-2	LOC A	DIST 66	REVISIONS				
			P	LTR	DESCRIPTION	DATE	DWN
				B	ECR-16-004882	04APR2016	MR

-	1	1	1	1	1	2079764-1	WASHER, WAVE SPRING, CREST-TO-CREST	243
-	1	1	1	1	1	2119083-1	RETAINER, INSULATION DIAL	242
-	-	2	2	-	-	2168400-7	SHCS, LOW HEAD, RoHS, M5 X 10	240
-	-	-	-	-	1	2119580-1	MECHANICAL FEED ASSEMBLY	239
-	-	-	-	1	-	2063440-1	AIR FEED MODULE	238
-	-	1	1	-	-	2119740-2	TAG, IDENTIFICATION	213
-	-	REF	REF	-	-	1901697-1	FEED FINGER ASSEMBLY, EF	183
-	1	1	1	1	1	6-993111-6	PIN, SLOTTED SPRING 3.0 X 14.0	177
-	1	1	1	1	1	8-22280-7	SPRING, COMPRESSION	176
-	1	1	1	1	1	1752353-2	GUIDE PIN, HOLDDOWN	175
-	1	1	1	1	1	1901680-2	GUIDE PIN, HOLDDOWN	174
-	-	-	-	2	-	21045-3	RING, RETAIN, EXTERN, 3/16 CRESCENT	172
-	1	1	1	1	1	994969-1	MAGNET, RARE EARTH HIGH ENERGY	166
-	REF	REF	REF	REF	REF	994970-2	COUNTER, MAGNETIC	164
-	-	-	-	1	-	240638-1	SPRING, FEED FINGER	163
-	-	-	-	1	-	3-23627-7	PIN, RETAIN, GRVD, 3/16 X .854	137
-	-	REF	REF	-	-	SEE NOTE 4	MEMORY CHIP, PROGRAMMED	135
-	-	1	1	-	-	1633743-1	SERVO FEED LATCH ASM	133
-	1	1	1	1	1	455888-5	SPACER, CRIMPER	82
-	1	1	1	1	1	2119791-5	DEPRESSOR, WIRE	73
-	1	1	1	1	1	2119956-2	DOCUMENTATION PACKAGE	71
-	2	2	2	2	2	2-18032-2	SCR, SET, FLT POINT M3 X 10.0	70
-	1	-	-	1	1	2119740-1	TAG, IDENTIFICATION	67
-	2	2	2	2	2	2168078-1	SCREW, DRIVE, RH, RoHS, 2 x .188	66
-	1	1	1	1	1	1-1901681-8	HOLDDOWN, TERMINAL	65
-	2	2	2	2	2	2168400-5	SHCS, LOW HEAD, RoHS, M4 X 20	64
-	1	-	1	1	1	2119793-1	LIMITER, ADJUSTMENT BOLT	63
-	3	-	3	3	3	992763-5	SCR, SET, SOC, CONE POINT, M3 x 4.0	62
-	1	1	1	1	1	2079383-4	SCR, BHSC, RoHS (M4 X 8)	60
-	-	-	-	-	1	5-18022-5	SCR, HEX HD CAP, M4 X 6.0	59
-	-	-	-	-	1	2063961-1	FEED FINGER	58
-	3	3	3	3	3	2168400-4	SHCS, LOW HEAD, RoHS, M4 X 8	57
-	2	2	2	2	2	2168083-2	SCR, SKT HD CAP, RoHS, M4 X 8.0	56
-	2	2	2	2	2	5018030-2	NUT, HEX, REG, RoHS, M4	55
-	2	2	2	2	2	5018030-1	NUT, HEX, REG, RoHS, M3	54
-	2	2	2	2	2	986965-8	NUT, LOCK, HEX, TORQUE (M4)	53
-	1	1	1	1	1	1-5018030-0	NUT, HEX, REG, RoHS, M3.5	52
-	-	-	-	1	-	2119792-2	PAWL, EF, AIR	51
-	1	1	1	1	1	1752354-6	STANDOFF, HOLD-DOWN	50
-	-	-	-	1	2	18023-9	SCR, SKT HD CAP M4 X 6.0	49
-	-	-	-	-	1	2119652-1	FEED CAM, PRE FEED	48
-	-	-	-	-	1	2119653-1	FEED CAM, POST FEED	47
-	1	1	1	1	1	2119655-5	APPLICATOR BASIC ASSEMBLY, EF	46
-	1	-	1	1	1	2119369-1	RAM, AMP STYLE, END FEED	44
-	1	1	1	1	1	2079383-7	SCR, BHSC, RoHS (M8 X 25)	41
-	1	-	1	1	1	2119645-1	DISC, NUMBERED FA WIRE ADJUSTMENT	40
-	1	-	1	1	1	2119957-1	APPLICATOR SHIM PACK	39
-	1	1	1	1	1	2119644-1	RAM WASHER, PRECISION	38
-	1	1	1	1	1	2119085-1	FA HEAD, ATLANTIC STYLE	37
-	1	-	1	1	1	2119092-1	BOLT, ADJUSTMENT	35
-	7	7	7	7	7	1-18028-2	WASHER, FLAT, REG M4	33
-	2	2	2	2	2	2168083-9	SCR, SKT HD CAP, RoHS, M4 X 20	31
-	2	2	2	2	2	1-2168083-0	SCR, SKT HD CAP, RoHS, M4 X 10	29
-	1	1	1	1	1	240639-1	STRIPPER (MACHINING)	27
-	2	2	2	2	2	1320906-1	STUD, THREADED	25
-	1	1	1	1	1	1752371-5	PLATE, STRIP GUIDE	24
-	1	1	1	1	1	240825-7	PLATE, STRIP HOLD DOWN	23
-	2	2	2	2	2	2-22281-3	SPRING, COMPRESSION	22
-	1	1	1	1	1	1752373-4	DRAG	20
-	2	2	2	2	2	1901259-5	GUIDE, LOWER STRIP	18
-	4	4	4	4	4	1-2079383-1	SCR, BHSC, RoHS (M6 X 12)	17
-	1	1	1	1	1	1752360-1	SPACER, HOLD-DOWN	13
-	1	1	1	1	1	240644-1	PLATE, REAR SHEAR	11
-	-	-	-	-	-	-	-	10
-	1	1	1	1	1	690482-6	PLATE, FRONT SHEAR	9
1	1	1	1	1	1	3-1803000-7	ANVIL, COMBINATION, END FEED	8
-	1	1	1	1	1	2217206-4	BLADE, SLUG	7
-	-	-	-	-	-	-	-	6
-	1	1	1	1	1	240641-5	SPACER	5
-	1	1	1	1	1	238009-1	BLOCK, FL CRIMPER SPACER	4
1	1	1	1	1	1	5-2119582-2	CRIMPER, INSULATION F PREMIUM	3
-	1	1	1	1	1	455888-1	SPACER, CRIMPER	2
1	1	1	1	1	1	456402-2	CRIMPER, WIRE PREMIUM	1
-77	-7	-6	-5	-2	-1	PART NO	DESCRIPTION	ITEM NO


THIS IS SUBJECT TO CHANGE AND NOT BE USED FOR PRODUCTION PURPOSES. ANY CHANGES TO THIS DRAWING MUST BE APPROVED BY THE DESIGNING ORGANIZATION. CHANGES BE CONTACTED FOR THE LATEST REVISION.				DWN R. STAKEM	18OCT2013	 TE Connectivity Harrisburg, PA 17105-3608			
				CHK G. BAILEY	18OCT2013				
				APVD T. ELBIN	18OCT2013	NAME Ocean End Feed Applicator			
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		SIZE			
mm		0 PLC ±.01 1 PLC ±.01 2 PLC ±.01 3 PLC ±.01 4 PLC ±.01 ANGLES ±.01		APPLICATION SPEC		CASE CODE		DRAWING NO	
MATERIAL		FINISH		WEIGHT		A 00779		C=2150383	
				Customer Accessible Production Drawing		SCALE		1:1	
						SHEET		1 OF 4	
						REV		B	






HOLDDOWN SET-UP



FEED TYPE
MECHANICAL





PNEUMATIC

SERVO
LATCH PLATE

ATLANTIC VERSION

Shown on sheets 1 of 4 & 2 of 4
(Pacific version shown on sheets 3 of 4 & 4 of 4)

THIS DRAWING IS A CONTROLLED DOCUMENT FOR ISO/IEC CERTIFICATION CONFORMANCE THIS IS SUBJECT TO THE TERMS AND CONDITIONS OF THE CERTIFICATION PROGRAM SHOULD BE CONTACTED FOR THE LATEST REVISION		DWN K STAKEM 180C12013	 TE Connectivity Harrisburg, PA 17105-3608
DIMENSIONS: mm		CHN G BAILEY 180C12013	
TOLERANCES UNLESS OTHERWISE SPECIFIED: mm		APVD T ELBIN 180C12013	
		NAME Ocean End Feed Applicator	
MATERIAL -		APPLICATION SPEC -	SIZE A1
FINISH -		WEIGHT -	CASE CODE 00779
		DRAWING NO C-2150383	RESTRICTED TO -
		Customer Accessible Production Drawing	SCALE 1:1
		SHEET 2 OF 4	REV B

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.


RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

PACIFIC VERSION
TERMINATOR
INTERFACE ADAPTER



PART
NUMBER

2-2150383-1

REVISION

A

DESCRIPTION

FINE CRIMP HEIGHT ADJUST

FEED TYPE

MECHANICAL

CONVERT TO

PNEUMATIC FEED

PART NUMBERS REQUIRED

2119950-1

2119792-2

-

2119641-2

-

2063440-1

2119951-1

1901697-1

8-2150383-5

2161326-1

-

8-2150383-4

MECHANICAL FEED

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

SERVO LATCH PLATE

2119951-1

1901697-1

8-2150383-5

-

-

2168400-7 (QUANTITY 2)

SMART APPLICATOR

2161326-1

-

8-2150383-4

-

-

-

MECHANICAL FEED

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

PNEUMATIC FEED

2119950-1

2119792-2

-

2119641-2

-

2063440-1

-

-

-

-

-

-

-

-

-

-

-

-

-

-

2119950-1

2119792-2

-

2119641-2

-

2063440-1

-

-

-

-

-

-

-

-

-

-

-

-

-

-

APPLICATOR DATA

CRIMP

SIZE

TYPE

WIRE

.055 [1.40 mm]

F

INSUL

.140 [3.56 mm]

F

APPL INSTRUCTIONS

408-10390




TERMINAL DATA: TE TERMINAL

TE CRIMP SPECIFICATION


TERMINAL NAME: RECEPTACLE, FASTON, .187 SERIES

WIRE STRIP LENGTH



.153-.168 IN [3.87-4.25 mm]

INSULATION DIAMETER RANGE



Ø.060-.110 IN [1.52-2.79 mm]

TERMINAL APPLICATION SPECIFICATION

114-2036

-

-

-

-

-

TERMINALS APPLIED

TE TERMINAL

TE TERMINAL

TE TERMINAL

TE TERMINAL

1217129-1

63372-1

62138-1

62138-2

62138-3

WIRE SIZE





CRIMP HEIGHT mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



20 AWG OR 0.52mm2

1.22+/-0.000 [.048+/- .000]

4.8

22 AWG OR 0.32mm2

1.09+/-0.000 [.043+/- .000]

6.1

24 AWG OR 0.25mm2

1.02+/-0.000 [.040+/- .000]

6.8



RECOMMENDED SPARE PARTS

GREASE BEARING SURFACES LIGHTLY

3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

4. APPLICATOR SPECIFIC DATA TO BE ENTERED INTO BLANK MEMORY CHIP AT ASSEMBLY. SEE BELOW FOR PART NUMBER:
MECHANICAL FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150383-4
PNEUMATIC FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150383-4
SERVO FEED WITH "FINE CRIMP HEIGHT ADJUST": 8-2150383-5

5. ADJUSTMENT OF THE STRIPPER MAY BE REQUIRED WHEN MOVING THE APPLICATOR BETWEEN BENCH AND LEADMAKER APPLICATIONS.

6. APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEM 50 & 62.
APPLY PART NUMBER 2-23419-6 LOCTITE TO THREADS OF ITEM 242.

GREASE THREADS, GROOVE AND O-RING ON ITEMS 139 & 153.

8. MAGNET, ITEM 166 MUST BE ORIENTED CORRECTLY IN ORDER TO PROPERLY ACTUATE THE COUNTER.

9. CRIMP HEIGHT REFERENCE SETTING WAS THE SETTING USED WHEN THE APPLICATOR WAS QUALIFIED AT THE FACTORY. ADJUSTMENT MAY BE NECESSARY WHEN RUNNING APPLICATOR IN THE FIELD.

10. SPARE FEED CAM STORAGE LOCATION REFER TO INSTRUCTION SHEET FOR ADDITIONAL INFORMATION.

11. THE RECOMMENDED SET-UP FOR END FEED APPLICATORS IS POST-FEED WITH ITEM 2119653-2. THE APPLICATOR CAN BE CONFIGURED FOR PRE-FEED WITH ITEM 2119652-1 BUT MAY ENCOUNTER PROBLEMS WITH SOME APPLICATIONS. FEED ISSUES OR TERMINAL JAMMING MAY OCCUR IN THE PRE-FEED CONFIGURATION.

-

1

1

1

1

2119782-1

FINE ADJUST HEAD ASM, PACIFIC STYLE

251

-

-

-

1

-

2119640-1

PUSH ROD, AIR FEED

250

-

-

-

1

-

2079988-1

BUSHING, LCH5-12, MISUMI

249

-

1

1

1

1

1-22279-3

SPRING, COMPRESSION

246

-

1

1

1

1

2119082-9

CAM, SNAIL, INSULATION ADJUSTMENT

244

-

1

1

1

1

2079764-1

WASHER, WAVE SPRING, CREST-TO-CREST

243

-

1

1

1

1

2119083-1

RETAINER, INSULATION DIAL

242

-77-27-25-22-21

PART NO

DESCRIPTION

ITEM NO

PACIFIC VERSION

Shown on sheets 3 of 4 & 4 of 4

(Atlantic version shown on sheets 1 of 4 & 2 of 4)

SET UP GAUGE

2119599-2

LOC

A

DIST

66

P

LYR

-

SEE SHEET 1

-

-

2

-

-

2168400-7

SHCS, LOW HEAD, RoHS, M5 X 10

240

-

-

-

-

1

2119580-1

MECHANICAL FEED ASSEMBLY

239

-

-

-

-

1

2063440-1

AIR FEED MODULE

238

-

-

1

-

-

2119740-2

TAG, IDENTIFICATION

213

-

4

4

4

4

2079383-9

SCR, BHSC, RoHS (M6 X 20)

186

-

-

REF

-

-

1901697-1

FEED FINGER ASSEMBLY, EF

183

-

1

1

1

1

6-993111-6

PIN, SLOTTED SPRING 3.0 X 14.0

177

-

1

1

1

1

8-22280-7

SPRING, COMPRESSION

176

-

1

1

1

1

1752353-2

GUIDE PIN, HOLDDOWN

175

-

1

1

1

1

1901680-2

GUIDE PIN, HOLDDOWN

174

-

-

-

2

-

21045-3

RING, RETAIN, EXTERN, 3/16 CRESCENT

172

-

1

1

1

1

994969-1

MAGNET, RARE EARTH HIGH ENERGY

166

-

REF

REF

REF

REF

994970-2

COUNTER, MAGNETIC

164

-

-

-

1

-

240638-1

SPRING, FEED FINGER

163

-

1

1

1

1

8-21084-1

O-RING, .801 ID, .070 DIA. MAT.

153

-

-

-

1

-

2119641-2

FEED CAM, AIR FEED

152

-

1

1

1

1

2119798-2

DETENT PIN

145

-

1

1

1

1

2079383-8

SCR, BHSC, RoHS (M4 X 16)

144

-

-

-

-

1

2119653-2

FEED CAM, POST FEED

142

-

1

1

1

1

2119655-6

APPLICATOR BASIC ASSEMBLY, EF

141

-

1

1

1

1

2119651-1

RAM, ASIAN STYLE, END FEED

140

-

1

1

1

1

2119092-2

BOLT, ADJUSTMENT

139

-

-

-

1

-

3-23627-7

PIN, RETAIN, GRVD, 3/16 X .854

137

-

-

REF

-

-

SEE NOTE 4

MEMORY CHIP, PROGRAMMED

135

-

-

1

-

-

1633743-1

SERVO FEED LATCH ASM

133

-

1

1

1

1

455888-5

SPACER, CRIMPER

82

-

1

1

1

1

2119791-5

DEPRESSOR, WIRE

73

-

1

1

1

1

2119956-2

DOCUMENTATION PACKAGE

71

-

2

2

2

2

2-18032-2

SCR, SET, FLT POINT M3 X 10.0

70

-

1

-

1

1

2119740-1

TAG, IDENTIFICATION

67

-

2

2

2

2

2168078-1

SCREW, DRIVE, RH, RoHS, 2 x .188

66

-

1

1

1

1

1-1901681-8

HOLDDOWN, TERMINAL

65

-

2

2

2

2

2168400-5

SHCS, LOW HEAD, RoHS, M4 X 20

64

-

1

1

1

1

2119793-1

LIMITER, ADJUSTMENT BOLT

63

-

3

3

3

3

992763-5

SCR, SET, SOC, CONE POINT, M3 x 4.0

62

-

-

-

-

1

5-18022-5

SCR, HEX HD CAP, M4 X 6.0

59

-

-

-

-

1

2063961-1

FEED FINGER

58

-

3

3

3

3

2168400-4

SHCS, LOW HEAD, RoHS, M4 X 8

57

-

2

2

2

2

2168083-2

SCR, SKT HD CAP, RoHS, M4 X 8.0

56

-

2

2

2

2

5018030-2

NUT, HEX, REG, RoHS, M4

55

-

2

2

2

2

5018030-1

NUT, HEX, REG, RoHS, M3

54

-

2

2

2

2

986965-8

NUT, LOCK, HEX, TORQUE (M4)

53

-

1

1

1

1

1-5018030-0

NUT, HEX, REG, RoHS, M3.5

52

-

-

-

1

-

2119792-2

PAWL, EF, AIR

51

-

1

1

1

1

1752354-6

STANDOFF, HOLD-DOWN

50

-

-

-

1

2

18023-9

SCR, SKT HD CAP M4 X 6.0

49

-

-

-

-

1

2119652-1

FEED CAM, PRE FEED

48

-

1

1

1

1

2079383-7

SCR, BHSC, RoHS (M8 X 25)

41

-

1

1

1

1

2119645-1

DISC, NUMBERED FA WIRE ADJUSTMENT

40

-

1

1

1

1

2119957-1

APPLICATOR SHIM PACK

39

-

1

1

1

1

2119644-1

RAM WASHER, PRECISION

38

-

7

7

7

7

1-18028-2

WASHER, FLAT, REG M4

33

-

2

2

2

2

2168083-9

SCR, SKT HD CAP, RoHS, M4 X 20

31

-

2

2

2

2

1-2168083-0

SCR, SKT HD CAP, RoHS, M4 X 10

29

-

1

1

1

1

240639-1

STRIPPER (MACHINING)

27

-

2

2

2

2

1320906-1

STUD, THREADED

25

-

1

1

1

1

1752371-5

PLATE, STRIP GUIDE

24

-

1

1

1

1

240825-7

PLATE, STRIP HOLD DOWN

23

-

2

2

2

2

2-22281-3

SPRING, COMPRESSION

22

-

1

1

1

1

1752373-4

DRAG

20

-

2

2

2

2

1901259-5

GUIDE, LOWER STRIP

18

-

1

1

1

1

1752360-1

SPACER, HOLD-DOWN

13

-

1

1

1

1

240644-1

PLATE, REAR SHEAR

11

-

-

-

-

-

-

-

10

-

1

1

1

1

690482-6

PLATE, FRONT SHEAR

9

-

1

1

1

1

1

3-1803000-7

ANVIL, COMBINATION, END FEED

8

-

1

1

1

1

1

2217206-4

BLADE, SLUG

7

-

-

-

-

-

-

-

6

-

1

1

1

1

1

240641-5

SPACER

5

-

1

1

1

1

1

238009-1

BLOCK, FL CRIMPER SPACER

4

-

1

1

1

1

1

5-2119582-2

CRIMPER, INSULATION F PREMIUM

3

-

1

1

1

1

1

455888-1

SPACER, CRIMPER

2

-

1

1

1

1

1

456402-2

CRIMPER, WIRE PREMIUM

1

-77-27-25-22-21

PART NO


DESCRIPTION

ITEM NO

THIS DRAWING IS UNPUBLISHED. IT IS SUBJECT TO CHANGE AND THE USER SHALL BE RESPONSIBLE FOR VERIFYING THE LATEST REVISIONS. NO OTHER ORGANIZATION SHALL BE CONTACTED FOR THE LATEST REVISION.

DIMENSIONS:

mm



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±

1 PLC ±

2 PLC ±

3 PLC ±

4 PLC ±

ANGLES ±

FINISH

MATERIAL

-

DRAWN

AL STAKEM

18OCT2013

CHEK

G. BAILEY

18OCT2013

APVD

T. ELBIN

18OCT2013

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

Customer Accessible Production Drawing

SCALE

1:1

SHEET

3

OF

4

REV

B

NAME

Ocean End Feed Applicator

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A1

00779

©=2150383

-

AMP 4805 REV 31MAR2000

SHEETS 1 & 2 ARE NOT REQUIRED FOR PACIFIC VERSION

