

FIXED ATTENUATORS

Designer's Kit K2-VAT2+

MINI-CIRCUITS DESIGNER'S KITS
SPEED UP
 THE SOLUTION!



DC to 6 GHz

VAT-W2+ Features

- Wideband, 50 Ω
- Input power 2 W max.
- 1 to 10 dB attenuation
- Rugged Unibody construction
- SMA Male and Female connectors
- Length less than 1.5"
- Low cost



All models are
RoHS compliant

\$124⁹⁵
 only *ea. kit (10 models, 1 of each, 10 total)*

Kit K2-VAT2+ Electrical specifications of each model

Model	Frequency (GHz) <i>f_L-f_U</i>	Attenuation ² (dB) Flatness ¹					VSWR (:1)					Input Power (W) Max.
		Nom.	DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz		3-5 GHz		5-6 GHz	
			Typ.	Typ.	Typ.	Typ.	Typ.	Max.	Typ.	Max.	Typ.	
VAT-1W2+	DC-6	1±0.3	0.20	0.20	0.20	0.60	1.10	1.20	1.30	1.50	1.55	2
VAT-2W2+	DC-6	2±0.3	0.20	0.20	0.25	0.65	1.10	1.20	1.30	1.50	1.50	2
VAT-3W2+	DC-6	3±0.3	0.20	0.15	0.15	0.45	1.05	1.20	1.30	1.40	1.45	2
VAT-4W2+	DC-6	4±0.3	0.20	0.15	0.20	0.55	1.05	1.20	1.30	1.45	1.50	2
VAT-5W2+	DC-6	5±0.3	0.20	0.10	0.15	0.35	1.10	1.20	1.40	1.50	1.65	2
VAT-6W2+	DC-6	6±0.3	0.20	0.10	0.20	0.45	1.10	1.20	1.30	1.45	1.50	2
VAT-7W2+	DC-6	7±0.3	0.25	0.15	0.10	0.45	1.10	1.20	1.25	1.40	1.40	2
VAT-8W2+	DC-6	8±0.3	0.15	0.10	0.15	0.25	1.10	1.25	1.25	1.40	1.60	2
VAT-9W2+	DC-6	9±0.3	0.15	0.10	0.10	0.15	1.10	1.20	1.15	1.40	1.50	2
VAT-10W2+	DC-6	10±0.3	0.10	0.20	0.15	0.35	1.15	1.25	1.35	1.60	1.60	2

1. Flatness=variation over band divided by 2.
 2. Attenuation varies by 0.3 dB max. over temperature.



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For quick access to product information see MINI-CIRCUITS CATALOG & WEB SITE

RF/IF & MICROWAVE COMPONENTS