


U2Y004J



<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	EFE
<b>Model</b>	EFE300
<b>Status</b>	Production
<b>Feature</b>	Peak power capability
	Full digital control
<b>Options</b>	With chassis
	With cover
	Fan supply
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Input Voltage Range[DC]	
Efficiency	90% Typ.
Rated Output Voltage[DC]	24Vdc
Output Voltage Range[DC]	22.8 to 26.4Vdc
Maximum Output Current	12.5A
Maximum Average Current	
Maximum Peak Current	16.7A
Maximum Output Power	300W
Maximum Average Power	
Maximum Peak Power	400W

### Package Type & Size

Package / Mounting	Enclosed / Unit type
Width(W)	
Height(H)	
Depth(D)	
Weight	310g Typ. (0.7lbs Typ.)

### Other

Operating Temp. Range	0 to 50°C
Cooling	Forced air Convection

Safety Standard(Certified)

IEC60950-1

CSA60950-1

EN60950-1

UL60950-1

IEC61010-1

EN61010-1

---

Safety Standard(Conformed)

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

---

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.