

Ultrafast Recovery Power Rectifier

General Description

The SFN5A600 is ideally as boost diode in discontinuous or critical mode power factor corrections. The planar structure and the platinum doper life time control guarantee the best overall performance, ruggedness reliability characteristics. The device is also intended for use as a freewheeling diode in power supplies and other power switching applications.



TO-220F-2L

Features and Benefits

- Æ Low forward drop voltage
- Æ Ultrafast recovery time and high speed switching
- Æ Full lead (Pb)-free device and RoHS compliant device


Applications

- Æ Switching power supply
- Æ Power inverters
- Æ Power conversion system

Ordering Information



Part Number	Marking Code	Package	Packaging
SFN5A600	SFN5A600	TO-220F-2L	Tube

Marking Information



AUK = Manufacture Logo
 ☒ = Management Code
 ∇ = Control Code of Manufacture
 YMDD = Date Code Marking
 -. Y = Year Code
 -. M = Monthly Code
 -. DD = Daily Code
 SFN5A600 = Specific Device Code

Pinning Information

Pin	Description	Simplified Outline	Graphic Symbol
1	Cathode		
2	Anode		

Absolute Maximum Ratings (Limiting values at 25°C, unless otherwise specified)

Characteristic	Symbol	Ratings	Unit
Maximum repetitive reverse voltage Maximum working peak reverse voltage Maximum DC blocking voltage	V_{RRM} V_{RWM} V_R	600	V
Maximum average forward rectified current	$I_{F(AV)}$	5	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	80	A
Storage temperature range	T_{stg}	-45 to +150	°C
Maximum operating junction temperature	T_J	150	

Thermal Characteristics

Characteristic	Symbol	Ratings	Unit
Maximum thermal resistance	$R_{th(j-c)}$	4.0	°C/W
	$R_{th(j-a)}$	62.5	

Electrical Characteristics

Characteristic	Symbol	Test Condition		Min.	Typ.	Max.	Unit
Peak forward voltage drop	$V_{FM}^{1)}$	$I_{FM} = 5A$	$T_J = 25^\circ C$	-	1.35	1.9	V
Reverse leakage current	$I_{RM}^{2)}$	$V_R = V_{RRM}$	$T_J = 25^\circ C$	-	-	5	µA
			$T_J = 125^\circ C$	-	-	200	
Junction capacitance	C_J	$V_R = 10V_{DC}, f = 1MHz$		-	19	-	pF

¹⁾ Pulse test: $t_p \leq 380\mu s$, Duty cycle $\leq 2\%$

²⁾ Pulse test: $t_p \leq 20ms$, Duty cycle $\leq 2\%$

Dynamic Recovery Characteristics

Characteristic	Symbol	Test Condition		Min.	Typ.	Max.	Unit
Reverse recovery time	t_{rr}	$I_F = 1A,$ $dI/dt = -100A/\mu s$	$T_J = 25 \mu s$	-	23	27	ns
			$T_J = 125 \mu s$	-	42	-	
		$I_F = 5A,$ $dI/dt = -100A/\mu s$	$T_J = 25 \mu s$	-	33	-	
			$T_J = 125 \mu s$	-	62	-	
Reverse recovery current	I_{rr}	$I_F = 1A,$ $dI/dt = -100A/\mu s$	$T_J = 25 \mu s$	-	1.4	-	A
			$T_J = 125 \mu s$	-	2.4	-	
		$I_F = 5A,$ $dI/dt = -100A/\mu s$	$T_J = 25 \mu s$	-	1.9	-	
			$T_J = 125 \mu s$	-	3.2	-	
Reverse recovery charge	Q_{rr}	$I_F = 1A,$ $dI/dt = -100A/\mu s$	$T_J = 25 \mu s$	-	18	-	nC
			$T_J = 125 \mu s$	-	55	-	
		$I_F = 5A,$ $dI/dt = -100A/\mu s$	$T_J = 25 \mu s$	-	34	-	
			$T_J = 125 \mu s$	-	109	-	

Rating & Electrical Characteristic Curves

Fig. 1) Typical Forward Characteristics




Fig. 2) Typical Reverse Characteristics




Fig. 3) Typical Reverse Recovery Time





Fig. 4) Typical Reverse Recovery Charge



Rating & Electrical Characteristic Curves

Fig. 5) Typical Junction Capacitance Characteristics




Fig. 6) Peak Forward Surge Current Characteristics




Fig. 7) Thermal Impedance Characteristics






Fig. 8) Average Forward Current Characteristics



Package Outline Dimensions (Unit: mm)



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	-	-	4.60	
A1	2.45	2.50	2.55	
A2	1.95	2.00	2.05	
b	0.65	0.75	0.85	
b1	1.07	1.27	1.47	
C	0.40	0.50	0.60	
C1	2.70	2.80	2.90	
D	9.90	10.00	10.10	
E	28.00	-	28.60	
E1	15.50	15.60	15.70	
E2	12.30	12.40	12.50	
E3	9.15	9.20	9.25	
F	3.30	3.40	3.50	
G	3.10	3.20	3.30	
e	5.08 BSC			
L	12.40	-	13.00	
L1	3.46 BSC			
L2	2.21 BSC			

The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.