Product data sheet
Characteristics

HT3025
3P 600V 25A H-FRAME MOULDED CASE CIRCUIT BREAKER TRIP UNIT

Price* : 563.00 USD

Main

Product name	PowerPact
Product or component type	Trip unit
Trip unit rating	25 A
Trip unit technology	Thermal-magnetic
Circuit breaker type	H-frame

Complementary

Number of poles	3
[Ue] rated operational voltage	600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Tightening torque	7.97…9.74 lbf.in (0.9…1.1 N.m) 43.37…46.91 lbf.in (4.9…5.3 N.m)

Environment

Product certifications	UL CSA

Ordering and shipping details

Category	01103-H,J,COMPACT NS UL/IEC CB ACCESS
Discount Schedule	DE2
GTIN	00785901446279
Package weight(Lbs)	16.00 oz (453.592 g)
Returnability	No
Country of origin	US

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months