


GBU15005 THRU GBU1510


Single-Phase 15.0A Glass Passivated Bridge Rectifier



Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Plastic material-UL flammability 94V-0
- This is a Pb – Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Circuit Diagram



Mechanical Data

- Case: GBU, Molded plastic
- Terminals: Plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting Position: Any
- Lead Free: For RoHS / Lead Free Version

Maximum Ratings: @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Type Number	Symbol	GBU 15005	GBU 1501	GBU 1502	GBU 1504	GBU 1506	GBU 1508	GBU 1510	Units
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{DC}	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Average forward rectified output current (Note 1) @T _A = 40°C	I_o	15							A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	200							A

Electrical Characteristics:@T_A=25°C unless otherwise specified

Type Number	Symbol	GBU 15005	GBU 1501	GBU 1502	GBU 1504	GBU 1506	GBU 1508	GBU 1510	Units
Forward Voltage (per element) @I _F =7.5A @I _F =15A	V _F				1.0 1.1				V
Peak Reverse Current @T _A = 25°C At Rated DC Blocking Voltage @T _A = 125°C	I _{RM}				5.0 500				μA
Typical Junction Capacitance(per leg) (Note 2)	C _J				70				pF



* Pulse width < 300 μs, duty cycle < 2%

Thermal-Mechanical Specifications:@T_A=25°C unless otherwise specified



Type Number	Symbol	GBU 15005	GBU 1501	GBU 1502	GBU 1504	GBU 1506	GBU 1508	GBU 1510	Units
Typical Thermal Resistance (per leg)	R _{θJA} R _{θJL}				25 2.2				°C/W
Operating and Storage Temperature Range	T _J , T _{STG}				-55 to +150				°C

Note: 1. Mounted on glass epoxy PC board with 1.3mm² solder pad.
2. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.

Ratings and Characteristics Curves



Technical Data
Data Sheet N1802, Rev. A




Ordering Information

Device	Package	Plating	Shipping
GBU10005 THRU GBU1010	GBU (Pb-Free)	Pure Sn	20pcs / tube

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.


Marking Diagram



Where XXXXX is YYWWL

SSG = SSG
YY = Year
WW = Week
L = Lot Number
GBU15005 = Type Number

Cautions: Molding resin
Epoxy resin UL:94V-0



RoHS



Technical drawing of a mechanical part, showing dimensions in inches (in parentheses) and millimeters (in brackets). The drawing includes a top view, a side view, and a cross-sectional view.

Top View Dimensions:

- Overall width: .874 (22.2)
- Distance from left edge to centerline: .437 (11.1)
- Distance from left edge to right edge: .858 (21.8)
- Distance from left edge to centerline (bottom): .429 (10.9)
- Distance from centerline to right edge: .154 (3.9)
- Distance from centerline to right edge (bottom): .146 (3.7)
- Distance from left edge to centerline (bottom): .232 (5.9)
- Distance from left edge to centerline (bottom): .217 (5.5)
- Distance from centerline to right edge (bottom): .091 (2.3)
- Distance from centerline to right edge (bottom): .087 (2.2)
- Distance from centerline to right edge (bottom): .051 (1.3)
- Distance from centerline to right edge (bottom): .035 (0.9)
- Distance from centerline to right edge (bottom): .20 x 5.30
- Distance from centerline to right edge (bottom): .189 (4.80)

Side View Dimensions:

- Overall height: .752 (19.1)
- Distance from top edge to centerline: .720 (18.3)
- Distance from top edge to centerline (bottom): .680 (17.27)
- Distance from top edge to centerline (bottom): .091 (2.3)
- Distance from top edge to centerline (bottom): .083 (2.1)
- Distance from top edge to centerline (bottom): .022 (.56)
- Distance from top edge to centerline (bottom): .018 (.46)

Cross-sectional View Dimensions:

- Overall width: .139 (3.53)
- Distance from left edge to centerline: .133 (3.37)
- Distance from left edge to centerline (bottom): .087 (2.2)
- Distance from left edge to centerline (bottom): .071 (1.8)

Other Features:

- Chamfer: .126 (3.2) * 45° CHAMFER
- 60° angle

- China - Germany - Korea - Singapore - United States •
• <http://www.smc-diodes.com> - sales@smc-diodes.com •

**Technical Data
Data Sheet N1802, Rev. A**



DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.