
SuperPlanar™ Bridge Rectifiers GBL3J--GBL3K

Features



- Planar passivated chips
- Ultra low leakage reverse current
- High temperature performance
- High surge current capability
- Ideal for printed circuit boards
- High temperature soldering guaranteed:260°C/10 seconds
- RoHS Compliant

Mechanical Data

- Case: GBL molded plastic
- Molding compound, UL flammability classification rating 94V-0
- Terminals: Leads solderable per MIL-STD-750,
- Mounting position: Any

Maximum Ratings (@T_A = 25°C unless otherwise specified)

Characteristic		Symbol	GBL3J	GBL3K	Units
Peak repetitive reverse voltage		V_{RRM}	600	800	V
RMS reverse voltage		V_{RMS}	420	560	V
DC blocking voltage		V_{DC}	600	800	V
Maximum average forward output current		$I_{F(AV)}$	3.0		A
Peak forward surge current, 8.3ms single half-sine-wave	@T_J= 25°C	I_{FSM}	90		A
I^2t Rating for fusing	@T_J= 25°C	I^2t	33.6		A^2s

Thermal Characteristics

Parameter	Symbol	GBL3J	GBL3K	Units
Typical thermal resistance per leg (Note 1)	$R_{\Theta JA}$	36		°C /W
	$R_{\Theta JC}$	8		
Operating junction temperature range	T_J	- 55 ---- + 150		°C
Storage temperature range	T_{STG}	- 55 ---- + 150		°C

Note:

(1) Units mounted on PCB without heatsink

SuperPlanar™ Bridge Rectifiers GBL3J--GBL3K

Electrical Characteristics (@T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test conditions		Typ.	Max.	Units
Maximum instantaneous forward voltage	V_F	I_F=1.5A Per Diode		0.91	0.95	V
		I_F=3.0A Per Diode		0.95	1.0	
Maximum Reverse current	I_R	Rated V_R, Per Diode	@T_A=25°C	0.1	1.0	μ A
			@T_A=150°C	20	80	

SuperPlanar™ Bridge Rectifiers GBL3J--GBL3K

Ratings and Characteristic Curves (T_A=25°C unless otherwise noted)

Fig.1-Forward Current Derating Curve




Fig.2- Surge Current Derating Curve




Fig.3- Typical Forward Voltage Characteristic






Fig.4- Typical Reverse Characteristic



SuperPlanar™ Bridge Rectifiers GBL3J--GBL3K

Package Outline Dimensions(unit:mm)



Ordering Information

Part No.	Marking	Package
GBL3J	GBL3J	GBL
GBL3K	GBL3K	GBL