

Compact cylinder ADN-S-63-15-A-P-A-F1A

Part number: 8142929

FESTO



Data sheet

| Feature | Value |
|--|---|
| Stroke | 15 mm |
| Piston diameter | 63 mm |
| Cushioning | Elastic cushioning rings/pads at both ends |
| Mounting position | Any |
| Mode of operation | Double-acting |
| Piston rod end | External thread |
| Structural design | Piston Piston rod |
| Position sensing | For proximity sensor |
| Symbol | 00991217 |
| Variants | Recommended for production facilities for the manufacture of lithium-ion batteries Piston rod at one end |
| Operating pressure | 0.04 MPa ... 1 MPa |
| Operating pressure | 0.4 bar ... 10 bar |
| Operating pressure | 5.8 psi ... 145 psi |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |
| Ambient temperature | 0 °C ... 60 °C |
| Impact energy in the end positions | 1.3 J |
| Theoretical force at 6 bar, retracting | 1750 N |
| Theoretical force at 6 bar, advancing | 1870 N |
| Moving mass at 0 mm stroke | 151 g |
| Additional weight per 10 mm stroke | 77 g |
| Basic weight with 0 mm stroke | 499 g |
| Additional moving mass per 10 mm stroke | 16 g |
| Type of mounting | With through-hole With internal thread |
| Pneumatic connection | G1/8 |
| Note on materials | RoHS-compliant |
| Cover material | Wrought aluminum alloy, anodized |
| Material of dynamic seals | TPE-U(PU) |
| Housing material | Wrought aluminum alloy, anodized |
| Piston rod material | High-alloy stainless steel |