



SPECIFICATION

Contact Rating: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min. 500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.25mm
 Operating Temp: -30°C~+85°C
 Storage Temp: -30°C~+80°C

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Pa46		—
②	Cover	—	1	Spcc	Plating Nickel	—
①	Keystake	—	1	Pa46		—

					units:	mm	DSND		DATE	SCALE: N/A	MODEL TYPE:		
Δx					tolerance:		DWN		DATE	VIEW:	TACT SWITCH		
Δx					X.X	±0.2mm	CHKD		DATE	UNIT: mm	PART NO.:		
Δx					X.XX	±0.1mm	APPD		DATE	SIZE: A4	DWG NO.:		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX	±0.05mm					TC-1102-C-20-B		
					REVISIONS	UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET	REVISION
					www.xk-dg.cn www.helloxkb.com www.helloxkb.cn						1.0g	1/1	A0