





Recommended P.C.B Layout  
P.C.B Board Tolerance±0.05

NOTES:

Voltage Rating:250V AC/DC  
Current Rating:3.0A AC/DC  
Dielectric Withstand Voltage:500V AC/minute  
Contact Voltage:20M Max.  
Insulation Voltage:1000M Min  
Operation temperature:-40 °C to +105 °C  
Insulator Material:Polyester.Ul94V-0  
Contact Material:Brass  
Contact Plating:AuorSn Plated on Nickel Overall



塑胶高度可选 (mm)				常用
H	1.0	1.5	2.0	2.54

Dimension antitheses list				
item	PA	---	PC	L
Standard	6.00	---	3.00	11.50
Alternate	---	---	---	---

AO	VER	MODIFICATION	DRAW	DATE
----	-----	--------------	------	------

TOLERANCE UNLESS OTHERWISE			
X.	±0.30	X°	±5°
.X	±0.20	.X°	±2°
.XX	±0.08	.XX°	±1°
.XXX	±0.03	.XXX°	±0.5°

DRAWN	CK tan	<b>XFCN</b> 兴飞连接器有限公司 CONNECTORS XFCN CONNECTORS CO., LTD.
CHKD		
APPD		
VIEW		
PRODUCT NAME		2.54mm Pin Header Connectors
PART. NO.		PZ254V-12-XX

SHEET	1/1
DATE	2010. 4. 12
UNITS	mm
SCALE	1:1
DWG. NO.	009