



Coaxial Cable

141 SMNM Model Series

50Ω DC to 18 GHz



CASE STYLE: KQ1668-XX

XX= cable length in inches

The Big Deal

- SMA to N-Type Connection
- Excellent Return Loss and Insertion Loss
- Tight Bend Radius (8mm min.)
- Ideal for interconnect of assembled systems

Product Overview

141 SMNM+ series Hand-Flex coaxial cables are ideal for integrating coaxial components and sub-systems in tight spaces and dense system configurations. SMA to N-Type connection avoids need for an adapter between components with SMA-F and N-F connection ports, reducing system cost and improving reliability. Sturdy, hand-formable cable construction maintains shape after bending with bend-radius as small as 8mm. 141 SMNM+ coaxial cables have the advantages of wide frequency range and excellent return loss and insertion loss. Available in a variety of lengths.

Key Features

| Feature | Advantages |
|--|---|
| Hand-Formable | 141 SMNM+ series Hand-Flex cables avoid the need for cable-bending tools, alleviating the risk of damage during bending processes typical of semi-rigid cable assemblies. |
| Tight Bend Radius | Capable of bending to radii as small as 8mm, the 141 SMNM+ series is ideal for making connections in tight spaces and dense system assemblies. |
| Excellent Return loss | Typical return loss of 25 dB to 6 GHz and 18 dB to 18 GHz makes the 141 SMNM+ series ideal for interconnecting a wide variety of RF components while minimizing VSWR ripple contribution due to mating cables & connectors. |
| High Power Handling Capability: <ul style="list-style-type: none"> • 546W at 0.5 GHz • 90W at 18 GHz | Mini-Circuits 141 SMNM+ series cables can support medium to high RF power levels and can be used in the transmit path. (NOTE: power rating at sea-level). |
| Built-in Anti-torque Nut | Supports the connector bodies during installation, preventing stress to the connector/cable interface. |
| SMA-Male / N-Male connectors | Eliminates need for adapter when connecting to SMA-F and N-F connectors, reducing cost and improving reliability. |

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp





Coaxial Cable

50Ω 6 inch DC to 18 GHz

141-6SMNM+



CASE STYLE: KQ1668-6

| Connectors | Model |
|-------------------|------------|
| SMA-Male / N-Male | 141-6SMNM+ |

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Maximum Ratings

| | | |
|-------------------------|----------------|---------|
| Operating Temperature | -55°C to 105°C | |
| Storage Temperature | -55°C to 105°C | |
| Power Handling at 25°C, | 546W at | 0.5 GHz |
| Sea Level | 387W at | 1 GHz |
| | 273W at | 2 GHz |
| | 156W at | 6 GHz |
| | 121W at | 10 GHz |
| | 90W at | 18 GHz |

Permanent damage may occur if any of these limits are exceeded.

Features

- Wideband frequency coverage, DC to 18 GHz
- Low Loss, 0.45 dB at 18 GHz
- Excellent Return Loss, 24 dB at 18 GHz
- Hand formable to almost any custom shape without special bending tools
- 8mm bend radius for tight installations
- Anti-torque nut prevents cable stress during installation
- Insulated outer jacket standard
- **Ideal for interconnect of assembled systems**

Applications


- Replacement for custom bent 0.141" semi-rigid cables
- Communication receivers and transmitters
- Military and aerospace system
- Environmental and test chambers

Electrical Specifications at 25°C

| Parameter | Condition (GHz) | Min. | Typ. | Max. | Unit |
|---------------------|-----------------|------|------|------|--------|
| Frequency Range | | DC | | 18 | GHz |
| Length ¹ | | | 6 | | inches |
| Insertion Loss | DC - 2 | — | 0.10 | 0.28 | dB |
| | 2 - 6 | — | 0.25 | 0.50 | |
| | 6 - 10 | — | 0.33 | 0.66 | |
| | 10 - 18 | — | 0.67 | 0.91 | |
| Return Loss | DC - 2 | 23 | 31 | — | dB |
| | 2 - 6 | 23 | 25 | — | |
| | 6 - 10 | 17 | 21 | — | |
| | 10 - 18 | 17 | 19 | — | |

1. Custom sizes available, consult factory.

Outline Drawing




* OVERALL CONNECTOR DIMENSION (CONNECTOR SHAPE MAY VARY)

Outline Dimensions (inch/mm)

| | | | | |
|--------|------|-----------|------|-------|
| A | B | C1 | C2 | D |
| 5.0 | .36 | .313 | .250 | .88 |
| 127.00 | 9.14 | 7.95 | 6.35 | 22.35 |
| E1 | E2 | F | T | wt |
| .750 | .375 | .163±.004 | .05 | grams |
| 19.05 | 9.53 | 4.14±0.10 | 1.27 | 39.02 |

Cable Construction





SMA-Male Connector:
Coupling Nut: Stainless Steel Passivated
Body: Stainless Steel Gold Plated
Center Pin: Silver Plated Copper Clad Steel

N-Male Connector:
Coupling Nut: Brass, Nickel Plated
Body: Brass, Nickel Plated
Center Pin: Brass, Gold Plated

Typical Performance Data

| Frequency (MHz) | Insertion Loss (dB) | Return Loss (dB) | |
|-----------------|---------------------|------------------|--------|
| | | SMA-Male | N-Male |
| 100 | 0.01 | 47.4 | 48.2 |
| 1000 | 0.05 | 39.9 | 37.8 |
| 1800 | 0.08 | 36.5 | 35.6 |
| 2404 | 0.07 | 33.4 | 33.9 |
| 4001 | 0.16 | 28.3 | 29.6 |
| 5000 | 0.13 | 28.0 | 30.0 |
| 6000 | 0.13 | 32.6 | 35.0 |
| 7001 | 0.10 | 35.4 | 35.3 |
| 8001 | 0.14 | 34.0 | 32.3 |
| 9000 | 0.15 | 29.3 | 27.2 |
| 10000 | 0.17 | 25.0 | 24.3 |
| 12001 | 0.28 | 25.6 | 24.8 |
| 14001 | 0.14 | 29.0 | 31.6 |
| 16242 | 0.38 | 26.5 | 26.1 |
| 18000 | 0.45 | 24.9 | 23.6 |



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Rev. B
M167677
141-6SMNM+
RK/CP/AM
180504

Proper Cable Connection Using Anti-Torque Nut

Mini-Circuits 141-series HandFlex™ interconnect cables are constructed with an anti-torque nut adjacent to the connector coupling nut. When used properly, this feature prevents possible damage to the cable due to torquing and twisting when tightening the cable connector.

To properly tighten the cable connector:

- 1) The cable connector includes a coupling nut which rotates to fasten the connector, and an anti-torque nut, which is fixed to prevent the cable from twisting during connection.



- 2) To properly tighten the cable, use a standard 1/4-inch open end wrench to brace the anti-torque nut.



- 3) Using a 5/16-inch open end wrench, rotate the coupling nut clockwise to tighten the cable connector.

***NOTE:** Mini-Circuits recommends using a 5/16-inch open end wrench calibrated to 8 inch-pounds maximum torque to prevent damage due to over-torquing the connector.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

