

SPECIFICATION SHEET
JFW MODEL 50T-334-XXX
TERMINATION/MISMATCH

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-3000 MHz
Impedance	50 Ohms (referenced)
Available Values	1.0:1 through 5.0:1 in any 0.1 increment (1.0:1 = termination)
VSWR	1.15:1 maximum (1.0:1) ±10% of nominal (all other values)
RF Input Power	50 Watts average @ +25°C Derate to 25 Watts @ +70°C
Peak Power	1000 Watts (1 microsecond pulse)
RF Connector	N, TNC, BNC, SMA or 7/16 (male or female) or N male hex (13/16")
Operating Temperature Range	-55°C to +100°C
Physical Size	See outline drawing 092-3560

XXX - Insert VSWR required
 i.e. - termination = 50T-334-1.0
 1.5:1 mismatch = 50T-334-1.5
 5.0:1 mismatch = 50T-334-5.0

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
2855	12/13/2001	A		4231	04/03/2003	D	CLV 04/03/2003
2857	12/17/2001	B		10275	12/15/2004	E	SL 12/15/2004
9999	02/25/2003	C		11954	10/06/2005	F	SL 10/06/2005