



TPRH8D28 TYPE

● FEATURE

1. High current capacity and Low DCR
2. Magnetic shielded for low radiation
3. Low core loss for high frequency power application

● Applications

1. Personal Computer
2. Set top box, and other electronic equipment

● Shape and Dimension● Schematics and Land Patterns(mm)

A=8.30mm MAX ; B=8.30mm MAX ; D=3.00mm MAX

● Specification

P/N	L (μ H)	Marking	RDC (Ω)Max	Isat (A)	Irms (A)
TPRH8D28-1R0□	1.0	1R0	11.0m	6.50	7.50
TPRH8D28-2R5□	2.5	2R5	15.6m	4.50	6.40
TPRH8D28-3R3□	3.3	3R3	18.2m	4.00	6.00
TPRH8D28-4R7□	4.7	4R7	24.7m	3.40	4.50
TPRH8D28-6R8□	6.8	6R8	37.0m	2.85	4.00
TPRH8D28-7R3□	7.3	7R3	39.0m	2.80	3.40
TPRH8D28-100□	10	100	47.0m	2.50	3.20
TPRH8D28-150□	15	150	69.0m	1.90	2.35
TPRH8D28-220□	22	220	99.0m	1.60	1.85
TPRH8D28-330□	33	330	156m	1.30	1.45
TPRH8D28-470□	47	470	195m	1.15	1.30
TPRH8D28-680□	68	680	286m	920m	980m
TRPH8D28-101□	100	101	430m	750m	800m

Note1. Measurement frequency of Inductance value : at 100KHz

Note2. Measurement ambient temperature of L, DCR and IDC : at 25°C

Note3. Isat: DC current at which the inductance drops 35%(typ.) from its value without current

Note4. Irms: Average current for 40°C temperature rise from 25°C ambient

Note5. Inductance tolerance: M: $\pm 20\%$; N: $\pm 30\%$

Note6. Ordering Code: TYPE NAME: TPRH8D28


Main Inductance: 100 (10uH)

Tolerance : M ($\pm 20\%$)

Note7. Packaging: Taping ; Quantity: 1500 Pieces/reel


GENERAL CHARACTERISTICS

1. Operating temperature range: -40 TO $+105^{\circ}\text{C}$ (Includes temperature when the coil is heated)
2. External appearance: On visual inspection, the coil has no external defects.
3. Terminal strength: After soldering. Between copper plate and terminals of coil. Push in two directions of X.Y withstanding at below conditions.
Terminal should not peel off. (refer to figure at right) 5. 0N 60 sec.



4. Insulating resistance: Over $100\text{M}\Omega$ at 100V D.C. between coil and core.
5. Dielectric strength: No dielectric breakdown at 100V D.C. for 1 minute between coil and core.
6. Temperature characteristics: Inductance coefficient $(0\sim 2,000)\times 10^{-6}/^{\circ}\text{C}$ ($-25\sim +80^{\circ}\text{C}$ degree Celsius), inductance deviation within $\pm 5.0\%$, after 96 hours.
7. Humidity characteristics (Moisture Resistance): Inductance deviation within $\pm 5\%$, after 96 hours in $90\sim 95\%$ relative humidity at $40 \pm 2^{\circ}\text{C}$ and 1 hour drying under normal condition.
8. Vibration resistance: Inductance deviation within $\pm 5\%$, after vibration for 1 hour. In each of three orientations at sweep vibration ($10\sim 55\sim 10\text{ Hz}$) with 1.5mm P-P amplitudes.
9. Shock resistance: Inductance deviation within $\pm 5\%$, after being dropped once with 981m/s^2 (100G) shock attitude upon a rubber block method shock testing machine, in three different orientations.
10. Resistance to Soldering Heat: 260°C , 10 seconds (See attached recommend reflow)
11. Storage condition: Temperature Range: $0^{\circ}\text{C} \sim 35^{\circ}\text{C}$; $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ (after PCB) · Humidity Range: $50\% \sim 70\% \text{ RH}$
12. Use components within 12 months. If 12 months or more have elapsed, check solderability before use.
13. Reflow profile recommend:

Lead-free heat endurance test



Lead-free the recommended reflow condition

