GSS4505

N AND P-CHANNEL ENHANCEMENT MODE POWER MOSFET

N-CH	BV_{DSS}	30V
	$R_{DS(ON)}$	20mΩ
	I_D	8.3A
P-CH	BV_{DSS}	-30V
	$R_{DS(ON)}$	28mΩ
	I_D	-7.1A

Description

The GSS4505 provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.
The SOP-8 package is universally preferred for all commercial-industrial surface mount applications and suited for low voltage applications such as DC/DC converters.

Features

*Simple Drive Requirement
*Lower On-resistance
*Fast Switching Performance

Package Dimensions







REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	5.80	6.20	M	0.10	0.25
B	4.80	5.00	H	0.35	0.49
C	3.80	4.00	L	1.35	1.75
D	0°	8°	J	0.375 REF.	
E	0.40	0.90	K	45°	
F	0.19	0.25	G	1.27 TYP.	

Absolute Maximum Ratings

Parameter	Symbol	Ratings		Unit
		N-channel	P-channel	
Drain-Source Voltage	V_{DS}	30	-30	V
Gate-Source Voltage	V_{GS}	±20	±20	V
Continuous Drain Current[3]	I_D @T_A=25℃	8.3	-7.1	A
Continuous Drain Current[3]	I_D @T_A=70℃	6.7	-5.7	A
Pulsed Drain Current[1]	I_{DM}	30	-30	A
Total Power Dissipation	P_D @T_A=25℃	2.0		W
Linear Derating Factor		0.016		W/℃
Operating Junction and Storage Temperature Range	Tj, Tstg	-55 ~ +150		℃

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-ambient[3] Max.	Rthj-a	62.5	℃/W

N-Channel Electrical Characteristics(Tj = 25℃ Unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV_{DSS}	30	-	-	V	V_{GS}=0, I_D=250uA
Breakdown Voltage Temperature Coefficient	$\triangle BV_{DSS}/\triangle Tj$	-	0.02	-	V/℃	Reference to 25℃, I_D=1mA
Gate Threshold Voltage	$V_{GS(th)}$	1.0	-	3.0	V	V_{DS}=V_{GS}, I_D=250uA
Forward Transconductance	g_{fs}	-	13	-	S	V_{DS}=10V, I_D=8A
Gate-Source Leakage Current	I_{GSS}	-	-	±100	nA	V_{GS}= ±20V
Drain-Source Leakage Current(Tj=25℃)	I_{DSS}	-	-	1	uA	V_{DS}=30V, V_{GS}=0
Drain-Source Leakage Current(Tj=70℃)		-	-	25	uA	V_{DS}=24V, V_{GS}=0
Static Drain-Source On-Resistance[2]	$R_{DS(ON)}$	-	-	20	mΩ	V_{GS}=10V, I_D=8A
		-	-	28		V_{GS}=4.5V, I_D=5A
Total Gate Charge[2]	Q_g	-	20	30	nC	I_D=8A V_{DS}=24V V_{GS}=4.5V
Gate-Source Charge	Q_{gs}	-	5	-		
Gate-Drain ("Miller") Change	Q_{gd}	-	12	-		
Turn-on Delay Time[2]	$T_{d(on)}$	-	12	-	ns	V_{DS}=15V I_D=1A V_{GS}=10V R_G=3.3Ω R_D=15Ω
Rise Time	T_r	-	8	-		
Turn-off Delay Time	$T_{d(off)}$	-	31	-		
Fall Time	T_f	-	12	-		
Input Capacitance	C_{iss}	-	1450	2230	pF	V_{GS}=0V V_{DS}=25V f=1.0MHz
Output Capacitance	C_{oss}	-	320	-		
Reverse Transfer Capacitance	C_{rss}	-	230	-		

Source-Drain Diode

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage[2]	V_{SD}	-	-	1.2	V	I_S=1.7A, V_{GS}=0V
Reverse Recovery Time[2]	T_{rr}	-	27	-	ns	I_S=8A, V_{GS}=0V dI/dt=100A/μs
Reverse Recovery Charge	Q_{rr}	-	18	-	nC	

Notes: 1. Pulse width limited by Max. junction temperature.

2. Pulse width≦300us, duty cycle≦2%.

3. Surface mounted on 1 in^2 copper pad of FR4 board; 135℃/W when mounted on Min. copper pad.

P-Channel Electrical Characteristics(Tj = 25℃ Unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV_{DSS}	-30	-	-	V	V_{GS}=0, I_D=-250uA
Breakdown Voltage Temperature Coefficient	$\triangle BV_{DSS}/\triangle Tj$	-	-0.01	-	V/℃	Reference to 25℃, I_D=-1mA
Gate Threshold Voltage	$V_{GS(th)}$	-1.0	-	-3.0	V	V_{DS}=V_{GS}, I_D=-250uA
Forward Transconductance	g_{fs}	-	11	-	S	V_{DS}=-10V, I_D=-7A
Gate-Source Leakage Current	I_{GSS}	-	-	±100	nA	V_{GS}= ±20V
Drain-Source Leakage Current(Tj=25℃)	I_{DSS}	-	-	-1	uA	V_{DS}=-30V, V_{GS}=0
Drain-Source Leakage Current(Tj=70℃)		-	-	-25	uA	V_{DS}=-24V, V_{GS}=0
Static Drain-Source On-Resistance[2]	$R_{DS(ON)}$	-	-	28	mΩ	V_{GS}=-10V, I_D=-7A
		-	-	45		V_{GS}=-4.5V, I_D=-4A
Total Gate Charge[2]	Q_g	-	21	33	nC	I_D=-7A V_{DS}=-24V V_{GS}=-4.5V
Gate-Source Charge	Q_{gs}	-	3	-		
Gate-Drain ("Miller") Change	Q_{gd}	-	15	-		
Turn-on Delay Time[2]	$T_{d(on)}$	-	13	-	ns	V_{DS}=-15V I_D=-1A V_{GS}=-10V R_G=3.3Ω R_D=15Ω
Rise Time	T_r	-	10	-		
Turn-off Delay Time	$T_{d(off)}$	-	51	-		
Fall Time	T_f	-	52	-		
Input Capacitance	C_{iss}	-	1170	1870	pF	V_{GS}=0V V_{DS}=-25V f=1.0MHz
Output Capacitance	C_{oss}	-	430	-		
Reverse Transfer Capacitance	C_{rss}	-	340	-		

Source-Drain Diode

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage[2]	V_{SD}	-	-	-1.2	V	I_S=-1.7A, V_{GS}=0V
Reverse Recovery Time[2]	T_{rr}	-	40	-	ns	I_S=-7A, V_{GS}=0V dI/dt=100A/μs
Reverse Recovery Charge	Q_{rr}	-	33	-	nC	

Notes: 1. Pulse width limited by Max. junction temperature.

2. Pulse width≦300us, duty cycle≦2%.

3. Surface mounted on 1 in^2 copper pad of FR4 board; 135℃/W when mounted on Min. copper pad.

Characteristics Curve N-Channel



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. On-Resistance v.s. Gate Voltage



Fig 4. Normalized On-Resistance v.s. Junction Temperature



Fig 5. Forward Characteristics of Reverse Diode



Fig 6. Gate Threshold Voltage v.s. Junction Temperature

N-Channel



Fig 7. Gate Charge Characteristics



Fig 8. Typical Capacitance Characteristics



Fig 9. Maximum Safe Operating Area



Fig 10. Effective Transient Thermal Impedance



Fig 11. Switching Time Waveform



Fig 12. Gate Charge Waveform

P-Channel



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. On-Resistance v.s. Gate Voltage



Fig 4. Normalized On-Resistance v.s. Junction Temperature



Fig 5. Forward Characteristics of Reverse Diode



Fig 6. Gate Threshold Voltage v.s. Junction Temperature

P-Channel



Fig 7. Gate Charge Characteristics



Fig 8. Typical Capacitance Characteristics



Fig 9. Maximum Safe Operating Area



Fig 10. Effective Transient Thermal Impedance



Fig 11. Switching Time Waveform



Fig 12. Gate Charge Waveform

Important Notice:
- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:
- **Taiwan**: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
  TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China**: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
  TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165