muRata
INNOVATOR IN ELECTRONICS

Chip Multilayer Ceramic Capacitors for General



2018

Contents

Product specifications are as of September 2017.

Explanation of Symbols in This Catalog ··· p2
Selection Guide ··· p3
Catalog information ··· p4
Part Numbering ··· p5
Capacitance Table ··· p9

Cap. Table

Chip Multilayer Ceramic Capacitors for General Purpose
GRM Series ··· p40 p10
GRM Series Specifications and Test Methods ··· p108

High Effective Capacitance & High Ripple Current Chip Multilayer Ceramic Capacitors for General Purpose GR3 Series ··· p109 p27
GR3 Series Specifications and Test Methods (1) ··· p111
GR3 Series Specifications and Test Methods (2) ··· p114
GR3 Series Specifications and Test Methods (3) ··· p117

Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose
GRJ Series ··· p120 p28
GRJ Series Specifications and Test Methods ··· p124

Chip Multilayer Ceramic Capacitors for Ethernet LAN and Primary-secondary Coupling of DC-DC Converters GR4 Series ··· p125 p30
GR4 Series Specifications and Test Methods (1) ··· p127

Chip Multilayer Ceramic Capacitors for Camera Flash circuit only
GR7 Series ··· p130 p30
GR7 Series Specifications and Test Methods (1) ··· p132

High Q Chip Multilayer Ceramic Capacitors for General Purpose
GJM Series ··· p135 p30
GJM Series Specifications and Test Methods (1) ··· p157
GJM Series Specifications and Test Methods (2) ··· p160

High Q and High Power Chip Multilayer Ceramic Capacitors for General Purpose
GQM Series ··· p164 p31
GQM Series Specifications and Test Methods (1) ··· p172
GQM Series Specifications and Test Methods (2) ··· p175
GQM Series Specifications and Test Methods (3) ··· p178
GQM Series Specifications and Test Methods (4) ··· p181

Based on the Electrical Appliance and Material Safety Law of Japan Chip Multilayer Ceramic Capacitors for General Purpose GA2 Series ··· p184 p32
GA2 Series Specifications and Test Methods (1) ··· p186

Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose / IEC60384-14 Class X2 GA3 Series Type GB ··· p189 p32
GA3 Series Type GB Specifications and Test Methods (1) ··· p192

Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose / Acquired certifications of UL60950-1 GA3 Series Type GD ··· p196 p32
GA3 Series Type GD Specifications and Test Methods (1) ··· p199
GA3 Series Type GD Specifications and Test Methods (2) ··· p203

Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose / Acquired certifications of IEC60384-14 Class X1/Y2 and UL60950-1
GA3 Series Type GF ··· p207 p33
GA3 Series Type GF Specifications and Test Methods (1) ··· p211
GA3 Series Type GF Specifications and Test Methods (2) ··· p215

LW Reversed Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL Series ··· p219 p34
LLL Series Specifications and Test Methods ··· p221

Cap. Table

8 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLA Series ····· p222 p34
LLA Series Specifications and Test Methods (1) ····· p224
LLA Series Specifications and Test Methods (2) ····· p226

10 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLM Series ····· p228 p35
LLM Series Specifications and Test Methods (1) ····· p230

LW Reversed Controlled ESR Low ESL Chip Multilayer Ceramic Capacitors for General Purpose LLR Series ····· p232 p35
LLR Series Specifications and Test Methods (1) ····· p234

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series ····· p236 p35
NFM Series Specifications and Test Methods ····· p238

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series ····· p239 p36
KRM Series Specifications and Test Methods ····· p242

High Effective Capacitance & High Allowable Ripple Current Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose KR3 Series ····· p243 p37
KR3 Series Specifications and Test Methods (1) ····· p246

Wire Bonding Mount Multilayer Microchip Capacitors for General Purpose
GMA Series ····· p249 p37
GMA Series Specifications and Test Methods (1) ····· p252
GMA Series Specifications and Test Methods (2) ····· p254

Wire Bonding/AuSn Soldering Mount Chip Multilayer Ceramic Capacitors for General Purpose GMD Series ····· p256 p38
GMD Series Specifications and Test Methods (1) ····· p259
GMD Series Specifications and Test Methods (2) ····· p261
GMD Series Specifications and Test Methods (3) ····· p263

⚠Caution/Notice/Soldering and Mounting ····· p265
Introduction of Website SimSurfing ····· p291
Product Information ····· p292

Please check the MURATA website (**https://www.murata.com/**)
if you cannot find a part number in this catalog.

EU RoHS Compliant

- All the products in this catalog comply with EU RoHS.
- EU RoHS is "the European Directive 2011/65/EU on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment."
- For more details, please refer to our web page, "Murata's Approach for EU RoHS" (https://www.murata.com/en-eu/support/compliance/rohs).

Qualified Standards

- The products listed here have been produced by ISO 9001 certified factory.

<Plant>
- Fukui Murata Mfg. Co., Ltd.
- Izumo Murata Mfg. Co., Ltd.
- Murata Electronics Singapore (Pte.) Ltd.
- Wuxi Murata Electronics Co., Ltd.
- PHILIPPINE MANUFACTURING CO. OF MURATA, INC.

Explanation of Symbols in This Catalog

WEB	Links are provided to the latest information from the PDF version of the catalog, which is available on the web.

General	For applications that do not require the particular reliability such as the general equipment
Info-tainment	Infotainment for Automotive The product for entertainment equipment like car navigations, car audios, and body control equipment like wipers, power windows.
Power-train	Powertrain/Safety for Automotive Product used for applications (running, turning, stopping and safety devices) which particularly concern human life, such as in devices for automobiles.
Medical Device	Medical-grade products for Implanted Medical Devices These products are intended for use in implanted medical devices such as cardiac pacemakers, cochlear implants, insulin pumps and gastric electrostimulators. They are suitable for use in non-critical circuits. *1 *1 Non-critical circuits This term refers to circuits in implanted medical devices that are not directly linked to life support, i.e. circuits that will not directly endanger the life of the patient should the functionality of the device be reduced or halted by failure of the circuit.
AEC-Q200	AEC-Q200 compliant product
Safety standard	Safety Standard Certified Product Products that acquired safety standard certification IEC60384-14 and products based on the Electrical Appliance and Material Safety Law of Japan.
Japanese Safety Law	Based on the Electrical Appliance and Material Safety Law of Japan Products that are based on the electrical appliance and material safety law of Japan.
High Q	Low dissipation for high frequency By devising ceramic materials and electrode materials, low dissipation is achieved in frequency bands of VHF, UHF and microwave or beyond.
Low ESL	Low inductance This capacitor is designed so that the parasitic inductance component (ESL) that the capacitor has on the high frequency side becomes lower.
Fail safe	Fail safe product This capacitor is designed to prevent failures as much as possible by short mode.
Deflecting crack	Product resistant to deflection cracking This capacitor is designed to prevent failures as much as possible by short mode caused by cracking when there is board deflection.
Soldering crack	Product with solder cracking suppression "This capacitor is configured with metal terminals and leads connected to the chip. The metal terminals and leads relieve the stress from expansion and contraction of the solder, to suppress solder cracking."
Anti-noise	Product suitable for acoustic noise reduction and low distortion This product suppresses acoustic noise, which occurs when a ceramic capacitor is used, by devising the materials and configuration.
Effective Cap	No DC bias characteristics Polymer capacitor is no capacitance change with DC bias due to aluminum oxidized film for dielectric.
EMI FIL®	Low-inductance product suitable for noise suppression. This product has extremely low ESL and is suitable for suppression of noise, including high frequencies. This product can also be used as a low-ESL, high-performance bypass capacitor.
Bonding	Product for bonding Since gold is used for the external electrodes, the capacitor can be mounted by die bonding/wire bonding.

D1 Derating 1

Derating 1
This product is suitable when a voltage continuously applied to a capacitor in an operating circuit, is used below (derated) the rated voltage of the capacitor. This model guarantees the test conditions in the endurance test, at a rated voltage x 100% at the maximum operating temperature. A reliability assurance level equivalent to a common product can be secured, by using this product within the voltage and temperature derated conditions recommended in the figure below.

Recommended Conditions of the Derating Operating Voltage and Temperature



D2 Derating 2

Derating 2
When the product temperature exceeds 105°C, please use this product within the voltage and temperature derated conditions in the figure below.



D3 Derating 3

Derating 3
Please apply the derating curve according to the operating temperature.
Please refer to detailed specifications sheet for details.

D4 Derating 4

Derating 4
When the product temperature exceeds 125°C, please use this product within the voltage and temperature derated conditions in the figure below.



D5 Derating 5

Derating 5
Please apply the rated voltage derating over 150 °C.
Please refer to detailed specifications sheet for details.

Selection Guide for Capacitors

For general

General

SMD

Solder mounting

Chip type

GRM			p40
GRM		For LCD backlight inverter circuit only	WEB
GR3	Anti-noise	High effective capacitance & high ripple current	p109
GRJ	Deflecting crack	Soft termination	p120
GXM	Water Repellent		WEB
GR4		For information devices only	p125
GR7		For camera flash circuit only	p130
GJM	High Q		p135
GQM	High Q	High power	p164
GA2	Japanese Safety Law	Based on the Electrical Appliance and Material Safety Law of Japan	p184
GA3	Safety standard		p189
LLL	Low ESL	LW reversed	p219
LLA	Low ESL	8 terminals	p222
LLM	Low ESL	10 terminals	p228
LLR	Low ESL	LW reversed controlled ESR	p232
NFM	Low ESL	3 terminals	p236
GJ4	Anti-noise	Low distortion	WEB
GJ8	Anti-noise	Low acoustic noise	WEB

On interposer board

ZRA	Anti-noise		WEB
ZRB	Anti-noise		WEB

Metal terminal type

KRM	Anti-noise, Deflecting crack, Soldering crack		p239
KR3	Anti-noise, Deflecting crack, Soldering crack	High effective capacitance & high ripple current	p243

Resin molding SMD type

DK1	Safety standard		WEB

Wire bonding mounting

Bonding

Chip type

GMA		Microchip	p249
GMD			p256

Lead type

Solder mounting

RDE	Anti-noise, Deflecting crack, Soldering crack		WEB
DEH		High temperature low loss	WEB
DEA		High temperature Class 1	WEB
DEB		Class 2	WEB
DEC			WEB
DEF		For LCD backlight inverter circuit only	WEB
DHR	Ultrahigh-voltage, Deflecting crack, Soldering crack		WEB
DEJ	Japanese Safety Law	Based on the Electrical Appliance and Material Safety Law of Japan	WEB
DE1	Safety standard	X1/Y1 Class certified product	WEB
DE2	Safety standard	X1/Y2 Class certified product	WEB

Screw termination mounting

DHS	Ultrahigh-voltage		WEB
DHK	Ultrahigh-voltage	High voltage AC rated	WEB

Infotainment for automotive

Infotainment, AEC-Q200

SMD

Solder mounting

Chip type

GRT			WEB

Powertrain/Safety for automotive

Powertrain, AEC-Q200

SMD

Solder mounting

Chip type

GCM			WEB
GC3	Anti-noise	High effective capacitance & high ripple current	WEB
GCJ	Fail safe, Deflecting crack	Soft termination	WEB
GGM	Water Repellent		WEB
GCQ	High Q		WEB
GCD	Fail safe, Deflecting crack	MLSC design	WEB
GCE	Fail safe, Deflecting crack	Soft termination MLSC design	WEB
GGD	Fail safe, Deflecting crack, Water Repellent	MLSC design	WEB
NFM	Low ESL	3 terminals	WEB

Metal terminal type

KCM	Anti-noise, Deflecting crack, Soldering crack		WEB
KC3	Anti-noise, Deflecting crack, Soldering crack	High effective capacitance & high ripple current	WEB
KCA	Safety standard, Anti-noise, Deflecting crack, Soldering crack		WEB

Limited to Conductive Glue Mounting

Limited to conductive glue mounting

Chip type

GCB	Deflecting crack, Soldering crack	Ni plating + Pd plating termination conductive glue mounting	WEB
GCG	Deflecting crack, Soldering crack	AgPd termination conductive glue mounting	WEB

Lead type

Solder mounting

RCE	Anti-noise, Deflecting crack, Soldering crack		WEB
RHE	Anti-noise, Deflecting crack, Soldering crack	150°C operation leaded	WEB
RHS	Anti-noise, Deflecting crack, Soldering crack	200°C operation leaded	WEB
DE6	Safety standard		WEB

Medical-grade products for implanted medical devices

Medical Device

SMD

Solder mounting

Chip type

GCH			WEB

Catalog Information

Catalog relates to a multilayer ceramic capacitor is below.



Chip Multilayer Ceramic Capacitors for General

Cat No. C02E-21



Chip Multilayer Ceramic Capacitors for Automotive

Cat No. C03E-9



Safety Certified Ceramic Capacitors/ High Voltage Ceramic Capacitors

Cat No. C85E-5



Radial Lead Type Monolithic Ceramic Capacitors

Cat No. C49E-23

Part Numbering

Chip Multilayer Ceramic Capacitors for General

WEB

(Part Number)

GR	M	18	8	B1	1H	102	K	A01	D
❶	❷	❸	❹	❺	❻	❼	❽	❾	❿

❶Product ID ❷Series

Product ID	Code	Series
GA	2	Based on the Electrical Appliance and Material Safety Law of Japan Chip Multilayer Ceramic Capacitors for General Purpose
	3	Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose
GJ	M	High Q Chip Multilayer Ceramic Capacitors for General Purpose
GM	A	Wire Bonding Mount Multilayer Microchip Capacitors for General Purpose
	D	Wire Bonding/AuSn Soldering Mount Chip Multilayer Ceramic Capacitors for General Purpose
GQ	M	High Q and High Power Chip Multilayer Ceramic Capacitors for General Purpose
GR	3	High Effective Capacitance & High Ripple Current Chip Multilayer Ceramic Capacitors for General Purpose
	4	Chip Multilayer Ceramic Capacitors for Camera Flash Circuit only
	7	Chip Multilayer Ceramic Capacitors for Ethernet LAN and Primary-secondary Coupling of DC-DC Converters
	J	Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose
	M	Chip Multilayer Ceramic Capacitors for General Purpose
KR	3	High Effective Capacitance & High Allowable Ripple Current Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
	M	Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
LL	A	8 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
	L	LW Reversed Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
	M	10 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
	R	LW Reversed Controlled ESR Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

❸Chip Dimensions (LxW)

Code	Dimensions (LxW)	EIA
02	0.4x0.2mm	01005
0D	0.38x0.38mm	015015
03	0.6x0.3mm	0201
05	0.5x0.5mm	0202
08	0.8x0.8mm	0303
1U	0.6x1.0mm	02404
15	1.0x0.5mm	0402
18	1.6x0.8mm	0603
21	2.0x1.25mm	0805
22	2.8x2.8mm	1111
31	3.2x1.6mm	1206
32	3.2x2.5mm	1210
42	4.5x2.0mm	1808
43	4.5x3.2mm	1812
52	5.7x2.8mm	2211
55	5.7x5.0mm	2220

Continued on the following page.↗

(Part Number) GR M 18 8 B1 1H 102 K A01 D
❶ ❷ ❸ ❹ ❺ ❻ ❼ ❽ ❾ ❿

Continued from the preceding page.↘

❹Height Dimension (T) (Except **KR**□)

Code	Dimension (T)
2	0.2mm
3	0.3mm
4	0.4mm
5	0.5mm
6	0.6mm
7	0.7mm
8	0.8mm
9	0.85mm
A	1.0mm
B	1.25mm
C	1.6mm
D	2.0mm
E	2.5mm
M	1.15mm
Q	1.5mm
X	Depends on individual standards.

❹Height Dimension (T) (**KR**□ Only)

Code	Dimension (T)
E	1.8mm
F	1.9mm
K	2.7mm
L	2.8mm
Q	3.7mm
T	4.8mm
W	6.4mm

❺Temperature Characteristics

Temperature Characteristic Codes			Temperature Characteristics			Operating Temperature Range	Capacitance Change Each Temperature (%)					
Code	Public STD Code		Reference Temperature	Temperature Range	Capacitance Change or Temperature Coefficient		−55°C		*6		−10°C	
							Max.	Min.	Max.	Min.	Max.	Min.
1X	SL	JIS	20°C	20 to 85°C	+350 to −1000ppm/°C	−55 to 125°C	-	-	-	-	-	-
2C	CH	JIS	20°C	20 to 125°C	0±60ppm/°C	−55 to 125°C	0.82	−0.45	0.49	−0.27	0.33	−0.18
3C	CJ	JIS	20°C	20 to 125°C	0±120ppm/°C	−55 to 125°C	1.37	−0.9	0.82	−0.54	0.55	−0.36
3U	UJ	JIS	20°C	20 to 85°C	−750±120ppm/°C	−25 to 85°C	-	-	4.94	2.84	3.29	1.89
4C	CK	JIS	20°C	20 to 125°C	0±250ppm/°C	−55 to 125°C	2.56	−1.88	1.54	−1.13	1.02	−0.75
5C	C0G	EIA	25°C	25 to 125°C	0±30ppm/°C	−55 to 125°C	0.58	−0.24	0.4	−0.17	0.25	−0.11
5G	X8G	*2	25°C	25 to 150°C	0±30ppm/°C	−55 to 150°C	0.58	−0.24	0.4	−0.17	0.25	−0.11
7U	U2J	EIA	25°C	25 to 125°C *3	−750±120ppm/°C	−55 to 125°C	8.78	5.04	6.04	3.47	3.84	2.21
B1	B *1	JIS	20°C	−25 to 85°C	±10%	−25 to 85°C	-	-	-	-	-	-
B3	B	JIS	20°C	−25 to 85°C	±10%	−25 to 85°C	-	-	-	-	-	-
C7	X7S	EIA	25°C	−55 to 125°C	±22%	−55 to 125°C	-	-	-	-	-	-
C8	X6S	EIA	25°C	−55 to 105°C	±22%	−55 to 105°C	-	-	-	-	-	-
D7	X7T	EIA	25°C	−55 to 125°C	+22%, −33%	−55 to 125°C	-	-	-	-	-	-
D8	X6T	EIA	25°C	−55 to 105°C	+22%, −33%	−55 to 105°C	-	-	-	-	-	-
E7	X7U	EIA	25°C	−55 to 125°C	+22%, −56%	−55 to 125°C	-	-	-	-	-	-
R1	R *1	JIS	20°C	−55 to 125°C	±15%	−55 to 125°C	-	-	-	-	-	-
R6	X5R	EIA	25°C	−55 to 85°C	±15%	−55 to 85°C	-	-	-	-	-	-
R7	X7R	EIA	25°C	−55 to 125°C	±15%	−55 to 125°C	-	-	-	-	-	-
W0	X7T	EIA	25°C	−55 to 125°C	±10% *4	−55 to 125°C	-	-	-	-	-	-
					+22%, −33% *5		-	-	-	-	-	-

*1 Capacitance change is specified with 50% rated voltage applied.
*2 Murata Temperature Characteristic Code.
*3 Rated Voltage 100Vdc max: 25 to 85°C
*4 Apply DC350V bias.
*5 No DC bias.
*6 −25°C (Reference Temperature 20°C) / −30°C (Reference Temperature 25°C)

Continued on the following page.↗

(Part Number)

GR	M	18	8	B1	1H	102	K	A01	D
❶	❷	❸	❹	❺	❻	❼	❽	❾	❿

Continued from the preceding page.↘

❻Rated Voltage

Code	Rated Voltage
0E	DC2.5V
0G	DC4V
0J	DC6.3V
1A	DC10V
1C	DC16V
1E	DC25V
1H	DC50V
1J	DC63V
1K	DC80V
2A	DC100V
2D	DC200V
2E	DC250V
2W	DC450V
2H	DC500V
2J	DC630V
3A	DC1kV
3D	DC2kV
3F	DC3.15kV
BB	DC350V
E2	AC250V
GB	X2; AC250V (Safety Standard Certified Type GB)
GD	Y3; AC250V (Safety Standard Certified Type GD)
GF	Y2, X1/Y2; AC250V (Safety Standard Certified Type GF)
YA	DC35V

❼Capacitance

Expressed by three-digit alphanumerics. The unit is picofarad (pF). The first and second figures are significant digits, and the third figure expresses the number of zeros which follow the two numbers. If there is a decimal point, it is expressed by the capital letter "**R**." In this case, all figures are significant digits.
If any alphabet, other than "**R**", is included, this indicates the specific part number is a non-standard part.

Ex.)

Code	Capacitance
R50	0.50pF
1R0	1.0pF
100	10pF
103	10000pF

❽Capacitance Tolerance

Code	Capacitance Tolerance
B	±0.1pF
C	±0.25pF
D	±0.5pF (Less than 10pF)
	±0.5% (10pF and over)
F	±1%
G	±2%
J	±5%
K	±10%
M	±20%
W	±0.05pF

❾Individual Specification Code (Except **LLR**)

Expressed by three figures.

❾ESR (**LLR** Only)

Code	ESR
E01	100mΩ
E03	220mΩ
E05	470mΩ
E07	1000mΩ

❿Packaging

Code	Packaging
L	ø180mm Embossed Taping
D/E/W	ø180mm Paper Taping
K	ø330mm Embossed Taping
J/F	ø330mm Paper Taping
T	Bulk Tray

Please contact us if you find any part number not provided in this table.

3 Terminal Low ESL Multilayer Ceramic Capacitors

WEB

(Part Number)

NF	M	3D	CC	102	R	1H	3	L
❶	❷	❸	❹	❺	❻	❼	❽	❾

❶Product ID ❷Series

Product ID	Series
NFM	3 Terminals Low ESL Chip Multilayer Ceramic Capacitors

❸Dimensions (LxW)

Code	Dimensions (LxW)	EIA
15	1.0x0.5mm	0402
18	1.6x0.8mm	0603
21	2.0x1.25mm	0805
3D	3.2x1.25mm	1205
31	3.2x1.6mm	1206
41	4.5x1.6mm	1806

❹Features

Code	Features	
CC	For General	For Signal Lines
PC		For Large Current
PS		High Insertion Loss Type for Large Current
KC		For Very Large Current

❺Capacitance

Expressed by three figures. The unit is in pico-farad (pF). The first and second figures are significant digits, and the third figure expresses the number of zeros that follow the two figures.

❻Characteristics

Code	Capacitance Temperature Characteristics
B	±10%, ±12.5%, +10/-13%
C	±22%
D	+22/-33%
F	+30/-80%, +30/-84%
R	±15%, +15/-18%

❼Rated Voltage

Code	Rated Voltage
0E	2.5V
0G	4V
0J	6.3V
1A	10V
1C	16V
1E	25V
1H	50V
2A	100V

❽Electrode

Code	Electrode
3	Sn Plating

❾Packaging

Code	Packaging
B	Bulk
L	Embossed Taping (ø180mm Reel)
D	Paper Taping (ø180mm Reel)

Capacitance Table

How to read the Capacitance Table

L×W (mm)	0.4×0.2		0.6		
T max. (mm)	0.22		0.		
Rated Voltage (Vdc)	25		50		
Cap. / TC Code	C0G	CΔ	C0G	CK	CJ
0.10pF					
0.20pF	p140	p143	p146	p146	
1.0pF	p140	p143		p146	
2.0pF	p140	p143		p146	
3.0pF	p140	p143			p146

The values can be narrowed down in the order of size, rated voltage, and temperature characteristics.

Refers to the page of the part number list.
Check the part number list for the applicable product number.

Temperature Characteristics Table

The Table is colored by temperature characteristic codes.
Refer to the following Table for the meaning of each code.

EIA: C0G U2J X7R X7S X7T X7U X6S X6T X5R
JIS: CK CJ CH SL UJ R B
Murata Temperature Characteristic: X8G

Temperature Characteristic Codes		Temperature Characteristics			Operating Temperature Range	Capacitance Change Each Temperature (%)					
Public STD Code		Reference Temperature	Temperature Range	Capacitance Change or Temperature Coefficient		−55°C		*3		−10°C	
						Max.	Min.	Max.	Min.	Max.	Min.
C0G	EIA	25°C	25 to 125°C	0±30ppm/°C	−55 to 125°C	0.58	−0.24	0.4	−0.17	0.25	−0.11
CK	JIS	20°C	20 to 125°C	0±250ppm/°C	−55 to 125°C	2.56	−1.88	1.54	−1.13	1.02	−0.75
CJ	JIS	20°C	20 to 125°C	0±120ppm/°C	−55 to 125°C	1.37	−0.9	0.82	−0.54	0.55	−0.36
CH	JIS	20°C	20 to 125°C	0±60ppm/°C	−55 to 125°C	0.82	−0.45	0.49	−0.27	0.33	−0.18
SL	JIS	20°C	20 to 85°C	+350 to −1000ppm/°C	−55 to 125°C	-	-	-	-	-	-
U2J	EIA	25°C	25 to 125°C *2	−750±120ppm/°C	−55 to 125°C	8.78	5.04	6.04	3.47	3.84	2.21
UJ	JIS	20°C	20 to 85°C	−750±120ppm/°C	−25 to 85°C	-	-	4.94	2.84	3.29	1.89
X8G	*1	25°C	25 to 150°C	0±30ppm/°C	−55 to 150°C	0.58	−0.24	0.4	−0.17	0.25	−0.11
X7R	EIA	25°C	−55 to 125°C	±15%	−55 to 125°C	-	-	-	-	-	-
X7S	EIA	25°C	−55 to 125°C	±22%	−55 to 125°C	-	-	-	-	-	-
X7T	EIA	25°C	−55 to 125°C	+22%, −33%	−55 to 125°C	-	-	-	-	-	-
X7U	EIA	25°C	−55 to 125°C	+22%, −56%	−55 to 125°C	-	-	-	-	-	-
R	JIS	20°C	−55 to 125°C	±15%	−55 to 125°C	-	-	-	-	-	-
X6S	EIA	25°C	−55 to 105°C	±22%	−55 to 105°C	-	-	-	-	-	-
X6T	EIA	25°C	−55 to 105°C	+22%, −33%	−55 to 105°C	-	-	-	-	-	-
X5R	EIA	25°C	−55 to 85°C	±15%	−55 to 85°C	-	-	-	-	-	-
B	JIS	20°C	−25 to 85°C	±10%	−25 to 85°C	-	-	-	-	-	-

*1 Murata Temperature Characteristic Code.
*2 Rated Voltage 100Vdc max: 25 to 85°C
*3 −25°C (Reference Temperature 20°C) / −30°C (Reference Temperature 25°C)

Capacitance Table

GRM Series Temperature Compensating Type

p00 ← Part Number List JIS: CK CJ CH SL UJ EIA: C0G U2J

L×W (mm)	0.4×0.2						0.6×0.3						1.0×0.5							1.6×0.8							
T max. (mm)	0.22						0.33						0.55							0.5						0.9	
Rated Voltage (Vdc)	50		25		16		100		50		25		100		50		10			50			10			100	
Cap. / TC Code	C0G	CΔ	C0G	CH	C0G	CH	C0G	CΔ	C0G	CΔ	C0G	CH	C0G	CΔ	C0G	CΔ	SL	U2J	UJ	SL	U2J	UJ	SL	U2J	UJ	C0G	CΔ
0.10pF							p48	p51	p55	p58			p62	p65	p69	p72											
0.20pF	p41	p44					p48	p51	p55	p58			p62	p65	p69	p72											
0.50pF	p41	p44					p48	p51	p55	p58			p62	p65	p69	p72										p76	p79
1.0pF	p41	p44					p48	p51	p55	p58			p62	p65	p69	p72										p76	p80
2.0pF	p41	p44					p48	p52	p55	p58			p62	p66	p69	p73										p77	p80
3.0pF	p41	p45					p48	p52	p55	p59			p63	p66	p69	p73										p77	p80
4.0pF	p42	p45					p49	p52	p56	p59			p63	p66	p70	p73										p77	p80
5.0pF	p42	p45					p49	p52	p56	p59			p63	p66	p70	p73										p77	p81
6.0pF	p42	p46					p49	p53	p56	p60			p63	p67	p70	p74										p78	p81
7.0pF	p43	p46					p50	p53	p57	p60			p64	p67	p71	p74										p78	p81
8.0pF	p43	p46					p50	p53	p57	p60			p64	p68	p71	p74										p79	p82
9.0pF	p43	p47					p50	p54	p57	p61			p65	p68	p71	p75										p79	p82
10pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
11pF	p44	p47																									
12pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
13pF	p44	p47																									
15pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
16pF	p44	p47																									
17pF	p44	p47																									
18pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
19pF	p44	p47																									
20pF	p44	p47					p51	p54																			
21pF	p44	p47																									
22pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
23pF	p44	p47																									
24pF	p44	p47					p51	p54																			
27pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
30pF	p44	p47					p51	p54																			
33pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
36pF	p44	p47					p51	p54																			
39pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
43pF	p44	p47					p51	p54																			
47pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
51pF	p44	p47					p51	p54																			
56pF	p44	p47					p51	p54	p58	p61			p65	p68	p72	p75										p79	p83
62pF	p44	p47					p51	p55																			
68pF	p44	p47					p51	p55	p58	p61			p65	p68	p72	p75										p79	p83
75pF	p44	p47					p51	p55																			
82pF	p44	p47					p51	p55	p58	p61			p65	p68	p72	p75										p79	p83
91pF	p44	p47					p51	p55																			
100pF	p44	p47					p51	p55	p58	p61			p65	p69	p72	p75										p79	p83
120pF			p47	p47	p47	p47			p58	p61					p72	p75										p79	p83
150pF			p47	p47	p47	p48			p58	p61					p72	p75										p79	p83
180pF			p47	p47	p47	p48			p58	p61					p72	p75										p79	p83
220pF			p47	p47	p47	p48			p58	p61					p72	p76										p79	p83
270pF											p61	p62			p72	p76										p79	p83
330pF											p61	p62			p72	p76										p79	p83
390pF											p62	p62			p72	p76										p79	p83
470pF											p62	p62			p72	p76										p79	p83
560pF											p62	p62			p72	p76										p79	p83
680pF											p62	p62			p72	p76										p79	p83
820pF											p62	p62			p72	p76										p79	p83
910pF											p62																
1000pF											p62	p62			p72	p76										p79	p83
1200pF																	p76	p76	p76							p79	p83
1500pF																	p76	p76	p76							p79	p83
1800pF																	p76	p76	p76								
2200pF																	p76	p76	p76	p76	p76	p76					
2700pF																	p76	p76	p76	p76	p76	p76					
3300pF																	p76	p76	p76	p76	p76	p76					
3900pF																	p76	p76	p76	p76	p76	p76					
4700pF																	p76	p76	p76	p76	p76	p76					
5600pF																							p76	p76	p76		
6800pF																							p76	p76	p76		
8200pF																							p76	p76	p76		
10000pF																							p76	p76	p76		
12000pF																											
15000pF																											
18000pF																											
22000pF																											
27000pF																											
33000pF																											
39000pF																											
47000pF																											
56000pF																											
68000pF																											
82000pF																											
0.10μF																											
0.12μF																											

The indication for every 0.1 pF has been omitted for less than 10 pF. Refer to the Part Number List for details.

Continued on the following page.↗

Capacitance Table

(→ GRM Series Temperature Compensating Type)

p00 ← Part Number List JIS: CK CJ CH SL UJ EIA: C0G U2J

L×W (mm)	1.6×0.8								2.0×1.25																		
T max. (mm)	0.9								0.7							0.95								1.0			
Rated Voltage (Vdc)	50					10			100		50					50					10			630	250		200
Cap. / TC Code	C0G	CΔ	SL	U2J	UJ	SL	U2J	UJ	C0G	CH	C0G	CH	SL	U2J	UJ	C0G	CH	SL	U2J	UJ	SL	U2J	UJ	C0G	C0G	U2J	C0G
0.10pF																											
0.20pF																											
0.50pF	p83	p86																									
1.0pF	p83	p86																									
2.0pF	p83	p87																									
3.0pF	p83	p87																									
4.0pF	p84	p87																									
5.0pF	p84	p87																									
6.0pF	p84	p88																									
7.0pF	p85	p88																									
8.0pF	p85	p88																									
9.0pF	p85	p89																									
10pF	p86	p89																						p91	p91		p91
11pF																											
12pF	p86	p89																						p91	p91		p92
13pF																											
15pF	p86	p89																						p91	p91		p92
16pF																											
17pF																											
18pF	p86	p89																						p91	p91		p92
19pF																											
20pF																											
21pF																											
22pF	p86	p89																						p91	p91		p92
23pF																											
24pF																											
27pF	p86	p89																						p91	p91		p92
30pF																											
33pF	p86	p89																						p91	p91		p92
36pF																											
39pF	p86	p89																						p91	p91		p92
43pF																											
47pF	p86	p89																						p91	p91		p92
51pF																											
56pF	p86	p89																						p91	p91		p92
62pF																											
68pF	p86	p89																						p91	p91		p92
75pF																											
82pF	p86	p89																						p91	p91		p92
91pF																											
100pF	p86	p89							p90	p90														p91	p91	p91	p92
120pF	p86	p89							p90	p90														p91	p91	p91	p92
150pF	p86	p89							p90	p90														p91	p91	p91	p92
180pF	p86	p89							p90	p90														p91	p91	p91	p92
220pF	p86	p89							p90	p90														p91	p91	p91	p92
270pF	p86	p89							p90	p90														p91	p91	p91	p92
330pF	p86	p89							p90	p90														p91	p91	p91	p92
390pF	p86	p89							p90	p90														p91	p91	p91	
470pF	p86	p89							p90	p90														p91	p91	p91	
560pF	p86	p89							p90	p90														p91	p91	p91	
680pF	p86	p89							p90	p90															p91	p91	
820pF	p86	p89							p90	p90															p91	p91	
910pF																											
1000pF	p86	p89			p90				p90	p90															p91	p91	
1200pF	p86	p89	p90	p90	p90				p90	p90	p90	p90													p91	p91	
1500pF	p86	p89	p90	p90	p90				p90	p90	p91	p90													p91	p91	
1800pF	p86	p89	p90	p90	p90				p90	p90	p91	p90													p91	p91	
2200pF	p86	p89	p90	p90	p90				p90	p90	p91	p90													p91	p91	
2700pF	p86	p89	p90	p90	p90				p90	p90	p91	p90													p91		
3300pF	p86	p90	p90	p90	p90				p90	p90	p91	p90															
3900pF	p86	p90	p90	p90	p90						p91	p90															
4700pF	p86	p90	p90	p90	p90						p91	p90															
5600pF	p86	p90	p90	p90	p90											p91	p91										
6800pF	p86	p90	p90	p90	p90											p91	p91										
8200pF	p86	p90	p90	p90	p90											p91	p91										
10000pF	p86	p90	p90	p90	p90										p91	p91	p91										
12000pF						p90	p90	p90					p91	p91	p91	p91	p91										
15000pF						p90	p90	p90					p91	p91	p91	p91	p91										
18000pF						p90	p90	p90					p91	p91	p91												
22000pF						p90	p90	p90										p91	p91	p91							
27000pF																		p91	p91	p91							
33000pF																											
39000pF																											
47000pF																											
56000pF																					p91	p91	p91				
68000pF																											
82000pF																											
0.10μF																											
0.12μF																											

Continued on the following page.↗

Capacitance Table

(→ GRM Series Temperature Compensating Type)

p00 ← Part Number List JIS: CK CJ CH SL UJ EIA: C0G U2J

L×W (mm)	2.0×1.25																3.2×1.6										
T max. (mm)	1.0				1.35								1.45				0.95							1.0			
Rated Voltage (Vdc)	200	50			50					10			630	250		200	100		50					2000	1000		630
Cap. / TC Code	U2J	SL	U2J	UJ	C0G	CH	SL	U2J	UJ	SL	U2J	UJ	C0G	C0G	U2J	U2J	C0G	CH	C0G	CH	SL	UJ	U2J	U2J	C0G	U2J	C0G
0.10pF																											
0.20pF																											
0.50pF																											
1.0pF																											
2.0pF																											
3.0pF																											
4.0pF																											
5.0pF																											
6.0pF																											
7.0pF																											
8.0pF																											
9.0pF																											
10pF																							p93	p93	p93	p93	p93
11pF																											
12pF																							p93	p93	p93	p93	p93
13pF																											
15pF																							p93	p93	p93	p93	p93
16pF																											
17pF																											
18pF																							p93	p93	p93	p93	p93
19pF																											
20pF																											
21pF																											
22pF																							p93	p93	p93	p93	p93
23pF																											
24pF																											
27pF																							p93	p93	p93	p93	p93
30pF																											
33pF																							p93	p93	p93	p93	p93
36pF																											
39pF																							p93	p93	p93	p93	p93
43pF																											
47pF																							p93	p93	p93	p93	p93
51pF																											
56pF																							p93	p93	p93	p93	p93
62pF																											
68pF																							p93	p93	p93	p93	p93
75pF																											
82pF																								p93	p93	p93	p93
91pF																											
100pF	p92																							p93	p93	p93	p93
120pF	p92																							p93	p93	p93	p93
150pF	p92																							p93	p93	p93	p93
180pF	p92																							p93	p93	p93	p93
220pF	p92																							p93	p93	p93	p93
270pF	p92																							p93	p93	p93	p93
330pF	p92																							p93	p93	p93	p93
390pF	p92																							p93		p93	p93
470pF	p92																							p93		p93	p93
560pF	p92																									p93	p93
680pF	p92												p92														
820pF	p92												p92														
910pF																											
1000pF	p92												p92														
1200pF	p92												p92														p93
1500pF	p92																										p93
1800pF	p92																p92	p92									p93
2200pF	p92																p92	p92									
2700pF															p92	p92	p92	p92									
3300pF														p92	p92	p92	p92	p92									
3900pF														p92	p92	p92	p92	p92									
4700pF														p92	p92	p92	p92	p92									
5600pF															p92	p92	p92	p92									
6800pF																	p92	p92									
8200pF																	p92	p92									
10000pF																	p92	p92									
12000pF																	p92	p92	p93	p93							
15000pF																	p92	p92	p93	p93							
18000pF					p92	p92											p92	p93	p93	p93							
22000pF					p92	p92											p92	p93	p93	p93							
27000pF																	p92	p93	p93	p93							
33000pF		p92	p92	p92													p92	p93	p93	p93							
39000pF							p92	p92	p92								p92	p93	p93	p93							
47000pF							p92	p92	p92																		
56000pF																					p93	p93	p93				
68000pF										p92	p92	p92															
82000pF										p92	p92	p92															
0.10μF										p92	p92	p92															
0.12μF																											

Continued on the following page.↗

Capacitance Table

(→ GRM Series Temperature Compensating Type)

p00 ← Part Number List JIS: CK CJ CH SL UJ EIA: C0G U2J

L×W (mm)	3.2×1.6																										
T max. (mm)	1.0						1.25															1.8					
Rated Voltage (Vdc)	630	500		250		200	1000		630		500		250		200	100		50				1000		630		500	
Cap. / TC Code	U2J	C0G	U2J	C0G	U2J	U2J	C0G	U2J	C0G	U2J	C0G	U2J	C0G	U2J	U2J	C0G	CH	C0G	CH	SL	U2J	UJ	C0G	U2J	C0G	U2J	U2J
0.10pF																											
0.20pF																											
0.50pF																											
1.0pF																											
2.0pF																											
3.0pF																											
4.0pF																											
5.0pF																											
6.0pF																											
7.0pF																											
8.0pF																											
9.0pF																											
10pF	p93	p94	p94																								
11pF																											
12pF	p93	p94	p94																								
13pF																											
15pF	p93	p94	p94																								
16pF																											
17pF																											
18pF	p93	p94	p94																								
19pF																											
20pF																											
21pF																											
22pF	p93	p94	p94																								
23pF																											
24pF																											
27pF	p93	p94	p94																								
30pF																											
33pF	p93	p94	p94																								
36pF																											
39pF	p93	p94	p94																								
43pF																											
47pF	p93	p94	p94																								
51pF																											
56pF	p93	p94	p94																								
62pF																											
68pF	p94	p94	p94																								
75pF																											
82pF	p94	p94	p94																								
91pF																											
100pF	p94	p94	p94																								
120pF	p94	p94	p94																								
150pF	p94	p94	p94																								
180pF	p94	p94	p94																								
220pF	p94	p94	p94																								
270pF	p94	p94	p94																								
330pF	p94	p94	p94																								
390pF	p94	p94	p94	p94				p94																			
470pF	p94	p94	p94	p94				p94																			
560pF	p94	p94	p94	p94			p94	p94																			
680pF	p94		p94	p94			p94	p94	p94		p95																
820pF	p94		p94	p94					p94		p95											p95	p95				
910pF																											
1000pF	p94		p94	p94					p94		p95											p95	p95				
1200pF	p94		p94	p94																							
1500pF	p94		p94	p94																							
1800pF	p94		p94	p94																							
2200pF	p94		p94	p94					p94																		
2700pF				p94	p94	p94			p94	p94		p95															
3300pF				p94	p94	p94				p95		p95												p95			
3900pF				p94	p94	p94																			p95	p95	
4700pF				p94	p94	p94																			p95	p95	
5600pF				p94	p94	p94																					
6800pF				p94										p95	p95												
8200pF													p95	p95	p95												
10000pF													p95	p95	p95												
12000pF													p95	p95													
15000pF																											
18000pF																											
22000pF																											
27000pF																											
33000pF																											
39000pF																											
47000pF																p95	p95	p95	p95								
56000pF																p95	p95	p95	p95								
68000pF																				p95	p95	p95					
82000pF																				p95	p95	p95					
0.10μF																				p95	p95	p95					
0.12μF																											

Continued on the following page.↗

Capacitance Table

(→ GRM Series Temperature Compensating Type)

p00 ← Part Number List JIS: CK CJ CH SL UJ EIA: C0G U2J

L×W (mm)	3.2×1.6										3.2×2.5															4.5×2.0	4.5×3.2
T max. (mm)	1.8										1.0			1.25				1.5				2.0				1.0	1.5
Rated Voltage (Vdc)	250		100		50		25		16		2000	630	500	2000	1000	630	500	1000	630	500	250	1000	630	500	250	3150	1000
Cap. / TC Code	C0G	U2J	C0G	CH	C0G	CH	C0G	CH	C0G	CH	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J
0.10pF																											
0.20pF																											
0.50pF																											
1.0pF																											
2.0pF																											
3.0pF																											
4.0pF																											
5.0pF																											
6.0pF																											
7.0pF																											
8.0pF																											
9.0pF																											
10pF																										p95	
11pF																											
12pF																										p95	
13pF																											
15pF																										p95	
16pF																											
17pF																											
18pF																										p95	
19pF																											
20pF																											
21pF																											
22pF																										p95	
23pF																											
24pF																											
27pF																										p95	
30pF																											
33pF																										p96	
36pF																											
39pF																										p96	
43pF																											
47pF																										p96	
51pF																											
56pF																										p96	
62pF																											
68pF																										p96	
75pF																											
82pF											p95															p96	
91pF																											
100pF											p95															p96	
120pF											p95																
150pF											p95																
180pF														p95													
220pF														p95													
270pF																											
330pF																											
390pF																											
470pF																											
560pF																											
680pF																											
820pF																											
910pF																											
1000pF																											
1200pF												p95	p95		p95												
1500pF												p95	p95					p95									
1800pF												p95	p95									p95					
2200pF												p95	p95									p95					
2700pF																											p96
3300pF																											p96
3900pF																											
4700pF																											
5600pF																p95	p95										
6800pF																			p95	p95							
8200pF																							p95	p95			
10000pF																							p95	p95			
12000pF																											
15000pF	p95	p95																									
18000pF		p95																									
22000pF		p95																									
27000pF																					p95						
33000pF																									p95		
39000pF																									p95		
47000pF																									p95		
56000pF																											
68000pF			p95	p95	p95	p95																					
82000pF			p95	p95	p95	p95																					
0.10μF			p95	p95	p95	p95																					
0.12μF							p95	p95	p95	p95																	

Continued on the following page.↗

Capacitance Table

(→ GRM Series Temperature Compensating Type)

p00 ← Part Number List JIS: CK CJ CH SL UJ EIA: C0G U2J

L×W (mm)	4.5×3.2					5.7×5.0					
T max. (mm)	1.5		2.0			1.5			2.0		
Rated Voltage (Vdc)	630	500	1000	630	500	1000	630	500	1000	630	500
Cap. / TC Code	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J	U2J
0.10pF											
0.20pF											
0.50pF											
1.0pF											
2.0pF											
3.0pF											
4.0pF											
5.0pF											
6.0pF											
7.0pF											
8.0pF											
9.0pF											
10pF											
11pF											
12pF											
13pF											
15pF											
16pF											
17pF											
18pF											
19pF											
20pF											
21pF											
22pF											
23pF											
24pF											
27pF											
30pF											
33pF											
36pF											
39pF											
43pF											
47pF											
51pF											
56pF											
62pF											
68pF											
75pF											
82pF											
91pF											
100pF											
120pF											
150pF											
180pF											
220pF											
270pF											
330pF											
390pF											
470pF											
560pF											
680pF											
820pF											
910pF											
1000pF											
1200pF											
1500pF											
1800pF											
2200pF											
2700pF											
3300pF											
3900pF			p96								
4700pF			p96								
5600pF						p96					
6800pF						p96					
8200pF									p96		
10000pF									p96		
12000pF	p96	p96									
15000pF				p96	p96						
18000pF				p96	p96						
22000pF				p96	p96						
27000pF							p96	p96			
33000pF										p96	p96
39000pF										p96	p96
47000pF										p96	p96
56000pF											
68000pF											
82000pF											
0.10μF											
0.12μF											

Capacitance Table

GRM Series High Dielectric Constant Type

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	0.4×0.2							0.6×0.3														1.0×0.5		
T max. (mm)	0.22							0.33														0.22		
Rated Voltage (Vdc)	16	10		6.3		4	2.5	50		35	25			16		10		6.3			4	10	6.3	
Cap. / TC Code	X7R	X7R	X5R, B	X5R, B	X6T	X5R	X6T	X7R	X5R, B	X5R	X7R, R	X6S	X5R, B	X7Δ, R	X6S	X5R, B	X7Δ, R	X5R, B	X7R, R	X6S	X5R, B	X6S	X5R, B	X6S	X5R, B
100pF	p97	p97	p97 p97					p98	p98		p98													
150pF	p97	p97	p97 p97					p98	p98		p98													
220pF	p97	p97	p97 p97					p98	p98		p98													
330pF	p97	p97	p97 p97					p98	p98		p98													
470pF	p97	p97	p97 p97					p98	p98 p98		p98													
680pF		p97	p97 p97					p98	p98		p98													
820pF		p97																						
1000pF	p97	p97	p97 p97	p97 p97				p98	p98		p98 p98		p98											
1500pF			p97 p97	p97 p97				p98	p98		p98 p98		p98											
2200pF			p97 p97	p97 p97							p98		p98	p98 p98		p99								
3300pF			p97 p97	p97 p97							p98		p98	p98 p98		p99								
4700pF			p97 p97	p97 p97							p98		p98	p98			p99 p99	p99 p99	p99 p99		p99			
6800pF			p97 p97	p97 p97							p98		p98	p98			p99 p99	p99 p99	p99 p99		p99			
10000pF			p97 p97	p97 p97							p98		p98 p98	p98		p98 p99	p99 p99		p99 p99					
15000pF				p97		p97										p98 p99		p99 p99		p99	p99			
22000pF				p97		p97										p98 p99		p99 p99		p99	p99			
33000pF				p97		p98										p98 p99		p99 p99		p99	p99			
47000pF				p97		p98										p99 p99		p99 p99		p99				
68000pF				p97		p98										p99 p99		p99 p99		p99				
0.10μF				p97	p97	p98	p98			p98		p98	p98	p98	p98	p99 p99	p99	p99 p99		p99			p99 p100	p100 p100
0.15μF																								
0.22μF																		p99		p99	p99	p99	p100 p100	p100 p100
0.33μF																								
0.47μF																								p100 p100
0.68μF																								
1.0μF																								p100
2.2μF																								
4.7μF																								
10μF																								
22μF																								
47μF																								
100μF																								
150μF																								
220μF																								

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	1.0×0.5																									
T max. (mm)	0.22				0.3							0.33				0.55										
Rated Voltage (Vdc)	4			2.5	50		25		16		10	10	6.3		4	100	50			35		25				16
Cap. / TC Code	X7T	X6Δ	X5R	X7T	X7R, R	B	X7R	B	X7R	B	X5R	X5R, B	X6T	X5R, B	X6T	X7R	X7R, R	X6S	X5R, B	X6S	X5R	X7R, R	X6S	X5R, B	X7R, R
100pF																									
150pF																									
220pF					p100 p100	p100										p100	p101 p100		p101						
330pF					p100 p100	p100										p100	p101 p100		p101						
470pF					p100 p100	p100										p100	p101 p100		p101						
680pF					p100 p100	p100										p100	p101 p100		p101						
820pF																									
1000pF					p100 p100	p100										p100	p101 p100		p101						
1500pF					p100 p100	p100										p100	p101 p100		p101						
2200pF							p100	p100								p100	p101 p100		p101			p101		p101	
3300pF									p100	p100						p100	p101 p101		p101						
4700pF									p100	p100						p100	p101 p101		p101						p102
6800pF									p100	p100							p101 p101		p101			p101			
10000pF									p100	p100							p101 p101		p101			p101 p101		p101	p102
15000pF											p100						p101		p101			p101 p101		p101	
22000pF											p100						p101		p101			p101 p101		p101	
33000pF											p100						p101	p101	p101			p101 p101		p101	
47000pF																	p101	p101	p101			p101 p101		p102	
68000pF																	p101	p101	p101			p101		p101 p102	p102 p102
0.10μF	p100	p100		p100													p101		p101			p101		p101 p102	
0.15μF																									p102
0.22μF	p100	p100		p100																p101	p101		p101	p101	p102
0.33μF																									
0.47μF		p100																			p101			p101	
0.68μF																									
1.0μF		p100	p100									p100 p100	p100	p100 p100	p100				p101					p101 p102	
2.2μF																									
4.7μF																									
10μF																									
22μF																									
47μF																									
100μF																									
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	1.0×0.5																								
T max. (mm)	0.55											0.6							0.65						0.7
Rated Voltage (Vdc)	16		10			6.3			4			50	35	25	16	6.3	4	2.5	25	16		10		6.3	25
Cap. / TC Code	X6S	X5R, B	X7R	X6S	X5R, B	X7R	X6S	X5R, B	X7R	X6S	X5R	X5R	X5R	X6S	X6S	X5R, B	X5R, B	X6T	X6T	X7T	X6T	X7T	X5R	X6S	X5R
100pF																									
150pF																									
220pF																									
330pF																									
470pF																									
680pF																									
820pF																									
1000pF																									
1500pF																									
2200pF																									
3300pF																									
4700pF																									
6800pF																									
10000pF		p102																							
15000pF																									
22000pF																									
33000pF					p102																				
47000pF																									
68000pF																									
0.10μF					p102			p102																	
0.15μF					p102 p102			p102 p102																	
0.22μF		p102	p102		p102 p102		p102	p102 p102		p102															
0.33μF					p102 p102			p102 p102																	
0.47μF	p102		p102		p102 p102			p102 p102				p102													
0.68μF					p102 p102			p102 p102																	
1.0μF		p102 p102		p102	p102 p102	p102		p102 p102	p102		p102		p102	p102	p102										
2.2μF					p102		p102	p102											p102	p103	p103	p103			p103
4.7μF																p102 p102	p102 p102	p102					p103	p103	
10μF																									
22μF																									
47μF																									
100μF																									
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	1.0×0.5							1.6×0.8																
T max. (mm)	0.7							0.5				0.55					0.9							
Rated Voltage (Vdc)	16		10		6.3	4	2.5	25	16	6.3	4	16	10		6.3		250	200	25		16		10	6.3
Cap. / TC Code	X6S	X5R	X7S	X6S	X7S	X5R	X5R	X5R, B	X5R, B	X5R	X5R	X5R	X6S	X5R	X7T	X6S	X7R	X7R	X7R	X5R, B	X6S	X5R, B	X7R	X5R	X6S
100pF																									
150pF																									
220pF																	p103	p103							
330pF																	p103	p103							
470pF																	p103	p103							
680pF																	p103	p103							
820pF																									
1000pF																	p103	p103							
1500pF																	p103	p103							
2200pF																	p103	p103							
3300pF																									
4700pF																									
6800pF																									
10000pF																									
15000pF																									
22000pF																									
33000pF																									
47000pF																									
68000pF																									
0.10μF																									
0.15μF																									
0.22μF																									
0.33μF																									
0.47μF																									
0.68μF																									
1.0μF								p103	p103	p103	p103								p103						
2.2μF	p103	p103	p103	p103	p103															p103	p103	p103	p103	p103	p103	
4.7μF												p103	p103	p103	p103	p103									p103	p103
10μF						p103	p103			p103	p103														
22μF																									
47μF																									
100μF																									
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	1.6×0.8																				2.0×1.25				
T max. (mm)	0.9		0.95					1.0													0.7	0.95			
Rated Voltage (Vdc)	6.3	4	25	16		10		50	35		25			16		10	6.3		4		16	50	35		25
Cap. / TC Code	X5R, B	X5R	X5R	X6S	X5R, B	X7S	X5R, B	X5R	X6S	X5R	X7S	X6S	X5R	X7S	X6S	X7T	X7T	X5R, B	X6S	X5R, B	X6S	X5R, B	X6S	X5R	X7R
100pF																									
150pF																									
220pF																									
330pF																									
470pF																									
680pF																									
820pF																									
1000pF																									
1500pF																									
2200pF																									
3300pF																									
4700pF																									
6800pF																									
10000pF																									
15000pF																									
22000pF																									
33000pF																									
47000pF																									
68000pF																									
0.10μF																									
0.15μF																									
0.22μF																									
0.33μF																									
0.47μF																									
0.68μF																									
1.0μF																					p104	p104 p104			p104
2.2μF								p103	p103		p103	p103		p103								p104 p104	p104		
4.7μF			p103	p103	p103 p103	p103				p103		p103		p103										p104	
10μF	p103 p103	p103			p103		p103 p103						p103		p103	p103	p103								
22μF																		p104 p104	p104	p104 p104					
47μF																									
100μF																									
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	2.0×1.25																								
T max. (mm)	0.95											1.0								1.35				1.4	
Rated Voltage (Vdc)	25		16		10		6.3		4		2.5	500	250	200	35	25		16		25		16		50	25
Cap. / TC Code	X6S	X5R, B	X7R	X5R, B	X7Δ	X5R, B	X6S	X5R, B	X6S	X5R	X6T	X7R	X7R	X7R	X6S	X7S	X6S	X7S	X5R	X6S	X5R, B	X7R	X5R, B	X5R, B	X7R
100pF																									
150pF																									
220pF																									
330pF																									
470pF																									
680pF																									
820pF																									
1000pF												p104	p104	p104											
1500pF												p104	p104	p104											
2200pF												p104	p104	p104											
3300pF												p104	p104	p104											
4700pF												p104	p104	p104											
6800pF												p104	p104	p104											
10000pF																									
15000pF																									
22000pF																									
33000pF																									
47000pF																									
68000pF																									
0.10μF																									
0.15μF																									
0.22μF																									
0.33μF																									
0.47μF																									
0.68μF																									
1.0μF																									
2.2μF	p104	p104 p104	p104		p104																p104	p104		p104 p104	p104
4.7μF		p104		p104 p104	p104										p104	p104	p104	p104		p104	p104 p104			p104 p104	
10μF		p104 p104		p104 p104			p104		p104														p104 p104		
22μF						p104 p104		p104 p104											p104						
47μF										p104	p104														
100μF																									
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	2.0×1.25																								
T max. (mm)	1.4							1.45																	
Rated Voltage (Vdc)	25	16	10	6.3		4		500	250	200	50		35			25			16			10			6.3
Cap. / TC Code	X5R, B	X6S	B	X7R	X6S	X7U	X6S	X7R	X7R	X7R	X7S	X6S	X7S	X6S	X5R	X7S	X6S	X5R	X7S	X6S	X5R	X7T	X6S	X5R	X7T
100pF																									
150pF																									
220pF																									
330pF																									
470pF																									
680pF																									
820pF																									
1000pF																									
1500pF																									
2200pF																									
3300pF																									
4700pF																									
6800pF																									
10000pF								p105	p105	p105															
15000pF									p105	p105															
22000pF									p105	p105															
33000pF																									
47000pF																									
68000pF																									
0.10μF																									
0.15μF																									
0.22μF																									
0.33μF																									
0.47μF																									
0.68μF																									
1.0μF																									
2.2μF																									
4.7μF											p105	p105	p105			p105									
10μF	p105	p105	p105		p105									p105	p105	p105	p105		p105						
22μF				p105		p105	p105	p105										p105		p105	p105	p105	p105	p105	p105
47μF																								p105	
100μF																									
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	2.0×1.25				3.2×1.6																			
T max. (mm)	1.45				0.95					1.0	1.25						1.8							
Rated Voltage (Vdc)	6.3	4		2.5	35	16	10	6.3		630	1000	630	500	250	200	50	25	1000	630	500	250	200	100	50	
Cap. / TC Code	X5R, B	X6S	X5R, B	X6S	X5R	X5R, B	X5R, B	X6S	X5R, B	X7R	X7R	X7R	X7R	X7R	X7R	B	X5R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X5R, B
100pF																									
150pF																									
220pF																									
330pF																									
470pF											p105														
680pF											p105														
820pF																									
1000pF										p105	p105														
1500pF										p105	p105														
2200pF										p105	p105														
3300pF										p105	p105														
4700pF										p105	p105														
6800pF										p105		p105						p105							
10000pF										p105								p105							
15000pF													p105	p105	p105				p105						
22000pF													p105	p105	p105				p105						
33000pF																				p105	p105	p105			
47000pF																				p105	p105	p105			
68000pF														p105	p105										
0.10μF																					p105	p105			
0.15μF																									
0.22μF																									
0.33μF																									
0.47μF																									
0.68μF																									
1.0μF																p105							p105		
2.2μF																									
4.7μF																								p105	p106
10μF					p105	p105	p105										p105								p106 p106
22μF						p105	p105	p105 p105	p105	p105 p105															
47μF	p105 p105	p105	p105 p105																						
100μF	p105	p105		p105																					
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	3.2×1.6																							3.2×2.5	
T max. (mm)	1.8											1.9												1.5	
Rated Voltage (Vdc)	25		16		10		6.3			4		25	16		10		6.3		4			2.5		1000	630
Cap. / TC Code	X7R	X5R, B	X6S	X5R, B	X7R	X5R, B	X7Δ	X6S	X5R, B	X7U	X6S	X6S	X7S	X5R	X6S	X5R	X6T	X5R	X7U	X6Δ	X5R	X6S	X5R	X7R	X7R
100pF																									
150pF																									
220pF																									
330pF																									
470pF																									
680pF																									
820pF																									
1000pF																									
1500pF																									
2200pF																									
3300pF																									
4700pF																									
6800pF																								p106	
10000pF																								p106	
15000pF																									
22000pF																									p106
33000pF																									
47000pF																									
68000pF																									
0.10μF																									
0.15μF																									
0.22μF																									
0.33μF																									
0.47μF																									
0.68μF																									
1.0μF																									
2.2μF																									
4.7μF																									
10μF	p106	p106																							
22μF		p106	p106	p106	p106	p106	p106		p106						p106	p106									
47μF						p106	p106	p106	p106	p106	p106	p106	p106				p106	p106							
100μF																			p106	p106	p106	p106	p106	p106			
150μF																					p106		p106	p106	p106		
220μF																								p106		p106	

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	3.2×2.5																							
T max. (mm)	1.5			1.8	2.0					2.2		2.7												
Rated Voltage (Vdc)	500	250	200	100	1000	630	500	250	200	100	25	100	80	63	50		35		25		16			10	
Cap. / TC Code	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R	X7R	X5R, B	X7R	X5R, B	X7R	X5R, B	X7R	X6S	X5R, B	X7R	X5R, B
100pF																									
150pF																									
220pF																									
330pF																									
470pF																									
680pF																									
820pF																									
1000pF																									
1500pF																									
2200pF																									
3300pF																									
4700pF																									
6800pF																									
10000pF																									
15000pF					p106																				
22000pF					p106																				
33000pF						p106																			
47000pF						p106																			
68000pF	p106	p106	p106																						
0.10μF							p106	p106	p106																
0.15μF		p106	p106																						
0.22μF								p106	p106																
0.33μF																									
0.47μF																									
0.68μF																									
1.0μF				p106																					
2.2μF												p106													
4.7μF										p106			p106		p106										
10μF											p106			p106	p106	p106	p106	p106	p106	p106					
22μF																			p106	p106	p106	p106			
47μF																						p106	p106	p106	p106	p106	p106
100μF																										p106	
150μF																									
220μF																									

Continued on the following page.↗

Capacitance Table

(→ GRM Series High Dielectric Constant Type)

p00 ← Part Number List JIS: R B EIA: X7R X7S X7T X7U X6S X6T X5R

L×W (mm)	3.2×2.5			4.5×3.2									5.7×5.0				
T max. (mm)	2.7			1.5				2.0					2.0				
Rated Voltage (Vdc)	6.3		4	630	500	250	200	1000	630	500	250	200	1000	630	500	250	200
Cap. / TC Code	X7Δ	X5R, B	X7U	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R
100pF																	
150pF																	
220pF																	
330pF																	
470pF																	
680pF																	
820pF																	
1000pF																	
1500pF																	
2200pF																	
3300pF																	
4700pF																	
6800pF																	
10000pF																	
15000pF																	
22000pF																	
33000pF								p107									
47000pF								p107									
68000pF				p107									p107				
0.10μF									p107				p107				
0.15μF					p107	p107	p107							p107			
0.22μF										p107	p107	p107		p107			
0.33μF											p107	p107			p107	p107	p107
0.47μF											p107	p107			p107	p107	p107
0.68μF																p107	p107
1.0μF																p107	p107
2.2μF																	
4.7μF																	
10μF																	
22μF																	
47μF	p106																
100μF	p106	p106	p106	p106													
150μF																	
220μF																	

Capacitance Table

GR3 Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7T

L×W (mm)	2.0×1.25		3.2×1.6								3.2×2.5					4.5×3.2				5.7×5.0				
T max. (mm)	1.0	1.45	1.0		1.25			1.8			1.5		2.0			1.5	2.0			2.0			2.7	
Rated Voltage (Vdc)	250	250	450	250	630	450	250	630	450	250	630	250	630	450	250	250	630	450	250	630	450	250	630	250
Cap. / TC Code	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T
10000pF	p110		p110		p110																			
15000pF	p110		p110					p110																
22000pF		p110				p110					p110													
33000pF				p110		p110							p110											
47000pF							p110		p110				p110											
68000pF										p110				p110			p110							
0.10μF												p110		p110						p110				
0.15μF															p110			p110		p110				
0.22μF																p110					p110		p110	
0.33μF																			p110		p110			
0.47μF																					p110	p110		
0.68μF																						p110		
1.0μF																								p110

Capacitance Table

GRJ Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7R X7S X5R

L×W (mm)	1.6×0.8							2.0×1.25											3.2×1.6			
T max. (mm)	0.9						1.0	0.7		0.95	1.0	1.45						1.5	0.95		1.25	
Rated Voltage (Vdc)	100	50	35	25	16	6.3	6.3	100	50	100	250	250	100	50	25	16	10	100	100	50	1000	630
Cap. / TC Code	X7R	X7R	X5R	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R
220pF										p121												
470pF									p121	p121											p122	
680pF																					p122	
1000pF	p121	p121						p121	p121		p121										p122	p122
1500pF											p121										p122	p122
2200pF	p121	p121						p121	p121		p121										p122	p122
3300pF											p121										p122	p122
4700pF	p121	p121						p121	p121		p121										p122	p122
6800pF											p121											p122
10000pF	p121	p121						p121	p121			p121										p122
15000pF												p121										
22000pF	p121	p121						p121	p121			p121										
33000pF																						
47000pF		p121		p121									p121	p121								
68000pF																						
0.10μF	p121	p121											p121	p121					p122	p122		
0.15μF																						
0.22μF		p121		p121										p121								
0.33μF																						
0.47μF					p121									p121								
0.68μF																						
1.0μF			p121	p121										p121	p121			p121				
2.2μF						p121									p121							
4.7μF							p121									p121						
10μF																	p121					
22μF																						
47μF																						

L×W (mm)	3.2×2.5							4.5×3.2					5.7×5.0		
T max. (mm)	2.8						2.85	1.5		2.0			2.0		
Rated Voltage (Vdc)	50		25	16	10	6.3	25	630	250	1000	630	250	1000	630	250
Cap. / TC Code	X7R	X7S	X7R	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R
33000pF										p123					
47000pF										p123					
68000pF								p123					p123		
0.10μF											p123		p123		
0.15μF									p123					p123	
0.22μF												p123		p123	
0.33μF												p123			p123
0.47μF												p123			p123
0.68μF															p123
1.0μF															p123
2.2μF															
4.7μF	p122														
10μF	p122	p122	p122												
22μF				p122	p122		p122								
47μF					p122	p122									

3.2×1.6														3.2×2.5								L×W (mm)
1.25	1.35				1.8			1.9						1.5			2.0			2.3		T max. (mm)
250	100	50	25	16	1000	630	250	100	50	25	16	10	6.3	1000	630	250	1000	630	250	100		Rated Voltage (Vdc)
X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7S	Cap. / TC Code
																						220pF
																						470pF
																						680pF
																						1000pF
																						1500pF
																						2200pF
																						3300pF
																						4700pF
					p122									p122								6800pF
					p122									p122								10000pF
p122						p122											p122					15000pF
p122						p122									p122		p122					22000pF
							p122											p122				33000pF
							p122											p122				47000pF
p122																p122						68000pF
		p122					p122												p122			0.10μF
																p122						0.15μF
	p122	p122																	p122			0.22μF
																						0.33μF
		p122																				0.47μF
																						0.68μF
		p122						p122	p122													1.0μF
			p122	p122					p122											p122		2.2μF
									p122		p122										p122	4.7μF
										p122	p122	p122										10μF
												p122	p122									22μF
																						47μF

Continued to the following table.↙

Capacitance Table

GR4 Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7R

L×W (mm)	0.4×0.2	4.5×3.2		5.7×5.0
T max. (mm)	1.5	1.5	2.0	2.0
Rated Voltage (Vdc)	2000	2000	2000	2000
Cap. / TC Code	X7R	X7R	X7R	X7R
100pF	p126			
120pF	p126			
150pF	p126			
180pF	p126			
220pF	p126			
270pF	p126			
330pF	p126			
390pF	p126			
470pF	p126			
560pF	p126			
680pF	p126			
820pF	p126			
1000pF	p126			
1200pF	p126			
1500pF	p126			
1800pF		p126		
2200pF		p126		
2700pF		p126		
3300pF		p126		
3900pF		p126		
4700pF			p126	
10000pF				p126

GR7 Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7T

L×W (mm)	2.0×1.25		3.2×1.6		
T max. (mm)	1.0	1.45	1.0	1.25	1.8
Rated Voltage (Vdc)	350	350	350	350	350
Cap. / TC Code	X7T	X7T	X7T	X7T	X7T
10000pF	p131		p131		
15000pF	p131		p131		
22000pF		p131	p131	p131	
27000pF		p131	p131		
33000pF			p131	p131	
47000pF					p131

GJM Series Temperature Compensating Type

p00 ← Part Number List JIS: CK CJ CH EIA: C0G

L×W (mm)	0.4×0.2		0.6×0.3						1.0×0.5	
T max. (mm)	0.22		0.33						0.55	
Rated Voltage (Vdc)	25		50				25		50	
Cap. / TC Code	C0G	CΔ	C0G	CK	CJ	CH	C0G	CΔ	C0G	CΔ
0.10pF									p149	p153
0.20pF	p136	p139	p142	p142		p142			p149	p153
1.0pF	p136	p139		p142			p143	p146	p149	p153
2.0pF	p136	p139		p142			p143	p146	p149	p153
3.0pF	p136	p139			p142		p143	p146	p150	p153
4.0pF	p137	p140					p143	p147	p150	p154
5.0pF	p137	p140					p144	p147	p150	p154
6.0pF	p137	p140					p144	p147	p151	p154
7.0pF	p138	p141					p144	p148	p151	p155
8.0pF	p138	p141					p145	p148	p151	p155
9.0pF	p138	p142					p145	p148	p152	p155
10pF	p139	p142					p146	p149	p152	p156
11pF	p139	p142					p146	p149	p152	p156
12pF	p139	p142					p146	p149	p152	p156
13pF	p139	p142					p146	p149	p152	p156
15pF	p139	p142					p146	p149	p152	p156
16pF	p139	p142					p146	p149	p152	p156
18pF	p139	p142					p146	p149	p152	p156
20pF	p139	p142					p146	p149	p152	p156
22pF	p139	p142					p146	p149	p152	p156
24pF							p146	p149	p152	p156
27pF							p146	p149	p152	p156
30pF							p146	p149	p152	p156
33pF							p146	p149	p152	p156
36pF									p152	p156
39pF									p152	p156
43pF									p152	p156
47pF									p153	p156

The indication for every 0.1 pF has been omitted for less than 10 pF. Refer to the Part Number List for details.

Capacitance Table

GQM Series Temperature Compensating Type

p00 ← Part Number List EIA: C0G Murata Temperature Characteristic: X8G

L×W (mm)	1.0×0.5		1.6×0.8		2.0×1.25			2.8×2.8
T max. (mm)	0.55		0.8		1.0			1.35
Rated Voltage (Vdc)	200	100	250		500	250		500
Cap. / TC Code	C0G	C0G	C0G	X8G	X8G	C0G	X8G	C0G
0.10pF	p165							
1.0pF	p165		p166	p166	p167	p168	p169	p170
1.1pF	p165		p166	p166	p167	p168	p169	p170
1.2pF	p165		p166	p167	p167	p168	p169	p170
1.3pF	p165		p166	p167	p167	p168	p169	p170
1.5pF	p165		p166	p167	p167	p168	p169	p170
1.6pF	p165		p166	p167	p167	p168	p169	p170
1.8pF	p165		p166	p167	p167	p168	p169	p170
2.0pF	p165		p166	p167	p167	p168	p169	p170
2.2pF	p165		p166	p167	p167	p168	p169	p170
2.4pF	p165		p166	p167	p167	p168	p169	p170
2.7pF	p165		p166	p167	p167	p168	p169	p170
3.0pF	p165		p166	p167	p168	p168	p169	p170
3.3pF	p165		p166	p167	p168	p168	p169	p170
3.6pF	p165		p166	p167	p168	p168	p169	p170
3.9pF	p165		p166	p167	p168	p168	p169	p170
4.0pF	p165		p166	p167	p168	p168	p169	p170
4.3pF	p165		p166	p167	p168	p168	p169	p170
4.7pF	p165		p166	p167	p168	p168	p169	p170
5.0pF	p165		p166	p167	p168	p168	p169	p170
5.1pF	p165		p166	p167	p168	p168	p169	p170
5.6pF	p165		p166	p167	p168	p168	p169	p170
6.0pF	p165		p166	p167	p168	p168	p169	p170
6.2pF	p165		p166	p167	p168	p168	p169	p170
6.8pF	p165		p166	p167	p168	p168	p169	p170
7.0pF	p165		p166	p167	p168	p168	p169	p171
7.5pF	p165		p166	p167	p168	p168	p170	p171
8.0pF	p165		p166	p167	p168	p169	p170	p171
8.2pF	p165		p166	p167	p168	p169	p170	p171
9.0pF	p165		p166	p167	p168	p169	p170	p171
9.1pF	p165		p166	p167	p168	p169	p170	p171
10pF	p165		p166	p167	p168	p169	p170	p171
11pF	p165		p166	p167	p168	p169	p170	p171
12pF	p165		p166	p167	p168	p169	p170	p171
13pF	p165		p166	p167	p168	p169	p170	p171
15pF	p165		p166	p167	p168	p169	p170	p171
16pF	p165		p166	p167	p168	p169	p170	p171
18pF	p165		p166	p167	p168	p169	p170	p171
20pF	p165		p166	p167	p168	p169	p170	p171
22pF	p165		p166	p167	p168	p169	p170	p171
24pF	p165		p166	p167		p169	p170	p171
27pF	p165		p166	p167		p169	p170	p171
30pF	p165		p166	p167		p169	p170	p171
33pF	p165		p166			p169	p170	p171
36pF		p165	p166			p169	p170	p171
39pF		p166	p166			p169	p170	p171
43pF		p166	p166			p169	p170	p171
47pF		p166	p166			p169	p170	p171
51pF						p169	p170	p171
56pF						p169	p170	p171
62pF						p169	p170	p171
68pF						p169	p170	p171
75pF						p169	p170	p171
82pF						p169	p170	p171
91pF						p169		p171
100pF						p169		p171

The indication for every 0.1 pF has been omitted for less than 10 pF.
Refer to the Part Number List for details.

Capacitance Table

GR2 Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7R

L×W (mm)	4.5×2.0	4.5×3.2		5.7×5.0
T max. (mm)	1.5	1.5	2.0	2.0
Rated Voltage (Vac)	250	250	250	250
Cap. / TC Code	X7R	X7R	X7R	X7R
470pF	p185			
1000pF	p185			
2200pF		p185		
3300pF		p185		
4700pF			p185	
10000pF		p185		
22000pF		p185		
47000pF			p185	
0.10μF				p185

GA3 Series Type GB High Dielectric Constant Type

p00 ← Part Number List EIA: X7R

L×W (mm)	5.7×5.0			
T max. (mm)	1.5	2.0	2.5	2.9
Rated Voltage (Vac)	250	250	250	250
Cap. / TC Code	X7R	X7R	X7R	X7R
10000pF	p191			
15000pF	p191			
22000pF		p191		
33000pF			p191	
47000pF			p191	
56000pF				p191

GA3 Series Type GD Temperature Compensating Type

p00 ← Part Number List JIS: SL

L×W (mm)	4.5×2.0
T max. (mm)	1.0
Rated Voltage (Vac)	250
Cap. / TC Code	SL
10pF	p197
12pF	p197
15pF	p197
18pF	p197
22pF	p197
27pF	p197
33pF	p197
39pF	p197
47pF	p197
56pF	p197
68pF	p197
82pF	p197

GA3 Series Type GD High Dielectric Constant Type

p00 ← Part Number List EIA: X7R

L×W (mm)	4.5×2.0	4.5×3.2	
T max. (mm)	1.5	1.5	2.0
Rated Voltage (Vac)	250	250	250
Cap. / TC Code	X7R	X7R	X7R
100pF	p198		
150pF	p198		
220pF	p198		
330pF	p198		
470pF	p198		
680pF	p198		
1000pF	p198		
1500pF	p198		
1800pF		p198	
2200pF		p198	
4700pF			p198

Capacitance Table

GA3 Series Type GF Temperature Compensating Type

p00 ← Part Number List JIS: SL

L×W (mm)	4.5×2.0
T max. (mm)	1.0
Rated Voltage (Vac)	250
Cap. / TC Code	SL
10pF	p209
12pF	p209
15pF	p209
18pF	p209
22pF	p209
27pF	p209
33pF	p209
39pF	p209
47pF	p209
56pF	p209
68pF	p209
82pF	p209

GA3 Series Type GF High Dielectric Constant Type

p00 ← Part Number List EIA: X7R

L×W (mm)	4.5×2.0		5.7×2.8	5.7×5.0	
T max. (mm)	1.5	2.2	1.5	1.5	2.0
Rated Voltage (Vac)	250	250	250	250	250
Cap. / TC Code	X7R	X7R	X7R	X7R	X7R
100pF	p210		p210		
150pF	p210		p210		
220pF		p210	p210		
330pF		p210	p210		
470pF	p210		p210		
680pF	p210		p210		
1000pF		p210	p210		
1500pF			p210		
1800pF				p210	
2200pF				p210	
3300pF				p210	
4700pF					p210

Capacitance Table

LLL Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7R X7S X6S X5R

L×W (mm)	0.5×1.0			0.6×1.0	0.8×1.6										1.25×2.0							
T max. (mm)	0.35			0.45	0.5				0.55	0.6					0.5						0.7	
Rated Voltage (Vdc)	6.3	4		4	25	16	10	4	4	50	25	16	10	4	50	25	16	10	6.3	4	50	25
Cap. / TC Code	X6S	X7S	X6S	X5R	X7R	X7R	X7R	X7S	X7S	X7R	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R	X7R	X7S	X7R	X7R
2200pF										p220												
4700pF										p220												
10000pF					p220						p220				p220						p220	
22000pF						p220					p220					p220					p220	
47000pF						p220						p220					p220					p220
0.10μF	p220						p220						p220				p220					p220
0.22μF	p220							p220					p220					p220				
0.47μF		p220												p220					p220			
1.0μF			p220																	p220		
2.2μF									p220													
4.3μF				p220																		
4.7μF																						
10μF																						

Continued to the following table.↙

L×W (mm)	1.25×2.0				1.6×3.2														
T max. (mm)	0.7	0.95			0.5				0.8					1.25					
Rated Voltage (Vdc)	10	16	10	4	50	25	16	10	50	25	16	10	6.3	50	25	16	10	6.3	
Cap. / TC Code	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X5R
2200pF																			
4700pF																			
10000pF					p220				p220										
22000pF					p220				p220										
47000pF						p220			p220										
0.10μF						p220				p220				p220					
0.22μF	p220	p220					p220				p220				p220				
0.47μF			p220					p220			p220				p220				
1.0μF			p220									p220				p220			
2.2μF				p220									p220				p220		
4.3μF																			
4.7μF																		p220	
10μF																			p220

LLA Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7R X7S

L×W (mm)	1.6×0.8	2.0×1.25									
T max. (mm)	0.55	0.55					0.95				
Rated Voltage (Vdc)	4	25	16	10	6.3	4	25	16	10	6.3	4
Cap. / TC Code	X7S	X7R	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R	X7S
10000pF		p223					p223				
22000pF		p223					p223				
47000pF			p223				p223				
0.10μF	p223		p223					p223			
0.22μF	p223			p223				p223			
0.47μF	p223				p223				p223		
1.0μF						p223				p223	
2.2μF	p223										p223
4.7μF						p223					

Capacitance Table

LLM Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7R X7S

L×W (mm)	2.0×1.25	
T max. (mm)	0.55	
Rated Voltage (Vdc)	6.3	4
Cap. / TC Code	X7R	X7S
0.22μF	p229	
0.47μF	p229	
1.0μF		p229

LLR Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7S

L×W (mm)	0.8×1.6			
T max. (mm)	0.55			
Rated Voltage (Vdc)	4			
TC Code	X7S			
Cap. / ESR (mΩ)	100	220	470	1000
1.0μF	p233	p233	p233	p233

NFM Series

p00 ← Part Number List

L×W (mm)	1.0×0.5								1.6×0.8				2.0×1.25					3.2×1.25	3.2×1.6			4.5×1.6		
T max. (mm)	0.35		0.5				0.65	0.7	0.7		0.9		0.95					0.9	1.5			1.2		
Rated Voltage (Vdc)	6.3	4	16	10	6.3	2.5	2.5	2.5	16	6.3	10	6.3	50	25	16	10	6.3	50	100	50	6.3	100	50	25
Cap. / TC Code	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
100pF									p237															
220pF									p237				p237					p237						
470pF									p237				p237					p237				p237		
1000pF									p237				p237					p237				p237		
2200pF			p237	p237					p237				p237					p237				p237		
10000pF																			p237	p237				
15000pF																			p237	p237				
22000pF			p237	p237					p237				p237					p237	p237	p237		p237		
47000pF			p237	p237																				
0.10μF				p237	p237				p237					p237					p237	p237				
0.20μF																								
0.22μF				p237	p237					p237					p237									
0.47μF	p237	p237								p237					p237									
1.0μF		p237								p237		p237			p237	p237								
1.5μF																							p237	p237
2.2μF										p237	p237						p237							
4.3μF						p237																		
4.7μF																p237								
7.5μF							p237																	
9.1μF								p237																
10μF																	p237							
27μF																					p237			

Capacitance Table

KRM Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7R X7S X6S X5R

L×W (mm)	2.2×1.25					3.5×1.7					3.6×1.7	3.7×1.85	6.1×5.3									
T max. (mm)	1.9		2.0			2.0	2.9				2.9	2.9	3.0									3.9
Rated Voltage (Vdc)	25	16	25			25	100	50	35	25	50	100	1000	630	450	250	100	63	50	35	25	100
Cap. / TC Code	X5R	X5R	X7S	X6S	X5R	X5R	X7R	X7R	X6S	X6S	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R
68000pF													p241									
0.10μF													p241									
0.15μF														p241								
0.22μF														p241								
0.33μF															p241							
0.47μF															p241							
0.68μF																p241						
1.0μF							p241									p241						
1.5μF																						
2.2μF											p241	p241										
4.7μF								p241									p241	p241	p241			
6.8μF																						p241
10μF	p241	p241	p241	p241		p241			p241	p241									p241	p241		p241
15μF																				p241	p241	
17μF																						
22μF					p241																	
33μF																						
47μF																						
68μF																						
100μF																						

Continued to the following table.↙

L×W (mm)	6.1×5.3																	
T max. (mm)	3.9					5.0								6.7				
Rated Voltage (Vdc)	63	50	35	25		1000	630	450	250	100	50	35	25	100	63	50	35	25	
Cap. / TC Code	X7R	X7R	X7R	X7R	X7S	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7R	X7S
68000pF																			
0.10μF																			
0.15μF						p241													
0.22μF						p241													
0.33μF							p241												
0.47μF							p241												
0.68μF								p241											
1.0μF								p241											
1.5μF									p241										
2.2μF									p241										
4.7μF																			
6.8μF																			
10μF	p241									p241									
15μF														p241					
17μF		p241	p241																
22μF			p241	p241							p241	p241		p241	p241				
33μF				p241								p241	p241			p241			
47μF					p241												p241	p241	
68μF																		p241	
100μF																			p241

Capacitance Table

KR3 Series High Dielectric Constant Type

p00 ← Part Number List EIA: X7T

L×W (mm)	6.1×5.3										
T max. (mm)	3.0			3.9			5.0		6.7		
Rated Voltage (Vdc)	630	450	250	630	450	250	450	250	630	450	250
Cap. / TC Code	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T	X7T
0.10μF	p245										
0.15μF	p245										
0.22μF		p245		p245							
0.27μF				p245							
0.33μF		p245									
0.47μF		p245	p245						p245		
0.56μF					p245				p245		
0.68μF			p245				p245				
1.0μF						p245	p245				
1.2μF										p245	
1.5μF								p245			
2.2μF											p245

GMA Series High Dielectric Constant Type

p00 ← Part Number List JIS: R B EIA: X7R X5R

L×W (mm)	0.38×0.38			0.5×0.5							0.8×0.8							
T max. (mm)	0.35			0.4							0.6							
Rated Voltage (Vdc)	10			100	25		10			6.3	100	25		10			6.3	
Cap. / TC Code	X7R	R	B	X7R	X7R	B	X7R	R	B	X5R	B	X7R	X7R	B	X7R	R	B	X5R	B
100pF				p251															
150pF				p251															
220pF				p251															
330pF				p251															
470pF				p251															
680pF				p251															
1000pF	p251	p251	p251	p251															
1500pF	p251	p251	p251		p251	p251						p251							
1800pF	p251	p251	p251																
2200pF					p251	p251						p251							
3300pF					p251	p251						p251							
4700pF					p251	p251						p251							
6800pF							p251	p251	p251			p251							
10000pF	p251	p251					p251	p251	p251				p251	p251					
15000pF							p251	p251	p251				p251	p251					
22000pF							p251	p251	p251				p251	p251					
33000pF															p251	p251	p251		
47000pF															p251	p251	p251		
68000pF															p251	p251	p251		
0.10μF										p251	p251				p251	p251	p251		
0.47μF																		p251	p251

Capacitance Table

GMD Series High Dielectric Constant Type

p00 ← Part Number List JIS: R B EIA: X7R X5R

L×W (mm)	0.6×0.3											1.0×0.5										
T max. (mm)	0.33											0.55										
Rated Voltage (Vdc)	25			16			10			6.3		50			25			16			10	
Cap. / TC Code	X7R	R	B	X7R	R	B	X7R	R	B	X5R	B	X7R	R	B	X7R	R	B	X7R	R	B	X5R	B
100pF	p257	p257	p257																			
120pF	p257	p257	p257																			
150pF	p257	p257	p257																			
180pF	p257	p257	p257																			
220pF	p257	p257	p257									p257	p257	p258								
270pF	p257	p257	p257									p257	p258	p258								
330pF	p257	p257	p257									p257	p258	p258								
390pF	p257	p257	p257									p257	p258	p258								
470pF	p257	p257	p257									p257	p258	p258								
560pF	p257	p257	p257									p257	p258	p258								
680pF	p257	p257	p257									p257	p258	p258								
820pF	p257	p257	p257									p257	p258	p258								
1000pF	p257	p257	p257									p257	p258	p258								
1200pF	p257	p257	p257									p257	p258	p258								
1500pF	p257	p257	p257									p257	p258	p258								
1800pF				p257	p257	p257						p257	p258	p258								
2200pF				p257	p257	p257						p257	p258	p258								
2700pF				p257	p257	p257						p257	p258	p258								
3300pF				p257	p257	p257						p257	p258	p258								
3900pF							p257	p257	p257			p257	p258	p258								
4700pF							p257	p257	p257			p257	p258	p258								
5600pF							p257	p257	p257						p258	p258	p258					
6800pF							p257	p257	p257						p258	p258	p258					
8200pF							p257	p257	p257						p258	p258	p258					
10000pF							p257	p257	p257						p258	p258	p258					
12000pF															p258	p258	p258					
15000pF															p258	p258	p258					
18000pF															p258	p258	p258					
22000pF															p258	p258	p258					
27000pF															p258	p258	p258					
33000pF															p258	p258	p258					
39000pF															p258	p258	p258					
47000pF															p258	p258	p258					
56000pF										p257	p257							p258	p258	p258		
68000pF										p257	p257							p258	p258	p258		
82000pF										p257	p257							p258	p258	p258		
0.10μF										p257	p257							p258	p258	p258		
0.12μF																					p258	p258
0.15μF																					p258	p258
0.18μF																					p258	p258
0.22μF																					p258	p258
0.27μF																					p258	p258
0.33μF																					p258	p258
0.39μF																					p258	p258
0.47μF																					p258	p258

Search Capacitors

Specifications and Test Methods, Package, Chart of Characteristic Data, please refer to the search web page.
https://www.murata.com/en-global/products/capacitor

Links are provided to the product detail pages on the web, and are shown below in the product number table from the PDF version of the catalog which is available on the web.

Status and Features Icons

The status and features of products can be checked at once. When ? is clicked, a description of each icon will be displayed

Stock Check (Where to buy)

Some products can request free samples.
Reference inventory information from agents and web-based companies.

Data Sheet

The product details page can be output in PDF.

How to read part numbers

Describes the meaning of the part number

Series Information

This links to the introduction page of each series.

Detailed Specifications Sheet

- Rated value
- Specifications and Test Methods
- Package
- Caution, Notice
  (Storage, Soldering and Mounting, ...etc.)

Characteristics Data

The following characteristics data of the main products can be acquired.
- SPICE Netlist (mod type)
- S parameter (S2P type)
- Reliability Test Data *Typical data

- Shape (Dimensions)
- Rated Values

- Specification by Packaging Code/ Minimum Order Quantity
- Weight (1 pc/ø180mm reel)

Chart of Characteristic Data

The main products published characteristic data.
- Frequency characteristics (ESR, Impedance)
- DC bias characteristics
- AC voltage characteristics
- Capacitance - temperature characteristics
- Calorific property by ripple current

Design Tools SimSurfing

The SimSurfing design tools are useful for displaying the graph, downloading CSV data and overwriting the product number graph.

Chip Multilayer Ceramic Capacitors for General Purpose

GRM Series

WEB

This is Murata primary products renowned for both small size and large capacitance value with latest advanced technology.

Features

1 Achieves large-capacity and small size in a multilayer structure.



<Example of Structure>



2 Sn plating is applied to the external electrodes; excellent solderability.

3 High reliability with no polarity.

	Ceramic Capacitors	Tantalum Capacitor	Aluminum Electrolytic Capacitor	Conductive Polymer Capacitor
Price	○	○	◎	○
Comparison between Impedance Frequency Characteristics	◎	△	△	○
Capacitance temperature characteristics	○	◎	○	○
DC breakdown voltage	◎	△	△	△
Polarity	No	Yes	Yes	Yes
Pulse response	◎	△	△	○
Allowable ripple current	◎	△	△	△
Reliability	◎	○	○	○
DC bias characteristics	△	◎	◎	◎

◎: Particularly excellent ○: Excellent △: Inferior

Specifications

Size (mm)	0.25×0.125mm to 5.7×5.0mm
Rated Voltage	2.5Vdc to 3150Vdc
Capacitance	0.10pF to 330μF
Main Applications	1. Rated voltage 100V Max. High Dielectric Constant Type · · · For decoupling and smoothing circuits Temperature Compensating Type · · · For tuning circuits, oscillating circuits, and high frequency filter circuits 2. Rated voltage 200V min. High Dielectric Constant Type · · · For clamp snubber circuits and smoothing circuits Temperature Compensating Type · · · Power supply damper snubber



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

GRM Series Temperature Compensating Type Part Number List

0.4×0.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	C0G	0.20pF	±0.05pF	GRM0225C1HR20WA03#	
				±0.1pF	GRM0225C1HR20BA03#	
			0.30pF	±0.05pF	GRM0225C1HR30WA03#	
				±0.1pF	GRM0225C1HR30BA03#	
			0.40pF	±0.05pF	GRM0225C1HR40WA03#	
				±0.1pF	GRM0225C1HR40BA03#	
			0.50pF	±0.05pF	GRM0225C1HR50WA03#	
				±0.1pF	GRM0225C1HR50BA03#	
			0.60pF	±0.05pF	GRM0225C1HR60WA03#	
				±0.1pF	GRM0225C1HR60BA03#	
			0.70pF	±0.05pF	GRM0225C1HR70WA03#	
				±0.1pF	GRM0225C1HR70BA03#	
			0.80pF	±0.05pF	GRM0225C1HR80WA03#	
				±0.1pF	GRM0225C1HR80BA03#	
			0.90pF	±0.05pF	GRM0225C1HR90WA03#	
				±0.1pF	GRM0225C1HR90BA03#	
			1.0pF	±0.05pF	GRM0225C1H1R0WA03#	
				±0.1pF	GRM0225C1H1R0BA03#	
				±0.25pF	GRM0225C1H1R0CA03#	
			1.1pF	±0.05pF	GRM0225C1H1R1WA03#	
				±0.1pF	GRM0225C1H1R1BA03#	
				±0.25pF	GRM0225C1H1R1CA03#	
			1.2pF	±0.05pF	GRM0225C1H1R2WA03#	
				±0.1pF	GRM0225C1H1R2BA03#	
				±0.25pF	GRM0225C1H1R2CA03#	
			1.3pF	±0.05pF	GRM0225C1H1R3WA03#	
				±0.1pF	GRM0225C1H1R3BA03#	
				±0.25pF	GRM0225C1H1R3CA03#	
			1.4pF	±0.05pF	GRM0225C1H1R4WA03#	
				±0.1pF	GRM0225C1H1R4BA03#	
				±0.25pF	GRM0225C1H1R4CA03#	
			1.5pF	±0.05pF	GRM0225C1H1R5WA03#	
				±0.1pF	GRM0225C1H1R5BA03#	
				±0.25pF	GRM0225C1H1R5CA03#	
			1.6pF	±0.05pF	GRM0225C1H1R6WA03#	
				±0.1pF	GRM0225C1H1R6BA03#	
				±0.25pF	GRM0225C1H1R6CA03#	
			1.7pF	±0.05pF	GRM0225C1H1R7WA03#	
				±0.1pF	GRM0225C1H1R7BA03#	
				±0.25pF	GRM0225C1H1R7CA03#	
			1.8pF	±0.05pF	GRM0225C1H1R8WA03#	
				±0.1pF	GRM0225C1H1R8BA03#	
				±0.25pF	GRM0225C1H1R8CA03#	
			1.9pF	±0.05pF	GRM0225C1H1R9WA03#	
				±0.1pF	GRM0225C1H1R9BA03#	
				±0.25pF	GRM0225C1H1R9CA03#	
			2.0pF	±0.05pF	GRM0225C1H2R0WA03#	
				±0.1pF	GRM0225C1H2R0BA03#	
				±0.25pF	GRM0225C1H2R0CA03#	
			2.1pF	±0.05pF	GRM0225C1H2R1WA03#	
				±0.1pF	GRM0225C1H2R1BA03#	
				±0.25pF	GRM0225C1H2R1CA03#	
0.22mm	50Vdc	C0G	2.2pF	±0.05pF	GRM0225C1H2R2WA03#	
				±0.1pF	GRM0225C1H2R2BA03#	
				±0.25pF	GRM0225C1H2R2CA03#	
			2.3pF	±0.05pF	GRM0225C1H2R3WA03#	
				±0.1pF	GRM0225C1H2R3BA03#	
				±0.25pF	GRM0225C1H2R3CA03#	
			2.4pF	±0.05pF	GRM0225C1H2R4WA03#	
				±0.1pF	GRM0225C1H2R4BA03#	
				±0.25pF	GRM0225C1H2R4CA03#	
			2.5pF	±0.05pF	GRM0225C1H2R5WA03#	
				±0.1pF	GRM0225C1H2R5BA03#	
				±0.25pF	GRM0225C1H2R5CA03#	
			2.6pF	±0.05pF	GRM0225C1H2R6WA03#	
				±0.1pF	GRM0225C1H2R6BA03#	
				±0.25pF	GRM0225C1H2R6CA03#	
			2.7pF	±0.05pF	GRM0225C1H2R7WA03#	
				±0.1pF	GRM0225C1H2R7BA03#	
				±0.25pF	GRM0225C1H2R7CA03#	
			2.8pF	±0.05pF	GRM0225C1H2R8WA03#	
				±0.1pF	GRM0225C1H2R8BA03#	
				±0.25pF	GRM0225C1H2R8CA03#	
			2.9pF	±0.05pF	GRM0225C1H2R9WA03#	
				±0.1pF	GRM0225C1H2R9BA03#	
				±0.25pF	GRM0225C1H2R9CA03#	
			3.0pF	±0.05pF	GRM0225C1H3R0WA03#	
				±0.1pF	GRM0225C1H3R0BA03#	
				±0.25pF	GRM0225C1H3R0CA03#	
			3.1pF	±0.05pF	GRM0225C1H3R1WA03#	
				±0.1pF	GRM0225C1H3R1BA03#	
				±0.25pF	GRM0225C1H3R1CA03#	
			3.2pF	±0.05pF	GRM0225C1H3R2WA03#	
				±0.1pF	GRM0225C1H3R2BA03#	
				±0.25pF	GRM0225C1H3R2CA03#	
			3.3pF	±0.05pF	GRM0225C1H3R3WA03#	
				±0.1pF	GRM0225C1H3R3BA03#	
				±0.25pF	GRM0225C1H3R3CA03#	
			3.4pF	±0.05pF	GRM0225C1H3R4WA03#	
				±0.1pF	GRM0225C1H3R4BA03#	
				±0.25pF	GRM0225C1H3R4CA03#	
			3.5pF	±0.05pF	GRM0225C1H3R5WA03#	
				±0.1pF	GRM0225C1H3R5BA03#	
				±0.25pF	GRM0225C1H3R5CA03#	
			3.6pF	±0.05pF	GRM0225C1H3R6WA03#	
				±0.1pF	GRM0225C1H3R6BA03#	
				±0.25pF	GRM0225C1H3R6CA03#	
			3.7pF	±0.05pF	GRM0225C1H3R7WA03#	
				±0.1pF	GRM0225C1H3R7BA03#	
				±0.25pF	GRM0225C1H3R7CA03#	
			3.8pF	±0.05pF	GRM0225C1H3R8WA03#	
				±0.1pF	GRM0225C1H3R8BA03#	
				±0.25pF	GRM0225C1H3R8CA03#	
			3.9pF	±0.05pF	GRM0225C1H3R9WA03#	
				±0.1pF	GRM0225C1H3R9BA03#	
				±0.25pF	GRM0225C1H3R9CA03#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	C0G	4.0pF	±0.05pF	GRM0225C1H4R0WA03#	
				±0.1pF	GRM0225C1H4R0BA03#	
				±0.25pF	GRM0225C1H4R0CA03#	
			4.1pF	±0.05pF	GRM0225C1H4R1WA03#	
				±0.1pF	GRM0225C1H4R1BA03#	
				±0.25pF	GRM0225C1H4R1CA03#	
			4.2pF	±0.05pF	GRM0225C1H4R2WA03#	
				±0.1pF	GRM0225C1H4R2BA03#	
				±0.25pF	GRM0225C1H4R2CA03#	
			4.3pF	±0.05pF	GRM0225C1H4R3WA03#	
				±0.1pF	GRM0225C1H4R3BA03#	
				±0.25pF	GRM0225C1H4R3CA03#	
			4.4pF	±0.05pF	GRM0225C1H4R4WA03#	
				±0.1pF	GRM0225C1H4R4BA03#	
				±0.25pF	GRM0225C1H4R4CA03#	
			4.5pF	±0.05pF	GRM0225C1H4R5WA03#	
				±0.1pF	GRM0225C1H4R5BA03#	
				±0.25pF	GRM0225C1H4R5CA03#	
			4.6pF	±0.05pF	GRM0225C1H4R6WA03#	
				±0.1pF	GRM0225C1H4R6BA03#	
				±0.25pF	GRM0225C1H4R6CA03#	
			4.7pF	±0.05pF	GRM0225C1H4R7WA03#	
				±0.1pF	GRM0225C1H4R7BA03#	
				±0.25pF	GRM0225C1H4R7CA03#	
			4.8pF	±0.05pF	GRM0225C1H4R8WA03#	
				±0.1pF	GRM0225C1H4R8BA03#	
				±0.25pF	GRM0225C1H4R8CA03#	
			4.9pF	±0.05pF	GRM0225C1H4R9WA03#	
				±0.1pF	GRM0225C1H4R9BA03#	
				±0.25pF	GRM0225C1H4R9CA03#	
			5.0pF	±0.05pF	GRM0225C1H5R0WA03#	
				±0.1pF	GRM0225C1H5R0BA03#	
				±0.25pF	GRM0225C1H5R0CA03#	
			5.1pF	±0.05pF	GRM0225C1H5R1WA03#	
				±0.1pF	GRM0225C1H5R1BA03#	
				±0.25pF	GRM0225C1H5R1CA03#	
				±0.5pF	GRM0225C1H5R1DA03#	
			5.2pF	±0.05pF	GRM0225C1H5R2WA03#	
				±0.1pF	GRM0225C1H5R2BA03#	
				±0.25pF	GRM0225C1H5R2CA03#	
				±0.5pF	GRM0225C1H5R2DA03#	
			5.3pF	±0.05pF	GRM0225C1H5R3WA03#	
				±0.1pF	GRM0225C1H5R3BA03#	
				±0.25pF	GRM0225C1H5R3CA03#	
				±0.5pF	GRM0225C1H5R3DA03#	
			5.4pF	±0.05pF	GRM0225C1H5R4WA03#	
				±0.1pF	GRM0225C1H5R4BA03#	
				±0.25pF	GRM0225C1H5R4CA03#	
				±0.5pF	GRM0225C1H5R4DA03#	
			5.5pF	±0.05pF	GRM0225C1H5R5WA03#	
				±0.1pF	GRM0225C1H5R5BA03#	
				±0.25pF	GRM0225C1H5R5CA03#	
				±0.5pF	GRM0225C1H5R5DA03#	
			5.6pF	±0.05pF	GRM0225C1H5R6WA03#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	C0G	5.6pF	±0.1pF	GRM0225C1H5R6BA03#	
				±0.25pF	GRM0225C1H5R6CA03#	
				±0.5pF	GRM0225C1H5R6DA03#	
			5.7pF	±0.05pF	GRM0225C1H5R7WA03#	
				±0.1pF	GRM0225C1H5R7BA03#	
				±0.25pF	GRM0225C1H5R7CA03#	
				±0.5pF	GRM0225C1H5R7DA03#	
			5.8pF	±0.05pF	GRM0225C1H5R8WA03#	
				±0.1pF	GRM0225C1H5R8BA03#	
				±0.25pF	GRM0225C1H5R8CA03#	
				±0.5pF	GRM0225C1H5R8DA03#	
			5.9pF	±0.05pF	GRM0225C1H5R9WA03#	
				±0.1pF	GRM0225C1H5R9BA03#	
				±0.25pF	GRM0225C1H5R9CA03#	
				±0.5pF	GRM0225C1H5R9DA03#	
			6.0pF	±0.05pF	GRM0225C1H6R0WA03#	
				±0.1pF	GRM0225C1H6R0BA03#	
				±0.25pF	GRM0225C1H6R0CA03#	
				±0.5pF	GRM0225C1H6R0DA03#	
			6.1pF	±0.05pF	GRM0225C1H6R1WA03#	
				±0.1pF	GRM0225C1H6R1BA03#	
				±0.25pF	GRM0225C1H6R1CA03#	
				±0.5pF	GRM0225C1H6R1DA03#	
			6.2pF	±0.05pF	GRM0225C1H6R2WA03#	
				±0.1pF	GRM0225C1H6R2BA03#	
				±0.25pF	GRM0225C1H6R2CA03#	
				±0.5pF	GRM0225C1H6R2DA03#	
			6.3pF	±0.05pF	GRM0225C1H6R3WA03#	
				±0.1pF	GRM0225C1H6R3BA03#	
				±0.25pF	GRM0225C1H6R3CA03#	
				±0.5pF	GRM0225C1H6R3DA03#	
			6.4pF	±0.05pF	GRM0225C1H6R4WA03#	
				±0.1pF	GRM0225C1H6R4BA03#	
				±0.25pF	GRM0225C1H6R4CA03#	
				±0.5pF	GRM0225C1H6R4DA03#	
			6.5pF	±0.05pF	GRM0225C1H6R5WA03#	
				±0.1pF	GRM0225C1H6R5BA03#	
				±0.25pF	GRM0225C1H6R5CA03#	
				±0.5pF	GRM0225C1H6R5DA03#	
			6.6pF	±0.05pF	GRM0225C1H6R6WA03#	
				±0.1pF	GRM0225C1H6R6BA03#	
				±0.25pF	GRM0225C1H6R6CA03#	
				±0.5pF	GRM0225C1H6R6DA03#	
			6.7pF	±0.05pF	GRM0225C1H6R7WA03#	
				±0.1pF	GRM0225C1H6R7BA03#	
				±0.25pF	GRM0225C1H6R7CA03#	
				±0.5pF	GRM0225C1H6R7DA03#	
			6.8pF	±0.05pF	GRM0225C1H6R8WA03#	
				±0.1pF	GRM0225C1H6R8BA03#	
				±0.25pF	GRM0225C1H6R8CA03#	
				±0.5pF	GRM0225C1H6R8DA03#	
			6.9pF	±0.05pF	GRM0225C1H6R9WA03#	
				±0.1pF	GRM0225C1H6R9BA03#	
				±0.25pF	GRM0225C1H6R9CA03#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	C0G	6.9pF	±0.5pF	GRM0225C1H6R9DA03#	
			7.0pF	±0.05pF	GRM0225C1H7R0WA03#	
				±0.1pF	GRM0225C1H7R0BA03#	
				±0.25pF	GRM0225C1H7R0CA03#	
				±0.5pF	GRM0225C1H7R0DA03#	
			7.1pF	±0.05pF	GRM0225C1H7R1WA03#	
				±0.1pF	GRM0225C1H7R1BA03#	
				±0.25pF	GRM0225C1H7R1CA03#	
				±0.5pF	GRM0225C1H7R1DA03#	
			7.2pF	±0.05pF	GRM0225C1H7R2WA03#	
				±0.1pF	GRM0225C1H7R2BA03#	
				±0.25pF	GRM0225C1H7R2CA03#	
				±0.5pF	GRM0225C1H7R2DA03#	
			7.3pF	±0.05pF	GRM0225C1H7R3WA03#	
				±0.1pF	GRM0225C1H7R3BA03#	
				±0.25pF	GRM0225C1H7R3CA03#	
				±0.5pF	GRM0225C1H7R3DA03#	
			7.4pF	±0.05pF	GRM0225C1H7R4WA03#	
				±0.1pF	GRM0225C1H7R4BA03#	
				±0.25pF	GRM0225C1H7R4CA03#	
				±0.5pF	GRM0225C1H7R4DA03#	
			7.5pF	±0.05pF	GRM0225C1H7R5WA03#	
				±0.1pF	GRM0225C1H7R5BA03#	
				±0.25pF	GRM0225C1H7R5CA03#	
				±0.5pF	GRM0225C1H7R5DA03#	
			7.6pF	±0.05pF	GRM0225C1H7R6WA03#	
				±0.1pF	GRM0225C1H7R6BA03#	
				±0.25pF	GRM0225C1H7R6CA03#	
				±0.5pF	GRM0225C1H7R6DA03#	
			7.7pF	±0.05pF	GRM0225C1H7R7WA03#	
				±0.1pF	GRM0225C1H7R7BA03#	
				±0.25pF	GRM0225C1H7R7CA03#	
				±0.5pF	GRM0225C1H7R7DA03#	
			7.8pF	±0.05pF	GRM0225C1H7R8WA03#	
				±0.1pF	GRM0225C1H7R8BA03#	
				±0.25pF	GRM0225C1H7R8CA03#	
				±0.5pF	GRM0225C1H7R8DA03#	
			7.9pF	±0.05pF	GRM0225C1H7R9WA03#	
				±0.1pF	GRM0225C1H7R9BA03#	
				±0.25pF	GRM0225C1H7R9CA03#	
				±0.5pF	GRM0225C1H7R9DA03#	
			8.0pF	±0.05pF	GRM0225C1H8R0WA03#	
				±0.1pF	GRM0225C1H8R0BA03#	
				±0.25pF	GRM0225C1H8R0CA03#	
				±0.5pF	GRM0225C1H8R0DA03#	
			8.1pF	±0.05pF	GRM0225C1H8R1WA03#	
				±0.1pF	GRM0225C1H8R1BA03#	
				±0.25pF	GRM0225C1H8R1CA03#	
				±0.5pF	GRM0225C1H8R1DA03#	
			8.2pF	±0.05pF	GRM0225C1H8R2WA03#	
				±0.1pF	GRM0225C1H8R2BA03#	
				±0.25pF	GRM0225C1H8R2CA03#	
				±0.5pF	GRM0225C1H8R2DA03#	
			8.3pF	±0.05pF	GRM0225C1H8R3WA03#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	C0G	8.3pF	±0.1pF	GRM0225C1H8R3BA03#	
				±0.25pF	GRM0225C1H8R3CA03#	
				±0.5pF	GRM0225C1H8R3DA03#	
			8.4pF	±0.05pF	GRM0225C1H8R4WA03#	
				±0.1pF	GRM0225C1H8R4BA03#	
				±0.25pF	GRM0225C1H8R4CA03#	
				±0.5pF	GRM0225C1H8R4DA03#	
			8.5pF	±0.05pF	GRM0225C1H8R5WA03#	
				±0.1pF	GRM0225C1H8R5BA03#	
				±0.25pF	GRM0225C1H8R5CA03#	
				±0.5pF	GRM0225C1H8R5DA03#	
			8.6pF	±0.05pF	GRM0225C1H8R6WA03#	
				±0.1pF	GRM0225C1H8R6BA03#	
				±0.25pF	GRM0225C1H8R6CA03#	
				±0.5pF	GRM0225C1H8R6DA03#	
			8.7pF	±0.05pF	GRM0225C1H8R7WA03#	
				±0.1pF	GRM0225C1H8R7BA03#	
				±0.25pF	GRM0225C1H8R7CA03#	
				±0.5pF	GRM0225C1H8R7DA03#	
			8.8pF	±0.05pF	GRM0225C1H8R8WA03#	
				±0.1pF	GRM0225C1H8R8BA03#	
				±0.25pF	GRM0225C1H8R8CA03#	
				±0.5pF	GRM0225C1H8R8DA03#	
			8.9pF	±0.05pF	GRM0225C1H8R9WA03#	
				±0.1pF	GRM0225C1H8R9BA03#	
				±0.25pF	GRM0225C1H8R9CA03#	
				±0.5pF	GRM0225C1H8R9DA03#	
			9.0pF	±0.05pF	GRM0225C1H9R0WA03#	
				±0.1pF	GRM0225C1H9R0BA03#	
				±0.25pF	GRM0225C1H9R0CA03#	
				±0.5pF	GRM0225C1H9R0DA03#	
			9.1pF	±0.05pF	GRM0225C1H9R1WA03#	
				±0.1pF	GRM0225C1H9R1BA03#	
				±0.25pF	GRM0225C1H9R1CA03#	
				±0.5pF	GRM0225C1H9R1DA03#	
			9.2pF	±0.05pF	GRM0225C1H9R2WA03#	
				±0.1pF	GRM0225C1H9R2BA03#	
				±0.25pF	GRM0225C1H9R2CA03#	
				±0.5pF	GRM0225C1H9R2DA03#	
			9.3pF	±0.05pF	GRM0225C1H9R3WA03#	
				±0.1pF	GRM0225C1H9R3BA03#	
				±0.25pF	GRM0225C1H9R3CA03#	
				±0.5pF	GRM0225C1H9R3DA03#	
			9.4pF	±0.05pF	GRM0225C1H9R4WA03#	
				±0.1pF	GRM0225C1H9R4BA03#	
				±0.25pF	GRM0225C1H9R4CA03#	
				±0.5pF	GRM0225C1H9R4DA03#	
			9.5pF	±0.05pF	GRM0225C1H9R5WA03#	
				±0.1pF	GRM0225C1H9R5BA03#	
				±0.25pF	GRM0225C1H9R5CA03#	
				±0.5pF	GRM0225C1H9R5DA03#	
			9.6pF	±0.05pF	GRM0225C1H9R6WA03#	
				±0.1pF	GRM0225C1H9R6BA03#	
				±0.25pF	GRM0225C1H9R6CA03#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	C0G	9.6pF	±0.5pF	GRM0225C1H9R6DA03#	
			9.7pF	±0.05pF	GRM0225C1H9R7WA03#	
				±0.1pF	GRM0225C1H9R7BA03#	
				±0.25pF	GRM0225C1H9R7CA03#	
				±0.5pF	GRM0225C1H9R7DA03#	
			9.8pF	±0.05pF	GRM0225C1H9R8WA03#	
				±0.1pF	GRM0225C1H9R8BA03#	
				±0.25pF	GRM0225C1H9R8CA03#	
				±0.5pF	GRM0225C1H9R8DA03#	
			9.9pF	±0.05pF	GRM0225C1H9R9WA03#	
				±0.1pF	GRM0225C1H9R9BA03#	
				±0.25pF	GRM0225C1H9R9CA03#	
				±0.5pF	GRM0225C1H9R9DA03#	
			10pF	±2%	GRM0225C1H100GA03#	
				±5%	GRM0225C1H100JA03#	
			11pF	±2%	GRM0225C1H110GA03#	
				±5%	GRM0225C1H110JA03#	
			12pF	±2%	GRM0225C1H120GA03#	
				±5%	GRM0225C1H120JA03#	
			13pF	±2%	GRM0225C1H130GA03#	
				±5%	GRM0225C1H130JA03#	
			15pF	±2%	GRM0225C1H150GA03#	
				±5%	GRM0225C1H150JA03#	
			16pF	±2%	GRM0225C1H160GA03#	
				±5%	GRM0225C1H160JA03#	
			17pF	±5%	GRM0225C1H170JA02#	
			18pF	±5%	GRM0225C1H180JA02#	
			19pF	±5%	GRM0225C1H190JA02#	
			20pF	±5%	GRM0225C1H200JA02#	
			21pF	±5%	GRM0225C1H210JA02#	
			22pF	±5%	GRM0225C1H220JA02#	
			23pF	±5%	GRM0225C1H230JA02#	
			24pF	±5%	GRM0225C1H240JA02#	
			27pF	±5%	GRM0225C1H270JA02#	
			30pF	±5%	GRM0225C1H300JA02#	
			33pF	±5%	GRM0225C1H330JA02#	
			36pF	±5%	GRM0225C1H360JA02#	
			39pF	±5%	GRM0225C1H390JA02#	
			43pF	±5%	GRM0225C1H430JA02#	
			47pF	±5%	GRM0225C1H470JA02#	
			51pF	±5%	GRM0225C1H510JA02#	
			56pF	±5%	GRM0225C1H560JA02#	
			62pF	±5%	GRM0225C1H620JA02#	
			68pF	±5%	GRM0225C1H680JA02#	
			75pF	±5%	GRM0225C1H750JA02#	
			82pF	±5%	GRM0225C1H820JA02#	
			91pF	±5%	GRM0225C1H910JA02#	
			100pF	±5%	GRM0225C1H101JA02#	
		CK	0.20pF	±0.05pF	GRM0224C1HR20WA03#	
				±0.1pF	GRM0224C1HR20BA03#	
			0.30pF	±0.05pF	GRM0224C1HR30WA03#	
				±0.1pF	GRM0224C1HR30BA03#	
			0.40pF	±0.05pF	GRM0224C1HR40WA03#	
				±0.1pF	GRM0224C1HR40BA03#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	CK	0.50pF	±0.05pF	GRM0224C1HR50WA03#	
				±0.1pF	GRM0224C1HR50BA03#	
			0.51pF	±0.05pF	GRM0224C1HR51WA03#	
			0.60pF	±0.05pF	GRM0224C1HR60WA03#	
				±0.1pF	GRM0224C1HR60BA03#	
			0.70pF	±0.05pF	GRM0224C1HR70WA03#	
				±0.1pF	GRM0224C1HR70BA03#	
			0.80pF	±0.05pF	GRM0224C1HR80WA03#	
				±0.1pF	GRM0224C1HR80BA03#	
			0.90pF	±0.05pF	GRM0224C1HR90WA03#	
				±0.1pF	GRM0224C1HR90BA03#	
			1.0pF	±0.05pF	GRM0224C1H1R0WA03#	
				±0.1pF	GRM0224C1H1R0BA03#	
				±0.25pF	GRM0224C1H1R0CA03#	
			1.1pF	±0.05pF	GRM0224C1H1R1WA03#	
				±0.1pF	GRM0224C1H1R1BA03#	
				±0.25pF	GRM0224C1H1R1CA03#	
			1.2pF	±0.05pF	GRM0224C1H1R2WA03#	
				±0.1pF	GRM0224C1H1R2BA03#	
				±0.25pF	GRM0224C1H1R2CA03#	
			1.3pF	±0.05pF	GRM0224C1H1R3WA03#	
				±0.1pF	GRM0224C1H1R3BA03#	
				±0.25pF	GRM0224C1H1R3CA03#	
			1.4pF	±0.05pF	GRM0224C1H1R4WA03#	
				±0.1pF	GRM0224C1H1R4BA03#	
				±0.25pF	GRM0224C1H1R4CA03#	
			1.5pF	±0.05pF	GRM0224C1H1R5WA03#	
				±0.1pF	GRM0224C1H1R5BA03#	
				±0.25pF	GRM0224C1H1R5CA03#	
			1.6pF	±0.05pF	GRM0224C1H1R6WA03#	
				±0.1pF	GRM0224C1H1R6BA03#	
				±0.25pF	GRM0224C1H1R6CA03#	
			1.7pF	±0.05pF	GRM0224C1H1R7WA03#	
				±0.1pF	GRM0224C1H1R7BA03#	
				±0.25pF	GRM0224C1H1R7CA03#	
			1.8pF	±0.05pF	GRM0224C1H1R8WA03#	
				±0.1pF	GRM0224C1H1R8BA03#	
				±0.25pF	GRM0224C1H1R8CA03#	
			1.9pF	±0.05pF	GRM0224C1H1R9WA03#	
				±0.1pF	GRM0224C1H1R9BA03#	
				±0.25pF	GRM0224C1H1R9CA03#	
			2.0pF	±0.05pF	GRM0224C1H2R0WA03#	
				±0.1pF	GRM0224C1H2R0BA03#	
				±0.25pF	GRM0224C1H2R0CA03#	
		CJ	2.1pF	±0.05pF	GRM0223C1H2R1WA03#	
				±0.1pF	GRM0223C1H2R1BA03#	
				±0.25pF	GRM0223C1H2R1CA03#	
			2.2pF	±0.05pF	GRM0223C1H2R2WA03#	
				±0.1pF	GRM0223C1H2R2BA03#	
				±0.25pF	GRM0223C1H2R2CA03#	
			2.3pF	±0.05pF	GRM0223C1H2R3WA03#	
				±0.1pF	GRM0223C1H2R3BA03#	
				±0.25pF	GRM0223C1H2R3CA03#	
			2.4pF	±0.05pF	GRM0223C1H2R4WA03#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	CJ	2.4pF	±0.1pF	GRM0223C1H2R4BA03#	
				±0.25pF	GRM0223C1H2R4CA03#	
			2.5pF	±0.05pF	GRM0223C1H2R5WA03#	
				±0.1pF	GRM0223C1H2R5BA03#	
				±0.25pF	GRM0223C1H2R5CA03#	
			2.6pF	±0.05pF	GRM0223C1H2R6WA03#	
				±0.1pF	GRM0223C1H2R6BA03#	
				±0.25pF	GRM0223C1H2R6CA03#	
			2.7pF	±0.05pF	GRM0223C1H2R7WA03#	
				±0.1pF	GRM0223C1H2R7BA03#	
				±0.25pF	GRM0223C1H2R7CA03#	
			2.8pF	±0.05pF	GRM0223C1H2R8WA03#	
				±0.1pF	GRM0223C1H2R8BA03#	
				±0.25pF	GRM0223C1H2R8CA03#	
			2.9pF	±0.05pF	GRM0223C1H2R9WA03#	
				±0.1pF	GRM0223C1H2R9BA03#	
				±0.25pF	GRM0223C1H2R9CA03#	
			3.0pF	±0.05pF	GRM0223C1H3R0WA03#	
				±0.1pF	GRM0223C1H3R0BA03#	
				±0.25pF	GRM0223C1H3R0CA03#	
			3.1pF	±0.05pF	GRM0223C1H3R1WA03#	
				±0.1pF	GRM0223C1H3R1BA03#	
				±0.25pF	GRM0223C1H3R1CA03#	
			3.2pF	±0.05pF	GRM0223C1H3R2WA03#	
				±0.1pF	GRM0223C1H3R2BA03#	
				±0.25pF	GRM0223C1H3R2CA03#	
			3.3pF	±0.05pF	GRM0223C1H3R3WA03#	
				±0.1pF	GRM0223C1H3R3BA03#	
				±0.25pF	GRM0223C1H3R3CA03#	
			3.4pF	±0.05pF	GRM0223C1H3R4WA03#	
				±0.1pF	GRM0223C1H3R4BA03#	
				±0.25pF	GRM0223C1H3R4CA03#	
			3.5pF	±0.05pF	GRM0223C1H3R5WA03#	
				±0.1pF	GRM0223C1H3R5BA03#	
				±0.25pF	GRM0223C1H3R5CA03#	
			3.6pF	±0.05pF	GRM0223C1H3R6WA03#	
				±0.1pF	GRM0223C1H3R6BA03#	
				±0.25pF	GRM0223C1H3R6CA03#	
			3.7pF	±0.05pF	GRM0223C1H3R7WA03#	
				±0.1pF	GRM0223C1H3R7BA03#	
				±0.25pF	GRM0223C1H3R7CA03#	
			3.8pF	±0.05pF	GRM0223C1H3R8WA03#	
				±0.1pF	GRM0223C1H3R8BA03#	
				±0.25pF	GRM0223C1H3R8CA03#	
			3.9pF	±0.05pF	GRM0223C1H3R9WA03#	
				±0.1pF	GRM0223C1H3R9BA03#	
				±0.25pF	GRM0223C1H3R9CA03#	
		CH	4.0pF	±0.05pF	GRM0222C1H4R0WA03#	
				±0.1pF	GRM0222C1H4R0BA03#	
				±0.25pF	GRM0222C1H4R0CA03#	
			4.1pF	±0.05pF	GRM0222C1H4R1WA03#	
				±0.1pF	GRM0222C1H4R1BA03#	
				±0.25pF	GRM0222C1H4R1CA03#	
			4.2pF	±0.05pF	GRM0222C1H4R2WA03#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	CH	4.2pF	±0.1pF	GRM0222C1H4R2BA03#	
				±0.25pF	GRM0222C1H4R2CA03#	
			4.3pF	±0.05pF	GRM0222C1H4R3WA03#	
				±0.1pF	GRM0222C1H4R3BA03#	
				±0.25pF	GRM0222C1H4R3CA03#	
			4.4pF	±0.05pF	GRM0222C1H4R4WA03#	
				±0.1pF	GRM0222C1H4R4BA03#	
				±0.25pF	GRM0222C1H4R4CA03#	
			4.5pF	±0.05pF	GRM0222C1H4R5WA03#	
				±0.1pF	GRM0222C1H4R5BA03#	
				±0.25pF	GRM0222C1H4R5CA03#	
			4.6pF	±0.05pF	GRM0222C1H4R6WA03#	
				±0.1pF	GRM0222C1H4R6BA03#	
				±0.25pF	GRM0222C1H4R6CA03#	
			4.7pF	±0.05pF	GRM0222C1H4R7WA03#	
				±0.1pF	GRM0222C1H4R7BA03#	
				±0.25pF	GRM0222C1H4R7CA03#	
			4.8pF	±0.05pF	GRM0222C1H4R8WA03#	
				±0.1pF	GRM0222C1H4R8BA03#	
				±0.25pF	GRM0222C1H4R8CA03#	
			4.9pF	±0.05pF	GRM0222C1H4R9WA03#	
				±0.1pF	GRM0222C1H4R9BA03#	
				±0.25pF	GRM0222C1H4R9CA03#	
			5.0pF	±0.05pF	GRM0222C1H5R0WA03#	
				±0.1pF	GRM0222C1H5R0BA03#	
				±0.25pF	GRM0222C1H5R0CA03#	
			5.1pF	±0.05pF	GRM0222C1H5R1WA03#	
				±0.1pF	GRM0222C1H5R1BA03#	
				±0.25pF	GRM0222C1H5R1CA03#	
				±0.5pF	GRM0222C1H5R1DA03#	
			5.2pF	±0.05pF	GRM0222C1H5R2WA03#	
				±0.1pF	GRM0222C1H5R2BA03#	
				±0.25pF	GRM0222C1H5R2CA03#	
				±0.5pF	GRM0222C1H5R2DA03#	
			5.3pF	±0.05pF	GRM0222C1H5R3WA03#	
				±0.1pF	GRM0222C1H5R3BA03#	
				±0.25pF	GRM0222C1H5R3CA03#	
				±0.5pF	GRM0222C1H5R3DA03#	
			5.4pF	±0.05pF	GRM0222C1H5R4WA03#	
				±0.1pF	GRM0222C1H5R4BA03#	
				±0.25pF	GRM0222C1H5R4CA03#	
				±0.5pF	GRM0222C1H5R4DA03#	
			5.5pF	±0.05pF	GRM0222C1H5R5WA03#	
				±0.1pF	GRM0222C1H5R5BA03#	
				±0.25pF	GRM0222C1H5R5CA03#	
				±0.5pF	GRM0222C1H5R5DA03#	
			5.6pF	±0.05pF	GRM0222C1H5R6WA03#	
				±0.1pF	GRM0222C1H5R6BA03#	
				±0.25pF	GRM0222C1H5R6CA03#	
				±0.5pF	GRM0222C1H5R6DA03#	
			5.7pF	±0.05pF	GRM0222C1H5R7WA03#	
				±0.1pF	GRM0222C1H5R7BA03#	
				±0.25pF	GRM0222C1H5R7CA03#	
				±0.5pF	GRM0222C1H5R7DA03#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	CH	5.8pF	±0.05pF	GRM0222C1H5R8WA03#	
				±0.1pF	GRM0222C1H5R8BA03#	
				±0.25pF	GRM0222C1H5R8CA03#	
				±0.5pF	GRM0222C1H5R8DA03#	
			5.9pF	±0.05pF	GRM0222C1H5R9WA03#	
				±0.1pF	GRM0222C1H5R9BA03#	
				±0.25pF	GRM0222C1H5R9CA03#	
				±0.5pF	GRM0222C1H5R9DA03#	
			6.0pF	±0.05pF	GRM0222C1H6R0WA03#	
				±0.1pF	GRM0222C1H6R0BA03#	
				±0.25pF	GRM0222C1H6R0CA03#	
				±0.5pF	GRM0222C1H6R0DA03#	
			6.1pF	±0.05pF	GRM0222C1H6R1WA03#	
				±0.1pF	GRM0222C1H6R1BA03#	
				±0.25pF	GRM0222C1H6R1CA03#	
				±0.5pF	GRM0222C1H6R1DA03#	
			6.2pF	±0.05pF	GRM0222C1H6R2WA03#	
				±0.1pF	GRM0222C1H6R2BA03#	
				±0.25pF	GRM0222C1H6R2CA03#	
				±0.5pF	GRM0222C1H6R2DA03#	
			6.3pF	±0.05pF	GRM0222C1H6R3WA03#	
				±0.1pF	GRM0222C1H6R3BA03#	
				±0.25pF	GRM0222C1H6R3CA03#	
				±0.5pF	GRM0222C1H6R3DA03#	
			6.4pF	±0.05pF	GRM0222C1H6R4WA03#	
				±0.1pF	GRM0222C1H6R4BA03#	
				±0.25pF	GRM0222C1H6R4CA03#	
				±0.5pF	GRM0222C1H6R4DA03#	
			6.5pF	±0.05pF	GRM0222C1H6R5WA03#	
				±0.1pF	GRM0222C1H6R5BA03#	
				±0.25pF	GRM0222C1H6R5CA03#	
				±0.5pF	GRM0222C1H6R5DA03#	
			6.6pF	±0.05pF	GRM0222C1H6R6WA03#	
				±0.1pF	GRM0222C1H6R6BA03#	
				±0.25pF	GRM0222C1H6R6CA03#	
				±0.5pF	GRM0222C1H6R6DA03#	
			6.7pF	±0.05pF	GRM0222C1H6R7WA03#	
				±0.1pF	GRM0222C1H6R7BA03#	
				±0.25pF	GRM0222C1H6R7CA03#	
				±0.5pF	GRM0222C1H6R7DA03#	
			6.8pF	±0.05pF	GRM0222C1H6R8WA03#	
				±0.1pF	GRM0222C1H6R8BA03#	
				±0.25pF	GRM0222C1H6R8CA03#	
				±0.5pF	GRM0222C1H6R8DA03#	
			6.9pF	±0.05pF	GRM0222C1H6R9WA03#	
				±0.1pF	GRM0222C1H6R9BA03#	
				±0.25pF	GRM0222C1H6R9CA03#	
				±0.5pF	GRM0222C1H6R9DA03#	
			7.0pF	±0.05pF	GRM0222C1H7R0WA03#	
				±0.1pF	GRM0222C1H7R0BA03#	
				±0.25pF	GRM0222C1H7R0CA03#	
				±0.5pF	GRM0222C1H7R0DA03#	
			7.1pF	±0.05pF	GRM0222C1H7R1WA03#	
				±0.1pF	GRM0222C1H7R1BA03#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	CH	7.1pF	±0.25pF	GRM0222C1H7R1CA03#	
				±0.5pF	GRM0222C1H7R1DA03#	
			7.2pF	±0.05pF	GRM0222C1H7R2WA03#	
				±0.1pF	GRM0222C1H7R2BA03#	
				±0.25pF	GRM0222C1H7R2CA03#	
				±0.5pF	GRM0222C1H7R2DA03#	
			7.3pF	±0.05pF	GRM0222C1H7R3WA03#	
				±0.1pF	GRM0222C1H7R3BA03#	
				±0.25pF	GRM0222C1H7R3CA03#	
				±0.5pF	GRM0222C1H7R3DA03#	
			7.4pF	±0.05pF	GRM0222C1H7R4WA03#	
				±0.1pF	GRM0222C1H7R4BA03#	
				±0.25pF	GRM0222C1H7R4CA03#	
				±0.5pF	GRM0222C1H7R4DA03#	
			7.5pF	±0.05pF	GRM0222C1H7R5WA03#	
				±0.1pF	GRM0222C1H7R5BA03#	
				±0.25pF	GRM0222C1H7R5CA03#	
				±0.5pF	GRM0222C1H7R5DA03#	
			7.6pF	±0.05pF	GRM0222C1H7R6WA03#	
				±0.1pF	GRM0222C1H7R6BA03#	
				±0.25pF	GRM0222C1H7R6CA03#	
				±0.5pF	GRM0222C1H7R6DA03#	
			7.7pF	±0.05pF	GRM0222C1H7R7WA03#	
				±0.1pF	GRM0222C1H7R7BA03#	
				±0.25pF	GRM0222C1H7R7CA03#	
				±0.5pF	GRM0222C1H7R7DA03#	
			7.8pF	±0.05pF	GRM0222C1H7R8WA03#	
				±0.1pF	GRM0222C1H7R8BA03#	
				±0.25pF	GRM0222C1H7R8CA03#	
				±0.5pF	GRM0222C1H7R8DA03#	
			7.9pF	±0.05pF	GRM0222C1H7R9WA03#	
				±0.1pF	GRM0222C1H7R9BA03#	
				±0.25pF	GRM0222C1H7R9CA03#	
				±0.5pF	GRM0222C1H7R9DA03#	
			8.0pF	±0.05pF	GRM0222C1H8R0WA03#	
				±0.1pF	GRM0222C1H8R0BA03#	
				±0.25pF	GRM0222C1H8R0CA03#	
				±0.5pF	GRM0222C1H8R0DA03#	
			8.1pF	±0.05pF	GRM0222C1H8R1WA03#	
				±0.1pF	GRM0222C1H8R1BA03#	
				±0.25pF	GRM0222C1H8R1CA03#	
				±0.5pF	GRM0222C1H8R1DA03#	
			8.2pF	±0.05pF	GRM0222C1H8R2WA03#	
				±0.1pF	GRM0222C1H8R2BA03#	
				±0.25pF	GRM0222C1H8R2CA03#	
				±0.5pF	GRM0222C1H8R2DA03#	
			8.3pF	±0.05pF	GRM0222C1H8R3WA03#	
				±0.1pF	GRM0222C1H8R3BA03#	
				±0.25pF	GRM0222C1H8R3CA03#	
				±0.5pF	GRM0222C1H8R3DA03#	
			8.4pF	±0.05pF	GRM0222C1H8R4WA03#	
				±0.1pF	GRM0222C1H8R4BA03#	
				±0.25pF	GRM0222C1H8R4CA03#	
				±0.5pF	GRM0222C1H8R4DA03#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	CH	8.5pF	±0.05pF	GRM0222C1H8R5WA03#	
				±0.1pF	GRM0222C1H8R5BA03#	
				±0.25pF	GRM0222C1H8R5CA03#	
				±0.5pF	GRM0222C1H8R5DA03#	
			8.6pF	±0.05pF	GRM0222C1H8R6WA03#	
				±0.1pF	GRM0222C1H8R6BA03#	
				±0.25pF	GRM0222C1H8R6CA03#	
				±0.5pF	GRM0222C1H8R6DA03#	
			8.7pF	±0.05pF	GRM0222C1H8R7WA03#	
				±0.1pF	GRM0222C1H8R7BA03#	
				±0.25pF	GRM0222C1H8R7CA03#	
				±0.5pF	GRM0222C1H8R7DA03#	
			8.8pF	±0.05pF	GRM0222C1H8R8WA03#	
				±0.1pF	GRM0222C1H8R8BA03#	
				±0.25pF	GRM0222C1H8R8CA03#	
				±0.5pF	GRM0222C1H8R8DA03#	
			8.9pF	±0.05pF	GRM0222C1H8R9WA03#	
				±0.1pF	GRM0222C1H8R9BA03#	
				±0.25pF	GRM0222C1H8R9CA03#	
				±0.5pF	GRM0222C1H8R9DA03#	
			9.0pF	±0.05pF	GRM0222C1H9R0WA03#	
				±0.1pF	GRM0222C1H9R0BA03#	
				±0.25pF	GRM0222C1H9R0CA03#	
				±0.5pF	GRM0222C1H9R0DA03#	
			9.1pF	±0.05pF	GRM0222C1H9R1WA03#	
				±0.1pF	GRM0222C1H9R1BA03#	
				±0.25pF	GRM0222C1H9R1CA03#	
				±0.5pF	GRM0222C1H9R1DA03#	
			9.2pF	±0.05pF	GRM0222C1H9R2WA03#	
				±0.1pF	GRM0222C1H9R2BA03#	
				±0.25pF	GRM0222C1H9R2CA03#	
				±0.5pF	GRM0222C1H9R2DA03#	
			9.3pF	±0.05pF	GRM0222C1H9R3WA03#	
				±0.1pF	GRM0222C1H9R3BA03#	
				±0.25pF	GRM0222C1H9R3CA03#	
				±0.5pF	GRM0222C1H9R3DA03#	
			9.4pF	±0.05pF	GRM0222C1H9R4WA03#	
				±0.1pF	GRM0222C1H9R4BA03#	
				±0.25pF	GRM0222C1H9R4CA03#	
				±0.5pF	GRM0222C1H9R4DA03#	
			9.5pF	±0.05pF	GRM0222C1H9R5WA03#	
				±0.1pF	GRM0222C1H9R5BA03#	
				±0.25pF	GRM0222C1H9R5CA03#	
				±0.5pF	GRM0222C1H9R5DA03#	
			9.6pF	±0.05pF	GRM0222C1H9R6WA03#	
				±0.1pF	GRM0222C1H9R6BA03#	
				±0.25pF	GRM0222C1H9R6CA03#	
				±0.5pF	GRM0222C1H9R6DA03#	
			9.7pF	±0.05pF	GRM0222C1H9R7WA03#	
				±0.1pF	GRM0222C1H9R7BA03#	
				±0.25pF	GRM0222C1H9R7CA03#	
				±0.5pF	GRM0222C1H9R7DA03#	
			9.8pF	±0.05pF	GRM0222C1H9R8WA03#	
				±0.1pF	GRM0222C1H9R8BA03#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	50Vdc	CH	9.8pF	±0.25pF	GRM0222C1H9R8CA03#	
				±0.5pF	GRM0222C1H9R8DA03#	
			9.9pF	±0.05pF	GRM0222C1H9R9WA03#	
				±0.1pF	GRM0222C1H9R9BA03#	
				±0.25pF	GRM0222C1H9R9CA03#	
				±0.5pF	GRM0222C1H9R9DA03#	
			10pF	±2%	GRM0222C1H100GA03#	
				±5%	GRM0222C1H100JA03#	
			11pF	±2%	GRM0222C1H110GA03#	
				±5%	GRM0222C1H110JA03#	
			12pF	±2%	GRM0222C1H120GA03#	
				±5%	GRM0222C1H120JA03#	
			13pF	±2%	GRM0222C1H130GA03#	
				±5%	GRM0222C1H130JA03#	
			15pF	±2%	GRM0222C1H150GA03#	
				±5%	GRM0222C1H150JA03#	
			16pF	±2%	GRM0222C1H160GA03#	
				±5%	GRM0222C1H160JA03#	
			17pF	±5%	GRM0222C1H170JA02#	
			18pF	±5%	GRM0222C1H180JA02#	
			19pF	±5%	GRM0222C1H190JA02#	
			20pF	±5%	GRM0222C1H200JA02#	
			21pF	±5%	GRM0222C1H210JA02#	
			22pF	±5%	GRM0222C1H220JA02#	
			23pF	±5%	GRM0222C1H230JA02#	
			24pF	±5%	GRM0222C1H240JA02#	
			27pF	±5%	GRM0222C1H270JA02#	
			30pF	±5%	GRM0222C1H300JA02#	
			33pF	±5%	GRM0222C1H330JA02#	
			36pF	±5%	GRM0222C1H360JA02#	
			39pF	±5%	GRM0222C1H390JA02#	
			43pF	±5%	GRM0222C1H430JA02#	
			47pF	±5%	GRM0222C1H470JA02#	
			51pF	±5%	GRM0222C1H510JA02#	
			56pF	±5%	GRM0222C1H560JA02#	
			62pF	±5%	GRM0222C1H620JA02#	
			68pF	±5%	GRM0222C1H680JA02#	
			75pF	±5%	GRM0222C1H750JA02#	
			82pF	±5%	GRM0222C1H820JA02#	
			91pF	±5%	GRM0222C1H910JA02#	
			100pF	±5%	GRM0222C1H101JA02#	
	25Vdc	C0G	120pF	±5%	GRM0225C1E121JA02#	
			150pF	±5%	GRM0225C1E151JA02#	
			180pF	±5%	GRM0225C1E181JA02#	
			220pF	±5%	GRM0225C1E221JA02#	
		CH	120pF	±5%	GRM0222C1E121JA02#	
			150pF	±5%	GRM0222C1E151JA02#	
			180pF	±5%	GRM0222C1E181JA02#	
			220pF	±5%	GRM0222C1E221JA02#	
	16Vdc	C0G	120pF	±5%	GRM0225C1C121JA02#	
			150pF	±5%	GRM0225C1C151JA02#	
			180pF	±5%	GRM0225C1C181JA02#	
			220pF	±5%	GRM0225C1C221JA02#	
		CH	120pF	±5%	GRM0222C1C121JA02#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	16Vdc	CH	150pF	±5%	**GRM0222C1C151JA02#**	
			180pF	±5%	**GRM0222C1C181JA02#**	
			220pF	±5%	**GRM0222C1C221JA02#**	

0.6×0.3mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	0.10pF	±0.05pF	**GRM0335C2AR10WA01#**	
			0.20pF	±0.05pF	**GRM0335C2AR20WA01#**	
				±0.1pF	**GRM0335C2AR20BA01#**	
			0.30pF	±0.05pF	**GRM0335C2AR30WA01#**	
				±0.1pF	**GRM0335C2AR30BA01#**	
			0.40pF	±0.05pF	**GRM0335C2AR40WA01#**	
				±0.1pF	**GRM0335C2AR40BA01#**	
			0.50pF	±0.05pF	**GRM0335C2AR50WA01#**	
				±0.1pF	**GRM0335C2AR50BA01#**	
			0.60pF	±0.05pF	**GRM0335C2AR60WA01#**	
				±0.1pF	**GRM0335C2AR60BA01#**	
			0.70pF	±0.05pF	**GRM0335C2AR70WA01#**	
				±0.1pF	**GRM0335C2AR70BA01#**	
			0.80pF	±0.05pF	**GRM0335C2AR80WA01#**	
				±0.1pF	**GRM0335C2AR80BA01#**	
			0.90pF	±0.05pF	**GRM0335C2AR90WA01#**	
				±0.1pF	**GRM0335C2AR90BA01#**	
			1.0pF	±0.05pF	**GRM0335C2A1R0WA01#**	
				±0.1pF	**GRM0335C2A1R0BA01#**	
				±0.25pF	**GRM0335C2A1R0CA01#**	
			1.1pF	±0.05pF	**GRM0335C2A1R1WA01#**	
				±0.1pF	**GRM0335C2A1R1BA01#**	
				±0.25pF	**GRM0335C2A1R1CA01#**	
			1.2pF	±0.05pF	**GRM0335C2A1R2WA01#**	
				±0.1pF	**GRM0335C2A1R2BA01#**	
				±0.25pF	**GRM0335C2A1R2CA01#**	
			1.3pF	±0.05pF	**GRM0335C2A1R3WA01#**	
				±0.1pF	**GRM0335C2A1R3BA01#**	
				±0.25pF	**GRM0335C2A1R3CA01#**	
			1.4pF	±0.05pF	**GRM0335C2A1R4WA01#**	
				±0.1pF	**GRM0335C2A1R4BA01#**	
				±0.25pF	**GRM0335C2A1R4CA01#**	
			1.5pF	±0.05pF	**GRM0335C2A1R5WA01#**	
				±0.1pF	**GRM0335C2A1R5BA01#**	
				±0.25pF	**GRM0335C2A1R5CA01#**	
			1.6pF	±0.05pF	**GRM0335C2A1R6WA01#**	
				±0.1pF	**GRM0335C2A1R6BA01#**	
				±0.25pF	**GRM0335C2A1R6CA01#**	
			1.7pF	±0.05pF	**GRM0335C2A1R7WA01#**	
				±0.1pF	**GRM0335C2A1R7BA01#**	
				±0.25pF	**GRM0335C2A1R7CA01#**	
			1.8pF	±0.05pF	**GRM0335C2A1R8WA01#**	
				±0.1pF	**GRM0335C2A1R8BA01#**	
				±0.25pF	**GRM0335C2A1R8CA01#**	
			1.9pF	±0.05pF	**GRM0335C2A1R9WA01#**	
				±0.1pF	**GRM0335C2A1R9BA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	1.9pF	±0.25pF	**GRM0335C2A1R9CA01#**	
			2.0pF	±0.05pF	**GRM0335C2A2R0WA01#**	
				±0.1pF	**GRM0335C2A2R0BA01#**	
				±0.25pF	**GRM0335C2A2R0CA01#**	
			2.1pF	±0.05pF	**GRM0335C2A2R1WA01#**	
				±0.1pF	**GRM0335C2A2R1BA01#**	
				±0.25pF	**GRM0335C2A2R1CA01#**	
			2.2pF	±0.05pF	**GRM0335C2A2R2WA01#**	
				±0.1pF	**GRM0335C2A2R2BA01#**	
				±0.25pF	**GRM0335C2A2R2CA01#**	
			2.3pF	±0.05pF	**GRM0335C2A2R3WA01#**	
				±0.1pF	**GRM0335C2A2R3BA01#**	
				±0.25pF	**GRM0335C2A2R3CA01#**	
			2.4pF	±0.05pF	**GRM0335C2A2R4WA01#**	
				±0.1pF	**GRM0335C2A2R4BA01#**	
				±0.25pF	**GRM0335C2A2R4CA01#**	
			2.5pF	±0.05pF	**GRM0335C2A2R5WA01#**	
				±0.1pF	**GRM0335C2A2R5BA01#**	
				±0.25pF	**GRM0335C2A2R5CA01#**	
			2.6pF	±0.05pF	**GRM0335C2A2R6WA01#**	
				±0.1pF	**GRM0335C2A2R6BA01#**	
				±0.25pF	**GRM0335C2A2R6CA01#**	
			2.7pF	±0.05pF	**GRM0335C2A2R7WA01#**	
				±0.1pF	**GRM0335C2A2R7BA01#**	
				±0.25pF	**GRM0335C2A2R7CA01#**	
			2.8pF	±0.05pF	**GRM0335C2A2R8WA01#**	
				±0.1pF	**GRM0335C2A2R8BA01#**	
				±0.25pF	**GRM0335C2A2R8CA01#**	
			2.9pF	±0.05pF	**GRM0335C2A2R9WA01#**	
				±0.1pF	**GRM0335C2A2R9BA01#**	
				±0.25pF	**GRM0335C2A2R9CA01#**	
			3.0pF	±0.05pF	**GRM0335C2A3R0WA01#**	
				±0.1pF	**GRM0335C2A3R0BA01#**	
				±0.25pF	**GRM0335C2A3R0CA01#**	
			3.1pF	±0.05pF	**GRM0335C2A3R1WA01#**	
				±0.1pF	**GRM0335C2A3R1BA01#**	
				±0.25pF	**GRM0335C2A3R1CA01#**	
			3.2pF	±0.05pF	**GRM0335C2A3R2WA01#**	
				±0.1pF	**GRM0335C2A3R2BA01#**	
				±0.25pF	**GRM0335C2A3R2CA01#**	
			3.3pF	±0.05pF	**GRM0335C2A3R3WA01#**	
				±0.1pF	**GRM0335C2A3R3BA01#**	
				±0.25pF	**GRM0335C2A3R3CA01#**	
			3.4pF	±0.05pF	**GRM0335C2A3R4WA01#**	
				±0.1pF	**GRM0335C2A3R4BA01#**	
				±0.25pF	**GRM0335C2A3R4CA01#**	
			3.5pF	±0.05pF	**GRM0335C2A3R5WA01#**	
				±0.1pF	**GRM0335C2A3R5BA01#**	
				±0.25pF	**GRM0335C2A3R5CA01#**	
			3.6pF	±0.05pF	**GRM0335C2A3R6WA01#**	
				±0.1pF	**GRM0335C2A3R6BA01#**	
				±0.25pF	**GRM0335C2A3R6CA01#**	
			3.7pF	±0.05pF	**GRM0335C2A3R7WA01#**	
				±0.1pF	**GRM0335C2A3R7BA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	3.7pF	±0.25pF	GRM0335C2A3R7CA01#	
			3.8pF	±0.05pF	GRM0335C2A3R8WA01#	
				±0.1pF	GRM0335C2A3R8BA01#	
				±0.25pF	GRM0335C2A3R8CA01#	
			3.9pF	±0.05pF	GRM0335C2A3R9WA01#	
				±0.1pF	GRM0335C2A3R9BA01#	
				±0.25pF	GRM0335C2A3R9CA01#	
			4.0pF	±0.05pF	GRM0335C2A4R0WA01#	
				±0.1pF	GRM0335C2A4R0BA01#	
				±0.25pF	GRM0335C2A4R0CA01#	
			4.1pF	±0.05pF	GRM0335C2A4R1WA01#	
				±0.1pF	GRM0335C2A4R1BA01#	
				±0.25pF	GRM0335C2A4R1CA01#	
			4.2pF	±0.05pF	GRM0335C2A4R2WA01#	
				±0.1pF	GRM0335C2A4R2BA01#	
				±0.25pF	GRM0335C2A4R2CA01#	
			4.3pF	±0.05pF	GRM0335C2A4R3WA01#	
				±0.1pF	GRM0335C2A4R3BA01#	
				±0.25pF	GRM0335C2A4R3CA01#	
			4.4pF	±0.05pF	GRM0335C2A4R4WA01#	
				±0.1pF	GRM0335C2A4R4BA01#	
				±0.25pF	GRM0335C2A4R4CA01#	
			4.5pF	±0.05pF	GRM0335C2A4R5WA01#	
				±0.1pF	GRM0335C2A4R5BA01#	
				±0.25pF	GRM0335C2A4R5CA01#	
			4.6pF	±0.05pF	GRM0335C2A4R6WA01#	
				±0.1pF	GRM0335C2A4R6BA01#	
				±0.25pF	GRM0335C2A4R6CA01#	
			4.7pF	±0.05pF	GRM0335C2A4R7WA01#	
				±0.1pF	GRM0335C2A4R7BA01#	
				±0.25pF	GRM0335C2A4R7CA01#	
			4.8pF	±0.05pF	GRM0335C2A4R8WA01#	
				±0.1pF	GRM0335C2A4R8BA01#	
				±0.25pF	GRM0335C2A4R8CA01#	
			4.9pF	±0.05pF	GRM0335C2A4R9WA01#	
				±0.1pF	GRM0335C2A4R9BA01#	
				±0.25pF	GRM0335C2A4R9CA01#	
			5.0pF	±0.05pF	GRM0335C2A5R0WA01#	
				±0.1pF	GRM0335C2A5R0BA01#	
				±0.25pF	GRM0335C2A5R0CA01#	
			5.1pF	±0.05pF	GRM0335C2A5R1WA01#	
				±0.1pF	GRM0335C2A5R1BA01#	
				±0.25pF	GRM0335C2A5R1CA01#	
				±0.5pF	GRM0335C2A5R1DA01#	
			5.2pF	±0.05pF	GRM0335C2A5R2WA01#	
				±0.1pF	GRM0335C2A5R2BA01#	
				±0.25pF	GRM0335C2A5R2CA01#	
				±0.5pF	GRM0335C2A5R2DA01#	
			5.3pF	±0.05pF	GRM0335C2A5R3WA01#	
				±0.1pF	GRM0335C2A5R3BA01#	
				±0.25pF	GRM0335C2A5R3CA01#	
				±0.5pF	GRM0335C2A5R3DA01#	
			5.4pF	±0.05pF	GRM0335C2A5R4WA01#	
				±0.1pF	GRM0335C2A5R4BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	5.4pF	±0.25pF	GRM0335C2A5R4CA01#	
				±0.5pF	GRM0335C2A5R4DA01#	
			5.5pF	±0.05pF	GRM0335C2A5R5WA01#	
				±0.1pF	GRM0335C2A5R5BA01#	
				±0.25pF	GRM0335C2A5R5CA01#	
				±0.5pF	GRM0335C2A5R5DA01#	
			5.6pF	±0.05pF	GRM0335C2A5R6WA01#	
				±0.1pF	GRM0335C2A5R6BA01#	
				±0.25pF	GRM0335C2A5R6CA01#	
				±0.5pF	GRM0335C2A5R6DA01#	
			5.7pF	±0.05pF	GRM0335C2A5R7WA01#	
				±0.1pF	GRM0335C2A5R7BA01#	
				±0.25pF	GRM0335C2A5R7CA01#	
				±0.5pF	GRM0335C2A5R7DA01#	
			5.8pF	±0.05pF	GRM0335C2A5R8WA01#	
				±0.1pF	GRM0335C2A5R8BA01#	
				±0.25pF	GRM0335C2A5R8CA01#	
				±0.5pF	GRM0335C2A5R8DA01#	
			5.9pF	±0.05pF	GRM0335C2A5R9WA01#	
				±0.1pF	GRM0335C2A5R9BA01#	
				±0.25pF	GRM0335C2A5R9CA01#	
				±0.5pF	GRM0335C2A5R9DA01#	
			6.0pF	±0.05pF	GRM0335C2A6R0WA01#	
				±0.1pF	GRM0335C2A6R0BA01#	
				±0.25pF	GRM0335C2A6R0CA01#	
				±0.5pF	GRM0335C2A6R0DA01#	
			6.1pF	±0.05pF	GRM0335C2A6R1WA01#	
				±0.1pF	GRM0335C2A6R1BA01#	
				±0.25pF	GRM0335C2A6R1CA01#	
				±0.5pF	GRM0335C2A6R1DA01#	
			6.2pF	±0.05pF	GRM0335C2A6R2WA01#	
				±0.1pF	GRM0335C2A6R2BA01#	
				±0.25pF	GRM0335C2A6R2CA01#	
				±0.5pF	GRM0335C2A6R2DA01#	
			6.3pF	±0.05pF	GRM0335C2A6R3WA01#	
				±0.1pF	GRM0335C2A6R3BA01#	
				±0.25pF	GRM0335C2A6R3CA01#	
				±0.5pF	GRM0335C2A6R3DA01#	
			6.4pF	±0.05pF	GRM0335C2A6R4WA01#	
				±0.1pF	GRM0335C2A6R4BA01#	
				±0.25pF	GRM0335C2A6R4CA01#	
				±0.5pF	GRM0335C2A6R4DA01#	
			6.5pF	±0.05pF	GRM0335C2A6R5WA01#	
				±0.1pF	GRM0335C2A6R5BA01#	
				±0.25pF	GRM0335C2A6R5CA01#	
				±0.5pF	GRM0335C2A6R5DA01#	
			6.6pF	±0.05pF	GRM0335C2A6R6WA01#	
				±0.1pF	GRM0335C2A6R6BA01#	
				±0.25pF	GRM0335C2A6R6CA01#	
				±0.5pF	GRM0335C2A6R6DA01#	
			6.7pF	±0.05pF	GRM0335C2A6R7WA01#	
				±0.1pF	GRM0335C2A6R7BA01#	
				±0.25pF	GRM0335C2A6R7CA01#	
				±0.5pF	GRM0335C2A6R7DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	6.8pF	±0.05pF	**GRM0335C2A6R8WA01#**	
				±0.1pF	**GRM0335C2A6R8BA01#**	
				±0.25pF	**GRM0335C2A6R8CA01#**	
				±0.5pF	**GRM0335C2A6R8DA01#**	
			6.9pF	±0.05pF	**GRM0335C2A6R9WA01#**	
				±0.1pF	**GRM0335C2A6R9BA01#**	
				±0.25pF	**GRM0335C2A6R9CA01#**	
				±0.5pF	**GRM0335C2A6R9DA01#**	
			7.0pF	±0.05pF	**GRM0335C2A7R0WA01#**	
				±0.1pF	**GRM0335C2A7R0BA01#**	
				±0.25pF	**GRM0335C2A7R0CA01#**	
				±0.5pF	**GRM0335C2A7R0DA01#**	
			7.1pF	±0.05pF	**GRM0335C2A7R1WA01#**	
				±0.1pF	**GRM0335C2A7R1BA01#**	
				±0.25pF	**GRM0335C2A7R1CA01#**	
				±0.5pF	**GRM0335C2A7R1DA01#**	
			7.2pF	±0.05pF	**GRM0335C2A7R2WA01#**	
				±0.1pF	**GRM0335C2A7R2BA01#**	
				±0.25pF	**GRM0335C2A7R2CA01#**	
				±0.5pF	**GRM0335C2A7R2DA01#**	
			7.3pF	±0.05pF	**GRM0335C2A7R3WA01#**	
				±0.1pF	**GRM0335C2A7R3BA01#**	
				±0.25pF	**GRM0335C2A7R3CA01#**	
				±0.5pF	**GRM0335C2A7R3DA01#**	
			7.4pF	±0.05pF	**GRM0335C2A7R4WA01#**	
				±0.1pF	**GRM0335C2A7R4BA01#**	
				±0.25pF	**GRM0335C2A7R4CA01#**	
				±0.5pF	**GRM0335C2A7R4DA01#**	
			7.5pF	±0.05pF	**GRM0335C2A7R5WA01#**	
				±0.1pF	**GRM0335C2A7R5BA01#**	
				±0.25pF	**GRM0335C2A7R5CA01#**	
				±0.5pF	**GRM0335C2A7R5DA01#**	
			7.6pF	±0.05pF	**GRM0335C2A7R6WA01#**	
				±0.1pF	**GRM0335C2A7R6BA01#**	
				±0.25pF	**GRM0335C2A7R6CA01#**	
				±0.5pF	**GRM0335C2A7R6DA01#**	
			7.7pF	±0.05pF	**GRM0335C2A7R7WA01#**	
				±0.1pF	**GRM0335C2A7R7BA01#**	
				±0.25pF	**GRM0335C2A7R7CA01#**	
				±0.5pF	**GRM0335C2A7R7DA01#**	
			7.8pF	±0.05pF	**GRM0335C2A7R8WA01#**	
				±0.1pF	**GRM0335C2A7R8BA01#**	
				±0.25pF	**GRM0335C2A7R8CA01#**	
				±0.5pF	**GRM0335C2A7R8DA01#**	
			7.9pF	±0.05pF	**GRM0335C2A7R9WA01#**	
				±0.1pF	**GRM0335C2A7R9BA01#**	
				±0.25pF	**GRM0335C2A7R9CA01#**	
				±0.5pF	**GRM0335C2A7R9DA01#**	
			8.0pF	±0.05pF	**GRM0335C2A8R0WA01#**	
				±0.1pF	**GRM0335C2A8R0BA01#**	
				±0.25pF	**GRM0335C2A8R0CA01#**	
				±0.5pF	**GRM0335C2A8R0DA01#**	
			8.1pF	±0.05pF	**GRM0335C2A8R1WA01#**	
				±0.1pF	**GRM0335C2A8R1BA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	8.1pF	±0.25pF	**GRM0335C2A8R1CA01#**	
				±0.5pF	**GRM0335C2A8R1DA01#**	
			8.2pF	±0.05pF	**GRM0335C2A8R2WA01#**	
				±0.1pF	**GRM0335C2A8R2BA01#**	
				±0.25pF	**GRM0335C2A8R2CA01#**	
				±0.5pF	**GRM0335C2A8R2DA01#**	
			8.3pF	±0.05pF	**GRM0335C2A8R3WA01#**	
				±0.1pF	**GRM0335C2A8R3BA01#**	
				±0.25pF	**GRM0335C2A8R3CA01#**	
				±0.5pF	**GRM0335C2A8R3DA01#**	
			8.4pF	±0.05pF	**GRM0335C2A8R4WA01#**	
				±0.1pF	**GRM0335C2A8R4BA01#**	
				±0.25pF	**GRM0335C2A8R4CA01#**	
				±0.5pF	**GRM0335C2A8R4DA01#**	
			8.5pF	±0.05pF	**GRM0335C2A8R5WA01#**	
				±0.1pF	**GRM0335C2A8R5BA01#**	
				±0.25pF	**GRM0335C2A8R5CA01#**	
				±0.5pF	**GRM0335C2A8R5DA01#**	
			8.6pF	±0.05pF	**GRM0335C2A8R6WA01#**	
				±0.1pF	**GRM0335C2A8R6BA01#**	
				±0.25pF	**GRM0335C2A8R6CA01#**	
				±0.5pF	**GRM0335C2A8R6DA01#**	
			8.7pF	±0.05pF	**GRM0335C2A8R7WA01#**	
				±0.1pF	**GRM0335C2A8R7BA01#**	
				±0.25pF	**GRM0335C2A8R7CA01#**	
				±0.5pF	**GRM0335C2A8R7DA01#**	
			8.8pF	±0.05pF	**GRM0335C2A8R8WA01#**	
				±0.1pF	**GRM0335C2A8R8BA01#**	
				±0.25pF	**GRM0335C2A8R8CA01#**	
				±0.5pF	**GRM0335C2A8R8DA01#**	
			8.9pF	±0.05pF	**GRM0335C2A8R9WA01#**	
				±0.1pF	**GRM0335C2A8R9BA01#**	
				±0.25pF	**GRM0335C2A8R9CA01#**	
				±0.5pF	**GRM0335C2A8R9DA01#**	
			9.0pF	±0.05pF	**GRM0335C2A9R0WA01#**	
				±0.1pF	**GRM0335C2A9R0BA01#**	
				±0.25pF	**GRM0335C2A9R0CA01#**	
				±0.5pF	**GRM0335C2A9R0DA01#**	
			9.1pF	±0.05pF	**GRM0335C2A9R1WA01#**	
				±0.1pF	**GRM0335C2A9R1BA01#**	
				±0.25pF	**GRM0335C2A9R1CA01#**	
				±0.5pF	**GRM0335C2A9R1DA01#**	
			9.2pF	±0.05pF	**GRM0335C2A9R2WA01#**	
				±0.1pF	**GRM0335C2A9R2BA01#**	
				±0.25pF	**GRM0335C2A9R2CA01#**	
				±0.5pF	**GRM0335C2A9R2DA01#**	
			9.3pF	±0.05pF	**GRM0335C2A9R3WA01#**	
				±0.1pF	**GRM0335C2A9R3BA01#**	
				±0.25pF	**GRM0335C2A9R3CA01#**	
				±0.5pF	**GRM0335C2A9R3DA01#**	
			9.4pF	±0.05pF	**GRM0335C2A9R4WA01#**	
				±0.1pF	**GRM0335C2A9R4BA01#**	
				±0.25pF	**GRM0335C2A9R4CA01#**	
				±0.5pF	**GRM0335C2A9R4DA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	9.5pF	±0.05pF	GRM0335C2A9R5WA01#	
				±0.1pF	GRM0335C2A9R5BA01#	
				±0.25pF	GRM0335C2A9R5CA01#	
				±0.5pF	GRM0335C2A9R5DA01#	
			9.6pF	±0.05pF	GRM0335C2A9R6WA01#	
				±0.1pF	GRM0335C2A9R6BA01#	
				±0.25pF	GRM0335C2A9R6CA01#	
				±0.5pF	GRM0335C2A9R6DA01#	
			9.7pF	±0.05pF	GRM0335C2A9R7WA01#	
				±0.1pF	GRM0335C2A9R7BA01#	
				±0.25pF	GRM0335C2A9R7CA01#	
				±0.5pF	GRM0335C2A9R7DA01#	
			9.8pF	±0.05pF	GRM0335C2A9R8WA01#	
				±0.1pF	GRM0335C2A9R8BA01#	
				±0.25pF	GRM0335C2A9R8CA01#	
				±0.5pF	GRM0335C2A9R8DA01#	
			9.9pF	±0.05pF	GRM0335C2A9R9WA01#	
				±0.1pF	GRM0335C2A9R9BA01#	
				±0.25pF	GRM0335C2A9R9CA01#	
				±0.5pF	GRM0335C2A9R9DA01#	
			10pF	±2%	GRM0335C2A100GA01#	
				±5%	GRM0335C2A100JA01#	
			12pF	±2%	GRM0335C2A120GA01#	
				±5%	GRM0335C2A120JA01#	
			15pF	±2%	GRM0335C2A150GA01#	
				±5%	GRM0335C2A150JA01#	
			18pF	±2%	GRM0335C2A180GA01#	
				±5%	GRM0335C2A180JA01#	
			20pF	±2%	GRM0335C2A200GA01#	
				±5%	GRM0335C2A200JA01#	
			22pF	±2%	GRM0335C2A220GA01#	
				±5%	GRM0335C2A220JA01#	
			24pF	±2%	GRM0335C2A240GA01#	
				±5%	GRM0335C2A240JA01#	
			27pF	±2%	GRM0335C2A270GA01#	
				±5%	GRM0335C2A270JA01#	
			30pF	±2%	GRM0335C2A300GA01#	
				±5%	GRM0335C2A300JA01#	
			33pF	±2%	GRM0335C2A330GA01#	
				±5%	GRM0335C2A330JA01#	
			36pF	±2%	GRM0335C2A360GA01#	
				±5%	GRM0335C2A360JA01#	
			39pF	±2%	GRM0335C2A390GA01#	
				±5%	GRM0335C2A390JA01#	
			43pF	±2%	GRM0335C2A430GA01#	
				±5%	GRM0335C2A430JA01#	
			47pF	±2%	GRM0335C2A470GA01#	
				±5%	GRM0335C2A470JA01#	
			51pF	±2%	GRM0335C2A510GA01#	
				±5%	GRM0335C2A510JA01#	
			56pF	±2%	GRM0335C2A560GA01#	
				±5%	GRM0335C2A560JA01#	
			62pF	±2%	GRM0335C2A620GA01#	
				±5%	GRM0335C2A620JA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	C0G	68pF	±2%	GRM0335C2A680GA01#	
				±5%	GRM0335C2A680JA01#	
			75pF	±2%	GRM0335C2A750GA01#	
				±5%	GRM0335C2A750JA01#	
			82pF	±2%	GRM0335C2A820GA01#	
				±5%	GRM0335C2A820JA01#	
			91pF	±2%	GRM0335C2A910GA01#	
				±5%	GRM0335C2A910JA01#	
			100pF	±2%	GRM0335C2A101GA01#	
				±5%	GRM0335C2A101JA01#	
		CK	0.10pF	±0.05pF	GRM0334C2AR10WA01#	
			0.20pF	±0.05pF	GRM0334C2AR20WA01#	
				±0.1pF	GRM0334C2AR20BA01#	
			0.30pF	±0.05pF	GRM0334C2AR30WA01#	
				±0.1pF	GRM0334C2AR30BA01#	
			0.40pF	±0.05pF	GRM0334C2AR40WA01#	
				±0.1pF	GRM0334C2AR40BA01#	
			0.50pF	±0.05pF	GRM0334C2AR50WA01#	
				±0.1pF	GRM0334C2AR50BA01#	
			0.60pF	±0.05pF	GRM0334C2AR60WA01#	
				±0.1pF	GRM0334C2AR60BA01#	
			0.70pF	±0.05pF	GRM0334C2AR70WA01#	
				±0.1pF	GRM0334C2AR70BA01#	
			0.80pF	±0.05pF	GRM0334C2AR80WA01#	
				±0.1pF	GRM0334C2AR80BA01#	
			0.90pF	±0.05pF	GRM0334C2AR90WA01#	
				±0.1pF	GRM0334C2AR90BA01#	
			1.0pF	±0.05pF	GRM0334C2A1R0WA01#	
				±0.1pF	GRM0334C2A1R0BA01#	
				±0.25pF	GRM0334C2A1R0CA01#	
			1.1pF	±0.05pF	GRM0334C2A1R1WA01#	
				±0.1pF	GRM0334C2A1R1BA01#	
				±0.25pF	GRM0334C2A1R1CA01#	
			1.2pF	±0.05pF	GRM0334C2A1R2WA01#	
				±0.1pF	GRM0334C2A1R2BA01#	
				±0.25pF	GRM0334C2A1R2CA01#	
			1.3pF	±0.05pF	GRM0334C2A1R3WA01#	
				±0.1pF	GRM0334C2A1R3BA01#	
				±0.25pF	GRM0334C2A1R3CA01#	
			1.4pF	±0.05pF	GRM0334C2A1R4WA01#	
				±0.1pF	GRM0334C2A1R4BA01#	
				±0.25pF	GRM0334C2A1R4CA01#	
			1.5pF	±0.05pF	GRM0334C2A1R5WA01#	
				±0.1pF	GRM0334C2A1R5BA01#	
				±0.25pF	GRM0334C2A1R5CA01#	
			1.6pF	±0.05pF	GRM0334C2A1R6WA01#	
				±0.1pF	GRM0334C2A1R6BA01#	
				±0.25pF	GRM0334C2A1R6CA01#	
			1.7pF	±0.05pF	GRM0334C2A1R7WA01#	
				±0.1pF	GRM0334C2A1R7BA01#	
				±0.25pF	GRM0334C2A1R7CA01#	
			1.8pF	±0.05pF	GRM0334C2A1R8WA01#	
				±0.1pF	GRM0334C2A1R8BA01#	
				±0.25pF	GRM0334C2A1R8CA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	CK	1.9pF	±0.05pF	GRM0334C2A1R9WA01#	
				±0.1pF	GRM0334C2A1R9BA01#	
				±0.25pF	GRM0334C2A1R9CA01#	
			2.0pF	±0.05pF	GRM0334C2A2R0WA01#	
				±0.1pF	GRM0334C2A2R0BA01#	
				±0.25pF	GRM0334C2A2R0CA01#	
		CJ	2.1pF	±0.05pF	GRM0333C2A2R1WA01#	
				±0.1pF	GRM0333C2A2R1BA01#	
				±0.25pF	GRM0333C2A2R1CA01#	
			2.2pF	±0.05pF	GRM0333C2A2R2WA01#	
				±0.1pF	GRM0333C2A2R2BA01#	
				±0.25pF	GRM0333C2A2R2CA01#	
			2.3pF	±0.05pF	GRM0333C2A2R3WA01#	
				±0.1pF	GRM0333C2A2R3BA01#	
				±0.25pF	GRM0333C2A2R3CA01#	
			2.4pF	±0.05pF	GRM0333C2A2R4WA01#	
				±0.1pF	GRM0333C2A2R4BA01#	
				±0.25pF	GRM0333C2A2R4CA01#	
			2.5pF	±0.05pF	GRM0333C2A2R5WA01#	
				±0.1pF	GRM0333C2A2R5BA01#	
				±0.25pF	GRM0333C2A2R5CA01#	
			2.6pF	±0.05pF	GRM0333C2A2R6WA01#	
				±0.1pF	GRM0333C2A2R6BA01#	
				±0.25pF	GRM0333C2A2R6CA01#	
			2.7pF	±0.05pF	GRM0333C2A2R7WA01#	
				±0.1pF	GRM0333C2A2R7BA01#	
				±0.25pF	GRM0333C2A2R7CA01#	
			2.8pF	±0.05pF	GRM0333C2A2R8WA01#	
				±0.1pF	GRM0333C2A2R8BA01#	
				±0.25pF	GRM0333C2A2R8CA01#	
			2.9pF	±0.05pF	GRM0333C2A2R9WA01#	
				±0.1pF	GRM0333C2A2R9BA01#	
				±0.25pF	GRM0333C2A2R9CA01#	
			3.0pF	±0.05pF	GRM0333C2A3R0WA01#	
				±0.1pF	GRM0333C2A3R0BA01#	
				±0.25pF	GRM0333C2A3R0CA01#	
			3.1pF	±0.05pF	GRM0333C2A3R1WA01#	
				±0.1pF	GRM0333C2A3R1BA01#	
				±0.25pF	GRM0333C2A3R1CA01#	
			3.2pF	±0.05pF	GRM0333C2A3R2WA01#	
				±0.1pF	GRM0333C2A3R2BA01#	
				±0.25pF	GRM0333C2A3R2CA01#	
			3.3pF	±0.05pF	GRM0333C2A3R3WA01#	
				±0.1pF	GRM0333C2A3R3BA01#	
				±0.25pF	GRM0333C2A3R3CA01#	
			3.4pF	±0.05pF	GRM0333C2A3R4WA01#	
				±0.1pF	GRM0333C2A3R4BA01#	
				±0.25pF	GRM0333C2A3R4CA01#	
			3.5pF	±0.05pF	GRM0333C2A3R5WA01#	
				±0.1pF	GRM0333C2A3R5BA01#	
				±0.25pF	GRM0333C2A3R5CA01#	
			3.6pF	±0.05pF	GRM0333C2A3R6WA01#	
				±0.1pF	GRM0333C2A3R6BA01#	
				±0.25pF	GRM0333C2A3R6CA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	CJ	3.7pF	±0.05pF	GRM0333C2A3R7WA01#	
				±0.1pF	GRM0333C2A3R7BA01#	
				±0.25pF	GRM0333C2A3R7CA01#	
			3.8pF	±0.05pF	GRM0333C2A3R8WA01#	
				±0.1pF	GRM0333C2A3R8BA01#	
				±0.25pF	GRM0333C2A3R8CA01#	
			3.9pF	±0.05pF	GRM0333C2A3R9WA01#	
				±0.1pF	GRM0333C2A3R9BA01#	
				±0.25pF	GRM0333C2A3R9CA01#	
		CH	4.0pF	±0.05pF	GRM0332C2A4R0WA01#	
				±0.1pF	GRM0332C2A4R0BA01#	
				±0.25pF	GRM0332C2A4R0CA01#	
			4.1pF	±0.05pF	GRM0332C2A4R1WA01#	
				±0.1pF	GRM0332C2A4R1BA01#	
				±0.25pF	GRM0332C2A4R1CA01#	
			4.2pF	±0.05pF	GRM0332C2A4R2WA01#	
				±0.1pF	GRM0332C2A4R2BA01#	
				±0.25pF	GRM0332C2A4R2CA01#	
			4.3pF	±0.05pF	GRM0332C2A4R3WA01#	
				±0.1pF	GRM0332C2A4R3BA01#	
				±0.25pF	GRM0332C2A4R3CA01#	
			4.4pF	±0.05pF	GRM0332C2A4R4WA01#	
				±0.1pF	GRM0332C2A4R4BA01#	
				±0.25pF	GRM0332C2A4R4CA01#	
			4.5pF	±0.05pF	GRM0332C2A4R5WA01#	
				±0.1pF	GRM0332C2A4R5BA01#	
				±0.25pF	GRM0332C2A4R5CA01#	
			4.6pF	±0.05pF	GRM0332C2A4R6WA01#	
				±0.1pF	GRM0332C2A4R6BA01#	
				±0.25pF	GRM0332C2A4R6CA01#	
			4.7pF	±0.05pF	GRM0332C2A4R7WA01#	
				±0.1pF	GRM0332C2A4R7BA01#	
				±0.25pF	GRM0332C2A4R7CA01#	
			4.8pF	±0.05pF	GRM0332C2A4R8WA01#	
				±0.1pF	GRM0332C2A4R8BA01#	
				±0.25pF	GRM0332C2A4R8CA01#	
			4.9pF	±0.05pF	GRM0332C2A4R9WA01#	
				±0.1pF	GRM0332C2A4R9BA01#	
				±0.25pF	GRM0332C2A4R9CA01#	
			5.0pF	±0.05pF	GRM0332C2A5R0WA01#	
				±0.1pF	GRM0332C2A5R0BA01#	
				±0.25pF	GRM0332C2A5R0CA01#	
			5.1pF	±0.05pF	GRM0332C2A5R1WA01#	
				±0.1pF	GRM0332C2A5R1BA01#	
				±0.25pF	GRM0332C2A5R1CA01#	
				±0.5pF	GRM0332C2A5R1DA01#	
			5.2pF	±0.05pF	GRM0332C2A5R2WA01#	
				±0.1pF	GRM0332C2A5R2BA01#	
				±0.25pF	GRM0332C2A5R2CA01#	
				±0.5pF	GRM0332C2A5R2DA01#	
			5.3pF	±0.05pF	GRM0332C2A5R3WA01#	
				±0.1pF	GRM0332C2A5R3BA01#	
				±0.25pF	GRM0332C2A5R3CA01#	
				±0.5pF	GRM0332C2A5R3DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	CH	5.4pF	±0.05pF	GRM0332C2A5R4WA01#	
				±0.1pF	GRM0332C2A5R4BA01#	
				±0.25pF	GRM0332C2A5R4CA01#	
				±0.5pF	GRM0332C2A5R4DA01#	
			5.5pF	±0.05pF	GRM0332C2A5R5WA01#	
				±0.1pF	GRM0332C2A5R5BA01#	
				±0.25pF	GRM0332C2A5R5CA01#	
				±0.5pF	GRM0332C2A5R5DA01#	
			5.6pF	±0.05pF	GRM0332C2A5R6WA01#	
				±0.1pF	GRM0332C2A5R6BA01#	
				±0.25pF	GRM0332C2A5R6CA01#	
				±0.5pF	GRM0332C2A5R6DA01#	
			5.7pF	±0.05pF	GRM0332C2A5R7WA01#	
				±0.1pF	GRM0332C2A5R7BA01#	
				±0.25pF	GRM0332C2A5R7CA01#	
				±0.5pF	GRM0332C2A5R7DA01#	
			5.8pF	±0.05pF	GRM0332C2A5R8WA01#	
				±0.1pF	GRM0332C2A5R8BA01#	
				±0.25pF	GRM0332C2A5R8CA01#	
				±0.5pF	GRM0332C2A5R8DA01#	
			5.9pF	±0.05pF	GRM0332C2A5R9WA01#	
				±0.1pF	GRM0332C2A5R9BA01#	
				±0.25pF	GRM0332C2A5R9CA01#	
				±0.5pF	GRM0332C2A5R9DA01#	
			6.0pF	±0.05pF	GRM0332C2A6R0WA01#	
				±0.1pF	GRM0332C2A6R0BA01#	
				±0.25pF	GRM0332C2A6R0CA01#	
				±0.5pF	GRM0332C2A6R0DA01#	
			6.1pF	±0.05pF	GRM0332C2A6R1WA01#	
				±0.1pF	GRM0332C2A6R1BA01#	
				±0.25pF	GRM0332C2A6R1CA01#	
				±0.5pF	GRM0332C2A6R1DA01#	
			6.2pF	±0.05pF	GRM0332C2A6R2WA01#	
				±0.1pF	GRM0332C2A6R2BA01#	
				±0.25pF	GRM0332C2A6R2CA01#	
				±0.5pF	GRM0332C2A6R2DA01#	
			6.3pF	±0.05pF	GRM0332C2A6R3WA01#	
				±0.1pF	GRM0332C2A6R3BA01#	
				±0.25pF	GRM0332C2A6R3CA01#	
				±0.5pF	GRM0332C2A6R3DA01#	
			6.4pF	±0.05pF	GRM0332C2A6R4WA01#	
				±0.1pF	GRM0332C2A6R4BA01#	
				±0.25pF	GRM0332C2A6R4CA01#	
				±0.5pF	GRM0332C2A6R4DA01#	
			6.5pF	±0.05pF	GRM0332C2A6R5WA01#	
				±0.1pF	GRM0332C2A6R5BA01#	
				±0.25pF	GRM0332C2A6R5CA01#	
				±0.5pF	GRM0332C2A6R5DA01#	
			6.6pF	±0.05pF	GRM0332C2A6R6WA01#	
				±0.1pF	GRM0332C2A6R6BA01#	
				±0.25pF	GRM0332C2A6R6CA01#	
				±0.5pF	GRM0332C2A6R6DA01#	
			6.7pF	±0.05pF	GRM0332C2A6R7WA01#	
				±0.1pF	GRM0332C2A6R7BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	CH	6.7pF	±0.25pF	GRM0332C2A6R7CA01#	
				±0.5pF	GRM0332C2A6R7DA01#	
			6.8pF	±0.05pF	GRM0332C2A6R8WA01#	
				±0.1pF	GRM0332C2A6R8BA01#	
				±0.25pF	GRM0332C2A6R8CA01#	
				±0.5pF	GRM0332C2A6R8DA01#	
			6.9pF	±0.05pF	GRM0332C2A6R9WA01#	
				±0.1pF	GRM0332C2A6R9BA01#	
				±0.25pF	GRM0332C2A6R9CA01#	
				±0.5pF	GRM0332C2A6R9DA01#	
			7.0pF	±0.05pF	GRM0332C2A7R0WA01#	
				±0.1pF	GRM0332C2A7R0BA01#	
				±0.25pF	GRM0332C2A7R0CA01#	
				±0.5pF	GRM0332C2A7R0DA01#	
			7.1pF	±0.05pF	GRM0332C2A7R1WA01#	
				±0.1pF	GRM0332C2A7R1BA01#	
				±0.25pF	GRM0332C2A7R1CA01#	
				±0.5pF	GRM0332C2A7R1DA01#	
			7.2pF	±0.05pF	GRM0332C2A7R2WA01#	
				±0.1pF	GRM0332C2A7R2BA01#	
				±0.25pF	GRM0332C2A7R2CA01#	
				±0.5pF	GRM0332C2A7R2DA01#	
			7.3pF	±0.05pF	GRM0332C2A7R3WA01#	
				±0.1pF	GRM0332C2A7R3BA01#	
				±0.25pF	GRM0332C2A7R3CA01#	
				±0.5pF	GRM0332C2A7R3DA01#	
			7.4pF	±0.05pF	GRM0332C2A7R4WA01#	
				±0.1pF	GRM0332C2A7R4BA01#	
				±0.25pF	GRM0332C2A7R4CA01#	
				±0.5pF	GRM0332C2A7R4DA01#	
			7.5pF	±0.05pF	GRM0332C2A7R5WA01#	
				±0.1pF	GRM0332C2A7R5BA01#	
				±0.25pF	GRM0332C2A7R5CA01#	
				±0.5pF	GRM0332C2A7R5DA01#	
			7.6pF	±0.05pF	GRM0332C2A7R6WA01#	
				±0.1pF	GRM0332C2A7R6BA01#	
				±0.25pF	GRM0332C2A7R6CA01#	
				±0.5pF	GRM0332C2A7R6DA01#	
			7.7pF	±0.05pF	GRM0332C2A7R7WA01#	
				±0.1pF	GRM0332C2A7R7BA01#	
				±0.25pF	GRM0332C2A7R7CA01#	
				±0.5pF	GRM0332C2A7R7DA01#	
			7.8pF	±0.05pF	GRM0332C2A7R8WA01#	
				±0.1pF	GRM0332C2A7R8BA01#	
				±0.25pF	GRM0332C2A7R8CA01#	
				±0.5pF	GRM0332C2A7R8DA01#	
			7.9pF	±0.05pF	GRM0332C2A7R9WA01#	
				±0.1pF	GRM0332C2A7R9BA01#	
				±0.25pF	GRM0332C2A7R9CA01#	
				±0.5pF	GRM0332C2A7R9DA01#	
			8.0pF	±0.05pF	GRM0332C2A8R0WA01#	
				±0.1pF	GRM0332C2A8R0BA01#	
				±0.25pF	GRM0332C2A8R0CA01#	
				±0.5pF	GRM0332C2A8R0DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	CH	8.1pF	±0.05pF	GRM0332C2A8R1WA01#	
				±0.1pF	GRM0332C2A8R1BA01#	
				±0.25pF	GRM0332C2A8R1CA01#	
				±0.5pF	GRM0332C2A8R1DA01#	
			8.2pF	±0.05pF	GRM0332C2A8R2WA01#	
				±0.1pF	GRM0332C2A8R2BA01#	
				±0.25pF	GRM0332C2A8R2CA01#	
				±0.5pF	GRM0332C2A8R2DA01#	
			8.3pF	±0.05pF	GRM0332C2A8R3WA01#	
				±0.1pF	GRM0332C2A8R3BA01#	
				±0.25pF	GRM0332C2A8R3CA01#	
				±0.5pF	GRM0332C2A8R3DA01#	
			8.4pF	±0.05pF	GRM0332C2A8R4WA01#	
				±0.1pF	GRM0332C2A8R4BA01#	
				±0.25pF	GRM0332C2A8R4CA01#	
				±0.5pF	GRM0332C2A8R4DA01#	
			8.5pF	±0.05pF	GRM0332C2A8R5WA01#	
				±0.1pF	GRM0332C2A8R5BA01#	
				±0.25pF	GRM0332C2A8R5CA01#	
				±0.5pF	GRM0332C2A8R5DA01#	
			8.6pF	±0.05pF	GRM0332C2A8R6WA01#	
				±0.1pF	GRM0332C2A8R6BA01#	
				±0.25pF	GRM0332C2A8R6CA01#	
				±0.5pF	GRM0332C2A8R6DA01#	
			8.7pF	±0.05pF	GRM0332C2A8R7WA01#	
				±0.1pF	GRM0332C2A8R7BA01#	
				±0.25pF	GRM0332C2A8R7CA01#	
				±0.5pF	GRM0332C2A8R7DA01#	
			8.8pF	±0.05pF	GRM0332C2A8R8WA01#	
				±0.1pF	GRM0332C2A8R8BA01#	
				±0.25pF	GRM0332C2A8R8CA01#	
				±0.5pF	GRM0332C2A8R8DA01#	
			8.9pF	±0.05pF	GRM0332C2A8R9WA01#	
				±0.1pF	GRM0332C2A8R9BA01#	
				±0.25pF	GRM0332C2A8R9CA01#	
				±0.5pF	GRM0332C2A8R9DA01#	
			9.0pF	±0.05pF	GRM0332C2A9R0WA01#	
				±0.1pF	GRM0332C2A9R0BA01#	
				±0.25pF	GRM0332C2A9R0CA01#	
				±0.5pF	GRM0332C2A9R0DA01#	
			9.1pF	±0.05pF	GRM0332C2A9R1WA01#	
				±0.1pF	GRM0332C2A9R1BA01#	
				±0.25pF	GRM0332C2A9R1CA01#	
				±0.5pF	GRM0332C2A9R1DA01#	
			9.2pF	±0.05pF	GRM0332C2A9R2WA01#	
				±0.1pF	GRM0332C2A9R2BA01#	
				±0.25pF	GRM0332C2A9R2CA01#	
				±0.5pF	GRM0332C2A9R2DA01#	
			9.3pF	±0.05pF	GRM0332C2A9R3WA01#	
				±0.1pF	GRM0332C2A9R3BA01#	
				±0.25pF	GRM0332C2A9R3CA01#	
				±0.5pF	GRM0332C2A9R3DA01#	
			9.4pF	±0.05pF	GRM0332C2A9R4WA01#	
				±0.1pF	GRM0332C2A9R4BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	CH	9.4pF	±0.25pF	GRM0332C2A9R4CA01#	
				±0.5pF	GRM0332C2A9R4DA01#	
			9.5pF	±0.05pF	GRM0332C2A9R5WA01#	
				±0.1pF	GRM0332C2A9R5BA01#	
				±0.25pF	GRM0332C2A9R5CA01#	
				±0.5pF	GRM0332C2A9R5DA01#	
			9.6pF	±0.05pF	GRM0332C2A9R6WA01#	
				±0.1pF	GRM0332C2A9R6BA01#	
				±0.25pF	GRM0332C2A9R6CA01#	
				±0.5pF	GRM0332C2A9R6DA01#	
			9.7pF	±0.05pF	GRM0332C2A9R7WA01#	
				±0.1pF	GRM0332C2A9R7BA01#	
				±0.25pF	GRM0332C2A9R7CA01#	
				±0.5pF	GRM0332C2A9R7DA01#	
			9.8pF	±0.05pF	GRM0332C2A9R8WA01#	
				±0.1pF	GRM0332C2A9R8BA01#	
				±0.25pF	GRM0332C2A9R8CA01#	
				±0.5pF	GRM0332C2A9R8DA01#	
			9.9pF	±0.05pF	GRM0332C2A9R9WA01#	
				±0.1pF	GRM0332C2A9R9BA01#	
				±0.25pF	GRM0332C2A9R9CA01#	
				±0.5pF	GRM0332C2A9R9DA01#	
			10pF	±2%	GRM0332C2A100GA01#	
				±5%	GRM0332C2A100JA01#	
			12pF	±2%	GRM0332C2A120GA01#	
				±5%	GRM0332C2A120JA01#	
			15pF	±2%	GRM0332C2A150GA01#	
				±5%	GRM0332C2A150JA01#	
			18pF	±2%	GRM0332C2A180GA01#	
				±5%	GRM0332C2A180JA01#	
			20pF	±2%	GRM0332C2A200GA01#	
				±5%	GRM0332C2A200JA01#	
			22pF	±2%	GRM0332C2A220GA01#	
				±5%	GRM0332C2A220JA01#	
			24pF	±2%	GRM0332C2A240GA01#	
				±5%	GRM0332C2A240JA01#	
			27pF	±2%	GRM0332C2A270GA01#	
				±5%	GRM0332C2A270JA01#	
			30pF	±2%	GRM0332C2A300GA01#	
				±5%	GRM0332C2A300JA01#	
			33pF	±2%	GRM0332C2A330GA01#	
				±5%	GRM0332C2A330JA01#	
			36pF	±2%	GRM0332C2A360GA01#	
				±5%	GRM0332C2A360JA01#	
			39pF	±2%	GRM0332C2A390GA01#	
				±5%	GRM0332C2A390JA01#	
			43pF	±2%	GRM0332C2A430GA01#	
				±5%	GRM0332C2A430JA01#	
			47pF	±2%	GRM0332C2A470GA01#	
				±5%	GRM0332C2A470JA01#	
			51pF	±2%	GRM0332C2A510GA01#	
				±5%	GRM0332C2A510JA01#	
			56pF	±2%	GRM0332C2A560GA01#	
				±5%	GRM0332C2A560JA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	100Vdc	CH	62pF	±2%	**GRM0332C2A620GA01#**	
				±5%	**GRM0332C2A620JA01#**	
			68pF	±2%	**GRM0332C2A680GA01#**	
				±5%	**GRM0332C2A680JA01#**	
			75pF	±2%	**GRM0332C2A750GA01#**	
				±5%	**GRM0332C2A750JA01#**	
			82pF	±2%	**GRM0332C2A820GA01#**	
				±5%	**GRM0332C2A820JA01#**	
			91pF	±2%	**GRM0332C2A910GA01#**	
				±5%	**GRM0332C2A910JA01#**	
			100pF	±2%	**GRM0332C2A101GA01#**	
				±5%	**GRM0332C2A101JA01#**	
	50Vdc	C0G	0.10pF	±0.05pF	**GRM0335C1HR10WA01#**	
			0.20pF	±0.05pF	**GRM0335C1HR20WA01#**	
				±0.1pF	**GRM0335C1HR20BA01#**	
			0.30pF	±0.05pF	**GRM0335C1HR30WA01#**	
				±0.1pF	**GRM0335C1HR30BA01#**	
			0.40pF	±0.05pF	**GRM0335C1HR40WA01#**	
				±0.1pF	**GRM0335C1HR40BA01#**	
			0.50pF	±0.05pF	**GRM0335C1HR50WA01#**	
				±0.1pF	**GRM0335C1HR50BA01#**	
			0.60pF	±0.05pF	**GRM0335C1HR60WA01#**	
				±0.1pF	**GRM0335C1HR60BA01#**	
			0.70pF	±0.05pF	**GRM0335C1HR70WA01#**	
				±0.1pF	**GRM0335C1HR70BA01#**	
			0.80pF	±0.05pF	**GRM0335C1HR80WA01#**	
				±0.1pF	**GRM0335C1HR80BA01#**	
			0.90pF	±0.05pF	**GRM0335C1HR90WA01#**	
				±0.1pF	**GRM0335C1HR90BA01#**	
			1.0pF	±0.05pF	**GRM0335C1H1R0WA01#**	
				±0.1pF	**GRM0335C1H1R0BA01#**	
				±0.25pF	**GRM0335C1H1R0CA01#**	
			1.1pF	±0.05pF	**GRM0335C1H1R1WA01#**	
				±0.1pF	**GRM0335C1H1R1BA01#**	
				±0.25pF	**GRM0335C1H1R1CA01#**	
			1.2pF	±0.05pF	**GRM0335C1H1R2WA01#**	
				±0.1pF	**GRM0335C1H1R2BA01#**	
				±0.25pF	**GRM0335C1H1R2CA01#**	
			1.3pF	±0.05pF	**GRM0335C1H1R3WA01#**	
				±0.1pF	**GRM0335C1H1R3BA01#**	
				±0.25pF	**GRM0335C1H1R3CA01#**	
			1.4pF	±0.05pF	**GRM0335C1H1R4WA01#**	
				±0.1pF	**GRM0335C1H1R4BA01#**	
				±0.25pF	**GRM0335C1H1R4CA01#**	
			1.5pF	±0.05pF	**GRM0335C1H1R5WA01#**	
				±0.1pF	**GRM0335C1H1R5BA01#**	
				±0.25pF	**GRM0335C1H1R5CA01#**	
			1.6pF	±0.05pF	**GRM0335C1H1R6WA01#**	
				±0.1pF	**GRM0335C1H1R6BA01#**	
				±0.25pF	**GRM0335C1H1R6CA01#**	
			1.7pF	±0.05pF	**GRM0335C1H1R7WA01#**	
				±0.1pF	**GRM0335C1H1R7BA01#**	
				±0.25pF	**GRM0335C1H1R7CA01#**	
			1.8pF	±0.05pF	**GRM0335C1H1R8WA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	C0G	1.8pF	±0.1pF	**GRM0335C1H1R8BA01#**	
				±0.25pF	**GRM0335C1H1R8CA01#**	
			1.9pF	±0.05pF	**GRM0335C1H1R9WA01#**	
				±0.1pF	**GRM0335C1H1R9BA01#**	
				±0.25pF	**GRM0335C1H1R9CA01#**	
			2.0pF	±0.05pF	**GRM0335C1H2R0WA01#**	
				±0.1pF	**GRM0335C1H2R0BA01#**	
				±0.25pF	**GRM0335C1H2R0CA01#**	
			2.1pF	±0.05pF	**GRM0335C1H2R1WA01#**	
				±0.1pF	**GRM0335C1H2R1BA01#**	
				±0.25pF	**GRM0335C1H2R1CA01#**	
			2.2pF	±0.05pF	**GRM0335C1H2R2WA01#**	
				±0.1pF	**GRM0335C1H2R2BA01#**	
				±0.25pF	**GRM0335C1H2R2CA01#**	
			2.3pF	±0.05pF	**GRM0335C1H2R3WA01#**	
				±0.1pF	**GRM0335C1H2R3BA01#**	
				±0.25pF	**GRM0335C1H2R3CA01#**	
			2.4pF	±0.05pF	**GRM0335C1H2R4WA01#**	
				±0.1pF	**GRM0335C1H2R4BA01#**	
				±0.25pF	**GRM0335C1H2R4CA01#**	
			2.5pF	±0.05pF	**GRM0335C1H2R5WA01#**	
				±0.1pF	**GRM0335C1H2R5BA01#**	
				±0.25pF	**GRM0335C1H2R5CA01#**	
			2.6pF	±0.05pF	**GRM0335C1H2R6WA01#**	
				±0.1pF	**GRM0335C1H2R6BA01#**	
				±0.25pF	**GRM0335C1H2R6CA01#**	
			2.7pF	±0.05pF	**GRM0335C1H2R7WA01#**	
				±0.1pF	**GRM0335C1H2R7BA01#**	
				±0.25pF	**GRM0335C1H2R7CA01#**	
			2.8pF	±0.05pF	**GRM0335C1H2R8WA01#**	
				±0.1pF	**GRM0335C1H2R8BA01#**	
				±0.25pF	**GRM0335C1H2R8CA01#**	
			2.9pF	±0.05pF	**GRM0335C1H2R9WA01#**	
				±0.1pF	**GRM0335C1H2R9BA01#**	
				±0.25pF	**GRM0335C1H2R9CA01#**	
			3.0pF	±0.05pF	**GRM0335C1H3R0WA01#**	
				±0.1pF	**GRM0335C1H3R0BA01#**	
				±0.25pF	**GRM0335C1H3R0CA01#**	
			3.1pF	±0.05pF	**GRM0335C1H3R1WA01#**	
				±0.1pF	**GRM0335C1H3R1BA01#**	
				±0.25pF	**GRM0335C1H3R1CA01#**	
			3.2pF	±0.05pF	**GRM0335C1H3R2WA01#**	
				±0.1pF	**GRM0335C1H3R2BA01#**	
				±0.25pF	**GRM0335C1H3R2CA01#**	
			3.3pF	±0.05pF	**GRM0335C1H3R3WA01#**	
				±0.1pF	**GRM0335C1H3R3BA01#**	
				±0.25pF	**GRM0335C1H3R3CA01#**	
			3.4pF	±0.05pF	**GRM0335C1H3R4WA01#**	
				±0.1pF	**GRM0335C1H3R4BA01#**	
				±0.25pF	**GRM0335C1H3R4CA01#**	
			3.5pF	±0.05pF	**GRM0335C1H3R5WA01#**	
				±0.1pF	**GRM0335C1H3R5BA01#**	
				±0.25pF	**GRM0335C1H3R5CA01#**	
			3.6pF	±0.05pF	**GRM0335C1H3R6WA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	C0G	3.6pF	±0.1pF	GRM0335C1H3R6BA01#	
				±0.25pF	GRM0335C1H3R6CA01#	
			3.7pF	±0.05pF	GRM0335C1H3R7WA01#	
				±0.1pF	GRM0335C1H3R7BA01#	
				±0.25pF	GRM0335C1H3R7CA01#	
			3.8pF	±0.05pF	GRM0335C1H3R8WA01#	
				±0.1pF	GRM0335C1H3R8BA01#	
				±0.25pF	GRM0335C1H3R8CA01#	
			3.9pF	±0.05pF	GRM0335C1H3R9WA01#	
				±0.1pF	GRM0335C1H3R9BA01#	
				±0.25pF	GRM0335C1H3R9CA01#	
			4.0pF	±0.05pF	GRM0335C1H4R0WA01#	
				±0.1pF	GRM0335C1H4R0BA01#	
				±0.25pF	GRM0335C1H4R0CA01#	
			4.1pF	±0.05pF	GRM0335C1H4R1WA01#	
				±0.1pF	GRM0335C1H4R1BA01#	
				±0.25pF	GRM0335C1H4R1CA01#	
			4.2pF	±0.05pF	GRM0335C1H4R2WA01#	
				±0.1pF	GRM0335C1H4R2BA01#	
				±0.25pF	GRM0335C1H4R2CA01#	
			4.3pF	±0.05pF	GRM0335C1H4R3WA01#	
				±0.1pF	GRM0335C1H4R3BA01#	
				±0.25pF	GRM0335C1H4R3CA01#	
			4.4pF	±0.05pF	GRM0335C1H4R4WA01#	
				±0.1pF	GRM0335C1H4R4BA01#	
				±0.25pF	GRM0335C1H4R4CA01#	
			4.5pF	±0.05pF	GRM0335C1H4R5WA01#	
				±0.1pF	GRM0335C1H4R5BA01#	
				±0.25pF	GRM0335C1H4R5CA01#	
			4.6pF	±0.05pF	GRM0335C1H4R6WA01#	
				±0.1pF	GRM0335C1H4R6BA01#	
				±0.25pF	GRM0335C1H4R6CA01#	
			4.7pF	±0.05pF	GRM0335C1H4R7WA01#	
				±0.1pF	GRM0335C1H4R7BA01#	
				±0.25pF	GRM0335C1H4R7CA01#	
			4.8pF	±0.05pF	GRM0335C1H4R8WA01#	
				±0.1pF	GRM0335C1H4R8BA01#	
				±0.25pF	GRM0335C1H4R8CA01#	
			4.9pF	±0.05pF	GRM0335C1H4R9WA01#	
				±0.1pF	GRM0335C1H4R9BA01#	
				±0.25pF	GRM0335C1H4R9CA01#	
			5.0pF	±0.05pF	GRM0335C1H5R0WA01#	
				±0.1pF	GRM0335C1H5R0BA01#	
				±0.25pF	GRM0335C1H5R0CA01#	
			5.1pF	±0.05pF	GRM0335C1H5R1WA01#	
				±0.1pF	GRM0335C1H5R1BA01#	
				±0.25pF	GRM0335C1H5R1CA01#	
				±0.5pF	GRM0335C1H5R1DA01#	
			5.2pF	±0.05pF	GRM0335C1H5R2WA01#	
				±0.1pF	GRM0335C1H5R2BA01#	
				±0.25pF	GRM0335C1H5R2CA01#	
				±0.5pF	GRM0335C1H5R2DA01#	
			5.3pF	±0.05pF	GRM0335C1H5R3WA01#	
				±0.1pF	GRM0335C1H5R3BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	C0G	5.3pF	±0.25pF	GRM0335C1H5R3CA01#	
				±0.5pF	GRM0335C1H5R3DA01#	
			5.4pF	±0.05pF	GRM0335C1H5R4WA01#	
				±0.1pF	GRM0335C1H5R4BA01#	
				±0.25pF	GRM0335C1H5R4CA01#	
				±0.5pF	GRM0335C1H5R4DA01#	
			5.5pF	±0.05pF	GRM0335C1H5R5WA01#	
				±0.1pF	GRM0335C1H5R5BA01#	
				±0.25pF	GRM0335C1H5R5CA01#	
				±0.5pF	GRM0335C1H5R5DA01#	
			5.6pF	±0.05pF	GRM0335C1H5R6WA01#	
				±0.1pF	GRM0335C1H5R6BA01#	
				±0.25pF	GRM0335C1H5R6CA01#	
				±0.5pF	GRM0335C1H5R6DA01#	
			5.7pF	±0.05pF	GRM0335C1H5R7WA01#	
				±0.1pF	GRM0335C1H5R7BA01#	
				±0.25pF	GRM0335C1H5R7CA01#	
				±0.5pF	GRM0335C1H5R7DA01#	
			5.8pF	±0.05pF	GRM0335C1H5R8WA01#	
				±0.1pF	GRM0335C1H5R8BA01#	
				±0.25pF	GRM0335C1H5R8CA01#	
				±0.5pF	GRM0335C1H5R8DA01#	
			5.9pF	±0.05pF	GRM0335C1H5R9WA01#	
				±0.1pF	GRM0335C1H5R9BA01#	
				±0.25pF	GRM0335C1H5R9CA01#	
				±0.5pF	GRM0335C1H5R9DA01#	
			6.0pF	±0.05pF	GRM0335C1H6R0WA01#	
				±0.1pF	GRM0335C1H6R0BA01#	
				±0.25pF	GRM0335C1H6R0CA01#	
				±0.5pF	GRM0335C1H6R0DA01#	
			6.1pF	±0.05pF	GRM0335C1H6R1WA01#	
				±0.1pF	GRM0335C1H6R1BA01#	
				±0.25pF	GRM0335C1H6R1CA01#	
				±0.5pF	GRM0335C1H6R1DA01#	
			6.2pF	±0.05pF	GRM0335C1H6R2WA01#	
				±0.1pF	GRM0335C1H6R2BA01#	
				±0.25pF	GRM0335C1H6R2CA01#	
				±0.5pF	GRM0335C1H6R2DA01#	
			6.3pF	±0.05pF	GRM0335C1H6R3WA01#	
				±0.1pF	GRM0335C1H6R3BA01#	
				±0.25pF	GRM0335C1H6R3CA01#	
				±0.5pF	GRM0335C1H6R3DA01#	
			6.4pF	±0.05pF	GRM0335C1H6R4WA01#	
				±0.1pF	GRM0335C1H6R4BA01#	
				±0.25pF	GRM0335C1H6R4CA01#	
				±0.5pF	GRM0335C1H6R4DA01#	
			6.5pF	±0.05pF	GRM0335C1H6R5WA01#	
				±0.1pF	GRM0335C1H6R5BA01#	
				±0.25pF	GRM0335C1H6R5CA01#	
				±0.5pF	GRM0335C1H6R5DA01#	
			6.6pF	±0.05pF	GRM0335C1H6R6WA01#	
				±0.1pF	GRM0335C1H6R6BA01#	
				±0.25pF	GRM0335C1H6R6CA01#	
				±0.5pF	GRM0335C1H6R6DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	C0G	6.7pF	±0.05pF	GRM0335C1H6R7WA01#	
				±0.1pF	GRM0335C1H6R7BA01#	
				±0.25pF	GRM0335C1H6R7CA01#	
				±0.5pF	GRM0335C1H6R7DA01#	
			6.8pF	±0.05pF	GRM0335C1H6R8WA01#	
				±0.1pF	GRM0335C1H6R8BA01#	
				±0.25pF	GRM0335C1H6R8CA01#	
				±0.5pF	GRM0335C1H6R8DA01#	
			6.9pF	±0.05pF	GRM0335C1H6R9WA01#	
				±0.1pF	GRM0335C1H6R9BA01#	
				±0.25pF	GRM0335C1H6R9CA01#	
				±0.5pF	GRM0335C1H6R9DA01#	
			7.0pF	±0.05pF	GRM0335C1H7R0WA01#	
				±0.1pF	GRM0335C1H7R0BA01#	
				±0.25pF	GRM0335C1H7R0CA01#	
				±0.5pF	GRM0335C1H7R0DA01#	
			7.1pF	±0.05pF	GRM0335C1H7R1WA01#	
				±0.1pF	GRM0335C1H7R1BA01#	
				±0.25pF	GRM0335C1H7R1CA01#	
				±0.5pF	GRM0335C1H7R1DA01#	
			7.2pF	±0.05pF	GRM0335C1H7R2WA01#	
				±0.1pF	GRM0335C1H7R2BA01#	
				±0.25pF	GRM0335C1H7R2CA01#	
				±0.5pF	GRM0335C1H7R2DA01#	
			7.3pF	±0.05pF	GRM0335C1H7R3WA01#	
				±0.1pF	GRM0335C1H7R3BA01#	
				±0.25pF	GRM0335C1H7R3CA01#	
				±0.5pF	GRM0335C1H7R3DA01#	
			7.4pF	±0.05pF	GRM0335C1H7R4WA01#	
				±0.1pF	GRM0335C1H7R4BA01#	
				±0.25pF	GRM0335C1H7R4CA01#	
				±0.5pF	GRM0335C1H7R4DA01#	
			7.5pF	±0.05pF	GRM0335C1H7R5WA01#	
				±0.1pF	GRM0335C1H7R5BA01#	
				±0.25pF	GRM0335C1H7R5CA01#	
				±0.5pF	GRM0335C1H7R5DA01#	
			7.6pF	±0.05pF	GRM0335C1H7R6WA01#	
				±0.1pF	GRM0335C1H7R6BA01#	
				±0.25pF	GRM0335C1H7R6CA01#	
				±0.5pF	GRM0335C1H7R6DA01#	
			7.7pF	±0.05pF	GRM0335C1H7R7WA01#	
				±0.1pF	GRM0335C1H7R7BA01#	
				±0.25pF	GRM0335C1H7R7CA01#	
				±0.5pF	GRM0335C1H7R7DA01#	
			7.8pF	±0.05pF	GRM0335C1H7R8WA01#	
				±0.1pF	GRM0335C1H7R8BA01#	
				±0.25pF	GRM0335C1H7R8CA01#	
				±0.5pF	GRM0335C1H7R8DA01#	
			7.9pF	±0.05pF	GRM0335C1H7R9WA01#	
				±0.1pF	GRM0335C1H7R9BA01#	
				±0.25pF	GRM0335C1H7R9CA01#	
				±0.5pF	GRM0335C1H7R9DA01#	
			8.0pF	±0.05pF	GRM0335C1H8R0WA01#	
				±0.1pF	GRM0335C1H8R0BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	C0G	8.0pF	±0.25pF	GRM0335C1H8R0CA01#	
				±0.5pF	GRM0335C1H8R0DA01#	
			8.1pF	±0.05pF	GRM0335C1H8R1WA01#	
				±0.1pF	GRM0335C1H8R1BA01#	
				±0.25pF	GRM0335C1H8R1CA01#	
				±0.5pF	GRM0335C1H8R1DA01#	
			8.2pF	±0.05pF	GRM0335C1H8R2WA01#	
				±0.1pF	GRM0335C1H8R2BA01#	
				±0.25pF	GRM0335C1H8R2CA01#	
				±0.5pF	GRM0335C1H8R2DA01#	
			8.3pF	±0.05pF	GRM0335C1H8R3WA01#	
				±0.1pF	GRM0335C1H8R3BA01#	
				±0.25pF	GRM0335C1H8R3CA01#	
				±0.5pF	GRM0335C1H8R3DA01#	
			8.4pF	±0.05pF	GRM0335C1H8R4WA01#	
				±0.1pF	GRM0335C1H8R4BA01#	
				±0.25pF	GRM0335C1H8R4CA01#	
				±0.5pF	GRM0335C1H8R4DA01#	
			8.5pF	±0.05pF	GRM0335C1H8R5WA01#	
				±0.1pF	GRM0335C1H8R5BA01#	
				±0.25pF	GRM0335C1H8R5CA01#	
				±0.5pF	GRM0335C1H8R5DA01#	
			8.6pF	±0.05pF	GRM0335C1H8R6WA01#	
				±0.1pF	GRM0335C1H8R6BA01#	
				±0.25pF	GRM0335C1H8R6CA01#	
				±0.5pF	GRM0335C1H8R6DA01#	
			8.7pF	±0.05pF	GRM0335C1H8R7WA01#	
				±0.1pF	GRM0335C1H8R7BA01#	
				±0.25pF	GRM0335C1H8R7CA01#	
				±0.5pF	GRM0335C1H8R7DA01#	
			8.8pF	±0.05pF	GRM0335C1H8R8WA01#	
				±0.1pF	GRM0335C1H8R8BA01#	
				±0.25pF	GRM0335C1H8R8CA01#	
				±0.5pF	GRM0335C1H8R8DA01#	
			8.9pF	±0.05pF	GRM0335C1H8R9WA01#	
				±0.1pF	GRM0335C1H8R9BA01#	
				±0.25pF	GRM0335C1H8R9CA01#	
				±0.5pF	GRM0335C1H8R9DA01#	
			9.0pF	±0.05pF	GRM0335C1H9R0WA01#	
				±0.1pF	GRM0335C1H9R0BA01#	
				±0.25pF	GRM0335C1H9R0CA01#	
				±0.5pF	GRM0335C1H9R0DA01#	
			9.1pF	±0.05pF	GRM0335C1H9R1WA01#	
				±0.1pF	GRM0335C1H9R1BA01#	
				±0.25pF	GRM0335C1H9R1CA01#	
				±0.5pF	GRM0335C1H9R1DA01#	
			9.2pF	±0.05pF	GRM0335C1H9R2WA01#	
				±0.1pF	GRM0335C1H9R2BA01#	
				±0.25pF	GRM0335C1H9R2CA01#	
				±0.5pF	GRM0335C1H9R2DA01#	
			9.3pF	±0.05pF	GRM0335C1H9R3WA01#	
				±0.1pF	GRM0335C1H9R3BA01#	
				±0.25pF	GRM0335C1H9R3CA01#	
				±0.5pF	GRM0335C1H9R3DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	C0G	9.4pF	±0.05pF	GRM0335C1H9R4WA01#	
				±0.1pF	GRM0335C1H9R4BA01#	
				±0.25pF	GRM0335C1H9R4CA01#	
				±0.5pF	GRM0335C1H9R4DA01#	
			9.5pF	±0.05pF	GRM0335C1H9R5WA01#	
				±0.1pF	GRM0335C1H9R5BA01#	
				±0.25pF	GRM0335C1H9R5CA01#	
				±0.5pF	GRM0335C1H9R5DA01#	
			9.6pF	±0.05pF	GRM0335C1H9R6WA01#	
				±0.1pF	GRM0335C1H9R6BA01#	
				±0.25pF	GRM0335C1H9R6CA01#	
				±0.5pF	GRM0335C1H9R6DA01#	
			9.7pF	±0.05pF	GRM0335C1H9R7WA01#	
				±0.1pF	GRM0335C1H9R7BA01#	
				±0.25pF	GRM0335C1H9R7CA01#	
				±0.5pF	GRM0335C1H9R7DA01#	
			9.8pF	±0.05pF	GRM0335C1H9R8WA01#	
				±0.1pF	GRM0335C1H9R8BA01#	
				±0.25pF	GRM0335C1H9R8CA01#	
				±0.5pF	GRM0335C1H9R8DA01#	
			9.9pF	±0.05pF	GRM0335C1H9R9WA01#	
				±0.1pF	GRM0335C1H9R9BA01#	
				±0.25pF	GRM0335C1H9R9CA01#	
				±0.5pF	GRM0335C1H9R9DA01#	
			10pF	±2%	GRM0335C1H100GA01#	
				±5%	GRM0335C1H100JA01#	
			12pF	±2%	GRM0335C1H120GA01#	
				±5%	GRM0335C1H120JA01#	
			15pF	±2%	GRM0335C1H150GA01#	
				±5%	GRM0335C1H150JA01#	
			18pF	±2%	GRM0335C1H180GA01#	
				±5%	GRM0335C1H180JA01#	
			22pF	±2%	GRM0335C1H220GA01#	
				±5%	GRM0335C1H220JA01#	
			27pF	±2%	GRM0335C1H270GA01#	
				±5%	GRM0335C1H270JA01#	
			33pF	±2%	GRM0335C1H330GA01#	
				±5%	GRM0335C1H330JA01#	
			39pF	±2%	GRM0335C1H390GA01#	
				±5%	GRM0335C1H390JA01#	
			47pF	±2%	GRM0335C1H470GA01#	
				±5%	GRM0335C1H470JA01#	
			56pF	±2%	GRM0335C1H560GA01#	
				±5%	GRM0335C1H560JA01#	
			68pF	±2%	GRM0335C1H680GA01#	
				±5%	GRM0335C1H680JA01#	
			82pF	±2%	GRM0335C1H820GA01#	
				±5%	GRM0335C1H820JA01#	
			100pF	±2%	GRM0335C1H101GA01#	
				±5%	GRM0335C1H101JA01#	
			120pF	±2%	GRM0335C1H121GA01#	
				±5%	GRM0335C1H121JA01#	
			150pF	±2%	GRM0335C1H151GA01#	
				±5%	GRM0335C1H151JA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	C0G	180pF	±2%	GRM0335C1H181GA01#	
				±5%	GRM0335C1H181JA01#	
			220pF	±2%	GRM0335C1H221GA01#	
				±5%	GRM0335C1H221JA01#	
		CK	0.10pF	±0.05pF	GRM0334C1HR10WA01#	
			0.20pF	±0.05pF	GRM0334C1HR20WA01#	
				±0.1pF	GRM0334C1HR20BA01#	
			0.30pF	±0.05pF	GRM0334C1HR30WA01#	
				±0.1pF	GRM0334C1HR30BA01#	
			0.40pF	±0.05pF	GRM0334C1HR40WA01#	
				±0.1pF	GRM0334C1HR40BA01#	
			0.50pF	±0.05pF	GRM0334C1HR50WA01#	
				±0.1pF	GRM0334C1HR50BA01#	
			0.60pF	±0.05pF	GRM0334C1HR60WA01#	
				±0.1pF	GRM0334C1HR60BA01#	
			0.70pF	±0.05pF	GRM0334C1HR70WA01#	
				±0.1pF	GRM0334C1HR70BA01#	
			0.80pF	±0.05pF	GRM0334C1HR80WA01#	
				±0.1pF	GRM0334C1HR80BA01#	
			0.90pF	±0.05pF	GRM0334C1HR90WA01#	
				±0.1pF	GRM0334C1HR90BA01#	
			1.0pF	±0.05pF	GRM0334C1H1R0WA01#	
				±0.1pF	GRM0334C1H1R0BA01#	
				±0.25pF	GRM0334C1H1R0CA01#	
			1.1pF	±0.05pF	GRM0334C1H1R1WA01#	
				±0.1pF	GRM0334C1H1R1BA01#	
				±0.25pF	GRM0334C1H1R1CA01#	
			1.2pF	±0.05pF	GRM0334C1H1R2WA01#	
				±0.1pF	GRM0334C1H1R2BA01#	
				±0.25pF	GRM0334C1H1R2CA01#	
			1.3pF	±0.05pF	GRM0334C1H1R3WA01#	
				±0.1pF	GRM0334C1H1R3BA01#	
				±0.25pF	GRM0334C1H1R3CA01#	
			1.4pF	±0.05pF	GRM0334C1H1R4WA01#	
				±0.1pF	GRM0334C1H1R4BA01#	
				±0.25pF	GRM0334C1H1R4CA01#	
			1.5pF	±0.05pF	GRM0334C1H1R5WA01#	
				±0.1pF	GRM0334C1H1R5BA01#	
				±0.25pF	GRM0334C1H1R5CA01#	
			1.6pF	±0.05pF	GRM0334C1H1R6WA01#	
				±0.1pF	GRM0334C1H1R6BA01#	
				±0.25pF	GRM0334C1H1R6CA01#	
			1.7pF	±0.05pF	GRM0334C1H1R7WA01#	
				±0.1pF	GRM0334C1H1R7BA01#	
				±0.25pF	GRM0334C1H1R7CA01#	
			1.8pF	±0.05pF	GRM0334C1H1R8WA01#	
				±0.1pF	GRM0334C1H1R8BA01#	
				±0.25pF	GRM0334C1H1R8CA01#	
			1.9pF	±0.05pF	GRM0334C1H1R9WA01#	
				±0.1pF	GRM0334C1H1R9BA01#	
				±0.25pF	GRM0334C1H1R9CA01#	
			2.0pF	±0.05pF	GRM0334C1H2R0WA01#	
				±0.1pF	GRM0334C1H2R0BA01#	
				±0.25pF	GRM0334C1H2R0CA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	CJ	2.1pF	±0.05pF	GRM0333C1H2R1WA01#	
				±0.1pF	GRM0333C1H2R1BA01#	
				±0.25pF	GRM0333C1H2R1CA01#	
			2.2pF	±0.05pF	GRM0333C1H2R2WA01#	
				±0.1pF	GRM0333C1H2R2BA01#	
				±0.25pF	GRM0333C1H2R2CA01#	
			2.3pF	±0.05pF	GRM0333C1H2R3WA01#	
				±0.1pF	GRM0333C1H2R3BA01#	
				±0.25pF	GRM0333C1H2R3CA01#	
			2.4pF	±0.05pF	GRM0333C1H2R4WA01#	
				±0.1pF	GRM0333C1H2R4BA01#	
				±0.25pF	GRM0333C1H2R4CA01#	
			2.5pF	±0.05pF	GRM0333C1H2R5WA01#	
				±0.1pF	GRM0333C1H2R5BA01#	
				±0.25pF	GRM0333C1H2R5CA01#	
			2.6pF	±0.05pF	GRM0333C1H2R6WA01#	
				±0.1pF	GRM0333C1H2R6BA01#	
				±0.25pF	GRM0333C1H2R6CA01#	
			2.7pF	±0.05pF	GRM0333C1H2R7WA01#	
				±0.1pF	GRM0333C1H2R7BA01#	
				±0.25pF	GRM0333C1H2R7CA01#	
			2.8pF	±0.05pF	GRM0333C1H2R8WA01#	
				±0.1pF	GRM0333C1H2R8BA01#	
				±0.25pF	GRM0333C1H2R8CA01#	
			2.9pF	±0.05pF	GRM0333C1H2R9WA01#	
				±0.1pF	GRM0333C1H2R9BA01#	
				±0.25pF	GRM0333C1H2R9CA01#	
			3.0pF	±0.05pF	GRM0333C1H3R0WA01#	
				±0.1pF	GRM0333C1H3R0BA01#	
				±0.25pF	GRM0333C1H3R0CA01#	
			3.1pF	±0.05pF	GRM0333C1H3R1WA01#	
				±0.1pF	GRM0333C1H3R1BA01#	
				±0.25pF	GRM0333C1H3R1CA01#	
			3.2pF	±0.05pF	GRM0333C1H3R2WA01#	
				±0.1pF	GRM0333C1H3R2BA01#	
				±0.25pF	GRM0333C1H3R2CA01#	
			3.3pF	±0.05pF	GRM0333C1H3R3WA01#	
				±0.1pF	GRM0333C1H3R3BA01#	
				±0.25pF	GRM0333C1H3R3CA01#	
			3.4pF	±0.05pF	GRM0333C1H3R4WA01#	
				±0.1pF	GRM0333C1H3R4BA01#	
				±0.25pF	GRM0333C1H3R4CA01#	
			3.5pF	±0.05pF	GRM0333C1H3R5WA01#	
				±0.1pF	GRM0333C1H3R5BA01#	
				±0.25pF	GRM0333C1H3R5CA01#	
			3.6pF	±0.05pF	GRM0333C1H3R6WA01#	
				±0.1pF	GRM0333C1H3R6BA01#	
				±0.25pF	GRM0333C1H3R6CA01#	
			3.7pF	±0.05pF	GRM0333C1H3R7WA01#	
				±0.1pF	GRM0333C1H3R7BA01#	
				±0.25pF	GRM0333C1H3R7CA01#	
			3.8pF	±0.05pF	GRM0333C1H3R8WA01#	
				±0.1pF	GRM0333C1H3R8BA01#	
				±0.25pF	GRM0333C1H3R8CA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	CJ	3.9pF	±0.05pF	GRM0333C1H3R9WA01#	
				±0.1pF	GRM0333C1H3R9BA01#	
				±0.25pF	GRM0333C1H3R9CA01#	
		CH	4.0pF	±0.05pF	GRM0332C1H4R0WA01#	
				±0.1pF	GRM0332C1H4R0BA01#	
				±0.25pF	GRM0332C1H4R0CA01#	
			4.1pF	±0.05pF	GRM0332C1H4R1WA01#	
				±0.1pF	GRM0332C1H4R1BA01#	
				±0.25pF	GRM0332C1H4R1CA01#	
			4.2pF	±0.05pF	GRM0332C1H4R2WA01#	
				±0.1pF	GRM0332C1H4R2BA01#	
				±0.25pF	GRM0332C1H4R2CA01#	
			4.3pF	±0.05pF	GRM0332C1H4R3WA01#	
				±0.1pF	GRM0332C1H4R3BA01#	
				±0.25pF	GRM0332C1H4R3CA01#	
			4.4pF	±0.05pF	GRM0332C1H4R4WA01#	
				±0.1pF	GRM0332C1H4R4BA01#	
				±0.25pF	GRM0332C1H4R4CA01#	
			4.5pF	±0.05pF	GRM0332C1H4R5WA01#	
				±0.1pF	GRM0332C1H4R5BA01#	
				±0.25pF	GRM0332C1H4R5CA01#	
			4.6pF	±0.05pF	GRM0332C1H4R6WA01#	
				±0.1pF	GRM0332C1H4R6BA01#	
				±0.25pF	GRM0332C1H4R6CA01#	
			4.7pF	±0.05pF	GRM0332C1H4R7WA01#	
				±0.1pF	GRM0332C1H4R7BA01#	
				±0.25pF	GRM0332C1H4R7CA01#	
			4.8pF	±0.05pF	GRM0332C1H4R8WA01#	
				±0.1pF	GRM0332C1H4R8BA01#	
				±0.25pF	GRM0332C1H4R8CA01#	
			4.9pF	±0.05pF	GRM0332C1H4R9WA01#	
				±0.1pF	GRM0332C1H4R9BA01#	
				±0.25pF	GRM0332C1H4R9CA01#	
			5.0pF	±0.05pF	GRM0332C1H5R0WA01#	
				±0.1pF	GRM0332C1H5R0BA01#	
				±0.25pF	GRM0332C1H5R0CA01#	
			5.1pF	±0.05pF	GRM0332C1H5R1WA01#	
				±0.1pF	GRM0332C1H5R1BA01#	
				±0.25pF	GRM0332C1H5R1CA01#	
				±0.5pF	GRM0332C1H5R1DA01#	
			5.2pF	±0.05pF	GRM0332C1H5R2WA01#	
				±0.1pF	GRM0332C1H5R2BA01#	
				±0.25pF	GRM0332C1H5R2CA01#	
				±0.5pF	GRM0332C1H5R2DA01#	
			5.3pF	±0.05pF	GRM0332C1H5R3WA01#	
				±0.1pF	GRM0332C1H5R3BA01#	
				±0.25pF	GRM0332C1H5R3CA01#	
				±0.5pF	GRM0332C1H5R3DA01#	
			5.4pF	±0.05pF	GRM0332C1H5R4WA01#	
				±0.1pF	GRM0332C1H5R4BA01#	
				±0.25pF	GRM0332C1H5R4CA01#	
				±0.5pF	GRM0332C1H5R4DA01#	
			5.5pF	±0.05pF	GRM0332C1H5R5WA01#	
				±0.1pF	GRM0332C1H5R5BA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	CH	5.5pF	±0.25pF	GRM0332C1H5R5CA01#	
				±0.5pF	GRM0332C1H5R5DA01#	
			5.6pF	±0.05pF	GRM0332C1H5R6WA01#	
				±0.1pF	GRM0332C1H5R6BA01#	
				±0.25pF	GRM0332C1H5R6CA01#	
				±0.5pF	GRM0332C1H5R6DA01#	
			5.7pF	±0.05pF	GRM0332C1H5R7WA01#	
				±0.1pF	GRM0332C1H5R7BA01#	
				±0.25pF	GRM0332C1H5R7CA01#	
				±0.5pF	GRM0332C1H5R7DA01#	
			5.8pF	±0.05pF	GRM0332C1H5R8WA01#	
				±0.1pF	GRM0332C1H5R8BA01#	
				±0.25pF	GRM0332C1H5R8CA01#	
				±0.5pF	GRM0332C1H5R8DA01#	
			5.9pF	±0.05pF	GRM0332C1H5R9WA01#	
				±0.1pF	GRM0332C1H5R9BA01#	
				±0.25pF	GRM0332C1H5R9CA01#	
				±0.5pF	GRM0332C1H5R9DA01#	
			6.0pF	±0.05pF	GRM0332C1H6R0WA01#	
				±0.1pF	GRM0332C1H6R0BA01#	
				±0.25pF	GRM0332C1H6R0CA01#	
				±0.5pF	GRM0332C1H6R0DA01#	
			6.1pF	±0.05pF	GRM0332C1H6R1WA01#	
				±0.1pF	GRM0332C1H6R1BA01#	
				±0.25pF	GRM0332C1H6R1CA01#	
				±0.5pF	GRM0332C1H6R1DA01#	
			6.2pF	±0.05pF	GRM0332C1H6R2WA01#	
				±0.1pF	GRM0332C1H6R2BA01#	
				±0.25pF	GRM0332C1H6R2CA01#	
				±0.5pF	GRM0332C1H6R2DA01#	
			6.3pF	±0.05pF	GRM0332C1H6R3WA01#	
				±0.1pF	GRM0332C1H6R3BA01#	
				±0.25pF	GRM0332C1H6R3CA01#	
				±0.5pF	GRM0332C1H6R3DA01#	
			6.4pF	±0.05pF	GRM0332C1H6R4WA01#	
				±0.1pF	GRM0332C1H6R4BA01#	
				±0.25pF	GRM0332C1H6R4CA01#	
				±0.5pF	GRM0332C1H6R4DA01#	
			6.5pF	±0.05pF	GRM0332C1H6R5WA01#	
				±0.1pF	GRM0332C1H6R5BA01#	
				±0.25pF	GRM0332C1H6R5CA01#	
				±0.5pF	GRM0332C1H6R5DA01#	
			6.6pF	±0.05pF	GRM0332C1H6R6WA01#	
				±0.1pF	GRM0332C1H6R6BA01#	
				±0.25pF	GRM0332C1H6R6CA01#	
				±0.5pF	GRM0332C1H6R6DA01#	
			6.7pF	±0.05pF	GRM0332C1H6R7WA01#	
				±0.1pF	GRM0332C1H6R7BA01#	
				±0.25pF	GRM0332C1H6R7CA01#	
				±0.5pF	GRM0332C1H6R7DA01#	
			6.8pF	±0.05pF	GRM0332C1H6R8WA01#	
				±0.1pF	GRM0332C1H6R8BA01#	
				±0.25pF	GRM0332C1H6R8CA01#	
				±0.5pF	GRM0332C1H6R8DA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	CH	6.9pF	±0.05pF	GRM0332C1H6R9WA01#	
				±0.1pF	GRM0332C1H6R9BA01#	
				±0.25pF	GRM0332C1H6R9CA01#	
				±0.5pF	GRM0332C1H6R9DA01#	
			7.0pF	±0.05pF	GRM0332C1H7R0WA01#	
				±0.1pF	GRM0332C1H7R0BA01#	
				±0.25pF	GRM0332C1H7R0CA01#	
				±0.5pF	GRM0332C1H7R0DA01#	
			7.1pF	±0.05pF	GRM0332C1H7R1WA01#	
				±0.1pF	GRM0332C1H7R1BA01#	
				±0.25pF	GRM0332C1H7R1CA01#	
				±0.5pF	GRM0332C1H7R1DA01#	
			7.2pF	±0.05pF	GRM0332C1H7R2WA01#	
				±0.1pF	GRM0332C1H7R2BA01#	
				±0.25pF	GRM0332C1H7R2CA01#	
				±0.5pF	GRM0332C1H7R2DA01#	
			7.3pF	±0.05pF	GRM0332C1H7R3WA01#	
				±0.1pF	GRM0332C1H7R3BA01#	
				±0.25pF	GRM0332C1H7R3CA01#	
				±0.5pF	GRM0332C1H7R3DA01#	
			7.4pF	±0.05pF	GRM0332C1H7R4WA01#	
				±0.1pF	GRM0332C1H7R4BA01#	
				±0.25pF	GRM0332C1H7R4CA01#	
				±0.5pF	GRM0332C1H7R4DA01#	
			7.5pF	±0.05pF	GRM0332C1H7R5WA01#	
				±0.1pF	GRM0332C1H7R5BA01#	
				±0.25pF	GRM0332C1H7R5CA01#	
				±0.5pF	GRM0332C1H7R5DA01#	
			7.6pF	±0.05pF	GRM0332C1H7R6WA01#	
				±0.1pF	GRM0332C1H7R6BA01#	
				±0.25pF	GRM0332C1H7R6CA01#	
				±0.5pF	GRM0332C1H7R6DA01#	
			7.7pF	±0.05pF	GRM0332C1H7R7WA01#	
				±0.1pF	GRM0332C1H7R7BA01#	
				±0.25pF	GRM0332C1H7R7CA01#	
				±0.5pF	GRM0332C1H7R7DA01#	
			7.8pF	±0.05pF	GRM0332C1H7R8WA01#	
				±0.1pF	GRM0332C1H7R8BA01#	
				±0.25pF	GRM0332C1H7R8CA01#	
				±0.5pF	GRM0332C1H7R8DA01#	
			7.9pF	±0.05pF	GRM0332C1H7R9WA01#	
				±0.1pF	GRM0332C1H7R9BA01#	
				±0.25pF	GRM0332C1H7R9CA01#	
				±0.5pF	GRM0332C1H7R9DA01#	
			8.0pF	±0.05pF	GRM0332C1H8R0WA01#	
				±0.1pF	GRM0332C1H8R0BA01#	
				±0.25pF	GRM0332C1H8R0CA01#	
				±0.5pF	GRM0332C1H8R0DA01#	
			8.1pF	±0.05pF	GRM0332C1H8R1WA01#	
				±0.1pF	GRM0332C1H8R1BA01#	
				±0.25pF	GRM0332C1H8R1CA01#	
				±0.5pF	GRM0332C1H8R1DA01#	
			8.2pF	±0.05pF	GRM0332C1H8R2WA01#	
				±0.1pF	GRM0332C1H8R2BA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	CH	8.2pF	±0.25pF	GRM0332C1H8R2CA01#	
				±0.5pF	GRM0332C1H8R2DA01#	
			8.3pF	±0.05pF	GRM0332C1H8R3WA01#	
				±0.1pF	GRM0332C1H8R3BA01#	
				±0.25pF	GRM0332C1H8R3CA01#	
				±0.5pF	GRM0332C1H8R3DA01#	
			8.4pF	±0.05pF	GRM0332C1H8R4WA01#	
				±0.1pF	GRM0332C1H8R4BA01#	
				±0.25pF	GRM0332C1H8R4CA01#	
				±0.5pF	GRM0332C1H8R4DA01#	
			8.5pF	±0.05pF	GRM0332C1H8R5WA01#	
				±0.1pF	GRM0332C1H8R5BA01#	
				±0.25pF	GRM0332C1H8R5CA01#	
				±0.5pF	GRM0332C1H8R5DA01#	
			8.6pF	±0.05pF	GRM0332C1H8R6WA01#	
				±0.1pF	GRM0332C1H8R6BA01#	
				±0.25pF	GRM0332C1H8R6CA01#	
				±0.5pF	GRM0332C1H8R6DA01#	
			8.7pF	±0.05pF	GRM0332C1H8R7WA01#	
				±0.1pF	GRM0332C1H8R7BA01#	
				±0.25pF	GRM0332C1H8R7CA01#	
				±0.5pF	GRM0332C1H8R7DA01#	
			8.8pF	±0.05pF	GRM0332C1H8R8WA01#	
				±0.1pF	GRM0332C1H8R8BA01#	
				±0.25pF	GRM0332C1H8R8CA01#	
				±0.5pF	GRM0332C1H8R8DA01#	
			8.9pF	±0.05pF	GRM0332C1H8R9WA01#	
				±0.1pF	GRM0332C1H8R9BA01#	
				±0.25pF	GRM0332C1H8R9CA01#	
				±0.5pF	GRM0332C1H8R9DA01#	
			9.0pF	±0.05pF	GRM0332C1H9R0WA01#	
				±0.1pF	GRM0332C1H9R0BA01#	
				±0.25pF	GRM0332C1H9R0CA01#	
				±0.5pF	GRM0332C1H9R0DA01#	
			9.1pF	±0.05pF	GRM0332C1H9R1WA01#	
				±0.1pF	GRM0332C1H9R1BA01#	
				±0.25pF	GRM0332C1H9R1CA01#	
				±0.5pF	GRM0332C1H9R1DA01#	
			9.2pF	±0.05pF	GRM0332C1H9R2WA01#	
				±0.1pF	GRM0332C1H9R2BA01#	
				±0.25pF	GRM0332C1H9R2CA01#	
				±0.5pF	GRM0332C1H9R2DA01#	
			9.3pF	±0.05pF	GRM0332C1H9R3WA01#	
				±0.1pF	GRM0332C1H9R3BA01#	
				±0.25pF	GRM0332C1H9R3CA01#	
				±0.5pF	GRM0332C1H9R3DA01#	
			9.4pF	±0.05pF	GRM0332C1H9R4WA01#	
				±0.1pF	GRM0332C1H9R4BA01#	
				±0.25pF	GRM0332C1H9R4CA01#	
				±0.5pF	GRM0332C1H9R4DA01#	
			9.5pF	±0.05pF	GRM0332C1H9R5WA01#	
				±0.1pF	GRM0332C1H9R5BA01#	
				±0.25pF	GRM0332C1H9R5CA01#	
				±0.5pF	GRM0332C1H9R5DA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	CH	9.6pF	±0.05pF	GRM0332C1H9R6WA01#	
				±0.1pF	GRM0332C1H9R6BA01#	
				±0.25pF	GRM0332C1H9R6CA01#	
				±0.5pF	GRM0332C1H9R6DA01#	
			9.7pF	±0.05pF	GRM0332C1H9R7WA01#	
				±0.1pF	GRM0332C1H9R7BA01#	
				±0.25pF	GRM0332C1H9R7CA01#	
				±0.5pF	GRM0332C1H9R7DA01#	
			9.8pF	±0.05pF	GRM0332C1H9R8WA01#	
				±0.1pF	GRM0332C1H9R8BA01#	
				±0.25pF	GRM0332C1H9R8CA01#	
				±0.5pF	GRM0332C1H9R8DA01#	
			9.9pF	±0.05pF	GRM0332C1H9R9WA01#	
				±0.1pF	GRM0332C1H9R9BA01#	
				±0.25pF	GRM0332C1H9R9CA01#	
				±0.5pF	GRM0332C1H9R9DA01#	
			10pF	±2%	GRM0332C1H100GA01#	
				±5%	GRM0332C1H100JA01#	
			12pF	±2%	GRM0332C1H120GA01#	
				±5%	GRM0332C1H120JA01#	
			15pF	±2%	GRM0332C1H150GA01#	
				±5%	GRM0332C1H150JA01#	
			18pF	±2%	GRM0332C1H180GA01#	
				±5%	GRM0332C1H180JA01#	
			22pF	±2%	GRM0332C1H220GA01#	
				±5%	GRM0332C1H220JA01#	
			27pF	±2%	GRM0332C1H270GA01#	
				±5%	GRM0332C1H270JA01#	
			33pF	±2%	GRM0332C1H330GA01#	
				±5%	GRM0332C1H330JA01#	
			39pF	±2%	GRM0332C1H390GA01#	
				±5%	GRM0332C1H390JA01#	
			47pF	±2%	GRM0332C1H470GA01#	
				±5%	GRM0332C1H470JA01#	
			56pF	±2%	GRM0332C1H560GA01#	
				±5%	GRM0332C1H560JA01#	
			68pF	±2%	GRM0332C1H680GA01#	
				±5%	GRM0332C1H680JA01#	
			82pF	±2%	GRM0332C1H820GA01#	
				±5%	GRM0332C1H820JA01#	
			100pF	±2%	GRM0332C1H101GA01#	
				±5%	GRM0332C1H101JA01#	
			120pF	±2%	GRM0332C1H121GA01#	
				±5%	GRM0332C1H121JA01#	
			150pF	±2%	GRM0332C1H151GA01#	
				±5%	GRM0332C1H151JA01#	
			180pF	±2%	GRM0332C1H181GA01#	
				±5%	GRM0332C1H181JA01#	
			220pF	±2%	GRM0332C1H221GA01#	
				±5%	GRM0332C1H221JA01#	
	25Vdc	C0G	270pF	±2%	GRM0335C1E271GA01#	
				±5%	GRM0335C1E271JA01#	
			330pF	±2%	GRM0335C1E331GA01#	
				±5%	GRM0335C1E331JA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	25Vdc	C0G	390pF	±2%	GRM0335C1E391GA01#	
				±5%	GRM0335C1E391JA01#	
			470pF	±2%	GRM0335C1E471GA01#	
				±5%	GRM0335C1E471JA01#	
			560pF	±2%	GRM0335C1E561GA01#	
				±5%	GRM0335C1E561JA01#	
			680pF	±2%	GRM0335C1E681GA01#	
				±5%	GRM0335C1E681JA01#	
			820pF	±2%	GRM0335C1E821GA01#	
				±5%	GRM0335C1E821JA01#	
			910pF	±2%	GRM0335C1E911GA01#	
				±5%	GRM0335C1E911JA01#	
			1000pF	±2%	GRM0335C1E102GA01#	
				±5%	GRM0335C1E102JA01#	
		CH	270pF	±2%	GRM0332C1E271GA01#	
				±5%	GRM0332C1E271JA01#	
			330pF	±2%	GRM0332C1E331GA01#	
				±5%	GRM0332C1E331JA01#	
			390pF	±2%	GRM0332C1E391GA01#	
				±5%	GRM0332C1E391JA01#	
			470pF	±2%	GRM0332C1E471GA01#	
				±5%	GRM0332C1E471JA01#	
			560pF	±2%	GRM0332C1E561GA01#	
				±5%	GRM0332C1E561JA01#	
			680pF	±2%	GRM0332C1E681GA01#	
				±5%	GRM0332C1E681JA01#	
			820pF	±2%	GRM0332C1E821GA01#	
				±5%	GRM0332C1E821JA01#	
			1000pF	±2%	GRM0332C1E102GA01#	
				±5%	GRM0332C1E102JA01#	

1.0×0.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	0.10pF	±0.05pF	GRM1555C2AR10WA01#	
			0.20pF	±0.05pF	GRM1555C2AR20WA01#	
				±0.1pF	GRM1555C2AR20BA01#	
			0.30pF	±0.05pF	GRM1555C2AR30WA01#	
				±0.1pF	GRM1555C2AR30BA01#	
			0.40pF	±0.05pF	GRM1555C2AR40WA01#	
				±0.1pF	GRM1555C2AR40BA01#	
			0.50pF	±0.05pF	GRM1555C2AR50WA01#	
				±0.1pF	GRM1555C2AR50BA01#	
			0.60pF	±0.05pF	GRM1555C2AR60WA01#	
				±0.1pF	GRM1555C2AR60BA01#	
			0.70pF	±0.05pF	GRM1555C2AR70WA01#	
				±0.1pF	GRM1555C2AR70BA01#	
			0.80pF	±0.05pF	GRM1555C2AR80WA01#	
				±0.1pF	GRM1555C2AR80BA01#	
			0.90pF	±0.05pF	GRM1555C2AR90WA01#	
				±0.1pF	GRM1555C2AR90BA01#	
			1.0pF	±0.05pF	GRM1555C2A1R0WA01#	
				±0.1pF	GRM1555C2A1R0BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	1.0pF	±0.25pF	GRM1555C2A1R0CA01#	
			1.1pF	±0.05pF	GRM1555C2A1R1WA01#	
				±0.1pF	GRM1555C2A1R1BA01#	
				±0.25pF	GRM1555C2A1R1CA01#	
			1.2pF	±0.05pF	GRM1555C2A1R2WA01#	
				±0.1pF	GRM1555C2A1R2BA01#	
				±0.25pF	GRM1555C2A1R2CA01#	
			1.3pF	±0.05pF	GRM1555C2A1R3WA01#	
				±0.1pF	GRM1555C2A1R3BA01#	
				±0.25pF	GRM1555C2A1R3CA01#	
			1.4pF	±0.05pF	GRM1555C2A1R4WA01#	
				±0.1pF	GRM1555C2A1R4BA01#	
				±0.25pF	GRM1555C2A1R4CA01#	
			1.5pF	±0.05pF	GRM1555C2A1R5WA01#	
				±0.1pF	GRM1555C2A1R5BA01#	
				±0.25pF	GRM1555C2A1R5CA01#	
			1.6pF	±0.05pF	GRM1555C2A1R6WA01#	
				±0.1pF	GRM1555C2A1R6BA01#	
				±0.25pF	GRM1555C2A1R6CA01#	
			1.7pF	±0.05pF	GRM1555C2A1R7WA01#	
				±0.1pF	GRM1555C2A1R7BA01#	
				±0.25pF	GRM1555C2A1R7CA01#	
			1.8pF	±0.05pF	GRM1555C2A1R8WA01#	
				±0.1pF	GRM1555C2A1R8BA01#	
				±0.25pF	GRM1555C2A1R8CA01#	
			1.9pF	±0.05pF	GRM1555C2A1R9WA01#	
				±0.1pF	GRM1555C2A1R9BA01#	
				±0.25pF	GRM1555C2A1R9CA01#	
			2.0pF	±0.05pF	GRM1555C2A2R0WA01#	
				±0.1pF	GRM1555C2A2R0BA01#	
				±0.25pF	GRM1555C2A2R0CA01#	
			2.1pF	±0.05pF	GRM1555C2A2R1WA01#	
				±0.1pF	GRM1555C2A2R1BA01#	
				±0.25pF	GRM1555C2A2R1CA01#	
			2.2pF	±0.05pF	GRM1555C2A2R2WA01#	
				±0.1pF	GRM1555C2A2R2BA01#	
				±0.25pF	GRM1555C2A2R2CA01#	
			2.3pF	±0.05pF	GRM1555C2A2R3WA01#	
				±0.1pF	GRM1555C2A2R3BA01#	
				±0.25pF	GRM1555C2A2R3CA01#	
			2.4pF	±0.05pF	GRM1555C2A2R4WA01#	
				±0.1pF	GRM1555C2A2R4BA01#	
				±0.25pF	GRM1555C2A2R4CA01#	
			2.5pF	±0.05pF	GRM1555C2A2R5WA01#	
				±0.1pF	GRM1555C2A2R5BA01#	
				±0.25pF	GRM1555C2A2R5CA01#	
			2.6pF	±0.05pF	GRM1555C2A2R6WA01#	
				±0.1pF	GRM1555C2A2R6BA01#	
				±0.25pF	GRM1555C2A2R6CA01#	
			2.7pF	±0.05pF	GRM1555C2A2R7WA01#	
				±0.1pF	GRM1555C2A2R7BA01#	
				±0.25pF	GRM1555C2A2R7CA01#	
			2.8pF	±0.05pF	GRM1555C2A2R8WA01#	
				±0.1pF	GRM1555C2A2R8BA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	2.8pF	±0.25pF	**GRM1555C2A2R8CA01#**	
			2.9pF	±0.05pF	**GRM1555C2A2R9WA01#**	
				±0.1pF	**GRM1555C2A2R9BA01#**	
				±0.25pF	**GRM1555C2A2R9CA01#**	
			3.0pF	±0.05pF	**GRM1555C2A3R0WA01#**	
				±0.1pF	**GRM1555C2A3R0BA01#**	
				±0.25pF	**GRM1555C2A3R0CA01#**	
			3.1pF	±0.05pF	**GRM1555C2A3R1WA01#**	
				±0.1pF	**GRM1555C2A3R1BA01#**	
				±0.25pF	**GRM1555C2A3R1CA01#**	
			3.2pF	±0.05pF	**GRM1555C2A3R2WA01#**	
				±0.1pF	**GRM1555C2A3R2BA01#**	
				±0.25pF	**GRM1555C2A3R2CA01#**	
			3.3pF	±0.05pF	**GRM1555C2A3R3WA01#**	
				±0.1pF	**GRM1555C2A3R3BA01#**	
				±0.25pF	**GRM1555C2A3R3CA01#**	
			3.4pF	±0.05pF	**GRM1555C2A3R4WA01#**	
				±0.1pF	**GRM1555C2A3R4BA01#**	
				±0.25pF	**GRM1555C2A3R4CA01#**	
			3.5pF	±0.05pF	**GRM1555C2A3R5WA01#**	
				±0.1pF	**GRM1555C2A3R5BA01#**	
				±0.25pF	**GRM1555C2A3R5CA01#**	
			3.6pF	±0.05pF	**GRM1555C2A3R6WA01#**	
				±0.1pF	**GRM1555C2A3R6BA01#**	
				±0.25pF	**GRM1555C2A3R6CA01#**	
			3.7pF	±0.05pF	**GRM1555C2A3R7WA01#**	
				±0.1pF	**GRM1555C2A3R7BA01#**	
				±0.25pF	**GRM1555C2A3R7CA01#**	
			3.8pF	±0.05pF	**GRM1555C2A3R8WA01#**	
				±0.1pF	**GRM1555C2A3R8BA01#**	
				±0.25pF	**GRM1555C2A3R8CA01#**	
			3.9pF	±0.05pF	**GRM1555C2A3R9WA01#**	
				±0.1pF	**GRM1555C2A3R9BA01#**	
				±0.25pF	**GRM1555C2A3R9CA01#**	
			4.0pF	±0.05pF	**GRM1555C2A4R0WA01#**	
				±0.1pF	**GRM1555C2A4R0BA01#**	
				±0.25pF	**GRM1555C2A4R0CA01#**	
			4.1pF	±0.05pF	**GRM1555C2A4R1WA01#**	
				±0.1pF	**GRM1555C2A4R1BA01#**	
				±0.25pF	**GRM1555C2A4R1CA01#**	
			4.2pF	±0.05pF	**GRM1555C2A4R2WA01#**	
				±0.1pF	**GRM1555C2A4R2BA01#**	
				±0.25pF	**GRM1555C2A4R2CA01#**	
			4.3pF	±0.05pF	**GRM1555C2A4R3WA01#**	
				±0.1pF	**GRM1555C2A4R3BA01#**	
				±0.25pF	**GRM1555C2A4R3CA01#**	
			4.4pF	±0.05pF	**GRM1555C2A4R4WA01#**	
				±0.1pF	**GRM1555C2A4R4BA01#**	
				±0.25pF	**GRM1555C2A4R4CA01#**	
			4.5pF	±0.05pF	**GRM1555C2A4R5WA01#**	
				±0.1pF	**GRM1555C2A4R5BA01#**	
				±0.25pF	**GRM1555C2A4R5CA01#**	
			4.6pF	±0.05pF	**GRM1555C2A4R6WA01#**	
				±0.1pF	**GRM1555C2A4R6BA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	4.6pF	±0.25pF	**GRM1555C2A4R6CA01#**	
			4.7pF	±0.05pF	**GRM1555C2A4R7WA01#**	
				±0.1pF	**GRM1555C2A4R7BA01#**	
				±0.25pF	**GRM1555C2A4R7CA01#**	
			4.8pF	±0.05pF	**GRM1555C2A4R8WA01#**	
				±0.1pF	**GRM1555C2A4R8BA01#**	
				±0.25pF	**GRM1555C2A4R8CA01#**	
			4.9pF	±0.05pF	**GRM1555C2A4R9WA01#**	
				±0.1pF	**GRM1555C2A4R9BA01#**	
				±0.25pF	**GRM1555C2A4R9CA01#**	
			5.0pF	±0.05pF	**GRM1555C2A5R0WA01#**	
				±0.1pF	**GRM1555C2A5R0BA01#**	
				±0.25pF	**GRM1555C2A5R0CA01#**	
			5.1pF	±0.05pF	**GRM1555C2A5R1WA01#**	
				±0.1pF	**GRM1555C2A5R1BA01#**	
				±0.25pF	**GRM1555C2A5R1CA01#**	
				±0.5pF	**GRM1555C2A5R1DA01#**	
			5.2pF	±0.05pF	**GRM1555C2A5R2WA01#**	
				±0.1pF	**GRM1555C2A5R2BA01#**	
				±0.25pF	**GRM1555C2A5R2CA01#**	
				±0.5pF	**GRM1555C2A5R2DA01#**	
			5.3pF	±0.05pF	**GRM1555C2A5R3WA01#**	
				±0.1pF	**GRM1555C2A5R3BA01#**	
				±0.25pF	**GRM1555C2A5R3CA01#**	
				±0.5pF	**GRM1555C2A5R3DA01#**	
			5.4pF	±0.05pF	**GRM1555C2A5R4WA01#**	
				±0.1pF	**GRM1555C2A5R4BA01#**	
				±0.25pF	**GRM1555C2A5R4CA01#**	
				±0.5pF	**GRM1555C2A5R4DA01#**	
			5.5pF	±0.05pF	**GRM1555C2A5R5WA01#**	
				±0.1pF	**GRM1555C2A5R5BA01#**	
				±0.25pF	**GRM1555C2A5R5CA01#**	
				±0.5pF	**GRM1555C2A5R5DA01#**	
			5.6pF	±0.05pF	**GRM1555C2A5R6WA01#**	
				±0.1pF	**GRM1555C2A5R6BA01#**	
				±0.25pF	**GRM1555C2A5R6CA01#**	
				±0.5pF	**GRM1555C2A5R6DA01#**	
			5.7pF	±0.05pF	**GRM1555C2A5R7WA01#**	
				±0.1pF	**GRM1555C2A5R7BA01#**	
				±0.25pF	**GRM1555C2A5R7CA01#**	
				±0.5pF	**GRM1555C2A5R7DA01#**	
			5.8pF	±0.05pF	**GRM1555C2A5R8WA01#**	
				±0.1pF	**GRM1555C2A5R8BA01#**	
				±0.25pF	**GRM1555C2A5R8CA01#**	
				±0.5pF	**GRM1555C2A5R8DA01#**	
			5.9pF	±0.05pF	**GRM1555C2A5R9WA01#**	
				±0.1pF	**GRM1555C2A5R9BA01#**	
				±0.25pF	**GRM1555C2A5R9CA01#**	
				±0.5pF	**GRM1555C2A5R9DA01#**	
			6.0pF	±0.05pF	**GRM1555C2A6R0WA01#**	
				±0.1pF	**GRM1555C2A6R0BA01#**	
				±0.25pF	**GRM1555C2A6R0CA01#**	
				±0.5pF	**GRM1555C2A6R0DA01#**	
			6.1pF	±0.05pF	**GRM1555C2A6R1WA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	6.1pF	±0.1pF	GRM1555C2A6R1BA01#	
				±0.25pF	GRM1555C2A6R1CA01#	
				±0.5pF	GRM1555C2A6R1DA01#	
			6.2pF	±0.05pF	GRM1555C2A6R2WA01#	
				±0.1pF	GRM1555C2A6R2BA01#	
				±0.25pF	GRM1555C2A6R2CA01#	
				±0.5pF	GRM1555C2A6R2DA01#	
			6.3pF	±0.05pF	GRM1555C2A6R3WA01#	
				±0.1pF	GRM1555C2A6R3BA01#	
				±0.25pF	GRM1555C2A6R3CA01#	
				±0.5pF	GRM1555C2A6R3DA01#	
			6.4pF	±0.05pF	GRM1555C2A6R4WA01#	
				±0.1pF	GRM1555C2A6R4BA01#	
				±0.25pF	GRM1555C2A6R4CA01#	
				±0.5pF	GRM1555C2A6R4DA01#	
			6.5pF	±0.05pF	GRM1555C2A6R5WA01#	
				±0.1pF	GRM1555C2A6R5BA01#	
				±0.25pF	GRM1555C2A6R5CA01#	
				±0.5pF	GRM1555C2A6R5DA01#	
			6.6pF	±0.05pF	GRM1555C2A6R6WA01#	
				±0.1pF	GRM1555C2A6R6BA01#	
				±0.25pF	GRM1555C2A6R6CA01#	
				±0.5pF	GRM1555C2A6R6DA01#	
			6.7pF	±0.05pF	GRM1555C2A6R7WA01#	
				±0.1pF	GRM1555C2A6R7BA01#	
				±0.25pF	GRM1555C2A6R7CA01#	
				±0.5pF	GRM1555C2A6R7DA01#	
			6.8pF	±0.05pF	GRM1555C2A6R8WA01#	
				±0.1pF	GRM1555C2A6R8BA01#	
				±0.25pF	GRM1555C2A6R8CA01#	
				±0.5pF	GRM1555C2A6R8DA01#	
			6.9pF	±0.05pF	GRM1555C2A6R9WA01#	
				±0.1pF	GRM1555C2A6R9BA01#	
				±0.25pF	GRM1555C2A6R9CA01#	
				±0.5pF	GRM1555C2A6R9DA01#	
			7.0pF	±0.05pF	GRM1555C2A7R0WA01#	
				±0.1pF	GRM1555C2A7R0BA01#	
				±0.25pF	GRM1555C2A7R0CA01#	
				±0.5pF	GRM1555C2A7R0DA01#	
			7.1pF	±0.05pF	GRM1555C2A7R1WA01#	
				±0.1pF	GRM1555C2A7R1BA01#	
				±0.25pF	GRM1555C2A7R1CA01#	
				±0.5pF	GRM1555C2A7R1DA01#	
			7.2pF	±0.05pF	GRM1555C2A7R2WA01#	
				±0.1pF	GRM1555C2A7R2BA01#	
				±0.25pF	GRM1555C2A7R2CA01#	
				±0.5pF	GRM1555C2A7R2DA01#	
			7.3pF	±0.05pF	GRM1555C2A7R3WA01#	
				±0.1pF	GRM1555C2A7R3BA01#	
				±0.25pF	GRM1555C2A7R3CA01#	
				±0.5pF	GRM1555C2A7R3DA01#	
			7.4pF	±0.05pF	GRM1555C2A7R4WA01#	
				±0.1pF	GRM1555C2A7R4BA01#	
				±0.25pF	GRM1555C2A7R4CA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	7.4pF	±0.5pF	GRM1555C2A7R4DA01#	
			7.5pF	±0.05pF	GRM1555C2A7R5WA01#	
				±0.1pF	GRM1555C2A7R5BA01#	
				±0.25pF	GRM1555C2A7R5CA01#	
				±0.5pF	GRM1555C2A7R5DA01#	
			7.6pF	±0.05pF	GRM1555C2A7R6WA01#	
				±0.1pF	GRM1555C2A7R6BA01#	
				±0.25pF	GRM1555C2A7R6CA01#	
				±0.5pF	GRM1555C2A7R6DA01#	
			7.7pF	±0.05pF	GRM1555C2A7R7WA01#	
				±0.1pF	GRM1555C2A7R7BA01#	
				±0.25pF	GRM1555C2A7R7CA01#	
				±0.5pF	GRM1555C2A7R7DA01#	
			7.8pF	±0.05pF	GRM1555C2A7R8WA01#	
				±0.1pF	GRM1555C2A7R8BA01#	
				±0.25pF	GRM1555C2A7R8CA01#	
				±0.5pF	GRM1555C2A7R8DA01#	
			7.9pF	±0.05pF	GRM1555C2A7R9WA01#	
				±0.1pF	GRM1555C2A7R9BA01#	
				±0.25pF	GRM1555C2A7R9CA01#	
				±0.5pF	GRM1555C2A7R9DA01#	
			8.0pF	±0.05pF	GRM1555C2A8R0WA01#	
				±0.1pF	GRM1555C2A8R0BA01#	
				±0.25pF	GRM1555C2A8R0CA01#	
				±0.5pF	GRM1555C2A8R0DA01#	
			8.1pF	±0.05pF	GRM1555C2A8R1WA01#	
				±0.1pF	GRM1555C2A8R1BA01#	
				±0.25pF	GRM1555C2A8R1CA01#	
				±0.5pF	GRM1555C2A8R1DA01#	
			8.2pF	±0.05pF	GRM1555C2A8R2WA01#	
				±0.1pF	GRM1555C2A8R2BA01#	
				±0.25pF	GRM1555C2A8R2CA01#	
				±0.5pF	GRM1555C2A8R2DA01#	
			8.3pF	±0.05pF	GRM1555C2A8R3WA01#	
				±0.1pF	GRM1555C2A8R3BA01#	
				±0.25pF	GRM1555C2A8R3CA01#	
				±0.5pF	GRM1555C2A8R3DA01#	
			8.4pF	±0.05pF	GRM1555C2A8R4WA01#	
				±0.1pF	GRM1555C2A8R4BA01#	
				±0.25pF	GRM1555C2A8R4CA01#	
				±0.5pF	GRM1555C2A8R4DA01#	
			8.5pF	±0.05pF	GRM1555C2A8R5WA01#	
				±0.1pF	GRM1555C2A8R5BA01#	
				±0.25pF	GRM1555C2A8R5CA01#	
				±0.5pF	GRM1555C2A8R5DA01#	
			8.6pF	±0.05pF	GRM1555C2A8R6WA01#	
				±0.1pF	GRM1555C2A8R6BA01#	
				±0.25pF	GRM1555C2A8R6CA01#	
				±0.5pF	GRM1555C2A8R6DA01#	
			8.7pF	±0.05pF	GRM1555C2A8R7WA01#	
				±0.1pF	GRM1555C2A8R7BA01#	
				±0.25pF	GRM1555C2A8R7CA01#	
				±0.5pF	GRM1555C2A8R7DA01#	
			8.8pF	±0.05pF	GRM1555C2A8R8WA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	8.8pF	±0.1pF	GRM1555C2A8R8BA01#	
				±0.25pF	GRM1555C2A8R8CA01#	
				±0.5pF	GRM1555C2A8R8DA01#	
			8.9pF	±0.05pF	GRM1555C2A8R9WA01#	
				±0.1pF	GRM1555C2A8R9BA01#	
				±0.25pF	GRM1555C2A8R9CA01#	
				±0.5pF	GRM1555C2A8R9DA01#	
			9.0pF	±0.05pF	GRM1555C2A9R0WA01#	
				±0.1pF	GRM1555C2A9R0BA01#	
				±0.25pF	GRM1555C2A9R0CA01#	
				±0.5pF	GRM1555C2A9R0DA01#	
			9.1pF	±0.05pF	GRM1555C2A9R1WA01#	
				±0.1pF	GRM1555C2A9R1BA01#	
				±0.25pF	GRM1555C2A9R1CA01#	
				±0.5pF	GRM1555C2A9R1DA01#	
			9.2pF	±0.05pF	GRM1555C2A9R2WA01#	
				±0.1pF	GRM1555C2A9R2BA01#	
				±0.25pF	GRM1555C2A9R2CA01#	
				±0.5pF	GRM1555C2A9R2DA01#	
			9.3pF	±0.05pF	GRM1555C2A9R3WA01#	
				±0.1pF	GRM1555C2A9R3BA01#	
				±0.25pF	GRM1555C2A9R3CA01#	
				±0.5pF	GRM1555C2A9R3DA01#	
			9.4pF	±0.05pF	GRM1555C2A9R4WA01#	
				±0.1pF	GRM1555C2A9R4BA01#	
				±0.25pF	GRM1555C2A9R4CA01#	
				±0.5pF	GRM1555C2A9R4DA01#	
			9.5pF	±0.05pF	GRM1555C2A9R5WA01#	
				±0.1pF	GRM1555C2A9R5BA01#	
				±0.25pF	GRM1555C2A9R5CA01#	
				±0.5pF	GRM1555C2A9R5DA01#	
			9.6pF	±0.05pF	GRM1555C2A9R6WA01#	
				±0.1pF	GRM1555C2A9R6BA01#	
				±0.25pF	GRM1555C2A9R6CA01#	
				±0.5pF	GRM1555C2A9R6DA01#	
			9.7pF	±0.05pF	GRM1555C2A9R7WA01#	
				±0.1pF	GRM1555C2A9R7BA01#	
				±0.25pF	GRM1555C2A9R7CA01#	
				±0.5pF	GRM1555C2A9R7DA01#	
			9.8pF	±0.05pF	GRM1555C2A9R8WA01#	
				±0.1pF	GRM1555C2A9R8BA01#	
				±0.25pF	GRM1555C2A9R8CA01#	
				±0.5pF	GRM1555C2A9R8DA01#	
			9.9pF	±0.05pF	GRM1555C2A9R9WA01#	
				±0.1pF	GRM1555C2A9R9BA01#	
				±0.25pF	GRM1555C2A9R9CA01#	
				±0.5pF	GRM1555C2A9R9DA01#	
			10pF	±2%	GRM1555C2A100GA01#	
				±5%	GRM1555C2A100JA01#	
			12pF	±2%	GRM1555C2A120GA01#	
				±5%	GRM1555C2A120JA01#	
			15pF	±2%	GRM1555C2A150GA01#	
				±5%	GRM1555C2A150JA01#	
			18pF	±2%	GRM1555C2A180GA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	C0G	18pF	±5%	GRM1555C2A180JA01#	
			22pF	±2%	GRM1555C2A220GA01#	
				±5%	GRM1555C2A220JA01#	
			27pF	±2%	GRM1555C2A270GA01#	
				±5%	GRM1555C2A270JA01#	
			33pF	±2%	GRM1555C2A330GA01#	
				±5%	GRM1555C2A330JA01#	
			39pF	±2%	GRM1555C2A390GA01#	
				±5%	GRM1555C2A390JA01#	
			47pF	±2%	GRM1555C2A470GA01#	
				±5%	GRM1555C2A470JA01#	
			56pF	±2%	GRM1555C2A560GA01#	
				±5%	GRM1555C2A560JA01#	
			68pF	±2%	GRM1555C2A680GA01#	
				±5%	GRM1555C2A680JA01#	
			82pF	±2%	GRM1555C2A820GA01#	
				±5%	GRM1555C2A820JA01#	
			100pF	±2%	GRM1555C2A101GA01#	
				±5%	GRM1555C2A101JA01#	
		CK	0.10pF	±0.05pF	GRM1554C2AR10WA01#	
			0.20pF	±0.05pF	GRM1554C2AR20WA01#	
				±0.1pF	GRM1554C2AR20BA01#	
			0.30pF	±0.05pF	GRM1554C2AR30WA01#	
				±0.1pF	GRM1554C2AR30BA01#	
			0.40pF	±0.05pF	GRM1554C2AR40WA01#	
				±0.1pF	GRM1554C2AR40BA01#	
			0.50pF	±0.05pF	GRM1554C2AR50WA01#	
				±0.1pF	GRM1554C2AR50BA01#	
			0.60pF	±0.05pF	GRM1554C2AR60WA01#	
				±0.1pF	GRM1554C2AR60BA01#	
			0.70pF	±0.05pF	GRM1554C2AR70WA01#	
				±0.1pF	GRM1554C2AR70BA01#	
			0.80pF	±0.05pF	GRM1554C2AR80WA01#	
				±0.1pF	GRM1554C2AR80BA01#	
			0.90pF	±0.05pF	GRM1554C2AR90WA01#	
				±0.1pF	GRM1554C2AR90BA01#	
			1.0pF	±0.05pF	GRM1554C2A1R0WA01#	
				±0.1pF	GRM1554C2A1R0BA01#	
				±0.25pF	GRM1554C2A1R0CA01#	
			1.1pF	±0.05pF	GRM1554C2A1R1WA01#	
				±0.1pF	GRM1554C2A1R1BA01#	
				±0.25pF	GRM1554C2A1R1CA01#	
			1.2pF	±0.05pF	GRM1554C2A1R2WA01#	
				±0.1pF	GRM1554C2A1R2BA01#	
				±0.25pF	GRM1554C2A1R2CA01#	
			1.3pF	±0.05pF	GRM1554C2A1R3WA01#	
				±0.1pF	GRM1554C2A1R3BA01#	
				±0.25pF	GRM1554C2A1R3CA01#	
			1.4pF	±0.05pF	GRM1554C2A1R4WA01#	
				±0.1pF	GRM1554C2A1R4BA01#	
				±0.25pF	GRM1554C2A1R4CA01#	
			1.5pF	±0.05pF	GRM1554C2A1R5WA01#	
				±0.1pF	GRM1554C2A1R5BA01#	
				±0.25pF	GRM1554C2A1R5CA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	CK	1.6pF	±0.05pF	GRM1554C2A1R6WA01#	
				±0.1pF	GRM1554C2A1R6BA01#	
				±0.25pF	GRM1554C2A1R6CA01#	
			1.7pF	±0.05pF	GRM1554C2A1R7WA01#	
				±0.1pF	GRM1554C2A1R7BA01#	
				±0.25pF	GRM1554C2A1R7CA01#	
			1.8pF	±0.05pF	GRM1554C2A1R8WA01#	
				±0.1pF	GRM1554C2A1R8BA01#	
				±0.25pF	GRM1554C2A1R8CA01#	
			1.9pF	±0.05pF	GRM1554C2A1R9WA01#	
				±0.1pF	GRM1554C2A1R9BA01#	
				±0.25pF	GRM1554C2A1R9CA01#	
			2.0pF	±0.05pF	GRM1554C2A2R0WA01#	
				±0.1pF	GRM1554C2A2R0BA01#	
				±0.25pF	GRM1554C2A2R0CA01#	
		CJ	2.1pF	±0.05pF	GRM1553C2A2R1WA01#	
				±0.1pF	GRM1553C2A2R1BA01#	
				±0.25pF	GRM1553C2A2R1CA01#	
			2.2pF	±0.05pF	GRM1553C2A2R2WA01#	
				±0.1pF	GRM1553C2A2R2BA01#	
				±0.25pF	GRM1553C2A2R2CA01#	
			2.3pF	±0.05pF	GRM1553C2A2R3WA01#	
				±0.1pF	GRM1553C2A2R3BA01#	
				±0.25pF	GRM1553C2A2R3CA01#	
			2.4pF	±0.05pF	GRM1553C2A2R4WA01#	
				±0.1pF	GRM1553C2A2R4BA01#	
				±0.25pF	GRM1553C2A2R4CA01#	
			2.5pF	±0.05pF	GRM1553C2A2R5WA01#	
				±0.1pF	GRM1553C2A2R5BA01#	
				±0.25pF	GRM1553C2A2R5CA01#	
			2.6pF	±0.05pF	GRM1553C2A2R6WA01#	
				±0.1pF	GRM1553C2A2R6BA01#	
				±0.25pF	GRM1553C2A2R6CA01#	
			2.7pF	±0.05pF	GRM1553C2A2R7WA01#	
				±0.1pF	GRM1553C2A2R7BA01#	
				±0.25pF	GRM1553C2A2R7CA01#	
			2.8pF	±0.05pF	GRM1553C2A2R8WA01#	
				±0.1pF	GRM1553C2A2R8BA01#	
				±0.25pF	GRM1553C2A2R8CA01#	
			2.9pF	±0.05pF	GRM1553C2A2R9WA01#	
				±0.1pF	GRM1553C2A2R9BA01#	
				±0.25pF	GRM1553C2A2R9CA01#	
			3.0pF	±0.05pF	GRM1553C2A3R0WA01#	
				±0.1pF	GRM1553C2A3R0BA01#	
				±0.25pF	GRM1553C2A3R0CA01#	
			3.1pF	±0.05pF	GRM1553C2A3R1WA01#	
				±0.1pF	GRM1553C2A3R1BA01#	
				±0.25pF	GRM1553C2A3R1CA01#	
			3.2pF	±0.05pF	GRM1553C2A3R2WA01#	
				±0.1pF	GRM1553C2A3R2BA01#	
				±0.25pF	GRM1553C2A3R2CA01#	
			3.3pF	±0.05pF	GRM1553C2A3R3WA01#	
				±0.1pF	GRM1553C2A3R3BA01#	
				±0.25pF	GRM1553C2A3R3CA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	CJ	3.4pF	±0.05pF	GRM1553C2A3R4WA01#	
				±0.1pF	GRM1553C2A3R4BA01#	
				±0.25pF	GRM1553C2A3R4CA01#	
			3.5pF	±0.05pF	GRM1553C2A3R5WA01#	
				±0.1pF	GRM1553C2A3R5BA01#	
				±0.25pF	GRM1553C2A3R5CA01#	
			3.6pF	±0.05pF	GRM1553C2A3R6WA01#	
				±0.1pF	GRM1553C2A3R6BA01#	
				±0.25pF	GRM1553C2A3R6CA01#	
			3.7pF	±0.05pF	GRM1553C2A3R7WA01#	
				±0.1pF	GRM1553C2A3R7BA01#	
				±0.25pF	GRM1553C2A3R7CA01#	
			3.8pF	±0.05pF	GRM1553C2A3R8WA01#	
				±0.1pF	GRM1553C2A3R8BA01#	
				±0.25pF	GRM1553C2A3R8CA01#	
			3.9pF	±0.05pF	GRM1553C2A3R9WA01#	
				±0.1pF	GRM1553C2A3R9BA01#	
				±0.25pF	GRM1553C2A3R9CA01#	
		CH	4.0pF	±0.05pF	GRM1552C2A4R0WA01#	
				±0.1pF	GRM1552C2A4R0BA01#	
				±0.25pF	GRM1552C2A4R0CA01#	
			4.1pF	±0.05pF	GRM1552C2A4R1WA01#	
				±0.1pF	GRM1552C2A4R1BA01#	
				±0.25pF	GRM1552C2A4R1CA01#	
			4.2pF	±0.05pF	GRM1552C2A4R2WA01#	
				±0.1pF	GRM1552C2A4R2BA01#	
				±0.25pF	GRM1552C2A4R2CA01#	
			4.3pF	±0.05pF	GRM1552C2A4R3WA01#	
				±0.1pF	GRM1552C2A4R3BA01#	
				±0.25pF	GRM1552C2A4R3CA01#	
			4.4pF	±0.05pF	GRM1552C2A4R4WA01#	
				±0.1pF	GRM1552C2A4R4BA01#	
				±0.25pF	GRM1552C2A4R4CA01#	
			4.5pF	±0.05pF	GRM1552C2A4R5WA01#	
				±0.1pF	GRM1552C2A4R5BA01#	
				±0.25pF	GRM1552C2A4R5CA01#	
			4.6pF	±0.05pF	GRM1552C2A4R6WA01#	
				±0.1pF	GRM1552C2A4R6BA01#	
				±0.25pF	GRM1552C2A4R6CA01#	
			4.7pF	±0.05pF	GRM1552C2A4R7WA01#	
				±0.1pF	GRM1552C2A4R7BA01#	
				±0.25pF	GRM1552C2A4R7CA01#	
			4.8pF	±0.05pF	GRM1552C2A4R8WA01#	
				±0.1pF	GRM1552C2A4R8BA01#	
				±0.25pF	GRM1552C2A4R8CA01#	
			4.9pF	±0.05pF	GRM1552C2A4R9WA01#	
				±0.1pF	GRM1552C2A4R9BA01#	
				±0.25pF	GRM1552C2A4R9CA01#	
			5.0pF	±0.05pF	GRM1552C2A5R0WA01#	
				±0.1pF	GRM1552C2A5R0BA01#	
				±0.25pF	GRM1552C2A5R0CA01#	
			5.1pF	±0.05pF	GRM1552C2A5R1WA01#	
				±0.1pF	GRM1552C2A5R1BA01#	
				±0.25pF	GRM1552C2A5R1CA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	CH	5.1pF	±0.5pF	GRM1552C2A5R1DA01#	
			5.2pF	±0.05pF	GRM1552C2A5R2WA01#	
				±0.1pF	GRM1552C2A5R2BA01#	
				±0.25pF	GRM1552C2A5R2CA01#	
				±0.5pF	GRM1552C2A5R2DA01#	
			5.3pF	±0.05pF	GRM1552C2A5R3WA01#	
				±0.1pF	GRM1552C2A5R3BA01#	
				±0.25pF	GRM1552C2A5R3CA01#	
				±0.5pF	GRM1552C2A5R3DA01#	
			5.4pF	±0.05pF	GRM1552C2A5R4WA01#	
				±0.1pF	GRM1552C2A5R4BA01#	
				±0.25pF	GRM1552C2A5R4CA01#	
				±0.5pF	GRM1552C2A5R4DA01#	
			5.5pF	±0.05pF	GRM1552C2A5R5WA01#	
				±0.1pF	GRM1552C2A5R5BA01#	
				±0.25pF	GRM1552C2A5R5CA01#	
				±0.5pF	GRM1552C2A5R5DA01#	
			5.6pF	±0.05pF	GRM1552C2A5R6WA01#	
				±0.1pF	GRM1552C2A5R6BA01#	
				±0.25pF	GRM1552C2A5R6CA01#	
				±0.5pF	GRM1552C2A5R6DA01#	
			5.7pF	±0.05pF	GRM1552C2A5R7WA01#	
				±0.1pF	GRM1552C2A5R7BA01#	
				±0.25pF	GRM1552C2A5R7CA01#	
				±0.5pF	GRM1552C2A5R7DA01#	
			5.8pF	±0.05pF	GRM1552C2A5R8WA01#	
				±0.1pF	GRM1552C2A5R8BA01#	
				±0.25pF	GRM1552C2A5R8CA01#	
				±0.5pF	GRM1552C2A5R8DA01#	
			5.9pF	±0.05pF	GRM1552C2A5R9WA01#	
				±0.1pF	GRM1552C2A5R9BA01#	
				±0.25pF	GRM1552C2A5R9CA01#	
				±0.5pF	GRM1552C2A5R9DA01#	
			6.0pF	±0.05pF	GRM1552C2A6R0WA01#	
				±0.1pF	GRM1552C2A6R0BA01#	
				±0.25pF	GRM1552C2A6R0CA01#	
				±0.5pF	GRM1552C2A6R0DA01#	
			6.1pF	±0.05pF	GRM1552C2A6R1WA01#	
				±0.1pF	GRM1552C2A6R1BA01#	
				±0.25pF	GRM1552C2A6R1CA01#	
				±0.5pF	GRM1552C2A6R1DA01#	
			6.2pF	±0.05pF	GRM1552C2A6R2WA01#	
				±0.1pF	GRM1552C2A6R2BA01#	
				±0.25pF	GRM1552C2A6R2CA01#	
				±0.5pF	GRM1552C2A6R2DA01#	
			6.3pF	±0.05pF	GRM1552C2A6R3WA01#	
				±0.1pF	GRM1552C2A6R3BA01#	
				±0.25pF	GRM1552C2A6R3CA01#	
				±0.5pF	GRM1552C2A6R3DA01#	
			6.4pF	±0.05pF	GRM1552C2A6R4WA01#	
				±0.1pF	GRM1552C2A6R4BA01#	
				±0.25pF	GRM1552C2A6R4CA01#	
				±0.5pF	GRM1552C2A6R4DA01#	
			6.5pF	±0.05pF	GRM1552C2A6R5WA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	CH	6.5pF	±0.1pF	GRM1552C2A6R5BA01#	
				±0.25pF	GRM1552C2A6R5CA01#	
				±0.5pF	GRM1552C2A6R5DA01#	
			6.6pF	±0.05pF	GRM1552C2A6R6WA01#	
				±0.1pF	GRM1552C2A6R6BA01#	
				±0.25pF	GRM1552C2A6R6CA01#	
				±0.5pF	GRM1552C2A6R6DA01#	
			6.7pF	±0.05pF	GRM1552C2A6R7WA01#	
				±0.1pF	GRM1552C2A6R7BA01#	
				±0.25pF	GRM1552C2A6R7CA01#	
				±0.5pF	GRM1552C2A6R7DA01#	
			6.8pF	±0.05pF	GRM1552C2A6R8WA01#	
				±0.1pF	GRM1552C2A6R8BA01#	
				±0.25pF	GRM1552C2A6R8CA01#	
				±0.5pF	GRM1552C2A6R8DA01#	
			6.9pF	±0.05pF	GRM1552C2A6R9WA01#	
				±0.1pF	GRM1552C2A6R9BA01#	
				±0.25pF	GRM1552C2A6R9CA01#	
				±0.5pF	GRM1552C2A6R9DA01#	
			7.0pF	±0.05pF	GRM1552C2A7R0WA01#	
				±0.1pF	GRM1552C2A7R0BA01#	
				±0.25pF	GRM1552C2A7R0CA01#	
				±0.5pF	GRM1552C2A7R0DA01#	
			7.1pF	±0.05pF	GRM1552C2A7R1WA01#	
				±0.1pF	GRM1552C2A7R1BA01#	
				±0.25pF	GRM1552C2A7R1CA01#	
				±0.5pF	GRM1552C2A7R1DA01#	
			7.2pF	±0.05pF	GRM1552C2A7R2WA01#	
				±0.1pF	GRM1552C2A7R2BA01#	
				±0.25pF	GRM1552C2A7R2CA01#	
				±0.5pF	GRM1552C2A7R2DA01#	
			7.3pF	±0.05pF	GRM1552C2A7R3WA01#	
				±0.1pF	GRM1552C2A7R3BA01#	
				±0.25pF	GRM1552C2A7R3CA01#	
				±0.5pF	GRM1552C2A7R3DA01#	
			7.4pF	±0.05pF	GRM1552C2A7R4WA01#	
				±0.1pF	GRM1552C2A7R4BA01#	
				±0.25pF	GRM1552C2A7R4CA01#	
				±0.5pF	GRM1552C2A7R4DA01#	
			7.5pF	±0.05pF	GRM1552C2A7R5WA01#	
				±0.1pF	GRM1552C2A7R5BA01#	
				±0.25pF	GRM1552C2A7R5CA01#	
				±0.5pF	GRM1552C2A7R5DA01#	
			7.6pF	±0.05pF	GRM1552C2A7R6WA01#	
				±0.1pF	GRM1552C2A7R6BA01#	
				±0.25pF	GRM1552C2A7R6CA01#	
				±0.5pF	GRM1552C2A7R6DA01#	
			7.7pF	±0.05pF	GRM1552C2A7R7WA01#	
				±0.1pF	GRM1552C2A7R7BA01#	
				±0.25pF	GRM1552C2A7R7CA01#	
				±0.5pF	GRM1552C2A7R7DA01#	
			7.8pF	±0.05pF	GRM1552C2A7R8WA01#	
				±0.1pF	GRM1552C2A7R8BA01#	
				±0.25pF	GRM1552C2A7R8CA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	CH	7.8pF	±0.5pF	GRM1552C2A7R8DA01#	
			7.9pF	±0.05pF	GRM1552C2A7R9WA01#	
				±0.1pF	GRM1552C2A7R9BA01#	
				±0.25pF	GRM1552C2A7R9CA01#	
				±0.5pF	GRM1552C2A7R9DA01#	
			8.0pF	±0.05pF	GRM1552C2A8R0WA01#	
				±0.1pF	GRM1552C2A8R0BA01#	
				±0.25pF	GRM1552C2A8R0CA01#	
				±0.5pF	GRM1552C2A8R0DA01#	
			8.1pF	±0.05pF	GRM1552C2A8R1WA01#	
				±0.1pF	GRM1552C2A8R1BA01#	
				±0.25pF	GRM1552C2A8R1CA01#	
				±0.5pF	GRM1552C2A8R1DA01#	
			8.2pF	±0.05pF	GRM1552C2A8R2WA01#	
				±0.1pF	GRM1552C2A8R2BA01#	
				±0.25pF	GRM1552C2A8R2CA01#	
				±0.5pF	GRM1552C2A8R2DA01#	
			8.3pF	±0.05pF	GRM1552C2A8R3WA01#	
				±0.1pF	GRM1552C2A8R3BA01#	
				±0.25pF	GRM1552C2A8R3CA01#	
				±0.5pF	GRM1552C2A8R3DA01#	
			8.4pF	±0.05pF	GRM1552C2A8R4WA01#	
				±0.1pF	GRM1552C2A8R4BA01#	
				±0.25pF	GRM1552C2A8R4CA01#	
				±0.5pF	GRM1552C2A8R4DA01#	
			8.5pF	±0.05pF	GRM1552C2A8R5WA01#	
				±0.1pF	GRM1552C2A8R5BA01#	
				±0.25pF	GRM1552C2A8R5CA01#	
				±0.5pF	GRM1552C2A8R5DA01#	
			8.6pF	±0.05pF	GRM1552C2A8R6WA01#	
				±0.1pF	GRM1552C2A8R6BA01#	
				±0.25pF	GRM1552C2A8R6CA01#	
				±0.5pF	GRM1552C2A8R6DA01#	
			8.7pF	±0.05pF	GRM1552C2A8R7WA01#	
				±0.1pF	GRM1552C2A8R7BA01#	
				±0.25pF	GRM1552C2A8R7CA01#	
				±0.5pF	GRM1552C2A8R7DA01#	
			8.8pF	±0.05pF	GRM1552C2A8R8WA01#	
				±0.1pF	GRM1552C2A8R8BA01#	
				±0.25pF	GRM1552C2A8R8CA01#	
				±0.5pF	GRM1552C2A8R8DA01#	
			8.9pF	±0.05pF	GRM1552C2A8R9WA01#	
				±0.1pF	GRM1552C2A8R9BA01#	
				±0.25pF	GRM1552C2A8R9CA01#	
				±0.5pF	GRM1552C2A8R9DA01#	
			9.0pF	±0.05pF	GRM1552C2A9R0WA01#	
				±0.1pF	GRM1552C2A9R0BA01#	
				±0.25pF	GRM1552C2A9R0CA01#	
				±0.5pF	GRM1552C2A9R0DA01#	
			9.1pF	±0.05pF	GRM1552C2A9R1WA01#	
				±0.1pF	GRM1552C2A9R1BA01#	
				±0.25pF	GRM1552C2A9R1CA01#	
				±0.5pF	GRM1552C2A9R1DA01#	
			9.2pF	±0.05pF	GRM1552C2A9R2WA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	CH	9.2pF	±0.1pF	GRM1552C2A9R2BA01#	
				±0.25pF	GRM1552C2A9R2CA01#	
				±0.5pF	GRM1552C2A9R2DA01#	
			9.3pF	±0.05pF	GRM1552C2A9R3WA01#	
				±0.1pF	GRM1552C2A9R3BA01#	
				±0.25pF	GRM1552C2A9R3CA01#	
				±0.5pF	GRM1552C2A9R3DA01#	
			9.4pF	±0.05pF	GRM1552C2A9R4WA01#	
				±0.1pF	GRM1552C2A9R4BA01#	
				±0.25pF	GRM1552C2A9R4CA01#	
				±0.5pF	GRM1552C2A9R4DA01#	
			9.5pF	±0.05pF	GRM1552C2A9R5WA01#	
				±0.1pF	GRM1552C2A9R5BA01#	
				±0.25pF	GRM1552C2A9R5CA01#	
				±0.5pF	GRM1552C2A9R5DA01#	
			9.6pF	±0.05pF	GRM1552C2A9R6WA01#	
				±0.1pF	GRM1552C2A9R6BA01#	
				±0.25pF	GRM1552C2A9R6CA01#	
				±0.5pF	GRM1552C2A9R6DA01#	
			9.7pF	±0.05pF	GRM1552C2A9R7WA01#	
				±0.1pF	GRM1552C2A9R7BA01#	
				±0.25pF	GRM1552C2A9R7CA01#	
				±0.5pF	GRM1552C2A9R7DA01#	
			9.8pF	±0.05pF	GRM1552C2A9R8WA01#	
				±0.1pF	GRM1552C2A9R8BA01#	
				±0.25pF	GRM1552C2A9R8CA01#	
				±0.5pF	GRM1552C2A9R8DA01#	
			9.9pF	±0.05pF	GRM1552C2A9R9WA01#	
				±0.1pF	GRM1552C2A9R9BA01#	
				±0.25pF	GRM1552C2A9R9CA01#	
				±0.5pF	GRM1552C2A9R9DA01#	
			10pF	±2%	GRM1552C2A100GA01#	
				±5%	GRM1552C2A100JA01#	
			12pF	±2%	GRM1552C2A120GA01#	
				±5%	GRM1552C2A120JA01#	
			15pF	±2%	GRM1552C2A150GA01#	
				±5%	GRM1552C2A150JA01#	
			18pF	±2%	GRM1552C2A180GA01#	
				±5%	GRM1552C2A180JA01#	
			22pF	±2%	GRM1552C2A220GA01#	
				±5%	GRM1552C2A220JA01#	
			27pF	±2%	GRM1552C2A270GA01#	
				±5%	GRM1552C2A270JA01#	
			33pF	±2%	GRM1552C2A330GA01#	
				±5%	GRM1552C2A330JA01#	
			39pF	±2%	GRM1552C2A390GA01#	
				±5%	GRM1552C2A390JA01#	
			47pF	±2%	GRM1552C2A470GA01#	
				±5%	GRM1552C2A470JA01#	
			56pF	±2%	GRM1552C2A560GA01#	
				±5%	GRM1552C2A560JA01#	
			68pF	±2%	GRM1552C2A680GA01#	
				±5%	GRM1552C2A680JA01#	
			82pF	±2%	GRM1552C2A820GA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	100Vdc	CH	82pF	±5%	**GRM1552C2A820JA01#**	
			100pF	±2%	**GRM1552C2A101GA01#**	
				±5%	**GRM1552C2A101JA01#**	
	50Vdc	C0G	0.10pF	±0.05pF	**GRM1555C1HR10WA01#**	
			0.20pF	±0.05pF	**GRM1555C1HR20WA01#**	
				±0.1pF	**GRM1555C1HR20BA01#**	
			0.30pF	±0.05pF	**GRM1555C1HR30WA01#**	
				±0.1pF	**GRM1555C1HR30BA01#**	
			0.40pF	±0.05pF	**GRM1555C1HR40WA01#**	
				±0.1pF	**GRM1555C1HR40BA01#**	
			0.50pF	±0.05pF	**GRM1555C1HR50WA01#**	
				±0.1pF	**GRM1555C1HR50BA01#**	
			0.60pF	±0.05pF	**GRM1555C1HR60WA01#**	
				±0.1pF	**GRM1555C1HR60BA01#**	
			0.70pF	±0.05pF	**GRM1555C1HR70WA01#**	
				±0.1pF	**GRM1555C1HR70BA01#**	
			0.80pF	±0.05pF	**GRM1555C1HR80WA01#**	
				±0.1pF	**GRM1555C1HR80BA01#**	
			0.90pF	±0.05pF	**GRM1555C1HR90WA01#**	
				±0.1pF	**GRM1555C1HR90BA01#**	
			1.0pF	±0.05pF	**GRM1555C1H1R0WA01#**	
				±0.1pF	**GRM1555C1H1R0BA01#**	
				±0.25pF	**GRM1555C1H1R0CA01#**	
			1.1pF	±0.05pF	**GRM1555C1H1R1WA01#**	
				±0.1pF	**GRM1555C1H1R1BA01#**	
				±0.25pF	**GRM1555C1H1R1CA01#**	
			1.2pF	±0.05pF	**GRM1555C1H1R2WA01#**	
				±0.1pF	**GRM1555C1H1R2BA01#**	
				±0.25pF	**GRM1555C1H1R2CA01#**	
			1.3pF	±0.05pF	**GRM1555C1H1R3WA01#**	
				±0.1pF	**GRM1555C1H1R3BA01#**	
				±0.25pF	**GRM1555C1H1R3CA01#**	
			1.4pF	±0.05pF	**GRM1555C1H1R4WA01#**	
				±0.1pF	**GRM1555C1H1R4BA01#**	
				±0.25pF	**GRM1555C1H1R4CA01#**	
			1.5pF	±0.05pF	**GRM1555C1H1R5WA01#**	
				±0.1pF	**GRM1555C1H1R5BA01#**	
				±0.25pF	**GRM1555C1H1R5CA01#**	
			1.6pF	±0.05pF	**GRM1555C1H1R6WA01#**	
				±0.1pF	**GRM1555C1H1R6BA01#**	
				±0.25pF	**GRM1555C1H1R6CA01#**	
			1.7pF	±0.05pF	**GRM1555C1H1R7WA01#**	
				±0.1pF	**GRM1555C1H1R7BA01#**	
				±0.25pF	**GRM1555C1H1R7CA01#**	
			1.8pF	±0.05pF	**GRM1555C1H1R8WA01#**	
				±0.1pF	**GRM1555C1H1R8BA01#**	
				±0.25pF	**GRM1555C1H1R8CA01#**	
			1.9pF	±0.05pF	**GRM1555C1H1R9WA01#**	
				±0.1pF	**GRM1555C1H1R9BA01#**	
				±0.25pF	**GRM1555C1H1R9CA01#**	
			2.0pF	±0.05pF	**GRM1555C1H2R0WA01#**	
				±0.1pF	**GRM1555C1H2R0BA01#**	
				±0.25pF	**GRM1555C1H2R0CA01#**	
			2.1pF	±0.05pF	**GRM1555C1H2R1WA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	C0G	2.1pF	±0.1pF	**GRM1555C1H2R1BA01#**	
				±0.25pF	**GRM1555C1H2R1CA01#**	
			2.2pF	±0.05pF	**GRM1555C1H2R2WA01#**	
				±0.1pF	**GRM1555C1H2R2BA01#**	
				±0.25pF	**GRM1555C1H2R2CA01#**	
			2.3pF	±0.05pF	**GRM1555C1H2R3WA01#**	
				±0.1pF	**GRM1555C1H2R3BA01#**	
				±0.25pF	**GRM1555C1H2R3CA01#**	
			2.4pF	±0.05pF	**GRM1555C1H2R4WA01#**	
				±0.1pF	**GRM1555C1H2R4BA01#**	
				±0.25pF	**GRM1555C1H2R4CA01#**	
			2.5pF	±0.05pF	**GRM1555C1H2R5WA01#**	
				±0.1pF	**GRM1555C1H2R5BA01#**	
				±0.25pF	**GRM1555C1H2R5CA01#**	
			2.6pF	±0.05pF	**GRM1555C1H2R6WA01#**	
				±0.1pF	**GRM1555C1H2R6BA01#**	
				±0.25pF	**GRM1555C1H2R6CA01#**	
			2.7pF	±0.05pF	**GRM1555C1H2R7WA01#**	
				±0.1pF	**GRM1555C1H2R7BA01#**	
				±0.25pF	**GRM1555C1H2R7CA01#**	
			2.8pF	±0.05pF	**GRM1555C1H2R8WA01#**	
				±0.1pF	**GRM1555C1H2R8BA01#**	
				±0.25pF	**GRM1555C1H2R8CA01#**	
			2.9pF	±0.05pF	**GRM1555C1H2R9WA01#**	
				±0.1pF	**GRM1555C1H2R9BA01#**	
				±0.25pF	**GRM1555C1H2R9CA01#**	
			3.0pF	±0.05pF	**GRM1555C1H3R0WA01#**	
				±0.1pF	**GRM1555C1H3R0BA01#**	
				±0.25pF	**GRM1555C1H3R0CA01#**	
			3.1pF	±0.05pF	**GRM1555C1H3R1WA01#**	
				±0.1pF	**GRM1555C1H3R1BA01#**	
				±0.25pF	**GRM1555C1H3R1CA01#**	
			3.2pF	±0.05pF	**GRM1555C1H3R2WA01#**	
				±0.1pF	**GRM1555C1H3R2BA01#**	
				±0.25pF	**GRM1555C1H3R2CA01#**	
			3.3pF	±0.05pF	**GRM1555C1H3R3WA01#**	
				±0.1pF	**GRM1555C1H3R3BA01#**	
				±0.25pF	**GRM1555C1H3R3CA01#**	
			3.4pF	±0.05pF	**GRM1555C1H3R4WA01#**	
				±0.1pF	**GRM1555C1H3R4BA01#**	
				±0.25pF	**GRM1555C1H3R4CA01#**	
			3.5pF	±0.05pF	**GRM1555C1H3R5WA01#**	
				±0.1pF	**GRM1555C1H3R5BA01#**	
				±0.25pF	**GRM1555C1H3R5CA01#**	
			3.6pF	±0.05pF	**GRM1555C1H3R6WA01#**	
				±0.1pF	**GRM1555C1H3R6BA01#**	
				±0.25pF	**GRM1555C1H3R6CA01#**	
			3.7pF	±0.05pF	**GRM1555C1H3R7WA01#**	
				±0.1pF	**GRM1555C1H3R7BA01#**	
				±0.25pF	**GRM1555C1H3R7CA01#**	
			3.8pF	±0.05pF	**GRM1555C1H3R8WA01#**	
				±0.1pF	**GRM1555C1H3R8BA01#**	
				±0.25pF	**GRM1555C1H3R8CA01#**	
			3.9pF	±0.05pF	**GRM1555C1H3R9WA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	C0G	3.9pF	±0.1pF	GRM1555C1H3R9BA01#	
				±0.25pF	GRM1555C1H3R9CA01#	
			4.0pF	±0.05pF	GRM1555C1H4R0WA01#	
				±0.1pF	GRM1555C1H4R0BA01#	
				±0.25pF	GRM1555C1H4R0CA01#	
			4.1pF	±0.05pF	GRM1555C1H4R1WA01#	
				±0.1pF	GRM1555C1H4R1BA01#	
				±0.25pF	GRM1555C1H4R1CA01#	
			4.2pF	±0.05pF	GRM1555C1H4R2WA01#	
				±0.1pF	GRM1555C1H4R2BA01#	
				±0.25pF	GRM1555C1H4R2CA01#	
			4.3pF	±0.05pF	GRM1555C1H4R3WA01#	
				±0.1pF	GRM1555C1H4R3BA01#	
				±0.25pF	GRM1555C1H4R3CA01#	
			4.4pF	±0.05pF	GRM1555C1H4R4WA01#	
				±0.1pF	GRM1555C1H4R4BA01#	
				±0.25pF	GRM1555C1H4R4CA01#	
			4.5pF	±0.05pF	GRM1555C1H4R5WA01#	
				±0.1pF	GRM1555C1H4R5BA01#	
				±0.25pF	GRM1555C1H4R5CA01#	
			4.6pF	±0.05pF	GRM1555C1H4R6WA01#	
				±0.1pF	GRM1555C1H4R6BA01#	
				±0.25pF	GRM1555C1H4R6CA01#	
			4.7pF	±0.05pF	GRM1555C1H4R7WA01#	
				±0.1pF	GRM1555C1H4R7BA01#	
				±0.25pF	GRM1555C1H4R7CA01#	
			4.8pF	±0.05pF	GRM1555C1H4R8WA01#	
				±0.1pF	GRM1555C1H4R8BA01#	
				±0.25pF	GRM1555C1H4R8CA01#	
			4.9pF	±0.05pF	GRM1555C1H4R9WA01#	
				±0.1pF	GRM1555C1H4R9BA01#	
				±0.25pF	GRM1555C1H4R9CA01#	
			5.0pF	±0.05pF	GRM1555C1H5R0WA01#	
				±0.1pF	GRM1555C1H5R0BA01#	
				±0.25pF	GRM1555C1H5R0CA01#	
			5.1pF	±0.05pF	GRM1555C1H5R1WA01#	
				±0.1pF	GRM1555C1H5R1BA01#	
				±0.25pF	GRM1555C1H5R1CA01#	
				±0.5pF	GRM1555C1H5R1DA01#	
			5.2pF	±0.05pF	GRM1555C1H5R2WA01#	
				±0.1pF	GRM1555C1H5R2BA01#	
				±0.25pF	GRM1555C1H5R2CA01#	
				±0.5pF	GRM1555C1H5R2DA01#	
			5.3pF	±0.05pF	GRM1555C1H5R3WA01#	
				±0.1pF	GRM1555C1H5R3BA01#	
				±0.25pF	GRM1555C1H5R3CA01#	
				±0.5pF	GRM1555C1H5R3DA01#	
			5.4pF	±0.05pF	GRM1555C1H5R4WA01#	
				±0.1pF	GRM1555C1H5R4BA01#	
				±0.25pF	GRM1555C1H5R4CA01#	
				±0.5pF	GRM1555C1H5R4DA01#	
			5.5pF	±0.05pF	GRM1555C1H5R5WA01#	
				±0.1pF	GRM1555C1H5R5BA01#	
				±0.25pF	GRM1555C1H5R5CA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	C0G	5.5pF	±0.5pF	GRM1555C1H5R5DA01#	
			5.6pF	±0.05pF	GRM1555C1H5R6WA01#	
				±0.1pF	GRM1555C1H5R6BA01#	
				±0.25pF	GRM1555C1H5R6CA01#	
				±0.5pF	GRM1555C1H5R6DA01#	
			5.7pF	±0.05pF	GRM1555C1H5R7WA01#	
				±0.1pF	GRM1555C1H5R7BA01#	
				±0.25pF	GRM1555C1H5R7CA01#	
				±0.5pF	GRM1555C1H5R7DA01#	
			5.8pF	±0.05pF	GRM1555C1H5R8WA01#	
				±0.1pF	GRM1555C1H5R8BA01#	
				±0.25pF	GRM1555C1H5R8CA01#	
				±0.5pF	GRM1555C1H5R8DA01#	
			5.9pF	±0.05pF	GRM1555C1H5R9WA01#	
				±0.1pF	GRM1555C1H5R9BA01#	
				±0.25pF	GRM1555C1H5R9CA01#	
				±0.5pF	GRM1555C1H5R9DA01#	
			6.0pF	±0.05pF	GRM1555C1H6R0WA01#	
				±0.1pF	GRM1555C1H6R0BA01#	
				±0.25pF	GRM1555C1H6R0CA01#	
				±0.5pF	GRM1555C1H6R0DA01#	
			6.1pF	±0.05pF	GRM1555C1H6R1WA01#	
				±0.1pF	GRM1555C1H6R1BA01#	
				±0.25pF	GRM1555C1H6R1CA01#	
				±0.5pF	GRM1555C1H6R1DA01#	
			6.2pF	±0.05pF	GRM1555C1H6R2WA01#	
				±0.1pF	GRM1555C1H6R2BA01#	
				±0.25pF	GRM1555C1H6R2CA01#	
				±0.5pF	GRM1555C1H6R2DA01#	
			6.3pF	±0.05pF	GRM1555C1H6R3WA01#	
				±0.1pF	GRM1555C1H6R3BA01#	
				±0.25pF	GRM1555C1H6R3CA01#	
				±0.5pF	GRM1555C1H6R3DA01#	
			6.4pF	±0.05pF	GRM1555C1H6R4WA01#	
				±0.1pF	GRM1555C1H6R4BA01#	
				±0.25pF	GRM1555C1H6R4CA01#	
				±0.5pF	GRM1555C1H6R4DA01#	
			6.5pF	±0.05pF	GRM1555C1H6R5WA01#	
				±0.1pF	GRM1555C1H6R5BA01#	
				±0.25pF	GRM1555C1H6R5CA01#	
				±0.5pF	GRM1555C1H6R5DA01#	
			6.6pF	±0.05pF	GRM1555C1H6R6WA01#	
				±0.1pF	GRM1555C1H6R6BA01#	
				±0.25pF	GRM1555C1H6R6CA01#	
				±0.5pF	GRM1555C1H6R6DA01#	
			6.7pF	±0.05pF	GRM1555C1H6R7WA01#	
				±0.1pF	GRM1555C1H6R7BA01#	
				±0.25pF	GRM1555C1H6R7CA01#	
				±0.5pF	GRM1555C1H6R7DA01#	
			6.8pF	±0.05pF	GRM1555C1H6R8WA01#	
				±0.1pF	GRM1555C1H6R8BA01#	
				±0.25pF	GRM1555C1H6R8CA01#	
				±0.5pF	GRM1555C1H6R8DA01#	
			6.9pF	±0.05pF	GRM1555C1H6R9WA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	C0G	6.9pF	±0.1pF	GRM1555C1H6R9BA01#	
				±0.25pF	GRM1555C1H6R9CA01#	
				±0.5pF	GRM1555C1H6R9DA01#	
			7.0pF	±0.05pF	GRM1555C1H7R0WA01#	
				±0.1pF	GRM1555C1H7R0BA01#	
				±0.25pF	GRM1555C1H7R0CA01#	
				±0.5pF	GRM1555C1H7R0DA01#	
			7.1pF	±0.05pF	GRM1555C1H7R1WA01#	
				±0.1pF	GRM1555C1H7R1BA01#	
				±0.25pF	GRM1555C1H7R1CA01#	
				±0.5pF	GRM1555C1H7R1DA01#	
			7.2pF	±0.05pF	GRM1555C1H7R2WA01#	
				±0.1pF	GRM1555C1H7R2BA01#	
				±0.25pF	GRM1555C1H7R2CA01#	
				±0.5pF	GRM1555C1H7R2DA01#	
			7.3pF	±0.05pF	GRM1555C1H7R3WA01#	
				±0.1pF	GRM1555C1H7R3BA01#	
				±0.25pF	GRM1555C1H7R3CA01#	
				±0.5pF	GRM1555C1H7R3DA01#	
			7.4pF	±0.05pF	GRM1555C1H7R4WA01#	
				±0.1pF	GRM1555C1H7R4BA01#	
				±0.25pF	GRM1555C1H7R4CA01#	
				±0.5pF	GRM1555C1H7R4DA01#	
			7.5pF	±0.05pF	GRM1555C1H7R5WA01#	
				±0.1pF	GRM1555C1H7R5BA01#	
				±0.25pF	GRM1555C1H7R5CA01#	
				±0.5pF	GRM1555C1H7R5DA01#	
			7.6pF	±0.05pF	GRM1555C1H7R6WA01#	
				±0.1pF	GRM1555C1H7R6BA01#	
				±0.25pF	GRM1555C1H7R6CA01#	
				±0.5pF	GRM1555C1H7R6DA01#	
			7.7pF	±0.05pF	GRM1555C1H7R7WA01#	
				±0.1pF	GRM1555C1H7R7BA01#	
				±0.25pF	GRM1555C1H7R7CA01#	
				±0.5pF	GRM1555C1H7R7DA01#	
			7.8pF	±0.05pF	GRM1555C1H7R8WA01#	
				±0.1pF	GRM1555C1H7R8BA01#	
				±0.25pF	GRM1555C1H7R8CA01#	
				±0.5pF	GRM1555C1H7R8DA01#	
			7.9pF	±0.05pF	GRM1555C1H7R9WA01#	
				±0.1pF	GRM1555C1H7R9BA01#	
				±0.25pF	GRM1555C1H7R9CA01#	
				±0.5pF	GRM1555C1H7R9DA01#	
			8.0pF	±0.05pF	GRM1555C1H8R0WA01#	
				±0.1pF	GRM1555C1H8R0BA01#	
				±0.25pF	GRM1555C1H8R0CA01#	
				±0.5pF	GRM1555C1H8R0DA01#	
			8.1pF	±0.05pF	GRM1555C1H8R1WA01#	
				±0.1pF	GRM1555C1H8R1BA01#	
				±0.25pF	GRM1555C1H8R1CA01#	
				±0.5pF	GRM1555C1H8R1DA01#	
			8.2pF	±0.05pF	GRM1555C1H8R2WA01#	
				±0.1pF	GRM1555C1H8R2BA01#	
				±0.25pF	GRM1555C1H8R2CA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	C0G	8.2pF	±0.5pF	GRM1555C1H8R2DA01#	
			8.3pF	±0.05pF	GRM1555C1H8R3WA01#	
				±0.1pF	GRM1555C1H8R3BA01#	
				±0.25pF	GRM1555C1H8R3CA01#	
				±0.5pF	GRM1555C1H8R3DA01#	
			8.4pF	±0.05pF	GRM1555C1H8R4WA01#	
				±0.1pF	GRM1555C1H8R4BA01#	
				±0.25pF	GRM1555C1H8R4CA01#	
				±0.5pF	GRM1555C1H8R4DA01#	
			8.5pF	±0.05pF	GRM1555C1H8R5WA01#	
				±0.1pF	GRM1555C1H8R5BA01#	
				±0.25pF	GRM1555C1H8R5CA01#	
				±0.5pF	GRM1555C1H8R5DA01#	
			8.6pF	±0.05pF	GRM1555C1H8R6WA01#	
				±0.1pF	GRM1555C1H8R6BA01#	
				±0.25pF	GRM1555C1H8R6CA01#	
				±0.5pF	GRM1555C1H8R6DA01#	
			8.7pF	±0.05pF	GRM1555C1H8R7WA01#	
				±0.1pF	GRM1555C1H8R7BA01#	
				±0.25pF	GRM1555C1H8R7CA01#	
				±0.5pF	GRM1555C1H8R7DA01#	
			8.8pF	±0.05pF	GRM1555C1H8R8WA01#	
				±0.1pF	GRM1555C1H8R8BA01#	
				±0.25pF	GRM1555C1H8R8CA01#	
				±0.5pF	GRM1555C1H8R8DA01#	
			8.9pF	±0.05pF	GRM1555C1H8R9WA01#	
				±0.1pF	GRM1555C1H8R9BA01#	
				±0.25pF	GRM1555C1H8R9CA01#	
				±0.5pF	GRM1555C1H8R9DA01#	
			9.0pF	±0.05pF	GRM1555C1H9R0WA01#	
				±0.1pF	GRM1555C1H9R0BA01#	
				±0.25pF	GRM1555C1H9R0CA01#	
				±0.5pF	GRM1555C1H9R0DA01#	
			9.1pF	±0.05pF	GRM1555C1H9R1WA01#	
				±0.1pF	GRM1555C1H9R1BA01#	
				±0.25pF	GRM1555C1H9R1CA01#	
				±0.5pF	GRM1555C1H9R1DA01#	
			9.2pF	±0.05pF	GRM1555C1H9R2WA01#	
				±0.1pF	GRM1555C1H9R2BA01#	
				±0.25pF	GRM1555C1H9R2CA01#	
				±0.5pF	GRM1555C1H9R2DA01#	
			9.3pF	±0.05pF	GRM1555C1H9R3WA01#	
				±0.1pF	GRM1555C1H9R3BA01#	
				±0.25pF	GRM1555C1H9R3CA01#	
				±0.5pF	GRM1555C1H9R3DA01#	
			9.4pF	±0.05pF	GRM1555C1H9R4WA01#	
				±0.1pF	GRM1555C1H9R4BA01#	
				±0.25pF	GRM1555C1H9R4CA01#	
				±0.5pF	GRM1555C1H9R4DA01#	
			9.5pF	±0.05pF	GRM1555C1H9R5WA01#	
				±0.1pF	GRM1555C1H9R5BA01#	
				±0.25pF	GRM1555C1H9R5CA01#	
				±0.5pF	GRM1555C1H9R5DA01#	
			9.6pF	±0.05pF	GRM1555C1H9R6WA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	C0G	9.6pF	±0.1pF	GRM1555C1H9R6BA01#	
				±0.25pF	GRM1555C1H9R6CA01#	
				±0.5pF	GRM1555C1H9R6DA01#	
			9.7pF	±0.05pF	GRM1555C1H9R7WA01#	
				±0.1pF	GRM1555C1H9R7BA01#	
				±0.25pF	GRM1555C1H9R7CA01#	
				±0.5pF	GRM1555C1H9R7DA01#	
			9.8pF	±0.05pF	GRM1555C1H9R8WA01#	
				±0.1pF	GRM1555C1H9R8BA01#	
				±0.25pF	GRM1555C1H9R8CA01#	
				±0.5pF	GRM1555C1H9R8DA01#	
			9.9pF	±0.05pF	GRM1555C1H9R9WA01#	
				±0.1pF	GRM1555C1H9R9BA01#	
				±0.25pF	GRM1555C1H9R9CA01#	
				±0.5pF	GRM1555C1H9R9DA01#	
			10pF	±2%	GRM1555C1H100GA01#	
				±5%	GRM1555C1H100JA01#	
			12pF	±2%	GRM1555C1H120GA01#	
				±5%	GRM1555C1H120JA01#	
			15pF	±2%	GRM1555C1H150GA01#	
				±5%	GRM1555C1H150JA01#	
			18pF	±2%	GRM1555C1H180GA01#	
				±5%	GRM1555C1H180JA01#	
			22pF	±2%	GRM1555C1H220GA01#	
				±5%	GRM1555C1H220JA01#	
			27pF	±2%	GRM1555C1H270GA01#	
				±5%	GRM1555C1H270JA01#	
			33pF	±2%	GRM1555C1H330GA01#	
				±5%	GRM1555C1H330JA01#	
			39pF	±2%	GRM1555C1H390GA01#	
				±5%	GRM1555C1H390JA01#	
			47pF	±2%	GRM1555C1H470GA01#	
				±5%	GRM1555C1H470JA01#	
			56pF	±2%	GRM1555C1H560GA01#	
				±5%	GRM1555C1H560JA01#	
			68pF	±2%	GRM1555C1H680GA01#	
				±5%	GRM1555C1H680JA01#	
			82pF	±2%	GRM1555C1H820GA01#	
				±5%	GRM1555C1H820JA01#	
			100pF	±2%	GRM1555C1H101GA01#	
				±5%	GRM1555C1H101JA01#	
			120pF	±2%	GRM1555C1H121GA01#	
				±5%	GRM1555C1H121JA01#	
			150pF	±2%	GRM1555C1H151GA01#	
				±5%	GRM1555C1H151JA01#	
			180pF	±2%	GRM1555C1H181GA01#	
				±5%	GRM1555C1H181JA01#	
			220pF	±2%	GRM1555C1H221GA01#	
				±5%	GRM1555C1H221JA01#	
			270pF	±2%	GRM1555C1H271GA01#	
				±5%	GRM1555C1H271JA01#	
			330pF	±2%	GRM1555C1H331GA01#	
				±5%	GRM1555C1H331JA01#	
			390pF	±2%	GRM1555C1H391GA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	C0G	390pF	±5%	GRM1555C1H391JA01#	
			470pF	±2%	GRM1555C1H471GA01#	
				±5%	GRM1555C1H471JA01#	
			560pF	±2%	GRM1555C1H561GA01#	
				±5%	GRM1555C1H561JA01#	
			680pF	±2%	GRM1555C1H681GA01#	
				±5%	GRM1555C1H681JA01#	
			820pF	±2%	GRM1555C1H821GA01#	
				±5%	GRM1555C1H821JA01#	
			1000pF	±2%	GRM1555C1H102GA01#	
				±5%	GRM1555C1H102JA01#	
		CK	0.10pF	±0.05pF	GRM1554C1HR10WA01#	
			0.20pF	±0.05pF	GRM1554C1HR20WA01#	
				±0.1pF	GRM1554C1HR20BA01#	
			0.30pF	±0.05pF	GRM1554C1HR30WA01#	
				±0.1pF	GRM1554C1HR30BA01#	
			0.40pF	±0.05pF	GRM1554C1HR40WA01#	
				±0.1pF	GRM1554C1HR40BA01#	
			0.50pF	±0.05pF	GRM1554C1HR50WA01#	
				±0.1pF	GRM1554C1HR50BA01#	
			0.60pF	±0.05pF	GRM1554C1HR60WA01#	
				±0.1pF	GRM1554C1HR60BA01#	
			0.70pF	±0.05pF	GRM1554C1HR70WA01#	
				±0.1pF	GRM1554C1HR70BA01#	
			0.80pF	±0.05pF	GRM1554C1HR80WA01#	
				±0.1pF	GRM1554C1HR80BA01#	
			0.90pF	±0.05pF	GRM1554C1HR90WA01#	
				±0.1pF	GRM1554C1HR90BA01#	
			1.0pF	±0.05pF	GRM1554C1H1R0WA01#	
				±0.1pF	GRM1554C1H1R0BA01#	
				±0.25pF	GRM1554C1H1R0CA01#	
			1.1pF	±0.05pF	GRM1554C1H1R1WA01#	
				±0.1pF	GRM1554C1H1R1BA01#	
				±0.25pF	GRM1554C1H1R1CA01#	
			1.2pF	±0.05pF	GRM1554C1H1R2WA01#	
				±0.1pF	GRM1554C1H1R2BA01#	
				±0.25pF	GRM1554C1H1R2CA01#	
			1.3pF	±0.05pF	GRM1554C1H1R3WA01#	
				±0.1pF	GRM1554C1H1R3BA01#	
				±0.25pF	GRM1554C1H1R3CA01#	
			1.4pF	±0.05pF	GRM1554C1H1R4WA01#	
				±0.1pF	GRM1554C1H1R4BA01#	
				±0.25pF	GRM1554C1H1R4CA01#	
			1.5pF	±0.05pF	GRM1554C1H1R5WA01#	
				±0.1pF	GRM1554C1H1R5BA01#	
				±0.25pF	GRM1554C1H1R5CA01#	
			1.6pF	±0.05pF	GRM1554C1H1R6WA01#	
				±0.1pF	GRM1554C1H1R6BA01#	
				±0.25pF	GRM1554C1H1R6CA01#	
			1.7pF	±0.05pF	GRM1554C1H1R7WA01#	
				±0.1pF	GRM1554C1H1R7BA01#	
				±0.25pF	GRM1554C1H1R7CA01#	
			1.8pF	±0.05pF	GRM1554C1H1R8WA01#	
				±0.1pF	GRM1554C1H1R8BA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	CK	1.8pF	±0.25pF	**GRM1554C1H1R8CA01#**	
			1.9pF	±0.05pF	**GRM1554C1H1R9WA01#**	
				±0.1pF	**GRM1554C1H1R9BA01#**	
				±0.25pF	**GRM1554C1H1R9CA01#**	
			2.0pF	±0.05pF	**GRM1554C1H2R0WA01#**	
				±0.1pF	**GRM1554C1H2R0BA01#**	
				±0.25pF	**GRM1554C1H2R0CA01#**	
		CJ	2.1pF	±0.05pF	**GRM1553C1H2R1WA01#**	
				±0.1pF	**GRM1553C1H2R1BA01#**	
				±0.25pF	**GRM1553C1H2R1CA01#**	
			2.2pF	±0.05pF	**GRM1553C1H2R2WA01#**	
				±0.1pF	**GRM1553C1H2R2BA01#**	
				±0.25pF	**GRM1553C1H2R2CA01#**	
			2.3pF	±0.05pF	**GRM1553C1H2R3WA01#**	
				±0.1pF	**GRM1553C1H2R3BA01#**	
				±0.25pF	**GRM1553C1H2R3CA01#**	
			2.4pF	±0.05pF	**GRM1553C1H2R4WA01#**	
				±0.1pF	**GRM1553C1H2R4BA01#**	
				±0.25pF	**GRM1553C1H2R4CA01#**	
			2.5pF	±0.05pF	**GRM1553C1H2R5WA01#**	
				±0.1pF	**GRM1553C1H2R5BA01#**	
				±0.25pF	**GRM1553C1H2R5CA01#**	
			2.6pF	±0.05pF	**GRM1553C1H2R6WA01#**	
				±0.1pF	**GRM1553C1H2R6BA01#**	
				±0.25pF	**GRM1553C1H2R6CA01#**	
			2.7pF	±0.05pF	**GRM1553C1H2R7WA01#**	
				±0.1pF	**GRM1553C1H2R7BA01#**	
				±0.25pF	**GRM1553C1H2R7CA01#**	
			2.8pF	±0.05pF	**GRM1553C1H2R8WA01#**	
				±0.1pF	**GRM1553C1H2R8BA01#**	
				±0.25pF	**GRM1553C1H2R8CA01#**	
			2.9pF	±0.05pF	**GRM1553C1H2R9WA01#**	
				±0.1pF	**GRM1553C1H2R9BA01#**	
				±0.25pF	**GRM1553C1H2R9CA01#**	
			3.0pF	±0.05pF	**GRM1553C1H3R0WA01#**	
				±0.1pF	**GRM1553C1H3R0BA01#**	
				±0.25pF	**GRM1553C1H3R0CA01#**	
			3.1pF	±0.05pF	**GRM1553C1H3R1WA01#**	
				±0.1pF	**GRM1553C1H3R1BA01#**	
				±0.25pF	**GRM1553C1H3R1CA01#**	
			3.2pF	±0.05pF	**GRM1553C1H3R2WA01#**	
				±0.1pF	**GRM1553C1H3R2BA01#**	
				±0.25pF	**GRM1553C1H3R2CA01#**	
			3.3pF	±0.05pF	**GRM1553C1H3R3WA01#**	
				±0.1pF	**GRM1553C1H3R3BA01#**	
				±0.25pF	**GRM1553C1H3R3CA01#**	
			3.4pF	±0.05pF	**GRM1553C1H3R4WA01#**	
				±0.1pF	**GRM1553C1H3R4BA01#**	
				±0.25pF	**GRM1553C1H3R4CA01#**	
			3.5pF	±0.05pF	**GRM1553C1H3R5WA01#**	
				±0.1pF	**GRM1553C1H3R5BA01#**	
				±0.25pF	**GRM1553C1H3R5CA01#**	
			3.6pF	±0.05pF	**GRM1553C1H3R6WA01#**	
				±0.1pF	**GRM1553C1H3R6BA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	CJ	3.6pF	±0.25pF	**GRM1553C1H3R6CA01#**	
			3.7pF	±0.05pF	**GRM1553C1H3R7WA01#**	
				±0.1pF	**GRM1553C1H3R7BA01#**	
				±0.25pF	**GRM1553C1H3R7CA01#**	
			3.8pF	±0.05pF	**GRM1553C1H3R8WA01#**	
				±0.1pF	**GRM1553C1H3R8BA01#**	
				±0.25pF	**GRM1553C1H3R8CA01#**	
			3.9pF	±0.05pF	**GRM1553C1H3R9WA01#**	
				±0.1pF	**GRM1553C1H3R9BA01#**	
				±0.25pF	**GRM1553C1H3R9CA01#**	
		CH	4.0pF	±0.05pF	**GRM1552C1H4R0WA01#**	
				±0.1pF	**GRM1552C1H4R0BA01#**	
				±0.25pF	**GRM1552C1H4R0CA01#**	
			4.1pF	±0.05pF	**GRM1552C1H4R1WA01#**	
				±0.1pF	**GRM1552C1H4R1BA01#**	
				±0.25pF	**GRM1552C1H4R1CA01#**	
			4.2pF	±0.05pF	**GRM1552C1H4R2WA01#**	
				±0.1pF	**GRM1552C1H4R2BA01#**	
				±0.25pF	**GRM1552C1H4R2CA01#**	
			4.3pF	±0.05pF	**GRM1552C1H4R3WA01#**	
				±0.1pF	**GRM1552C1H4R3BA01#**	
				±0.25pF	**GRM1552C1H4R3CA01#**	
			4.4pF	±0.05pF	**GRM1552C1H4R4WA01#**	
				±0.1pF	**GRM1552C1H4R4BA01#**	
				±0.25pF	**GRM1552C1H4R4CA01#**	
			4.5pF	±0.05pF	**GRM1552C1H4R5WA01#**	
				±0.1pF	**GRM1552C1H4R5BA01#**	
				±0.25pF	**GRM1552C1H4R5CA01#**	
			4.6pF	±0.05pF	**GRM1552C1H4R6WA01#**	
				±0.1pF	**GRM1552C1H4R6BA01#**	
				±0.25pF	**GRM1552C1H4R6CA01#**	
			4.7pF	±0.05pF	**GRM1552C1H4R7WA01#**	
				±0.1pF	**GRM1552C1H4R7BA01#**	
				±0.25pF	**GRM1552C1H4R7CA01#**	
			4.8pF	±0.05pF	**GRM1552C1H4R8WA01#**	
				±0.1pF	**GRM1552C1H4R8BA01#**	
				±0.25pF	**GRM1552C1H4R8CA01#**	
			4.9pF	±0.05pF	**GRM1552C1H4R9WA01#**	
				±0.1pF	**GRM1552C1H4R9BA01#**	
				±0.25pF	**GRM1552C1H4R9CA01#**	
			5.0pF	±0.05pF	**GRM1552C1H5R0WA01#**	
				±0.1pF	**GRM1552C1H5R0BA01#**	
				±0.25pF	**GRM1552C1H5R0CA01#**	
			5.1pF	±0.05pF	**GRM1552C1H5R1WA01#**	
				±0.1pF	**GRM1552C1H5R1BA01#**	
				±0.25pF	**GRM1552C1H5R1CA01#**	
				±0.5pF	**GRM1552C1H5R1DA01#**	
			5.2pF	±0.05pF	**GRM1552C1H5R2WA01#**	
				±0.1pF	**GRM1552C1H5R2BA01#**	
				±0.25pF	**GRM1552C1H5R2CA01#**	
				±0.5pF	**GRM1552C1H5R2DA01#**	
			5.3pF	±0.05pF	**GRM1552C1H5R3WA01#**	
				±0.1pF	**GRM1552C1H5R3BA01#**	
				±0.25pF	**GRM1552C1H5R3CA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	CH	5.3pF	±0.5pF	**GRM1552C1H5R3DA01#**	
			5.4pF	±0.05pF	**GRM1552C1H5R4WA01#**	
				±0.1pF	**GRM1552C1H5R4BA01#**	
				±0.25pF	**GRM1552C1H5R4CA01#**	
				±0.5pF	**GRM1552C1H5R4DA01#**	
			5.5pF	±0.05pF	**GRM1552C1H5R5WA01#**	
				±0.1pF	**GRM1552C1H5R5BA01#**	
				±0.25pF	**GRM1552C1H5R5CA01#**	
				±0.5pF	**GRM1552C1H5R5DA01#**	
			5.6pF	±0.05pF	**GRM1552C1H5R6WA01#**	
				±0.1pF	**GRM1552C1H5R6BA01#**	
				±0.25pF	**GRM1552C1H5R6CA01#**	
				±0.5pF	**GRM1552C1H5R6DA01#**	
			5.7pF	±0.05pF	**GRM1552C1H5R7WA01#**	
				±0.1pF	**GRM1552C1H5R7BA01#**	
				±0.25pF	**GRM1552C1H5R7CA01#**	
				±0.5pF	**GRM1552C1H5R7DA01#**	
			5.8pF	±0.05pF	**GRM1552C1H5R8WA01#**	
				±0.1pF	**GRM1552C1H5R8BA01#**	
				±0.25pF	**GRM1552C1H5R8CA01#**	
				±0.5pF	**GRM1552C1H5R8DA01#**	
			5.9pF	±0.05pF	**GRM1552C1H5R9WA01#**	
				±0.1pF	**GRM1552C1H5R9BA01#**	
				±0.25pF	**GRM1552C1H5R9CA01#**	
				±0.5pF	**GRM1552C1H5R9DA01#**	
			6.0pF	±0.05pF	**GRM1552C1H6R0WA01#**	
				±0.1pF	**GRM1552C1H6R0BA01#**	
				±0.25pF	**GRM1552C1H6R0CA01#**	
				±0.5pF	**GRM1552C1H6R0DA01#**	
			6.1pF	±0.05pF	**GRM1552C1H6R1WA01#**	
				±0.1pF	**GRM1552C1H6R1BA01#**	
				±0.25pF	**GRM1552C1H6R1CA01#**	
				±0.5pF	**GRM1552C1H6R1DA01#**	
			6.2pF	±0.05pF	**GRM1552C1H6R2WA01#**	
				±0.1pF	**GRM1552C1H6R2BA01#**	
				±0.25pF	**GRM1552C1H6R2CA01#**	
				±0.5pF	**GRM1552C1H6R2DA01#**	
			6.3pF	±0.05pF	**GRM1552C1H6R3WA01#**	
				±0.1pF	**GRM1552C1H6R3BA01#**	
				±0.25pF	**GRM1552C1H6R3CA01#**	
				±0.5pF	**GRM1552C1H6R3DA01#**	
			6.4pF	±0.05pF	**GRM1552C1H6R4WA01#**	
				±0.1pF	**GRM1552C1H6R4BA01#**	
				±0.25pF	**GRM1552C1H6R4CA01#**	
				±0.5pF	**GRM1552C1H6R4DA01#**	
			6.5pF	±0.05pF	**GRM1552C1H6R5WA01#**	
				±0.1pF	**GRM1552C1H6R5BA01#**	
				±0.25pF	**GRM1552C1H6R5CA01#**	
				±0.5pF	**GRM1552C1H6R5DA01#**	
			6.6pF	±0.05pF	**GRM1552C1H6R6WA01#**	
				±0.1pF	**GRM1552C1H6R6BA01#**	
				±0.25pF	**GRM1552C1H6R6CA01#**	
				±0.5pF	**GRM1552C1H6R6DA01#**	
			6.7pF	±0.05pF	**GRM1552C1H6R7WA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	CH	6.7pF	±0.1pF	**GRM1552C1H6R7BA01#**	
				±0.25pF	**GRM1552C1H6R7CA01#**	
				±0.5pF	**GRM1552C1H6R7DA01#**	
			6.8pF	±0.05pF	**GRM1552C1H6R8WA01#**	
				±0.1pF	**GRM1552C1H6R8BA01#**	
				±0.25pF	**GRM1552C1H6R8CA01#**	
				±0.5pF	**GRM1552C1H6R8DA01#**	
			6.9pF	±0.05pF	**GRM1552C1H6R9WA01#**	
				±0.1pF	**GRM1552C1H6R9BA01#**	
				±0.25pF	**GRM1552C1H6R9CA01#**	
				±0.5pF	**GRM1552C1H6R9DA01#**	
			7.0pF	±0.05pF	**GRM1552C1H7R0WA01#**	
				±0.1pF	**GRM1552C1H7R0BA01#**	
				±0.25pF	**GRM1552C1H7R0CA01#**	
				±0.5pF	**GRM1552C1H7R0DA01#**	
			7.1pF	±0.05pF	**GRM1552C1H7R1WA01#**	
				±0.1pF	**GRM1552C1H7R1BA01#**	
				±0.25pF	**GRM1552C1H7R1CA01#**	
				±0.5pF	**GRM1552C1H7R1DA01#**	
			7.2pF	±0.05pF	**GRM1552C1H7R2WA01#**	
				±0.1pF	**GRM1552C1H7R2BA01#**	
				±0.25pF	**GRM1552C1H7R2CA01#**	
				±0.5pF	**GRM1552C1H7R2DA01#**	
			7.3pF	±0.05pF	**GRM1552C1H7R3WA01#**	
				±0.1pF	**GRM1552C1H7R3BA01#**	
				±0.25pF	**GRM1552C1H7R3CA01#**	
				±0.5pF	**GRM1552C1H7R3DA01#**	
			7.4pF	±0.05pF	**GRM1552C1H7R4WA01#**	
				±0.1pF	**GRM1552C1H7R4BA01#**	
				±0.25pF	**GRM1552C1H7R4CA01#**	
				±0.5pF	**GRM1552C1H7R4DA01#**	
			7.5pF	±0.05pF	**GRM1552C1H7R5WA01#**	
				±0.1pF	**GRM1552C1H7R5BA01#**	
				±0.25pF	**GRM1552C1H7R5CA01#**	
				±0.5pF	**GRM1552C1H7R5DA01#**	
			7.6pF	±0.05pF	**GRM1552C1H7R6WA01#**	
				±0.1pF	**GRM1552C1H7R6BA01#**	
				±0.25pF	**GRM1552C1H7R6CA01#**	
				±0.5pF	**GRM1552C1H7R6DA01#**	
			7.7pF	±0.05pF	**GRM1552C1H7R7WA01#**	
				±0.1pF	**GRM1552C1H7R7BA01#**	
				±0.25pF	**GRM1552C1H7R7CA01#**	
				±0.5pF	**GRM1552C1H7R7DA01#**	
			7.8pF	±0.05pF	**GRM1552C1H7R8WA01#**	
				±0.1pF	**GRM1552C1H7R8BA01#**	
				±0.25pF	**GRM1552C1H7R8CA01#**	
				±0.5pF	**GRM1552C1H7R8DA01#**	
			7.9pF	±0.05pF	**GRM1552C1H7R9WA01#**	
				±0.1pF	**GRM1552C1H7R9BA01#**	
				±0.25pF	**GRM1552C1H7R9CA01#**	
				±0.5pF	**GRM1552C1H7R9DA01#**	
			8.0pF	±0.05pF	**GRM1552C1H8R0WA01#**	
				±0.1pF	**GRM1552C1H8R0BA01#**	
				±0.25pF	**GRM1552C1H8R0CA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	CH	8.0pF	±0.5pF	GRM1552C1H8R0DA01#	
			8.1pF	±0.05pF	GRM1552C1H8R1WA01#	
				±0.1pF	GRM1552C1H8R1BA01#	
				±0.25pF	GRM1552C1H8R1CA01#	
				±0.5pF	GRM1552C1H8R1DA01#	
			8.2pF	±0.05pF	GRM1552C1H8R2WA01#	
				±0.1pF	GRM1552C1H8R2BA01#	
				±0.25pF	GRM1552C1H8R2CA01#	
				±0.5pF	GRM1552C1H8R2DA01#	
			8.3pF	±0.05pF	GRM1552C1H8R3WA01#	
				±0.1pF	GRM1552C1H8R3BA01#	
				±0.25pF	GRM1552C1H8R3CA01#	
				±0.5pF	GRM1552C1H8R3DA01#	
			8.4pF	±0.05pF	GRM1552C1H8R4WA01#	
				±0.1pF	GRM1552C1H8R4BA01#	
				±0.25pF	GRM1552C1H8R4CA01#	
				±0.5pF	GRM1552C1H8R4DA01#	
			8.5pF	±0.05pF	GRM1552C1H8R5WA01#	
				±0.1pF	GRM1552C1H8R5BA01#	
				±0.25pF	GRM1552C1H8R5CA01#	
				±0.5pF	GRM1552C1H8R5DA01#	
			8.6pF	±0.05pF	GRM1552C1H8R6WA01#	
				±0.1pF	GRM1552C1H8R6BA01#	
				±0.25pF	GRM1552C1H8R6CA01#	
				±0.5pF	GRM1552C1H8R6DA01#	
			8.7pF	±0.05pF	GRM1552C1H8R7WA01#	
				±0.1pF	GRM1552C1H8R7BA01#	
				±0.25pF	GRM1552C1H8R7CA01#	
				±0.5pF	GRM1552C1H8R7DA01#	
			8.8pF	±0.05pF	GRM1552C1H8R8WA01#	
				±0.1pF	GRM1552C1H8R8BA01#	
				±0.25pF	GRM1552C1H8R8CA01#	
				±0.5pF	GRM1552C1H8R8DA01#	
			8.9pF	±0.05pF	GRM1552C1H8R9WA01#	
				±0.1pF	GRM1552C1H8R9BA01#	
				±0.25pF	GRM1552C1H8R9CA01#	
				±0.5pF	GRM1552C1H8R9DA01#	
			9.0pF	±0.05pF	GRM1552C1H9R0WA01#	
				±0.1pF	GRM1552C1H9R0BA01#	
				±0.25pF	GRM1552C1H9R0CA01#	
				±0.5pF	GRM1552C1H9R0DA01#	
			9.1pF	±0.05pF	GRM1552C1H9R1WA01#	
				±0.1pF	GRM1552C1H9R1BA01#	
				±0.25pF	GRM1552C1H9R1CA01#	
				±0.5pF	GRM1552C1H9R1DA01#	
			9.2pF	±0.05pF	GRM1552C1H9R2WA01#	
				±0.1pF	GRM1552C1H9R2BA01#	
				±0.25pF	GRM1552C1H9R2CA01#	
				±0.5pF	GRM1552C1H9R2DA01#	
			9.3pF	±0.05pF	GRM1552C1H9R3WA01#	
				±0.1pF	GRM1552C1H9R3BA01#	
				±0.25pF	GRM1552C1H9R3CA01#	
				±0.5pF	GRM1552C1H9R3DA01#	
			9.4pF	±0.05pF	GRM1552C1H9R4WA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	CH	9.4pF	±0.1pF	GRM1552C1H9R4BA01#	
				±0.25pF	GRM1552C1H9R4CA01#	
				±0.5pF	GRM1552C1H9R4DA01#	
			9.5pF	±0.05pF	GRM1552C1H9R5WA01#	
				±0.1pF	GRM1552C1H9R5BA01#	
				±0.25pF	GRM1552C1H9R5CA01#	
				±0.5pF	GRM1552C1H9R5DA01#	
			9.6pF	±0.05pF	GRM1552C1H9R6WA01#	
				±0.1pF	GRM1552C1H9R6BA01#	
				±0.25pF	GRM1552C1H9R6CA01#	
				±0.5pF	GRM1552C1H9R6DA01#	
			9.7pF	±0.05pF	GRM1552C1H9R7WA01#	
				±0.1pF	GRM1552C1H9R7BA01#	
				±0.25pF	GRM1552C1H9R7CA01#	
				±0.5pF	GRM1552C1H9R7DA01#	
			9.8pF	±0.05pF	GRM1552C1H9R8WA01#	
				±0.1pF	GRM1552C1H9R8BA01#	
				±0.25pF	GRM1552C1H9R8CA01#	
				±0.5pF	GRM1552C1H9R8DA01#	
			9.9pF	±0.05pF	GRM1552C1H9R9WA01#	
				±0.1pF	GRM1552C1H9R9BA01#	
				±0.25pF	GRM1552C1H9R9CA01#	
				±0.5pF	GRM1552C1H9R9DA01#	
			10pF	±2%	GRM1552C1H100GA01#	
				±5%	GRM1552C1H100JA01#	
			12pF	±2%	GRM1552C1H120GA01#	
				±5%	GRM1552C1H120JA01#	
			15pF	±2%	GRM1552C1H150GA01#	
				±5%	GRM1552C1H150JA01#	
			18pF	±2%	GRM1552C1H180GA01#	
				±5%	GRM1552C1H180JA01#	
			22pF	±2%	GRM1552C1H220GA01#	
				±5%	GRM1552C1H220JA01#	
			27pF	±2%	GRM1552C1H270GA01#	
				±5%	GRM1552C1H270JA01#	
			33pF	±2%	GRM1552C1H330GA01#	
				±5%	GRM1552C1H330JA01#	
			39pF	±2%	GRM1552C1H390GA01#	
				±5%	GRM1552C1H390JA01#	
			47pF	±2%	GRM1552C1H470GA01#	
				±5%	GRM1552C1H470JA01#	
			56pF	±2%	GRM1552C1H560GA01#	
				±5%	GRM1552C1H560JA01#	
			68pF	±2%	GRM1552C1H680GA01#	
				±5%	GRM1552C1H680JA01#	
			82pF	±2%	GRM1552C1H820GA01#	
				±5%	GRM1552C1H820JA01#	
			100pF	±2%	GRM1552C1H101GA01#	
				±5%	GRM1552C1H101JA01#	
			120pF	±2%	GRM1552C1H121GA01#	
				±5%	GRM1552C1H121JA01#	
			150pF	±2%	GRM1552C1H151GA01#	
				±5%	GRM1552C1H151JA01#	
			180pF	±2%	GRM1552C1H181GA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	CH	180pF	±5%	GRM1552C1H181JA01#	
			220pF	±2%	GRM1552C1H221GA01#	
				±5%	GRM1552C1H221JA01#	
			270pF	±2%	GRM1552C1H271GA01#	
				±5%	GRM1552C1H271JA01#	
			330pF	±2%	GRM1552C1H331GA01#	
				±5%	GRM1552C1H331JA01#	
			390pF	±2%	GRM1552C1H391GA01#	
				±5%	GRM1552C1H391JA01#	
			470pF	±2%	GRM1552C1H471GA01#	
				±5%	GRM1552C1H471JA01#	
			560pF	±2%	GRM1552C1H561GA01#	
				±5%	GRM1552C1H561JA01#	
			680pF	±2%	GRM1552C1H681GA01#	
				±5%	GRM1552C1H681JA01#	
			820pF	±2%	GRM1552C1H821GA01#	
				±5%	GRM1552C1H821JA01#	
			1000pF	±2%	GRM1552C1H102GA01#	
				±5%	GRM1552C1H102JA01#	
	10Vdc	SL	1200pF	±5%	GRM1551X1A122JA01#	
			1500pF	±5%	GRM1551X1A152JA01#	
			1800pF	±5%	GRM1551X1A182JA01#	
			2200pF	±5%	GRM1551X1A222JA01#	
			2700pF	±5%	GRM1551X1A272JA01#	
			3300pF	±5%	GRM1551X1A332JA01#	
			3900pF	±5%	GRM1551X1A392JA01#	
			4700pF	±5%	GRM1551X1A472JA01#	
		U2J	1200pF	±5%	GRM1557U1A122JA01#	
			1500pF	±5%	GRM1557U1A152JA01#	
			1800pF	±5%	GRM1557U1A182JA01#	
			2200pF	±5%	GRM1557U1A222JA01#	
			2700pF	±5%	GRM1557U1A272JA01#	
			3300pF	±5%	GRM1557U1A332JA01#	
			3900pF	±5%	GRM1557U1A392JA01#	
			4700pF	±5%	GRM1557U1A472JA01#	
		UJ	1200pF	±5%	GRM1553U1A122JA01#	
			1500pF	±5%	GRM1553U1A152JA01#	
			1800pF	±5%	GRM1553U1A182JA01#	
			2200pF	±5%	GRM1553U1A222JA01#	
			2700pF	±5%	GRM1553U1A272JA01#	
			3300pF	±5%	GRM1553U1A332JA01#	
			3900pF	±5%	GRM1553U1A392JA01#	
			4700pF	±5%	GRM1553U1A472JA01#	

1.6×0.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.5mm	50Vdc	SL	2200pF	±5%	GRM1851X1H222JA44#	
			2700pF	±5%	GRM1851X1H272JA44#	
			3300pF	±5%	GRM1851X1H332JA44#	
			3900pF	±5%	GRM1851X1H392JA44#	
			4700pF	±5%	GRM1851X1H472JA44#	
		U2J	2200pF	±5%	GRM1857U1H222JA44#	
0.5mm	50Vdc	U2J	2700pF	±5%	GRM1857U1H272JA44#	
			3300pF	±5%	GRM1857U1H332JA44#	
			3900pF	±5%	GRM1857U1H392JA44#	
			4700pF	±5%	GRM1857U1H472JA44#	
		UJ	2200pF	±5%	GRM1853U1H222JA44#	
			2700pF	±5%	GRM1853U1H272JA44#	
			3300pF	±5%	GRM1853U1H332JA44#	
			3900pF	±5%	GRM1853U1H392JA44#	
			4700pF	±5%	GRM1853U1H472JA44#	
	10Vdc	SL	5600pF	±5%	GRM1851X1A562JA44#	
			6800pF	±5%	GRM1851X1A682JA44#	
			8200pF	±5%	GRM1851X1A822JA44#	
			10000pF	±5%	GRM1851X1A103JA44#	
		U2J	5600pF	±5%	GRM1857U1A562JA44#	
			6800pF	±5%	GRM1857U1A682JA44#	
			8200pF	±5%	GRM1857U1A822JA44#	
			10000pF	±5%	GRM1857U1A103JA44#	
		UJ	5600pF	±5%	GRM1853U1A562JA44#	
			6800pF	±5%	GRM1853U1A682JA44#	
			8200pF	±5%	GRM1853U1A822JA44#	
			10000pF	±5%	GRM1853U1A103JA44#	
0.9mm	100Vdc	C0G	0.50pF	±0.05pF	GRM1885C2AR50WA01#	
				±0.1pF	GRM1885C2AR50BA01#	
			0.60pF	±0.05pF	GRM1885C2AR60WA01#	
				±0.1pF	GRM1885C2AR60BA01#	
			0.70pF	±0.05pF	GRM1885C2AR70WA01#	
				±0.1pF	GRM1885C2AR70BA01#	
			0.80pF	±0.05pF	GRM1885C2AR80WA01#	
				±0.1pF	GRM1885C2AR80BA01#	
			0.90pF	±0.05pF	GRM1885C2AR90WA01#	
				±0.1pF	GRM1885C2AR90BA01#	
			1.0pF	±0.05pF	GRM1885C2A1R0WA01#	
				±0.1pF	GRM1885C2A1R0BA01#	
				±0.25pF	GRM1885C2A1R0CA01#	
			1.1pF	±0.05pF	GRM1885C2A1R1WA01#	
				±0.1pF	GRM1885C2A1R1BA01#	
				±0.25pF	GRM1885C2A1R1CA01#	
			1.2pF	±0.05pF	GRM1885C2A1R2WA01#	
				±0.1pF	GRM1885C2A1R2BA01#	
				±0.25pF	GRM1885C2A1R2CA01#	
			1.3pF	±0.05pF	GRM1885C2A1R3WA01#	
				±0.1pF	GRM1885C2A1R3BA01#	
				±0.25pF	GRM1885C2A1R3CA01#	
			1.4pF	±0.05pF	GRM1885C2A1R4WA01#	
				±0.1pF	GRM1885C2A1R4BA01#	
				±0.25pF	GRM1885C2A1R4CA01#	
			1.5pF	±0.05pF	GRM1885C2A1R5WA01#	
				±0.1pF	GRM1885C2A1R5BA01#	
				±0.25pF	GRM1885C2A1R5CA01#	
			1.6pF	±0.05pF	GRM1885C2A1R6WA01#	
				±0.1pF	GRM1885C2A1R6BA01#	
				±0.25pF	GRM1885C2A1R6CA01#	
			1.7pF	±0.05pF	GRM1885C2A1R7WA01#	
				±0.1pF	GRM1885C2A1R7BA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	C0G	1.7pF	±0.25pF	**GRM1885C2A1R7CA01#**	
			1.8pF	±0.05pF	**GRM1885C2A1R8WA01#**	
				±0.1pF	**GRM1885C2A1R8BA01#**	
				±0.25pF	**GRM1885C2A1R8CA01#**	
			1.9pF	±0.05pF	**GRM1885C2A1R9WA01#**	
				±0.1pF	**GRM1885C2A1R9BA01#**	
				±0.25pF	**GRM1885C2A1R9CA01#**	
			2.0pF	±0.05pF	**GRM1885C2A2R0WA01#**	
				±0.1pF	**GRM1885C2A2R0BA01#**	
				±0.25pF	**GRM1885C2A2R0CA01#**	
			2.1pF	±0.05pF	**GRM1885C2A2R1WA01#**	
				±0.1pF	**GRM1885C2A2R1BA01#**	
				±0.25pF	**GRM1885C2A2R1CA01#**	
			2.2pF	±0.05pF	**GRM1885C2A2R2WA01#**	
				±0.1pF	**GRM1885C2A2R2BA01#**	
				±0.25pF	**GRM1885C2A2R2CA01#**	
			2.3pF	±0.05pF	**GRM1885C2A2R3WA01#**	
				±0.1pF	**GRM1885C2A2R3BA01#**	
				±0.25pF	**GRM1885C2A2R3CA01#**	
			2.4pF	±0.05pF	**GRM1885C2A2R4WA01#**	
				±0.1pF	**GRM1885C2A2R4BA01#**	
				±0.25pF	**GRM1885C2A2R4CA01#**	
			2.5pF	±0.05pF	**GRM1885C2A2R5WA01#**	
				±0.1pF	**GRM1885C2A2R5BA01#**	
				±0.25pF	**GRM1885C2A2R5CA01#**	
			2.6pF	±0.05pF	**GRM1885C2A2R6WA01#**	
				±0.1pF	**GRM1885C2A2R6BA01#**	
				±0.25pF	**GRM1885C2A2R6CA01#**	
			2.7pF	±0.05pF	**GRM1885C2A2R7WA01#**	
				±0.1pF	**GRM1885C2A2R7BA01#**	
				±0.25pF	**GRM1885C2A2R7CA01#**	
			2.8pF	±0.05pF	**GRM1885C2A2R8WA01#**	
				±0.1pF	**GRM1885C2A2R8BA01#**	
				±0.25pF	**GRM1885C2A2R8CA01#**	
			2.9pF	±0.05pF	**GRM1885C2A2R9WA01#**	
				±0.1pF	**GRM1885C2A2R9BA01#**	
				±0.25pF	**GRM1885C2A2R9CA01#**	
			3.0pF	±0.05pF	**GRM1885C2A3R0WA01#**	
				±0.1pF	**GRM1885C2A3R0BA01#**	
				±0.25pF	**GRM1885C2A3R0CA01#**	
			3.1pF	±0.05pF	**GRM1885C2A3R1WA01#**	
				±0.1pF	**GRM1885C2A3R1BA01#**	
				±0.25pF	**GRM1885C2A3R1CA01#**	
			3.2pF	±0.05pF	**GRM1885C2A3R2WA01#**	
				±0.1pF	**GRM1885C2A3R2BA01#**	
				±0.25pF	**GRM1885C2A3R2CA01#**	
			3.3pF	±0.05pF	**GRM1885C2A3R3WA01#**	
				±0.1pF	**GRM1885C2A3R3BA01#**	
				±0.25pF	**GRM1885C2A3R3CA01#**	
			3.4pF	±0.05pF	**GRM1885C2A3R4WA01#**	
				±0.1pF	**GRM1885C2A3R4BA01#**	
				±0.25pF	**GRM1885C2A3R4CA01#**	
			3.5pF	±0.05pF	**GRM1885C2A3R5WA01#**	
				±0.1pF	**GRM1885C2A3R5BA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	C0G	3.5pF	±0.25pF	**GRM1885C2A3R5CA01#**	
			3.6pF	±0.05pF	**GRM1885C2A3R6WA01#**	
				±0.1pF	**GRM1885C2A3R6BA01#**	
				±0.25pF	**GRM1885C2A3R6CA01#**	
			3.7pF	±0.05pF	**GRM1885C2A3R7WA01#**	
				±0.1pF	**GRM1885C2A3R7BA01#**	
				±0.25pF	**GRM1885C2A3R7CA01#**	
			3.8pF	±0.05pF	**GRM1885C2A3R8WA01#**	
				±0.1pF	**GRM1885C2A3R8BA01#**	
				±0.25pF	**GRM1885C2A3R8CA01#**	
			3.9pF	±0.05pF	**GRM1885C2A3R9WA01#**	
				±0.1pF	**GRM1885C2A3R9BA01#**	
				±0.25pF	**GRM1885C2A3R9CA01#**	
			4.0pF	±0.05pF	**GRM1885C2A4R0WA01#**	
				±0.1pF	**GRM1885C2A4R0BA01#**	
				±0.25pF	**GRM1885C2A4R0CA01#**	
			4.1pF	±0.05pF	**GRM1885C2A4R1WA01#**	
				±0.1pF	**GRM1885C2A4R1BA01#**	
				±0.25pF	**GRM1885C2A4R1CA01#**	
			4.2pF	±0.05pF	**GRM1885C2A4R2WA01#**	
				±0.1pF	**GRM1885C2A4R2BA01#**	
				±0.25pF	**GRM1885C2A4R2CA01#**	
			4.3pF	±0.05pF	**GRM1885C2A4R3WA01#**	
				±0.1pF	**GRM1885C2A4R3BA01#**	
				±0.25pF	**GRM1885C2A4R3CA01#**	
			4.4pF	±0.05pF	**GRM1885C2A4R4WA01#**	
				±0.1pF	**GRM1885C2A4R4BA01#**	
				±0.25pF	**GRM1885C2A4R4CA01#**	
			4.5pF	±0.05pF	**GRM1885C2A4R5WA01#**	
				±0.1pF	**GRM1885C2A4R5BA01#**	
				±0.25pF	**GRM1885C2A4R5CA01#**	
			4.6pF	±0.05pF	**GRM1885C2A4R6WA01#**	
				±0.1pF	**GRM1885C2A4R6BA01#**	
				±0.25pF	**GRM1885C2A4R6CA01#**	
			4.7pF	±0.05pF	**GRM1885C2A4R7WA01#**	
				±0.1pF	**GRM1885C2A4R7BA01#**	
				±0.25pF	**GRM1885C2A4R7CA01#**	
			4.8pF	±0.05pF	**GRM1885C2A4R8WA01#**	
				±0.1pF	**GRM1885C2A4R8BA01#**	
				±0.25pF	**GRM1885C2A4R8CA01#**	
			4.9pF	±0.05pF	**GRM1885C2A4R9WA01#**	
				±0.1pF	**GRM1885C2A4R9BA01#**	
				±0.25pF	**GRM1885C2A4R9CA01#**	
			5.0pF	±0.05pF	**GRM1885C2A5R0WA01#**	
				±0.1pF	**GRM1885C2A5R0BA01#**	
				±0.25pF	**GRM1885C2A5R0CA01#**	
			5.1pF	±0.05pF	**GRM1885C2A5R1WA01#**	
				±0.1pF	**GRM1885C2A5R1BA01#**	
				±0.25pF	**GRM1885C2A5R1CA01#**	
				±0.5pF	**GRM1885C2A5R1DA01#**	
			5.2pF	±0.05pF	**GRM1885C2A5R2WA01#**	
				±0.1pF	**GRM1885C2A5R2BA01#**	
				±0.25pF	**GRM1885C2A5R2CA01#**	
				±0.5pF	**GRM1885C2A5R2DA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	C0G	5.3pF	±0.05pF	**GRM1885C2A5R3WA01#**	
				±0.1pF	**GRM1885C2A5R3BA01#**	
				±0.25pF	**GRM1885C2A5R3CA01#**	
				±0.5pF	**GRM1885C2A5R3DA01#**	
			5.4pF	±0.05pF	**GRM1885C2A5R4WA01#**	
				±0.1pF	**GRM1885C2A5R4BA01#**	
				±0.25pF	**GRM1885C2A5R4CA01#**	
				±0.5pF	**GRM1885C2A5R4DA01#**	
			5.5pF	±0.05pF	**GRM1885C2A5R5WA01#**	
				±0.1pF	**GRM1885C2A5R5BA01#**	
				±0.25pF	**GRM1885C2A5R5CA01#**	
				±0.5pF	**GRM1885C2A5R5DA01#**	
			5.6pF	±0.05pF	**GRM1885C2A5R6WA01#**	
				±0.1pF	**GRM1885C2A5R6BA01#**	
				±0.25pF	**GRM1885C2A5R6CA01#**	
				±0.5pF	**GRM1885C2A5R6DA01#**	
			5.7pF	±0.05pF	**GRM1885C2A5R7WA01#**	
				±0.1pF	**GRM1885C2A5R7BA01#**	
				±0.25pF	**GRM1885C2A5R7CA01#**	
				±0.5pF	**GRM1885C2A5R7DA01#**	
			5.8pF	±0.05pF	**GRM1885C2A5R8WA01#**	
				±0.1pF	**GRM1885C2A5R8BA01#**	
				±0.25pF	**GRM1885C2A5R8CA01#**	
				±0.5pF	**GRM1885C2A5R8DA01#**	
			5.9pF	±0.05pF	**GRM1885C2A5R9WA01#**	
				±0.1pF	**GRM1885C2A5R9BA01#**	
				±0.25pF	**GRM1885C2A5R9CA01#**	
				±0.5pF	**GRM1885C2A5R9DA01#**	
			6.0pF	±0.05pF	**GRM1885C2A6R0WA01#**	
				±0.1pF	**GRM1885C2A6R0BA01#**	
				±0.25pF	**GRM1885C2A6R0CA01#**	
				±0.5pF	**GRM1885C2A6R0DA01#**	
			6.1pF	±0.05pF	**GRM1885C2A6R1WA01#**	
				±0.1pF	**GRM1885C2A6R1BA01#**	
				±0.25pF	**GRM1885C2A6R1CA01#**	
				±0.5pF	**GRM1885C2A6R1DA01#**	
			6.2pF	±0.05pF	**GRM1885C2A6R2WA01#**	
				±0.1pF	**GRM1885C2A6R2BA01#**	
				±0.25pF	**GRM1885C2A6R2CA01#**	
				±0.5pF	**GRM1885C2A6R2DA01#**	
			6.3pF	±0.05pF	**GRM1885C2A6R3WA01#**	
				±0.1pF	**GRM1885C2A6R3BA01#**	
				±0.25pF	**GRM1885C2A6R3CA01#**	
				±0.5pF	**GRM1885C2A6R3DA01#**	
			6.4pF	±0.05pF	**GRM1885C2A6R4WA01#**	
				±0.1pF	**GRM1885C2A6R4BA01#**	
				±0.25pF	**GRM1885C2A6R4CA01#**	
				±0.5pF	**GRM1885C2A6R4DA01#**	
			6.5pF	±0.05pF	**GRM1885C2A6R5WA01#**	
				±0.1pF	**GRM1885C2A6R5BA01#**	
				±0.25pF	**GRM1885C2A6R5CA01#**	
				±0.5pF	**GRM1885C2A6R5DA01#**	
			6.6pF	±0.05pF	**GRM1885C2A6R6WA01#**	
				±0.1pF	**GRM1885C2A6R6BA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	C0G	6.6pF	±0.25pF	**GRM1885C2A6R6CA01#**	
				±0.5pF	**GRM1885C2A6R6DA01#**	
			6.7pF	±0.05pF	**GRM1885C2A6R7WA01#**	
				±0.1pF	**GRM1885C2A6R7BA01#**	
				±0.25pF	**GRM1885C2A6R7CA01#**	
				±0.5pF	**GRM1885C2A6R7DA01#**	
			6.8pF	±0.05pF	**GRM1885C2A6R8WA01#**	
				±0.1pF	**GRM1885C2A6R8BA01#**	
				±0.25pF	**GRM1885C2A6R8CA01#**	
				±0.5pF	**GRM1885C2A6R8DA01#**	
			6.9pF	±0.05pF	**GRM1885C2A6R9WA01#**	
				±0.1pF	**GRM1885C2A6R9BA01#**	
				±0.25pF	**GRM1885C2A6R9CA01#**	
				±0.5pF	**GRM1885C2A6R9DA01#**	
			7.0pF	±0.05pF	**GRM1885C2A7R0WA01#**	
				±0.1pF	**GRM1885C2A7R0BA01#**	
				±0.25pF	**GRM1885C2A7R0CA01#**	
				±0.5pF	**GRM1885C2A7R0DA01#**	
			7.1pF	±0.05pF	**GRM1885C2A7R1WA01#**	
				±0.1pF	**GRM1885C2A7R1BA01#**	
				±0.25pF	**GRM1885C2A7R1CA01#**	
				±0.5pF	**GRM1885C2A7R1DA01#**	
			7.2pF	±0.05pF	**GRM1885C2A7R2WA01#**	
				±0.1pF	**GRM1885C2A7R2BA01#**	
				±0.25pF	**GRM1885C2A7R2CA01#**	
				±0.5pF	**GRM1885C2A7R2DA01#**	
			7.3pF	±0.05pF	**GRM1885C2A7R3WA01#**	
				±0.1pF	**GRM1885C2A7R3BA01#**	
				±0.25pF	**GRM1885C2A7R3CA01#**	
				±0.5pF	**GRM1885C2A7R3DA01#**	
			7.4pF	±0.05pF	**GRM1885C2A7R4WA01#**	
				±0.1pF	**GRM1885C2A7R4BA01#**	
				±0.25pF	**GRM1885C2A7R4CA01#**	
				±0.5pF	**GRM1885C2A7R4DA01#**	
			7.5pF	±0.05pF	**GRM1885C2A7R5WA01#**	
				±0.1pF	**GRM1885C2A7R5BA01#**	
				±0.25pF	**GRM1885C2A7R5CA01#**	
				±0.5pF	**GRM1885C2A7R5DA01#**	
			7.6pF	±0.05pF	**GRM1885C2A7R6WA01#**	
				±0.1pF	**GRM1885C2A7R6BA01#**	
				±0.25pF	**GRM1885C2A7R6CA01#**	
				±0.5pF	**GRM1885C2A7R6DA01#**	
			7.7pF	±0.05pF	**GRM1885C2A7R7WA01#**	
				±0.1pF	**GRM1885C2A7R7BA01#**	
				±0.25pF	**GRM1885C2A7R7CA01#**	
				±0.5pF	**GRM1885C2A7R7DA01#**	
			7.8pF	±0.05pF	**GRM1885C2A7R8WA01#**	
				±0.1pF	**GRM1885C2A7R8BA01#**	
				±0.25pF	**GRM1885C2A7R8CA01#**	
				±0.5pF	**GRM1885C2A7R8DA01#**	
			7.9pF	±0.05pF	**GRM1885C2A7R9WA01#**	
				±0.1pF	**GRM1885C2A7R9BA01#**	
				±0.25pF	**GRM1885C2A7R9CA01#**	
				±0.5pF	**GRM1885C2A7R9DA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	C0G	8.0pF	±0.05pF	**GRM1885C2A8R0WA01#**	
				±0.1pF	**GRM1885C2A8R0BA01#**	
				±0.25pF	**GRM1885C2A8R0CA01#**	
				±0.5pF	**GRM1885C2A8R0DA01#**	
			8.1pF	±0.05pF	**GRM1885C2A8R1WA01#**	
				±0.1pF	**GRM1885C2A8R1BA01#**	
				±0.25pF	**GRM1885C2A8R1CA01#**	
				±0.5pF	**GRM1885C2A8R1DA01#**	
			8.2pF	±0.05pF	**GRM1885C2A8R2WA01#**	
				±0.1pF	**GRM1885C2A8R2BA01#**	
				±0.25pF	**GRM1885C2A8R2CA01#**	
				±0.5pF	**GRM1885C2A8R2DA01#**	
			8.3pF	±0.05pF	**GRM1885C2A8R3WA01#**	
				±0.1pF	**GRM1885C2A8R3BA01#**	
				±0.25pF	**GRM1885C2A8R3CA01#**	
				±0.5pF	**GRM1885C2A8R3DA01#**	
			8.4pF	±0.05pF	**GRM1885C2A8R4WA01#**	
				±0.1pF	**GRM1885C2A8R4BA01#**	
				±0.25pF	**GRM1885C2A8R4CA01#**	
				±0.5pF	**GRM1885C2A8R4DA01#**	
			8.5pF	±0.05pF	**GRM1885C2A8R5WA01#**	
				±0.1pF	**GRM1885C2A8R5BA01#**	
				±0.25pF	**GRM1885C2A8R5CA01#**	
				±0.5pF	**GRM1885C2A8R5DA01#**	
			8.6pF	±0.05pF	**GRM1885C2A8R6WA01#**	
				±0.1pF	**GRM1885C2A8R6BA01#**	
				±0.25pF	**GRM1885C2A8R6CA01#**	
				±0.5pF	**GRM1885C2A8R6DA01#**	
			8.7pF	±0.05pF	**GRM1885C2A8R7WA01#**	
				±0.1pF	**GRM1885C2A8R7BA01#**	
				±0.25pF	**GRM1885C2A8R7CA01#**	
				±0.5pF	**GRM1885C2A8R7DA01#**	
			8.8pF	±0.05pF	**GRM1885C2A8R8WA01#**	
				±0.1pF	**GRM1885C2A8R8BA01#**	
				±0.25pF	**GRM1885C2A8R8CA01#**	
				±0.5pF	**GRM1885C2A8R8DA01#**	
			8.9pF	±0.05pF	**GRM1885C2A8R9WA01#**	
				±0.1pF	**GRM1885C2A8R9BA01#**	
				±0.25pF	**GRM1885C2A8R9CA01#**	
				±0.5pF	**GRM1885C2A8R9DA01#**	
			9.0pF	±0.05pF	**GRM1885C2A9R0WA01#**	
				±0.1pF	**GRM1885C2A9R0BA01#**	
				±0.25pF	**GRM1885C2A9R0CA01#**	
				±0.5pF	**GRM1885C2A9R0DA01#**	
			9.1pF	±0.05pF	**GRM1885C2A9R1WA01#**	
				±0.1pF	**GRM1885C2A9R1BA01#**	
				±0.25pF	**GRM1885C2A9R1CA01#**	
				±0.5pF	**GRM1885C2A9R1DA01#**	
			9.2pF	±0.05pF	**GRM1885C2A9R2WA01#**	
				±0.1pF	**GRM1885C2A9R2BA01#**	
				±0.25pF	**GRM1885C2A9R2CA01#**	
				±0.5pF	**GRM1885C2A9R2DA01#**	
			9.3pF	±0.05pF	**GRM1885C2A9R3WA01#**	
				±0.1pF	**GRM1885C2A9R3BA01#**	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	C0G	9.3pF	±0.25pF	**GRM1885C2A9R3CA01#**	
				±0.5pF	**GRM1885C2A9R3DA01#**	
			9.4pF	±0.05pF	**GRM1885C2A9R4WA01#**	
				±0.1pF	**GRM1885C2A9R4BA01#**	
				±0.25pF	**GRM1885C2A9R4CA01#**	
				±0.5pF	**GRM1885C2A9R4DA01#**	
			9.5pF	±0.05pF	**GRM1885C2A9R5WA01#**	
				±0.1pF	**GRM1885C2A9R5BA01#**	
				±0.25pF	**GRM1885C2A9R5CA01#**	
				±0.5pF	**GRM1885C2A9R5DA01#**	
			9.6pF	±0.05pF	**GRM1885C2A9R6WA01#**	
				±0.1pF	**GRM1885C2A9R6BA01#**	
				±0.25pF	**GRM1885C2A9R6CA01#**	
				±0.5pF	**GRM1885C2A9R6DA01#**	
			9.7pF	±0.05pF	**GRM1885C2A9R7WA01#**	
				±0.1pF	**GRM1885C2A9R7BA01#**	
				±0.25pF	**GRM1885C2A9R7CA01#**	
				±0.5pF	**GRM1885C2A9R7DA01#**	
			9.8pF	±0.05pF	**GRM1885C2A9R8WA01#**	
				±0.1pF	**GRM1885C2A9R8BA01#**	
				±0.25pF	**GRM1885C2A9R8CA01#**	
				±0.5pF	**GRM1885C2A9R8DA01#**	
			9.9pF	±0.05pF	**GRM1885C2A9R9WA01#**	
				±0.1pF	**GRM1885C2A9R9BA01#**	
				±0.25pF	**GRM1885C2A9R9CA01#**	
				±0.5pF	**GRM1885C2A9R9DA01#**	
			10pF	±5%	**GRM1885C2A100JA01#**	
			12pF	±5%	**GRM1885C2A120JA01#**	
			15pF	±5%	**GRM1885C2A150JA01#**	
			18pF	±5%	**GRM1885C2A180JA01#**	
			22pF	±5%	**GRM1885C2A220JA01#**	
			27pF	±5%	**GRM1885C2A270JA01#**	
			33pF	±5%	**GRM1885C2A330JA01#**	
			39pF	±5%	**GRM1885C2A390JA01#**	
			47pF	±5%	**GRM1885C2A470JA01#**	
			56pF	±5%	**GRM1885C2A560JA01#**	
			68pF	±5%	**GRM1885C2A680JA01#**	
			82pF	±5%	**GRM1885C2A820JA01#**	
			100pF	±5%	**GRM1885C2A101JA01#**	
			120pF	±5%	**GRM1885C2A121JA01#**	
			150pF	±5%	**GRM1885C2A151JA01#**	
			180pF	±5%	**GRM1885C2A181JA01#**	
			220pF	±5%	**GRM1885C2A221JA01#**	
			270pF	±5%	**GRM1885C2A271JA01#**	
			330pF	±5%	**GRM1885C2A331JA01#**	
			390pF	±5%	**GRM1885C2A391JA01#**	
			470pF	±5%	**GRM1885C2A471JA01#**	
			560pF	±5%	**GRM1885C2A561JA01#**	
			680pF	±5%	**GRM1885C2A681JA01#**	
			820pF	±5%	**GRM1885C2A821JA01#**	
			1000pF	±5%	**GRM1885C2A102JA01#**	
			1200pF	±5%	**GRM1885C2A122JA01#**	
			1500pF	±5%	**GRM1885C2A152JA01#**	
		CK	0.50pF	±0.05pF	**GRM1884C2AR50WA01#**	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	CK	0.50pF	±0.1pF	GRM1884C2AR50BA01#	
			0.60pF	±0.05pF	GRM1884C2AR60WA01#	
				±0.1pF	GRM1884C2AR60BA01#	
			0.70pF	±0.05pF	GRM1884C2AR70WA01#	
				±0.1pF	GRM1884C2AR70BA01#	
			0.80pF	±0.05pF	GRM1884C2AR80WA01#	
				±0.1pF	GRM1884C2AR80BA01#	
			0.90pF	±0.05pF	GRM1884C2AR90WA01#	
				±0.1pF	GRM1884C2AR90BA01#	
			1.0pF	±0.05pF	GRM1884C2A1R0WA01#	
				±0.1pF	GRM1884C2A1R0BA01#	
				±0.25pF	GRM1884C2A1R0CA01#	
			1.1pF	±0.05pF	GRM1884C2A1R1WA01#	
				±0.1pF	GRM1884C2A1R1BA01#	
				±0.25pF	GRM1884C2A1R1CA01#	
			1.2pF	±0.05pF	GRM1884C2A1R2WA01#	
				±0.1pF	GRM1884C2A1R2BA01#	
				±0.25pF	GRM1884C2A1R2CA01#	
			1.3pF	±0.05pF	GRM1884C2A1R3WA01#	
				±0.1pF	GRM1884C2A1R3BA01#	
				±0.25pF	GRM1884C2A1R3CA01#	
			1.4pF	±0.05pF	GRM1884C2A1R4WA01#	
				±0.1pF	GRM1884C2A1R4BA01#	
				±0.25pF	GRM1884C2A1R4CA01#	
			1.5pF	±0.05pF	GRM1884C2A1R5WA01#	
				±0.1pF	GRM1884C2A1R5BA01#	
				±0.25pF	GRM1884C2A1R5CA01#	
			1.6pF	±0.05pF	GRM1884C2A1R6WA01#	
				±0.1pF	GRM1884C2A1R6BA01#	
				±0.25pF	GRM1884C2A1R6CA01#	
			1.7pF	±0.05pF	GRM1884C2A1R7WA01#	
				±0.1pF	GRM1884C2A1R7BA01#	
				±0.25pF	GRM1884C2A1R7CA01#	
			1.8pF	±0.05pF	GRM1884C2A1R8WA01#	
				±0.1pF	GRM1884C2A1R8BA01#	
				±0.25pF	GRM1884C2A1R8CA01#	
			1.9pF	±0.05pF	GRM1884C2A1R9WA01#	
				±0.1pF	GRM1884C2A1R9BA01#	
				±0.25pF	GRM1884C2A1R9CA01#	
			2.0pF	±0.05pF	GRM1884C2A2R0WA01#	
				±0.1pF	GRM1884C2A2R0BA01#	
				±0.25pF	GRM1884C2A2R0CA01#	
		CJ	2.1pF	±0.05pF	GRM1883C2A2R1WA01#	
				±0.1pF	GRM1883C2A2R1BA01#	
				±0.25pF	GRM1883C2A2R1CA01#	
			2.2pF	±0.05pF	GRM1883C2A2R2WA01#	
				±0.1pF	GRM1883C2A2R2BA01#	
				±0.25pF	GRM1883C2A2R2CA01#	
			2.3pF	±0.05pF	GRM1883C2A2R3WA01#	
				±0.1pF	GRM1883C2A2R3BA01#	
				±0.25pF	GRM1883C2A2R3CA01#	
			2.4pF	±0.05pF	GRM1883C2A2R4WA01#	
				±0.1pF	GRM1883C2A2R4BA01#	
				±0.25pF	GRM1883C2A2R4CA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	CJ	2.5pF	±0.05pF	GRM1883C2A2R5WA01#	
				±0.1pF	GRM1883C2A2R5BA01#	
				±0.25pF	GRM1883C2A2R5CA01#	
			2.6pF	±0.05pF	GRM1883C2A2R6WA01#	
				±0.1pF	GRM1883C2A2R6BA01#	
				±0.25pF	GRM1883C2A2R6CA01#	
			2.7pF	±0.05pF	GRM1883C2A2R7WA01#	
				±0.1pF	GRM1883C2A2R7BA01#	
				±0.25pF	GRM1883C2A2R7CA01#	
			2.8pF	±0.05pF	GRM1883C2A2R8WA01#	
				±0.1pF	GRM1883C2A2R8BA01#	
				±0.25pF	GRM1883C2A2R8CA01#	
			2.9pF	±0.05pF	GRM1883C2A2R9WA01#	
				±0.1pF	GRM1883C2A2R9BA01#	
				±0.25pF	GRM1883C2A2R9CA01#	
			3.0pF	±0.05pF	GRM1883C2A3R0WA01#	
				±0.1pF	GRM1883C2A3R0BA01#	
				±0.25pF	GRM1883C2A3R0CA01#	
			3.1pF	±0.05pF	GRM1883C2A3R1WA01#	
				±0.1pF	GRM1883C2A3R1BA01#	
				±0.25pF	GRM1883C2A3R1CA01#	
			3.2pF	±0.05pF	GRM1883C2A3R2WA01#	
				±0.1pF	GRM1883C2A3R2BA01#	
				±0.25pF	GRM1883C2A3R2CA01#	
			3.3pF	±0.05pF	GRM1883C2A3R3WA01#	
				±0.1pF	GRM1883C2A3R3BA01#	
				±0.25pF	GRM1883C2A3R3CA01#	
			3.4pF	±0.05pF	GRM1883C2A3R4WA01#	
				±0.1pF	GRM1883C2A3R4BA01#	
				±0.25pF	GRM1883C2A3R4CA01#	
			3.5pF	±0.05pF	GRM1883C2A3R5WA01#	
				±0.1pF	GRM1883C2A3R5BA01#	
				±0.25pF	GRM1883C2A3R5CA01#	
			3.6pF	±0.05pF	GRM1883C2A3R6WA01#	
				±0.1pF	GRM1883C2A3R6BA01#	
				±0.25pF	GRM1883C2A3R6CA01#	
			3.7pF	±0.05pF	GRM1883C2A3R7WA01#	
				±0.1pF	GRM1883C2A3R7BA01#	
				±0.25pF	GRM1883C2A3R7CA01#	
			3.8pF	±0.05pF	GRM1883C2A3R8WA01#	
				±0.1pF	GRM1883C2A3R8BA01#	
				±0.25pF	GRM1883C2A3R8CA01#	
			3.9pF	±0.05pF	GRM1883C2A3R9WA01#	
				±0.1pF	GRM1883C2A3R9BA01#	
				±0.25pF	GRM1883C2A3R9CA01#	
		CH	4.0pF	±0.05pF	GRM1882C2A4R0WA01#	
				±0.1pF	GRM1882C2A4R0BA01#	
				±0.25pF	GRM1882C2A4R0CA01#	
			4.1pF	±0.05pF	GRM1882C2A4R1WA01#	
				±0.1pF	GRM1882C2A4R1BA01#	
				±0.25pF	GRM1882C2A4R1CA01#	
			4.2pF	±0.05pF	GRM1882C2A4R2WA01#	
				±0.1pF	GRM1882C2A4R2BA01#	
				±0.25pF	GRM1882C2A4R2CA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	CH	4.3pF	±0.05pF	GRM1882C2A4R3WA01#	
				±0.1pF	GRM1882C2A4R3BA01#	
				±0.25pF	GRM1882C2A4R3CA01#	
			4.4pF	±0.05pF	GRM1882C2A4R4WA01#	
				±0.1pF	GRM1882C2A4R4BA01#	
				±0.25pF	GRM1882C2A4R4CA01#	
			4.5pF	±0.05pF	GRM1882C2A4R5WA01#	
				±0.1pF	GRM1882C2A4R5BA01#	
				±0.25pF	GRM1882C2A4R5CA01#	
			4.6pF	±0.05pF	GRM1882C2A4R6WA01#	
				±0.1pF	GRM1882C2A4R6BA01#	
				±0.25pF	GRM1882C2A4R6CA01#	
			4.7pF	±0.05pF	GRM1882C2A4R7WA01#	
				±0.1pF	GRM1882C2A4R7BA01#	
				±0.25pF	GRM1882C2A4R7CA01#	
			4.8pF	±0.05pF	GRM1882C2A4R8WA01#	
				±0.1pF	GRM1882C2A4R8BA01#	
				±0.25pF	GRM1882C2A4R8CA01#	
			4.9pF	±0.05pF	GRM1882C2A4R9WA01#	
				±0.1pF	GRM1882C2A4R9BA01#	
				±0.25pF	GRM1882C2A4R9CA01#	
			5.0pF	±0.05pF	GRM1882C2A5R0WA01#	
				±0.1pF	GRM1882C2A5R0BA01#	
				±0.25pF	GRM1882C2A5R0CA01#	
			5.1pF	±0.05pF	GRM1882C2A5R1WA01#	
				±0.1pF	GRM1882C2A5R1BA01#	
				±0.25pF	GRM1882C2A5R1CA01#	
				±0.5pF	GRM1882C2A5R1DA01#	
			5.2pF	±0.05pF	GRM1882C2A5R2WA01#	
				±0.1pF	GRM1882C2A5R2BA01#	
				±0.25pF	GRM1882C2A5R2CA01#	
				±0.5pF	GRM1882C2A5R2DA01#	
			5.3pF	±0.05pF	GRM1882C2A5R3WA01#	
				±0.1pF	GRM1882C2A5R3BA01#	
				±0.25pF	GRM1882C2A5R3CA01#	
				±0.5pF	GRM1882C2A5R3DA01#	
			5.4pF	±0.05pF	GRM1882C2A5R4WA01#	
				±0.1pF	GRM1882C2A5R4BA01#	
				±0.25pF	GRM1882C2A5R4CA01#	
				±0.5pF	GRM1882C2A5R4DA01#	
			5.5pF	±0.05pF	GRM1882C2A5R5WA01#	
				±0.1pF	GRM1882C2A5R5BA01#	
				±0.25pF	GRM1882C2A5R5CA01#	
				±0.5pF	GRM1882C2A5R5DA01#	
			5.6pF	±0.05pF	GRM1882C2A5R6WA01#	
				±0.1pF	GRM1882C2A5R6BA01#	
				±0.25pF	GRM1882C2A5R6CA01#	
				±0.5pF	GRM1882C2A5R6DA01#	
			5.7pF	±0.05pF	GRM1882C2A5R7WA01#	
				±0.1pF	GRM1882C2A5R7BA01#	
				±0.25pF	GRM1882C2A5R7CA01#	
				±0.5pF	GRM1882C2A5R7DA01#	
			5.8pF	±0.05pF	GRM1882C2A5R8WA01#	
				±0.1pF	GRM1882C2A5R8BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	CH	5.8pF	±0.25pF	GRM1882C2A5R8CA01#	
				±0.5pF	GRM1882C2A5R8DA01#	
			5.9pF	±0.05pF	GRM1882C2A5R9WA01#	
				±0.1pF	GRM1882C2A5R9BA01#	
				±0.25pF	GRM1882C2A5R9CA01#	
				±0.5pF	GRM1882C2A5R9DA01#	
			6.0pF	±0.05pF	GRM1882C2A6R0WA01#	
				±0.1pF	GRM1882C2A6R0BA01#	
				±0.25pF	GRM1882C2A6R0CA01#	
				±0.5pF	GRM1882C2A6R0DA01#	
			6.1pF	±0.05pF	GRM1882C2A6R1WA01#	
				±0.1pF	GRM1882C2A6R1BA01#	
				±0.25pF	GRM1882C2A6R1CA01#	
				±0.5pF	GRM1882C2A6R1DA01#	
			6.2pF	±0.05pF	GRM1882C2A6R2WA01#	
				±0.1pF	GRM1882C2A6R2BA01#	
				±0.25pF	GRM1882C2A6R2CA01#	
				±0.5pF	GRM1882C2A6R2DA01#	
			6.3pF	±0.05pF	GRM1882C2A6R3WA01#	
				±0.1pF	GRM1882C2A6R3BA01#	
				±0.25pF	GRM1882C2A6R3CA01#	
				±0.5pF	GRM1882C2A6R3DA01#	
			6.4pF	±0.05pF	GRM1882C2A6R4WA01#	
				±0.1pF	GRM1882C2A6R4BA01#	
				±0.25pF	GRM1882C2A6R4CA01#	
				±0.5pF	GRM1882C2A6R4DA01#	
			6.5pF	±0.05pF	GRM1882C2A6R5WA01#	
				±0.1pF	GRM1882C2A6R5BA01#	
				±0.25pF	GRM1882C2A6R5CA01#	
				±0.5pF	GRM1882C2A6R5DA01#	
			6.6pF	±0.05pF	GRM1882C2A6R6WA01#	
				±0.1pF	GRM1882C2A6R6BA01#	
				±0.25pF	GRM1882C2A6R6CA01#	
				±0.5pF	GRM1882C2A6R6DA01#	
			6.7pF	±0.05pF	GRM1882C2A6R7WA01#	
				±0.1pF	GRM1882C2A6R7BA01#	
				±0.25pF	GRM1882C2A6R7CA01#	
				±0.5pF	GRM1882C2A6R7DA01#	
			6.8pF	±0.05pF	GRM1882C2A6R8WA01#	
				±0.1pF	GRM1882C2A6R8BA01#	
				±0.25pF	GRM1882C2A6R8CA01#	
				±0.5pF	GRM1882C2A6R8DA01#	
			6.9pF	±0.05pF	GRM1882C2A6R9WA01#	
				±0.1pF	GRM1882C2A6R9BA01#	
				±0.25pF	GRM1882C2A6R9CA01#	
				±0.5pF	GRM1882C2A6R9DA01#	
			7.0pF	±0.05pF	GRM1882C2A7R0WA01#	
				±0.1pF	GRM1882C2A7R0BA01#	
				±0.25pF	GRM1882C2A7R0CA01#	
				±0.5pF	GRM1882C2A7R0DA01#	
			7.1pF	±0.05pF	GRM1882C2A7R1WA01#	
				±0.1pF	GRM1882C2A7R1BA01#	
				±0.25pF	GRM1882C2A7R1CA01#	
				±0.5pF	GRM1882C2A7R1DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	CH	7.2pF	±0.05pF	GRM1882C2A7R2WA01#	
				±0.1pF	GRM1882C2A7R2BA01#	
				±0.25pF	GRM1882C2A7R2CA01#	
				±0.5pF	GRM1882C2A7R2DA01#	
			7.3pF	±0.05pF	GRM1882C2A7R3WA01#	
				±0.1pF	GRM1882C2A7R3BA01#	
				±0.25pF	GRM1882C2A7R3CA01#	
				±0.5pF	GRM1882C2A7R3DA01#	
			7.4pF	±0.05pF	GRM1882C2A7R4WA01#	
				±0.1pF	GRM1882C2A7R4BA01#	
				±0.25pF	GRM1882C2A7R4CA01#	
				±0.5pF	GRM1882C2A7R4DA01#	
			7.5pF	±0.05pF	GRM1882C2A7R5WA01#	
				±0.1pF	GRM1882C2A7R5BA01#	
				±0.25pF	GRM1882C2A7R5CA01#	
				±0.5pF	GRM1882C2A7R5DA01#	
			7.6pF	±0.05pF	GRM1882C2A7R6WA01#	
				±0.1pF	GRM1882C2A7R6BA01#	
				±0.25pF	GRM1882C2A7R6CA01#	
				±0.5pF	GRM1882C2A7R6DA01#	
			7.7pF	±0.05pF	GRM1882C2A7R7WA01#	
				±0.1pF	GRM1882C2A7R7BA01#	
				±0.25pF	GRM1882C2A7R7CA01#	
				±0.5pF	GRM1882C2A7R7DA01#	
			7.8pF	±0.05pF	GRM1882C2A7R8WA01#	
				±0.1pF	GRM1882C2A7R8BA01#	
				±0.25pF	GRM1882C2A7R8CA01#	
				±0.5pF	GRM1882C2A7R8DA01#	
			7.9pF	±0.05pF	GRM1882C2A7R9WA01#	
				±0.1pF	GRM1882C2A7R9BA01#	
				±0.25pF	GRM1882C2A7R9CA01#	
				±0.5pF	GRM1882C2A7R9DA01#	
			8.0pF	±0.05pF	GRM1882C2A8R0WA01#	
				±0.1pF	GRM1882C2A8R0BA01#	
				±0.25pF	GRM1882C2A8R0CA01#	
				±0.5pF	GRM1882C2A8R0DA01#	
			8.1pF	±0.05pF	GRM1882C2A8R1WA01#	
				±0.1pF	GRM1882C2A8R1BA01#	
				±0.25pF	GRM1882C2A8R1CA01#	
				±0.5pF	GRM1882C2A8R1DA01#	
			8.2pF	±0.05pF	GRM1882C2A8R2WA01#	
				±0.1pF	GRM1882C2A8R2BA01#	
				±0.25pF	GRM1882C2A8R2CA01#	
				±0.5pF	GRM1882C2A8R2DA01#	
			8.3pF	±0.05pF	GRM1882C2A8R3WA01#	
				±0.1pF	GRM1882C2A8R3BA01#	
				±0.25pF	GRM1882C2A8R3CA01#	
				±0.5pF	GRM1882C2A8R3DA01#	
			8.4pF	±0.05pF	GRM1882C2A8R4WA01#	
				±0.1pF	GRM1882C2A8R4BA01#	
				±0.25pF	GRM1882C2A8R4CA01#	
				±0.5pF	GRM1882C2A8R4DA01#	
			8.5pF	±0.05pF	GRM1882C2A8R5WA01#	
				±0.1pF	GRM1882C2A8R5BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	CH	8.5pF	±0.25pF	GRM1882C2A8R5CA01#	
				±0.5pF	GRM1882C2A8R5DA01#	
			8.6pF	±0.05pF	GRM1882C2A8R6WA01#	
				±0.1pF	GRM1882C2A8R6BA01#	
				±0.25pF	GRM1882C2A8R6CA01#	
				±0.5pF	GRM1882C2A8R6DA01#	
			8.7pF	±0.05pF	GRM1882C2A8R7WA01#	
				±0.1pF	GRM1882C2A8R7BA01#	
				±0.25pF	GRM1882C2A8R7CA01#	
				±0.5pF	GRM1882C2A8R7DA01#	
			8.8pF	±0.05pF	GRM1882C2A8R8WA01#	
				±0.1pF	GRM1882C2A8R8BA01#	
				±0.25pF	GRM1882C2A8R8CA01#	
				±0.5pF	GRM1882C2A8R8DA01#	
			8.9pF	±0.05pF	GRM1882C2A8R9WA01#	
				±0.1pF	GRM1882C2A8R9BA01#	
				±0.25pF	GRM1882C2A8R9CA01#	
				±0.5pF	GRM1882C2A8R9DA01#	
			9.0pF	±0.05pF	GRM1882C2A9R0WA01#	
				±0.1pF	GRM1882C2A9R0BA01#	
				±0.25pF	GRM1882C2A9R0CA01#	
				±0.5pF	GRM1882C2A9R0DA01#	
			9.1pF	±0.05pF	GRM1882C2A9R1WA01#	
				±0.1pF	GRM1882C2A9R1BA01#	
				±0.25pF	GRM1882C2A9R1CA01#	
				±0.5pF	GRM1882C2A9R1DA01#	
			9.2pF	±0.05pF	GRM1882C2A9R2WA01#	
				±0.1pF	GRM1882C2A9R2BA01#	
				±0.25pF	GRM1882C2A9R2CA01#	
				±0.5pF	GRM1882C2A9R2DA01#	
			9.3pF	±0.05pF	GRM1882C2A9R3WA01#	
				±0.1pF	GRM1882C2A9R3BA01#	
				±0.25pF	GRM1882C2A9R3CA01#	
				±0.5pF	GRM1882C2A9R3DA01#	
			9.4pF	±0.05pF	GRM1882C2A9R4WA01#	
				±0.1pF	GRM1882C2A9R4BA01#	
				±0.25pF	GRM1882C2A9R4CA01#	
				±0.5pF	GRM1882C2A9R4DA01#	
			9.5pF	±0.05pF	GRM1882C2A9R5WA01#	
				±0.1pF	GRM1882C2A9R5BA01#	
				±0.25pF	GRM1882C2A9R5CA01#	
				±0.5pF	GRM1882C2A9R5DA01#	
			9.6pF	±0.05pF	GRM1882C2A9R6WA01#	
				±0.1pF	GRM1882C2A9R6BA01#	
				±0.25pF	GRM1882C2A9R6CA01#	
				±0.5pF	GRM1882C2A9R6DA01#	
			9.7pF	±0.05pF	GRM1882C2A9R7WA01#	
				±0.1pF	GRM1882C2A9R7BA01#	
				±0.25pF	GRM1882C2A9R7CA01#	
				±0.5pF	GRM1882C2A9R7DA01#	
			9.8pF	±0.05pF	GRM1882C2A9R8WA01#	
				±0.1pF	GRM1882C2A9R8BA01#	
				±0.25pF	GRM1882C2A9R8CA01#	
				±0.5pF	GRM1882C2A9R8DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	CH	9.9pF	±0.05pF	GRM1882C2A9R9WA01#	
				±0.1pF	GRM1882C2A9R9BA01#	
				±0.25pF	GRM1882C2A9R9CA01#	
				±0.5pF	GRM1882C2A9R9DA01#	
			10pF	±5%	GRM1882C2A100JA01#	
			12pF	±5%	GRM1882C2A120JA01#	
			15pF	±5%	GRM1882C2A150JA01#	
			18pF	±5%	GRM1882C2A180JA01#	
			22pF	±5%	GRM1882C2A220JA01#	
			27pF	±5%	GRM1882C2A270JA01#	
			33pF	±5%	GRM1882C2A330JA01#	
			39pF	±5%	GRM1882C2A390JA01#	
			47pF	±5%	GRM1882C2A470JA01#	
			56pF	±5%	GRM1882C2A560JA01#	
			68pF	±5%	GRM1882C2A680JA01#	
			82pF	±5%	GRM1882C2A820JA01#	
			100pF	±5%	GRM1882C2A101JA01#	
			120pF	±5%	GRM1882C2A121JA01#	
			150pF	±5%	GRM1882C2A151JA01#	
			180pF	±5%	GRM1882C2A181JA01#	
			220pF	±5%	GRM1882C2A221JA01#	
			270pF	±5%	GRM1882C2A271JA01#	
			330pF	±5%	GRM1882C2A331JA01#	
			390pF	±5%	GRM1882C2A391JA01#	
			470pF	±5%	GRM1882C2A471JA01#	
			560pF	±5%	GRM1882C2A561JA01#	
			680pF	±5%	GRM1882C2A681JA01#	
			820pF	±5%	GRM1882C2A821JA01#	
			1000pF	±5%	GRM1882C2A102JA01#	
			1200pF	±5%	GRM1882C2A122JA01#	
			1500pF	±5%	GRM1882C2A152JA01#	
	50Vdc	C0G	0.50pF	±0.05pF	GRM1885C1HR50WA01#	
				±0.1pF	GRM1885C1HR50BA01#	
			0.60pF	±0.05pF	GRM1885C1HR60WA01#	
				±0.1pF	GRM1885C1HR60BA01#	
			0.70pF	±0.05pF	GRM1885C1HR70WA01#	
				±0.1pF	GRM1885C1HR70BA01#	
			0.80pF	±0.05pF	GRM1885C1HR80WA01#	
				±0.1pF	GRM1885C1HR80BA01#	
			0.90pF	±0.05pF	GRM1885C1HR90WA01#	
				±0.1pF	GRM1885C1HR90BA01#	
			1.0pF	±0.05pF	GRM1885C1H1R0WA01#	
				±0.1pF	GRM1885C1H1R0BA01#	
				±0.25pF	GRM1885C1H1R0CA01#	
			1.1pF	±0.05pF	GRM1885C1H1R1WA01#	
				±0.1pF	GRM1885C1H1R1BA01#	
				±0.25pF	GRM1885C1H1R1CA01#	
			1.2pF	±0.05pF	GRM1885C1H1R2WA01#	
				±0.1pF	GRM1885C1H1R2BA01#	
				±0.25pF	GRM1885C1H1R2CA01#	
			1.3pF	±0.05pF	GRM1885C1H1R3WA01#	
				±0.1pF	GRM1885C1H1R3BA01#	
				±0.25pF	GRM1885C1H1R3CA01#	
			1.4pF	±0.05pF	GRM1885C1H1R4WA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	C0G	1.4pF	±0.1pF	GRM1885C1H1R4BA01#	
				±0.25pF	GRM1885C1H1R4CA01#	
			1.5pF	±0.05pF	GRM1885C1H1R5WA01#	
				±0.1pF	GRM1885C1H1R5BA01#	
				±0.25pF	GRM1885C1H1R5CA01#	
			1.6pF	±0.05pF	GRM1885C1H1R6WA01#	
				±0.1pF	GRM1885C1H1R6BA01#	
				±0.25pF	GRM1885C1H1R6CA01#	
			1.7pF	±0.05pF	GRM1885C1H1R7WA01#	
				±0.1pF	GRM1885C1H1R7BA01#	
				±0.25pF	GRM1885C1H1R7CA01#	
			1.8pF	±0.05pF	GRM1885C1H1R8WA01#	
				±0.1pF	GRM1885C1H1R8BA01#	
				±0.25pF	GRM1885C1H1R8CA01#	
			1.9pF	±0.05pF	GRM1885C1H1R9WA01#	
				±0.1pF	GRM1885C1H1R9BA01#	
				±0.25pF	GRM1885C1H1R9CA01#	
			2.0pF	±0.05pF	GRM1885C1H2R0WA01#	
				±0.1pF	GRM1885C1H2R0BA01#	
				±0.25pF	GRM1885C1H2R0CA01#	
			2.1pF	±0.05pF	GRM1885C1H2R1WA01#	
				±0.1pF	GRM1885C1H2R1BA01#	
				±0.25pF	GRM1885C1H2R1CA01#	
			2.2pF	±0.05pF	GRM1885C1H2R2WA01#	
				±0.1pF	GRM1885C1H2R2BA01#	
				±0.25pF	GRM1885C1H2R2CA01#	
			2.3pF	±0.05pF	GRM1885C1H2R3WA01#	
				±0.1pF	GRM1885C1H2R3BA01#	
				±0.25pF	GRM1885C1H2R3CA01#	
			2.4pF	±0.05pF	GRM1885C1H2R4WA01#	
				±0.1pF	GRM1885C1H2R4BA01#	
				±0.25pF	GRM1885C1H2R4CA01#	
			2.5pF	±0.05pF	GRM1885C1H2R5WA01#	
				±0.1pF	GRM1885C1H2R5BA01#	
				±0.25pF	GRM1885C1H2R5CA01#	
			2.6pF	±0.05pF	GRM1885C1H2R6WA01#	
				±0.1pF	GRM1885C1H2R6BA01#	
				±0.25pF	GRM1885C1H2R6CA01#	
			2.7pF	±0.05pF	GRM1885C1H2R7WA01#	
				±0.1pF	GRM1885C1H2R7BA01#	
				±0.25pF	GRM1885C1H2R7CA01#	
			2.8pF	±0.05pF	GRM1885C1H2R8WA01#	
				±0.1pF	GRM1885C1H2R8BA01#	
				±0.25pF	GRM1885C1H2R8CA01#	
			2.9pF	±0.05pF	GRM1885C1H2R9WA01#	
				±0.1pF	GRM1885C1H2R9BA01#	
				±0.25pF	GRM1885C1H2R9CA01#	
			3.0pF	±0.05pF	GRM1885C1H3R0WA01#	
				±0.1pF	GRM1885C1H3R0BA01#	
				±0.25pF	GRM1885C1H3R0CA01#	
			3.1pF	±0.05pF	GRM1885C1H3R1WA01#	
				±0.1pF	GRM1885C1H3R1BA01#	
				±0.25pF	GRM1885C1H3R1CA01#	
			3.2pF	±0.05pF	GRM1885C1H3R2WA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	C0G	3.2pF	±0.1pF	GRM1885C1H3R2BA01#	
				±0.25pF	GRM1885C1H3R2CA01#	
			3.3pF	±0.05pF	GRM1885C1H3R3WA01#	
				±0.1pF	GRM1885C1H3R3BA01#	
				±0.25pF	GRM1885C1H3R3CA01#	
			3.4pF	±0.05pF	GRM1885C1H3R4WA01#	
				±0.1pF	GRM1885C1H3R4BA01#	
				±0.25pF	GRM1885C1H3R4CA01#	
			3.5pF	±0.05pF	GRM1885C1H3R5WA01#	
				±0.1pF	GRM1885C1H3R5BA01#	
				±0.25pF	GRM1885C1H3R5CA01#	
			3.6pF	±0.05pF	GRM1885C1H3R6WA01#	
				±0.1pF	GRM1885C1H3R6BA01#	
				±0.25pF	GRM1885C1H3R6CA01#	
			3.7pF	±0.05pF	GRM1885C1H3R7WA01#	
				±0.1pF	GRM1885C1H3R7BA01#	
				±0.25pF	GRM1885C1H3R7CA01#	
			3.8pF	±0.05pF	GRM1885C1H3R8WA01#	
				±0.1pF	GRM1885C1H3R8BA01#	
				±0.25pF	GRM1885C1H3R8CA01#	
			3.9pF	±0.05pF	GRM1885C1H3R9WA01#	
				±0.1pF	GRM1885C1H3R9BA01#	
				±0.25pF	GRM1885C1H3R9CA01#	
			4.0pF	±0.05pF	GRM1885C1H4R0WA01#	
				±0.1pF	GRM1885C1H4R0BA01#	
				±0.25pF	GRM1885C1H4R0CA01#	
			4.1pF	±0.05pF	GRM1885C1H4R1WA01#	
				±0.1pF	GRM1885C1H4R1BA01#	
				±0.25pF	GRM1885C1H4R1CA01#	
			4.2pF	±0.05pF	GRM1885C1H4R2WA01#	
				±0.1pF	GRM1885C1H4R2BA01#	
				±0.25pF	GRM1885C1H4R2CA01#	
			4.3pF	±0.05pF	GRM1885C1H4R3WA01#	
				±0.1pF	GRM1885C1H4R3BA01#	
				±0.25pF	GRM1885C1H4R3CA01#	
			4.4pF	±0.05pF	GRM1885C1H4R4WA01#	
				±0.1pF	GRM1885C1H4R4BA01#	
				±0.25pF	GRM1885C1H4R4CA01#	
			4.5pF	±0.05pF	GRM1885C1H4R5WA01#	
				±0.1pF	GRM1885C1H4R5BA01#	
				±0.25pF	GRM1885C1H4R5CA01#	
			4.6pF	±0.05pF	GRM1885C1H4R6WA01#	
				±0.1pF	GRM1885C1H4R6BA01#	
				±0.25pF	GRM1885C1H4R6CA01#	
			4.7pF	±0.05pF	GRM1885C1H4R7WA01#	
				±0.1pF	GRM1885C1H4R7BA01#	
				±0.25pF	GRM1885C1H4R7CA01#	
			4.8pF	±0.05pF	GRM1885C1H4R8WA01#	
				±0.1pF	GRM1885C1H4R8BA01#	
				±0.25pF	GRM1885C1H4R8CA01#	
			4.9pF	±0.05pF	GRM1885C1H4R9WA01#	
				±0.1pF	GRM1885C1H4R9BA01#	
				±0.25pF	GRM1885C1H4R9CA01#	
			5.0pF	±0.05pF	GRM1885C1H5R0WA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	C0G	5.0pF	±0.1pF	GRM1885C1H5R0BA01#	
				±0.25pF	GRM1885C1H5R0CA01#	
			5.1pF	±0.05pF	GRM1885C1H5R1WA01#	
				±0.1pF	GRM1885C1H5R1BA01#	
				±0.25pF	GRM1885C1H5R1CA01#	
				±0.5pF	GRM1885C1H5R1DA01#	
			5.2pF	±0.05pF	GRM1885C1H5R2WA01#	
				±0.1pF	GRM1885C1H5R2BA01#	
				±0.25pF	GRM1885C1H5R2CA01#	
				±0.5pF	GRM1885C1H5R2DA01#	
			5.3pF	±0.05pF	GRM1885C1H5R3WA01#	
				±0.1pF	GRM1885C1H5R3BA01#	
				±0.25pF	GRM1885C1H5R3CA01#	
				±0.5pF	GRM1885C1H5R3DA01#	
			5.4pF	±0.05pF	GRM1885C1H5R4WA01#	
				±0.1pF	GRM1885C1H5R4BA01#	
				±0.25pF	GRM1885C1H5R4CA01#	
				±0.5pF	GRM1885C1H5R4DA01#	
			5.5pF	±0.05pF	GRM1885C1H5R5WA01#	
				±0.1pF	GRM1885C1H5R5BA01#	
				±0.25pF	GRM1885C1H5R5CA01#	
				±0.5pF	GRM1885C1H5R5DA01#	
			5.6pF	±0.05pF	GRM1885C1H5R6WA01#	
				±0.1pF	GRM1885C1H5R6BA01#	
				±0.25pF	GRM1885C1H5R6CA01#	
				±0.5pF	GRM1885C1H5R6DA01#	
			5.7pF	±0.05pF	GRM1885C1H5R7WA01#	
				±0.1pF	GRM1885C1H5R7BA01#	
				±0.25pF	GRM1885C1H5R7CA01#	
				±0.5pF	GRM1885C1H5R7DA01#	
			5.8pF	±0.05pF	GRM1885C1H5R8WA01#	
				±0.1pF	GRM1885C1H5R8BA01#	
				±0.25pF	GRM1885C1H5R8CA01#	
				±0.5pF	GRM1885C1H5R8DA01#	
			5.9pF	±0.05pF	GRM1885C1H5R9WA01#	
				±0.1pF	GRM1885C1H5R9BA01#	
				±0.25pF	GRM1885C1H5R9CA01#	
				±0.5pF	GRM1885C1H5R9DA01#	
			6.0pF	±0.05pF	GRM1885C1H6R0WA01#	
				±0.1pF	GRM1885C1H6R0BA01#	
				±0.25pF	GRM1885C1H6R0CA01#	
				±0.5pF	GRM1885C1H6R0DA01#	
			6.1pF	±0.05pF	GRM1885C1H6R1WA01#	
				±0.1pF	GRM1885C1H6R1BA01#	
				±0.25pF	GRM1885C1H6R1CA01#	
				±0.5pF	GRM1885C1H6R1DA01#	
			6.2pF	±0.05pF	GRM1885C1H6R2WA01#	
				±0.1pF	GRM1885C1H6R2BA01#	
				±0.25pF	GRM1885C1H6R2CA01#	
				±0.5pF	GRM1885C1H6R2DA01#	
			6.3pF	±0.05pF	GRM1885C1H6R3WA01#	
				±0.1pF	GRM1885C1H6R3BA01#	
				±0.25pF	GRM1885C1H6R3CA01#	
				±0.5pF	GRM1885C1H6R3DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	C0G	6.4pF	±0.05pF	GRM1885C1H6R4WA01#	
				±0.1pF	GRM1885C1H6R4BA01#	
				±0.25pF	GRM1885C1H6R4CA01#	
				±0.5pF	GRM1885C1H6R4DA01#	
			6.5pF	±0.05pF	GRM1885C1H6R5WA01#	
				±0.1pF	GRM1885C1H6R5BA01#	
				±0.25pF	GRM1885C1H6R5CA01#	
				±0.5pF	GRM1885C1H6R5DA01#	
			6.6pF	±0.05pF	GRM1885C1H6R6WA01#	
				±0.1pF	GRM1885C1H6R6BA01#	
				±0.25pF	GRM1885C1H6R6CA01#	
				±0.5pF	GRM1885C1H6R6DA01#	
			6.7pF	±0.05pF	GRM1885C1H6R7WA01#	
				±0.1pF	GRM1885C1H6R7BA01#	
				±0.25pF	GRM1885C1H6R7CA01#	
				±0.5pF	GRM1885C1H6R7DA01#	
			6.8pF	±0.05pF	GRM1885C1H6R8WA01#	
				±0.1pF	GRM1885C1H6R8BA01#	
				±0.25pF	GRM1885C1H6R8CA01#	
				±0.5pF	GRM1885C1H6R8DA01#	
			6.9pF	±0.05pF	GRM1885C1H6R9WA01#	
				±0.1pF	GRM1885C1H6R9BA01#	
				±0.25pF	GRM1885C1H6R9CA01#	
				±0.5pF	GRM1885C1H6R9DA01#	
			7.0pF	±0.05pF	GRM1885C1H7R0WA01#	
				±0.1pF	GRM1885C1H7R0BA01#	
				±0.25pF	GRM1885C1H7R0CA01#	
				±0.5pF	GRM1885C1H7R0DA01#	
			7.1pF	±0.05pF	GRM1885C1H7R1WA01#	
				±0.1pF	GRM1885C1H7R1BA01#	
				±0.25pF	GRM1885C1H7R1CA01#	
				±0.5pF	GRM1885C1H7R1DA01#	
			7.2pF	±0.05pF	GRM1885C1H7R2WA01#	
				±0.1pF	GRM1885C1H7R2BA01#	
				±0.25pF	GRM1885C1H7R2CA01#	
				±0.5pF	GRM1885C1H7R2DA01#	
			7.3pF	±0.05pF	GRM1885C1H7R3WA01#	
				±0.1pF	GRM1885C1H7R3BA01#	
				±0.25pF	GRM1885C1H7R3CA01#	
				±0.5pF	GRM1885C1H7R3DA01#	
			7.4pF	±0.05pF	GRM1885C1H7R4WA01#	
				±0.1pF	GRM1885C1H7R4BA01#	
				±0.25pF	GRM1885C1H7R4CA01#	
				±0.5pF	GRM1885C1H7R4DA01#	
			7.5pF	±0.05pF	GRM1885C1H7R5WA01#	
				±0.1pF	GRM1885C1H7R5BA01#	
				±0.25pF	GRM1885C1H7R5CA01#	
				±0.5pF	GRM1885C1H7R5DA01#	
			7.6pF	±0.05pF	GRM1885C1H7R6WA01#	
				±0.1pF	GRM1885C1H7R6BA01#	
				±0.25pF	GRM1885C1H7R6CA01#	
				±0.5pF	GRM1885C1H7R6DA01#	
			7.7pF	±0.05pF	GRM1885C1H7R7WA01#	
				±0.1pF	GRM1885C1H7R7BA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	C0G	7.7pF	±0.25pF	GRM1885C1H7R7CA01#	
				±0.5pF	GRM1885C1H7R7DA01#	
			7.8pF	±0.05pF	GRM1885C1H7R8WA01#	
				±0.1pF	GRM1885C1H7R8BA01#	
				±0.25pF	GRM1885C1H7R8CA01#	
				±0.5pF	GRM1885C1H7R8DA01#	
			7.9pF	±0.05pF	GRM1885C1H7R9WA01#	
				±0.1pF	GRM1885C1H7R9BA01#	
				±0.25pF	GRM1885C1H7R9CA01#	
				±0.5pF	GRM1885C1H7R9DA01#	
			8.0pF	±0.05pF	GRM1885C1H8R0WA01#	
				±0.1pF	GRM1885C1H8R0BA01#	
				±0.25pF	GRM1885C1H8R0CA01#	
				±0.5pF	GRM1885C1H8R0DA01#	
			8.1pF	±0.05pF	GRM1885C1H8R1WA01#	
				±0.1pF	GRM1885C1H8R1BA01#	
				±0.25pF	GRM1885C1H8R1CA01#	
				±0.5pF	GRM1885C1H8R1DA01#	
			8.2pF	±0.05pF	GRM1885C1H8R2WA01#	
				±0.1pF	GRM1885C1H8R2BA01#	
				±0.25pF	GRM1885C1H8R2CA01#	
				±0.5pF	GRM1885C1H8R2DA01#	
			8.3pF	±0.05pF	GRM1885C1H8R3WA01#	
				±0.1pF	GRM1885C1H8R3BA01#	
				±0.25pF	GRM1885C1H8R3CA01#	
				±0.5pF	GRM1885C1H8R3DA01#	
			8.4pF	±0.05pF	GRM1885C1H8R4WA01#	
				±0.1pF	GRM1885C1H8R4BA01#	
				±0.25pF	GRM1885C1H8R4CA01#	
				±0.5pF	GRM1885C1H8R4DA01#	
			8.5pF	±0.05pF	GRM1885C1H8R5WA01#	
				±0.1pF	GRM1885C1H8R5BA01#	
				±0.25pF	GRM1885C1H8R5CA01#	
				±0.5pF	GRM1885C1H8R5DA01#	
			8.6pF	±0.05pF	GRM1885C1H8R6WA01#	
				±0.1pF	GRM1885C1H8R6BA01#	
				±0.25pF	GRM1885C1H8R6CA01#	
				±0.5pF	GRM1885C1H8R6DA01#	
			8.7pF	±0.05pF	GRM1885C1H8R7WA01#	
				±0.1pF	GRM1885C1H8R7BA01#	
				±0.25pF	GRM1885C1H8R7CA01#	
				±0.5pF	GRM1885C1H8R7DA01#	
			8.8pF	±0.05pF	GRM1885C1H8R8WA01#	
				±0.1pF	GRM1885C1H8R8BA01#	
				±0.25pF	GRM1885C1H8R8CA01#	
				±0.5pF	GRM1885C1H8R8DA01#	
			8.9pF	±0.05pF	GRM1885C1H8R9WA01#	
				±0.1pF	GRM1885C1H8R9BA01#	
				±0.25pF	GRM1885C1H8R9CA01#	
				±0.5pF	GRM1885C1H8R9DA01#	
			9.0pF	±0.05pF	GRM1885C1H9R0WA01#	
				±0.1pF	GRM1885C1H9R0BA01#	
				±0.25pF	GRM1885C1H9R0CA01#	
				±0.5pF	GRM1885C1H9R0DA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	C0G	9.1pF	±0.05pF	GRM1885C1H9R1WA01#	
				±0.1pF	GRM1885C1H9R1BA01#	
				±0.25pF	GRM1885C1H9R1CA01#	
				±0.5pF	GRM1885C1H9R1DA01#	
			9.2pF	±0.05pF	GRM1885C1H9R2WA01#	
				±0.1pF	GRM1885C1H9R2BA01#	
				±0.25pF	GRM1885C1H9R2CA01#	
				±0.5pF	GRM1885C1H9R2DA01#	
			9.3pF	±0.05pF	GRM1885C1H9R3WA01#	
				±0.1pF	GRM1885C1H9R3BA01#	
				±0.25pF	GRM1885C1H9R3CA01#	
				±0.5pF	GRM1885C1H9R3DA01#	
			9.4pF	±0.05pF	GRM1885C1H9R4WA01#	
				±0.1pF	GRM1885C1H9R4BA01#	
				±0.25pF	GRM1885C1H9R4CA01#	
				±0.5pF	GRM1885C1H9R4DA01#	
			9.5pF	±0.05pF	GRM1885C1H9R5WA01#	
				±0.1pF	GRM1885C1H9R5BA01#	
				±0.25pF	GRM1885C1H9R5CA01#	
				±0.5pF	GRM1885C1H9R5DA01#	
			9.6pF	±0.05pF	GRM1885C1H9R6WA01#	
				±0.1pF	GRM1885C1H9R6BA01#	
				±0.25pF	GRM1885C1H9R6CA01#	
				±0.5pF	GRM1885C1H9R6DA01#	
			9.7pF	±0.05pF	GRM1885C1H9R7WA01#	
				±0.1pF	GRM1885C1H9R7BA01#	
				±0.25pF	GRM1885C1H9R7CA01#	
				±0.5pF	GRM1885C1H9R7DA01#	
			9.8pF	±0.05pF	GRM1885C1H9R8WA01#	
				±0.1pF	GRM1885C1H9R8BA01#	
				±0.25pF	GRM1885C1H9R8CA01#	
				±0.5pF	GRM1885C1H9R8DA01#	
			9.9pF	±0.05pF	GRM1885C1H9R9WA01#	
				±0.1pF	GRM1885C1H9R9BA01#	
				±0.25pF	GRM1885C1H9R9CA01#	
				±0.5pF	GRM1885C1H9R9DA01#	
			10pF	±5%	GRM1885C1H100JA01#	
			12pF	±5%	GRM1885C1H120JA01#	
			15pF	±5%	GRM1885C1H150JA01#	
			18pF	±5%	GRM1885C1H180JA01#	
			22pF	±5%	GRM1885C1H220JA01#	
			27pF	±5%	GRM1885C1H270JA01#	
			33pF	±5%	GRM1885C1H330JA01#	
			39pF	±5%	GRM1885C1H390JA01#	
			47pF	±5%	GRM1885C1H470JA01#	
			56pF	±5%	GRM1885C1H560JA01#	
			68pF	±5%	GRM1885C1H680JA01#	
			82pF	±5%	GRM1885C1H820JA01#	
			100pF	±5%	GRM1885C1H101JA01#	
			120pF	±5%	GRM1885C1H121JA01#	
			150pF	±5%	GRM1885C1H151JA01#	
			180pF	±5%	GRM1885C1H181JA01#	
			220pF	±5%	GRM1885C1H221JA01#	
			270pF	±5%	GRM1885C1H271JA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	C0G	330pF	±5%	GRM1885C1H331JA01#	
			390pF	±5%	GRM1885C1H391JA01#	
			470pF	±5%	GRM1885C1H471JA01#	
			560pF	±5%	GRM1885C1H561JA01#	
			680pF	±5%	GRM1885C1H681JA01#	
			820pF	±5%	GRM1885C1H821JA01#	
			1000pF	±5%	GRM1885C1H102JA01#	
			1200pF	±5%	GRM1885C1H122JA01#	
			1500pF	±5%	GRM1885C1H152JA01#	
			1800pF	±5%	GRM1885C1H182JA01#	
			2200pF	±5%	GRM1885C1H222JA01#	
			2700pF	±5%	GRM1885C1H272JA01#	
			3300pF	±5%	GRM1885C1H332JA01#	
			3900pF	±5%	GRM1885C1H392JA01#	
			4700pF	±5%	GRM1885C1H472JA01#	
			5600pF	±5%	GRM1885C1H562JA01#	
			6800pF	±5%	GRM1885C1H682JA01#	
			8200pF	±5%	GRM1885C1H822JA01#	
			10000pF	±5%	GRM1885C1H103JA01#	
		CK	0.50pF	±0.05pF	GRM1884C1HR50WA01#	
				±0.1pF	GRM1884C1HR50BA01#	
			0.60pF	±0.05pF	GRM1884C1HR60WA01#	
				±0.1pF	GRM1884C1HR60BA01#	
			0.70pF	±0.05pF	GRM1884C1HR70WA01#	
				±0.1pF	GRM1884C1HR70BA01#	
			0.80pF	±0.05pF	GRM1884C1HR80WA01#	
				±0.1pF	GRM1884C1HR80BA01#	
			0.90pF	±0.05pF	GRM1884C1HR90WA01#	
				±0.1pF	GRM1884C1HR90BA01#	
			1.0pF	±0.05pF	GRM1884C1H1R0WA01#	
				±0.1pF	GRM1884C1H1R0BA01#	
				±0.25pF	GRM1884C1H1R0CA01#	
			1.1pF	±0.05pF	GRM1884C1H1R1WA01#	
				±0.1pF	GRM1884C1H1R1BA01#	
				±0.25pF	GRM1884C1H1R1CA01#	
			1.2pF	±0.05pF	GRM1884C1H1R2WA01#	
				±0.1pF	GRM1884C1H1R2BA01#	
				±0.25pF	GRM1884C1H1R2CA01#	
			1.3pF	±0.05pF	GRM1884C1H1R3WA01#	
				±0.1pF	GRM1884C1H1R3BA01#	
				±0.25pF	GRM1884C1H1R3CA01#	
			1.4pF	±0.05pF	GRM1884C1H1R4WA01#	
				±0.1pF	GRM1884C1H1R4BA01#	
				±0.25pF	GRM1884C1H1R4CA01#	
			1.5pF	±0.05pF	GRM1884C1H1R5WA01#	
				±0.1pF	GRM1884C1H1R5BA01#	
				±0.25pF	GRM1884C1H1R5CA01#	
			1.6pF	±0.05pF	GRM1884C1H1R6WA01#	
				±0.1pF	GRM1884C1H1R6BA01#	
				±0.25pF	GRM1884C1H1R6CA01#	
			1.7pF	±0.05pF	GRM1884C1H1R7WA01#	
				±0.1pF	GRM1884C1H1R7BA01#	
				±0.25pF	GRM1884C1H1R7CA01#	
			1.8pF	±0.05pF	GRM1884C1H1R8WA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	CK	1.8pF	±0.1pF	GRM1884C1H1R8BA01#	
				±0.25pF	GRM1884C1H1R8CA01#	
			1.9pF	±0.05pF	GRM1884C1H1R9WA01#	
				±0.1pF	GRM1884C1H1R9BA01#	
				±0.25pF	GRM1884C1H1R9CA01#	
			2.0pF	±0.05pF	GRM1884C1H2R0WA01#	
				±0.1pF	GRM1884C1H2R0BA01#	
				±0.25pF	GRM1884C1H2R0CA01#	
		CJ	2.1pF	±0.05pF	GRM1883C1H2R1WA01#	
				±0.1pF	GRM1883C1H2R1BA01#	
				±0.25pF	GRM1883C1H2R1CA01#	
			2.2pF	±0.05pF	GRM1883C1H2R2WA01#	
				±0.1pF	GRM1883C1H2R2BA01#	
				±0.25pF	GRM1883C1H2R2CA01#	
			2.3pF	±0.05pF	GRM1883C1H2R3WA01#	
				±0.1pF	GRM1883C1H2R3BA01#	
				±0.25pF	GRM1883C1H2R3CA01#	
			2.4pF	±0.05pF	GRM1883C1H2R4WA01#	
				±0.1pF	GRM1883C1H2R4BA01#	
				±0.25pF	GRM1883C1H2R4CA01#	
			2.5pF	±0.05pF	GRM1883C1H2R5WA01#	
				±0.1pF	GRM1883C1H2R5BA01#	
				±0.25pF	GRM1883C1H2R5CA01#	
			2.6pF	±0.05pF	GRM1883C1H2R6WA01#	
				±0.1pF	GRM1883C1H2R6BA01#	
				±0.25pF	GRM1883C1H2R6CA01#	
			2.7pF	±0.05pF	GRM1883C1H2R7WA01#	
				±0.1pF	GRM1883C1H2R7BA01#	
				±0.25pF	GRM1883C1H2R7CA01#	
			2.8pF	±0.05pF	GRM1883C1H2R8WA01#	
				±0.1pF	GRM1883C1H2R8BA01#	
				±0.25pF	GRM1883C1H2R8CA01#	
			2.9pF	±0.05pF	GRM1883C1H2R9WA01#	
				±0.1pF	GRM1883C1H2R9BA01#	
				±0.25pF	GRM1883C1H2R9CA01#	
			3.0pF	±0.05pF	GRM1883C1H3R0WA01#	
				±0.1pF	GRM1883C1H3R0BA01#	
				±0.25pF	GRM1883C1H3R0CA01#	
			3.1pF	±0.05pF	GRM1883C1H3R1WA01#	
				±0.1pF	GRM1883C1H3R1BA01#	
				±0.25pF	GRM1883C1H3R1CA01#	
			3.2pF	±0.05pF	GRM1883C1H3R2WA01#	
				±0.1pF	GRM1883C1H3R2BA01#	
				±0.25pF	GRM1883C1H3R2CA01#	
			3.3pF	±0.05pF	GRM1883C1H3R3WA01#	
				±0.1pF	GRM1883C1H3R3BA01#	
				±0.25pF	GRM1883C1H3R3CA01#	
			3.4pF	±0.05pF	GRM1883C1H3R4WA01#	
				±0.1pF	GRM1883C1H3R4BA01#	
				±0.25pF	GRM1883C1H3R4CA01#	
			3.5pF	±0.05pF	GRM1883C1H3R5WA01#	
				±0.1pF	GRM1883C1H3R5BA01#	
				±0.25pF	GRM1883C1H3R5CA01#	
			3.6pF	±0.05pF	GRM1883C1H3R6WA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	CJ	3.6pF	±0.1pF	GRM1883C1H3R6BA01#	
				±0.25pF	GRM1883C1H3R6CA01#	
			3.7pF	±0.05pF	GRM1883C1H3R7WA01#	
				±0.1pF	GRM1883C1H3R7BA01#	
				±0.25pF	GRM1883C1H3R7CA01#	
			3.8pF	±0.05pF	GRM1883C1H3R8WA01#	
				±0.1pF	GRM1883C1H3R8BA01#	
				±0.25pF	GRM1883C1H3R8CA01#	
			3.9pF	±0.05pF	GRM1883C1H3R9WA01#	
				±0.1pF	GRM1883C1H3R9BA01#	
				±0.25pF	GRM1883C1H3R9CA01#	
		CH	4.0pF	±0.05pF	GRM1882C1H4R0WA01#	
				±0.1pF	GRM1882C1H4R0BA01#	
				±0.25pF	GRM1882C1H4R0CA01#	
			4.1pF	±0.05pF	GRM1882C1H4R1WA01#	
				±0.1pF	GRM1882C1H4R1BA01#	
				±0.25pF	GRM1882C1H4R1CA01#	
			4.2pF	±0.05pF	GRM1882C1H4R2WA01#	
				±0.1pF	GRM1882C1H4R2BA01#	
				±0.25pF	GRM1882C1H4R2CA01#	
			4.3pF	±0.05pF	GRM1882C1H4R3WA01#	
				±0.1pF	GRM1882C1H4R3BA01#	
				±0.25pF	GRM1882C1H4R3CA01#	
			4.4pF	±0.05pF	GRM1882C1H4R4WA01#	
				±0.1pF	GRM1882C1H4R4BA01#	
				±0.25pF	GRM1882C1H4R4CA01#	
			4.5pF	±0.05pF	GRM1882C1H4R5WA01#	
				±0.1pF	GRM1882C1H4R5BA01#	
				±0.25pF	GRM1882C1H4R5CA01#	
			4.6pF	±0.05pF	GRM1882C1H4R6WA01#	
				±0.1pF	GRM1882C1H4R6BA01#	
				±0.25pF	GRM1882C1H4R6CA01#	
			4.7pF	±0.05pF	GRM1882C1H4R7WA01#	
				±0.1pF	GRM1882C1H4R7BA01#	
				±0.25pF	GRM1882C1H4R7CA01#	
			4.8pF	±0.05pF	GRM1882C1H4R8WA01#	
				±0.1pF	GRM1882C1H4R8BA01#	
				±0.25pF	GRM1882C1H4R8CA01#	
			4.9pF	±0.05pF	GRM1882C1H4R9WA01#	
				±0.1pF	GRM1882C1H4R9BA01#	
				±0.25pF	GRM1882C1H4R9CA01#	
			5.0pF	±0.05pF	GRM1882C1H5R0WA01#	
				±0.1pF	GRM1882C1H5R0BA01#	
				±0.25pF	GRM1882C1H5R0CA01#	
			5.1pF	±0.05pF	GRM1882C1H5R1WA01#	
				±0.1pF	GRM1882C1H5R1BA01#	
				±0.25pF	GRM1882C1H5R1CA01#	
				±0.5pF	GRM1882C1H5R1DA01#	
			5.2pF	±0.05pF	GRM1882C1H5R2WA01#	
				±0.1pF	GRM1882C1H5R2BA01#	
				±0.25pF	GRM1882C1H5R2CA01#	
				±0.5pF	GRM1882C1H5R2DA01#	
			5.3pF	±0.05pF	GRM1882C1H5R3WA01#	
				±0.1pF	GRM1882C1H5R3BA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	CH	5.3pF	±0.25pF	GRM1882C1H5R3CA01#	
				±0.5pF	GRM1882C1H5R3DA01#	
			5.4pF	±0.05pF	GRM1882C1H5R4WA01#	
				±0.1pF	GRM1882C1H5R4BA01#	
				±0.25pF	GRM1882C1H5R4CA01#	
				±0.5pF	GRM1882C1H5R4DA01#	
			5.5pF	±0.05pF	GRM1882C1H5R5WA01#	
				±0.1pF	GRM1882C1H5R5BA01#	
				±0.25pF	GRM1882C1H5R5CA01#	
				±0.5pF	GRM1882C1H5R5DA01#	
			5.6pF	±0.05pF	GRM1882C1H5R6WA01#	
				±0.1pF	GRM1882C1H5R6BA01#	
				±0.25pF	GRM1882C1H5R6CA01#	
				±0.5pF	GRM1882C1H5R6DA01#	
			5.7pF	±0.05pF	GRM1882C1H5R7WA01#	
				±0.1pF	GRM1882C1H5R7BA01#	
				±0.25pF	GRM1882C1H5R7CA01#	
				±0.5pF	GRM1882C1H5R7DA01#	
			5.8pF	±0.05pF	GRM1882C1H5R8WA01#	
				±0.1pF	GRM1882C1H5R8BA01#	
				±0.25pF	GRM1882C1H5R8CA01#	
				±0.5pF	GRM1882C1H5R8DA01#	
			5.9pF	±0.05pF	GRM1882C1H5R9WA01#	
				±0.1pF	GRM1882C1H5R9BA01#	
				±0.25pF	GRM1882C1H5R9CA01#	
				±0.5pF	GRM1882C1H5R9DA01#	
			6.0pF	±0.05pF	GRM1882C1H6R0WA01#	
				±0.1pF	GRM1882C1H6R0BA01#	
				±0.25pF	GRM1882C1H6R0CA01#	
				±0.5pF	GRM1882C1H6R0DA01#	
			6.1pF	±0.05pF	GRM1882C1H6R1WA01#	
				±0.1pF	GRM1882C1H6R1BA01#	
				±0.25pF	GRM1882C1H6R1CA01#	
				±0.5pF	GRM1882C1H6R1DA01#	
			6.2pF	±0.05pF	GRM1882C1H6R2WA01#	
				±0.1pF	GRM1882C1H6R2BA01#	
				±0.25pF	GRM1882C1H6R2CA01#	
				±0.5pF	GRM1882C1H6R2DA01#	
			6.3pF	±0.05pF	GRM1882C1H6R3WA01#	
				±0.1pF	GRM1882C1H6R3BA01#	
				±0.25pF	GRM1882C1H6R3CA01#	
				±0.5pF	GRM1882C1H6R3DA01#	
			6.4pF	±0.05pF	GRM1882C1H6R4WA01#	
				±0.1pF	GRM1882C1H6R4BA01#	
				±0.25pF	GRM1882C1H6R4CA01#	
				±0.5pF	GRM1882C1H6R4DA01#	
			6.5pF	±0.05pF	GRM1882C1H6R5WA01#	
				±0.1pF	GRM1882C1H6R5BA01#	
				±0.25pF	GRM1882C1H6R5CA01#	
				±0.5pF	GRM1882C1H6R5DA01#	
			6.6pF	±0.05pF	GRM1882C1H6R6WA01#	
				±0.1pF	GRM1882C1H6R6BA01#	
				±0.25pF	GRM1882C1H6R6CA01#	
				±0.5pF	GRM1882C1H6R6DA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	CH	6.7pF	±0.05pF	GRM1882C1H6R7WA01#	
				±0.1pF	GRM1882C1H6R7BA01#	
				±0.25pF	GRM1882C1H6R7CA01#	
				±0.5pF	GRM1882C1H6R7DA01#	
			6.8pF	±0.05pF	GRM1882C1H6R8WA01#	
				±0.1pF	GRM1882C1H6R8BA01#	
				±0.25pF	GRM1882C1H6R8CA01#	
				±0.5pF	GRM1882C1H6R8DA01#	
			6.9pF	±0.05pF	GRM1882C1H6R9WA01#	
				±0.1pF	GRM1882C1H6R9BA01#	
				±0.25pF	GRM1882C1H6R9CA01#	
				±0.5pF	GRM1882C1H6R9DA01#	
			7.0pF	±0.05pF	GRM1882C1H7R0WA01#	
				±0.1pF	GRM1882C1H7R0BA01#	
				±0.25pF	GRM1882C1H7R0CA01#	
				±0.5pF	GRM1882C1H7R0DA01#	
			7.1pF	±0.05pF	GRM1882C1H7R1WA01#	
				±0.1pF	GRM1882C1H7R1BA01#	
				±0.25pF	GRM1882C1H7R1CA01#	
				±0.5pF	GRM1882C1H7R1DA01#	
			7.2pF	±0.05pF	GRM1882C1H7R2WA01#	
				±0.1pF	GRM1882C1H7R2BA01#	
				±0.25pF	GRM1882C1H7R2CA01#	
				±0.5pF	GRM1882C1H7R2DA01#	
			7.3pF	±0.05pF	GRM1882C1H7R3WA01#	
				±0.1pF	GRM1882C1H7R3BA01#	
				±0.25pF	GRM1882C1H7R3CA01#	
				±0.5pF	GRM1882C1H7R3DA01#	
			7.4pF	±0.05pF	GRM1882C1H7R4WA01#	
				±0.1pF	GRM1882C1H7R4BA01#	
				±0.25pF	GRM1882C1H7R4CA01#	
				±0.5pF	GRM1882C1H7R4DA01#	
			7.5pF	±0.05pF	GRM1882C1H7R5WA01#	
				±0.1pF	GRM1882C1H7R5BA01#	
				±0.25pF	GRM1882C1H7R5CA01#	
				±0.5pF	GRM1882C1H7R5DA01#	
			7.6pF	±0.05pF	GRM1882C1H7R6WA01#	
				±0.1pF	GRM1882C1H7R6BA01#	
				±0.25pF	GRM1882C1H7R6CA01#	
				±0.5pF	GRM1882C1H7R6DA01#	
			7.7pF	±0.05pF	GRM1882C1H7R7WA01#	
				±0.1pF	GRM1882C1H7R7BA01#	
				±0.25pF	GRM1882C1H7R7CA01#	
				±0.5pF	GRM1882C1H7R7DA01#	
			7.8pF	±0.05pF	GRM1882C1H7R8WA01#	
				±0.1pF	GRM1882C1H7R8BA01#	
				±0.25pF	GRM1882C1H7R8CA01#	
				±0.5pF	GRM1882C1H7R8DA01#	
			7.9pF	±0.05pF	GRM1882C1H7R9WA01#	
				±0.1pF	GRM1882C1H7R9BA01#	
				±0.25pF	GRM1882C1H7R9CA01#	
				±0.5pF	GRM1882C1H7R9DA01#	
			8.0pF	±0.05pF	GRM1882C1H8R0WA01#	
				±0.1pF	GRM1882C1H8R0BA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	CH	8.0pF	±0.25pF	GRM1882C1H8R0CA01#	
				±0.5pF	GRM1882C1H8R0DA01#	
			8.1pF	±0.05pF	GRM1882C1H8R1WA01#	
				±0.1pF	GRM1882C1H8R1BA01#	
				±0.25pF	GRM1882C1H8R1CA01#	
				±0.5pF	GRM1882C1H8R1DA01#	
			8.2pF	±0.05pF	GRM1882C1H8R2WA01#	
				±0.1pF	GRM1882C1H8R2BA01#	
				±0.25pF	GRM1882C1H8R2CA01#	
				±0.5pF	GRM1882C1H8R2DA01#	
			8.3pF	±0.05pF	GRM1882C1H8R3WA01#	
				±0.1pF	GRM1882C1H8R3BA01#	
				±0.25pF	GRM1882C1H8R3CA01#	
				±0.5pF	GRM1882C1H8R3DA01#	
			8.4pF	±0.05pF	GRM1882C1H8R4WA01#	
				±0.1pF	GRM1882C1H8R4BA01#	
				±0.25pF	GRM1882C1H8R4CA01#	
				±0.5pF	GRM1882C1H8R4DA01#	
			8.5pF	±0.05pF	GRM1882C1H8R5WA01#	
				±0.1pF	GRM1882C1H8R5BA01#	
				±0.25pF	GRM1882C1H8R5CA01#	
				±0.5pF	GRM1882C1H8R5DA01#	
			8.6pF	±0.05pF	GRM1882C1H8R6WA01#	
				±0.1pF	GRM1882C1H8R6BA01#	
				±0.25pF	GRM1882C1H8R6CA01#	
				±0.5pF	GRM1882C1H8R6DA01#	
			8.7pF	±0.05pF	GRM1882C1H8R7WA01#	
				±0.1pF	GRM1882C1H8R7BA01#	
				±0.25pF	GRM1882C1H8R7CA01#	
				±0.5pF	GRM1882C1H8R7DA01#	
			8.8pF	±0.05pF	GRM1882C1H8R8WA01#	
				±0.1pF	GRM1882C1H8R8BA01#	
				±0.25pF	GRM1882C1H8R8CA01#	
				±0.5pF	GRM1882C1H8R8DA01#	
			8.9pF	±0.05pF	GRM1882C1H8R9WA01#	
				±0.1pF	GRM1882C1H8R9BA01#	
				±0.25pF	GRM1882C1H8R9CA01#	
				±0.5pF	GRM1882C1H8R9DA01#	
			9.0pF	±0.05pF	GRM1882C1H9R0WA01#	
				±0.1pF	GRM1882C1H9R0BA01#	
				±0.25pF	GRM1882C1H9R0CA01#	
				±0.5pF	GRM1882C1H9R0DA01#	
			9.1pF	±0.05pF	GRM1882C1H9R1WA01#	
				±0.1pF	GRM1882C1H9R1BA01#	
				±0.25pF	GRM1882C1H9R1CA01#	
				±0.5pF	GRM1882C1H9R1DA01#	
			9.2pF	±0.05pF	GRM1882C1H9R2WA01#	
				±0.1pF	GRM1882C1H9R2BA01#	
				±0.25pF	GRM1882C1H9R2CA01#	
				±0.5pF	GRM1882C1H9R2DA01#	
			9.3pF	±0.05pF	GRM1882C1H9R3WA01#	
				±0.1pF	GRM1882C1H9R3BA01#	
				±0.25pF	GRM1882C1H9R3CA01#	
				±0.5pF	GRM1882C1H9R3DA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	CH	9.4pF	±0.05pF	GRM1882C1H9R4WA01#	
				±0.1pF	GRM1882C1H9R4BA01#	
				±0.25pF	GRM1882C1H9R4CA01#	
				±0.5pF	GRM1882C1H9R4DA01#	
			9.5pF	±0.05pF	GRM1882C1H9R5WA01#	
				±0.1pF	GRM1882C1H9R5BA01#	
				±0.25pF	GRM1882C1H9R5CA01#	
				±0.5pF	GRM1882C1H9R5DA01#	
			9.6pF	±0.05pF	GRM1882C1H9R6WA01#	
				±0.1pF	GRM1882C1H9R6BA01#	
				±0.25pF	GRM1882C1H9R6CA01#	
				±0.5pF	GRM1882C1H9R6DA01#	
			9.7pF	±0.05pF	GRM1882C1H9R7WA01#	
				±0.1pF	GRM1882C1H9R7BA01#	
				±0.25pF	GRM1882C1H9R7CA01#	
				±0.5pF	GRM1882C1H9R7DA01#	
			9.8pF	±0.05pF	GRM1882C1H9R8WA01#	
				±0.1pF	GRM1882C1H9R8BA01#	
				±0.25pF	GRM1882C1H9R8CA01#	
				±0.5pF	GRM1882C1H9R8DA01#	
			9.9pF	±0.05pF	GRM1882C1H9R9WA01#	
				±0.1pF	GRM1882C1H9R9BA01#	
				±0.25pF	GRM1882C1H9R9CA01#	
				±0.5pF	GRM1882C1H9R9DA01#	
			10pF	±5%	GRM1882C1H100JA01#	
			12pF	±5%	GRM1882C1H120JA01#	
			15pF	±5%	GRM1882C1H150JA01#	
			18pF	±5%	GRM1882C1H180JA01#	
			22pF	±5%	GRM1882C1H220JA01#	
			27pF	±5%	GRM1882C1H270JA01#	
			33pF	±5%	GRM1882C1H330JA01#	
			39pF	±5%	GRM1882C1H390JA01#	
			47pF	±5%	GRM1882C1H470JA01#	
			56pF	±5%	GRM1882C1H560JA01#	
			68pF	±5%	GRM1882C1H680JA01#	
			82pF	±5%	GRM1882C1H820JA01#	
			100pF	±5%	GRM1882C1H101JA01#	
			120pF	±5%	GRM1882C1H121JA01#	
			150pF	±5%	GRM1882C1H151JA01#	
			180pF	±5%	GRM1882C1H181JA01#	
			220pF	±5%	GRM1882C1H221JA01#	
			270pF	±5%	GRM1882C1H271JA01#	
			330pF	±5%	GRM1882C1H331JA01#	
			390pF	±5%	GRM1882C1H391JA01#	
			470pF	±5%	GRM1882C1H471JA01#	
			560pF	±5%	GRM1882C1H561JA01#	
			680pF	±5%	GRM1882C1H681JA01#	
			820pF	±5%	GRM1882C1H821JA01#	
			1000pF	±5%	GRM1882C1H102JA01#	
			1200pF	±5%	GRM1882C1H122JA01#	
			1500pF	±5%	GRM1882C1H152JA01#	
			1800pF	±5%	GRM1882C1H182JA01#	
			2200pF	±5%	GRM1882C1H222JA01#	
			2700pF	±5%	GRM1882C1H272JA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	50Vdc	CH	3300pF	±5%	GRM1882C1H332JA01#	
			3900pF	±5%	GRM1882C1H392JA01#	
			4700pF	±5%	GRM1882C1H472JA01#	
			5600pF	±5%	GRM1882C1H562JA01#	
			6800pF	±5%	GRM1882C1H682JA01#	
			8200pF	±5%	GRM1882C1H822JA01#	
			10000pF	±5%	GRM1882C1H103JA01#	
		SL	1200pF	±5%	GRM1881X1H122JA01#	
			1500pF	±5%	GRM1881X1H152JA01#	
			1800pF	±5%	GRM1881X1H182JA01#	
			2200pF	±5%	GRM1881X1H222JA01#	
			2700pF	±5%	GRM1881X1H272JA01#	
			3300pF	±5%	GRM1881X1H332JA01#	
			3900pF	±5%	GRM1881X1H392JA01#	
			4700pF	±5%	GRM1881X1H472JA01#	
			5600pF	±5%	GRM1881X1H562JA01#	
			6800pF	±5%	GRM1881X1H682JA01#	
			8200pF	±5%	GRM1881X1H822JA01#	
			10000pF	±5%	GRM1881X1H103JA01#	
		U2J	1200pF	±5%	GRM1887U1H122JA01#	
			1500pF	±5%	GRM1887U1H152JA01#	
			1800pF	±5%	GRM1887U1H182JA01#	
			2200pF	±5%	GRM1887U1H222JA01#	
			2700pF	±5%	GRM1887U1H272JA01#	
			3300pF	±5%	GRM1887U1H332JA01#	
			3900pF	±5%	GRM1887U1H392JA01#	
			4700pF	±5%	GRM1887U1H472JA01#	
			5600pF	±5%	GRM1887U1H562JA01#	
			6800pF	±5%	GRM1887U1H682JA01#	
			8200pF	±5%	GRM1887U1H822JA01#	
			10000pF	±5%	GRM1887U1H103JA01#	
		UJ	1000pF	±5%	GRM1883U1H102JA01#	
			1200pF	±5%	GRM1883U1H122JA01#	
			1500pF	±5%	GRM1883U1H152JA01#	
			1800pF	±5%	GRM1883U1H182JA01#	
			2200pF	±5%	GRM1883U1H222JA01#	
			2700pF	±5%	GRM1883U1H272JA01#	
			3300pF	±5%	GRM1883U1H332JA01#	
			3900pF	±5%	GRM1883U1H392JA01#	
			4700pF	±5%	GRM1883U1H472JA01#	
			5600pF	±5%	GRM1883U1H562JA01#	
			6800pF	±5%	GRM1883U1H682JA01#	
			8200pF	±5%	GRM1883U1H822JA01#	
			10000pF	±5%	GRM1883U1H103JA01#	
	10Vdc	SL	12000pF	±5%	GRM1881X1A123JA01#	
			15000pF	±5%	GRM1881X1A153JA01#	
			18000pF	±5%	GRM1881X1A183JA01#	
			22000pF	±5%	GRM1881X1A223JA01#	
		U2J	12000pF	±5%	GRM1887U1A123JA01#	
			15000pF	±5%	GRM1887U1A153JA01#	
			18000pF	±5%	GRM1887U1A183JA01#	
			22000pF	±5%	GRM1887U1A223JA01#	
		UJ	12000pF	±5%	GRM1883U1A123JA01#	
			15000pF	±5%	GRM1883U1A153JA01#	
0.9mm	10Vdc	UJ	18000pF	±5%	GRM1883U1A183JA01#	
			22000pF	±5%	GRM1883U1A223JA01#	

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.7mm	100Vdc	C0G	100pF	±5%	GRM2165C2A101JA01#	
			120pF	±5%	GRM2165C2A121JA01#	
			150pF	±5%	GRM2165C2A151JA01#	
			180pF	±5%	GRM2165C2A181JA01#	
			220pF	±5%	GRM2165C2A221JA01#	
			270pF	±5%	GRM2165C2A271JA01#	
			330pF	±5%	GRM2165C2A331JA01#	
			390pF	±5%	GRM2165C2A391JA01#	
			470pF	±5%	GRM2165C2A471JA01#	
			560pF	±5%	GRM2165C2A561JA01#	
			680pF	±5%	GRM2165C2A681JA01#	
			820pF	±5%	GRM2165C2A821JA01#	
			1000pF	±5%	GRM2165C2A102JA01#	
			1200pF	±5%	GRM2165C2A122JA01#	
			1500pF	±5%	GRM2165C2A152JA01#	
			1800pF	±5%	GRM2165C2A182JA01#	
			2200pF	±5%	GRM2165C2A222JA01#	
			2700pF	±5%	GRM2165C2A272JA01#	
			3300pF	±5%	GRM2165C2A332JA01#	
		CH	100pF	±5%	GRM2162C2A101JA01#	
			120pF	±5%	GRM2162C2A121JA01#	
			150pF	±5%	GRM2162C2A151JA01#	
			180pF	±5%	GRM2162C2A181JA01#	
			220pF	±5%	GRM2162C2A221JA01#	
			270pF	±5%	GRM2162C2A271JA01#	
			330pF	±5%	GRM2162C2A331JA01#	
			390pF	±5%	GRM2162C2A391JA01#	
			470pF	±5%	GRM2162C2A471JA01#	
			560pF	±5%	GRM2162C2A561JA01#	
			680pF	±5%	GRM2162C2A681JA01#	
			820pF	±5%	GRM2162C2A821JA01#	
			1000pF	±5%	GRM2162C2A102JA01#	
			1200pF	±5%	GRM2162C2A122JA01#	
			1500pF	±5%	GRM2162C2A152JA01#	
			1800pF	±5%	GRM2162C2A182JA01#	
			2200pF	±5%	GRM2162C2A222JA01#	
			2700pF	±5%	GRM2162C2A272JA01#	
			3300pF	±5%	GRM2162C2A332JA01#	
	50Vdc	C0G	1200pF	±5%	GRM2165C1H122JA01#	
			1500pF	±5%	GRM2165C1H152JA01#	
			1800pF	±5%	GRM2165C1H182JA01#	
			2200pF	±5%	GRM2165C1H222JA01#	
			2700pF	±5%	GRM2165C1H272JA01#	
			3300pF	±5%	GRM2165C1H332JA01#	
			3900pF	±5%	GRM2165C1H392JA01#	
			4700pF	±5%	GRM2165C1H472JA01#	
		CH	1200pF	±5%	GRM2162C1H122JA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 2.0×1.25mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.7mm	50Vdc	CH	1500pF	±5%	GRM2162C1H152JA01#	
			1800pF	±5%	GRM2162C1H182JA01#	
			2200pF	±5%	GRM2162C1H222JA01#	
			2700pF	±5%	GRM2162C1H272JA01#	
			3300pF	±5%	GRM2162C1H332JA01#	
			3900pF	±5%	GRM2162C1H392JA01#	
			4700pF	±5%	GRM2162C1H472JA01#	
		SL	12000pF	±5%	GRM2161X1H123JA01#	
			15000pF	±5%	GRM2161X1H153JA01#	
			18000pF	±5%	GRM2161X1H183JA01#	
		U2J	12000pF	±5%	GRM2167U1H123JA01#	
			15000pF	±5%	GRM2167U1H153JA01#	
			18000pF	±5%	GRM2167U1H183JA01#	
		UJ	10000pF	±5%	GRM2163U1H103JA01#	
			12000pF	±5%	GRM2163U1H123JA01#	
			15000pF	±5%	GRM2163U1H153JA01#	
			18000pF	±5%	GRM2163U1H183JA01#	
0.95mm	50Vdc	C0G	5600pF	±5%	GRM2195C1H562JA01#	
			6800pF	±5%	GRM2195C1H682JA01#	
			8200pF	±5%	GRM2195C1H822JA01#	
			10000pF	±5%	GRM2195C1H103JA01#	
			12000pF	±5%	GRM2195C1H123JA01#	
			15000pF	±5%	GRM2195C1H153JA01#	
		CH	5600pF	±5%	GRM2192C1H562JA01#	
			6800pF	±5%	GRM2192C1H682JA01#	
			8200pF	±5%	GRM2192C1H822JA01#	
			10000pF	±5%	GRM2192C1H103JA01#	
			12000pF	±5%	GRM2192C1H123JA01#	
			15000pF	±5%	GRM2192C1H153JA01#	
		SL	22000pF	±5%	GRM2191X1H223JA01#	
			27000pF	±5%	GRM2191X1H273JA01#	
		U2J	22000pF	±5%	GRM2197U1H223JA01#	
			27000pF	±5%	GRM2197U1H273JA01#	
		UJ	22000pF	±5%	GRM2193U1H223JA01#	
			27000pF	±5%	GRM2193U1H273JA01#	
	10Vdc	SL	56000pF	±5%	GRM2191X1A563JA01#	
		U2J	56000pF	±5%	GRM2197U1A563JA01#	
		UJ	56000pF	±5%	GRM2193U1A563JA01#	
1.0mm	630Vdc	C0G	10pF	±5%	GRM21A5C2J100JWA1#	
			12pF	±5%	GRM21A5C2J120JWA1#	
			15pF	±5%	GRM21A5C2J150JWA1#	
			18pF	±5%	GRM21A5C2J180JWA1#	
			22pF	±5%	GRM21A5C2J220JWA1#	
			27pF	±5%	GRM21A5C2J270JWA1#	
			33pF	±5%	GRM21A5C2J330JWA1#	
			39pF	±5%	GRM21A5C2J390JWA1#	
			47pF	±5%	GRM21A5C2J470JWA1#	
			56pF	±5%	GRM21A5C2J560JWA1#	
			68pF	±5%	GRM21A5C2J680JWA1#	
			82pF	±5%	GRM21A5C2J820JWA1#	
			100pF	±5%	GRM21A5C2J101JWA1#	
			120pF	±5%	GRM21A5C2J121JWA1#	
			150pF	±5%	GRM21A5C2J151JWA1#	
			180pF	±5%	GRM21A5C2J181JWA1#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	630Vdc	C0G	220pF	±5%	GRM21A5C2J221JWA1#	
			270pF	±5%	GRM21A5C2J271JWA1#	
			330pF	±5%	GRM21A5C2J331JWA1#	
			390pF	±5%	GRM21A5C2J391JWA1#	
			470pF	±5%	GRM21A5C2J471JWA1#	
			560pF	±5%	GRM21A5C2J561JWA1#	
	250Vdc	C0G	10pF	±5%	GRM21A5C2E100JW01#	
			12pF	±5%	GRM21A5C2E120JW01#	
			15pF	±5%	GRM21A5C2E150JW01#	
			18pF	±5%	GRM21A5C2E180JW01#	
			22pF	±5%	GRM21A5C2E220JW01#	
			27pF	±5%	GRM21A5C2E270JW01#	
			33pF	±5%	GRM21A5C2E330JW01#	
			39pF	±5%	GRM21A5C2E390JW01#	
			47pF	±5%	GRM21A5C2E470JW01#	
			56pF	±5%	GRM21A5C2E560JW01#	
			68pF	±5%	GRM21A5C2E680JW01#	
			82pF	±5%	GRM21A5C2E820JW01#	
			100pF	±5%	GRM21A5C2E101JW01#	
			120pF	±5%	GRM21A5C2E121JW01#	
			150pF	±5%	GRM21A5C2E151JW01#	
			180pF	±5%	GRM21A5C2E181JW01#	
			220pF	±5%	GRM21A5C2E221JW01#	
			270pF	±5%	GRM21A5C2E271JW01#	
			330pF	±5%	GRM21A5C2E331JW01#	
			390pF	±5%	GRM21A5C2E391JWA1#	
			470pF	±5%	GRM21A5C2E471JWA1#	
			560pF	±5%	GRM21A5C2E561JWA1#	
			680pF	±5%	GRM21A5C2E681JWA1#	
			820pF	±5%	GRM21A5C2E821JWA1#	
			1000pF	±5%	GRM21A5C2E102JWA1#	
			1200pF	±5%	GRM21A5C2E122JWA1#	
			1500pF	±5%	GRM21A5C2E152JWA1#	
			1800pF	±5%	GRM21A5C2E182JWA1#	
			2200pF	±5%	GRM21A5C2E222JWA1#	
			2700pF	±5%	GRM21A5C2E272JWA1#	
		U2J	100pF	±5%	GRM21A7U2E101JW31#	
			120pF	±5%	GRM21A7U2E121JW31#	
			150pF	±5%	GRM21A7U2E151JW31#	
			180pF	±5%	GRM21A7U2E181JW31#	
			220pF	±5%	GRM21A7U2E221JW31#	
			270pF	±5%	GRM21A7U2E271JW31#	
			330pF	±5%	GRM21A7U2E331JW31#	
			390pF	±5%	GRM21A7U2E391JW31#	
			470pF	±5%	GRM21A7U2E471JW31#	
			560pF	±5%	GRM21A7U2E561JW31#	
			680pF	±5%	GRM21A7U2E681JW31#	
			820pF	±5%	GRM21A7U2E821JW31#	
			1000pF	±5%	GRM21A7U2E102JW31#	
			1200pF	±5%	GRM21A7U2E122JW31#	
			1500pF	±5%	GRM21A7U2E152JW31#	
			1800pF	±5%	GRM21A7U2E182JW31#	
			2200pF	±5%	GRM21A7U2E222JW31#	
	200Vdc	C0G	10pF	±5%	GRM21A5C2D100JW01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 2.0×1.25mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	200Vdc	C0G	12pF	±5%	GRM21A5C2D120JW01#	
			15pF	±5%	GRM21A5C2D150JW01#	
			18pF	±5%	GRM21A5C2D180JW01#	
			22pF	±5%	GRM21A5C2D220JW01#	
			27pF	±5%	GRM21A5C2D270JW01#	
			33pF	±5%	GRM21A5C2D330JW01#	
			39pF	±5%	GRM21A5C2D390JW01#	
			47pF	±5%	GRM21A5C2D470JW01#	
			56pF	±5%	GRM21A5C2D560JW01#	
			68pF	±5%	GRM21A5C2D680JW01#	
			82pF	±5%	GRM21A5C2D820JW01#	
			100pF	±5%	GRM21A5C2D101JW01#	
			120pF	±5%	GRM21A5C2D121JW01#	
			150pF	±5%	GRM21A5C2D151JW01#	
			180pF	±5%	GRM21A5C2D181JW01#	
			220pF	±5%	GRM21A5C2D221JW01#	
			270pF	±5%	GRM21A5C2D271JW01#	
			330pF	±5%	GRM21A5C2D331JW01#	
		U2J	100pF	±5%	GRM21A7U2D101JW31#	
			120pF	±5%	GRM21A7U2D121JW31#	
			150pF	±5%	GRM21A7U2D151JW31#	
			180pF	±5%	GRM21A7U2D181JW31#	
			220pF	±5%	GRM21A7U2D221JW31#	
			270pF	±5%	GRM21A7U2D271JW31#	
			330pF	±5%	GRM21A7U2D331JW31#	
			390pF	±5%	GRM21A7U2D391JW31#	
			470pF	±5%	GRM21A7U2D471JW31#	
			560pF	±5%	GRM21A7U2D561JW31#	
			680pF	±5%	GRM21A7U2D681JW31#	
			820pF	±5%	GRM21A7U2D821JW31#	
			1000pF	±5%	GRM21A7U2D102JW31#	
			1200pF	±5%	GRM21A7U2D122JW31#	
			1500pF	±5%	GRM21A7U2D152JW31#	
			1800pF	±5%	GRM21A7U2D182JW31#	
			2200pF	±5%	GRM21A7U2D222JW31#	
	50Vdc	SL	33000pF	±5%	GRM21A1X1H333JA39#	
		U2J	33000pF	±5%	GRM21A7U1H333JA39#	
		UJ	33000pF	±5%	GRM21A3U1H333JA39#	
1.35mm	50Vdc	C0G	18000pF	±5%	GRM21B5C1H183JA01#	
			22000pF	±5%	GRM21B5C1H223JA01#	
		CH	18000pF	±5%	GRM21B2C1H183JA01#	
			22000pF	±5%	GRM21B2C1H223JA01#	
		SL	39000pF	±5%	GRM21B1X1H393JA01#	
			47000pF	±5%	GRM21B1X1H473JA01#	
		U2J	39000pF	±5%	GRM21B7U1H393JA01#	
			47000pF	±5%	GRM21B7U1H473JA01#	
		UJ	39000pF	±5%	GRM21B3U1H393JA01#	
			47000pF	±5%	GRM21B3U1H473JA01#	
	10Vdc	SL	68000pF	±5%	GRM21B1X1A683JA01#	
			82000pF	±5%	GRM21B1X1A823JA01#	
			0.10μF	±5%	GRM21B1X1A104JA01#	
		U2J	68000pF	±5%	GRM21B7U1A683JA01#	
			82000pF	±5%	GRM21B7U1A823JA01#	
			0.10μF	±5%	GRM21B7U1A104JA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.35mm	10Vdc	UJ	68000pF	±5%	GRM21B3U1A683JA01#	
			82000pF	±5%	GRM21B3U1A823JA01#	
			0.10μF	±5%	GRM21B3U1A104JA01#	
1.45mm	630Vdc	C0G	680pF	±5%	GRM21B5C2J681JWA3#	
			820pF	±5%	GRM21B5C2J821JWA3#	
			1000pF	±5%	GRM21B5C2J102JWA3#	
			1200pF	±5%	GRM21B5C2J122JWA3#	
	250Vdc	C0G	3300pF	±5%	GRM21B5C2E332JWA1#	
			3900pF	±5%	GRM21B5C2E392JWA1#	
			4700pF	±5%	GRM21B5C2E472JWA1#	
		U2J	2700pF	±5%	GRM21B7U2E272JW32#	
			3300pF	±5%	GRM21B7U2E332JW32#	
			3900pF	±5%	GRM21B7U2E392JW32#	
			4700pF	±5%	GRM21B7U2E472JW32#	
			5600pF	±5%	GRM21B7U2E562JW32#	
	200Vdc	U2J	2700pF	±5%	GRM21B7U2D272JW32#	
			3300pF	±5%	GRM21B7U2D332JW32#	
			3900pF	±5%	GRM21B7U2D392JW32#	
			4700pF	±5%	GRM21B7U2D472JW32#	
			5600pF	±5%	GRM21B7U2D562JW32#	

3.2×1.6mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.95mm	100Vdc	C0G	1800pF	±5%	GRM3195C2A182JA01#	
			2200pF	±5%	GRM3195C2A222JA01#	
			2700pF	±5%	GRM3195C2A272JA01#	
			3300pF	±5%	GRM3195C2A332JA01#	
			3900pF	±5%	GRM3195C2A392JA01#	
			4700pF	±5%	GRM3195C2A472JA01#	
			5600pF	±5%	GRM3195C2A562JA01#	
			6800pF	±5%	GRM3195C2A682JA01#	
			8200pF	±5%	GRM3195C2A822JA01#	
			10000pF	±5%	GRM3195C2A103JA01#	
			12000pF	±5%	GRM3195C2A123JA01#	
			15000pF	±5%	GRM3195C2A153JA01#	
			18000pF	±5%	GRM3195C2A183JA01#	
			22000pF	±5%	GRM3195C2A223JA01#	
			27000pF	±5%	GRM3195C2A273JA01#	D1
			33000pF	±5%	GRM3195C2A333JA01#	D1
			39000pF	±5%	GRM3195C2A393JA01#	D1
		CH	1800pF	±5%	GRM3192C2A182JA01#	
			2200pF	±5%	GRM3192C2A222JA01#	
			2700pF	±5%	GRM3192C2A272JA01#	
			3300pF	±5%	GRM3192C2A332JA01#	
			3900pF	±5%	GRM3192C2A392JA01#	
			4700pF	±5%	GRM3192C2A472JA01#	
			5600pF	±5%	GRM3192C2A562JA01#	
			6800pF	±5%	GRM3192C2A682JA01#	
			8200pF	±5%	GRM3192C2A822JA01#	
			10000pF	±5%	GRM3192C2A103JA01#	
			12000pF	±5%	GRM3192C2A123JA01#	
			15000pF	±5%	GRM3192C2A153JA01#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 3.2×1.6mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.95mm	100Vdc	CH	18000pF	±5%	GRM3192C2A183JA01#	
			22000pF	±5%	GRM3192C2A223JA01#	
			27000pF	±5%	GRM3192C2A273JA01#	D1
			33000pF	±5%	GRM3192C2A333JA01#	D1
			39000pF	±5%	GRM3192C2A393JA01#	D1
	50Vdc	C0G	12000pF	±5%	GRM3195C1H123JA01#	
			15000pF	±5%	GRM3195C1H153JA01#	
			18000pF	±5%	GRM3195C1H183JA01#	
			22000pF	±5%	GRM3195C1H223JA01#	
			27000pF	±5%	GRM3195C1H273JA01#	
			33000pF	±5%	GRM3195C1H333JA01#	
			39000pF	±5%	GRM3195C1H393JA01#	
		CH	12000pF	±5%	GRM3192C1H123JA01#	
			15000pF	±5%	GRM3192C1H153JA01#	
			18000pF	±5%	GRM3192C1H183JA01#	
			22000pF	±5%	GRM3192C1H223JA01#	
			27000pF	±5%	GRM3192C1H273JA01#	
			33000pF	±5%	GRM3192C1H333JA01#	
			39000pF	±5%	GRM3192C1H393JA01#	
		SL	56000pF	±5%	GRM3191X1H563JA01#	
		U2J	56000pF	±5%	GRM3197U1H563JA01#	
		UJ	56000pF	±5%	GRM3193U1H563JA01#	
1.0mm	2000Vdc	U2J	10pF	±5%	GRM31A7U3D100JW31#	
			12pF	±5%	GRM31A7U3D120JW31#	
			15pF	±5%	GRM31A7U3D150JW31#	
			18pF	±5%	GRM31A7U3D180JW31#	
			22pF	±5%	GRM31A7U3D220JW31#	
			27pF	±5%	GRM31A7U3D270JW31#	
			33pF	±5%	GRM31A7U3D330JW31#	
			39pF	±5%	GRM31A7U3D390JW31#	
			47pF	±5%	GRM31A7U3D470JW31#	
			56pF	±5%	GRM31A7U3D560JW31#	
			68pF	±5%	GRM31A7U3D680JW31#	
	1000Vdc	C0G	10pF	±5%	GRM31A5C3A100JW01#	
			12pF	±5%	GRM31A5C3A120JW01#	
			15pF	±5%	GRM31A5C3A150JW01#	
			18pF	±5%	GRM31A5C3A180JW01#	
			22pF	±5%	GRM31A5C3A220JW01#	
			27pF	±5%	GRM31A5C3A270JW01#	
			33pF	±5%	GRM31A5C3A330JW01#	
			39pF	±5%	GRM31A5C3A390JW01#	
			47pF	±5%	GRM31A5C3A470JW01#	
			56pF	±5%	GRM31A5C3A560JW01#	
			68pF	±5%	GRM31A5C3A680JW01#	
			82pF	±5%	GRM31A5C3A820JW01#	
			100pF	±5%	GRM31A5C3A101JW01#	
			120pF	±5%	GRM31A5C3A121JW01#	
			150pF	±5%	GRM31A5C3A151JW01#	
			180pF	±5%	GRM31A5C3A181JW01#	
			220pF	±5%	GRM31A5C3A221JW01#	
			270pF	±5%	GRM31A5C3A271JWA1#	
			330pF	±5%	GRM31A5C3A331JWA1#	
			390pF	±5%	GRM31A5C3A391JWA1#	
			470pF	±5%	GRM31A5C3A471JWA1#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	1000Vdc	U2J	10pF	±5%	GRM31A7U3A100JW31#	
			12pF	±5%	GRM31A7U3A120JW31#	
			15pF	±5%	GRM31A7U3A150JW31#	
			18pF	±5%	GRM31A7U3A180JW31#	
			22pF	±5%	GRM31A7U3A220JW31#	
			27pF	±5%	GRM31A7U3A270JW31#	
			33pF	±5%	GRM31A7U3A330JW31#	
			39pF	±5%	GRM31A7U3A390JW31#	
			47pF	±5%	GRM31A7U3A470JW31#	
			56pF	±5%	GRM31A7U3A560JW31#	
			68pF	±5%	GRM31A7U3A680JW31#	
			82pF	±5%	GRM31A7U3A820JW31#	
			100pF	±5%	GRM31A7U3A101JW31#	
			120pF	±5%	GRM31A7U3A121JW31#	
			150pF	±5%	GRM31A7U3A151JW31#	
			180pF	±5%	GRM31A7U3A181JW31#	
			220pF	±5%	GRM31A7U3A221JW31#	
			270pF	±5%	GRM31A7U3A271JW31#	
			330pF	±5%	GRM31A7U3A331JW31#	
	630Vdc	C0G	10pF	±5%	GRM31A5C2J100JW01#	
			12pF	±5%	GRM31A5C2J120JW01#	
			15pF	±5%	GRM31A5C2J150JW01#	
			18pF	±5%	GRM31A5C2J180JW01#	
			22pF	±5%	GRM31A5C2J220JW01#	
			27pF	±5%	GRM31A5C2J270JW01#	
			33pF	±5%	GRM31A5C2J330JW01#	
			39pF	±5%	GRM31A5C2J390JW01#	
			47pF	±5%	GRM31A5C2J470JW01#	
			56pF	±5%	GRM31A5C2J560JW01#	
			68pF	±5%	GRM31A5C2J680JW01#	
			82pF	±5%	GRM31A5C2J820JW01#	
			100pF	±5%	GRM31A5C2J101JW01#	
			120pF	±5%	GRM31A5C2J121JW01#	
			150pF	±5%	GRM31A5C2J151JW01#	
			180pF	±5%	GRM31A5C2J181JW01#	
			220pF	±5%	GRM31A5C2J221JW01#	
			270pF	±5%	GRM31A5C2J271JW01#	
			330pF	±5%	GRM31A5C2J331JW01#	
			390pF	±5%	GRM31A5C2J391JW01#	
			470pF	±5%	GRM31A5C2J471JW01#	
			560pF	±5%	GRM31A5C2J561JW01#	
			1200pF	±5%	GRM31A5C2J122JWA1#	
			1500pF	±5%	GRM31A5C2J152JWA1#	
			1800pF	±5%	GRM31A5C2J182JWA1#	
		U2J	10pF	±5%	GRM31A7U2J100JW31#	
			12pF	±5%	GRM31A7U2J120JW31#	
			15pF	±5%	GRM31A7U2J150JW31#	
			18pF	±5%	GRM31A7U2J180JW31#	
			22pF	±5%	GRM31A7U2J220JW31#	
			27pF	±5%	GRM31A7U2J270JW31#	
			33pF	±5%	GRM31A7U2J330JW31#	
			39pF	±5%	GRM31A7U2J390JW31#	
			47pF	±5%	GRM31A7U2J470JW31#	
			56pF	±5%	GRM31A7U2J560JW31#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 3.2×1.6mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	630Vdc	U2J	68pF	±5%	GRM31A7U2J680JW31#	
			82pF	±5%	GRM31A7U2J820JW31#	
			100pF	±5%	GRM31A7U2J101JW31#	
			120pF	±5%	GRM31A7U2J121JW31#	
			150pF	±5%	GRM31A7U2J151JW31#	
			180pF	±5%	GRM31A7U2J181JW31#	
			220pF	±5%	GRM31A7U2J221JW31#	
			270pF	±5%	GRM31A7U2J271JW31#	
			330pF	±5%	GRM31A7U2J331JW31#	
			390pF	±5%	GRM31A7U2J391JW31#	
			470pF	±5%	GRM31A7U2J471JW31#	
			560pF	±5%	GRM31A7U2J561JW31#	
			680pF	±5%	GRM31A7U2J681JW31#	
			820pF	±5%	GRM31A7U2J821JW31#	
			1000pF	±5%	GRM31A7U2J102JW31#	
			1200pF	±5%	GRM31A7U2J122JW31#	
			1500pF	±5%	GRM31A7U2J152JW31#	
			1800pF	±5%	GRM31A7U2J182JW31#	
			2200pF	±5%	GRM31A7U2J222JW31#	
	500Vdc	C0G	10pF	±5%	GRM31A5C2H100JW01#	
			12pF	±5%	GRM31A5C2H120JW01#	
			15pF	±5%	GRM31A5C2H150JW01#	
			18pF	±5%	GRM31A5C2H180JW01#	
			22pF	±5%	GRM31A5C2H220JW01#	
			27pF	±5%	GRM31A5C2H270JW01#	
			33pF	±5%	GRM31A5C2H330JW01#	
			39pF	±5%	GRM31A5C2H390JW01#	
			47pF	±5%	GRM31A5C2H470JW01#	
			56pF	±5%	GRM31A5C2H560JW01#	
			68pF	±5%	GRM31A5C2H680JW01#	
			82pF	±5%	GRM31A5C2H820JW01#	
			100pF	±5%	GRM31A5C2H101JW01#	
			120pF	±5%	GRM31A5C2H121JW01#	
			150pF	±5%	GRM31A5C2H151JW01#	
			180pF	±5%	GRM31A5C2H181JW01#	
			220pF	±5%	GRM31A5C2H221JW01#	
			270pF	±5%	GRM31A5C2H271JW01#	
			330pF	±5%	GRM31A5C2H331JW01#	
			390pF	±5%	GRM31A5C2H391JW01#	
			470pF	±5%	GRM31A5C2H471JW01#	
			560pF	±5%	GRM31A5C2H561JW01#	
		U2J	10pF	±5%	GRM31A7U2H100JW31#	
			12pF	±5%	GRM31A7U2H120JW31#	
			15pF	±5%	GRM31A7U2H150JW31#	
			18pF	±5%	GRM31A7U2H180JW31#	
			22pF	±5%	GRM31A7U2H220JW31#	
			27pF	±5%	GRM31A7U2H270JW31#	
			33pF	±5%	GRM31A7U2H330JW31#	
			39pF	±5%	GRM31A7U2H390JW31#	
			47pF	±5%	GRM31A7U2H470JW31#	
			56pF	±5%	GRM31A7U2H560JW31#	
			68pF	±5%	GRM31A7U2H680JW31#	
			82pF	±5%	GRM31A7U2H820JW31#	
			100pF	±5%	GRM31A7U2H101JW31#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	500Vdc	U2J	120pF	±5%	GRM31A7U2H121JW31#	
			150pF	±5%	GRM31A7U2H151JW31#	
			180pF	±5%	GRM31A7U2H181JW31#	
			220pF	±5%	GRM31A7U2H221JW31#	
			270pF	±5%	GRM31A7U2H271JW31#	
			330pF	±5%	GRM31A7U2H331JW31#	
			390pF	±5%	GRM31A7U2H391JW31#	
			470pF	±5%	GRM31A7U2H471JW31#	
			560pF	±5%	GRM31A7U2H561JW31#	
			680pF	±5%	GRM31A7U2H681JW31#	
			820pF	±5%	GRM31A7U2H821JW31#	
			1000pF	±5%	GRM31A7U2H102JW31#	
			1200pF	±5%	GRM31A7U2H122JW31#	
			1500pF	±5%	GRM31A7U2H152JW31#	
			1800pF	±5%	GRM31A7U2H182JW31#	
			2200pF	±5%	GRM31A7U2H222JW31#	
	250Vdc	C0G	390pF	±5%	GRM31A5C2E391JWA1#	
			470pF	±5%	GRM31A5C2E471JWA1#	
			560pF	±5%	GRM31A5C2E561JWA1#	
			680pF	±5%	GRM31A5C2E681JWA1#	
			820pF	±5%	GRM31A5C2E821JWA1#	
			1000pF	±5%	GRM31A5C2E102JWA1#	
			1200pF	±5%	GRM31A5C2E122JWA1#	
			1500pF	±5%	GRM31A5C2E152JWA1#	
			1800pF	±5%	GRM31A5C2E182JWA1#	
			2200pF	±5%	GRM31A5C2E222JWA1#	
			2700pF	±5%	GRM31A5C2E272JWA1#	
			3300pF	±5%	GRM31A5C2E332JWA1#	
			3900pF	±5%	GRM31A5C2E392JWA1#	
			4700pF	±5%	GRM31A5C2E472JWA1#	
			5600pF	±5%	GRM31A5C2E562JWA1#	
			6800pF	±5%	GRM31A5C2E682JWA1#	
		U2J	2700pF	±5%	GRM31A7U2E272JW31#	
			3300pF	±5%	GRM31A7U2E332JW31#	
			3900pF	±5%	GRM31A7U2E392JW31#	
			4700pF	±5%	GRM31A7U2E472JW31#	
			5600pF	±5%	GRM31A7U2E562JW31#	
	200Vdc	U2J	2700pF	±5%	GRM31A7U2D272JW31#	
			3300pF	±5%	GRM31A7U2D332JW31#	
			3900pF	±5%	GRM31A7U2D392JW31#	
			4700pF	±5%	GRM31A7U2D472JW31#	
			5600pF	±5%	GRM31A7U2D562JW31#	
1.25mm	1000Vdc	C0G	560pF	±5%	GRM31B5C3A561JWA1#	
			680pF	±5%	GRM31B5C3A681JWA1#	
		U2J	390pF	±5%	GRM31B7U3A391JW31#	
			470pF	±5%	GRM31B7U3A471JW31#	
			560pF	±5%	GRM31B7U3A561JW31#	
			680pF	±5%	GRM31B7U3A681JW31#	
	630Vdc	C0G	680pF	±5%	GRM31B5C2J681JW01#	
			820pF	±5%	GRM31B5C2J821JW01#	
			1000pF	±5%	GRM31B5C2J102JW01#	
			2200pF	±5%	GRM31B5C2J222JWA1#	
			2700pF	±5%	GRM31B5C2J272JWA1#	
		U2J	2700pF	±5%	GRM31B7U2J272JW31#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 3.2×1.6mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.25mm	630Vdc	U2J	3300pF	±5%	GRM31B7U2J332JW31#	
	500Vdc	C0G	680pF	±5%	GRM31B5C2H681JW01#	
			820pF	±5%	GRM31B5C2H821JW01#	
			1000pF	±5%	GRM31B5C2H102JW01#	
		U2J	2700pF	±5%	GRM31B7U2H272JW31#	
			3300pF	±5%	GRM31B7U2H332JW31#	
	250Vdc	C0G	8200pF	±5%	GRM31B5C2E822JWA1#	
			10000pF	±5%	GRM31B5C2E103JWA1#	
			12000pF	±5%	GRM31B5C2E123JWA1#	
		U2J	6800pF	±5%	GRM31B7U2E682JW31#	
			8200pF	±5%	GRM31B7U2E822JW31#	
			10000pF	±5%	GRM31B7U2E103JW31#	
			12000pF	±5%	GRM31B7U2E123JW31#	
	200Vdc	U2J	6800pF	±5%	GRM31B7U2D682JW31#	
			8200pF	±5%	GRM31B7U2D822JW31#	
			10000pF	±5%	GRM31B7U2D103JW31#	
	100Vdc	C0G	47000pF	±5%	GRM31M5C2A473JA01#	D1
			56000pF	±5%	GRM31M5C2A563JA01#	D1
		CH	47000pF	±5%	GRM31M2C2A473JA01#	D1
			56000pF	±5%	GRM31M2C2A563JA01#	D1
	50Vdc	C0G	47000pF	±5%	GRM31M5C1H473JA01#	
			56000pF	±5%	GRM31M5C1H563JA01#	
		CH	47000pF	±5%	GRM31M2C1H473JA01#	
			56000pF	±5%	GRM31M2C1H563JA01#	
		SL	68000pF	±5%	GRM31M1X1H683JA01#	
			82000pF	±5%	GRM31M1X1H823JA01#	
			0.10μF	±5%	GRM31M1X1H104JA01#	
		U2J	68000pF	±5%	GRM31M7U1H683JA01#	
			82000pF	±5%	GRM31M7U1H823JA01#	
			0.10μF	±5%	GRM31M7U1H104JA01#	
		UJ	68000pF	±5%	GRM31M3U1H683JA01#	
			82000pF	±5%	GRM31M3U1H823JA01#	
			0.10μF	±5%	GRM31M3U1H104JA01#	
1.8mm	1000Vdc	C0G	820pF	±5%	GRM31C5C3A821JWA3#	
			1000pF	±5%	GRM31C5C3A102JWA3#	
		U2J	820pF	±5%	GRM31C7U3A821JW32#	
			1000pF	±5%	GRM31C7U3A102JW32#	
	630Vdc	C0G	3300pF	±5%	GRM31C5C2J332JWA3#	
		U2J	3900pF	±5%	GRM31C7U2J392JW32#	
			4700pF	±5%	GRM31C7U2J472JW32#	
	500Vdc	U2J	3900pF	±5%	GRM31C7U2H392JW32#	
			4700pF	±5%	GRM31C7U2H472JW32#	
	250Vdc	C0G	15000pF	±5%	GRM31C5C2E153JWA3#	
		U2J	15000pF	±5%	GRM31C7U2E153JW32#	
			18000pF	±5%	GRM31C7U2E183JW32#	
			22000pF	±5%	GRM31C7U2E223JW32#	
	100Vdc	C0G	68000pF	±5%	GRM31C5C2A683JA01#	D1
			82000pF	±5%	GRM31C5C2A823JA01#	D1
			0.10μF	±5%	GRM31C5C2A104JA01#	D1
		CH	68000pF	±5%	GRM31C2C2A683JA01#	D1
			82000pF	±5%	GRM31C2C2A823JA01#	D1
			0.10μF	±5%	GRM31C2C2A104JA01#	D1
	50Vdc	C0G	68000pF	±5%	GRM31C5C1H683JA01#	
			82000pF	±5%	GRM31C5C1H823JA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.8mm	50Vdc	C0G	0.10μF	±5%	GRM31C5C1H104JA01#	
		CH	68000pF	±5%	GRM31C2C1H683JA01#	
			82000pF	±5%	GRM31C2C1H823JA01#	
			0.10μF	±5%	GRM31C2C1H104JA01#	
	25Vdc	C0G	0.12μF	±5%	GRM31C5C1E124JA01#	
		CH	0.12μF	±5%	GRM31C2C1E124JA01#	
	16Vdc	C0G	0.12μF	±5%	GRM31C5C1C124JA01#	
		CH	0.12μF	±5%	GRM31C2C1C124JA01#	

3.2×2.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	2000Vdc	U2J	82pF	±5%	GRM32A7U3D820JW31#	
			100pF	±5%	GRM32A7U3D101JW31#	
			120pF	±5%	GRM32A7U3D121JW31#	
			150pF	±5%	GRM32A7U3D151JW31#	
	630Vdc	U2J	1200pF	±5%	GRM32A7U2J122JW31#	
			1500pF	±5%	GRM32A7U2J152JW31#	
			1800pF	±5%	GRM32A7U2J182JW31#	
			2200pF	±5%	GRM32A7U2J222JW31#	
	500Vdc	U2J	1200pF	±5%	GRM32A7U2H122JW31#	
			1500pF	±5%	GRM32A7U2H152JW31#	
			1800pF	±5%	GRM32A7U2H182JW31#	
			2200pF	±5%	GRM32A7U2H222JW31#	
1.25mm	2000Vdc	U2J	180pF	±5%	GRM32B7U3D181JW31#	
			220pF	±5%	GRM32B7U3D221JW31#	
	1000Vdc	U2J	1200pF	±5%	GRM32B7U3A122JW31#	
	630Vdc	U2J	5600pF	±5%	GRM32B7U2J562JW31#	
	500Vdc	U2J	5600pF	±5%	GRM32B7U2H562JW31#	
1.5mm	1000Vdc	U2J	1500pF	±5%	GRM32Q7U3A152JW31#	
	630Vdc	U2J	6800pF	±5%	GRM32Q7U2J682JW31#	
	500Vdc	U2J	6800pF	±5%	GRM32Q7U2H682JW31#	
	250Vdc	U2J	27000pF	±5%	GRM32Q7U2E273JW31#	
2.0mm	1000Vdc	U2J	1800pF	±5%	GRM32D7U3A182JW31#	
			2200pF	±5%	GRM32D7U3A222JW31#	
	630Vdc	U2J	8200pF	±5%	GRM32D7U2J822JW31#	
			10000pF	±5%	GRM32D7U2J103JW31#	
	500Vdc	U2J	8200pF	±5%	GRM32D7U2H822JW31#	
			10000pF	±5%	GRM32D7U2H103JW31#	
	250Vdc	U2J	33000pF	±5%	GRM32D7U2E333JW31#	
			39000pF	±5%	GRM32D7U2E393JW31#	
			47000pF	±5%	GRM32D7U2E473JW31#	

4.5×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	3150Vdc	U2J	10pF	±5%	GRM42A7U3F100JW31#	
			12pF	±5%	GRM42A7U3F120JW31#	
			15pF	±5%	GRM42A7U3F150JW31#	
			18pF	±5%	GRM42A7U3F180JW31#	
			22pF	±5%	GRM42A7U3F220JW31#	
			27pF	±5%	GRM42A7U3F270JW31#	

Part number # indicates the package specification code.

GRM Series Temperature Compensating Type Part Number List

(→ 4.5×2.0mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	3150Vdc	U2J	33pF	±5%	**GRM42A7U3F330JW31#**	
			39pF	±5%	**GRM42A7U3F390JW31#**	
			47pF	±5%	**GRM42A7U3F470JW31#**	
			56pF	±5%	**GRM42A7U3F560JW31#**	
			68pF	±5%	**GRM42A7U3F680JW31#**	
			82pF	±5%	**GRM42A7U3F820JW31#**	
			100pF	±5%	**GRM42A7U3F101JW31#**	

4.5×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.5mm	1000Vdc	U2J	2700pF	±5%	**GRM43Q7U3A272JW31#**	
			3300pF	±5%	**GRM43Q7U3A332JW31#**	
	630Vdc	U2J	12000pF	±5%	**GRM43Q7U2J123JW31#**	
	500Vdc	U2J	12000pF	±5%	**GRM43Q7U2H123JW31#**	
2.0mm	1000Vdc	U2J	3900pF	±5%	**GRM43D7U3A392JW31#**	
			4700pF	±5%	**GRM43D7U3A472JW31#**	
	630Vdc	U2J	15000pF	±5%	**GRM43D7U2J153JW31#**	
			18000pF	±5%	**GRM43D7U2J183JW31#**	
			22000pF	±5%	**GRM43D7U2J223JW31#**	
	500Vdc	U2J	15000pF	±5%	**GRM43D7U2H153JW31#**	
			18000pF	±5%	**GRM43D7U2H183JW31#**	
			22000pF	±5%	**GRM43D7U2H223JW31#**	

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.5mm	1000Vdc	U2J	5600pF	±5%	**GRM55Q7U3A562JW31#**	
			6800pF	±5%	**GRM55Q7U3A682JW31#**	
	630Vdc	U2J	27000pF	±5%	**GRM55Q7U2J273JW31#**	
	500Vdc	U2J	27000pF	±5%	**GRM55Q7U2H273JW31#**	
2.0mm	1000Vdc	U2J	8200pF	±5%	**GRM55D7U3A822JW31#**	
			10000pF	±5%	**GRM55D7U3A103JW31#**	
	630Vdc	U2J	33000pF	±5%	**GRM55D7U2J333JW31#**	
			39000pF	±5%	**GRM55D7U2J393JW31#**	
			47000pF	±5%	**GRM55D7U2J473JW31#**	
	500Vdc	U2J	33000pF	±5%	**GRM55D7U2H333JW31#**	
			39000pF	±5%	**GRM55D7U2H393JW31#**	
			47000pF	±5%	**GRM55D7U2H473JW31#**	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

0.4×0.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	16Vdc	X7R	100pF	±10%	GRM022R71C101KE14#	
				±20%	GRM022R71C101ME14#	
			150pF	±10%	GRM022R71C151KE14#	
				±20%	GRM022R71C151ME14#	
			220pF	±10%	GRM022R71C221KE14#	
				±20%	GRM022R71C221ME14#	
			330pF	±10%	GRM022R71C331KE14#	
				±20%	GRM022R71C331ME14#	
			470pF	±10%	GRM022R71C471KE14#	
				±20%	GRM022R71C471ME14#	
			1000pF	±10%	GRM022R71C102KE14#	
				±20%	GRM022R71C102ME14#	
	10Vdc	X7R	100pF	±10%	GRM022R71A101KA01#	
				±20%	GRM022R71A101MA01#	
			150pF	±10%	GRM022R71A151KA01#	
				±20%	GRM022R71A151MA01#	
			220pF	±10%	GRM022R71A221KA01#	
				±20%	GRM022R71A221MA01#	
			330pF	±10%	GRM022R71A331KA01#	
				±20%	GRM022R71A331MA01#	
			470pF	±10%	GRM022R71A471KA01#	
				±20%	GRM022R71A471MA01#	
			680pF	±10%	GRM022R71A681KA12#	
				±20%	GRM022R71A681MA12#	
			820pF	±10%	GRM022R71A821KA12#	
				±20%	GRM022R71A821MA12#	
			1000pF	±10%	GRM022R71A102KA12#	
				±20%	GRM022R71A102MA12#	
		X5R	100pF	±10%	GRM022R61A101KA01#	
				±20%	GRM022R61A101MA01#	
			150pF	±10%	GRM022R61A151KA01#	
				±20%	GRM022R61A151MA01#	
			220pF	±10%	GRM022R61A221KA01#	
				±20%	GRM022R61A221MA01#	
			330pF	±10%	GRM022R61A331KA01#	
				±20%	GRM022R61A331MA01#	
			470pF	±10%	GRM022R61A471KA01#	
				±20%	GRM022R61A471MA01#	
			680pF	±10%	GRM022R61A681KE19#	
				±20%	GRM022R61A681ME19#	
			1000pF	±10%	GRM022R61A102KE19#	
				±20%	GRM022R61A102ME19#	
			1500pF	±10%	GRM022R61A152KE19#	
				±20%	GRM022R61A152ME19#	
			2200pF	±10%	GRM022R61A222KE19#	
				±20%	GRM022R61A222ME19#	
			3300pF	±10%	GRM022R61A332KE19#	
				±20%	GRM022R61A332ME19#	
			4700pF	±10%	GRM022R61A472KE19#	
				±20%	GRM022R61A472ME19#	
			6800pF	±10%	GRM022R61A682KE19#	
				±20%	GRM022R61A682ME19#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	10Vdc	X5R	10000pF	±10%	GRM022R61A103KE19#	
				±20%	GRM022R61A103ME19#	
		B	100pF	±10%	GRM022B11A101KA01#	
				±20%	GRM022B11A101MA01#	
			150pF	±10%	GRM022B11A151KA01#	
				±20%	GRM022B11A151MA01#	
			220pF	±10%	GRM022B11A221KA01#	
				±20%	GRM022B11A221MA01#	
			330pF	±10%	GRM022B11A331KA01#	
				±20%	GRM022B11A331MA01#	
			470pF	±10%	GRM022B11A471KA01#	
				±20%	GRM022B11A471MA01#	
			680pF	±10%	GRM022B31A681KE19#	
				±20%	GRM022B31A681ME19#	
			1000pF	±10%	GRM022B31A102KE19#	
				±20%	GRM022B31A102ME19#	
			1500pF	±10%	GRM022B31A152KE19#	
				±20%	GRM022B31A152ME19#	
			2200pF	±10%	GRM022B31A222KE19#	
				±20%	GRM022B31A222ME19#	
			3300pF	±10%	GRM022B31A332KE19#	
				±20%	GRM022B31A332ME19#	
			4700pF	±10%	GRM022B31A472KE19#	
				±20%	GRM022B31A472ME19#	
			6800pF	±10%	GRM022B31A682KE19#	
				±20%	GRM022B31A682ME19#	
			10000pF	±10%	GRM022B31A103KE19#	
				±20%	GRM022B31A103ME19#	
	6.3Vdc	X5R	1000pF	±20%	GRM022R60J102ME19#	
			1500pF	±20%	GRM022R60J152ME19#	
			2200pF	±20%	GRM022R60J222ME19#	
			3300pF	±20%	GRM022R60J332ME19#	
			4700pF	±20%	GRM022R60J472ME19#	
			6800pF	±20%	GRM022R60J682ME19#	
			10000pF	±20%	GRM022R60J103ME19#	
			15000pF	±20%	GRM022R60J153ME15#	D1
			22000pF	±10%	GRM022R60J223KE15#	D1
				±20%	GRM022R60J223ME15#	D1
			33000pF	±20%	GRM022R60J333ME15#	D1
			47000pF	±20%	GRM022R60J473ME15#	D1
			68000pF	±20%	GRM022R60J683ME15#	D1
			0.10μF	±20%	GRM022R60J104ME15#	D1
		B	1000pF	±20%	GRM022B30J102ME19#	
			1500pF	±20%	GRM022B30J152ME19#	
			2200pF	±20%	GRM022B30J222ME19#	
			3300pF	±20%	GRM022B30J332ME19#	
			4700pF	±20%	GRM022B30J472ME19#	
			6800pF	±20%	GRM022B30J682ME19#	
			10000pF	±20%	GRM022B30J103ME19#	
	4Vdc	X6T	0.10μF	±20%	GRM022D80G104ME15#	D1
		X5R	15000pF	±10%	GRM022R60G153KE15#	
				±20%	GRM022R60G153ME15#	
			22000pF	±10%	GRM022R60G223KE15#	
				±20%	GRM022R60G223ME15#	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	4Vdc	X5R	33000pF	±10%	GRM022R60G333KE15#	
				±20%	GRM022R60G333ME15#	
			47000pF	±10%	GRM022R60G473KE15#	
				±20%	GRM022R60G473ME15#	
			68000pF	±20%	GRM022R60G683ME15#	
			0.10μF	±20%	GRM022R60G104ME15#	
	2.5Vdc	X6T	0.10μF	±20%	GRM022D80E104ME15#	

0.6×0.3mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	50Vdc	X7R	100pF	±10%	GRM033R71H101KA12#	
				±20%	GRM033R71H101MA12#	
			150pF	±10%	GRM033R71H151KA12#	
				±20%	GRM033R71H151MA12#	
			220pF	±10%	GRM033R71H221KA12#	
				±20%	GRM033R71H221MA12#	
			330pF	±10%	GRM033R71H331KA12#	
				±20%	GRM033R71H331MA12#	
			470pF	±10%	GRM033R71H471KA12#	
				±20%	GRM033R71H471MA12#	
			680pF	±10%	GRM033R71H681KA12#	
				±20%	GRM033R71H681MA12#	
			1000pF	±10%	GRM033R71H102KA12#	
				±20%	GRM033R71H102MA12#	
			1500pF	±10%	GRM033R71H152KA12#	
				±20%	GRM033R71H152MA12#	
		X5R	470pF	±10%	GRM033R61H471KA12#	
		B	100pF	±10%	GRM033B31H101KA12#	
				±20%	GRM033B31H101MA12#	
			150pF	±10%	GRM033B31H151KA12#	
				±20%	GRM033B31H151MA12#	
			220pF	±10%	GRM033B31H221KA12#	
				±20%	GRM033B31H221MA12#	
			330pF	±10%	GRM033B31H331KA12#	
				±20%	GRM033B31H331MA12#	
			470pF	±10%	GRM033B31H471KA12#	
				±20%	GRM033B31H471MA12#	
			680pF	±10%	GRM033B31H681KA12#	
				±20%	GRM033B31H681MA12#	
			1000pF	±10%	GRM033B31H102KA12#	
				±20%	GRM033B31H102MA12#	
			1500pF	±10%	GRM033B31H152KA12#	
				±20%	GRM033B31H152MA12#	
	35Vdc	X5R	0.10μF	±10%	GRM033R6YA104KE14#	D1
				±20%	GRM033R6YA104ME14#	D1
	25Vdc	X7R	1000pF	±10%	GRM033R71E102KA01#	
			1500pF	±10%	GRM033R71E152KA01#	
			2200pF	±10%	GRM033R71E222KA12#	
				±20%	GRM033R71E222MA12#	
			3300pF	±10%	GRM033R71E332KA12#	
				±20%	GRM033R71E332MA12#	
			4700pF	±10%	GRM033R71E472KE14#	D1

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	25Vdc	X7R	4700pF	±20%	GRM033R71E472ME14#	D1
			6800pF	±10%	GRM033R71E682KE14#	D1
				±20%	GRM033R71E682ME14#	D1
			10000pF	±10%	GRM033R71E103KE14#	D1
				±20%	GRM033R71E103ME14#	D1
		R	100pF	±10%	GRM033R11E101KA01#	
			150pF	±10%	GRM033R11E151KA01#	
			220pF	±10%	GRM033R11E221KA01#	
			330pF	±10%	GRM033R11E331KA01#	
			470pF	±10%	GRM033R11E471KA01#	
			680pF	±10%	GRM033R11E681KA01#	
			1000pF	±10%	GRM033R11E102KA01#	
			1500pF	±10%	GRM033R11E152KA01#	
		X6S	0.10μF	±10%	GRM033C81E104KE14#	D1
				±20%	GRM033C81E104ME14#	D1
		X5R	4700pF	±10%	GRM033R61E472KA12#	D1
				±20%	GRM033R61E472MA12#	D1
			6800pF	±10%	GRM033R61E682KA12#	D1
				±20%	GRM033R61E682MA12#	D1
			10000pF	±10%	GRM033R61E103KA12#	D1
				±20%	GRM033R61E103MA12#	D1
			0.10μF	±10%	GRM033R61E104KE14#	
				±20%	GRM033R61E104ME14#	
		B	1000pF	±10%	GRM033B11E102KA01#	
				±20%	GRM033B11E102MA01#	
			1500pF	±10%	GRM033B11E152KA01#	
				±20%	GRM033B11E152MA01#	
			2200pF	±10%	GRM033B31E222KA12#	
				±20%	GRM033B31E222MA12#	
			3300pF	±10%	GRM033B31E332KA12#	
				±20%	GRM033B31E332MA12#	
			10000pF	±10%	GRM033B31E103KA12#	D1
				±20%	GRM033B31E103MA12#	D1
	16Vdc	X7R	2200pF	±10%	GRM033R71C222KA88#	
			3300pF	±10%	GRM033R71C332KA88#	
			4700pF	±10%	GRM033R71C472KE14#	
				±20%	GRM033R71C472ME14#	
			6800pF	±10%	GRM033R71C682KE14#	
				±20%	GRM033R71C682ME14#	
			10000pF	±10%	GRM033R71C103KE14#	
				±20%	GRM033R71C103ME14#	
		X7S	0.10μF	±10%	GRM033C71C104KE14#	D1
				±20%	GRM033C71C104ME14#	D1
		R	2200pF	±10%	GRM033R11C222KA88#	
			3300pF	±10%	GRM033R11C332KA88#	
		X6S	0.10μF	±10%	GRM033C81C104KE14#	
				±20%	GRM033C81C104ME14#	
		X5R	10000pF	±10%	GRM033R61C103KA12#	
				±20%	GRM033R61C103MA12#	
			15000pF	±10%	GRM033R61C153KE84#	D1
				±20%	GRM033R61C153ME84#	D1
			22000pF	±10%	GRM033R61C223KE84#	D1
				±20%	GRM033R61C223ME84#	D1
			33000pF	±10%	GRM033R61C333KE84#	D1

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	16Vdc	X5R	33000pF	±20%	GRM033R61C333ME84#	D1
			47000pF	±10%	GRM033R61C473KE84#	D1
				±20%	GRM033R61C473ME84#	D1
			68000pF	±10%	GRM033R61C683KE84#	D1
				±20%	GRM033R61C683ME84#	D1
			0.10μF	±10%	GRM033R61C104KE14#	
				±20%	GRM033R61C104ME14#	
		B	2200pF	±10%	GRM033B31C222KA87#	
				±20%	GRM033B31C222MA87#	
			3300pF	±10%	GRM033B31C332KA87#	
				±20%	GRM033B31C332MA87#	
			10000pF	±10%	GRM033B31C103KA12#	
				±20%	GRM033B31C103MA12#	
			15000pF	±10%	GRM033B31C153KE84#	D1
				±20%	GRM033B31C153ME84#	D1
			22000pF	±10%	GRM033B31C223KE84#	D1
				±20%	GRM033B31C223ME84#	D1
			33000pF	±10%	GRM033B31C333KE84#	D1
				±20%	GRM033B31C333ME84#	D1
			47000pF	±10%	GRM033B31C473KE84#	D1
				±20%	GRM033B31C473ME84#	D1
			68000pF	±10%	GRM033B31C683KE84#	D1
				±20%	GRM033B31C683ME84#	D1
			0.10μF	±10%	GRM033B31C104KE84#	D1
				±20%	GRM033B31C104ME84#	D1
	10Vdc	X7R	4700pF	±10%	GRM033R71A472KA01#	
				±20%	GRM033R71A472MA01#	
			6800pF	±10%	GRM033R71A682KA01#	
				±20%	GRM033R71A682MA01#	
			10000pF	±10%	GRM033R71A103KA01#	
				±20%	GRM033R71A103MA01#	
		X7S	0.10μF	±10%	GRM033C71A104KE14#	
				±20%	GRM033C71A104ME14#	
		R	4700pF	±10%	GRM033R11A472KA01#	
				±20%	GRM033R11A472MA01#	
			6800pF	±10%	GRM033R11A682KA01#	
				±20%	GRM033R11A682MA01#	
			10000pF	±10%	GRM033R11A103KA01#	
				±20%	GRM033R11A103MA01#	
		X5R	4700pF	±10%	GRM033R61A472KA01#	
				±20%	GRM033R61A472MA01#	
			6800pF	±10%	GRM033R61A682KA01#	
				±20%	GRM033R61A682MA01#	
			15000pF	±10%	GRM033R61A153KE84#	
				±20%	GRM033R61A153ME84#	
			22000pF	±10%	GRM033R61A223KE84#	
				±20%	GRM033R61A223ME84#	
			33000pF	±10%	GRM033R61A333KE84#	
				±20%	GRM033R61A333ME84#	
			47000pF	±10%	GRM033R61A473KE84#	
				±20%	GRM033R61A473ME84#	
			68000pF	±10%	GRM033R61A683KE84#	
				±20%	GRM033R61A683ME84#	
			0.10μF	±10%	GRM033R61A104KE84#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.33mm	10Vdc	X5R	0.10μF	±20%	GRM033R61A104ME84#	
			0.22μF	±20%	GRM033R61A224ME90#	D1
		B	4700pF	±10%	GRM033B11A472KA01#	
				±20%	GRM033B11A472MA01#	
			6800pF	±10%	GRM033B11A682KA01#	
				±20%	GRM033B11A682MA01#	
			15000pF	±10%	GRM033B31A153KE84#	
				±20%	GRM033B31A153ME84#	
			22000pF	±10%	GRM033B31A223KE84#	
				±20%	GRM033B31A223ME84#	
			33000pF	±10%	GRM033B31A333KE84#	
				±20%	GRM033B31A333ME84#	
			47000pF	±10%	GRM033B31A473KE84#	
				±20%	GRM033B31A473ME84#	
			68000pF	±10%	GRM033B31A683KE84#	
				±20%	GRM033B31A683ME84#	
			0.10μF	±10%	GRM033B31A104KE84#	
				±20%	GRM033B31A104ME84#	
	6.3Vdc	X7R	4700pF	±10%	GRM033R70J472KA01#	
			6800pF	±10%	GRM033R70J682KA01#	
			10000pF	±10%	GRM033R70J103KA01#	
		R	4700pF	±10%	GRM033R10J472KA01#	
			6800pF	±10%	GRM033R10J682KA01#	
			10000pF	±10%	GRM033R10J103KA01#	
		X6S	15000pF	±10%	GRM033C80J153KE01#	
				±20%	GRM033C80J153ME01#	
			22000pF	±10%	GRM033C80J223KE01#	
				±20%	GRM033C80J223ME01#	
			33000pF	±10%	GRM033C80J333KE01#	
				±20%	GRM033C80J333ME01#	
			47000pF	±10%	GRM033C80J473KE19#	
				±20%	GRM033C80J473ME19#	
			68000pF	±10%	GRM033C80J683KE84#	D1
				±20%	GRM033C80J683ME84#	D1
			0.10μF	±10%	GRM033C80J104KE84#	D1
				±20%	GRM033C80J104ME84#	D1
			0.22μF	±20%	GRM033C80J224ME90#	D1
		X5R	0.22μF	±20%	GRM033R60J224ME90#	
		B	4700pF	±10%	GRM033B10J472KA01#	
			6800pF	±10%	GRM033B10J682KA01#	
			15000pF	±10%	GRM033B10J153KE01#	
				±20%	GRM033B10J153ME01#	
			22000pF	±10%	GRM033B10J223KE01#	
				±20%	GRM033B10J223ME01#	
			33000pF	±10%	GRM033B10J333KE01#	
				±20%	GRM033B10J333ME01#	
	4Vdc	X6S	0.22μF	±20%	GRM033C80G224ME90#	

1.0×0.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	10Vdc	X5R	0.10μF	±10%	GRM152R61A104KE19#	D1
				±20%	GRM152R61A104ME19#	D1

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.22mm	10Vdc	X5R	0.22μF	±10%	GRM152R61A224KE19#	D1
				±20%	GRM152R61A224ME19#	D1
		B	0.10μF	±10%	GRM152B31A104KE19#	D1
				±20%	GRM152B31A104ME19#	D1
			0.22μF	±10%	GRM152B31A224KE19#	D1
				±20%	GRM152B31A224ME19#	D1
	6.3Vdc	X6S	0.10μF	±10%	GRM152C80J104KE19#	D1
				±20%	GRM152C80J104ME19#	D1
			0.22μF	±10%	GRM152C80J224KE19#	D1
				±20%	GRM152C80J224ME19#	D1
		X5R	0.10μF	±10%	GRM152R60J104KE19#	
				±20%	GRM152R60J104ME19#	
			0.22μF	±10%	GRM152R60J224KE19#	
				±20%	GRM152R60J224ME19#	
			0.47μF	±20%	GRM152R60J474ME15#	D1
			1.0μF	±20%	GRM152R60J105ME15#	D1
		B	0.10μF	±10%	GRM152B30J104KE19#	
				±20%	GRM152B30J104ME19#	
			0.22μF	±10%	GRM152B30J224KE19#	
				±20%	GRM152B30J224ME19#	
			0.47μF	±20%	GRM152B30J474ME15#	D1
	4Vdc	X7T	0.10μF	±10%	GRM152D70G104KE15#	D1
				±20%	GRM152D70G104ME15#	D1
			0.22μF	±10%	GRM152D70G224KE15#	D1
				±20%	GRM152D70G224ME15#	D1
		X6S	0.10μF	±10%	GRM152C80G104KE19#	
				±20%	GRM152C80G104ME19#	
			0.22μF	±10%	GRM152C80G224KE19#	
				±20%	GRM152C80G224ME19#	
		X6T	0.47μF	±20%	GRM152D80G474ME15#	
			1.0μF	±20%	GRM152D80G105ME15#	D1
		X5R	1.0μF	±20%	GRM152R60G105ME15#	
	2.5Vdc	X7T	0.10μF	±10%	GRM152D70E104KE19#	
				±20%	GRM152D70E104ME19#	
			0.22μF	±10%	GRM152D70E224KE19#	
				±20%	GRM152D70E224ME19#	
0.3mm	50Vdc	X7R	220pF	±10%	GRM15XR71H221KA86#	
			330pF	±10%	GRM15XR71H331KA86#	
			470pF	±10%	GRM15XR71H471KA86#	
			680pF	±10%	GRM15XR71H681KA86#	
			1000pF	±10%	GRM15XR71H102KA86#	
			1500pF	±10%	GRM15XR71H152KA86#	
		R	220pF	±10%	GRM15XR11H221KA86#	
			330pF	±10%	GRM15XR11H331KA86#	
			470pF	±10%	GRM15XR11H471KA86#	
			680pF	±10%	GRM15XR11H681KA86#	
			1000pF	±10%	GRM15XR11H102KA86#	
			1500pF	±10%	GRM15XR11H152KA86#	
		B	220pF	±10%	GRM15XB11H221KA86#	
				±20%	GRM15XB11H221MA86#	
			330pF	±10%	GRM15XB11H331KA86#	
				±20%	GRM15XB11H331MA86#	
			470pF	±10%	GRM15XB11H471KA86#	
				±20%	GRM15XB11H471MA86#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.3mm	50Vdc	B	680pF	±10%	GRM15XB11H681KA86#	
				±20%	GRM15XB11H681MA86#	
			1000pF	±10%	GRM15XB11H102KA86#	
				±20%	GRM15XB11H102MA86#	
			1500pF	±10%	GRM15XB11H152KA86#	
				±20%	GRM15XB11H152MA86#	
	25Vdc	X7R	2200pF	±10%	GRM15XR71E222KA86#	
				±20%	GRM15XR71E222MA86#	
		B	2200pF	±10%	GRM15XB11E222KA86#	
				±20%	GRM15XB11E222MA86#	
	16Vdc	X7R	3300pF	±10%	GRM15XR71C332KA86#	
				±20%	GRM15XR71C332MA86#	
			4700pF	±10%	GRM15XR71C472KA86#	
				±20%	GRM15XR71C472MA86#	
			6800pF	±10%	GRM15XR71C682KA86#	
				±20%	GRM15XR71C682MA86#	
			10000pF	±10%	GRM15XR71C103KA86#	
				±20%	GRM15XR71C103MA86#	
		B	3300pF	±10%	GRM15XB11C332KA86#	
				±20%	GRM15XB11C332MA86#	
			4700pF	±10%	GRM15XB11C472KA86#	
				±20%	GRM15XB11C472MA86#	
			6800pF	±10%	GRM15XB11C682KA86#	
				±20%	GRM15XB11C682MA86#	
			10000pF	±10%	GRM15XB11C103KA86#	
				±20%	GRM15XB11C103MA86#	
	10Vdc	X5R	15000pF	±10%	GRM15XR61A153KA86#	
				±20%	GRM15XR61A153MA86#	
			22000pF	±10%	GRM15XR61A223KA86#	
				±20%	GRM15XR61A223MA86#	
			33000pF	±10%	GRM15XR61A333KA86#	
				±20%	GRM15XR61A333MA86#	
0.33mm	10Vdc	X5R	1.0μF	±20%	GRM153R61A105ME95#	D1
		B	1.0μF	±20%	GRM153B31A105ME95#	D1
	6.3Vdc	X6T	1.0μF	±20%	GRM153D80J105ME95#	D1
		X5R	1.0μF	±20%	GRM153R60J105ME95#	
		B	1.0μF	±20%	GRM153B30J105ME95#	
	4Vdc	X6T	1.0μF	±20%	GRM153D80G105ME95#	
0.55mm	100Vdc	X7R	220pF	±10%	GRM155R72A221KA01#	
			330pF	±10%	GRM155R72A331KA01#	
			470pF	±10%	GRM155R72A471KA01#	
			680pF	±10%	GRM155R72A681KA01#	
			1000pF	±10%	GRM155R72A102KA01#	
			1500pF	±10%	GRM155R72A152KA01#	
			2200pF	±10%	GRM155R72A222KA01#	
			3300pF	±10%	GRM155R72A332KA01#	
			4700pF	±10%	GRM155R72A472KA01#	
	50Vdc	X7R	220pF	±10%	GRM155R71H221KA01#	
			330pF	±10%	GRM155R71H331KA01#	
			470pF	±10%	GRM155R71H471KA01#	
			680pF	±10%	GRM155R71H681KA01#	
			1000pF	±10%	GRM155R71H102KA01#	
			1500pF	±10%	GRM155R71H152KA01#	
			2200pF	±10%	GRM155R71H222KA01#	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	X7R	3300pF	±10%	GRM155R71H332KA01#	
			4700pF	±10%	GRM155R71H472KA01#	
			6800pF	±10%	GRM155R71H682KA88#	
			10000pF	±10%	GRM155R71H103KA88#	
			15000pF	±10%	GRM155R71H153KA12#	
			22000pF	±10%	GRM155R71H223KA12#	
			33000pF	±10%	GRM155R71H333KE14#	
				±20%	GRM155R71H333ME14#	
			47000pF	±10%	GRM155R71H473KE14#	
				±20%	GRM155R71H473ME14#	
			68000pF	±10%	GRM155R71H683KE14#	
				±20%	GRM155R71H683ME14#	
			0.10μF	±10%	GRM155R71H104KE14#	
				±20%	GRM155R71H104ME14#	
		R	220pF	±10%	GRM155R11H221KA01#	
			330pF	±10%	GRM155R11H331KA01#	
			470pF	±10%	GRM155R11H471KA01#	
			680pF	±10%	GRM155R11H681KA01#	
			1000pF	±10%	GRM155R11H102KA01#	
			1500pF	±10%	GRM155R11H152KA01#	
			2200pF	±10%	GRM155R11H222KA01#	
			3300pF	±10%	GRM155R11H332KA01#	
			4700pF	±10%	GRM155R11H472KA01#	
			6800pF	±10%	GRM155R11H682KA88#	
			10000pF	±10%	GRM155R11H103KA88#	
		X6S	33000pF	±10%	GRM155C81H333KE14#	
				±20%	GRM155C81H333ME14#	
			47000pF	±10%	GRM155C81H473KE14#	
				±20%	GRM155C81H473ME14#	
			68000pF	±10%	GRM155C81H683KE14#	
				±20%	GRM155C81H683ME14#	
		X5R	33000pF	±10%	GRM155R61H333KE14#	
				±20%	GRM155R61H333ME14#	
			47000pF	±10%	GRM155R61H473KE14#	
				±20%	GRM155R61H473ME14#	
			68000pF	±10%	GRM155R61H683KE14#	
				±20%	GRM155R61H683ME14#	
			0.10μF	±10%	GRM155R61H104KE14#	
				±20%	GRM155R61H104ME14#	
		B	220pF	±10%	GRM155B11H221KA01#	
				±20%	GRM155B11H221MA01#	
			330pF	±10%	GRM155B11H331KA01#	
				±20%	GRM155B11H331MA01#	
			470pF	±10%	GRM155B11H471KA01#	
				±20%	GRM155B11H471MA01#	
			680pF	±10%	GRM155B11H681KA01#	
				±20%	GRM155B11H681MA01#	
			1000pF	±10%	GRM155B11H102KA01#	
				±20%	GRM155B11H102MA01#	
			1500pF	±10%	GRM155B11H152KA01#	
				±20%	GRM155B11H152MA01#	
			2200pF	±10%	GRM155B11H222KA01#	
				±20%	GRM155B11H222MA01#	
			3300pF	±10%	GRM155B11H332KA01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	50Vdc	B	3300pF	±20%	GRM155B11H332MA01#	
			4700pF	±10%	GRM155B11H472KA01#	
				±20%	GRM155B11H472MA01#	
			6800pF	±10%	GRM155B31H682KA88#	
				±20%	GRM155B31H682MA88#	
			10000pF	±10%	GRM155B31H103KA88#	
				±20%	GRM155B31H103MA88#	
			15000pF	±10%	GRM155B31H153KA12#	
				±20%	GRM155B31H153MA12#	
			22000pF	±10%	GRM155B31H223KA12#	
				±20%	GRM155B31H223MA12#	
			0.10μF	±10%	GRM155B31H104KE14#	
				±20%	GRM155B31H104ME14#	
	35Vdc	X6S	0.22μF	±10%	GRM155C8YA224KE01#	D1
				±20%	GRM155C8YA224ME01#	D1
		X5R	0.22μF	±10%	GRM155R6YA224KE01#	D1
				±20%	GRM155R6YA224ME01#	D1
			0.47μF	±10%	GRM155R6YA474KE01#	D1
				±20%	GRM155R6YA474ME01#	D1
	25Vdc	X7R	2200pF	±10%	GRM155R71E222KA01#	
			10000pF	±10%	GRM155R71E103KA01#	
			15000pF	±10%	GRM155R71E153KA61#	
			22000pF	±10%	GRM155R71E223KA61#	
			33000pF	±10%	GRM155R71E333KA88#	
			47000pF	±10%	GRM155R71E473KA88#	
			68000pF	±10%	GRM155R71E683KE14#	
				±20%	GRM155R71E683ME14#	
			0.10μF	±10%	GRM155R71E104KE14#	
				±20%	GRM155R71E104ME14#	
		R	6800pF	±10%	GRM155R11E682KA01#	
			10000pF	±10%	GRM155R11E103KA01#	
			15000pF	±10%	GRM155R11E153KA61#	
			22000pF	±10%	GRM155R11E223KA61#	
			33000pF	±10%	GRM155R11E333KA88#	
			47000pF	±10%	GRM155R11E473KA88#	
		X6S	0.22μF	±10%	GRM155C81E224KE01#	
				±20%	GRM155C81E224ME01#	
		X5R	68000pF	±10%	GRM155R61E683KA87#	
				±20%	GRM155R61E683MA87#	
			0.10μF	±10%	GRM155R61E104KA87#	
				±20%	GRM155R61E104MA87#	
			0.22μF	±10%	GRM155R61E224KE01#	
				±20%	GRM155R61E224ME01#	
			0.47μF	±10%	GRM155R61E474KE01#	
			1.0μF	±10%	GRM155R61E105KA12#	D1
				±20%	GRM155R61E105MA12#	D1
		B	2200pF	±10%	GRM155B11E222KA01#	
			10000pF	±10%	GRM155B11E103KA01#	
				±20%	GRM155B11E103MA01#	
			15000pF	±10%	GRM155B11E153KA61#	
				±20%	GRM155B11E153MA61#	
			22000pF	±10%	GRM155B11E223KA61#	
				±20%	GRM155B11E223MA61#	
			33000pF	±10%	GRM155B31E333KA87#	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	25Vdc	B	33000pF	±20%	GRM155B31E333MA87#	
			47000pF	±10%	GRM155B31E473KA87#	
				±20%	GRM155B31E473MA87#	
			68000pF	±10%	GRM155B31E683KA87#	
				±20%	GRM155B31E683MA87#	
			0.10μF	±10%	GRM155B31E104KA87#	
				±20%	GRM155B31E104MA87#	
			1.0μF	±10%	GRM155B31E105KA12#	D1
				±20%	GRM155B31E105MA12#	D1
	16Vdc	X7R	4700pF	±10%	GRM155R71C472KA01#	
			10000pF	±10%	GRM155R71C103KA01#	
				±20%	GRM155R71C103MA01#	
			68000pF	±10%	GRM155R71C683KA88#	
			0.15μF	±10%	GRM155R71C154KA12#	
			0.22μF	±10%	GRM155R71C224KA12#	
		R	68000pF	±10%	GRM155R11C683KA88#	
		X6S	0.47μF	±10%	GRM155C81C474KE01#	
				±20%	GRM155C81C474ME01#	
		X5R	0.22μF	±10%	GRM155R61C224KA12#	
				±20%	GRM155R61C224MA12#	
			1.0μF	±10%	GRM155R61C105KA12#	
				±20%	GRM155R61C105MA12#	
		B	10000pF	±10%	GRM155B11C103KA01#	
				±20%	GRM155B11C103MA01#	
			1.0μF	±10%	GRM155B31C105KA12#	
				±20%	GRM155B31C105MA12#	
	10Vdc	X7R	0.22μF	±10%	GRM155R71A224KE01#	
				±20%	GRM155R71A224ME01#	
			0.47μF	±10%	GRM155R71A474KE01#	
				±20%	GRM155R71A474ME01#	
		X6S	1.0μF	±10%	GRM155C81A105KA12#	
				±20%	GRM155C81A105MA12#	
		X5R	33000pF	±10%	GRM155R61A333KA01#	
			0.10μF	±10%	GRM155R61A104KA01#	
				±20%	GRM155R61A104MA01#	
			0.15μF	±10%	GRM155R61A154KE19#	
				±20%	GRM155R61A154ME19#	
			0.22μF	±10%	GRM155R61A224KE19#	
				±20%	GRM155R61A224ME19#	
			0.33μF	±10%	GRM155R61A334KE15#	
				±20%	GRM155R61A334ME15#	
			0.47μF	±10%	GRM155R61A474KE15#	
				±20%	GRM155R61A474ME15#	
			0.68μF	±10%	GRM155R61A684KE15#	
				±20%	GRM155R61A684ME15#	
			1.0μF	±20%	GRM155R61A105ME01#	
		B	0.15μF	±10%	GRM155B31A154KE18#	
				±20%	GRM155B31A154ME18#	
			0.22μF	±10%	GRM155B31A224KE18#	
				±20%	GRM155B31A224ME18#	
			0.33μF	±10%	GRM155B31A334KE14#	
				±20%	GRM155B31A334ME14#	
			0.47μF	±10%	GRM155B31A474KE14#	
				±20%	GRM155B31A474ME14#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.55mm	10Vdc	B	0.68μF	±10%	GRM155B31A684KE15#	
				±20%	GRM155B31A684ME15#	
			1.0μF	±20%	GRM155B31A105ME01#	
			2.2μF	±10%	GRM155B31A225KE95#	D1
				±20%	GRM155B31A225ME95#	D1
	6.3Vdc	X7R	1.0μF	±10%	GRM155R70J105KA12#	D1
				±20%	GRM155R70J105MA12#	D1
		X6S	0.22μF	±10%	GRM155C80J224KE01#	
				±20%	GRM155C80J224ME01#	
			2.2μF	±10%	GRM155C80J225KE95#	D1
				±20%	GRM155C80J225ME95#	D1
		X5R	0.10μF	±10%	GRM155R60J104KA01#	
				±20%	GRM155R60J104MA01#	
			0.15μF	±10%	GRM155R60J154KE01#	
				±20%	GRM155R60J154ME01#	
			0.22μF	±10%	GRM155R60J224KE01#	
				±20%	GRM155R60J224ME01#	
			0.33μF	±10%	GRM155R60J334KE01#	
				±20%	GRM155R60J334ME01#	
			0.47μF	±10%	GRM155R60J474KE19#	
				±20%	GRM155R60J474ME19#	
			0.68μF	±10%	GRM155R60J684KE19#	
				±20%	GRM155R60J684ME19#	
			1.0μF	±20%	GRM155R60J105ME19#	
		B	0.15μF	±10%	GRM155B10J154KE01#	
				±20%	GRM155B10J154ME01#	
			0.22μF	±10%	GRM155B10J224KE01#	
				±20%	GRM155B10J224ME01#	
			0.33μF	±10%	GRM155B10J334KE01#	
				±20%	GRM155B10J334ME01#	
			0.47μF	±10%	GRM155B30J474KE18#	
				±20%	GRM155B30J474ME18#	
			0.68μF	±10%	GRM155B30J684KE18#	
				±20%	GRM155B30J684ME18#	
			1.0μF	±20%	GRM155B30J105ME18#	
			2.2μF	±10%	GRM155B30J225KE95#	
				±20%	GRM155B30J225ME95#	
	4Vdc	X7R	1.0μF	±10%	GRM155R70G105KA12#	
				±20%	GRM155R70G105MA12#	
		X6S	0.22μF	±10%	GRM155C80G224KE01#	
				±20%	GRM155C80G224ME01#	
		X5R	1.0μF	±20%	GRM155R60G105ME01#	
0.6mm	50Vdc	X5R	0.47μF	±10%	GRM155R61H474KE11#	D1
	35Vdc	X5R	1.0μF	±10%	GRM155R6YA105KE11#	D1
	25Vdc	X6S	1.0μF	±10%	GRM155C81E105KE11#	D1
				±20%	GRM155C81E105ME11#	D1
	16Vdc	X6S	1.0μF	±10%	GRM155C81C105KE11#	
				±20%	GRM155C81C105ME11#	
	6.3Vdc	X5R	4.7μF	±20%	GRM155R60J475ME47#	D1
		B	4.7μF	±20%	GRM155B30J475ME47#	D1
	4Vdc	X5R	4.7μF	±20%	GRM155R60G475ME47#	
		B	4.7μF	±20%	GRM155B30G475ME47#	
	2.5Vdc	X6T	4.7μF	±20%	GRM155D80E475ME47#	D1
0.65mm	25Vdc	X6T	2.2μF	±20%	GRM155D81E225ME11#	D1

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.65mm	16Vdc	X7T	2.2μF	±20%	GRM155D71C225ME11#	D1
		X6T	2.2μF	±20%	GRM155D81C225ME11#	
	10Vdc	X7T	2.2μF	±20%	GRM155D71A225ME11#	
		X5R	4.7μF	±20%	GRM155R61A475MEAA#	D1
	6.3Vdc	X6S	4.7μF	±20%	GRM155C80J475MEAA#	D1
0.7mm	25Vdc	X5R	2.2μF	±10%	GRM155R61E225KE11#	
				±20%	GRM155R61E225ME11#	
	16Vdc	X6S	2.2μF	±10%	GRM155C81C225KE11#	
				±20%	GRM155C81C225ME11#	
		X5R	2.2μF	±10%	GRM155R61C225KE11#	
				±20%	GRM155R61C225ME11#	
	10Vdc	X7S	2.2μF	±10%	GRM155C71A225KE11#	
				±20%	GRM155C71A225ME11#	
		X6S	2.2μF	±10%	GRM155C81A225KE11#	
				±20%	GRM155C81A225ME11#	
	6.3Vdc	X7S	2.2μF	±10%	GRM155C70J225KE11#	
				±20%	GRM155C70J225ME11#	
	4Vdc	X5R	10μF	±20%	GRM155R60G106ME44#	
	2.5Vdc	X5R	10μF	±20%	GRM155R60E106ME16#	

1.6×0.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.5mm	25Vdc	X5R	1.0μF	±10%	GRM185R61E105KA12#	D1
				±20%	GRM185R61E105MA12#	D1
		B	1.0μF	±10%	GRM185B31E105KA12#	D1
				±20%	GRM185B31E105MA12#	D1
	16Vdc	X5R	1.0μF	±10%	GRM185R61C105KE44#	
				±20%	GRM185R61C105ME44#	
		B	1.0μF	±10%	GRM185B31C105KE43#	
				±20%	GRM185B31C105ME43#	
	6.3Vdc	X5R	10μF	±20%	GRM185R60J106ME15#	D1
	4Vdc	X5R	10μF	±20%	GRM185R60G106ME15#	
0.55mm	16Vdc	X5R	4.7μF	±10%	GRM185R61C475KE11#	
				±20%	GRM185R61C475ME11#	
	10Vdc	X6S	4.7μF	±10%	GRM185C81A475KE11#	D1
				±20%	GRM185C81A475ME11#	D1
		X5R	4.7μF	±10%	GRM185R61A475KE11#	
				±20%	GRM185R61A475ME11#	
	6.3Vdc	X7T	4.7μF	±20%	GRM185D70J475ME11#	D1
		X6S	4.7μF	±20%	GRM185C80J475ME11#	
0.9mm	250Vdc	X7R	220pF	±10%	GRM188R72E221KW07#	
			330pF	±10%	GRM188R72E331KW07#	
			470pF	±10%	GRM188R72E471KW07#	
			680pF	±10%	GRM188R72E681KW07#	
			1000pF	±10%	GRM188R72E102KW07#	
			1500pF	±10%	GRM188R72E152KW07#	
			2200pF	±10%	GRM188R72E222KW07#	
	200Vdc	X7R	220pF	±10%	GRM188R72D221KW07#	
			330pF	±10%	GRM188R72D331KW07#	
			470pF	±10%	GRM188R72D471KW07#	
			680pF	±10%	GRM188R72D681KW07#	
			1000pF	±10%	GRM188R72D102KW07#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	200Vdc	X7R	1500pF	±10%	GRM188R72D152KW07#	
			2200pF	±10%	GRM188R72D222KW07#	
	25Vdc	X7R	1.0μF	±10%	GRM188R71E105KA12#	
				±20%	GRM188R71E105MA12#	
		X5R	2.2μF	±10%	GRM188R61E225KA12#	
				±20%	GRM188R61E225MA12#	
		B	2.2μF	±10%	GRM188B31E225KA12#	
				±20%	GRM188B31E225MA12#	
	16Vdc	X6S	2.2μF	±10%	GRM188C81C225KA12#	
				±20%	GRM188C81C225MA12#	
		X5R	2.2μF	±10%	GRM188R61C225KE15#	
		B	2.2μF	±10%	GRM188B31C225KE14#	
	10Vdc	X7R	2.2μF	±10%	GRM188R71A225KE15#	
				±20%	GRM188R71A225ME15#	
		X5R	4.7μF	±10%	GRM188R61A475KE15#	D1
				±20%	GRM188R61A475ME15#	D1
	6.3Vdc	X6S	4.7μF	±20%	GRM188C80J475ME15#	D1
		X5R	10μF	±20%	GRM188R60J106ME47#	
		B	10μF	±20%	GRM188B30J106ME47#	
	4Vdc	X5R	10μF	±20%	GRM188R60G106ME47#	
0.95mm	25Vdc	X5R	4.7μF	±10%	GRM188R61E475KE11#	
				±20%	GRM188R61E475ME11#	
	16Vdc	X6S	4.7μF	±10%	GRM188C81C475KE11#	
				±20%	GRM188C81C475ME11#	
		X5R	4.7μF	±10%	GRM188R61C475KE11#	
				±20%	GRM188R61C475ME11#	
			10μF	±10%	GRM188R61C106KAAL#	
				±20%	GRM188R61C106MAAL#	
		B	4.7μF	±10%	GRM188B31C475KAAJ#	D1
				±20%	GRM188B31C475MAAJ#	D1
	10Vdc	X7S	4.7μF	±10%	GRM188C71A475KE11#	
				±20%	GRM188C71A475ME11#	
		X5R	10μF	±10%	GRM188R61A106KAAL#	
				±20%	GRM188R61A106MAAL#	
		B	10μF	±20%	GRM188B31A106ME69#	D1
1.0mm	50Vdc	X5R	2.2μF	±10%	GRM188R61H225KE11#	
				±20%	GRM188R61H225ME11#	
	35Vdc	X6S	2.2μF	±10%	GRM188C8YA225KE11#	
				±20%	GRM188C8YA225ME11#	
		X5R	4.7μF	±10%	GRM188R6YA475KE15#	
				±20%	GRM188R6YA475ME15#	
	25Vdc	X7S	2.2μF	±10%	GRM188C71E225KE11#	
				±20%	GRM188C71E225ME11#	
		X6S	2.2μF	±10%	GRM188C81E225KE11#	
				±20%	GRM188C81E225ME11#	
			4.7μF	±10%	GRM188C81E475KE11#	D1
				±20%	GRM188C81E475ME11#	D1
		X5R	10μF	±20%	GRM188R61E106MA73#	
	16Vdc	X7S	2.2μF	±10%	GRM188C71C225KE11#	
				±20%	GRM188C71C225ME11#	
			4.7μF	±10%	GRM188C71C475KE21#	
		X6S	10μF	±20%	GRM188C81C106MA73#	
	10Vdc	X7T	10μF	±20%	GRM188D71A106MA73#	
	6.3Vdc	X7T	10μF	±20%	GRM188D70J106MA73#	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.0mm	6.3Vdc	X5R	22μF	±20%	GRM188R60J226MEA0#	D1
		B	22μF	±20%	GRM188B30J226MEA0#	D1
	4Vdc	X6S	22μF	±20%	GRM188C80G226MEA0#	D1
		X5R	22μF	±20%	GRM188R60G226MEA0#	
		B	22μF	±20%	GRM188B30G226MEA0#	

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.7mm	16Vdc	X6S	1.0μF	±10%	GRM216C81C105KA12#	
0.95mm	50Vdc	X5R	1.0μF	±10%	GRM219R61H105KA73#	
				±20%	GRM219R61H105MA73#	
			2.2μF	±10%	GRM219R61H225KE15#	
				±20%	GRM219R61H225ME15#	
		B	1.0μF	±10%	GRM219B31H105KA73#	
				±20%	GRM219B31H105MA73#	
			2.2μF	±10%	GRM219B31H225KE15#	
				±20%	GRM219B31H225ME15#	
	35Vdc	X6S	2.2μF	±10%	GRM219C8YA225KE15#	
				±20%	GRM219C8YA225ME15#	
		X5R	4.7μF	±10%	GRM219R6YA475KA73#	D1
				±20%	GRM219R6YA475MA73#	D1
	25Vdc	X7R	1.0μF	±10%	GRM219R71E105KA88#	
		X6S	2.2μF	±10%	GRM219C81E225KE15#	
				±20%	GRM219C81E225ME15#	
		X5R	2.2μF	±10%	GRM219R61E225KA12#	
				±20%	GRM219R61E225MA12#	
			4.7μF	±10%	GRM219R61E475KA73#	
				±20%	GRM219R61E475MA73#	
			10μF	±10%	GRM219R61E106KA12#	D1
				±20%	GRM219R61E106MA12#	D1
		B	2.2μF	±10%	GRM219B31E225KA75#	
				±20%	GRM219B31E225MA75#	
			10μF	±10%	GRM219B31E106KA12#	D1
				±20%	GRM219B31E106MA12#	D1
	16Vdc	X7R	2.2μF	±10%	GRM219R71C225KE15#	
				±20%	GRM219R71C225ME15#	
		X5R	4.7μF	±10%	GRM219R61C475KE15#	
			10μF	±10%	GRM219R61C106KA73#	
				±20%	GRM219R61C106MA73#	
		B	4.7μF	±10%	GRM219B31C475KE15#	
			10μF	±10%	GRM219B31C106KA73#	
				±20%	GRM219B31C106MA73#	
	10Vdc	X7R	2.2μF	±10%	GRM219R71A225KE15#	
				±20%	GRM219R71A225ME15#	
		X7T	4.7μF	±10%	GRM219D71A475KE15#	D1
				±20%	GRM219D71A475ME15#	D1
		X5R	22μF	±20%	GRM219R61A226MEA0#	D1
		B	22μF	±20%	GRM219B31A226MEA0#	D1
	6.3Vdc	X6S	10μF	±10%	GRM219C80J106KE39#	
				±20%	GRM219C80J106ME39#	
		X5R	22μF	±20%	GRM219R60J226MEA0#	
		B	22μF	±20%	GRM219B30J226ME47#	D1

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.95mm	4Vdc	X6S	10μF	±10%	GRM219C80G106KE19#	
				±20%	GRM219C80G106ME19#	
		X5R	47μF	±20%	GRM219R60G476ME44#	D1
	2.5Vdc	X6T	47μF	±20%	GRM219D80E476ME44#	
1.0mm	500Vdc	X7R	1000pF	±10%	GRM21AR72H102KW10#	
			1500pF	±10%	GRM21AR72H152KW10#	
			2200pF	±10%	GRM21AR72H222KW10#	
			3300pF	±10%	GRM21AR72H332KW10#	
			4700pF	±10%	GRM21AR72H472KW10#	
			6800pF	±10%	GRM21AR72H682KW10#	
	250Vdc	X7R	1000pF	±10%	GRM21AR72E102KW01#	
			1500pF	±10%	GRM21AR72E152KW01#	
			2200pF	±10%	GRM21AR72E222KW01#	
			3300pF	±10%	GRM21AR72E332KW01#	
			4700pF	±10%	GRM21AR72E472KW01#	
			6800pF	±10%	GRM21AR72E682KW01#	
	200Vdc	X7R	1000pF	±10%	GRM21AR72D102KW01#	
			1500pF	±10%	GRM21AR72D152KW01#	
			2200pF	±10%	GRM21AR72D222KW01#	
			3300pF	±10%	GRM21AR72D332KW01#	
			4700pF	±10%	GRM21AR72D472KW01#	
			6800pF	±10%	GRM21AR72D682KW01#	
	35Vdc	X6S	4.7μF	±10%	GRM219C8YA475KE21#	D1
				±20%	GRM219C8YA475ME21#	D1
	25Vdc	X7S	4.7μF	±10%	GRM219C71E475KE21#	D1
				±20%	GRM219C71E475ME21#	D1
		X6S	4.7μF	±10%	GRM219C81E475KE21#	D1
				±20%	GRM219C81E475ME21#	D1
	16Vdc	X7S	4.7μF	±10%	GRM219C71C475KE21#	
				±20%	GRM219C71C475ME21#	
		X5R	22μF	±20%	GRM219R61C226ME15#	D1
1.35mm	25Vdc	X6S	4.7μF	±10%	GRM21BC81E475KA12#	
				±20%	GRM21BC81E475MA12#	
		X5R	4.7μF	±10%	GRM21BR61E475KA12#	
				±20%	GRM21BR61E475MA12#	
		B	2.2μF	±10%	GRM21BB31E225KA75#	
				±20%	GRM21BB31E225MA75#	
			4.7μF	±10%	GRM21BB31E475KA75#	
				±20%	GRM21BB31E475MA75#	
	16Vdc	X7R	2.2μF	±10%	GRM21BR71C225KA12#	
				±20%	GRM21BR71C225MA12#	
		X5R	10μF	±10%	GRM21BR61C106KE15#	
				±20%	GRM21BR61C106ME15#	
		B	10μF	±10%	GRM21BB31C106KE15#	
				±20%	GRM21BB31C106ME15#	
1.4mm	50Vdc	X5R	2.2μF	±10%	GRM21BR61H225KA73#	
				±20%	GRM21BR61H225MA73#	
			4.7μF	±10%	GRM21BR61H475KE51#	
				±20%	GRM21BR61H475ME51#	
		B	2.2μF	±10%	GRM21BB31H225KA73#	
				±20%	GRM21BB31H225MA73#	
			4.7μF	±10%	GRM21BB31H475KE51#	
				±20%	GRM21BB31H475ME51#	
	25Vdc	X7R	2.2μF	±10%	GRM21BR71E225KE11#	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 2.0×1.25mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.4mm	25Vdc	X7R	2.2μF	±20%	GRM21BR71E225ME11#	
		X5R	10μF	±10%	GRM21BR61E106KA73#	
				±20%	GRM21BR61E106MA73#	
		B	10μF	±10%	GRM21BB31E106KA73#	
				±20%	GRM21BB31E106MA73#	
	16Vdc	X6S	10μF	±10%	GRM21BC81C106KA73#	
				±20%	GRM21BC81C106MA73#	
	10Vdc	B	22μF	±20%	GRM21BB31A226ME51#	D1
	6.3Vdc	X7R	10μF	±10%	GRM21BR70J106KE76#	
		X6S	22μF	±20%	GRM21BC80J226ME51#	D1
	4Vdc	X7U	22μF	±20%	GRM21BE70G226ME51#	
		X6S	22μF	±20%	GRM21BC80G226ME39#	
1.45mm	500Vdc	X7R	10000pF	±10%	GRM21BR72H103KW09#	
	250Vdc	X7R	10000pF	±10%	GRM21BR72E103KW03#	
			15000pF	±10%	GRM21BR72E153KW03#	
			22000pF	±10%	GRM21BR72E223KW03#	
	200Vdc	X7R	10000pF	±10%	GRM21BR72D103KW03#	
			15000pF	±10%	GRM21BR72D153KW03#	
			22000pF	±10%	GRM21BR72D223KW03#	
	50Vdc	X7S	4.7μF	±10%	GRM21BC71H475KE11#	
				±20%	GRM21BC71H475ME11#	
		X6S	4.7μF	±10%	GRM21BC81H475KE11#	
				±20%	GRM21BC81H475ME11#	
	35Vdc	X7S	4.7μF	±10%	GRM21BC7YA475KE11#	
				±20%	GRM21BC7YA475ME11#	
		X6S	10μF	±10%	GRM21BC8YA106KE11#	D1
				±20%	GRM21BC8YA106ME11#	D1
		X5R	10μF	±10%	GRM21BR6YA106KE43#	D1
				±20%	GRM21BR6YA106ME43#	D1
	25Vdc	X7S	4.7μF	±10%	GRM21BC71E475KE11#	
				±20%	GRM21BC71E475ME11#	
			10μF	±10%	GRM21BC71E106KE11#	D1
				±20%	GRM21BC71E106ME11#	D1
		X6S	10μF	±10%	GRM21BC81E106KE11#	D1
				±20%	GRM21BC81E106ME11#	D1
		X5R	22μF	±20%	GRM21BR61E226ME44#	
	16Vdc	X7S	10μF	±10%	GRM21BC71C106KE11#	
				±20%	GRM21BC71C106ME11#	
		X6S	22μF	±20%	GRM21BC81C226ME44#	D1
		X5R	22μF	±20%	GRM21BR61C226ME44#	
	10Vdc	X7T	22μF	±20%	GRM21BD71A226ME44#	D1
		X6S	22μF	±20%	GRM21BC81A226ME44#	
		X5R	22μF	±20%	GRM21BR61A226ME44#	
			47μF	±20%	GRM21BR61A476ME15#	D1
	6.3Vdc	X7T	22μF	±20%	GRM21BD70J226ME44#	
		X5R	47μF	±20%	GRM21BR60J476ME15#	D1
			100μF	±20%	GRM21BR60J107ME15#	D1
		B	47μF	±20%	GRM21BB30J476ME15#	D1
	4Vdc	X6S	47μF	±20%	GRM21BC80G476ME15#	D1
			100μF	±20%	GRM21BC80G107ME15#	D1
		X5R	47μF	±20%	GRM21BR60G476ME15#	
		B	47μF	±20%	GRM21BB30G476ME15#	
	2.5Vdc	X6S	100μF	±20%	GRM21BC80E107ME15#	

3.2×1.6mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.95mm	35Vdc	X5R	10μF	±10%	GRM319R6YA106KA12#	D1
				±20%	GRM319R6YA106MA12#	D1
	16Vdc	X5R	10μF	±10%	GRM319R61C106KE15#	
				±20%	GRM319R61C106ME15#	
			22μF	±20%	GRM319R61C226ME15#	D1
		B	10μF	±10%	GRM319B31C106KE15#	
				±20%	GRM319B31C106ME15#	
			22μF	±20%	GRM319B31C226ME15#	D1
	10Vdc	X5R	22μF	±20%	GRM319R61A226ME15#	
		B	22μF	±20%	GRM319B31A226ME15#	
	6.3Vdc	X6S	22μF	±20%	GRM319C80J226ME15#	
		X5R	22μF	±20%	GRM319R60J226ME15#	
		B	22μF	±20%	GRM319B30J226ME15#	
1.0mm	630Vdc	X7R	1000pF	±10%	GRM31AR72J102KW01#	
			1500pF	±10%	GRM31AR72J152KW01#	
			2200pF	±10%	GRM31AR72J222KW01#	
			3300pF	±10%	GRM31AR72J332KW01#	
			4700pF	±10%	GRM31AR72J472KW01#	
			6800pF	±10%	GRM31AR72J682KW01#	
			10000pF	±10%	GRM31AR72J103KW01#	
1.25mm	1000Vdc	X7R	470pF	±10%	GRM31BR73A471KW01#	
			680pF	±10%	GRM31BR73A681KW01#	
			1000pF	±10%	GRM31BR73A102KW01#	
			1500pF	±10%	GRM31BR73A152KW01#	
			2200pF	±10%	GRM31BR73A222KW01#	
			3300pF	±10%	GRM31BR73A332KW01#	
			4700pF	±10%	GRM31BR73A472KW01#	
	630Vdc	X7R	6800pF	±10%	GRM31BR72J682KW01#	
	500Vdc	X7R	15000pF	±10%	GRM31BR72H153KW10#	
			22000pF	±10%	GRM31BR72H223KW10#	
	250Vdc	X7R	15000pF	±10%	GRM31BR72E153KW01#	
			22000pF	±10%	GRM31BR72E223KW01#	
			68000pF	±10%	GRM31BR72E683KW01#	
	200Vdc	X7R	15000pF	±10%	GRM31BR72D153KW01#	
			22000pF	±10%	GRM31BR72D223KW01#	
			68000pF	±10%	GRM31BR72D683KW01#	
	50Vdc	B	1.0μF	±10%	GRM31MB31H105KA87#	
	25Vdc	X5R	10μF	±20%	GRM31MR61E106MA12#	
1.8mm	1000Vdc	X7R	6800pF	±10%	GRM31CR73A682KW03#	
			10000pF	±10%	GRM31CR73A103KW03#	
	630Vdc	X7R	15000pF	±10%	GRM31CR72J153KW03#	
			22000pF	±10%	GRM31CR72J223KW03#	
	500Vdc	X7R	33000pF	±10%	GRM31CR72H333KW09#	
			47000pF	±10%	GRM31CR72H473KW09#	
	250Vdc	X7R	33000pF	±10%	GRM31CR72E333KW03#	
			47000pF	±10%	GRM31CR72E473KW03#	
			0.10μF	±10%	GRM31CR72E104KW03#	
	200Vdc	X7R	33000pF	±10%	GRM31CR72D333KW03#	
			47000pF	±10%	GRM31CR72D473KW03#	
			0.10μF	±10%	GRM31CR72D104KW03#	
	100Vdc	X7R	1.0μF	±10%	GRM31CR72A105KA01#	
	50Vdc	X7R	4.7μF	±10%	GRM31CR71H475KA12#	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

(→ 3.2×1.6mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.8mm	50Vdc	X7R	4.7μF	±20%	GRM31CR71H475MA12#	
		X5R	10μF	±10%	GRM31CR61H106KA12#	
				±20%	GRM31CR61H106MA12#	
		B	4.7μF	±10%	GRM31CB31H475KA12#	
				±20%	GRM31CB31H475MA12#	
			10μF	±10%	GRM31CB31H106KA12#	
				±20%	GRM31CB31H106MA12#	
	25Vdc	X7R	10μF	±10%	GRM31CR71E106KA12#	
				±20%	GRM31CR71E106MA12#	
		X5R	22μF	±20%	GRM31CR61E226ME15#	
		B	10μF	±10%	GRM31CB31E106KA75#	
			22μF	±20%	GRM31CB31E226ME15#	
	16Vdc	X6S	22μF	±20%	GRM31CC81C226ME15#	
		X5R	22μF	±20%	GRM31CR61C226ME15#	
		B	22μF	±20%	GRM31CB31C226ME15#	
	10Vdc	X7R	22μF	±20%	GRM31CR71A226ME15#	
		X5R	47μF	±20%	GRM31CR61A476ME15#	
		B	47μF	±20%	GRM31CB31A476ME15#	
	6.3Vdc	X7R	22μF	±20%	GRM31CR70J226ME19#	
		X7U	47μF	±20%	GRM31CE70J476ME15#	D1
		X6S	47μF	±20%	GRM31CC80J476ME18#	
		X5R	47μF	±20%	GRM31CR60J476ME19#	
		B	47μF	±20%	GRM31CB30J476ME18#	
	4Vdc	X7U	47μF	±20%	GRM31CE70G476ME15#	
		X6S	47μF	±20%	GRM31CC80G476ME19#	
1.9mm	25Vdc	X6S	22μF	±20%	GRM31CC81E226ME11#	
	16Vdc	X7S	22μF	±20%	GRM31CC71C226ME11#	
		X5R	47μF	±20%	GRM31CR61C476ME44#	
	10Vdc	X6S	47μF	±20%	GRM31CC81A476ME44#	
		X5R	100μF	±20%	GRM31CR61A107ME05#	D1
	6.3Vdc	X6T	100μF	±20%	GRM31CD80J107ME39#	D1
		X5R	100μF	±20%	GRM31CR60J107ME39#	
			150μF	±20%	GRM31CR60J157ME11#	D1
	4Vdc	X7U	100μF	±20%	GRM31CE70G107ME39#	D1
		X6S	150μF	±20%	GRM31CC80G157ME11#	D1
		X6T	100μF	±20%	GRM31CD80G107ME39#	
		X5R	100μF	±20%	GRM31CR60G107ME39#	
			150μF	±20%	GRM31CR60G157ME11#	
			220μF	±20%	GRM31CR60G227ME11#	
	2.5Vdc	X6S	150μF	±20%	GRM31CC80E157ME11#	
		X5R	220μF	±20%	GRM31CR60E227ME11#	

3.2×2.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.5mm	1000Vdc	X7R	6800pF	±10%	GRM32QR73A682KW01#	
			10000pF	±10%	GRM32QR73A103KW01#	
	630Vdc	X7R	22000pF	±10%	GRM32QR72J223KW01#	
	500Vdc	X7R	68000pF	±10%	GRM32QR72H683KW10#	
	250Vdc	X7R	68000pF	±10%	GRM32QR72E683KW01#	
			0.15μF	±10%	GRM32QR72E154KW01#	
	200Vdc	X7R	68000pF	±10%	GRM32QR72D683KW01#	
			0.15μF	±10%	GRM32QR72D154KW01#	

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.8mm	100Vdc	X7R	1.0μF	±10%	GRM32CR72A105KA35#	
				±20%	GRM32CR72A105MA35#	
2.0mm	1000Vdc	X7R	15000pF	±10%	GRM32DR73A153KW01#	
			22000pF	±10%	GRM32DR73A223KW01#	
	630Vdc	X7R	33000pF	±10%	GRM32DR72J333KW01#	
			47000pF	±10%	GRM32DR72J473KW01#	
	500Vdc	X7R	0.10μF	±10%	GRM32DR72H104KW10#	
	250Vdc	X7R	0.10μF	±10%	GRM32DR72E104KW01#	
			0.22μF	±10%	GRM32DR72E224KW01#	
	200Vdc	X7R	0.10μF	±10%	GRM32DR72D104KW01#	
			0.22μF	±10%	GRM32DR72D224KW01#	
2.2mm	100Vdc	X7S	4.7μF	±10%	GRM32DC72A475KE01#	
				±20%	GRM32DC72A475ME01#	
	25Vdc	X7R	10μF	±10%	GRM32DR71E106KA12#	
2.7mm	100Vdc	X7R	2.2μF	±10%	GRM32ER72A225KA35#	
				±20%	GRM32ER72A225MA35#	
	80Vdc	X7R	4.7μF	±10%	GRM32ER71K475KE14#	D1
				±20%	GRM32ER71K475ME14#	D1
	63Vdc	X7R	10μF	±10%	GRM32ER71J106KA12#	D1
				±20%	GRM32ER71J106MA12#	D1
	50Vdc	X7R	4.7μF	±10%	GRM32ER71H475KA88#	
			10μF	±10%	GRM32ER71H106KA12#	
				±20%	GRM32ER71H106MA12#	
		X5R	10μF	±10%	GRM32ER61H106KA12#	
				±20%	GRM32ER61H106MA12#	
		B	10μF	±10%	GRM32EB31H106KA12#	
				±20%	GRM32EB31H106MA12#	
	35Vdc	X7R	10μF	±10%	GRM32ER7YA106KA12#	
				±20%	GRM32ER7YA106MA12#	
		X5R	10μF	±10%	GRM32ER6YA106KA12#	
				±20%	GRM32ER6YA106MA12#	
		B	10μF	±10%	GRM32EB3YA106KA12#	
				±20%	GRM32EB3YA106MA12#	
	25Vdc	X7R	22μF	±20%	GRM32ER71E226ME15#	
		X5R	22μF	±20%	GRM32ER61E226ME15#	
		B	22μF	±20%	GRM32EB31E226ME15#	
	16Vdc	X7R	22μF	±20%	GRM32ER71C226MEA8#	
		X6S	47μF	±20%	GRM32EC81C476ME15#	D1
		X5R	47μF	±20%	GRM32ER61C476ME15#	
		B	47μF	±20%	GRM32EB31C476ME15#	
	10Vdc	X7R	47μF	±20%	GRM32ER71A476ME15#	
		X5R	47μF	±20%	GRM32ER61A476ME20#	
			100μF	±20%	GRM32ER61A107ME20#	D1
		B	47μF	±20%	GRM32EB31A476ME20#	
	6.3Vdc	X7R	47μF	±20%	GRM32ER70J476ME20#	
		X7U	100μF	±20%	GRM32EE70J107ME15#	D1
		X5R	100μF	±20%	GRM32ER60J107ME20#	
		B	100μF	±20%	GRM32EB30J107ME16#	
	4Vdc	X7U	100μF	±20%	GRM32EE70G107ME19#	

Part number # indicates the package specification code.

GRM Series High Dielectric Constant Type Part Number List

4.5×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.5mm	630Vdc	X7R	68000pF	±10%	**GRM43QR72J683KW01#**	
	500Vdc	X7R	0.15μF	±10%	**GRM43QR72H154KW10#**	
	250Vdc	X7R	0.15μF	±10%	**GRM43QR72E154KW01#**	
	200Vdc	X7R	0.15μF	±10%	**GRM43QR72D154KW01#**	
2.0mm	1000Vdc	X7R	33000pF	±10%	**GRM43DR73A333KW01#**	
			47000pF	±10%	**GRM43DR73A473KW01#**	
	630Vdc	X7R	0.10μF	±10%	**GRM43DR72J104KW01#**	
	500Vdc	X7R	0.22μF	±10%	**GRM43DR72H224KW10#**	
	250Vdc	X7R	0.22μF	±10%	**GRM43DR72E224KW01#**	
			0.33μF	±10%	**GRM43DR72E334KW01#**	
			0.47μF	±10%	**GRM43DR72E474KW01#**	
	200Vdc	X7R	0.22μF	±10%	**GRM43DR72D224KW01#**	
			0.33μF	±10%	**GRM43DR72D334KW01#**	
			0.47μF	±10%	**GRM43DR72D474KW01#**	

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
2.0mm	1000Vdc	X7R	68000pF	±10%	**GRM55DR73A683KW01#**	
			0.10μF	±10%	**GRM55DR73A104KW01#**	
	630Vdc	X7R	0.15μF	±10%	**GRM55DR72J154KW01#**	
			0.22μF	±10%	**GRM55DR72J224KW01#**	
	500Vdc	X7R	0.33μF	±10%	**GRM55DR72H334KW10#**	
			0.47μF	±10%	**GRM55DR72H474KW10#**	
	250Vdc	X7R	0.33μF	±10%	**GRM55DR72E334KW01#**	
			0.47μF	±10%	**GRM55DR72E474KW01#**	
			0.68μF	±10%	**GRM55DR72E684KW01#**	
			1.0μF	±10%	**GRM55DR72E105KW01#**	
	200Vdc	X7R	0.33μF	±10%	**GRM55DR72D334KW01#**	
			0.47μF	±10%	**GRM55DR72D474KW01#**	
			0.68μF	±10%	**GRM55DR72D684KW01#**	
			1.0μF	±10%	**GRM55DR72D105KW01#**	

Part number # indicates the package specification code.

GRM Series Specifications and Test Methods

Specifications and Test Methods, please refer to the search web page.
https://www.murata.com/en-global/products/capacitor



GRM Series Temperature Compensating

0.4×0.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number
0.22mm	50Vdc	C0G	0.20pF	±0.05pF	GRM0225C1HR20WA03#
				±0.1pF	GRM02[illegible]C1HR20BA03#
			0.30pF	±0.05pF	GRM[illegible]30WA03#
				±0.1pF	GRM0[illegible]30BA03#
			0.40pF	±0.05pF	GRM0225C1HR40WA03#
				±0.1pF	GRM0225C1HR40BA03#
			0.50pF	±0.05pF	GRM0225C1HR50WA03#
				±0.1pF	GRM0225C1HR50BA03#

Links are provided to the product detail pages on the web, and are shown below in the product number table from the PDF version of the catalog which is available on the web.

GRM0222C1C121JA02#

Shape

Specifications

References

Chart of characteristic data

Detailed Specifications Sheet

- Rated value
- Specifications and Test Methods
- Package
- Caution, Notice

muRata

■ Specifications and Test Methods

No	Item	Specification	Test Method (Ref. Standard:JIS C 5101, IEC60384)
1	Rated Voltage	Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance	No defects or abnormalities.	Visual inspection.
3	Dimension	Within the specified dimensions.	Using calipers. (GRM02 size is based on Microscope)
4	Voltage proof	No defects or abnormalities.	Measurement Point : Between the terminations Test Voltage : 300% of the rated voltage (Temperature compensating type) Applied Time : 1s to 5 s Charge/discharge current : 50mA max.
5	Insulation Resistance(I.R.)	C≦0.047μF:More than 10000MΩ C＞0.047μF:More than 500Ω·F C:Nominal Capacitance	Measurement Point : Between the terminations Measurement Voltage : DC Rated Voltage Charging Time : 1 min Charge/discharge current : 50mA max. Measurement Temperature : Room Temperature
6	Capacitance	Shown in Rated value.	Measurement Temperature : Room Temperature (1)Temperature Compensating Type Capacitance / Frequency / Voltage C≦1000pF / 1.0+/-0.1MHz / 0.5 to 5.0Vrms C＞1000pF / 1.0+/-0.1kHz / 1.0+/-0.2Vrms
7	Q or Dissipation Factor (D.F.)	30pF and over:Q≧1000 30pF and below:Q≧400+20C C:Nominal Capacitance(pF)	
8	Temperature Characteristics of Capacitance	Nominal values of the temperature coefficient is shown in Rated value. But,the Capacitance Change under 20℃ is shown in Table A. Capacitance Drift Within +/-0.2% or +/-0.05pF (Whichever is larger.)	The capacitance change should be measured after 5 min at each specified temp. stage. In case of applying voltage, the capacitance change should be measured after 1 min with applying voltage in equilibration of each temp. stage. Capacitance value as a reference is the value in step 3. The capacitance drift is calculated by dividing the differences between the maximum and minimum measured values in the step 1,3 and 5 by the cap. value in step 3. Step / Temperature(℃) 1 / Reference Temp.+/-2 2 / Min. Operating Temp.+/-3 3 / Reference Temp.+/-2 4 / Max. Operating Temp.+/-3 5 / Reference Temp.+/-2

High Effective Capacitance & High Ripple Current Chip Multilayer Ceramic Capacitors for General Purpose

GR3 Series

Anti-noise

WEB

This is a general purpose high ripple resistance product excellent in DC bias characteristics.

Features

① When a DC bias is applied, a capacitance higher than conventional products (X7R characteristics) can be acquired.

About twice the capacitance can be secured when DC200V is applied.



<Comparison between Capacitance - DC Bias Characteristics>

② Improved ripple resistance performance compared to conventional products (X7R characteristics).

In the case of a product with a capacitance of 1μF, when the exothermic temperature reaches 20ºC at frequency f=300kHz, the amount of resistance of a product with conventional material is 2.9Arms; however, the new material is 4.7Arms.



<Comparison of Ripple Heat Generation Characteristics>

③ This product has a noise reduction effect.

Since dielectric materials which enable a reduction of noise are used, this product is more effective for reducing noise compared to the general purpose GRM series.



Specifications

Size (mm)	2.0×1.25mm to 5.7×5.0mm
Rated Voltage	250Vdc to 630Vdc
Capacitance	10000pF to 1.0μF
Main Applications	For PFC (Power Factor Correction) Circuits of Power Supplies, EMI Suppression and Smoothing Circuits



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

GR3 Series High Dielectric Constant Type Anti-noise Part Number List

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	250Vdc	X7T	10000pF	±10%	**GR321AD72E103KW01#**	p111
			15000pF	±10%	**GR321AD72E153KW01#**	p111
1.45mm	250Vdc	X7T	22000pF	±10%	**GR321BD72E223KW03#**	p111

3.2×1.6mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	450Vdc	X7T	10000pF	±10%	**GR331AD72W103KW01#**	p114
			15000pF	±10%	**GR331AD72W153KW01#**	p114
	250Vdc	X7T	33000pF	±10%	**GR331AD72E333KW01#**	p111
1.25mm	630Vdc	X7T	10000pF	±10%	**GR331BD72J103KW01#**	p117
	450Vdc	X7T	22000pF	±10%	**GR331BD72W223KW01#**	p114
			33000pF	±10%	**GR331BD72W333KW01#**	p114
	250Vdc	X7T	47000pF	±10%	**GR331BD72E473KW01#**	p111
1.8mm	630Vdc	X7T	15000pF	±10%	**GR331CD72J153KW03#**	p117
	450Vdc	X7T	47000pF	±10%	**GR331CD72W473KW03#**	p114
	250Vdc	X7T	68000pF	±10%	**GR331CD72E683KW03#**	p111

3.2×2.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	630Vdc	X7T	22000pF	±10%	**GR332QD72J223KW01#**	p117
	250Vdc	X7T	0.10μF	±10%	**GR332QD72E104KW01#**	p111
2.0mm	630Vdc	X7T	33000pF	±10%	**GR332DD72J333KW01#**	p117
			47000pF	±10%	**GR332DD72J473KW01#**	p117
	450Vdc	X7T	68000pF	±10%	**GR332DD72W683KW01#**	p114
			0.10μF	±10%	**GR332DD72W104KW01#**	p114
	250Vdc	X7T	0.15μF	±10%	**GR332DD72E154KW01#**	p111

4.5×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vdc	X7T	0.22μF	±10%	**GR343QD72E224KW01#**	p111
2.0mm	630Vdc	X7T	68000pF	±10%	**GR343DD72J683KW01#**	p117
	450Vdc	X7T	0.15μF	±10%	**GR343DD72W154KW01#**	p114
	250Vdc	X7T	0.33μF	±10%	**GR343DD72E334KW01#**	p111

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
2.0mm	630Vdc	X7T	0.10μF	±10%	**GR355DD72J104KW01#**	p117
			0.15μF	±10%	**GR355DD72J154KW01#**	p117
	450Vdc	X7T	0.22μF	±10%	**GR355DD72W224KW01#**	p114
			0.33μF	±10%	**GR355DD72W334KW01#**	p114
			0.47μF	±10%	**GR355DD72W474KW01#**	p114
	250Vdc	X7T	0.47μF	±10%	**GR355DD72E474KW01#**	p111
			0.68μF	±10%	**GR355DD72E684KW01#**	p111
2.7mm	630Vdc	X7T	0.22μF	±10%	**GR355XD72J224KW05#**	p117
2.7mm	250Vdc	X7T	1.0μF	±10%	**GR355XD72E105KW05#**	p111

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GR3 Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: DC500V (200% of the rated voltage) Applied Time: 1 to 5s Charge/discharge current: 50mA max.
4	Insulation Resistance (I.R.)		More than 10000MΩ or 100MΩ ▪ μF (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC250±25V Charging Time: 60±5s Measurement Temperature: Room Temperature
5	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
6	Dissipation Factor (D.F.)		0.01 max.	
7	Temperature Characteristics of Capacitance		D7: Within +22/-33% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
8	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
9	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
10	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GR331 size max.: 120 to 150°C for 1min GR332 size min.: 100 to 120°C for 1min and 170 to 200°C for 1min ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±10%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
11	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
12	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 2mm (GR321 size: 1mm) Holding Time: 5±1s Soldering Method: Reflow soldering

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR3 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h. at room condition *.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
14	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: DC250V(DC Rated Voltage) Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000MΩ or 10MΩ • μF (Whichever is smaller)	
		Voltage Proof	No defects.	
15	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000+48/-0h Applied Voltage: DC375V (150% of the rated voltage) Charge/discharge current: 50mA max. Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000MΩ or 10MΩ • μF (Whichever is smaller)	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR3 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GR321	1.2	4.0	1.65
GR331	2.2	5.0	2.0
GR332	2.2	5.0	2.9
GR342	3.5	7.0	2.4
GR343	3.5	7.0	3.7
GR352	4.5	8.0	3.2
GR355	4.5	8.0	5.6

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension (mm)			
	a	b	c	d
GR321	1.2	4.0	1.65	1.0
GR331	2.2	5.0	2.0	1.0
GR332	2.2	5.0	2.9	1.0
GR342	3.5	7.0	2.4	1.0
GR343	3.5	7.0	3.7	1.0
GR352	4.5	8.0	3.2	1.0
GR355	4.5	8.0	5.6	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



2 GR3 Series Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: DC675V (150% of the rated voltage) Applied Time: 1 to 5s Charge/discharge current: 50mA max.
4	Insulation Resistance (I.R.)		More than 10000MΩ or 100MΩ ▪ μF (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC250±25V Charging Time: 60±5s Measurement Temperature: Room Temperature
5	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
6	Dissipation Factor (D.F.)		0.01 max.	
7	Temperature Characteristics of Capacitance		D7: Within +22/-33% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
8	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
9	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
10	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GR331 size max.: 120 to 150°C for 1min GR332 size min.: 100 to 120°C for 1min and 170 to 200°C for 1min ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±10%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
11	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
12	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 2mm Holding Time: 5±1s Soldering Method: Reflow soldering

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR3 Series Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h. at room condition *.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
14	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: DC450V (DC Rated Voltage) Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000MΩ or 10MΩ • μF (Whichever is smaller)	
		Voltage Proof	No defects.	
15	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000+48/-0h Applied Voltage: DC585V (130% of the rated voltage) Charge/discharge current: 50mA max. Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000MΩ or 10MΩ • μF (Whichever is smaller)	
		Voltage Proof	No defects.	

Step	Temp. (°C)	Time (min)
1	Min. Operating Temp. +0/-3	30±3
2	Room Temp.	2 to 3
3	Max. Operating Temp. +3/-0	30±3
4	Room Temp.	2 to 3

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR3 Series Specifications and Test Methods (2)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GR318	1.0	3.0	1.2
GR321	1.2	4.0	1.65
GR331	2.2	5.0	2.0
GR332	2.2	5.0	2.9
GR342	3.5	7.0	2.4
GR343	3.5	7.0	3.7
GR352	4.5	8.0	3.2
GR355	4.5	8.0	5.6

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension (mm)			
	a	b	c	d
GR318	1.0	3.0	1.2	1.0
GR321	1.2	4.0	1.65	1.0
GR331	2.2	5.0	2.0	1.0
GR332	2.2	5.0	2.9	1.0
GR342	3.5	7.0	2.4	1.0
GR343	3.5	7.0	3.7	1.0
GR352	4.5	8.0	3.2	1.0
GR355	4.5	8.0	5.6	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



3 GR3 Series Specifications and Test Methods (3)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: DC756V (120% of the rated voltage) Applied Time: 1 to 5s Charge/discharge current: 50mA max.
4	Insulation Resistance (I.R.)		More than 10000MΩ or 100MΩ ▪ μF (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Measurement Temperature: Room Temperature
5	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
6	Dissipation Factor (D.F.)		0.01 max.	
7	Temperature Characteristics of Capacitance		D7: Within +22/-33% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
8	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h. in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
9	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
10	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GR331 size max.: 120 to 150°C for 1min GR332 size min.: 100 to 120°C for 1min and 170 to 200°C for 1min ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±10%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
11	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR3 Series Specifications and Test Methods (3)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 2mm Holding Time: 5±1s Soldering Method: Reflow soldering
13	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h. at room condition *.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
14	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: DC630V (DC Rated Voltage) Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000MΩ or 10MΩ • μF (Whichever is smaller)	
		Voltage Proof	No defects.	
15	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000+48/-0h Applied Voltage: DC756V (120% of the rated voltage) Charge/discharge current: 50mA max. Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000MΩ or 10MΩ • μF (Whichever is smaller)	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR3 Series Specifications and Test Methods (3)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GR318	1.0	3.0	1.2
GR321	1.2	4.0	1.65
GR331	2.2	5.0	2.0
GR332	2.2	5.0	2.9
GR342	3.5	7.0	2.4
GR343	3.5	7.0	3.7
GR352	4.5	8.0	3.2
GR355	4.5	8.0	5.6

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension (mm)			
	a	b	c	d
GR318	1.0	3.0	1.2	1.0
GR321	1.2	4.0	1.65	1.0
GR331	2.2	5.0	2.0	1.0
GR332	2.2	5.0	2.9	1.0
GR342	3.5	7.0	2.4	1.0
GR343	3.5	7.0	3.7	1.0
GR352	4.5	8.0	3.2	1.0
GR355	4.5	8.0	5.6	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose

GRJ Series

Deflecting crack

WEB

Cracking caused by flexing stress after board mounting is minimized due to resin external electrodes!

Features

1 The resin external electrodes suppress cracks by board deflection.

Cracking of the ceramic element is suppressed by the resin of the external electrodes, which releases the stress.



Resin electrodes relieve the stress

<Example of Structure>

General Purpose Product (GRM Series)



Occurrence of cracking on edge of terminal electrode

Resin External Electrode Type (GRJ Series)



Conductive resin layer relieves the mechanical stress of the ceramic

Separated foundation electrode and resin electrode

Note: Cracks may occur in the capacitor body if excessive stress beyond the "guaranteed range of board bending strength (*) " provided in the specifications is applied. Capacitors with cracks in them may cause a drop in insulation resistance, which could lead to a short circuit.
(*) For details on the guaranteed range of board bending strength, check the "Detailed Specification Sheet" on the Product Details Page.

2 Suppresses the occurrence of cracking caused by deflection stress at the time of board mounting, etc.





Due to the specification of the measuring instrument, measurements can be performed up to 8mm.

3 Ideal for consumer and industrial electronic equipment, etc. where there heat stress, vibration and impact are applied.

Specifications

Size (mm)	0.6×0.3mm to 5.7×5.0mm
Rated Voltage	6.3Vdc to 1000Vdc
Capacitance	220pF to 47μF
Main Applications	Consumer & Industrial Electronic Equipment



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

GRJ Series High Dielectric Constant Type Deflecting crack Part Number List

1.6×0.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.9mm	100Vdc	X7R	1000pF	±10%	GRJ188R72A102KE11#	
				±20%	GRJ188R72A102ME11#	
			2200pF	±10%	GRJ188R72A222KE11#	
				±20%	GRJ188R72A222ME11#	
			4700pF	±10%	GRJ188R72A472KE11#	
				±20%	GRJ188R72A472ME11#	
			10000pF	±10%	GRJ188R72A103KE11#	
				±20%	GRJ188R72A103ME11#	
			22000pF	±10%	GRJ188R72A223KE11#	
				±20%	GRJ188R72A223ME11#	
			0.10μF	±10%	GRJ188R72A104KE11#	
				±20%	GRJ188R72A104ME11#	
	50Vdc	X7R	1000pF	±10%	GRJ188R71H102KE11#	
				±20%	GRJ188R71H102ME11#	
			2200pF	±10%	GRJ188R71H222KE11#	
				±20%	GRJ188R71H222ME11#	
			4700pF	±10%	GRJ188R71H472KE11#	
				±20%	GRJ188R71H472ME11#	
			10000pF	±10%	GRJ188R71H103KE11#	
				±20%	GRJ188R71H103ME11#	
			22000pF	±10%	GRJ188R71H223KE11#	
				±20%	GRJ188R71H223ME11#	
			47000pF	±10%	GRJ188R71H473KE11#	
				±20%	GRJ188R71H473ME11#	
			0.10μF	±10%	GRJ188R71H104KE11#	
				±20%	GRJ188R71H104ME11#	
			0.22μF	±10%	GRJ188R71H224KE11#	
				±20%	GRJ188R71H224ME11#	
	35Vdc	X5R	1.0μF	±10%	GRJ188R6YA105KE11#	
	25Vdc	X7R	47000pF	±10%	GRJ188R71E473KE11#	
				±20%	GRJ188R71E473ME11#	
			0.22μF	±10%	GRJ188R71E224KE11#	
				±20%	GRJ188R71E224ME11#	
			1.0μF	±10%	GRJ188R71E105KE11#	
				±20%	GRJ188R71E105ME11#	
	16Vdc	X7R	0.47μF	±10%	GRJ188R71C474KE11#	
				±20%	GRJ188R71C474ME11#	
	6.3Vdc	X7R	2.2μF	±10%	GRJ188R70J225KE11#	
				±20%	GRJ188R70J225ME11#	
1.0mm	6.3Vdc	X7S	4.7μF	±10%	GRJ188C70J475KE11#	
				±20%	GRJ188C70J475ME11#	

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.7mm	100Vdc	X7R	1000pF	±10%	GRJ216R72A102KE01#	
				±20%	GRJ216R72A102ME01#	
			2200pF	±10%	GRJ216R72A222KE01#	
				±20%	GRJ216R72A222ME01#	
			4700pF	±10%	GRJ216R72A472KE01#	
				±20%	GRJ216R72A472ME01#	
0.7mm	100Vdc	X7R	10000pF	±10%	GRJ216R72A103KE01#	
				±20%	GRJ216R72A103ME01#	
			22000pF	±10%	GRJ216R72A223KE01#	
				±20%	GRJ216R72A223ME01#	
	50Vdc	X7R	470pF	±10%	GRJ216R71H471KE01#	
				±20%	GRJ216R71H471ME01#	
			1000pF	±10%	GRJ216R71H102KE01#	
				±20%	GRJ216R71H102ME01#	
			2200pF	±10%	GRJ216R71H222KE01#	
				±20%	GRJ216R71H222ME01#	
			4700pF	±10%	GRJ216R71H472KE01#	
				±20%	GRJ216R71H472ME01#	
			10000pF	±10%	GRJ216R71H103KE01#	
				±20%	GRJ216R71H103ME01#	
			22000pF	±10%	GRJ216R71H223KE01#	
				±20%	GRJ216R71H223ME01#	
0.95mm	100Vdc	X7R	220pF	±10%	GRJ219R72A221KE01#	
				±20%	GRJ219R72A221ME01#	
			470pF	±10%	GRJ219R72A471KE01#	
				±20%	GRJ219R72A471ME01#	
1.0mm	250Vdc	X7R	1000pF	±10%	GRJ21AR72E102KWJ1#	
			1500pF	±10%	GRJ21AR72E152KWJ1#	
			2200pF	±10%	GRJ21AR72E222KWJ1#	
			3300pF	±10%	GRJ21AR72E332KWJ1#	
			4700pF	±10%	GRJ21AR72E472KWJ1#	
			6800pF	±10%	GRJ21AR72E682KWJ1#	
1.45mm	250Vdc	X7R	10000pF	±10%	GRJ21BR72E103KWJ3#	
			15000pF	±10%	GRJ21BR72E153KWJ3#	
			22000pF	±10%	GRJ21BR72E223KWJ3#	
	100Vdc	X7R	47000pF	±10%	GRJ21BR72A473KE01#	
				±20%	GRJ21BR72A473ME01#	
			0.10μF	±10%	GRJ21BR72A104KE01#	
				±20%	GRJ21BR72A104ME01#	
	50Vdc	X7R	47000pF	±10%	GRJ21BR71H473KE01#	
				±20%	GRJ21BR71H473ME01#	
			0.10μF	±10%	GRJ21BR71H104KE01#	
				±20%	GRJ21BR71H104ME01#	
			0.22μF	±10%	GRJ21BR71H224KE01#	
				±20%	GRJ21BR71H224ME01#	
			0.47μF	±10%	GRJ21BR71H474KE01#	
				±20%	GRJ21BR71H474ME01#	
			1.0μF	±10%	GRJ21BR71H105KE01#	
				±20%	GRJ21BR71H105ME01#	
	25Vdc	X7R	1.0μF	±10%	GRJ21BR71E105KE11#	
				±20%	GRJ21BR71E105ME11#	
			2.2μF	±10%	GRJ21BR71E225KE01#	
				±20%	GRJ21BR71E225ME01#	
	16Vdc	X7R	4.7μF	±10%	GRJ21BR71C475KE01#	
				±20%	GRJ21BR71C475ME01#	
	10Vdc	X7R	10μF	±10%	GRJ21BR71A106KE01#	
				±20%	GRJ21BR71A106ME01#	
1.5mm	100Vdc	X7S	1.0μF	±10%	GRJ21BC72A105KE11#	
				±20%	GRJ21BC72A105ME11#	

Part number # indicates the package specification code.

GRJ Series High Dielectric Constant Type Deflecting crack Part Number List

3.2×1.6mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.95mm	100Vdc	X7R	0.10μF	±10%	GRJ319R72A104KE11#	
				±20%	GRJ319R72A104ME11#	
	50Vdc	X7R	0.10μF	±10%	GRJ319R71H104KE11#	
				±20%	GRJ319R71H104ME11#	
1.25mm	1000Vdc	X7R	470pF	±10%	GRJ31BR73A471KWJ1#	
			680pF	±10%	GRJ31BR73A681KWJ1#	
			1000pF	±10%	GRJ31BR73A102KWJ1#	
			1500pF	±10%	GRJ31BR73A152KWJ1#	
			2200pF	±10%	GRJ31BR73A222KWJ1#	
			3300pF	±10%	GRJ31BR73A332KWJ1#	
			4700pF	±10%	GRJ31BR73A472KWJ1#	
	630Vdc	X7R	1000pF	±10%	GRJ31BR72J102KWJ1#	
			1500pF	±10%	GRJ31BR72J152KWJ1#	
			2200pF	±10%	GRJ31BR72J222KWJ1#	
			3300pF	±10%	GRJ31BR72J332KWJ1#	
			4700pF	±10%	GRJ31BR72J472KWJ1#	
			6800pF	±10%	GRJ31BR72J682KWJ1#	
			10000pF	±10%	GRJ31BR72J103KWJ1#	
	250Vdc	X7R	15000pF	±10%	GRJ31BR72E153KWJ1#	
			22000pF	±10%	GRJ31BR72E223KWJ1#	
			68000pF	±10%	GRJ31BR72E683KWJ1#	
1.35mm	100Vdc	X7R	0.22μF	±10%	GRJ31MR72A224KE01#	
				±20%	GRJ31MR72A224ME01#	
	50Vdc	X7R	0.10μF	±10%	GRJ31MR71H104KE01#	
				±20%	GRJ31MR71H104ME01#	
			0.22μF	±10%	GRJ31MR71H224KE01#	
				±20%	GRJ31MR71H224ME01#	
			0.47μF	±10%	GRJ31MR71H474KE01#	
				±20%	GRJ31MR71H474ME01#	
			1.0μF	±10%	GRJ31MR71H105KE01#	
				±20%	GRJ31MR71H105ME01#	
	25Vdc	X7R	2.2μF	±10%	GRJ31MR71E225KE11#	
				±20%	GRJ31MR71E225ME11#	
	16Vdc	X7R	2.2μF	±10%	GRJ31MR71C225KE11#	
				±20%	GRJ31MR71C225ME11#	
1.8mm	1000Vdc	X7R	6800pF	±10%	GRJ31CR73A682KWJ3#	
			10000pF	±10%	GRJ31CR73A103KWJ3#	
	630Vdc	X7R	15000pF	±10%	GRJ31CR72J153KWJ3#	
			22000pF	±10%	GRJ31CR72J223KWJ3#	
	250Vdc	X7R	33000pF	±10%	GRJ31CR72E333KWJ3#	
			47000pF	±10%	GRJ31CR72E473KWJ3#	
			0.10μF	±10%	GRJ31CR72E104KWJ3#	
1.9mm	100Vdc	X7R	1.0μF	±10%	GRJ31CR72A105KE11#	
				±20%	GRJ31CR72A105ME11#	
	50Vdc	X7R	1.0μF	±10%	GRJ31CR71H105KE11#	
				±20%	GRJ31CR71H105ME11#	
			2.2μF	±10%	GRJ31CR71H225KE11#	
				±20%	GRJ31CR71H225ME11#	
			4.7μF	±10%	GRJ31CR71H475KE11#	
				±20%	GRJ31CR71H475ME11#	
	35Vdc	X6S	10μF	±10%	GRJ31CC8YA106KE01#	D1
				±20%	GRJ31CC8YA106ME01#	D1
1.9mm	25Vdc	X7R	10μF	±10%	GRJ31CR71E106KE11#	
				±20%	GRJ31CR71E106ME11#	
	16Vdc	X7R	4.7μF	±10%	GRJ31CR71C475KE11#	
				±20%	GRJ31CR71C475ME11#	
			10μF	±10%	GRJ31CR71C106KE11#	
				±20%	GRJ31CR71C106ME11#	
	10Vdc	X7R	10μF	±10%	GRJ31CR71A106KE11#	
				±20%	GRJ31CR71A106ME11#	
			22μF	±10%	GRJ31CR71A226KE12#	
				±20%	GRJ31CR71A226ME12#	
	6.3Vdc	X7R	22μF	±10%	GRJ31CR70J226KE12#	
				±20%	GRJ31CR70J226ME12#	

3.2×2.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.5mm	1000Vdc	X7R	6800pF	±10%	GRJ32QR73A682KWJ1#	
			10000pF	±10%	GRJ32QR73A103KWJ1#	
	630Vdc	X7R	22000pF	±10%	GRJ32QR72J223KWJ1#	
	250Vdc	X7R	68000pF	±10%	GRJ32QR72E683KWJ1#	
			0.15μF	±10%	GRJ32QR72E154KWJ1#	
2.0mm	1000Vdc	X7R	15000pF	±10%	GRJ32DR73A153KWJ1#	
			22000pF	±10%	GRJ32DR73A223KWJ1#	
	630Vdc	X7R	33000pF	±10%	GRJ32DR72J333KWJ1#	
			47000pF	±10%	GRJ32DR72J473KWJ1#	
	250Vdc	X7R	0.10μF	±10%	GRJ32DR72E104KWJ1#	
			0.22μF	±10%	GRJ32DR72E224KWJ1#	
2.3mm	100Vdc	X7R	2.2μF	±10%	GRJ32DR72A225KE11#	
				±20%	GRJ32DR72A225ME11#	
		X7S	4.7μF	±10%	GRJ32DC72A475KE11#	
				±20%	GRJ32DC72A475ME11#	
2.8mm	50Vdc	X7R	4.7μF	±10%	GRJ32ER71H475KE11#	
				±20%	GRJ32ER71H475ME11#	
			10μF	±10%	GRJ32ER71H106KE11#	
				±20%	GRJ32ER71H106ME11#	
		X7S	10μF	±10%	GRJ32EC71H106KE11#	
				±20%	GRJ32EC71H106ME11#	
	25Vdc	X7R	10μF	±10%	GRJ32ER71E106KE11#	
				±20%	GRJ32ER71E106ME11#	
	16Vdc	X7R	22μF	±10%	GRJ32ER71C226KE11#	
				±20%	GRJ32ER71C226ME11#	
	10Vdc	X7R	22μF	±10%	GRJ32ER71A226KE11#	
				±20%	GRJ32ER71A226ME11#	
			47μF	±10%	GRJ32ER71A476KE11#	
				±20%	GRJ32ER71A476ME11#	
	6.3Vdc	X7R	47μF	±10%	GRJ32ER70J476KE11#	
				±20%	GRJ32ER70J476ME11#	
2.85mm	25Vdc	X7S	22μF	±10%	GRJ32EC71E226KE11#	

Part number # indicates the package specification code.

GRJ Series High Dielectric Constant Type Deflecting crack Part Number List

4.5×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.5mm	630Vdc	X7R	68000pF	±10%	**GRJ43QR72J683KWJ1#**	
	250Vdc	X7R	0.15μF	±10%	**GRJ43QR72E154KWJ1#**	
2.0mm	1000Vdc	X7R	33000pF	±10%	**GRJ43DR73A333KWJ1#**	
			47000pF	±10%	**GRJ43DR73A473KWJ1#**	
	630Vdc	X7R	0.10μF	±10%	**GRJ43DR72J104KWJ1#**	
	250Vdc	X7R	0.22μF	±10%	**GRJ43DR72E224KWJ1#**	
			0.33μF	±10%	**GRJ43DR72E334KWJ1#**	
			0.47μF	±10%	**GRJ43DR72E474KWJ1#**	

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
2.0mm	1000Vdc	X7R	68000pF	±10%	**GRJ55DR73A683KWJ1#**	
			0.10μF	±10%	**GRJ55DR73A104KWJ1#**	
	630Vdc	X7R	0.15μF	±10%	**GRJ55DR72J154KWJ1#**	
			0.22μF	±10%	**GRJ55DR72J224KWJ1#**	
	250Vdc	X7R	0.33μF	±10%	**GRJ55DR72E334KWJ1#**	
			0.47μF	±10%	**GRJ55DR72E474KWJ1#**	
			0.68μF	±10%	**GRJ55DR72E684KWJ1#**	
			1.0μF	±10%	**GRJ55DR72E105KWJ1#**	

Part number # indicates the package specification code.

GRJ Series Specifications and Test Methods

Specifications and Test Methods, please refer to the search web page.
https://www.murata.com/en-global/products/capacitor



GRJ Series High Dielectric Constant Typ

1.6×0.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number
0.9mm	100Vdc	X7R	1000pF	±10%	GRJ188R72A102KE11#
				±20%	GRJ188R72A102ME11#
			2200pF	±10%	GRJ[illegible]2KE11#
				±20%	GRJ1[illegible]2ME11#
			4700pF	±10%	GRJ188R72A472KE11#
				±20%	GRJ188R72A472ME11#
			10000pF	±10%	GRJ188R72A103KE11#
				±20%	GRJ188R72A103ME11#

Links are provided to the product detail pages on the web, and are shown below in the product number table from the PDF version of the catalog which is available on the web.



GRJ188C70J475KE11#

Shape

Specifications

Notes

References

Chart of characteristic data

Detailed Specifications Sheet

- Rated value
- Specifications and Test Methods
- Package
- Caution, Notice

muRata

■ **Specifications and Test Methods**

No	Item		Specification	Test Method (Ref. Standard:JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage proof		No defects or abnormalities.	Measurement Point : Between the terminations Test Voltage : 250% of the rated voltage Applied Time : 1 to 5 s Charge/discharge current : 50mA max.
5	Insulation Resistance(I.R.)		More than 2000MΩ or 50Ω · F (Whichever is smaller)	Measurement Point : Between the terminations Measurement Voltage : DC Rated Voltage Charging Time : 1 min Charge/discharge current : 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance / Frequency / Voltage C≦10μF (10V min.) / 1.0+/-0.1kHz / 1.0+/-0.2Vrms C≦10μF (6.3V max.) / 1.0+/-0.1kHz / 0.5+/-0.1Vrms * C＞10μF / 120+/-24Hz / 0.5+/-0.1Vrms * For item GRJ188C70J475, the capacitance should be measured using a voltage of 1.0+/-0.2Vrms instead of 0.5+/-0.1Vrms.
7	Dissipation Factor (D.F.)		B1,R1,B3,R6,R7,C6,C7,C8,D7 : 0.1 max. D8 : 0.15 max	
8	Temperature Characteristics of Capacitance	No bias	B1,B3 : Within +/-10% (-25°C to +85°C) R1,R7 : Within +/-15% (-55°C to +125°C) R6 : Within +/-15% (-55°C to +85°C) C6 : Within +/-22% (-55°C to +85°C) C7 : Within+/-22% (-55°C to +125°C) C8 : Within +/-22% (-55°C to +105°C) D7 : Within +22/-33% (-55°C to +125°C) D8 : Within +22/-33% (-55°C to +105°C)	The capacitance change should be measured after 5 min. at each specified temp. stage. In case of applying voltage, the capacitance change should be measured after 1 min. with applying voltage in equilibration of each temp. stage. Capacitance value as a reference is the value in step 3. · Measurement Voltage : 0.20+/-0.05Vrms Step / Temperature(°C) / Applying Voltage(VDC) 1 / Reference Temp.+/-2

Chip Multilayer Ceramic Capacitors for Ethernet LAN and Primary-secondary Coupling of DC-DC Converters

GR4 Series

WEB

Size (L*W) : 4.5x2.0mm - 5.7x5.0mm / X7R Char. / DC2kV
Realized large capacity and small size while maintaining high withstand voltages by the multilayer structure.

Features

1. **For information devices of Ethernet LAN (IEEE802.3.) and primary - secondary couplings of DC-DC converters.**

ex) DC-DC Converter



ex) LAN Connecter



2. **Realized large capacity and small size while maintaining high withstand voltages by the multilayer structure.**



<Example of Structure>

3. **Dedicated for reflow soldering.**

Specifications

Size (mm)	4.5×2.0mm to 5.7×5.0mm
Rated Voltage	2000Vdc
Capacitance	100pF to 10000pF
Main Applications	For Ethernet LAN, Primary-secondary coupling for DC-DC converters



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

GR4 Series High Dielectric Constant Type Part Number List

4.5×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	2000Vdc	X7R	100pF	±10%	**GR442QR73D101KW01#**	p127
			120pF	±10%	**GR442QR73D121KW01#**	p127
			150pF	±10%	**GR442QR73D151KW01#**	p127
			180pF	±10%	**GR442QR73D181KW01#**	p127
			220pF	±10%	**GR442QR73D221KW01#**	p127
			270pF	±10%	**GR442QR73D271KW01#**	p127
			330pF	±10%	**GR442QR73D331KW01#**	p127
			390pF	±10%	**GR442QR73D391KW01#**	p127
			470pF	±10%	**GR442QR73D471KW01#**	p127
			560pF	±10%	**GR442QR73D561KW01#**	p127
			680pF	±10%	**GR442QR73D681KW01#**	p127
			820pF	±10%	**GR442QR73D821KW01#**	p127
			1000pF	±10%	**GR442QR73D102KW01#**	p127
			1200pF	±10%	**GR442QR73D122KW01#**	p127
			1500pF	±10%	**GR442QR73D152KW01#**	p127

4.5×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	2000Vdc	X7R	1800pF	±10%	**GR443QR73D182KW01#**	p127
			2200pF	±10%	**GR443QR73D222KW01#**	p127
			2700pF	±10%	**GR443QR73D272KW01#**	p127
			3300pF	±10%	**GR443QR73D332KW01#**	p127
			3900pF	±10%	**GR443QR73D392KW01#**	p127
2.0mm	2000Vdc	X7R	4700pF	±10%	**GR443DR73D472KW01#**	p127

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
2.0mm	2000Vdc	X7R	10000pF	±10%	**GR455DR73D103KW01#**	p127

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GR4 Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: DC2400V, Time: 60s Test Voltage: AC1.5kV (r.m.s), Time: 60s Charge/discharge current: 50mA max.
4	Impulse Voltage		No self healing break downs or flash-overs have taken place in the capacitor.	10 impulse of alternating polarity is subjected. (5 impulse for each polarity) The interval between impulse is 60s. Applied Pulse: 1.2/50μs Applied Voltage: 2.5kVo-p
5	Insulation Resistance (I.R.)		6000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
7	Dissipation Factor (D.F.)		0.025 max.	
8	Temperature Characteristics of Capacitance		R7: Within ±15% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2 • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
9	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
10	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt) % Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
11	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h. at room condition *. Preheat: GR442 size min.: 100 to 120°C for 1min and 170 to 200°C for 1min • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h. at room condition *.
		Capacitance Change	Within ±10%	
		D.F.	Within the specified initial value.	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR4 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
13	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp / 2 to 3 Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h. at room condition *.
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
15	Humidity (Steady State)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h. Exposure Time: 24±2h. at room condition *. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
16	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000+48/-0h Applied Voltage: DC2.2kV (110% of the rated voltage) Charge/discharge current: 50mA max. Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±20%	
		D.F.	0.05 max.	
		I.R.	2000MΩ or more	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR4 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GR442	3.5	7.0	2.4
GR443	3.5	7.0	3.7
GR455	4.5	8.0	5.6

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension (mm)			
	a	b	c	d
GR442	3.5	7.0	2.4	1.0
GR443	3.5	7.0	3.7	1.0
GR455	4.5	8.0	5.6	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



Chip Multilayer Ceramic Capacitors for Camera Flash circuit only

GR7 Series

WEB

Limited to camera flashes. Ideal for trigger capacitors and voltage doubler capacitors!

Features

1 Ideal for the trigger of flash circuits, as a higher capacitance can be acquired compared to conventional products (X7R characteristics) when a DC bias is applied.



<Comparison between Capacitance - DC Bias Characteristics>



◆Standard current control circuit



◆Boost current control circuit



C1: Trigger capacitor
C3: Voltage doubler capacitor

2 Contributes to the miniaturization of cameras with the low profile.

Specifications

Size (mm)	2.0×1.25mm to 3.2×1.6mm
Rated Voltage	350Vdc
Capacitance	10000pF to 47000pF
Main Applications	For camera flash

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

GR7 Series High Dielectric Constant Type Part Number List

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	350Vdc	X7T	10000pF	±10%	**GR721AW0BB103KW01#**	p132
			15000pF	±10%	**GR721AW0BB153KW01#**	p132
1.45mm	350Vdc	X7T	22000pF	±10%	**GR721BW0BB223KW03#**	p132
			27000pF	±10%	**GR721BW0BB273KW03#**	p132

3.2×1.6mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	350Vdc	X7T	10000pF	±10%	**GR731AW0BB103KW01#**	p132
			15000pF	±10%	**GR731AW0BB153KW01#**	p132
			22000pF	±10%	**GR731AW0BB223KW01#**	p132
			27000pF	±10%	**GR731AW0BB273KW01#**	p132
			33000pF	±10%	**GR731AW0BB333KW01#**	p132
1.25mm	350Vdc	X7T	22000pF	±10%	**GR731BW0BB223KW01#**	p132
			33000pF	±10%	**GR731BW0BB333KW01#**	p132
1.8mm	350Vdc	X7T	47000pF	±10%	**GR731CW0BB473KW03#**	p132

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GR7 Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: DC500V Applied Time: 1 to 5s Charge/discharge current: 50mA max.
4	Charge and Discharge Cycle	Appearance	No defects or abnormalities.	Test temperature: 25°C Discharge voltage: below figure Discharge cycle: 100k cycle Discharge frequency: 100Hz Exposure Time: 24±2h at room condition*.  • Pretreatment Apply test voltage (DC350V) for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	C ≧ 0.01μF: 10MΩ • μF or more C < 0.01μF: 1000MΩ or more	
		Voltage Proof	No defects.	
5	Insulation Resistance (I.R.)		C ≧ 0.01μF: 100MΩ • μF or more C < 0.01μF: 10000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC250±25V Charging Time: 60±5s Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature:Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
7	Dissipation Factor (D.F.)		0.025 max.	
8	Temperature Characteristics of Capacitance	No Bias	W0: Within +22/-33% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Apply DC350V Bias	W0: Within ±10% (-55 to +125°C)	
9	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
10	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
11	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GR731 size max.: 120 to 150°C for 1min • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±10%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR7 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
13	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: DC Rated Voltage Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	C ≧ 0.01μF: 10MΩ • μF or more C < 0.01μF: 1000MΩ or more	
		Voltage Proof	No defects.	
16	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting Test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000+48/-0h Applied Voltage: DC350V Charge/discharge current: 50mA max. Exposure Time: 24±2h at room condition*. • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition*.
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	C ≧ 0.01μF: 10MΩ • μF or more C < 0.01μF: 1000MΩ or more	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GR7 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GR721	1.2	4.0	1.65
GR731	2.2	5.0	2.0

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension (mm)			
	a	b	c	d
GR721	1.2	4.0	1.65	1.0
GR731	2.2	5.0	2.0	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



High Q Chip Multilayer Ceramic Capacitors for General Purpose

GJM Series

High Q

WEB

This product improves the high frequency characteristics and contributes to a reduction of power consumption by the High Q and low ESR.

Features

① Mainly ideal for mobile communication devices and temperature compensation of related modules.

This product is ideal for temperature compensation of high frequency circuits, such as resonant circuits, tuning circuits, and impedance matching circuits where the operating characteristics of the device are greatly affected by the capacitance fluctuation.



<Example of Structure>

② High Q and low ESR in VHF, UHF and microwave frequency bands.

High Q and low ESR were achieved at a high frequency by adopting ceramic material as the dielectric material which enables an extremely low loss at high frequency, and base metal electrodes as the internal electrodes.



<Comparison between ESR - Frequency Characteristics>



<Comparison between Q - Frequency Characteristics>

③ Can be used for tight tolerance.

In addition to standard tolerance, the allowable range of this product is also suitable for the following tight tolerance.

Capacitance Range	Standard Capacitance Tolerance (Capacitance Tolerance Symbol)	Narrow Capacitance Tolerance (Capacitance Tolerance Symbol)
to 0.9pF	±0.1pF (B)	±0.05pF (W)
1.0 to 5.0pF	±0.25pF (C)	±0.05pF (W), ±0.1pF (B)
5.1 to 9.9pF	±0.5pF (D)	±0.05pF (W), ±0.1pF (B), ±0.25pF (C)
10pF to	±5% (J)	±2% (G)

Specifications

Size (mm)	0.4×0.2mm to 1.0×0.5mm
Rated Voltage	6.3Vdc to 50Vdc
Capacitance	0.10pF to 47pF
Main Applications	Small communication devices, such as mobile phones and high frequency communication modules



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

GJM Series Temperature Compensating Type Part Number List

0.4×0.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	C0G	0.20pF	±0.05pF	**GJM0225C1ER20WB01#**	p157
				±0.1pF	**GJM0225C1ER20BB01#**	p157
			0.30pF	±0.05pF	**GJM0225C1ER30WB01#**	p157
				±0.1pF	**GJM0225C1ER30BB01#**	p157
			0.40pF	±0.05pF	**GJM0225C1ER40WB01#**	p157
				±0.1pF	**GJM0225C1ER40BB01#**	p157
			0.50pF	±0.05pF	**GJM0225C1ER50WB01#**	p157
				±0.1pF	**GJM0225C1ER50BB01#**	p157
			0.60pF	±0.05pF	**GJM0225C1ER60WB01#**	p157
				±0.1pF	**GJM0225C1ER60BB01#**	p157
			0.70pF	±0.05pF	**GJM0225C1ER70WB01#**	p157
				±0.1pF	**GJM0225C1ER70BB01#**	p157
			0.80pF	±0.05pF	**GJM0225C1ER80WB01#**	p157
				±0.1pF	**GJM0225C1ER80BB01#**	p157
			0.90pF	±0.05pF	**GJM0225C1ER90WB01#**	p157
				±0.1pF	**GJM0225C1ER90BB01#**	p157
			1.0pF	±0.05pF	**GJM0225C1E1R0WB01#**	p157
				±0.1pF	**GJM0225C1E1R0BB01#**	p157
				±0.25pF	**GJM0225C1E1R0CB01#**	p157
			1.1pF	±0.05pF	**GJM0225C1E1R1WB01#**	p157
				±0.1pF	**GJM0225C1E1R1BB01#**	p157
				±0.25pF	**GJM0225C1E1R1CB01#**	p157
			1.2pF	±0.05pF	**GJM0225C1E1R2WB01#**	p157
				±0.1pF	**GJM0225C1E1R2BB01#**	p157
				±0.25pF	**GJM0225C1E1R2CB01#**	p157
			1.3pF	±0.05pF	**GJM0225C1E1R3WB01#**	p157
				±0.1pF	**GJM0225C1E1R3BB01#**	p157
				±0.25pF	**GJM0225C1E1R3CB01#**	p157
			1.4pF	±0.05pF	**GJM0225C1E1R4WB01#**	p157
				±0.1pF	**GJM0225C1E1R4BB01#**	p157
				±0.25pF	**GJM0225C1E1R4CB01#**	p157
			1.5pF	±0.05pF	**GJM0225C1E1R5WB01#**	p157
				±0.1pF	**GJM0225C1E1R5BB01#**	p157
				±0.25pF	**GJM0225C1E1R5CB01#**	p157
			1.6pF	±0.05pF	**GJM0225C1E1R6WB01#**	p157
				±0.1pF	**GJM0225C1E1R6BB01#**	p157
				±0.25pF	**GJM0225C1E1R6CB01#**	p157
			1.7pF	±0.05pF	**GJM0225C1E1R7WB01#**	p157
				±0.1pF	**GJM0225C1E1R7BB01#**	p157
				±0.25pF	**GJM0225C1E1R7CB01#**	p157
			1.8pF	±0.05pF	**GJM0225C1E1R8WB01#**	p157
				±0.1pF	**GJM0225C1E1R8BB01#**	p157
				±0.25pF	**GJM0225C1E1R8CB01#**	p157
			1.9pF	±0.05pF	**GJM0225C1E1R9WB01#**	p157
				±0.1pF	**GJM0225C1E1R9BB01#**	p157
				±0.25pF	**GJM0225C1E1R9CB01#**	p157
			2.0pF	±0.05pF	**GJM0225C1E2R0WB01#**	p157
				±0.1pF	**GJM0225C1E2R0BB01#**	p157
				±0.25pF	**GJM0225C1E2R0CB01#**	p157
			2.1pF	±0.05pF	**GJM0225C1E2R1WB01#**	p157
				±0.1pF	**GJM0225C1E2R1BB01#**	p157
				±0.25pF	**GJM0225C1E2R1CB01#**	p157
0.22mm	25Vdc	C0G	2.2pF	±0.05pF	**GJM0225C1E2R2WB01#**	p157
				±0.1pF	**GJM0225C1E2R2BB01#**	p157
				±0.25pF	**GJM0225C1E2R2CB01#**	p157
			2.3pF	±0.05pF	**GJM0225C1E2R3WB01#**	p157
				±0.1pF	**GJM0225C1E2R3BB01#**	p157
				±0.25pF	**GJM0225C1E2R3CB01#**	p157
			2.4pF	±0.05pF	**GJM0225C1E2R4WB01#**	p157
				±0.1pF	**GJM0225C1E2R4BB01#**	p157
				±0.25pF	**GJM0225C1E2R4CB01#**	p157
			2.5pF	±0.05pF	**GJM0225C1E2R5WB01#**	p157
				±0.1pF	**GJM0225C1E2R5BB01#**	p157
				±0.25pF	**GJM0225C1E2R5CB01#**	p157
			2.6pF	±0.05pF	**GJM0225C1E2R6WB01#**	p157
				±0.1pF	**GJM0225C1E2R6BB01#**	p157
				±0.25pF	**GJM0225C1E2R6CB01#**	p157
			2.7pF	±0.05pF	**GJM0225C1E2R7WB01#**	p157
				±0.1pF	**GJM0225C1E2R7BB01#**	p157
				±0.25pF	**GJM0225C1E2R7CB01#**	p157
			2.8pF	±0.05pF	**GJM0225C1E2R8WB01#**	p157
				±0.1pF	**GJM0225C1E2R8BB01#**	p157
				±0.25pF	**GJM0225C1E2R8CB01#**	p157
			2.9pF	±0.05pF	**GJM0225C1E2R9WB01#**	p157
				±0.1pF	**GJM0225C1E2R9BB01#**	p157
				±0.25pF	**GJM0225C1E2R9CB01#**	p157
			3.0pF	±0.05pF	**GJM0225C1E3R0WB01#**	p157
				±0.1pF	**GJM0225C1E3R0BB01#**	p157
				±0.25pF	**GJM0225C1E3R0CB01#**	p157
			3.1pF	±0.05pF	**GJM0225C1E3R1WB01#**	p157
				±0.1pF	**GJM0225C1E3R1BB01#**	p157
				±0.25pF	**GJM0225C1E3R1CB01#**	p157
			3.2pF	±0.05pF	**GJM0225C1E3R2WB01#**	p157
				±0.1pF	**GJM0225C1E3R2BB01#**	p157
				±0.25pF	**GJM0225C1E3R2CB01#**	p157
			3.3pF	±0.05pF	**GJM0225C1E3R3WB01#**	p157
				±0.1pF	**GJM0225C1E3R3BB01#**	p157
				±0.25pF	**GJM0225C1E3R3CB01#**	p157
			3.4pF	±0.05pF	**GJM0225C1E3R4WB01#**	p157
				±0.1pF	**GJM0225C1E3R4BB01#**	p157
				±0.25pF	**GJM0225C1E3R4CB01#**	p157
			3.5pF	±0.05pF	**GJM0225C1E3R5WB01#**	p157
				±0.1pF	**GJM0225C1E3R5BB01#**	p157
				±0.25pF	**GJM0225C1E3R5CB01#**	p157
			3.6pF	±0.05pF	**GJM0225C1E3R6WB01#**	p157
				±0.1pF	**GJM0225C1E3R6BB01#**	p157
				±0.25pF	**GJM0225C1E3R6CB01#**	p157
			3.7pF	±0.05pF	**GJM0225C1E3R7WB01#**	p157
				±0.1pF	**GJM0225C1E3R7BB01#**	p157
				±0.25pF	**GJM0225C1E3R7CB01#**	p157
			3.8pF	±0.05pF	**GJM0225C1E3R8WB01#**	p157
				±0.1pF	**GJM0225C1E3R8BB01#**	p157
				±0.25pF	**GJM0225C1E3R8CB01#**	p157
			3.9pF	±0.05pF	**GJM0225C1E3R9WB01#**	p157
				±0.1pF	**GJM0225C1E3R9BB01#**	p157
				±0.25pF	**GJM0225C1E3R9CB01#**	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	C0G	4.0pF	±0.05pF	GJM0225C1E4R0WB01#	p157
				±0.1pF	GJM0225C1E4R0BB01#	p157
				±0.25pF	GJM0225C1E4R0CB01#	p157
			4.1pF	±0.05pF	GJM0225C1E4R1WB01#	p157
				±0.1pF	GJM0225C1E4R1BB01#	p157
				±0.25pF	GJM0225C1E4R1CB01#	p157
			4.2pF	±0.05pF	GJM0225C1E4R2WB01#	p157
				±0.1pF	GJM0225C1E4R2BB01#	p157
				±0.25pF	GJM0225C1E4R2CB01#	p157
			4.3pF	±0.05pF	GJM0225C1E4R3WB01#	p157
				±0.1pF	GJM0225C1E4R3BB01#	p157
				±0.25pF	GJM0225C1E4R3CB01#	p157
			4.4pF	±0.05pF	GJM0225C1E4R4WB01#	p157
				±0.1pF	GJM0225C1E4R4BB01#	p157
				±0.25pF	GJM0225C1E4R4CB01#	p157
			4.5pF	±0.05pF	GJM0225C1E4R5WB01#	p157
				±0.1pF	GJM0225C1E4R5BB01#	p157
				±0.25pF	GJM0225C1E4R5CB01#	p157
			4.6pF	±0.05pF	GJM0225C1E4R6WB01#	p157
				±0.1pF	GJM0225C1E4R6BB01#	p157
				±0.25pF	GJM0225C1E4R6CB01#	p157
			4.7pF	±0.05pF	GJM0225C1E4R7WB01#	p157
				±0.1pF	GJM0225C1E4R7BB01#	p157
				±0.25pF	GJM0225C1E4R7CB01#	p157
			4.8pF	±0.05pF	GJM0225C1E4R8WB01#	p157
				±0.1pF	GJM0225C1E4R8BB01#	p157
				±0.25pF	GJM0225C1E4R8CB01#	p157
			4.9pF	±0.05pF	GJM0225C1E4R9WB01#	p157
				±0.1pF	GJM0225C1E4R9BB01#	p157
				±0.25pF	GJM0225C1E4R9CB01#	p157
			5.0pF	±0.05pF	GJM0225C1E5R0WB01#	p157
				±0.1pF	GJM0225C1E5R0BB01#	p157
				±0.25pF	GJM0225C1E5R0CB01#	p157
			5.1pF	±0.05pF	GJM0225C1E5R1WB01#	p157
				±0.1pF	GJM0225C1E5R1BB01#	p157
				±0.25pF	GJM0225C1E5R1CB01#	p157
				±0.5pF	GJM0225C1E5R1DB01#	p157
			5.2pF	±0.05pF	GJM0225C1E5R2WB01#	p157
				±0.1pF	GJM0225C1E5R2BB01#	p157
				±0.25pF	GJM0225C1E5R2CB01#	p157
				±0.5pF	GJM0225C1E5R2DB01#	p157
			5.3pF	±0.05pF	GJM0225C1E5R3WB01#	p157
				±0.1pF	GJM0225C1E5R3BB01#	p157
				±0.25pF	GJM0225C1E5R3CB01#	p157
				±0.5pF	GJM0225C1E5R3DB01#	p157
			5.4pF	±0.05pF	GJM0225C1E5R4WB01#	p157
				±0.1pF	GJM0225C1E5R4BB01#	p157
				±0.25pF	GJM0225C1E5R4CB01#	p157
				±0.5pF	GJM0225C1E5R4DB01#	p157
			5.5pF	±0.05pF	GJM0225C1E5R5WB01#	p157
				±0.1pF	GJM0225C1E5R5BB01#	p157
				±0.25pF	GJM0225C1E5R5CB01#	p157
				±0.5pF	GJM0225C1E5R5DB01#	p157
			5.6pF	±0.05pF	GJM0225C1E5R6WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	C0G	5.6pF	±0.1pF	GJM0225C1E5R6BB01#	p157
				±0.25pF	GJM0225C1E5R6CB01#	p157
				±0.5pF	GJM0225C1E5R6DB01#	p157
			5.7pF	±0.05pF	GJM0225C1E5R7WB01#	p157
				±0.1pF	GJM0225C1E5R7BB01#	p157
				±0.25pF	GJM0225C1E5R7CB01#	p157
				±0.5pF	GJM0225C1E5R7DB01#	p157
			5.8pF	±0.05pF	GJM0225C1E5R8WB01#	p157
				±0.1pF	GJM0225C1E5R8BB01#	p157
				±0.25pF	GJM0225C1E5R8CB01#	p157
				±0.5pF	GJM0225C1E5R8DB01#	p157
			5.9pF	±0.05pF	GJM0225C1E5R9WB01#	p157
				±0.1pF	GJM0225C1E5R9BB01#	p157
				±0.25pF	GJM0225C1E5R9CB01#	p157
				±0.5pF	GJM0225C1E5R9DB01#	p157
			6.0pF	±0.05pF	GJM0225C1E6R0WB01#	p157
				±0.1pF	GJM0225C1E6R0BB01#	p157
				±0.25pF	GJM0225C1E6R0CB01#	p157
				±0.5pF	GJM0225C1E6R0DB01#	p157
			6.1pF	±0.05pF	GJM0225C1E6R1WB01#	p157
				±0.1pF	GJM0225C1E6R1BB01#	p157
				±0.25pF	GJM0225C1E6R1CB01#	p157
				±0.5pF	GJM0225C1E6R1DB01#	p157
			6.2pF	±0.05pF	GJM0225C1E6R2WB01#	p157
				±0.1pF	GJM0225C1E6R2BB01#	p157
				±0.25pF	GJM0225C1E6R2CB01#	p157
				±0.5pF	GJM0225C1E6R2DB01#	p157
			6.3pF	±0.05pF	GJM0225C1E6R3WB01#	p157
				±0.1pF	GJM0225C1E6R3BB01#	p157
				±0.25pF	GJM0225C1E6R3CB01#	p157
				±0.5pF	GJM0225C1E6R3DB01#	p157
			6.4pF	±0.05pF	GJM0225C1E6R4WB01#	p157
				±0.1pF	GJM0225C1E6R4BB01#	p157
				±0.25pF	GJM0225C1E6R4CB01#	p157
				±0.5pF	GJM0225C1E6R4DB01#	p157
			6.5pF	±0.05pF	GJM0225C1E6R5WB01#	p157
				±0.1pF	GJM0225C1E6R5BB01#	p157
				±0.25pF	GJM0225C1E6R5CB01#	p157
				±0.5pF	GJM0225C1E6R5DB01#	p157
			6.6pF	±0.05pF	GJM0225C1E6R6WB01#	p157
				±0.1pF	GJM0225C1E6R6BB01#	p157
				±0.25pF	GJM0225C1E6R6CB01#	p157
				±0.5pF	GJM0225C1E6R6DB01#	p157
			6.7pF	±0.05pF	GJM0225C1E6R7WB01#	p157
				±0.1pF	GJM0225C1E6R7BB01#	p157
				±0.25pF	GJM0225C1E6R7CB01#	p157
				±0.5pF	GJM0225C1E6R7DB01#	p157
			6.8pF	±0.05pF	GJM0225C1E6R8WB01#	p157
				±0.1pF	GJM0225C1E6R8BB01#	p157
				±0.25pF	GJM0225C1E6R8CB01#	p157
				±0.5pF	GJM0225C1E6R8DB01#	p157
			6.9pF	±0.05pF	GJM0225C1E6R9WB01#	p157
				±0.1pF	GJM0225C1E6R9BB01#	p157
				±0.25pF	GJM0225C1E6R9CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	C0G	6.9pF	±0.5pF	GJM0225C1E6R9DB01#	p157
			7.0pF	±0.05pF	GJM0225C1E7R0WB01#	p157
				±0.1pF	GJM0225C1E7R0BB01#	p157
				±0.25pF	GJM0225C1E7R0CB01#	p157
				±0.5pF	GJM0225C1E7R0DB01#	p157
			7.1pF	±0.05pF	GJM0225C1E7R1WB01#	p157
				±0.1pF	GJM0225C1E7R1BB01#	p157
				±0.25pF	GJM0225C1E7R1CB01#	p157
				±0.5pF	GJM0225C1E7R1DB01#	p157
			7.2pF	±0.05pF	GJM0225C1E7R2WB01#	p157
				±0.1pF	GJM0225C1E7R2BB01#	p157
				±0.25pF	GJM0225C1E7R2CB01#	p157
				±0.5pF	GJM0225C1E7R2DB01#	p157
			7.3pF	±0.05pF	GJM0225C1E7R3WB01#	p157
				±0.1pF	GJM0225C1E7R3BB01#	p157
				±0.25pF	GJM0225C1E7R3CB01#	p157
				±0.5pF	GJM0225C1E7R3DB01#	p157
			7.4pF	±0.05pF	GJM0225C1E7R4WB01#	p157
				±0.1pF	GJM0225C1E7R4BB01#	p157
				±0.25pF	GJM0225C1E7R4CB01#	p157
				±0.5pF	GJM0225C1E7R4DB01#	p157
			7.5pF	±0.05pF	GJM0225C1E7R5WB01#	p157
				±0.1pF	GJM0225C1E7R5BB01#	p157
				±0.25pF	GJM0225C1E7R5CB01#	p157
				±0.5pF	GJM0225C1E7R5DB01#	p157
			7.6pF	±0.05pF	GJM0225C1E7R6WB01#	p157
				±0.1pF	GJM0225C1E7R6BB01#	p157
				±0.25pF	GJM0225C1E7R6CB01#	p157
				±0.5pF	GJM0225C1E7R6DB01#	p157
			7.7pF	±0.05pF	GJM0225C1E7R7WB01#	p157
				±0.1pF	GJM0225C1E7R7BB01#	p157
				±0.25pF	GJM0225C1E7R7CB01#	p157
				±0.5pF	GJM0225C1E7R7DB01#	p157
			7.8pF	±0.05pF	GJM0225C1E7R8WB01#	p157
				±0.1pF	GJM0225C1E7R8BB01#	p157
				±0.25pF	GJM0225C1E7R8CB01#	p157
				±0.5pF	GJM0225C1E7R8DB01#	p157
			7.9pF	±0.05pF	GJM0225C1E7R9WB01#	p157
				±0.1pF	GJM0225C1E7R9BB01#	p157
				±0.25pF	GJM0225C1E7R9CB01#	p157
				±0.5pF	GJM0225C1E7R9DB01#	p157
			8.0pF	±0.05pF	GJM0225C1E8R0WB01#	p157
				±0.1pF	GJM0225C1E8R0BB01#	p157
				±0.25pF	GJM0225C1E8R0CB01#	p157
				±0.5pF	GJM0225C1E8R0DB01#	p157
			8.1pF	±0.05pF	GJM0225C1E8R1WB01#	p157
				±0.1pF	GJM0225C1E8R1BB01#	p157
				±0.25pF	GJM0225C1E8R1CB01#	p157
				±0.5pF	GJM0225C1E8R1DB01#	p157
			8.2pF	±0.05pF	GJM0225C1E8R2WB01#	p157
				±0.1pF	GJM0225C1E8R2BB01#	p157
				±0.25pF	GJM0225C1E8R2CB01#	p157
				±0.5pF	GJM0225C1E8R2DB01#	p157
			8.3pF	±0.05pF	GJM0225C1E8R3WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	C0G	8.3pF	±0.1pF	GJM0225C1E8R3BB01#	p157
				±0.25pF	GJM0225C1E8R3CB01#	p157
				±0.5pF	GJM0225C1E8R3DB01#	p157
			8.4pF	±0.05pF	GJM0225C1E8R4WB01#	p157
				±0.1pF	GJM0225C1E8R4BB01#	p157
				±0.25pF	GJM0225C1E8R4CB01#	p157
				±0.5pF	GJM0225C1E8R4DB01#	p157
			8.5pF	±0.05pF	GJM0225C1E8R5WB01#	p157
				±0.1pF	GJM0225C1E8R5BB01#	p157
				±0.25pF	GJM0225C1E8R5CB01#	p157
				±0.5pF	GJM0225C1E8R5DB01#	p157
			8.6pF	±0.05pF	GJM0225C1E8R6WB01#	p157
				±0.1pF	GJM0225C1E8R6BB01#	p157
				±0.25pF	GJM0225C1E8R6CB01#	p157
				±0.5pF	GJM0225C1E8R6DB01#	p157
			8.7pF	±0.05pF	GJM0225C1E8R7WB01#	p157
				±0.1pF	GJM0225C1E8R7BB01#	p157
				±0.25pF	GJM0225C1E8R7CB01#	p157
				±0.5pF	GJM0225C1E8R7DB01#	p157
			8.8pF	±0.05pF	GJM0225C1E8R8WB01#	p157
				±0.1pF	GJM0225C1E8R8BB01#	p157
				±0.25pF	GJM0225C1E8R8CB01#	p157
				±0.5pF	GJM0225C1E8R8DB01#	p157
			8.9pF	±0.05pF	GJM0225C1E8R9WB01#	p157
				±0.1pF	GJM0225C1E8R9BB01#	p157
				±0.25pF	GJM0225C1E8R9CB01#	p157
				±0.5pF	GJM0225C1E8R9DB01#	p157
			9.0pF	±0.05pF	GJM0225C1E9R0WB01#	p157
				±0.1pF	GJM0225C1E9R0BB01#	p157
				±0.25pF	GJM0225C1E9R0CB01#	p157
				±0.5pF	GJM0225C1E9R0DB01#	p157
			9.1pF	±0.05pF	GJM0225C1E9R1WB01#	p157
				±0.1pF	GJM0225C1E9R1BB01#	p157
				±0.25pF	GJM0225C1E9R1CB01#	p157
				±0.5pF	GJM0225C1E9R1DB01#	p157
			9.2pF	±0.05pF	GJM0225C1E9R2WB01#	p157
				±0.1pF	GJM0225C1E9R2BB01#	p157
				±0.25pF	GJM0225C1E9R2CB01#	p157
				±0.5pF	GJM0225C1E9R2DB01#	p157
			9.3pF	±0.05pF	GJM0225C1E9R3WB01#	p157
				±0.1pF	GJM0225C1E9R3BB01#	p157
				±0.25pF	GJM0225C1E9R3CB01#	p157
				±0.5pF	GJM0225C1E9R3DB01#	p157
			9.4pF	±0.05pF	GJM0225C1E9R4WB01#	p157
				±0.1pF	GJM0225C1E9R4BB01#	p157
				±0.25pF	GJM0225C1E9R4CB01#	p157
				±0.5pF	GJM0225C1E9R4DB01#	p157
			9.5pF	±0.05pF	GJM0225C1E9R5WB01#	p157
				±0.1pF	GJM0225C1E9R5BB01#	p157
				±0.25pF	GJM0225C1E9R5CB01#	p157
				±0.5pF	GJM0225C1E9R5DB01#	p157
			9.6pF	±0.05pF	GJM0225C1E9R6WB01#	p157
				±0.1pF	GJM0225C1E9R6BB01#	p157
				±0.25pF	GJM0225C1E9R6CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	C0G	9.6pF	±0.5pF	GJM0225C1E9R6DB01#	p157
			9.7pF	±0.05pF	GJM0225C1E9R7WB01#	p157
				±0.1pF	GJM0225C1E9R7BB01#	p157
				±0.25pF	GJM0225C1E9R7CB01#	p157
				±0.5pF	GJM0225C1E9R7DB01#	p157
			9.8pF	±0.05pF	GJM0225C1E9R8WB01#	p157
				±0.1pF	GJM0225C1E9R8BB01#	p157
				±0.25pF	GJM0225C1E9R8CB01#	p157
				±0.5pF	GJM0225C1E9R8DB01#	p157
			9.9pF	±0.05pF	GJM0225C1E9R9WB01#	p157
				±0.1pF	GJM0225C1E9R9BB01#	p157
				±0.25pF	GJM0225C1E9R9CB01#	p157
				±0.5pF	GJM0225C1E9R9DB01#	p157
			10pF	±2%	GJM0225C1E100GB01#	p157
				±5%	GJM0225C1E100JB01#	p157
			11pF	±2%	GJM0225C1E110GB01#	p157
				±5%	GJM0225C1E110JB01#	p157
			12pF	±2%	GJM0225C1E120GB01#	p157
				±5%	GJM0225C1E120JB01#	p157
			13pF	±2%	GJM0225C1E130GB01#	p157
				±5%	GJM0225C1E130JB01#	p157
			15pF	±2%	GJM0225C1E150GB01#	p157
				±5%	GJM0225C1E150JB01#	p157
			16pF	±2%	GJM0225C1E160GB01#	p157
				±5%	GJM0225C1E160JB01#	p157
			18pF	±2%	GJM0225C1E180GB01#	p157
				±5%	GJM0225C1E180JB01#	p157
			20pF	±2%	GJM0225C1E200GB01#	p157
				±5%	GJM0225C1E200JB01#	p157
			22pF	±2%	GJM0225C1E220GB01#	p157
				±5%	GJM0225C1E220JB01#	p157
		CK	0.20pF	±0.05pF	GJM0224C1ER20WB01#	p157
				±0.1pF	GJM0224C1ER20BB01#	p157
			0.30pF	±0.05pF	GJM0224C1ER30WB01#	p157
				±0.1pF	GJM0224C1ER30BB01#	p157
			0.40pF	±0.05pF	GJM0224C1ER40WB01#	p157
				±0.1pF	GJM0224C1ER40BB01#	p157
			0.50pF	±0.05pF	GJM0224C1ER50WB01#	p157
				±0.1pF	GJM0224C1ER50BB01#	p157
			0.60pF	±0.05pF	GJM0224C1ER60WB01#	p157
				±0.1pF	GJM0224C1ER60BB01#	p157
			0.70pF	±0.05pF	GJM0224C1ER70WB01#	p157
				±0.1pF	GJM0224C1ER70BB01#	p157
			0.80pF	±0.05pF	GJM0224C1ER80WB01#	p157
				±0.1pF	GJM0224C1ER80BB01#	p157
			0.90pF	±0.05pF	GJM0224C1ER90WB01#	p157
				±0.1pF	GJM0224C1ER90BB01#	p157
			1.0pF	±0.05pF	GJM0224C1E1R0WB01#	p157
				±0.1pF	GJM0224C1E1R0BB01#	p157
				±0.25pF	GJM0224C1E1R0CB01#	p157
			1.1pF	±0.05pF	GJM0224C1E1R1WB01#	p157
				±0.1pF	GJM0224C1E1R1BB01#	p157
				±0.25pF	GJM0224C1E1R1CB01#	p157
			1.2pF	±0.05pF	GJM0224C1E1R2WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	CK	1.2pF	±0.1pF	GJM0224C1E1R2BB01#	p157
				±0.25pF	GJM0224C1E1R2CB01#	p157
			1.3pF	±0.05pF	GJM0224C1E1R3WB01#	p157
				±0.1pF	GJM0224C1E1R3BB01#	p157
				±0.25pF	GJM0224C1E1R3CB01#	p157
			1.4pF	±0.05pF	GJM0224C1E1R4WB01#	p157
				±0.1pF	GJM0224C1E1R4BB01#	p157
				±0.25pF	GJM0224C1E1R4CB01#	p157
			1.5pF	±0.05pF	GJM0224C1E1R5WB01#	p157
				±0.1pF	GJM0224C1E1R5BB01#	p157
				±0.25pF	GJM0224C1E1R5CB01#	p157
			1.6pF	±0.05pF	GJM0224C1E1R6WB01#	p157
				±0.1pF	GJM0224C1E1R6BB01#	p157
				±0.25pF	GJM0224C1E1R6CB01#	p157
			1.7pF	±0.05pF	GJM0224C1E1R7WB01#	p157
				±0.1pF	GJM0224C1E1R7BB01#	p157
				±0.25pF	GJM0224C1E1R7CB01#	p157
			1.8pF	±0.05pF	GJM0224C1E1R8WB01#	p157
				±0.1pF	GJM0224C1E1R8BB01#	p157
				±0.25pF	GJM0224C1E1R8CB01#	p157
			1.9pF	±0.05pF	GJM0224C1E1R9WB01#	p157
				±0.1pF	GJM0224C1E1R9BB01#	p157
				±0.25pF	GJM0224C1E1R9CB01#	p157
			2.0pF	±0.05pF	GJM0224C1E2R0WB01#	p157
				±0.1pF	GJM0224C1E2R0BB01#	p157
				±0.25pF	GJM0224C1E2R0CB01#	p157
		CJ	2.1pF	±0.05pF	GJM0223C1E2R1WB01#	p157
				±0.1pF	GJM0223C1E2R1BB01#	p157
				±0.25pF	GJM0223C1E2R1CB01#	p157
			2.2pF	±0.05pF	GJM0223C1E2R2WB01#	p157
				±0.1pF	GJM0223C1E2R2BB01#	p157
				±0.25pF	GJM0223C1E2R2CB01#	p157
			2.3pF	±0.05pF	GJM0223C1E2R3WB01#	p157
				±0.1pF	GJM0223C1E2R3BB01#	p157
				±0.25pF	GJM0223C1E2R3CB01#	p157
			2.4pF	±0.05pF	GJM0223C1E2R4WB01#	p157
				±0.1pF	GJM0223C1E2R4BB01#	p157
				±0.25pF	GJM0223C1E2R4CB01#	p157
			2.5pF	±0.05pF	GJM0223C1E2R5WB01#	p157
				±0.1pF	GJM0223C1E2R5BB01#	p157
				±0.25pF	GJM0223C1E2R5CB01#	p157
			2.6pF	±0.05pF	GJM0223C1E2R6WB01#	p157
				±0.1pF	GJM0223C1E2R6BB01#	p157
				±0.25pF	GJM0223C1E2R6CB01#	p157
			2.7pF	±0.05pF	GJM0223C1E2R7WB01#	p157
				±0.1pF	GJM0223C1E2R7BB01#	p157
				±0.25pF	GJM0223C1E2R7CB01#	p157
			2.8pF	±0.05pF	GJM0223C1E2R8WB01#	p157
				±0.1pF	GJM0223C1E2R8BB01#	p157
				±0.25pF	GJM0223C1E2R8CB01#	p157
			2.9pF	±0.05pF	GJM0223C1E2R9WB01#	p157
				±0.1pF	GJM0223C1E2R9BB01#	p157
				±0.25pF	GJM0223C1E2R9CB01#	p157
			3.0pF	±0.05pF	GJM0223C1E3R0WB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	CJ	3.0pF	±0.1pF	GJM0223C1E3R0BB01#	p157
				±0.25pF	GJM0223C1E3R0CB01#	p157
			3.1pF	±0.05pF	GJM0223C1E3R1WB01#	p157
				±0.1pF	GJM0223C1E3R1BB01#	p157
				±0.25pF	GJM0223C1E3R1CB01#	p157
			3.2pF	±0.05pF	GJM0223C1E3R2WB01#	p157
				±0.1pF	GJM0223C1E3R2BB01#	p157
				±0.25pF	GJM0223C1E3R2CB01#	p157
			3.3pF	±0.05pF	GJM0223C1E3R3WB01#	p157
				±0.1pF	GJM0223C1E3R3BB01#	p157
				±0.25pF	GJM0223C1E3R3CB01#	p157
			3.4pF	±0.05pF	GJM0223C1E3R4WB01#	p157
				±0.1pF	GJM0223C1E3R4BB01#	p157
				±0.25pF	GJM0223C1E3R4CB01#	p157
			3.5pF	±0.05pF	GJM0223C1E3R5WB01#	p157
				±0.1pF	GJM0223C1E3R5BB01#	p157
				±0.25pF	GJM0223C1E3R5CB01#	p157
			3.6pF	±0.05pF	GJM0223C1E3R6WB01#	p157
				±0.1pF	GJM0223C1E3R6BB01#	p157
				±0.25pF	GJM0223C1E3R6CB01#	p157
			3.7pF	±0.05pF	GJM0223C1E3R7WB01#	p157
				±0.1pF	GJM0223C1E3R7BB01#	p157
				±0.25pF	GJM0223C1E3R7CB01#	p157
			3.8pF	±0.05pF	GJM0223C1E3R8WB01#	p157
				±0.1pF	GJM0223C1E3R8BB01#	p157
				±0.25pF	GJM0223C1E3R8CB01#	p157
			3.9pF	±0.05pF	GJM0223C1E3R9WB01#	p157
				±0.1pF	GJM0223C1E3R9BB01#	p157
				±0.25pF	GJM0223C1E3R9CB01#	p157
		CH	4.0pF	±0.05pF	GJM0222C1E4R0WB01#	p157
				±0.1pF	GJM0222C1E4R0BB01#	p157
				±0.25pF	GJM0222C1E4R0CB01#	p157
			4.1pF	±0.05pF	GJM0222C1E4R1WB01#	p157
				±0.1pF	GJM0222C1E4R1BB01#	p157
				±0.25pF	GJM0222C1E4R1CB01#	p157
			4.2pF	±0.05pF	GJM0222C1E4R2WB01#	p157
				±0.1pF	GJM0222C1E4R2BB01#	p157
				±0.25pF	GJM0222C1E4R2CB01#	p157
			4.3pF	±0.05pF	GJM0222C1E4R3WB01#	p157
				±0.1pF	GJM0222C1E4R3BB01#	p157
				±0.25pF	GJM0222C1E4R3CB01#	p157
			4.4pF	±0.05pF	GJM0222C1E4R4WB01#	p157
				±0.1pF	GJM0222C1E4R4BB01#	p157
				±0.25pF	GJM0222C1E4R4CB01#	p157
			4.5pF	±0.05pF	GJM0222C1E4R5WB01#	p157
				±0.1pF	GJM0222C1E4R5BB01#	p157
				±0.25pF	GJM0222C1E4R5CB01#	p157
			4.6pF	±0.05pF	GJM0222C1E4R6WB01#	p157
				±0.1pF	GJM0222C1E4R6BB01#	p157
				±0.25pF	GJM0222C1E4R6CB01#	p157
			4.7pF	±0.05pF	GJM0222C1E4R7WB01#	p157
				±0.1pF	GJM0222C1E4R7BB01#	p157
				±0.25pF	GJM0222C1E4R7CB01#	p157
			4.8pF	±0.05pF	GJM0222C1E4R8WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	CH	4.8pF	±0.1pF	GJM0222C1E4R8BB01#	p157
				±0.25pF	GJM0222C1E4R8CB01#	p157
			4.9pF	±0.05pF	GJM0222C1E4R9WB01#	p157
				±0.1pF	GJM0222C1E4R9BB01#	p157
				±0.25pF	GJM0222C1E4R9CB01#	p157
			5.0pF	±0.05pF	GJM0222C1E5R0WB01#	p157
				±0.1pF	GJM0222C1E5R0BB01#	p157
				±0.25pF	GJM0222C1E5R0CB01#	p157
			5.1pF	±0.05pF	GJM0222C1E5R1WB01#	p157
				±0.1pF	GJM0222C1E5R1BB01#	p157
				±0.25pF	GJM0222C1E5R1CB01#	p157
				±0.5pF	GJM0222C1E5R1DB01#	p157
			5.2pF	±0.05pF	GJM0222C1E5R2WB01#	p157
				±0.1pF	GJM0222C1E5R2BB01#	p157
				±0.25pF	GJM0222C1E5R2CB01#	p157
				±0.5pF	GJM0222C1E5R2DB01#	p157
			5.3pF	±0.05pF	GJM0222C1E5R3WB01#	p157
				±0.1pF	GJM0222C1E5R3BB01#	p157
				±0.25pF	GJM0222C1E5R3CB01#	p157
				±0.5pF	GJM0222C1E5R3DB01#	p157
			5.4pF	±0.05pF	GJM0222C1E5R4WB01#	p157
				±0.1pF	GJM0222C1E5R4BB01#	p157
				±0.25pF	GJM0222C1E5R4CB01#	p157
				±0.5pF	GJM0222C1E5R4DB01#	p157
			5.5pF	±0.05pF	GJM0222C1E5R5WB01#	p157
				±0.1pF	GJM0222C1E5R5BB01#	p157
				±0.25pF	GJM0222C1E5R5CB01#	p157
				±0.5pF	GJM0222C1E5R5DB01#	p157
			5.6pF	±0.05pF	GJM0222C1E5R6WB01#	p157
				±0.1pF	GJM0222C1E5R6BB01#	p157
				±0.25pF	GJM0222C1E5R6CB01#	p157
				±0.5pF	GJM0222C1E5R6DB01#	p157
			5.7pF	±0.05pF	GJM0222C1E5R7WB01#	p157
				±0.1pF	GJM0222C1E5R7BB01#	p157
				±0.25pF	GJM0222C1E5R7CB01#	p157
				±0.5pF	GJM0222C1E5R7DB01#	p157
			5.8pF	±0.05pF	GJM0222C1E5R8WB01#	p157
				±0.1pF	GJM0222C1E5R8BB01#	p157
				±0.25pF	GJM0222C1E5R8CB01#	p157
				±0.5pF	GJM0222C1E5R8DB01#	p157
			5.9pF	±0.05pF	GJM0222C1E5R9WB01#	p157
				±0.1pF	GJM0222C1E5R9BB01#	p157
				±0.25pF	GJM0222C1E5R9CB01#	p157
				±0.5pF	GJM0222C1E5R9DB01#	p157
			6.0pF	±0.05pF	GJM0222C1E6R0WB01#	p157
				±0.1pF	GJM0222C1E6R0BB01#	p157
				±0.25pF	GJM0222C1E6R0CB01#	p157
				±0.5pF	GJM0222C1E6R0DB01#	p157
			6.1pF	±0.05pF	GJM0222C1E6R1WB01#	p157
				±0.1pF	GJM0222C1E6R1BB01#	p157
				±0.25pF	GJM0222C1E6R1CB01#	p157
				±0.5pF	GJM0222C1E6R1DB01#	p157
			6.2pF	±0.05pF	GJM0222C1E6R2WB01#	p157
				±0.1pF	GJM0222C1E6R2BB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	CH	6.2pF	±0.25pF	GJM0222C1E6R2CB01#	p157
				±0.5pF	GJM0222C1E6R2DB01#	p157
			6.3pF	±0.05pF	GJM0222C1E6R3WB01#	p157
				±0.1pF	GJM0222C1E6R3BB01#	p157
				±0.25pF	GJM0222C1E6R3CB01#	p157
				±0.5pF	GJM0222C1E6R3DB01#	p157
			6.4pF	±0.05pF	GJM0222C1E6R4WB01#	p157
				±0.1pF	GJM0222C1E6R4BB01#	p157
				±0.25pF	GJM0222C1E6R4CB01#	p157
				±0.5pF	GJM0222C1E6R4DB01#	p157
			6.5pF	±0.05pF	GJM0222C1E6R5WB01#	p157
				±0.1pF	GJM0222C1E6R5BB01#	p157
				±0.25pF	GJM0222C1E6R5CB01#	p157
				±0.5pF	GJM0222C1E6R5DB01#	p157
			6.6pF	±0.05pF	GJM0222C1E6R6WB01#	p157
				±0.1pF	GJM0222C1E6R6BB01#	p157
				±0.25pF	GJM0222C1E6R6CB01#	p157
				±0.5pF	GJM0222C1E6R6DB01#	p157
			6.7pF	±0.05pF	GJM0222C1E6R7WB01#	p157
				±0.1pF	GJM0222C1E6R7BB01#	p157
				±0.25pF	GJM0222C1E6R7CB01#	p157
				±0.5pF	GJM0222C1E6R7DB01#	p157
			6.8pF	±0.05pF	GJM0222C1E6R8WB01#	p157
				±0.1pF	GJM0222C1E6R8BB01#	p157
				±0.25pF	GJM0222C1E6R8CB01#	p157
				±0.5pF	GJM0222C1E6R8DB01#	p157
			6.9pF	±0.05pF	GJM0222C1E6R9WB01#	p157
				±0.1pF	GJM0222C1E6R9BB01#	p157
				±0.25pF	GJM0222C1E6R9CB01#	p157
				±0.5pF	GJM0222C1E6R9DB01#	p157
			7.0pF	±0.05pF	GJM0222C1E7R0WB01#	p157
				±0.1pF	GJM0222C1E7R0BB01#	p157
				±0.25pF	GJM0222C1E7R0CB01#	p157
				±0.5pF	GJM0222C1E7R0DB01#	p157
			7.1pF	±0.05pF	GJM0222C1E7R1WB01#	p157
				±0.1pF	GJM0222C1E7R1BB01#	p157
				±0.25pF	GJM0222C1E7R1CB01#	p157
				±0.5pF	GJM0222C1E7R1DB01#	p157
			7.2pF	±0.05pF	GJM0222C1E7R2WB01#	p157
				±0.1pF	GJM0222C1E7R2BB01#	p157
				±0.25pF	GJM0222C1E7R2CB01#	p157
				±0.5pF	GJM0222C1E7R2DB01#	p157
			7.3pF	±0.05pF	GJM0222C1E7R3WB01#	p157
				±0.1pF	GJM0222C1E7R3BB01#	p157
				±0.25pF	GJM0222C1E7R3CB01#	p157
				±0.5pF	GJM0222C1E7R3DB01#	p157
			7.4pF	±0.05pF	GJM0222C1E7R4WB01#	p157
				±0.1pF	GJM0222C1E7R4BB01#	p157
				±0.25pF	GJM0222C1E7R4CB01#	p157
				±0.5pF	GJM0222C1E7R4DB01#	p157
			7.5pF	±0.05pF	GJM0222C1E7R5WB01#	p157
				±0.1pF	GJM0222C1E7R5BB01#	p157
				±0.25pF	GJM0222C1E7R5CB01#	p157
				±0.5pF	GJM0222C1E7R5DB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	CH	7.6pF	±0.05pF	GJM0222C1E7R6WB01#	p157
				±0.1pF	GJM0222C1E7R6BB01#	p157
				±0.25pF	GJM0222C1E7R6CB01#	p157
				±0.5pF	GJM0222C1E7R6DB01#	p157
			7.7pF	±0.05pF	GJM0222C1E7R7WB01#	p157
				±0.1pF	GJM0222C1E7R7BB01#	p157
				±0.25pF	GJM0222C1E7R7CB01#	p157
				±0.5pF	GJM0222C1E7R7DB01#	p157
			7.8pF	±0.05pF	GJM0222C1E7R8WB01#	p157
				±0.1pF	GJM0222C1E7R8BB01#	p157
				±0.25pF	GJM0222C1E7R8CB01#	p157
				±0.5pF	GJM0222C1E7R8DB01#	p157
			7.9pF	±0.05pF	GJM0222C1E7R9WB01#	p157
				±0.1pF	GJM0222C1E7R9BB01#	p157
				±0.25pF	GJM0222C1E7R9CB01#	p157
				±0.5pF	GJM0222C1E7R9DB01#	p157
			8.0pF	±0.05pF	GJM0222C1E8R0WB01#	p157
				±0.1pF	GJM0222C1E8R0BB01#	p157
				±0.25pF	GJM0222C1E8R0CB01#	p157
				±0.5pF	GJM0222C1E8R0DB01#	p157
			8.1pF	±0.05pF	GJM0222C1E8R1WB01#	p157
				±0.1pF	GJM0222C1E8R1BB01#	p157
				±0.25pF	GJM0222C1E8R1CB01#	p157
				±0.5pF	GJM0222C1E8R1DB01#	p157
			8.2pF	±0.05pF	GJM0222C1E8R2WB01#	p157
				±0.1pF	GJM0222C1E8R2BB01#	p157
				±0.25pF	GJM0222C1E8R2CB01#	p157
				±0.5pF	GJM0222C1E8R2DB01#	p157
			8.3pF	±0.05pF	GJM0222C1E8R3WB01#	p157
				±0.1pF	GJM0222C1E8R3BB01#	p157
				±0.25pF	GJM0222C1E8R3CB01#	p157
				±0.5pF	GJM0222C1E8R3DB01#	p157
			8.4pF	±0.05pF	GJM0222C1E8R4WB01#	p157
				±0.1pF	GJM0222C1E8R4BB01#	p157
				±0.25pF	GJM0222C1E8R4CB01#	p157
				±0.5pF	GJM0222C1E8R4DB01#	p157
			8.5pF	±0.05pF	GJM0222C1E8R5WB01#	p157
				±0.1pF	GJM0222C1E8R5BB01#	p157
				±0.25pF	GJM0222C1E8R5CB01#	p157
				±0.5pF	GJM0222C1E8R5DB01#	p157
			8.6pF	±0.05pF	GJM0222C1E8R6WB01#	p157
				±0.1pF	GJM0222C1E8R6BB01#	p157
				±0.25pF	GJM0222C1E8R6CB01#	p157
				±0.5pF	GJM0222C1E8R6DB01#	p157
			8.7pF	±0.05pF	GJM0222C1E8R7WB01#	p157
				±0.1pF	GJM0222C1E8R7BB01#	p157
				±0.25pF	GJM0222C1E8R7CB01#	p157
				±0.5pF	GJM0222C1E8R7DB01#	p157
			8.8pF	±0.05pF	GJM0222C1E8R8WB01#	p157
				±0.1pF	GJM0222C1E8R8BB01#	p157
				±0.25pF	GJM0222C1E8R8CB01#	p157
				±0.5pF	GJM0222C1E8R8DB01#	p157
			8.9pF	±0.05pF	GJM0222C1E8R9WB01#	p157
				±0.1pF	GJM0222C1E8R9BB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.4×0.2mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.22mm	25Vdc	CH	8.9pF	±0.25pF	GJM0222C1E8R9CB01#	p157
				±0.5pF	GJM0222C1E8R9DB01#	p157
			9.0pF	±0.05pF	GJM0222C1E9R0WB01#	p157
				±0.1pF	GJM0222C1E9R0BB01#	p157
				±0.25pF	GJM0222C1E9R0CB01#	p157
				±0.5pF	GJM0222C1E9R0DB01#	p157
			9.1pF	±0.05pF	GJM0222C1E9R1WB01#	p157
				±0.1pF	GJM0222C1E9R1BB01#	p157
				±0.25pF	GJM0222C1E9R1CB01#	p157
				±0.5pF	GJM0222C1E9R1DB01#	p157
			9.2pF	±0.05pF	GJM0222C1E9R2WB01#	p157
				±0.1pF	GJM0222C1E9R2BB01#	p157
				±0.25pF	GJM0222C1E9R2CB01#	p157
				±0.5pF	GJM0222C1E9R2DB01#	p157
			9.3pF	±0.05pF	GJM0222C1E9R3WB01#	p157
				±0.1pF	GJM0222C1E9R3BB01#	p157
				±0.25pF	GJM0222C1E9R3CB01#	p157
				±0.5pF	GJM0222C1E9R3DB01#	p157
			9.4pF	±0.05pF	GJM0222C1E9R4WB01#	p157
				±0.1pF	GJM0222C1E9R4BB01#	p157
				±0.25pF	GJM0222C1E9R4CB01#	p157
				±0.5pF	GJM0222C1E9R4DB01#	p157
			9.5pF	±0.05pF	GJM0222C1E9R5WB01#	p157
				±0.1pF	GJM0222C1E9R5BB01#	p157
				±0.25pF	GJM0222C1E9R5CB01#	p157
				±0.5pF	GJM0222C1E9R5DB01#	p157
			9.6pF	±0.05pF	GJM0222C1E9R6WB01#	p157
				±0.1pF	GJM0222C1E9R6BB01#	p157
				±0.25pF	GJM0222C1E9R6CB01#	p157
				±0.5pF	GJM0222C1E9R6DB01#	p157
			9.7pF	±0.05pF	GJM0222C1E9R7WB01#	p157
				±0.1pF	GJM0222C1E9R7BB01#	p157
				±0.25pF	GJM0222C1E9R7CB01#	p157
				±0.5pF	GJM0222C1E9R7DB01#	p157
			9.8pF	±0.05pF	GJM0222C1E9R8WB01#	p157
				±0.1pF	GJM0222C1E9R8BB01#	p157
				±0.25pF	GJM0222C1E9R8CB01#	p157
				±0.5pF	GJM0222C1E9R8DB01#	p157
			9.9pF	±0.05pF	GJM0222C1E9R9WB01#	p157
				±0.1pF	GJM0222C1E9R9BB01#	p157
				±0.25pF	GJM0222C1E9R9CB01#	p157
				±0.5pF	GJM0222C1E9R9DB01#	p157
			10pF	±2%	GJM0222C1E100GB01#	p157
				±5%	GJM0222C1E100JB01#	p157
			11pF	±2%	GJM0222C1E110GB01#	p157
				±5%	GJM0222C1E110JB01#	p157
			12pF	±2%	GJM0222C1E120GB01#	p157
				±5%	GJM0222C1E120JB01#	p157
			13pF	±2%	GJM0222C1E130GB01#	p157
				±5%	GJM0222C1E130JB01#	p157
			15pF	±2%	GJM0222C1E150GB01#	p157
				±5%	GJM0222C1E150JB01#	p157
			16pF	±2%	GJM0222C1E160GB01#	p157
				±5%	GJM0222C1E160JB01#	p157
0.22mm	25Vdc	CH	18pF	±2%	GJM0222C1E180GB01#	p157
				±5%	GJM0222C1E180JB01#	p157
			20pF	±2%	GJM0222C1E200GB01#	p157
				±5%	GJM0222C1E200JB01#	p157
			22pF	±2%	GJM0222C1E220GB01#	p157
				±5%	GJM0222C1E220JB01#	p157

0.6×0.3mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	50Vdc	C0G	0.20pF	±0.05pF	GJM0335C1HR20WB01#	p160
				±0.1pF	GJM0335C1HR20BB01#	p160
			0.30pF	±0.05pF	GJM0335C1HR30WB01#	p160
				±0.1pF	GJM0335C1HR30BB01#	p160
			0.40pF	±0.05pF	GJM0335C1HR40WB01#	p160
				±0.1pF	GJM0335C1HR40BB01#	p160
			0.50pF	±0.05pF	GJM0335C1HR50WB01#	p160
				±0.1pF	GJM0335C1HR50BB01#	p160
			0.60pF	±0.05pF	GJM0335C1HR60WB01#	p160
				±0.1pF	GJM0335C1HR60BB01#	p160
			0.70pF	±0.05pF	GJM0335C1HR70WB01#	p160
				±0.1pF	GJM0335C1HR70BB01#	p160
			0.80pF	±0.05pF	GJM0335C1HR80WB01#	p160
				±0.1pF	GJM0335C1HR80BB01#	p160
			0.90pF	±0.05pF	GJM0335C1HR90WB01#	p160
				±0.1pF	GJM0335C1HR90BB01#	p160
		CK	0.20pF	±0.05pF	GJM0334C1HR20WB01#	p160
			0.30pF	±0.05pF	GJM0334C1HR30WB01#	p160
			0.40pF	±0.05pF	GJM0334C1HR40WB01#	p160
			0.50pF	±0.05pF	GJM0334C1HR50WB01#	p160
			0.60pF	±0.05pF	GJM0334C1HR60WB01#	p160
			0.70pF	±0.05pF	GJM0334C1HR70WB01#	p160
			0.80pF	±0.05pF	GJM0334C1HR80WB01#	p160
			0.90pF	±0.05pF	GJM0334C1HR90WB01#	p160
			1.0pF	±0.1pF	GJM0334C1H1R0BB01#	p160
			1.1pF	±0.1pF	GJM0334C1H1R1BB01#	p160
			1.2pF	±0.1pF	GJM0334C1H1R2BB01#	p160
			1.3pF	±0.1pF	GJM0334C1H1R3BB01#	p160
			1.5pF	±0.1pF	GJM0334C1H1R5BB01#	p160
			1.6pF	±0.1pF	GJM0334C1H1R6BB01#	p160
			1.8pF	±0.1pF	GJM0334C1H1R8BB01#	p160
			2.0pF	±0.1pF	GJM0334C1H2R0BB01#	p160
		CJ	2.2pF	±0.1pF	GJM0333C1H2R2BB01#	p160
			2.4pF	±0.1pF	GJM0333C1H2R4BB01#	p160
			2.7pF	±0.1pF	GJM0333C1H2R7BB01#	p160
			3.0pF	±0.1pF	GJM0333C1H3R0BB01#	p160
			3.3pF	±0.1pF	GJM0333C1H3R3BB01#	p160
			3.6pF	±0.1pF	GJM0333C1H3R6BB01#	p160
			3.9pF	±0.1pF	GJM0333C1H3R9BB01#	p160
		CH	0.20pF	±0.05pF	GJM0332C1HR20WB01#	p160
				±0.1pF	GJM0332C1HR20BB01#	p160
			0.30pF	±0.05pF	GJM0332C1HR30WB01#	p160
				±0.1pF	GJM0332C1HR30BB01#	p160

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	50Vdc	CH	0.40pF	±0.05pF	GJM0332C1HR40WB01#	p160
				±0.1pF	GJM0332C1HR40BB01#	p160
			0.50pF	±0.05pF	GJM0332C1HR50WB01#	p160
				±0.1pF	GJM0332C1HR50BB01#	p160
			0.60pF	±0.05pF	GJM0332C1HR60WB01#	p160
				±0.1pF	GJM0332C1HR60BB01#	p160
			0.70pF	±0.05pF	GJM0332C1HR70WB01#	p160
				±0.1pF	GJM0332C1HR70BB01#	p160
			0.80pF	±0.05pF	GJM0332C1HR80WB01#	p160
				±0.1pF	GJM0332C1HR80BB01#	p160
			0.90pF	±0.05pF	GJM0332C1HR90WB01#	p160
				±0.1pF	GJM0332C1HR90BB01#	p160
	25Vdc	C0G	1.0pF	±0.05pF	GJM0335C1E1R0WB01#	p157
				±0.1pF	GJM0335C1E1R0BB01#	p157
				±0.25pF	GJM0335C1E1R0CB01#	p157
			1.1pF	±0.05pF	GJM0335C1E1R1WB01#	p157
				±0.1pF	GJM0335C1E1R1BB01#	p157
				±0.25pF	GJM0335C1E1R1CB01#	p157
			1.2pF	±0.05pF	GJM0335C1E1R2WB01#	p157
				±0.1pF	GJM0335C1E1R2BB01#	p157
				±0.25pF	GJM0335C1E1R2CB01#	p157
			1.3pF	±0.05pF	GJM0335C1E1R3WB01#	p157
				±0.1pF	GJM0335C1E1R3BB01#	p157
				±0.25pF	GJM0335C1E1R3CB01#	p157
			1.4pF	±0.05pF	GJM0335C1E1R4WB01#	p157
				±0.1pF	GJM0335C1E1R4BB01#	p157
				±0.25pF	GJM0335C1E1R4CB01#	p157
			1.5pF	±0.05pF	GJM0335C1E1R5WB01#	p157
				±0.1pF	GJM0335C1E1R5BB01#	p157
				±0.25pF	GJM0335C1E1R5CB01#	p157
			1.6pF	±0.05pF	GJM0335C1E1R6WB01#	p157
				±0.1pF	GJM0335C1E1R6BB01#	p157
				±0.25pF	GJM0335C1E1R6CB01#	p157
			1.7pF	±0.05pF	GJM0335C1E1R7WB01#	p157
				±0.1pF	GJM0335C1E1R7BB01#	p157
				±0.25pF	GJM0335C1E1R7CB01#	p157
			1.8pF	±0.05pF	GJM0335C1E1R8WB01#	p157
				±0.1pF	GJM0335C1E1R8BB01#	p157
				±0.25pF	GJM0335C1E1R8CB01#	p157
			1.9pF	±0.05pF	GJM0335C1E1R9WB01#	p157
				±0.1pF	GJM0335C1E1R9BB01#	p157
				±0.25pF	GJM0335C1E1R9CB01#	p157
			2.0pF	±0.05pF	GJM0335C1E2R0WB01#	p157
				±0.1pF	GJM0335C1E2R0BB01#	p157
				±0.25pF	GJM0335C1E2R0CB01#	p157
			2.1pF	±0.05pF	GJM0335C1E2R1WB01#	p157
				±0.1pF	GJM0335C1E2R1BB01#	p157
				±0.25pF	GJM0335C1E2R1CB01#	p157
			2.2pF	±0.05pF	GJM0335C1E2R2WB01#	p157
				±0.1pF	GJM0335C1E2R2BB01#	p157
				±0.25pF	GJM0335C1E2R2CB01#	p157
			2.3pF	±0.05pF	GJM0335C1E2R3WB01#	p157
				±0.1pF	GJM0335C1E2R3BB01#	p157
				±0.25pF	GJM0335C1E2R3CB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	C0G	2.4pF	±0.05pF	GJM0335C1E2R4WB01#	p157
				±0.1pF	GJM0335C1E2R4BB01#	p157
				±0.25pF	GJM0335C1E2R4CB01#	p157
			2.5pF	±0.05pF	GJM0335C1E2R5WB01#	p157
				±0.1pF	GJM0335C1E2R5BB01#	p157
				±0.25pF	GJM0335C1E2R5CB01#	p157
			2.6pF	±0.05pF	GJM0335C1E2R6WB01#	p157
				±0.1pF	GJM0335C1E2R6BB01#	p157
				±0.25pF	GJM0335C1E2R6CB01#	p157
			2.7pF	±0.05pF	GJM0335C1E2R7WB01#	p157
				±0.1pF	GJM0335C1E2R7BB01#	p157
				±0.25pF	GJM0335C1E2R7CB01#	p157
			2.8pF	±0.05pF	GJM0335C1E2R8WB01#	p157
				±0.1pF	GJM0335C1E2R8BB01#	p157
				±0.25pF	GJM0335C1E2R8CB01#	p157
			2.9pF	±0.05pF	GJM0335C1E2R9WB01#	p157
				±0.1pF	GJM0335C1E2R9BB01#	p157
				±0.25pF	GJM0335C1E2R9CB01#	p157
			3.0pF	±0.05pF	GJM0335C1E3R0WB01#	p157
				±0.1pF	GJM0335C1E3R0BB01#	p157
				±0.25pF	GJM0335C1E3R0CB01#	p157
			3.1pF	±0.05pF	GJM0335C1E3R1WB01#	p157
				±0.1pF	GJM0335C1E3R1BB01#	p157
				±0.25pF	GJM0335C1E3R1CB01#	p157
			3.2pF	±0.05pF	GJM0335C1E3R2WB01#	p157
				±0.1pF	GJM0335C1E3R2BB01#	p157
				±0.25pF	GJM0335C1E3R2CB01#	p157
			3.3pF	±0.05pF	GJM0335C1E3R3WB01#	p157
				±0.1pF	GJM0335C1E3R3BB01#	p157
				±0.25pF	GJM0335C1E3R3CB01#	p157
			3.4pF	±0.05pF	GJM0335C1E3R4WB01#	p157
				±0.1pF	GJM0335C1E3R4BB01#	p157
				±0.25pF	GJM0335C1E3R4CB01#	p157
			3.5pF	±0.05pF	GJM0335C1E3R5WB01#	p157
				±0.1pF	GJM0335C1E3R5BB01#	p157
				±0.25pF	GJM0335C1E3R5CB01#	p157
			3.6pF	±0.05pF	GJM0335C1E3R6WB01#	p157
				±0.1pF	GJM0335C1E3R6BB01#	p157
				±0.25pF	GJM0335C1E3R6CB01#	p157
			3.7pF	±0.05pF	GJM0335C1E3R7WB01#	p157
				±0.1pF	GJM0335C1E3R7BB01#	p157
				±0.25pF	GJM0335C1E3R7CB01#	p157
			3.8pF	±0.05pF	GJM0335C1E3R8WB01#	p157
				±0.1pF	GJM0335C1E3R8BB01#	p157
				±0.25pF	GJM0335C1E3R8CB01#	p157
			3.9pF	±0.05pF	GJM0335C1E3R9WB01#	p157
				±0.1pF	GJM0335C1E3R9BB01#	p157
				±0.25pF	GJM0335C1E3R9CB01#	p157
			4.0pF	±0.05pF	GJM0335C1E4R0WB01#	p157
				±0.1pF	GJM0335C1E4R0BB01#	p157
				±0.25pF	GJM0335C1E4R0CB01#	p157
			4.1pF	±0.05pF	GJM0335C1E4R1WB01#	p157
				±0.1pF	GJM0335C1E4R1BB01#	p157
				±0.25pF	GJM0335C1E4R1CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	C0G	4.2pF	±0.05pF	GJM0335C1E4R2WB01#	p157
				±0.1pF	GJM0335C1E4R2BB01#	p157
				±0.25pF	GJM0335C1E4R2CB01#	p157
			4.3pF	±0.05pF	GJM0335C1E4R3WB01#	p157
				±0.1pF	GJM0335C1E4R3BB01#	p157
				±0.25pF	GJM0335C1E4R3CB01#	p157
			4.4pF	±0.05pF	GJM0335C1E4R4WB01#	p157
				±0.1pF	GJM0335C1E4R4BB01#	p157
				±0.25pF	GJM0335C1E4R4CB01#	p157
			4.5pF	±0.05pF	GJM0335C1E4R5WB01#	p157
				±0.1pF	GJM0335C1E4R5BB01#	p157
				±0.25pF	GJM0335C1E4R5CB01#	p157
			4.6pF	±0.05pF	GJM0335C1E4R6WB01#	p157
				±0.1pF	GJM0335C1E4R6BB01#	p157
				±0.25pF	GJM0335C1E4R6CB01#	p157
			4.7pF	±0.05pF	GJM0335C1E4R7WB01#	p157
				±0.1pF	GJM0335C1E4R7BB01#	p157
				±0.25pF	GJM0335C1E4R7CB01#	p157
			4.8pF	±0.05pF	GJM0335C1E4R8WB01#	p157
				±0.1pF	GJM0335C1E4R8BB01#	p157
				±0.25pF	GJM0335C1E4R8CB01#	p157
			4.9pF	±0.05pF	GJM0335C1E4R9WB01#	p157
				±0.1pF	GJM0335C1E4R9BB01#	p157
				±0.25pF	GJM0335C1E4R9CB01#	p157
			5.0pF	±0.05pF	GJM0335C1E5R0WB01#	p157
				±0.1pF	GJM0335C1E5R0BB01#	p157
				±0.25pF	GJM0335C1E5R0CB01#	p157
			5.1pF	±0.05pF	GJM0335C1E5R1WB01#	p157
				±0.1pF	GJM0335C1E5R1BB01#	p157
				±0.25pF	GJM0335C1E5R1CB01#	p157
				±0.5pF	GJM0335C1E5R1DB01#	p157
			5.2pF	±0.05pF	GJM0335C1E5R2WB01#	p157
				±0.1pF	GJM0335C1E5R2BB01#	p157
				±0.25pF	GJM0335C1E5R2CB01#	p157
				±0.5pF	GJM0335C1E5R2DB01#	p157
			5.3pF	±0.05pF	GJM0335C1E5R3WB01#	p157
				±0.1pF	GJM0335C1E5R3BB01#	p157
				±0.25pF	GJM0335C1E5R3CB01#	p157
				±0.5pF	GJM0335C1E5R3DB01#	p157
			5.4pF	±0.05pF	GJM0335C1E5R4WB01#	p157
				±0.1pF	GJM0335C1E5R4BB01#	p157
				±0.25pF	GJM0335C1E5R4CB01#	p157
				±0.5pF	GJM0335C1E5R4DB01#	p157
			5.5pF	±0.05pF	GJM0335C1E5R5WB01#	p157
				±0.1pF	GJM0335C1E5R5BB01#	p157
				±0.25pF	GJM0335C1E5R5CB01#	p157
				±0.5pF	GJM0335C1E5R5DB01#	p157
			5.6pF	±0.05pF	GJM0335C1E5R6WB01#	p157
				±0.1pF	GJM0335C1E5R6BB01#	p157
				±0.25pF	GJM0335C1E5R6CB01#	p157
				±0.5pF	GJM0335C1E5R6DB01#	p157
			5.7pF	±0.05pF	GJM0335C1E5R7WB01#	p157
				±0.1pF	GJM0335C1E5R7BB01#	p157
				±0.25pF	GJM0335C1E5R7CB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	C0G	5.7pF	±0.5pF	GJM0335C1E5R7DB01#	p157
			5.8pF	±0.05pF	GJM0335C1E5R8WB01#	p157
				±0.1pF	GJM0335C1E5R8BB01#	p157
				±0.25pF	GJM0335C1E5R8CB01#	p157
				±0.5pF	GJM0335C1E5R8DB01#	p157
			5.9pF	±0.05pF	GJM0335C1E5R9WB01#	p157
				±0.1pF	GJM0335C1E5R9BB01#	p157
				±0.25pF	GJM0335C1E5R9CB01#	p157
				±0.5pF	GJM0335C1E5R9DB01#	p157
			6.0pF	±0.05pF	GJM0335C1E6R0WB01#	p157
				±0.1pF	GJM0335C1E6R0BB01#	p157
				±0.25pF	GJM0335C1E6R0CB01#	p157
				±0.5pF	GJM0335C1E6R0DB01#	p157
			6.1pF	±0.05pF	GJM0335C1E6R1WB01#	p157
				±0.1pF	GJM0335C1E6R1BB01#	p157
				±0.25pF	GJM0335C1E6R1CB01#	p157
				±0.5pF	GJM0335C1E6R1DB01#	p157
			6.2pF	±0.05pF	GJM0335C1E6R2WB01#	p157
				±0.1pF	GJM0335C1E6R2BB01#	p157
				±0.25pF	GJM0335C1E6R2CB01#	p157
				±0.5pF	GJM0335C1E6R2DB01#	p157
			6.3pF	±0.05pF	GJM0335C1E6R3WB01#	p157
				±0.1pF	GJM0335C1E6R3BB01#	p157
				±0.25pF	GJM0335C1E6R3CB01#	p157
				±0.5pF	GJM0335C1E6R3DB01#	p157
			6.4pF	±0.05pF	GJM0335C1E6R4WB01#	p157
				±0.1pF	GJM0335C1E6R4BB01#	p157
				±0.25pF	GJM0335C1E6R4CB01#	p157
				±0.5pF	GJM0335C1E6R4DB01#	p157
			6.5pF	±0.05pF	GJM0335C1E6R5WB01#	p157
				±0.1pF	GJM0335C1E6R5BB01#	p157
				±0.25pF	GJM0335C1E6R5CB01#	p157
				±0.5pF	GJM0335C1E6R5DB01#	p157
			6.6pF	±0.05pF	GJM0335C1E6R6WB01#	p157
				±0.1pF	GJM0335C1E6R6BB01#	p157
				±0.25pF	GJM0335C1E6R6CB01#	p157
				±0.5pF	GJM0335C1E6R6DB01#	p157
			6.7pF	±0.05pF	GJM0335C1E6R7WB01#	p157
				±0.1pF	GJM0335C1E6R7BB01#	p157
				±0.25pF	GJM0335C1E6R7CB01#	p157
				±0.5pF	GJM0335C1E6R7DB01#	p157
			6.8pF	±0.05pF	GJM0335C1E6R8WB01#	p157
				±0.1pF	GJM0335C1E6R8BB01#	p157
				±0.25pF	GJM0335C1E6R8CB01#	p157
				±0.5pF	GJM0335C1E6R8DB01#	p157
			6.9pF	±0.05pF	GJM0335C1E6R9WB01#	p157
				±0.1pF	GJM0335C1E6R9BB01#	p157
				±0.25pF	GJM0335C1E6R9CB01#	p157
				±0.5pF	GJM0335C1E6R9DB01#	p157
			7.0pF	±0.05pF	GJM0335C1E7R0WB01#	p157
				±0.1pF	GJM0335C1E7R0BB01#	p157
				±0.25pF	GJM0335C1E7R0CB01#	p157
				±0.5pF	GJM0335C1E7R0DB01#	p157
			7.1pF	±0.05pF	GJM0335C1E7R1WB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	C0G	7.1pF	±0.1pF	GJM0335C1E7R1BB01#	p157
				±0.25pF	GJM0335C1E7R1CB01#	p157
				±0.5pF	GJM0335C1E7R1DB01#	p157
			7.2pF	±0.05pF	GJM0335C1E7R2WB01#	p157
				±0.1pF	GJM0335C1E7R2BB01#	p157
				±0.25pF	GJM0335C1E7R2CB01#	p157
				±0.5pF	GJM0335C1E7R2DB01#	p157
			7.3pF	±0.05pF	GJM0335C1E7R3WB01#	p157
				±0.1pF	GJM0335C1E7R3BB01#	p157
				±0.25pF	GJM0335C1E7R3CB01#	p157
				±0.5pF	GJM0335C1E7R3DB01#	p157
			7.4pF	±0.05pF	GJM0335C1E7R4WB01#	p157
				±0.1pF	GJM0335C1E7R4BB01#	p157
				±0.25pF	GJM0335C1E7R4CB01#	p157
				±0.5pF	GJM0335C1E7R4DB01#	p157
			7.5pF	±0.05pF	GJM0335C1E7R5WB01#	p157
				±0.1pF	GJM0335C1E7R5BB01#	p157
				±0.25pF	GJM0335C1E7R5CB01#	p157
				±0.5pF	GJM0335C1E7R5DB01#	p157
			7.6pF	±0.05pF	GJM0335C1E7R6WB01#	p157
				±0.1pF	GJM0335C1E7R6BB01#	p157
				±0.25pF	GJM0335C1E7R6CB01#	p157
				±0.5pF	GJM0335C1E7R6DB01#	p157
			7.7pF	±0.05pF	GJM0335C1E7R7WB01#	p157
				±0.1pF	GJM0335C1E7R7BB01#	p157
				±0.25pF	GJM0335C1E7R7CB01#	p157
				±0.5pF	GJM0335C1E7R7DB01#	p157
			7.8pF	±0.05pF	GJM0335C1E7R8WB01#	p157
				±0.1pF	GJM0335C1E7R8BB01#	p157
				±0.25pF	GJM0335C1E7R8CB01#	p157
				±0.5pF	GJM0335C1E7R8DB01#	p157
			7.9pF	±0.05pF	GJM0335C1E7R9WB01#	p157
				±0.1pF	GJM0335C1E7R9BB01#	p157
				±0.25pF	GJM0335C1E7R9CB01#	p157
				±0.5pF	GJM0335C1E7R9DB01#	p157
			8.0pF	±0.05pF	GJM0335C1E8R0WB01#	p157
				±0.1pF	GJM0335C1E8R0BB01#	p157
				±0.25pF	GJM0335C1E8R0CB01#	p157
				±0.5pF	GJM0335C1E8R0DB01#	p157
			8.1pF	±0.05pF	GJM0335C1E8R1WB01#	p157
				±0.1pF	GJM0335C1E8R1BB01#	p157
				±0.25pF	GJM0335C1E8R1CB01#	p157
				±0.5pF	GJM0335C1E8R1DB01#	p157
			8.2pF	±0.05pF	GJM0335C1E8R2WB01#	p157
				±0.1pF	GJM0335C1E8R2BB01#	p157
				±0.25pF	GJM0335C1E8R2CB01#	p157
				±0.5pF	GJM0335C1E8R2DB01#	p157
			8.3pF	±0.05pF	GJM0335C1E8R3WB01#	p157
				±0.1pF	GJM0335C1E8R3BB01#	p157
				±0.25pF	GJM0335C1E8R3CB01#	p157
				±0.5pF	GJM0335C1E8R3DB01#	p157
			8.4pF	±0.05pF	GJM0335C1E8R4WB01#	p157
				±0.1pF	GJM0335C1E8R4BB01#	p157
				±0.25pF	GJM0335C1E8R4CB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	C0G	8.4pF	±0.5pF	GJM0335C1E8R4DB01#	p157
			8.5pF	±0.05pF	GJM0335C1E8R5WB01#	p157
				±0.1pF	GJM0335C1E8R5BB01#	p157
				±0.25pF	GJM0335C1E8R5CB01#	p157
				±0.5pF	GJM0335C1E8R5DB01#	p157
			8.6pF	±0.05pF	GJM0335C1E8R6WB01#	p157
				±0.1pF	GJM0335C1E8R6BB01#	p157
				±0.25pF	GJM0335C1E8R6CB01#	p157
				±0.5pF	GJM0335C1E8R6DB01#	p157
			8.7pF	±0.05pF	GJM0335C1E8R7WB01#	p157
				±0.1pF	GJM0335C1E8R7BB01#	p157
				±0.25pF	GJM0335C1E8R7CB01#	p157
				±0.5pF	GJM0335C1E8R7DB01#	p157
			8.8pF	±0.05pF	GJM0335C1E8R8WB01#	p157
				±0.1pF	GJM0335C1E8R8BB01#	p157
				±0.25pF	GJM0335C1E8R8CB01#	p157
				±0.5pF	GJM0335C1E8R8DB01#	p157
			8.9pF	±0.05pF	GJM0335C1E8R9WB01#	p157
				±0.1pF	GJM0335C1E8R9BB01#	p157
				±0.25pF	GJM0335C1E8R9CB01#	p157
				±0.5pF	GJM0335C1E8R9DB01#	p157
			9.0pF	±0.05pF	GJM0335C1E9R0WB01#	p157
				±0.1pF	GJM0335C1E9R0BB01#	p157
				±0.25pF	GJM0335C1E9R0CB01#	p157
				±0.5pF	GJM0335C1E9R0DB01#	p157
			9.1pF	±0.05pF	GJM0335C1E9R1WB01#	p157
				±0.1pF	GJM0335C1E9R1BB01#	p157
				±0.25pF	GJM0335C1E9R1CB01#	p157
				±0.5pF	GJM0335C1E9R1DB01#	p157
			9.2pF	±0.05pF	GJM0335C1E9R2WB01#	p157
				±0.1pF	GJM0335C1E9R2BB01#	p157
				±0.25pF	GJM0335C1E9R2CB01#	p157
				±0.5pF	GJM0335C1E9R2DB01#	p157
			9.3pF	±0.05pF	GJM0335C1E9R3WB01#	p157
				±0.1pF	GJM0335C1E9R3BB01#	p157
				±0.25pF	GJM0335C1E9R3CB01#	p157
				±0.5pF	GJM0335C1E9R3DB01#	p157
			9.4pF	±0.05pF	GJM0335C1E9R4WB01#	p157
				±0.1pF	GJM0335C1E9R4BB01#	p157
				±0.25pF	GJM0335C1E9R4CB01#	p157
				±0.5pF	GJM0335C1E9R4DB01#	p157
			9.5pF	±0.05pF	GJM0335C1E9R5WB01#	p157
				±0.1pF	GJM0335C1E9R5BB01#	p157
				±0.25pF	GJM0335C1E9R5CB01#	p157
				±0.5pF	GJM0335C1E9R5DB01#	p157
			9.6pF	±0.05pF	GJM0335C1E9R6WB01#	p157
				±0.1pF	GJM0335C1E9R6BB01#	p157
				±0.25pF	GJM0335C1E9R6CB01#	p157
				±0.5pF	GJM0335C1E9R6DB01#	p157
			9.7pF	±0.05pF	GJM0335C1E9R7WB01#	p157
				±0.1pF	GJM0335C1E9R7BB01#	p157
				±0.25pF	GJM0335C1E9R7CB01#	p157
				±0.5pF	GJM0335C1E9R7DB01#	p157
			9.8pF	±0.05pF	GJM0335C1E9R8WB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	C0G	9.8pF	±0.1pF	GJM0335C1E9R8BB01#	p157
				±0.25pF	GJM0335C1E9R8CB01#	p157
				±0.5pF	GJM0335C1E9R8DB01#	p157
			9.9pF	±0.05pF	GJM0335C1E9R9WB01#	p157
				±0.1pF	GJM0335C1E9R9BB01#	p157
				±0.25pF	GJM0335C1E9R9CB01#	p157
				±0.5pF	GJM0335C1E9R9DB01#	p157
			10pF	±2%	GJM0335C1E100GB01#	p157
				±5%	GJM0335C1E100JB01#	p157
			11pF	±2%	GJM0335C1E110GB01#	p157
				±5%	GJM0335C1E110JB01#	p157
			12pF	±2%	GJM0335C1E120GB01#	p157
				±5%	GJM0335C1E120JB01#	p157
			13pF	±2%	GJM0335C1E130GB01#	p157
				±5%	GJM0335C1E130JB01#	p157
			15pF	±2%	GJM0335C1E150GB01#	p157
				±5%	GJM0335C1E150JB01#	p157
			16pF	±2%	GJM0335C1E160GB01#	p157
				±5%	GJM0335C1E160JB01#	p157
			18pF	±2%	GJM0335C1E180GB01#	p157
				±5%	GJM0335C1E180JB01#	p157
			20pF	±2%	GJM0335C1E200GB01#	p157
				±5%	GJM0335C1E200JB01#	p157
			22pF	±2%	GJM0335C1E220GB01#	p157
				±5%	GJM0335C1E220JB01#	p157
			24pF	±2%	GJM0335C1E240GB01#	p157
				±5%	GJM0335C1E240JB01#	p157
			27pF	±2%	GJM0335C1E270GB01#	p157
				±5%	GJM0335C1E270JB01#	p157
			30pF	±2%	GJM0335C1E300GB01#	p157
				±5%	GJM0335C1E300JB01#	p157
			33pF	±2%	GJM0335C1E330GB01#	p157
				±5%	GJM0335C1E330JB01#	p157
		CK	1.0pF	±0.05pF	GJM0334C1E1R0WB01#	p157
				±0.1pF	GJM0334C1E1R0BB01#	p157
				±0.25pF	GJM0334C1E1R0CB01#	p157
			1.1pF	±0.05pF	GJM0334C1E1R1WB01#	p157
				±0.1pF	GJM0334C1E1R1BB01#	p157
				±0.25pF	GJM0334C1E1R1CB01#	p157
			1.2pF	±0.05pF	GJM0334C1E1R2WB01#	p157
				±0.1pF	GJM0334C1E1R2BB01#	p157
				±0.25pF	GJM0334C1E1R2CB01#	p157
			1.3pF	±0.05pF	GJM0334C1E1R3WB01#	p157
				±0.1pF	GJM0334C1E1R3BB01#	p157
				±0.25pF	GJM0334C1E1R3CB01#	p157
			1.4pF	±0.05pF	GJM0334C1E1R4WB01#	p157
				±0.1pF	GJM0334C1E1R4BB01#	p157
				±0.25pF	GJM0334C1E1R4CB01#	p157
			1.5pF	±0.05pF	GJM0334C1E1R5WB01#	p157
				±0.1pF	GJM0334C1E1R5BB01#	p157
				±0.25pF	GJM0334C1E1R5CB01#	p157
			1.6pF	±0.05pF	GJM0334C1E1R6WB01#	p157
				±0.1pF	GJM0334C1E1R6BB01#	p157
				±0.25pF	GJM0334C1E1R6CB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	CK	1.7pF	±0.05pF	GJM0334C1E1R7WB01#	p157
				±0.1pF	GJM0334C1E1R7BB01#	p157
				±0.25pF	GJM0334C1E1R7CB01#	p157
			1.8pF	±0.05pF	GJM0334C1E1R8WB01#	p157
				±0.1pF	GJM0334C1E1R8BB01#	p157
				±0.25pF	GJM0334C1E1R8CB01#	p157
			1.9pF	±0.05pF	GJM0334C1E1R9WB01#	p157
				±0.1pF	GJM0334C1E1R9BB01#	p157
				±0.25pF	GJM0334C1E1R9CB01#	p157
			2.0pF	±0.05pF	GJM0334C1E2R0WB01#	p157
				±0.1pF	GJM0334C1E2R0BB01#	p157
				±0.25pF	GJM0334C1E2R0CB01#	p157
		CJ	2.1pF	±0.05pF	GJM0333C1E2R1WB01#	p157
				±0.1pF	GJM0333C1E2R1BB01#	p157
				±0.25pF	GJM0333C1E2R1CB01#	p157
			2.2pF	±0.05pF	GJM0333C1E2R2WB01#	p157
				±0.1pF	GJM0333C1E2R2BB01#	p157
				±0.25pF	GJM0333C1E2R2CB01#	p157
			2.3pF	±0.05pF	GJM0333C1E2R3WB01#	p157
				±0.1pF	GJM0333C1E2R3BB01#	p157
				±0.25pF	GJM0333C1E2R3CB01#	p157
			2.4pF	±0.05pF	GJM0333C1E2R4WB01#	p157
				±0.1pF	GJM0333C1E2R4BB01#	p157
				±0.25pF	GJM0333C1E2R4CB01#	p157
			2.5pF	±0.05pF	GJM0333C1E2R5WB01#	p157
				±0.1pF	GJM0333C1E2R5BB01#	p157
				±0.25pF	GJM0333C1E2R5CB01#	p157
			2.6pF	±0.05pF	GJM0333C1E2R6WB01#	p157
				±0.1pF	GJM0333C1E2R6BB01#	p157
				±0.25pF	GJM0333C1E2R6CB01#	p157
			2.7pF	±0.05pF	GJM0333C1E2R7WB01#	p157
				±0.1pF	GJM0333C1E2R7BB01#	p157
				±0.25pF	GJM0333C1E2R7CB01#	p157
			2.8pF	±0.05pF	GJM0333C1E2R8WB01#	p157
				±0.1pF	GJM0333C1E2R8BB01#	p157
				±0.25pF	GJM0333C1E2R8CB01#	p157
			2.9pF	±0.05pF	GJM0333C1E2R9WB01#	p157
				±0.1pF	GJM0333C1E2R9BB01#	p157
				±0.25pF	GJM0333C1E2R9CB01#	p157
			3.0pF	±0.05pF	GJM0333C1E3R0WB01#	p157
				±0.1pF	GJM0333C1E3R0BB01#	p157
				±0.25pF	GJM0333C1E3R0CB01#	p157
			3.1pF	±0.05pF	GJM0333C1E3R1WB01#	p157
				±0.1pF	GJM0333C1E3R1BB01#	p157
				±0.25pF	GJM0333C1E3R1CB01#	p157
			3.2pF	±0.05pF	GJM0333C1E3R2WB01#	p157
				±0.1pF	GJM0333C1E3R2BB01#	p157
				±0.25pF	GJM0333C1E3R2CB01#	p157
			3.3pF	±0.05pF	GJM0333C1E3R3WB01#	p157
				±0.1pF	GJM0333C1E3R3BB01#	p157
				±0.25pF	GJM0333C1E3R3CB01#	p157
			3.4pF	±0.05pF	GJM0333C1E3R4WB01#	p157
				±0.1pF	GJM0333C1E3R4BB01#	p157
				±0.25pF	GJM0333C1E3R4CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	CJ	3.5pF	±0.05pF	GJM0333C1E3R5WB01#	p157
				±0.1pF	GJM0333C1E3R5BB01#	p157
				±0.25pF	GJM0333C1E3R5CB01#	p157
			3.6pF	±0.05pF	GJM0333C1E3R6WB01#	p157
				±0.1pF	GJM0333C1E3R6BB01#	p157
				±0.25pF	GJM0333C1E3R6CB01#	p157
			3.7pF	±0.05pF	GJM0333C1E3R7WB01#	p157
				±0.1pF	GJM0333C1E3R7BB01#	p157
				±0.25pF	GJM0333C1E3R7CB01#	p157
			3.8pF	±0.05pF	GJM0333C1E3R8WB01#	p157
				±0.1pF	GJM0333C1E3R8BB01#	p157
				±0.25pF	GJM0333C1E3R8CB01#	p157
			3.9pF	±0.05pF	GJM0333C1E3R9WB01#	p157
				±0.1pF	GJM0333C1E3R9BB01#	p157
				±0.25pF	GJM0333C1E3R9CB01#	p157
		CH	4.0pF	±0.05pF	GJM0332C1E4R0WB01#	p157
				±0.1pF	GJM0332C1E4R0BB01#	p157
				±0.25pF	GJM0332C1E4R0CB01#	p157
			4.1pF	±0.05pF	GJM0332C1E4R1WB01#	p157
				±0.1pF	GJM0332C1E4R1BB01#	p157
				±0.25pF	GJM0332C1E4R1CB01#	p157
			4.2pF	±0.05pF	GJM0332C1E4R2WB01#	p157
				±0.1pF	GJM0332C1E4R2BB01#	p157
				±0.25pF	GJM0332C1E4R2CB01#	p157
			4.3pF	±0.05pF	GJM0332C1E4R3WB01#	p157
				±0.1pF	GJM0332C1E4R3BB01#	p157
				±0.25pF	GJM0332C1E4R3CB01#	p157
			4.4pF	±0.05pF	GJM0332C1E4R4WB01#	p157
				±0.1pF	GJM0332C1E4R4BB01#	p157
				±0.25pF	GJM0332C1E4R4CB01#	p157
			4.5pF	±0.05pF	GJM0332C1E4R5WB01#	p157
				±0.1pF	GJM0332C1E4R5BB01#	p157
				±0.25pF	GJM0332C1E4R5CB01#	p157
			4.6pF	±0.05pF	GJM0332C1E4R6WB01#	p157
				±0.1pF	GJM0332C1E4R6BB01#	p157
				±0.25pF	GJM0332C1E4R6CB01#	p157
			4.7pF	±0.05pF	GJM0332C1E4R7WB01#	p157
				±0.1pF	GJM0332C1E4R7BB01#	p157
				±0.25pF	GJM0332C1E4R7CB01#	p157
			4.8pF	±0.05pF	GJM0332C1E4R8WB01#	p157
				±0.1pF	GJM0332C1E4R8BB01#	p157
				±0.25pF	GJM0332C1E4R8CB01#	p157
			4.9pF	±0.05pF	GJM0332C1E4R9WB01#	p157
				±0.1pF	GJM0332C1E4R9BB01#	p157
				±0.25pF	GJM0332C1E4R9CB01#	p157
			5.0pF	±0.05pF	GJM0332C1E5R0WB01#	p157
				±0.1pF	GJM0332C1E5R0BB01#	p157
				±0.25pF	GJM0332C1E5R0CB01#	p157
			5.1pF	±0.05pF	GJM0332C1E5R1WB01#	p157
				±0.1pF	GJM0332C1E5R1BB01#	p157
				±0.25pF	GJM0332C1E5R1CB01#	p157
				±0.5pF	GJM0332C1E5R1DB01#	p157
			5.2pF	±0.05pF	GJM0332C1E5R2WB01#	p157
				±0.1pF	GJM0332C1E5R2BB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	CH	5.2pF	±0.25pF	GJM0332C1E5R2CB01#	p157
				±0.5pF	GJM0332C1E5R2DB01#	p157
			5.3pF	±0.05pF	GJM0332C1E5R3WB01#	p157
				±0.1pF	GJM0332C1E5R3BB01#	p157
				±0.25pF	GJM0332C1E5R3CB01#	p157
				±0.5pF	GJM0332C1E5R3DB01#	p157
			5.4pF	±0.05pF	GJM0332C1E5R4WB01#	p157
				±0.1pF	GJM0332C1E5R4BB01#	p157
				±0.25pF	GJM0332C1E5R4CB01#	p157
				±0.5pF	GJM0332C1E5R4DB01#	p157
			5.5pF	±0.05pF	GJM0332C1E5R5WB01#	p157
				±0.1pF	GJM0332C1E5R5BB01#	p157
				±0.25pF	GJM0332C1E5R5CB01#	p157
				±0.5pF	GJM0332C1E5R5DB01#	p157
			5.6pF	±0.05pF	GJM0332C1E5R6WB01#	p157
				±0.1pF	GJM0332C1E5R6BB01#	p157
				±0.25pF	GJM0332C1E5R6CB01#	p157
				±0.5pF	GJM0332C1E5R6DB01#	p157
			5.7pF	±0.05pF	GJM0332C1E5R7WB01#	p157
				±0.1pF	GJM0332C1E5R7BB01#	p157
				±0.25pF	GJM0332C1E5R7CB01#	p157
				±0.5pF	GJM0332C1E5R7DB01#	p157
			5.8pF	±0.05pF	GJM0332C1E5R8WB01#	p157
				±0.1pF	GJM0332C1E5R8BB01#	p157
				±0.25pF	GJM0332C1E5R8CB01#	p157
				±0.5pF	GJM0332C1E5R8DB01#	p157
			5.9pF	±0.05pF	GJM0332C1E5R9WB01#	p157
				±0.1pF	GJM0332C1E5R9BB01#	p157
				±0.25pF	GJM0332C1E5R9CB01#	p157
				±0.5pF	GJM0332C1E5R9DB01#	p157
			6.0pF	±0.05pF	GJM0332C1E6R0WB01#	p157
				±0.1pF	GJM0332C1E6R0BB01#	p157
				±0.25pF	GJM0332C1E6R0CB01#	p157
				±0.5pF	GJM0332C1E6R0DB01#	p157
			6.1pF	±0.05pF	GJM0332C1E6R1WB01#	p157
				±0.1pF	GJM0332C1E6R1BB01#	p157
				±0.25pF	GJM0332C1E6R1CB01#	p157
				±0.5pF	GJM0332C1E6R1DB01#	p157
			6.2pF	±0.05pF	GJM0332C1E6R2WB01#	p157
				±0.1pF	GJM0332C1E6R2BB01#	p157
				±0.25pF	GJM0332C1E6R2CB01#	p157
				±0.5pF	GJM0332C1E6R2DB01#	p157
			6.3pF	±0.05pF	GJM0332C1E6R3WB01#	p157
				±0.1pF	GJM0332C1E6R3BB01#	p157
				±0.25pF	GJM0332C1E6R3CB01#	p157
				±0.5pF	GJM0332C1E6R3DB01#	p157
			6.4pF	±0.05pF	GJM0332C1E6R4WB01#	p157
				±0.1pF	GJM0332C1E6R4BB01#	p157
				±0.25pF	GJM0332C1E6R4CB01#	p157
				±0.5pF	GJM0332C1E6R4DB01#	p157
			6.5pF	±0.05pF	GJM0332C1E6R5WB01#	p157
				±0.1pF	GJM0332C1E6R5BB01#	p157
				±0.25pF	GJM0332C1E6R5CB01#	p157
				±0.5pF	GJM0332C1E6R5DB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	CH	6.6pF	±0.05pF	GJM0332C1E6R6WB01#	p157
				±0.1pF	GJM0332C1E6R6BB01#	p157
				±0.25pF	GJM0332C1E6R6CB01#	p157
				±0.5pF	GJM0332C1E6R6DB01#	p157
			6.7pF	±0.05pF	GJM0332C1E6R7WB01#	p157
				±0.1pF	GJM0332C1E6R7BB01#	p157
				±0.25pF	GJM0332C1E6R7CB01#	p157
				±0.5pF	GJM0332C1E6R7DB01#	p157
			6.8pF	±0.05pF	GJM0332C1E6R8WB01#	p157
				±0.1pF	GJM0332C1E6R8BB01#	p157
				±0.25pF	GJM0332C1E6R8CB01#	p157
				±0.5pF	GJM0332C1E6R8DB01#	p157
			6.9pF	±0.05pF	GJM0332C1E6R9WB01#	p157
				±0.1pF	GJM0332C1E6R9BB01#	p157
				±0.25pF	GJM0332C1E6R9CB01#	p157
				±0.5pF	GJM0332C1E6R9DB01#	p157
			7.0pF	±0.05pF	GJM0332C1E7R0WB01#	p157
				±0.1pF	GJM0332C1E7R0BB01#	p157
				±0.25pF	GJM0332C1E7R0CB01#	p157
				±0.5pF	GJM0332C1E7R0DB01#	p157
			7.1pF	±0.05pF	GJM0332C1E7R1WB01#	p157
				±0.1pF	GJM0332C1E7R1BB01#	p157
				±0.25pF	GJM0332C1E7R1CB01#	p157
				±0.5pF	GJM0332C1E7R1DB01#	p157
			7.2pF	±0.05pF	GJM0332C1E7R2WB01#	p157
				±0.1pF	GJM0332C1E7R2BB01#	p157
				±0.25pF	GJM0332C1E7R2CB01#	p157
				±0.5pF	GJM0332C1E7R2DB01#	p157
			7.3pF	±0.05pF	GJM0332C1E7R3WB01#	p157
				±0.1pF	GJM0332C1E7R3BB01#	p157
				±0.25pF	GJM0332C1E7R3CB01#	p157
				±0.5pF	GJM0332C1E7R3DB01#	p157
			7.4pF	±0.05pF	GJM0332C1E7R4WB01#	p157
				±0.1pF	GJM0332C1E7R4BB01#	p157
				±0.25pF	GJM0332C1E7R4CB01#	p157
				±0.5pF	GJM0332C1E7R4DB01#	p157
			7.5pF	±0.05pF	GJM0332C1E7R5WB01#	p157
				±0.1pF	GJM0332C1E7R5BB01#	p157
				±0.25pF	GJM0332C1E7R5CB01#	p157
				±0.5pF	GJM0332C1E7R5DB01#	p157
			7.6pF	±0.05pF	GJM0332C1E7R6WB01#	p157
				±0.1pF	GJM0332C1E7R6BB01#	p157
				±0.25pF	GJM0332C1E7R6CB01#	p157
				±0.5pF	GJM0332C1E7R6DB01#	p157
			7.7pF	±0.05pF	GJM0332C1E7R7WB01#	p157
				±0.1pF	GJM0332C1E7R7BB01#	p157
				±0.25pF	GJM0332C1E7R7CB01#	p157
				±0.5pF	GJM0332C1E7R7DB01#	p157
			7.8pF	±0.05pF	GJM0332C1E7R8WB01#	p157
				±0.1pF	GJM0332C1E7R8BB01#	p157
				±0.25pF	GJM0332C1E7R8CB01#	p157
				±0.5pF	GJM0332C1E7R8DB01#	p157
			7.9pF	±0.05pF	GJM0332C1E7R9WB01#	p157
				±0.1pF	GJM0332C1E7R9BB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	CH	7.9pF	±0.25pF	GJM0332C1E7R9CB01#	p157
				±0.5pF	GJM0332C1E7R9DB01#	p157
			8.0pF	±0.05pF	GJM0332C1E8R0WB01#	p157
				±0.1pF	GJM0332C1E8R0BB01#	p157
				±0.25pF	GJM0332C1E8R0CB01#	p157
				±0.5pF	GJM0332C1E8R0DB01#	p157
			8.1pF	±0.05pF	GJM0332C1E8R1WB01#	p157
				±0.1pF	GJM0332C1E8R1BB01#	p157
				±0.25pF	GJM0332C1E8R1CB01#	p157
				±0.5pF	GJM0332C1E8R1DB01#	p157
			8.2pF	±0.05pF	GJM0332C1E8R2WB01#	p157
				±0.1pF	GJM0332C1E8R2BB01#	p157
				±0.25pF	GJM0332C1E8R2CB01#	p157
				±0.5pF	GJM0332C1E8R2DB01#	p157
			8.3pF	±0.05pF	GJM0332C1E8R3WB01#	p157
				±0.1pF	GJM0332C1E8R3BB01#	p157
				±0.25pF	GJM0332C1E8R3CB01#	p157
				±0.5pF	GJM0332C1E8R3DB01#	p157
			8.4pF	±0.05pF	GJM0332C1E8R4WB01#	p157
				±0.1pF	GJM0332C1E8R4BB01#	p157
				±0.25pF	GJM0332C1E8R4CB01#	p157
				±0.5pF	GJM0332C1E8R4DB01#	p157
			8.5pF	±0.05pF	GJM0332C1E8R5WB01#	p157
				±0.1pF	GJM0332C1E8R5BB01#	p157
				±0.25pF	GJM0332C1E8R5CB01#	p157
				±0.5pF	GJM0332C1E8R5DB01#	p157
			8.6pF	±0.05pF	GJM0332C1E8R6WB01#	p157
				±0.1pF	GJM0332C1E8R6BB01#	p157
				±0.25pF	GJM0332C1E8R6CB01#	p157
				±0.5pF	GJM0332C1E8R6DB01#	p157
			8.7pF	±0.05pF	GJM0332C1E8R7WB01#	p157
				±0.1pF	GJM0332C1E8R7BB01#	p157
				±0.25pF	GJM0332C1E8R7CB01#	p157
				±0.5pF	GJM0332C1E8R7DB01#	p157
			8.8pF	±0.05pF	GJM0332C1E8R8WB01#	p157
				±0.1pF	GJM0332C1E8R8BB01#	p157
				±0.25pF	GJM0332C1E8R8CB01#	p157
				±0.5pF	GJM0332C1E8R8DB01#	p157
			8.9pF	±0.05pF	GJM0332C1E8R9WB01#	p157
				±0.1pF	GJM0332C1E8R9BB01#	p157
				±0.25pF	GJM0332C1E8R9CB01#	p157
				±0.5pF	GJM0332C1E8R9DB01#	p157
			9.0pF	±0.05pF	GJM0332C1E9R0WB01#	p157
				±0.1pF	GJM0332C1E9R0BB01#	p157
				±0.25pF	GJM0332C1E9R0CB01#	p157
				±0.5pF	GJM0332C1E9R0DB01#	p157
			9.1pF	±0.05pF	GJM0332C1E9R1WB01#	p157
				±0.1pF	GJM0332C1E9R1BB01#	p157
				±0.25pF	GJM0332C1E9R1CB01#	p157
				±0.5pF	GJM0332C1E9R1DB01#	p157
			9.2pF	±0.05pF	GJM0332C1E9R2WB01#	p157
				±0.1pF	GJM0332C1E9R2BB01#	p157
				±0.25pF	GJM0332C1E9R2CB01#	p157
				±0.5pF	GJM0332C1E9R2DB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 0.6×0.3mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	CH	9.3pF	±0.05pF	GJM0332C1E9R3WB01#	p157
				±0.1pF	GJM0332C1E9R3BB01#	p157
				±0.25pF	GJM0332C1E9R3CB01#	p157
				±0.5pF	GJM0332C1E9R3DB01#	p157
			9.4pF	±0.05pF	GJM0332C1E9R4WB01#	p157
				±0.1pF	GJM0332C1E9R4BB01#	p157
				±0.25pF	GJM0332C1E9R4CB01#	p157
				±0.5pF	GJM0332C1E9R4DB01#	p157
			9.5pF	±0.05pF	GJM0332C1E9R5WB01#	p157
				±0.1pF	GJM0332C1E9R5BB01#	p157
				±0.25pF	GJM0332C1E9R5CB01#	p157
				±0.5pF	GJM0332C1E9R5DB01#	p157
			9.6pF	±0.05pF	GJM0332C1E9R6WB01#	p157
				±0.1pF	GJM0332C1E9R6BB01#	p157
				±0.25pF	GJM0332C1E9R6CB01#	p157
				±0.5pF	GJM0332C1E9R6DB01#	p157
			9.7pF	±0.05pF	GJM0332C1E9R7WB01#	p157
				±0.1pF	GJM0332C1E9R7BB01#	p157
				±0.25pF	GJM0332C1E9R7CB01#	p157
				±0.5pF	GJM0332C1E9R7DB01#	p157
			9.8pF	±0.05pF	GJM0332C1E9R8WB01#	p157
				±0.1pF	GJM0332C1E9R8BB01#	p157
				±0.25pF	GJM0332C1E9R8CB01#	p157
				±0.5pF	GJM0332C1E9R8DB01#	p157
			9.9pF	±0.05pF	GJM0332C1E9R9WB01#	p157
				±0.1pF	GJM0332C1E9R9BB01#	p157
				±0.25pF	GJM0332C1E9R9CB01#	p157
				±0.5pF	GJM0332C1E9R9DB01#	p157
			10pF	±2%	GJM0332C1E100GB01#	p157
				±5%	GJM0332C1E100JB01#	p157
			11pF	±2%	GJM0332C1E110GB01#	p157
				±5%	GJM0332C1E110JB01#	p157
			12pF	±2%	GJM0332C1E120GB01#	p157
				±5%	GJM0332C1E120JB01#	p157
			13pF	±2%	GJM0332C1E130GB01#	p157
				±5%	GJM0332C1E130JB01#	p157
			15pF	±2%	GJM0332C1E150GB01#	p157
				±5%	GJM0332C1E150JB01#	p157
			16pF	±2%	GJM0332C1E160GB01#	p157
				±5%	GJM0332C1E160JB01#	p157
			18pF	±2%	GJM0332C1E180GB01#	p157
				±5%	GJM0332C1E180JB01#	p157
			20pF	±2%	GJM0332C1E200GB01#	p157
				±5%	GJM0332C1E200JB01#	p157
			22pF	±2%	GJM0332C1E220GB01#	p157
				±5%	GJM0332C1E220JB01#	p157
			24pF	±2%	GJM0332C1E240GB01#	p157
				±5%	GJM0332C1E240JB01#	p157
			27pF	±2%	GJM0332C1E270GB01#	p157
				±5%	GJM0332C1E270JB01#	p157
			30pF	±2%	GJM0332C1E300GB01#	p157
				±5%	GJM0332C1E300JB01#	p157
			33pF	±2%	GJM0332C1E330GB01#	p157
				±5%	GJM0332C1E330JB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

1.0×0.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	0.10pF	±0.05pF	GJM1555C1HR10WB01#	p157
				±0.1pF	GJM1555C1HR10BB01#	p157
			0.20pF	±0.05pF	GJM1555C1HR20WB01#	p157
				±0.1pF	GJM1555C1HR20BB01#	p157
			0.30pF	±0.05pF	GJM1555C1HR30WB01#	p157
				±0.1pF	GJM1555C1HR30BB01#	p157
			0.40pF	±0.05pF	GJM1555C1HR40WB01#	p157
				±0.1pF	GJM1555C1HR40BB01#	p157
			0.50pF	±0.05pF	GJM1555C1HR50WB01#	p157
				±0.1pF	GJM1555C1HR50BB01#	p157
			0.60pF	±0.05pF	GJM1555C1HR60WB01#	p157
				±0.1pF	GJM1555C1HR60BB01#	p157
			0.70pF	±0.05pF	GJM1555C1HR70WB01#	p157
				±0.1pF	GJM1555C1HR70BB01#	p157
			0.80pF	±0.05pF	GJM1555C1HR80WB01#	p157
				±0.1pF	GJM1555C1HR80BB01#	p157
			0.90pF	±0.05pF	GJM1555C1HR90WB01#	p157
				±0.1pF	GJM1555C1HR90BB01#	p157
			1.0pF	±0.05pF	GJM1555C1H1R0WB01#	p157
				±0.1pF	GJM1555C1H1R0BB01#	p157
				±0.25pF	GJM1555C1H1R0CB01#	p157
			1.1pF	±0.05pF	GJM1555C1H1R1WB01#	p157
				±0.1pF	GJM1555C1H1R1BB01#	p157
				±0.25pF	GJM1555C1H1R1CB01#	p157
			1.2pF	±0.05pF	GJM1555C1H1R2WB01#	p157
				±0.1pF	GJM1555C1H1R2BB01#	p157
				±0.25pF	GJM1555C1H1R2CB01#	p157
			1.3pF	±0.05pF	GJM1555C1H1R3WB01#	p157
				±0.1pF	GJM1555C1H1R3BB01#	p157
				±0.25pF	GJM1555C1H1R3CB01#	p157
			1.4pF	±0.05pF	GJM1555C1H1R4WB01#	p157
				±0.1pF	GJM1555C1H1R4BB01#	p157
				±0.25pF	GJM1555C1H1R4CB01#	p157
			1.5pF	±0.05pF	GJM1555C1H1R5WB01#	p157
				±0.1pF	GJM1555C1H1R5BB01#	p157
				±0.25pF	GJM1555C1H1R5CB01#	p157
			1.6pF	±0.05pF	GJM1555C1H1R6WB01#	p157
				±0.1pF	GJM1555C1H1R6BB01#	p157
				±0.25pF	GJM1555C1H1R6CB01#	p157
			1.7pF	±0.05pF	GJM1555C1H1R7WB01#	p157
				±0.1pF	GJM1555C1H1R7BB01#	p157
				±0.25pF	GJM1555C1H1R7CB01#	p157
			1.8pF	±0.05pF	GJM1555C1H1R8WB01#	p157
				±0.1pF	GJM1555C1H1R8BB01#	p157
				±0.25pF	GJM1555C1H1R8CB01#	p157
			1.9pF	±0.05pF	GJM1555C1H1R9WB01#	p157
				±0.1pF	GJM1555C1H1R9BB01#	p157
				±0.25pF	GJM1555C1H1R9CB01#	p157
			2.0pF	±0.05pF	GJM1555C1H2R0WB01#	p157
				±0.1pF	GJM1555C1H2R0BB01#	p157
				±0.25pF	GJM1555C1H2R0CB01#	p157
			2.1pF	±0.05pF	GJM1555C1H2R1WB01#	p157

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	2.1pF	±0.1pF	GJM1555C1H2R1BB01#	p157
				±0.25pF	GJM1555C1H2R1CB01#	p157
			2.2pF	±0.05pF	GJM1555C1H2R2WB01#	p157
				±0.1pF	GJM1555C1H2R2BB01#	p157
				±0.25pF	GJM1555C1H2R2CB01#	p157
			2.3pF	±0.05pF	GJM1555C1H2R3WB01#	p157
				±0.1pF	GJM1555C1H2R3BB01#	p157
				±0.25pF	GJM1555C1H2R3CB01#	p157
			2.4pF	±0.05pF	GJM1555C1H2R4WB01#	p157
				±0.1pF	GJM1555C1H2R4BB01#	p157
				±0.25pF	GJM1555C1H2R4CB01#	p157
			2.5pF	±0.05pF	GJM1555C1H2R5WB01#	p157
				±0.1pF	GJM1555C1H2R5BB01#	p157
				±0.25pF	GJM1555C1H2R5CB01#	p157
			2.6pF	±0.05pF	GJM1555C1H2R6WB01#	p157
				±0.1pF	GJM1555C1H2R6BB01#	p157
				±0.25pF	GJM1555C1H2R6CB01#	p157
			2.7pF	±0.05pF	GJM1555C1H2R7WB01#	p157
				±0.1pF	GJM1555C1H2R7BB01#	p157
				±0.25pF	GJM1555C1H2R7CB01#	p157
			2.8pF	±0.05pF	GJM1555C1H2R8WB01#	p157
				±0.1pF	GJM1555C1H2R8BB01#	p157
				±0.25pF	GJM1555C1H2R8CB01#	p157
			2.9pF	±0.05pF	GJM1555C1H2R9WB01#	p157
				±0.1pF	GJM1555C1H2R9BB01#	p157
				±0.25pF	GJM1555C1H2R9CB01#	p157
			3.0pF	±0.05pF	GJM1555C1H3R0WB01#	p157
				±0.1pF	GJM1555C1H3R0BB01#	p157
				±0.25pF	GJM1555C1H3R0CB01#	p157
			3.1pF	±0.05pF	GJM1555C1H3R1WB01#	p157
				±0.1pF	GJM1555C1H3R1BB01#	p157
				±0.25pF	GJM1555C1H3R1CB01#	p157
			3.2pF	±0.05pF	GJM1555C1H3R2WB01#	p157
				±0.1pF	GJM1555C1H3R2BB01#	p157
				±0.25pF	GJM1555C1H3R2CB01#	p157
			3.3pF	±0.05pF	GJM1555C1H3R3WB01#	p157
				±0.1pF	GJM1555C1H3R3BB01#	p157
				±0.25pF	GJM1555C1H3R3CB01#	p157
			3.4pF	±0.05pF	GJM1555C1H3R4WB01#	p157
				±0.1pF	GJM1555C1H3R4BB01#	p157
				±0.25pF	GJM1555C1H3R4CB01#	p157
			3.5pF	±0.05pF	GJM1555C1H3R5WB01#	p157
				±0.1pF	GJM1555C1H3R5BB01#	p157
				±0.25pF	GJM1555C1H3R5CB01#	p157
			3.6pF	±0.05pF	GJM1555C1H3R6WB01#	p157
				±0.1pF	GJM1555C1H3R6BB01#	p157
				±0.25pF	GJM1555C1H3R6CB01#	p157
			3.7pF	±0.05pF	GJM1555C1H3R7WB01#	p157
				±0.1pF	GJM1555C1H3R7BB01#	p157
				±0.25pF	GJM1555C1H3R7CB01#	p157
			3.8pF	±0.05pF	GJM1555C1H3R8WB01#	p157
				±0.1pF	GJM1555C1H3R8BB01#	p157
				±0.25pF	GJM1555C1H3R8CB01#	p157
			3.9pF	±0.05pF	GJM1555C1H3R9WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	3.9pF	±0.1pF	GJM1555C1H3R9BB01#	p157
				±0.25pF	GJM1555C1H3R9CB01#	p157
			4.0pF	±0.05pF	GJM1555C1H4R0WB01#	p157
				±0.1pF	GJM1555C1H4R0BB01#	p157
				±0.25pF	GJM1555C1H4R0CB01#	p157
			4.1pF	±0.05pF	GJM1555C1H4R1WB01#	p157
				±0.1pF	GJM1555C1H4R1BB01#	p157
				±0.25pF	GJM1555C1H4R1CB01#	p157
			4.2pF	±0.05pF	GJM1555C1H4R2WB01#	p157
				±0.1pF	GJM1555C1H4R2BB01#	p157
				±0.25pF	GJM1555C1H4R2CB01#	p157
			4.3pF	±0.05pF	GJM1555C1H4R3WB01#	p157
				±0.1pF	GJM1555C1H4R3BB01#	p157
				±0.25pF	GJM1555C1H4R3CB01#	p157
			4.4pF	±0.05pF	GJM1555C1H4R4WB01#	p157
				±0.1pF	GJM1555C1H4R4BB01#	p157
				±0.25pF	GJM1555C1H4R4CB01#	p157
			4.5pF	±0.05pF	GJM1555C1H4R5WB01#	p157
				±0.1pF	GJM1555C1H4R5BB01#	p157
				±0.25pF	GJM1555C1H4R5CB01#	p157
			4.6pF	±0.05pF	GJM1555C1H4R6WB01#	p157
				±0.1pF	GJM1555C1H4R6BB01#	p157
				±0.25pF	GJM1555C1H4R6CB01#	p157
			4.7pF	±0.05pF	GJM1555C1H4R7WB01#	p157
				±0.1pF	GJM1555C1H4R7BB01#	p157
				±0.25pF	GJM1555C1H4R7CB01#	p157
			4.8pF	±0.05pF	GJM1555C1H4R8WB01#	p157
				±0.1pF	GJM1555C1H4R8BB01#	p157
				±0.25pF	GJM1555C1H4R8CB01#	p157
			4.9pF	±0.05pF	GJM1555C1H4R9WB01#	p157
				±0.1pF	GJM1555C1H4R9BB01#	p157
				±0.25pF	GJM1555C1H4R9CB01#	p157
			5.0pF	±0.05pF	GJM1555C1H5R0WB01#	p157
				±0.1pF	GJM1555C1H5R0BB01#	p157
				±0.25pF	GJM1555C1H5R0CB01#	p157
			5.1pF	±0.05pF	GJM1555C1H5R1WB01#	p157
				±0.1pF	GJM1555C1H5R1BB01#	p157
				±0.25pF	GJM1555C1H5R1CB01#	p157
				±0.5pF	GJM1555C1H5R1DB01#	p157
			5.2pF	±0.05pF	GJM1555C1H5R2WB01#	p157
				±0.1pF	GJM1555C1H5R2BB01#	p157
				±0.25pF	GJM1555C1H5R2CB01#	p157
				±0.5pF	GJM1555C1H5R2DB01#	p157
			5.3pF	±0.05pF	GJM1555C1H5R3WB01#	p157
				±0.1pF	GJM1555C1H5R3BB01#	p157
				±0.25pF	GJM1555C1H5R3CB01#	p157
				±0.5pF	GJM1555C1H5R3DB01#	p157
			5.4pF	±0.05pF	GJM1555C1H5R4WB01#	p157
				±0.1pF	GJM1555C1H5R4BB01#	p157
				±0.25pF	GJM1555C1H5R4CB01#	p157
				±0.5pF	GJM1555C1H5R4DB01#	p157
			5.5pF	±0.05pF	GJM1555C1H5R5WB01#	p157
				±0.1pF	GJM1555C1H5R5BB01#	p157
				±0.25pF	GJM1555C1H5R5CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	5.5pF	±0.5pF	GJM1555C1H5R5DB01#	p157
			5.6pF	±0.05pF	GJM1555C1H5R6WB01#	p157
				±0.1pF	GJM1555C1H5R6BB01#	p157
				±0.25pF	GJM1555C1H5R6CB01#	p157
				±0.5pF	GJM1555C1H5R6DB01#	p157
			5.7pF	±0.05pF	GJM1555C1H5R7WB01#	p157
				±0.1pF	GJM1555C1H5R7BB01#	p157
				±0.25pF	GJM1555C1H5R7CB01#	p157
				±0.5pF	GJM1555C1H5R7DB01#	p157
			5.8pF	±0.05pF	GJM1555C1H5R8WB01#	p157
				±0.1pF	GJM1555C1H5R8BB01#	p157
				±0.25pF	GJM1555C1H5R8CB01#	p157
				±0.5pF	GJM1555C1H5R8DB01#	p157
			5.9pF	±0.05pF	GJM1555C1H5R9WB01#	p157
				±0.1pF	GJM1555C1H5R9BB01#	p157
				±0.25pF	GJM1555C1H5R9CB01#	p157
				±0.5pF	GJM1555C1H5R9DB01#	p157
			6.0pF	±0.05pF	GJM1555C1H6R0WB01#	p157
				±0.1pF	GJM1555C1H6R0BB01#	p157
				±0.25pF	GJM1555C1H6R0CB01#	p157
				±0.5pF	GJM1555C1H6R0DB01#	p157
			6.1pF	±0.05pF	GJM1555C1H6R1WB01#	p157
				±0.1pF	GJM1555C1H6R1BB01#	p157
				±0.25pF	GJM1555C1H6R1CB01#	p157
				±0.5pF	GJM1555C1H6R1DB01#	p157
			6.2pF	±0.05pF	GJM1555C1H6R2WB01#	p157
				±0.1pF	GJM1555C1H6R2BB01#	p157
				±0.25pF	GJM1555C1H6R2CB01#	p157
				±0.5pF	GJM1555C1H6R2DB01#	p157
			6.3pF	±0.05pF	GJM1555C1H6R3WB01#	p157
				±0.1pF	GJM1555C1H6R3BB01#	p157
				±0.25pF	GJM1555C1H6R3CB01#	p157
				±0.5pF	GJM1555C1H6R3DB01#	p157
			6.4pF	±0.05pF	GJM1555C1H6R4WB01#	p157
				±0.1pF	GJM1555C1H6R4BB01#	p157
				±0.25pF	GJM1555C1H6R4CB01#	p157
				±0.5pF	GJM1555C1H6R4DB01#	p157
			6.5pF	±0.05pF	GJM1555C1H6R5WB01#	p157
				±0.1pF	GJM1555C1H6R5BB01#	p157
				±0.25pF	GJM1555C1H6R5CB01#	p157
				±0.5pF	GJM1555C1H6R5DB01#	p157
			6.6pF	±0.05pF	GJM1555C1H6R6WB01#	p157
				±0.1pF	GJM1555C1H6R6BB01#	p157
				±0.25pF	GJM1555C1H6R6CB01#	p157
				±0.5pF	GJM1555C1H6R6DB01#	p157
			6.7pF	±0.05pF	GJM1555C1H6R7WB01#	p157
				±0.1pF	GJM1555C1H6R7BB01#	p157
				±0.25pF	GJM1555C1H6R7CB01#	p157
				±0.5pF	GJM1555C1H6R7DB01#	p157
			6.8pF	±0.05pF	GJM1555C1H6R8WB01#	p157
				±0.1pF	GJM1555C1H6R8BB01#	p157
				±0.25pF	GJM1555C1H6R8CB01#	p157
				±0.5pF	GJM1555C1H6R8DB01#	p157
			6.9pF	±0.05pF	GJM1555C1H6R9WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	6.9pF	±0.1pF	GJM1555C1H6R9BB01#	p157
				±0.25pF	GJM1555C1H6R9CB01#	p157
				±0.5pF	GJM1555C1H6R9DB01#	p157
			7.0pF	±0.05pF	GJM1555C1H7R0WB01#	p157
				±0.1pF	GJM1555C1H7R0BB01#	p157
				±0.25pF	GJM1555C1H7R0CB01#	p157
				±0.5pF	GJM1555C1H7R0DB01#	p157
			7.1pF	±0.05pF	GJM1555C1H7R1WB01#	p157
				±0.1pF	GJM1555C1H7R1BB01#	p157
				±0.25pF	GJM1555C1H7R1CB01#	p157
				±0.5pF	GJM1555C1H7R1DB01#	p157
			7.2pF	±0.05pF	GJM1555C1H7R2WB01#	p157
				±0.1pF	GJM1555C1H7R2BB01#	p157
				±0.25pF	GJM1555C1H7R2CB01#	p157
				±0.5pF	GJM1555C1H7R2DB01#	p157
			7.3pF	±0.05pF	GJM1555C1H7R3WB01#	p157
				±0.1pF	GJM1555C1H7R3BB01#	p157
				±0.25pF	GJM1555C1H7R3CB01#	p157
				±0.5pF	GJM1555C1H7R3DB01#	p157
			7.4pF	±0.05pF	GJM1555C1H7R4WB01#	p157
				±0.1pF	GJM1555C1H7R4BB01#	p157
				±0.25pF	GJM1555C1H7R4CB01#	p157
				±0.5pF	GJM1555C1H7R4DB01#	p157
			7.5pF	±0.05pF	GJM1555C1H7R5WB01#	p157
				±0.1pF	GJM1555C1H7R5BB01#	p157
				±0.25pF	GJM1555C1H7R5CB01#	p157
				±0.5pF	GJM1555C1H7R5DB01#	p157
			7.6pF	±0.05pF	GJM1555C1H7R6WB01#	p157
				±0.1pF	GJM1555C1H7R6BB01#	p157
				±0.25pF	GJM1555C1H7R6CB01#	p157
				±0.5pF	GJM1555C1H7R6DB01#	p157
			7.7pF	±0.05pF	GJM1555C1H7R7WB01#	p157
				±0.1pF	GJM1555C1H7R7BB01#	p157
				±0.25pF	GJM1555C1H7R7CB01#	p157
				±0.5pF	GJM1555C1H7R7DB01#	p157
			7.8pF	±0.05pF	GJM1555C1H7R8WB01#	p157
				±0.1pF	GJM1555C1H7R8BB01#	p157
				±0.25pF	GJM1555C1H7R8CB01#	p157
				±0.5pF	GJM1555C1H7R8DB01#	p157
			7.9pF	±0.05pF	GJM1555C1H7R9WB01#	p157
				±0.1pF	GJM1555C1H7R9BB01#	p157
				±0.25pF	GJM1555C1H7R9CB01#	p157
				±0.5pF	GJM1555C1H7R9DB01#	p157
			8.0pF	±0.05pF	GJM1555C1H8R0WB01#	p157
				±0.1pF	GJM1555C1H8R0BB01#	p157
				±0.25pF	GJM1555C1H8R0CB01#	p157
				±0.5pF	GJM1555C1H8R0DB01#	p157
			8.1pF	±0.05pF	GJM1555C1H8R1WB01#	p157
				±0.1pF	GJM1555C1H8R1BB01#	p157
				±0.25pF	GJM1555C1H8R1CB01#	p157
				±0.5pF	GJM1555C1H8R1DB01#	p157
			8.2pF	±0.05pF	GJM1555C1H8R2WB01#	p157
				±0.1pF	GJM1555C1H8R2BB01#	p157
				±0.25pF	GJM1555C1H8R2CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	8.2pF	±0.5pF	GJM1555C1H8R2DB01#	p157
			8.3pF	±0.05pF	GJM1555C1H8R3WB01#	p157
				±0.1pF	GJM1555C1H8R3BB01#	p157
				±0.25pF	GJM1555C1H8R3CB01#	p157
				±0.5pF	GJM1555C1H8R3DB01#	p157
			8.4pF	±0.05pF	GJM1555C1H8R4WB01#	p157
				±0.1pF	GJM1555C1H8R4BB01#	p157
				±0.25pF	GJM1555C1H8R4CB01#	p157
				±0.5pF	GJM1555C1H8R4DB01#	p157
			8.5pF	±0.05pF	GJM1555C1H8R5WB01#	p157
				±0.1pF	GJM1555C1H8R5BB01#	p157
				±0.25pF	GJM1555C1H8R5CB01#	p157
				±0.5pF	GJM1555C1H8R5DB01#	p157
			8.6pF	±0.05pF	GJM1555C1H8R6WB01#	p157
				±0.1pF	GJM1555C1H8R6BB01#	p157
				±0.25pF	GJM1555C1H8R6CB01#	p157
				±0.5pF	GJM1555C1H8R6DB01#	p157
			8.7pF	±0.05pF	GJM1555C1H8R7WB01#	p157
				±0.1pF	GJM1555C1H8R7BB01#	p157
				±0.25pF	GJM1555C1H8R7CB01#	p157
				±0.5pF	GJM1555C1H8R7DB01#	p157
			8.8pF	±0.05pF	GJM1555C1H8R8WB01#	p157
				±0.1pF	GJM1555C1H8R8BB01#	p157
				±0.25pF	GJM1555C1H8R8CB01#	p157
				±0.5pF	GJM1555C1H8R8DB01#	p157
			8.9pF	±0.05pF	GJM1555C1H8R9WB01#	p157
				±0.1pF	GJM1555C1H8R9BB01#	p157
				±0.25pF	GJM1555C1H8R9CB01#	p157
				±0.5pF	GJM1555C1H8R9DB01#	p157
			9.0pF	±0.05pF	GJM1555C1H9R0WB01#	p157
				±0.1pF	GJM1555C1H9R0BB01#	p157
				±0.25pF	GJM1555C1H9R0CB01#	p157
				±0.5pF	GJM1555C1H9R0DB01#	p157
			9.1pF	±0.05pF	GJM1555C1H9R1WB01#	p157
				±0.1pF	GJM1555C1H9R1BB01#	p157
				±0.25pF	GJM1555C1H9R1CB01#	p157
				±0.5pF	GJM1555C1H9R1DB01#	p157
			9.2pF	±0.05pF	GJM1555C1H9R2WB01#	p157
				±0.1pF	GJM1555C1H9R2BB01#	p157
				±0.25pF	GJM1555C1H9R2CB01#	p157
				±0.5pF	GJM1555C1H9R2DB01#	p157
			9.3pF	±0.05pF	GJM1555C1H9R3WB01#	p157
				±0.1pF	GJM1555C1H9R3BB01#	p157
				±0.25pF	GJM1555C1H9R3CB01#	p157
				±0.5pF	GJM1555C1H9R3DB01#	p157
			9.4pF	±0.05pF	GJM1555C1H9R4WB01#	p157
				±0.1pF	GJM1555C1H9R4BB01#	p157
				±0.25pF	GJM1555C1H9R4CB01#	p157
				±0.5pF	GJM1555C1H9R4DB01#	p157
			9.5pF	±0.05pF	GJM1555C1H9R5WB01#	p157
				±0.1pF	GJM1555C1H9R5BB01#	p157
				±0.25pF	GJM1555C1H9R5CB01#	p157
				±0.5pF	GJM1555C1H9R5DB01#	p157
			9.6pF	±0.05pF	GJM1555C1H9R6WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	9.6pF	±0.1pF	GJM1555C1H9R6BB01#	p157
				±0.25pF	GJM1555C1H9R6CB01#	p157
				±0.5pF	GJM1555C1H9R6DB01#	p157
			9.7pF	±0.05pF	GJM1555C1H9R7WB01#	p157
				±0.1pF	GJM1555C1H9R7BB01#	p157
				±0.25pF	GJM1555C1H9R7CB01#	p157
				±0.5pF	GJM1555C1H9R7DB01#	p157
			9.8pF	±0.05pF	GJM1555C1H9R8WB01#	p157
				±0.1pF	GJM1555C1H9R8BB01#	p157
				±0.25pF	GJM1555C1H9R8CB01#	p157
				±0.5pF	GJM1555C1H9R8DB01#	p157
			9.9pF	±0.05pF	GJM1555C1H9R9WB01#	p157
				±0.1pF	GJM1555C1H9R9BB01#	p157
				±0.25pF	GJM1555C1H9R9CB01#	p157
				±0.5pF	GJM1555C1H9R9DB01#	p157
			10pF	±2%	GJM1555C1H100GB01#	p157
				±5%	GJM1555C1H100JB01#	p157
			11pF	±2%	GJM1555C1H110GB01#	p157
				±5%	GJM1555C1H110JB01#	p157
			12pF	±2%	GJM1555C1H120GB01#	p157
				±5%	GJM1555C1H120JB01#	p157
			13pF	±2%	GJM1555C1H130GB01#	p157
				±5%	GJM1555C1H130JB01#	p157
			15pF	±2%	GJM1555C1H150GB01#	p157
				±5%	GJM1555C1H150JB01#	p157
			16pF	±2%	GJM1555C1H160GB01#	p157
				±5%	GJM1555C1H160JB01#	p157
			18pF	±2%	GJM1555C1H180GB01#	p157
				±5%	GJM1555C1H180JB01#	p157
			20pF	±2%	GJM1555C1H200GB01#	p157
				±5%	GJM1555C1H200JB01#	p157
			22pF	±1%	GJM1555C1H220FB01#	p157
				±2%	GJM1555C1H220GB01#	p157
				±5%	GJM1555C1H220JB01#	p157
			24pF	±1%	GJM1555C1H240FB01#	p157
				±2%	GJM1555C1H240GB01#	p157
				±5%	GJM1555C1H240JB01#	p157
			27pF	±1%	GJM1555C1H270FB01#	p157
				±2%	GJM1555C1H270GB01#	p157
				±5%	GJM1555C1H270JB01#	p157
			30pF	±1%	GJM1555C1H300FB01#	p157
				±2%	GJM1555C1H300GB01#	p157
				±5%	GJM1555C1H300JB01#	p157
			33pF	±1%	GJM1555C1H330FB01#	p157
				±2%	GJM1555C1H330GB01#	p157
				±5%	GJM1555C1H330JB01#	p157
			36pF	±1%	GJM1555C1H360FB01#	p157
				±2%	GJM1555C1H360GB01#	p157
				±5%	GJM1555C1H360JB01#	p157
			39pF	±1%	GJM1555C1H390FB01#	p157
				±2%	GJM1555C1H390GB01#	p157
				±5%	GJM1555C1H390JB01#	p157
			43pF	±1%	GJM1555C1H430FB01#	p157
				±2%	GJM1555C1H430GB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	C0G	43pF	±5%	GJM1555C1H430JB01#	p157
			47pF	±1%	GJM1555C1H470FB01#	p157
				±2%	GJM1555C1H470GB01#	p157
				±5%	GJM1555C1H470JB01#	p157
		CK	0.10pF	±0.05pF	GJM1554C1HR10WB01#	p157
				±0.1pF	GJM1554C1HR10BB01#	p157
			0.20pF	±0.05pF	GJM1554C1HR20WB01#	p157
				±0.1pF	GJM1554C1HR20BB01#	p157
			0.30pF	±0.05pF	GJM1554C1HR30WB01#	p157
				±0.1pF	GJM1554C1HR30BB01#	p157
			0.40pF	±0.05pF	GJM1554C1HR40WB01#	p157
				±0.1pF	GJM1554C1HR40BB01#	p157
			0.50pF	±0.05pF	GJM1554C1HR50WB01#	p157
				±0.1pF	GJM1554C1HR50BB01#	p157
			0.60pF	±0.05pF	GJM1554C1HR60WB01#	p157
				±0.1pF	GJM1554C1HR60BB01#	p157
			0.70pF	±0.05pF	GJM1554C1HR70WB01#	p157
				±0.1pF	GJM1554C1HR70BB01#	p157
			0.80pF	±0.05pF	GJM1554C1HR80WB01#	p157
				±0.1pF	GJM1554C1HR80BB01#	p157
			0.90pF	±0.05pF	GJM1554C1HR90WB01#	p157
				±0.1pF	GJM1554C1HR90BB01#	p157
			1.0pF	±0.05pF	GJM1554C1H1R0WB01#	p157
				±0.1pF	GJM1554C1H1R0BB01#	p157
				±0.25pF	GJM1554C1H1R0CB01#	p157
			1.1pF	±0.05pF	GJM1554C1H1R1WB01#	p157
				±0.1pF	GJM1554C1H1R1BB01#	p157
				±0.25pF	GJM1554C1H1R1CB01#	p157
			1.2pF	±0.05pF	GJM1554C1H1R2WB01#	p157
				±0.1pF	GJM1554C1H1R2BB01#	p157
				±0.25pF	GJM1554C1H1R2CB01#	p157
			1.3pF	±0.05pF	GJM1554C1H1R3WB01#	p157
				±0.1pF	GJM1554C1H1R3BB01#	p157
				±0.25pF	GJM1554C1H1R3CB01#	p157
			1.4pF	±0.05pF	GJM1554C1H1R4WB01#	p157
				±0.1pF	GJM1554C1H1R4BB01#	p157
				±0.25pF	GJM1554C1H1R4CB01#	p157
			1.5pF	±0.05pF	GJM1554C1H1R5WB01#	p157
				±0.1pF	GJM1554C1H1R5BB01#	p157
				±0.25pF	GJM1554C1H1R5CB01#	p157
			1.6pF	±0.05pF	GJM1554C1H1R6WB01#	p157
				±0.1pF	GJM1554C1H1R6BB01#	p157
				±0.25pF	GJM1554C1H1R6CB01#	p157
			1.7pF	±0.05pF	GJM1554C1H1R7WB01#	p157
				±0.1pF	GJM1554C1H1R7BB01#	p157
				±0.25pF	GJM1554C1H1R7CB01#	p157
			1.8pF	±0.05pF	GJM1554C1H1R8WB01#	p157
				±0.1pF	GJM1554C1H1R8BB01#	p157
				±0.25pF	GJM1554C1H1R8CB01#	p157
			1.9pF	±0.05pF	GJM1554C1H1R9WB01#	p157
				±0.1pF	GJM1554C1H1R9BB01#	p157
				±0.25pF	GJM1554C1H1R9CB01#	p157
			2.0pF	±0.05pF	GJM1554C1H2R0WB01#	p157
				±0.1pF	GJM1554C1H2R0BB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	CK	2.0pF	±0.25pF	GJM1554C1H2R0CB01#	p157
		CJ	2.1pF	±0.05pF	GJM1553C1H2R1WB01#	p157
				±0.1pF	GJM1553C1H2R1BB01#	p157
				±0.25pF	GJM1553C1H2R1CB01#	p157
			2.2pF	±0.05pF	GJM1553C1H2R2WB01#	p157
				±0.1pF	GJM1553C1H2R2BB01#	p157
				±0.25pF	GJM1553C1H2R2CB01#	p157
			2.3pF	±0.05pF	GJM1553C1H2R3WB01#	p157
				±0.1pF	GJM1553C1H2R3BB01#	p157
				±0.25pF	GJM1553C1H2R3CB01#	p157
			2.4pF	±0.05pF	GJM1553C1H2R4WB01#	p157
				±0.1pF	GJM1553C1H2R4BB01#	p157
				±0.25pF	GJM1553C1H2R4CB01#	p157
			2.5pF	±0.05pF	GJM1553C1H2R5WB01#	p157
				±0.1pF	GJM1553C1H2R5BB01#	p157
				±0.25pF	GJM1553C1H2R5CB01#	p157
			2.6pF	±0.05pF	GJM1553C1H2R6WB01#	p157
				±0.1pF	GJM1553C1H2R6BB01#	p157
				±0.25pF	GJM1553C1H2R6CB01#	p157
			2.7pF	±0.05pF	GJM1553C1H2R7WB01#	p157
				±0.1pF	GJM1553C1H2R7BB01#	p157
				±0.25pF	GJM1553C1H2R7CB01#	p157
			2.8pF	±0.05pF	GJM1553C1H2R8WB01#	p157
				±0.1pF	GJM1553C1H2R8BB01#	p157
				±0.25pF	GJM1553C1H2R8CB01#	p157
			2.9pF	±0.05pF	GJM1553C1H2R9WB01#	p157
				±0.1pF	GJM1553C1H2R9BB01#	p157
				±0.25pF	GJM1553C1H2R9CB01#	p157
			3.0pF	±0.05pF	GJM1553C1H3R0WB01#	p157
				±0.1pF	GJM1553C1H3R0BB01#	p157
				±0.25pF	GJM1553C1H3R0CB01#	p157
			3.1pF	±0.05pF	GJM1553C1H3R1WB01#	p157
				±0.1pF	GJM1553C1H3R1BB01#	p157
				±0.25pF	GJM1553C1H3R1CB01#	p157
			3.2pF	±0.05pF	GJM1553C1H3R2WB01#	p157
				±0.1pF	GJM1553C1H3R2BB01#	p157
				±0.25pF	GJM1553C1H3R2CB01#	p157
			3.3pF	±0.05pF	GJM1553C1H3R3WB01#	p157
				±0.1pF	GJM1553C1H3R3BB01#	p157
				±0.25pF	GJM1553C1H3R3CB01#	p157
			3.4pF	±0.05pF	GJM1553C1H3R4WB01#	p157
				±0.1pF	GJM1553C1H3R4BB01#	p157
				±0.25pF	GJM1553C1H3R4CB01#	p157
			3.5pF	±0.05pF	GJM1553C1H3R5WB01#	p157
				±0.1pF	GJM1553C1H3R5BB01#	p157
				±0.25pF	GJM1553C1H3R5CB01#	p157
			3.6pF	±0.05pF	GJM1553C1H3R6WB01#	p157
				±0.1pF	GJM1553C1H3R6BB01#	p157
				±0.25pF	GJM1553C1H3R6CB01#	p157
			3.7pF	±0.05pF	GJM1553C1H3R7WB01#	p157
				±0.1pF	GJM1553C1H3R7BB01#	p157
				±0.25pF	GJM1553C1H3R7CB01#	p157
			3.8pF	±0.05pF	GJM1553C1H3R8WB01#	p157
				±0.1pF	GJM1553C1H3R8BB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	CJ	3.8pF	±0.25pF	GJM1553C1H3R8CB01#	p157
			3.9pF	±0.05pF	GJM1553C1H3R9WB01#	p157
				±0.1pF	GJM1553C1H3R9BB01#	p157
				±0.25pF	GJM1553C1H3R9CB01#	p157
		CH	4.0pF	±0.05pF	GJM1552C1H4R0WB01#	p157
				±0.1pF	GJM1552C1H4R0BB01#	p157
				±0.25pF	GJM1552C1H4R0CB01#	p157
			4.1pF	±0.05pF	GJM1552C1H4R1WB01#	p157
				±0.1pF	GJM1552C1H4R1BB01#	p157
				±0.25pF	GJM1552C1H4R1CB01#	p157
			4.2pF	±0.05pF	GJM1552C1H4R2WB01#	p157
				±0.1pF	GJM1552C1H4R2BB01#	p157
				±0.25pF	GJM1552C1H4R2CB01#	p157
			4.3pF	±0.05pF	GJM1552C1H4R3WB01#	p157
				±0.1pF	GJM1552C1H4R3BB01#	p157
				±0.25pF	GJM1552C1H4R3CB01#	p157
			4.4pF	±0.05pF	GJM1552C1H4R4WB01#	p157
				±0.1pF	GJM1552C1H4R4BB01#	p157
				±0.25pF	GJM1552C1H4R4CB01#	p157
			4.5pF	±0.05pF	GJM1552C1H4R5WB01#	p157
				±0.1pF	GJM1552C1H4R5BB01#	p157
				±0.25pF	GJM1552C1H4R5CB01#	p157
			4.6pF	±0.05pF	GJM1552C1H4R6WB01#	p157
				±0.1pF	GJM1552C1H4R6BB01#	p157
				±0.25pF	GJM1552C1H4R6CB01#	p157
			4.7pF	±0.05pF	GJM1552C1H4R7WB01#	p157
				±0.1pF	GJM1552C1H4R7BB01#	p157
				±0.25pF	GJM1552C1H4R7CB01#	p157
			4.8pF	±0.05pF	GJM1552C1H4R8WB01#	p157
				±0.1pF	GJM1552C1H4R8BB01#	p157
				±0.25pF	GJM1552C1H4R8CB01#	p157
			4.9pF	±0.05pF	GJM1552C1H4R9WB01#	p157
				±0.1pF	GJM1552C1H4R9BB01#	p157
				±0.25pF	GJM1552C1H4R9CB01#	p157
			5.0pF	±0.05pF	GJM1552C1H5R0WB01#	p157
				±0.1pF	GJM1552C1H5R0BB01#	p157
				±0.25pF	GJM1552C1H5R0CB01#	p157
			5.1pF	±0.05pF	GJM1552C1H5R1WB01#	p157
				±0.1pF	GJM1552C1H5R1BB01#	p157
				±0.25pF	GJM1552C1H5R1CB01#	p157
				±0.5pF	GJM1552C1H5R1DB01#	p157
			5.2pF	±0.05pF	GJM1552C1H5R2WB01#	p157
				±0.1pF	GJM1552C1H5R2BB01#	p157
				±0.25pF	GJM1552C1H5R2CB01#	p157
				±0.5pF	GJM1552C1H5R2DB01#	p157
			5.3pF	±0.05pF	GJM1552C1H5R3WB01#	p157
				±0.1pF	GJM1552C1H5R3BB01#	p157
				±0.25pF	GJM1552C1H5R3CB01#	p157
				±0.5pF	GJM1552C1H5R3DB01#	p157
			5.4pF	±0.05pF	GJM1552C1H5R4WB01#	p157
				±0.1pF	GJM1552C1H5R4BB01#	p157
				±0.25pF	GJM1552C1H5R4CB01#	p157
				±0.5pF	GJM1552C1H5R4DB01#	p157
			5.5pF	±0.05pF	GJM1552C1H5R5WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	CH	5.5pF	±0.1pF	GJM1552C1H5R5BB01#	p157
				±0.25pF	GJM1552C1H5R5CB01#	p157
				±0.5pF	GJM1552C1H5R5DB01#	p157
			5.6pF	±0.05pF	GJM1552C1H5R6WB01#	p157
				±0.1pF	GJM1552C1H5R6BB01#	p157
				±0.25pF	GJM1552C1H5R6CB01#	p157
				±0.5pF	GJM1552C1H5R6DB01#	p157
			5.7pF	±0.05pF	GJM1552C1H5R7WB01#	p157
				±0.1pF	GJM1552C1H5R7BB01#	p157
				±0.25pF	GJM1552C1H5R7CB01#	p157
				±0.5pF	GJM1552C1H5R7DB01#	p157
			5.8pF	±0.05pF	GJM1552C1H5R8WB01#	p157
				±0.1pF	GJM1552C1H5R8BB01#	p157
				±0.25pF	GJM1552C1H5R8CB01#	p157
				±0.5pF	GJM1552C1H5R8DB01#	p157
			5.9pF	±0.05pF	GJM1552C1H5R9WB01#	p157
				±0.1pF	GJM1552C1H5R9BB01#	p157
				±0.25pF	GJM1552C1H5R9CB01#	p157
				±0.5pF	GJM1552C1H5R9DB01#	p157
			6.0pF	±0.05pF	GJM1552C1H6R0WB01#	p157
				±0.1pF	GJM1552C1H6R0BB01#	p157
				±0.25pF	GJM1552C1H6R0CB01#	p157
				±0.5pF	GJM1552C1H6R0DB01#	p157
			6.1pF	±0.05pF	GJM1552C1H6R1WB01#	p157
				±0.1pF	GJM1552C1H6R1BB01#	p157
				±0.25pF	GJM1552C1H6R1CB01#	p157
				±0.5pF	GJM1552C1H6R1DB01#	p157
			6.2pF	±0.05pF	GJM1552C1H6R2WB01#	p157
				±0.1pF	GJM1552C1H6R2BB01#	p157
				±0.25pF	GJM1552C1H6R2CB01#	p157
				±0.5pF	GJM1552C1H6R2DB01#	p157
			6.3pF	±0.05pF	GJM1552C1H6R3WB01#	p157
				±0.1pF	GJM1552C1H6R3BB01#	p157
				±0.25pF	GJM1552C1H6R3CB01#	p157
				±0.5pF	GJM1552C1H6R3DB01#	p157
			6.4pF	±0.05pF	GJM1552C1H6R4WB01#	p157
				±0.1pF	GJM1552C1H6R4BB01#	p157
				±0.25pF	GJM1552C1H6R4CB01#	p157
				±0.5pF	GJM1552C1H6R4DB01#	p157
			6.5pF	±0.05pF	GJM1552C1H6R5WB01#	p157
				±0.1pF	GJM1552C1H6R5BB01#	p157
				±0.25pF	GJM1552C1H6R5CB01#	p157
				±0.5pF	GJM1552C1H6R5DB01#	p157
			6.6pF	±0.05pF	GJM1552C1H6R6WB01#	p157
				±0.1pF	GJM1552C1H6R6BB01#	p157
				±0.25pF	GJM1552C1H6R6CB01#	p157
				±0.5pF	GJM1552C1H6R6DB01#	p157
			6.7pF	±0.05pF	GJM1552C1H6R7WB01#	p157
				±0.1pF	GJM1552C1H6R7BB01#	p157
				±0.25pF	GJM1552C1H6R7CB01#	p157
				±0.5pF	GJM1552C1H6R7DB01#	p157
			6.8pF	±0.05pF	GJM1552C1H6R8WB01#	p157
				±0.1pF	GJM1552C1H6R8BB01#	p157
				±0.25pF	GJM1552C1H6R8CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	CH	6.8pF	±0.5pF	GJM1552C1H6R8DB01#	p157
			6.9pF	±0.05pF	GJM1552C1H6R9WB01#	p157
				±0.1pF	GJM1552C1H6R9BB01#	p157
				±0.25pF	GJM1552C1H6R9CB01#	p157
				±0.5pF	GJM1552C1H6R9DB01#	p157
			7.0pF	±0.05pF	GJM1552C1H7R0WB01#	p157
				±0.1pF	GJM1552C1H7R0BB01#	p157
				±0.25pF	GJM1552C1H7R0CB01#	p157
				±0.5pF	GJM1552C1H7R0DB01#	p157
			7.1pF	±0.05pF	GJM1552C1H7R1WB01#	p157
				±0.1pF	GJM1552C1H7R1BB01#	p157
				±0.25pF	GJM1552C1H7R1CB01#	p157
				±0.5pF	GJM1552C1H7R1DB01#	p157
			7.2pF	±0.05pF	GJM1552C1H7R2WB01#	p157
				±0.1pF	GJM1552C1H7R2BB01#	p157
				±0.25pF	GJM1552C1H7R2CB01#	p157
				±0.5pF	GJM1552C1H7R2DB01#	p157
			7.3pF	±0.05pF	GJM1552C1H7R3WB01#	p157
				±0.1pF	GJM1552C1H7R3BB01#	p157
				±0.25pF	GJM1552C1H7R3CB01#	p157
				±0.5pF	GJM1552C1H7R3DB01#	p157
			7.4pF	±0.05pF	GJM1552C1H7R4WB01#	p157
				±0.1pF	GJM1552C1H7R4BB01#	p157
				±0.25pF	GJM1552C1H7R4CB01#	p157
				±0.5pF	GJM1552C1H7R4DB01#	p157
			7.5pF	±0.05pF	GJM1552C1H7R5WB01#	p157
				±0.1pF	GJM1552C1H7R5BB01#	p157
				±0.25pF	GJM1552C1H7R5CB01#	p157
				±0.5pF	GJM1552C1H7R5DB01#	p157
			7.6pF	±0.05pF	GJM1552C1H7R6WB01#	p157
				±0.1pF	GJM1552C1H7R6BB01#	p157
				±0.25pF	GJM1552C1H7R6CB01#	p157
				±0.5pF	GJM1552C1H7R6DB01#	p157
			7.7pF	±0.05pF	GJM1552C1H7R7WB01#	p157
				±0.1pF	GJM1552C1H7R7BB01#	p157
				±0.25pF	GJM1552C1H7R7CB01#	p157
				±0.5pF	GJM1552C1H7R7DB01#	p157
			7.8pF	±0.05pF	GJM1552C1H7R8WB01#	p157
				±0.1pF	GJM1552C1H7R8BB01#	p157
				±0.25pF	GJM1552C1H7R8CB01#	p157
				±0.5pF	GJM1552C1H7R8DB01#	p157
			7.9pF	±0.05pF	GJM1552C1H7R9WB01#	p157
				±0.1pF	GJM1552C1H7R9BB01#	p157
				±0.25pF	GJM1552C1H7R9CB01#	p157
				±0.5pF	GJM1552C1H7R9DB01#	p157
			8.0pF	±0.05pF	GJM1552C1H8R0WB01#	p157
				±0.1pF	GJM1552C1H8R0BB01#	p157
				±0.25pF	GJM1552C1H8R0CB01#	p157
				±0.5pF	GJM1552C1H8R0DB01#	p157
			8.1pF	±0.05pF	GJM1552C1H8R1WB01#	p157
				±0.1pF	GJM1552C1H8R1BB01#	p157
				±0.25pF	GJM1552C1H8R1CB01#	p157
				±0.5pF	GJM1552C1H8R1DB01#	p157
			8.2pF	±0.05pF	GJM1552C1H8R2WB01#	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	CH	8.2pF	±0.1pF	GJM1552C1H8R2BB01#	p157
				±0.25pF	GJM1552C1H8R2CB01#	p157
				±0.5pF	GJM1552C1H8R2DB01#	p157
			8.3pF	±0.05pF	GJM1552C1H8R3WB01#	p157
				±0.1pF	GJM1552C1H8R3BB01#	p157
				±0.25pF	GJM1552C1H8R3CB01#	p157
				±0.5pF	GJM1552C1H8R3DB01#	p157
			8.4pF	±0.05pF	GJM1552C1H8R4WB01#	p157
				±0.1pF	GJM1552C1H8R4BB01#	p157
				±0.25pF	GJM1552C1H8R4CB01#	p157
				±0.5pF	GJM1552C1H8R4DB01#	p157
			8.5pF	±0.05pF	GJM1552C1H8R5WB01#	p157
				±0.1pF	GJM1552C1H8R5BB01#	p157
				±0.25pF	GJM1552C1H8R5CB01#	p157
				±0.5pF	GJM1552C1H8R5DB01#	p157
			8.6pF	±0.05pF	GJM1552C1H8R6WB01#	p157
				±0.1pF	GJM1552C1H8R6BB01#	p157
				±0.25pF	GJM1552C1H8R6CB01#	p157
				±0.5pF	GJM1552C1H8R6DB01#	p157
			8.7pF	±0.05pF	GJM1552C1H8R7WB01#	p157
				±0.1pF	GJM1552C1H8R7BB01#	p157
				±0.25pF	GJM1552C1H8R7CB01#	p157
				±0.5pF	GJM1552C1H8R7DB01#	p157
			8.8pF	±0.05pF	GJM1552C1H8R8WB01#	p157
				±0.1pF	GJM1552C1H8R8BB01#	p157
				±0.25pF	GJM1552C1H8R8CB01#	p157
				±0.5pF	GJM1552C1H8R8DB01#	p157
			8.9pF	±0.05pF	GJM1552C1H8R9WB01#	p157
				±0.1pF	GJM1552C1H8R9BB01#	p157
				±0.25pF	GJM1552C1H8R9CB01#	p157
				±0.5pF	GJM1552C1H8R9DB01#	p157
			9.0pF	±0.05pF	GJM1552C1H9R0WB01#	p157
				±0.1pF	GJM1552C1H9R0BB01#	p157
				±0.25pF	GJM1552C1H9R0CB01#	p157
				±0.5pF	GJM1552C1H9R0DB01#	p157
			9.1pF	±0.05pF	GJM1552C1H9R1WB01#	p157
				±0.1pF	GJM1552C1H9R1BB01#	p157
				±0.25pF	GJM1552C1H9R1CB01#	p157
				±0.5pF	GJM1552C1H9R1DB01#	p157
			9.2pF	±0.05pF	GJM1552C1H9R2WB01#	p157
				±0.1pF	GJM1552C1H9R2BB01#	p157
				±0.25pF	GJM1552C1H9R2CB01#	p157
				±0.5pF	GJM1552C1H9R2DB01#	p157
			9.3pF	±0.05pF	GJM1552C1H9R3WB01#	p157
				±0.1pF	GJM1552C1H9R3BB01#	p157
				±0.25pF	GJM1552C1H9R3CB01#	p157
				±0.5pF	GJM1552C1H9R3DB01#	p157
			9.4pF	±0.05pF	GJM1552C1H9R4WB01#	p157
				±0.1pF	GJM1552C1H9R4BB01#	p157
				±0.25pF	GJM1552C1H9R4CB01#	p157
				±0.5pF	GJM1552C1H9R4DB01#	p157
			9.5pF	±0.05pF	GJM1552C1H9R5WB01#	p157
				±0.1pF	GJM1552C1H9R5BB01#	p157
				±0.25pF	GJM1552C1H9R5CB01#	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GJM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	CH	9.5pF	±0.5pF	**GJM1552C1H9R5DB01#**	p157
			9.6pF	±0.05pF	**GJM1552C1H9R6WB01#**	p157
				±0.1pF	**GJM1552C1H9R6BB01#**	p157
				±0.25pF	**GJM1552C1H9R6CB01#**	p157
				±0.5pF	**GJM1552C1H9R6DB01#**	p157
			9.7pF	±0.05pF	**GJM1552C1H9R7WB01#**	p157
				±0.1pF	**GJM1552C1H9R7BB01#**	p157
				±0.25pF	**GJM1552C1H9R7CB01#**	p157
				±0.5pF	**GJM1552C1H9R7DB01#**	p157
			9.8pF	±0.05pF	**GJM1552C1H9R8WB01#**	p157
				±0.1pF	**GJM1552C1H9R8BB01#**	p157
				±0.25pF	**GJM1552C1H9R8CB01#**	p157
				±0.5pF	**GJM1552C1H9R8DB01#**	p157
			9.9pF	±0.05pF	**GJM1552C1H9R9WB01#**	p157
				±0.1pF	**GJM1552C1H9R9BB01#**	p157
				±0.25pF	**GJM1552C1H9R9CB01#**	p157
				±0.5pF	**GJM1552C1H9R9DB01#**	p157
			10pF	±2%	**GJM1552C1H100GB01#**	p157
				±5%	**GJM1552C1H100JB01#**	p157
			11pF	±2%	**GJM1552C1H110GB01#**	p157
				±5%	**GJM1552C1H110JB01#**	p157
			12pF	±2%	**GJM1552C1H120GB01#**	p157
				±5%	**GJM1552C1H120JB01#**	p157
			13pF	±2%	**GJM1552C1H130GB01#**	p157
				±5%	**GJM1552C1H130JB01#**	p157
			15pF	±2%	**GJM1552C1H150GB01#**	p157
				±5%	**GJM1552C1H150JB01#**	p157
			16pF	±2%	**GJM1552C1H160GB01#**	p157
				±5%	**GJM1552C1H160JB01#**	p157
			18pF	±2%	**GJM1552C1H180GB01#**	p157
				±5%	**GJM1552C1H180JB01#**	p157
			20pF	±2%	**GJM1552C1H200GB01#**	p157
				±5%	**GJM1552C1H200JB01#**	p157
			22pF	±1%	**GJM1552C1H220FB01#**	p157
				±2%	**GJM1552C1H220GB01#**	p157
				±5%	**GJM1552C1H220JB01#**	p157
			24pF	±1%	**GJM1552C1H240FB01#**	p157
				±2%	**GJM1552C1H240GB01#**	p157
				±5%	**GJM1552C1H240JB01#**	p157
			27pF	±1%	**GJM1552C1H270FB01#**	p157
				±2%	**GJM1552C1H270GB01#**	p157
				±5%	**GJM1552C1H270JB01#**	p157
			30pF	±1%	**GJM1552C1H300FB01#**	p157
				±2%	**GJM1552C1H300GB01#**	p157
				±5%	**GJM1552C1H300JB01#**	p157
			33pF	±1%	**GJM1552C1H330FB01#**	p157
				±2%	**GJM1552C1H330GB01#**	p157
				±5%	**GJM1552C1H330JB01#**	p157
			36pF	±1%	**GJM1552C1H360FB01#**	p157
				±2%	**GJM1552C1H360GB01#**	p157
				±5%	**GJM1552C1H360JB01#**	p157
			39pF	±1%	**GJM1552C1H390FB01#**	p157
				±2%	**GJM1552C1H390GB01#**	p157
				±5%	**GJM1552C1H390JB01#**	p157

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	CH	43pF	±1%	**GJM1552C1H430FB01#**	p157
				±2%	**GJM1552C1H430GB01#**	p157
				±5%	**GJM1552C1H430JB01#**	p157
			47pF	±1%	**GJM1552C1H470FB01#**	p157
				±2%	**GJM1552C1H470GB01#**	p157
				±5%	**GJM1552C1H470JB01#**	p157

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GJM Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	**Rated Voltage**		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	**Appearance**		No defects or abnormalities.	Visual inspection.
3	**Dimension**		Within the specified dimensions.	Using Measuring instrument of dimension.
4	**Impulse Voltage**		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 300% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	**Insulation Resistance (I.R.)**		C ≦ 0.047μF: More than 10000MΩ C > 0.047μF: More than 500Ω • F C: Nominal Capacitance	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	**Capacitance**		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance: C ≦ 1000pF; Frequency: 1.0±0.1MHz; Voltage: 0.5 to 5.0Vrms
7	**Q**		30pF and over: Q ≧ 1000 30pF and below: Q ≧ 400+20C C: Nominal Capacitance (pF)	
8	**Temperature Characteristics of Capacitance**		Nominal values of the temperature coefficient is shown in Rated value. But,the Capacitance Change under 20°C is shown in Table A. Capacitance Drift Within ±0.2% or ±0.05pF (Whichever is larger.)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. The capacitance drift is calculated by dividing the differences between the maximum and minimum measured values in the step 1, 3 and 5 by the cap. value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2
9	**Adhesive Strength of Termination**		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate shown in Fig.3. GJM02: 1; GJM03: 2; GJM15: 5 Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	**Vibration**	**Appearance**	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
11	**Substrate Bending Test**	**Appearance**	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.1. Pressurization method: Shown in Fig.2 Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
		Capacitance Change	Within ±5% or ±0.5pF (Whichever is larger)	
12	**Solderability**		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s

Continued on the following page.↗

GJM Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	<GJM02 size only> Test Method: Reflow soldering (hot plate) Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Reflow Time: 10±0.5s Test Substrate: Glass epoxy PCB Exposure Time: 24±2h Preheat: 120 to 150°C for 1min <GJM03/GJM15 size> Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Immersion time: 10±0.5s Exposure Time: 24±2h Preheat: 120 to 150°C for 1min
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Perform the five cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±7.5% or ±0.75pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 200 30pF and below: Q ≧ 100+10C/3 C: Nominal Capacitance (pF)	
		I.R.	More than 500MΩ or 25Ω • F (Whichever is smaller)	
16	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±3% or ±0.3pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 350 10pF and over, 30pF and below: Q ≧ 275+5C/2 10pF and below: Q ≧ 200+10C C: Nominal Capacitance (pF)	
		I.R.	More than 1000MΩ or 50Ω • F (Whichever is smaller)	
17	ESR (GJM02)		0.2pF ≦ C ≦ 1pF: 700mΩ/C below 1pF < C ≦ 2pF: 600mΩ below 2pF < C ≦ 5pF: 500mΩ below 5pF < C ≦ 10pF: 300mΩ below 10pF < C ≦ 22pF: 350mΩ below C: Nominal Capacitance (pF)	Measurement Frequency: 1.0±0.1GHz Measurement Temperature: Room Temp. Measurement Instrument: Equivalent to E4991A
	ESR (GJM03/GJM15)		0.1pF ≦ C ≦ 1pF: 350mΩ/C below 1pF < C ≦ 5pF: 300mΩ below 5pF < C ≦ 10pF: 250mΩ below C: Nominal Capacitance (pF)	Measurement Frequency: 1.0±0.2GHz Measurement Temperature: Room Temp. Measurement Instrument: Equivalent to BOONTON Model 34A
			10pF < C ≦ 47pF: 400mΩ below	Measurement Frequency: 500±50MHz Measurement Temperature: Room Temp. Measurement Instrument: Equivalent to HP8753B

Continued on the following page.↗

GJM Series Specifications and Test Methods (1)

Continued from the preceding page.↘

Table A

Char.	Capacitance Change from Value at Reference Temp. (%)							
	-55˚C		-30˚C		-25˚C		-10˚C	
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.
1C	0.54	-0.23	-	-	0.33	-0.14	0.22	-0.09
2C	0.82	-0.45	-	-	0.49	-0.27	0.33	-0.18
3C	1.37	-0.90	-	-	0.82	-0.54	0.55	-0.36
4C	2.56	-1.88	-	-	1.54	-1.13	1.02	-0.75
5C	0.58	-0.24	0.40	-0.17	-	-	0.25	-0.11
6C	0.87	-0.48	0.59	-0.33	-	-	0.38	-0.21

Substrate Bending Test

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs
  (Glass fabric base, epoxy resin)
  Thickness: 0.8mm
  : Solder resist
  (Coat with heat resistant resin for solder)



Copper foil thickness: 0.018mm

Copper foil thickness: 0.035mm

Part Number	Dimension (mm)		
	a	b	c
GJM02	0.2	0.56	023
GJM03	0.3	0.9	0.3
GJM15	0.4	1.5	0.5

Fig.1

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Pressurization Method



Fig.2

Adhesive Strength of Termination, Vibration, Temperature Sudden Change, Resistance to Soldering Heat (Reflow method) High Temperature High Humidity (Steady), Durability

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs
  (Glass fabric base, epoxy resin)
  Thickness: 1.6mm or 0.8mm
  Copper foil thickness: 0.035mm

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GJM02	0.2	0.56	023
GJM03	0.3	0.9	0.3
GJM15	0.4	1.5	0.5

Fig.3

2 GJM Series Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	**Rated Voltage**		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	**Appearance**		No defects or abnormalities.	Visual inspection.
3	**Dimension**		Within the specified dimensions.	Using Measuring instrument of dimension.
4	**Voltage Proof**		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 300% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	**Insulation Resistance (I.R.)**		C ≦ 0.047μF: More than 10000MΩ C > 0.047μF: More than 500Ω • F C: Nominal Capacitance	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	**Capacitance**		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance: C ≦ 1000pF; Frequency: 1.0±0.1MHz; Voltage: 0.5 to 5.0Vrms
7	**Q**		30pF and over: Q ≧ 1000 30pF and below: Q ≧ 400+20C C: Nominal Capacitance (pF)	
8	**Temperature Characteristics of Capacitance**		Nominal values of the temperature coefficient is shown in Rated value. But,the Capacitance Change under 20°C is shown in Table A. Capacitance Drift Within ±0.2% or ±0.05pF (Whichever is larger.)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. The capacitance drift is calculated by dividing the differences between the maximum and minimum measured values in the step 1, 3 and 5 by the cap. value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2
9	**Adhesive Strength of Termination**		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate shown in Fig.3. GJM02: Applied Force 1 N GJM03: Applied Force 2 N GJM15: Applied Force 5 N Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	**Vibration**	**Appearance**	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
11	**Substrate Bending Test**	**Appearance**	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.1. Pressurization method: Shown in Fig.2 Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
		Capacitance Change	Within ±5% or ±0.5pF (Whichever is larger)	
12	**Solderability**		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s

Continued on the following page.↗

GJM Series Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	<GJM02 size only> Test Method: Reflow soldering (hot plate) Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Reflow Time: 10±0.5s Test Substrate: Glass epoxy PCB Exposure Time: 24±2h Preheat: 120 to 150°C for 1min <GJM03/GJM15 size> Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Immersion time: 10±0.5s Exposure Time: 24±2h Preheat: 120 to 150°C for 1min
		Capacitance Change	Within ±2.5% or ± 0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Perform the five cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±7.5% or ±0.75pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 200 30pF and below: Q ≧ 100+10C/3 C: Nominal Capacitance (pF)	
		I.R.	More than 500MΩ or 25Ω • F (Whichever is smaller)	
16	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 100% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±3% or ±0.3pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 350 10pF and over, 30pF and below: Q ≧ 275+5C/2 10pF and below: Q ≧ 200+10C C: Nominal Capacitance (pF)	
		I.R.	More than 1000MΩ or 50Ω • F (Whichever is smaller)	
17	ESR (GJM02)		0.2pF ≦ C ≦ 1pF: 700mΩ/C below 1pF < C ≦ 2pF: 600mΩ below 2pF < C ≦ 5pF: 500mΩ below 5pF < C ≦ 10pF: 300mΩ below 10pF < C ≦ 22pF: 350mΩ below C: Nominal Capacitance (pF)	Measurement Frequency: 1.0±0.1GHz Measurement Temperature: Room Temp. Measurement Instrument: Equivalent to E4991A
	ESR (GJM03/GJM15)		0.1pF ≦ C ≦ 1pF: 350mΩ/C below 1pF < C ≦ 5pF: 300mΩ below 5pF < C ≦ 10pF: 250mΩ below C: Nominal Capacitance (pF)	Measurement Frequency: 1.0±0.2GHz Measurement Temperature: Room Temp. Measurement Instrument: Equivalent to BOONTON Model 34A
			10pF < C ≦ 47pF: 400mΩ below	Measurement Frequency: 500±50MHz Measurement Temperature: Room Temp. Measurement Instrument: Equivalent to HP8753B

Continued on the following page.↗

GJM Series Specifications and Test Methods (2)

Continued from the preceding page.↘

Table A

Char.	Capacitance Change from Value at Reference Temp. (%)							
	-55˚C		-30˚C		-25˚C		-10˚C	
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.
1C	0.54	-0.23	-	-	0.33	-0.14	0.22	-0.09
2C	0.82	-0.45	-	-	0.49	-0.27	0.33	-0.18
3C	1.37	-0.90	-	-	0.82	-0.54	0.55	-0.36
4C	2.56	-1.88	-	-	1.54	-1.13	1.02	-0.75
5C	0.58	-0.24	0.40	-0.17	-	-	0.25	-0.11
6C	0.87	-0.48	0.59	-0.33	-	-	0.38	-0.21

Recommended derating conditions on voltage and temperature



These Part Numbers are designed for use in the circuits where continuous applied voltage to the capacitor is derated than rated voltage, and guarantee Durability Test with 100% × rated voltage as testing voltage at the maximum operating temperature.
The voltage and temperature derating conditions on the upside are recommended for use to ensure the same reliability level as normal specification.

Continued on the following page.↗

GJM Series Specifications and Test Methods (2)

Continued from the preceding page.↘

Substrate Bending Test

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs
  (Glass fabric base, epoxy resin)
  Thickness: 0.8mm
  : Solder resist
  (Coat with heat resistant resin for solder)



Copper foil thickness: 0.018mm　　Copper foil thickness: 0.035mm

Part Number	Dimension (mm)		
	a	b	c
GJM02	0.2	0.56	023
GJM03	0.3	0.9	0.3
GJM15	0.4	1.5	0.5

Fig.1　(in mm)

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Pressurization Method



Fig.2

Adhesive Strength of Termination, Vibration, Temperature Sudden Change, Resistance to Soldering Heat (Reflow method) High Temperature High Humidity (Steady), Durability

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs
  (Glass fabric base, epoxy resin)
  Thickness: 1.6mm or 0.8mm
  Copper foil thickness: 0.035mm

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GJM02	0.2	0.56	023
GJM03	0.3	0.9	0.3
GJM15	0.4	1.5	0.5

Fig.3

High Q and High Power Chip Multilayer Ceramic Capacitors for General Purpose

GQM Series

High Q

WEB

High Frequency Capacitor Ideal for PA Design of Base Stations

Features

1 Mainly ideal for base stations of mobile communication devices and temperature compensation of related modules.

This product is ideal for temperature compensation of high frequency circuits, such as resonant circuits, tuning circuits, and impedance matching circuits where the operating characteristics of the device are greatly affected by the capacitance fluctuation.



<Example of Structure>

2 High Q and low ESR in VHF, UHF and microwave frequency bands.

High Q and low ESR were achieved at a high frequency by adopting ceramic material as the dielectric material which enables an extremely low loss at high frequency, and base metal electrodes as the internal electrodes.



<Comparison between Q - Frequency Characteristics>



<Comparison between Q - Frequency Characteristics>

3 Can be used for tight tolerance.

In addition to standard tolerance, the allowable range of this product is also suitable for the following narrow tolerance.

Capacitance Range	Standard Capacitance Tolerance (Capacitance Tolerance Symbol)	Narrow Capacitance Tolerance (Capacitance Tolerance Symbol)
to 0.9pF	±0.1pF (B)	±0.05pF (W)
1.0 to 5.0pF	±0.25pF (C)	±0.05pF (W), ±0.1pF (B)
5.1 to 9.9pF	±0.5pF (D)	±0.05pF (W), ±0.1pF (B), ±0.25pF (C)
10pF to	±5% (J)	±2% (G)

Specifications

Size (mm)	1.0×0.5mm to 2.8×2.8mm
Rated Voltage	50Vdc to 500Vdc
Capacitance	0.10pF to 510pF
Main Applications	Measuring instruments, other ultra compact/thin devices



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

GQM Series Temperature Compensating Type Part Number List

1.0×0.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	200Vdc	C0G	0.10pF	±0.1pF	GQM1555C2DR10BB01#	p172
			0.20pF	±0.1pF	GQM1555C2DR20BB01#	p172
			0.30pF	±0.1pF	GQM1555C2DR30BB01#	p172
				±0.25pF	GQM1555C2DR30CB01#	p172
			0.40pF	±0.1pF	GQM1555C2DR40BB01#	p172
				±0.25pF	GQM1555C2DR40CB01#	p172
			0.50pF	±0.1pF	GQM1555C2DR50BB01#	p172
				±0.25pF	GQM1555C2DR50CB01#	p172
			0.60pF	±0.1pF	GQM1555C2DR60BB01#	p172
				±0.25pF	GQM1555C2DR60CB01#	p172
			0.70pF	±0.1pF	GQM1555C2DR70BB01#	p172
				±0.25pF	GQM1555C2DR70CB01#	p172
			0.75pF	±0.1pF	GQM1555C2DR75BB01#	p172
				±0.25pF	GQM1555C2DR75CB01#	p172
			0.80pF	±0.1pF	GQM1555C2DR80BB01#	p172
				±0.25pF	GQM1555C2DR80CB01#	p172
			0.90pF	±0.1pF	GQM1555C2DR90BB01#	p172
				±0.25pF	GQM1555C2DR90CB01#	p172
			1.0pF	±0.1pF	GQM1555C2D1R0BB01#	p172
				±0.25pF	GQM1555C2D1R0CB01#	p172
			1.1pF	±0.1pF	GQM1555C2D1R1BB01#	p172
				±0.25pF	GQM1555C2D1R1CB01#	p172
			1.2pF	±0.1pF	GQM1555C2D1R2BB01#	p172
				±0.25pF	GQM1555C2D1R2CB01#	p172
			1.3pF	±0.1pF	GQM1555C2D1R3BB01#	p172
				±0.25pF	GQM1555C2D1R3CB01#	p172
			1.5pF	±0.1pF	GQM1555C2D1R5BB01#	p172
				±0.25pF	GQM1555C2D1R5CB01#	p172
			1.6pF	±0.1pF	GQM1555C2D1R6BB01#	p172
				±0.25pF	GQM1555C2D1R6CB01#	p172
			1.8pF	±0.1pF	GQM1555C2D1R8BB01#	p172
				±0.25pF	GQM1555C2D1R8CB01#	p172
			2.0pF	±0.1pF	GQM1555C2D2R0BB01#	p172
				±0.25pF	GQM1555C2D2R0CB01#	p172
			2.2pF	±0.1pF	GQM1555C2D2R2BB01#	p172
				±0.25pF	GQM1555C2D2R2CB01#	p172
			2.4pF	±0.1pF	GQM1555C2D2R4BB01#	p172
				±0.25pF	GQM1555C2D2R4CB01#	p172
			2.7pF	±0.1pF	GQM1555C2D2R7BB01#	p172
				±0.25pF	GQM1555C2D2R7CB01#	p172
			3.0pF	±0.1pF	GQM1555C2D3R0BB01#	p172
				±0.25pF	GQM1555C2D3R0CB01#	p172
			3.3pF	±0.1pF	GQM1555C2D3R3BB01#	p172
				±0.25pF	GQM1555C2D3R3CB01#	p172
			3.6pF	±0.1pF	GQM1555C2D3R6BB01#	p172
				±0.25pF	GQM1555C2D3R6CB01#	p172
			3.9pF	±0.1pF	GQM1555C2D3R9BB01#	p172
				±0.25pF	GQM1555C2D3R9CB01#	p172
			4.0pF	±0.1pF	GQM1555C2D4R0BB01#	p172
				±0.25pF	GQM1555C2D4R0CB01#	p172
			4.3pF	±0.1pF	GQM1555C2D4R3BB01#	p172
				±0.25pF	GQM1555C2D4R3CB01#	p172
			4.7pF	±0.1pF	GQM1555C2D4R7BB01#	p172
				±0.25pF	GQM1555C2D4R7CB01#	p172
			5.0pF	±0.1pF	GQM1555C2D5R0BB01#	p172
				±0.25pF	GQM1555C2D5R0CB01#	p172
			5.1pF	±0.1pF	GQM1555C2D5R1BB01#	p172
				±0.25pF	GQM1555C2D5R1CB01#	p172
			5.6pF	±0.1pF	GQM1555C2D5R6BB01#	p172
				±0.25pF	GQM1555C2D5R6CB01#	p172
			6.0pF	±0.1pF	GQM1555C2D6R0BB01#	p172
				±0.25pF	GQM1555C2D6R0CB01#	p172
			6.2pF	±0.1pF	GQM1555C2D6R2BB01#	p172
				±0.25pF	GQM1555C2D6R2CB01#	p172
			6.8pF	±0.1pF	GQM1555C2D6R8BB01#	p172
				±0.25pF	GQM1555C2D6R8CB01#	p172
			7.0pF	±0.1pF	GQM1555C2D7R0BB01#	p172
				±0.25pF	GQM1555C2D7R0CB01#	p172
			7.5pF	±0.1pF	GQM1555C2D7R5BB01#	p172
				±0.25pF	GQM1555C2D7R5CB01#	p172
			8.0pF	±0.1pF	GQM1555C2D8R0BB01#	p172
				±0.25pF	GQM1555C2D8R0CB01#	p172
			8.2pF	±0.1pF	GQM1555C2D8R2BB01#	p172
				±0.25pF	GQM1555C2D8R2CB01#	p172
			9.0pF	±0.1pF	GQM1555C2D9R0BB01#	p172
				±0.25pF	GQM1555C2D9R0CB01#	p172
			9.1pF	±0.1pF	GQM1555C2D9R1BB01#	p172
				±0.25pF	GQM1555C2D9R1CB01#	p172
			10pF	±2%	GQM1555C2D100GB01#	p172
				±5%	GQM1555C2D100JB01#	p172
			11pF	±2%	GQM1555C2D110GB01#	p172
				±5%	GQM1555C2D110JB01#	p172
			12pF	±2%	GQM1555C2D120GB01#	p172
				±5%	GQM1555C2D120JB01#	p172
			13pF	±2%	GQM1555C2D130GB01#	p172
				±5%	GQM1555C2D130JB01#	p172
			15pF	±2%	GQM1555C2D150GB01#	p172
				±5%	GQM1555C2D150JB01#	p172
			16pF	±2%	GQM1555C2D160GB01#	p172
				±5%	GQM1555C2D160JB01#	p172
			18pF	±2%	GQM1555C2D180GB01#	p172
				±5%	GQM1555C2D180JB01#	p172
			20pF	±2%	GQM1555C2D200GB01#	p172
				±5%	GQM1555C2D200JB01#	p172
			22pF	±2%	GQM1555C2D220GB01#	p172
				±5%	GQM1555C2D220JB01#	p172
			24pF	±2%	GQM1555C2D240GB01#	p172
				±5%	GQM1555C2D240JB01#	p172
			27pF	±2%	GQM1555C2D270GB01#	p172
				±5%	GQM1555C2D270JB01#	p172
			30pF	±2%	GQM1555C2D300GB01#	p172
				±5%	GQM1555C2D300JB01#	p172
			33pF	±2%	GQM1555C2D330GB01#	p172
				±5%	GQM1555C2D330JB01#	p172
	100Vdc	C0G	36pF	±2%	GQM1555C2A360GB01#	p172
				±5%	GQM1555C2A360JB01#	p172

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GQM Series Temperature Compensating Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	100Vdc	C0G	39pF	±2%	**GQM1555C2A390GB01#**	p172
				±5%	**GQM1555C2A390JB01#**	p172
			43pF	±2%	**GQM1555C2A430GB01#**	p172
				±5%	**GQM1555C2A430JB01#**	p172
			47pF	±2%	**GQM1555C2A470GB01#**	p172
				±5%	**GQM1555C2A470JB01#**	p172

1.6×0.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.8mm	250Vdc	C0G	1.0pF	±0.1pF	**GQM1875C2E1R0BB12#**	p178
				±0.25pF	**GQM1875C2E1R0CB12#**	p178
			1.1pF	±0.1pF	**GQM1875C2E1R1BB12#**	p178
				±0.25pF	**GQM1875C2E1R1CB12#**	p178
			1.2pF	±0.1pF	**GQM1875C2E1R2BB12#**	p178
				±0.25pF	**GQM1875C2E1R2CB12#**	p178
			1.3pF	±0.1pF	**GQM1875C2E1R3BB12#**	p178
				±0.25pF	**GQM1875C2E1R3CB12#**	p178
			1.5pF	±0.1pF	**GQM1875C2E1R5BB12#**	p178
				±0.25pF	**GQM1875C2E1R5CB12#**	p178
			1.6pF	±0.1pF	**GQM1875C2E1R6BB12#**	p178
				±0.25pF	**GQM1875C2E1R6CB12#**	p178
			1.8pF	±0.1pF	**GQM1875C2E1R8BB12#**	p178
				±0.25pF	**GQM1875C2E1R8CB12#**	p178
			2.0pF	±0.1pF	**GQM1875C2E2R0BB12#**	p178
				±0.25pF	**GQM1875C2E2R0CB12#**	p178
			2.2pF	±0.1pF	**GQM1875C2E2R2BB12#**	p178
				±0.25pF	**GQM1875C2E2R2CB12#**	p178
			2.4pF	±0.1pF	**GQM1875C2E2R4BB12#**	p178
				±0.25pF	**GQM1875C2E2R4CB12#**	p178
			2.7pF	±0.1pF	**GQM1875C2E2R7BB12#**	p178
				±0.25pF	**GQM1875C2E2R7CB12#**	p178
			3.0pF	±0.1pF	**GQM1875C2E3R0BB12#**	p178
				±0.25pF	**GQM1875C2E3R0CB12#**	p178
			3.3pF	±0.1pF	**GQM1875C2E3R3BB12#**	p178
				±0.25pF	**GQM1875C2E3R3CB12#**	p178
			3.6pF	±0.1pF	**GQM1875C2E3R6BB12#**	p178
				±0.25pF	**GQM1875C2E3R6CB12#**	p178
			3.9pF	±0.1pF	**GQM1875C2E3R9BB12#**	p178
				±0.25pF	**GQM1875C2E3R9CB12#**	p178
			4.0pF	±0.1pF	**GQM1875C2E4R0BB12#**	p178
				±0.25pF	**GQM1875C2E4R0CB12#**	p178
			4.3pF	±0.1pF	**GQM1875C2E4R3BB12#**	p178
				±0.25pF	**GQM1875C2E4R3CB12#**	p178
			4.7pF	±0.1pF	**GQM1875C2E4R7BB12#**	p178
				±0.25pF	**GQM1875C2E4R7CB12#**	p178
			5.0pF	±0.1pF	**GQM1875C2E5R0BB12#**	p178
				±0.25pF	**GQM1875C2E5R0CB12#**	p178
			5.1pF	±0.25pF	**GQM1875C2E5R1CB12#**	p178
				±0.5pF	**GQM1875C2E5R1DB12#**	p178
			5.6pF	±0.25pF	**GQM1875C2E5R6CB12#**	p178
				±0.5pF	**GQM1875C2E5R6DB12#**	p178
			6.0pF	±0.25pF	**GQM1875C2E6R0CB12#**	p178
0.8mm	250Vdc	C0G	6.0pF	±0.5pF	**GQM1875C2E6R0DB12#**	p178
			6.2pF	±0.25pF	**GQM1875C2E6R2CB12#**	p178
				±0.5pF	**GQM1875C2E6R2DB12#**	p178
			6.8pF	±0.25pF	**GQM1875C2E6R8CB12#**	p178
				±0.5pF	**GQM1875C2E6R8DB12#**	p178
			7.0pF	±0.25pF	**GQM1875C2E7R0CB12#**	p178
				±0.5pF	**GQM1875C2E7R0DB12#**	p178
			7.5pF	±0.25pF	**GQM1875C2E7R5CB12#**	p178
				±0.5pF	**GQM1875C2E7R5DB12#**	p178
			8.0pF	±0.25pF	**GQM1875C2E8R0CB12#**	p178
				±0.5pF	**GQM1875C2E8R0DB12#**	p178
			8.2pF	±0.25pF	**GQM1875C2E8R2CB12#**	p178
				±0.5pF	**GQM1875C2E8R2DB12#**	p178
			9.0pF	±0.25pF	**GQM1875C2E9R0CB12#**	p178
				±0.5pF	**GQM1875C2E9R0DB12#**	p178
			9.1pF	±0.25pF	**GQM1875C2E9R1CB12#**	p178
				±0.5pF	**GQM1875C2E9R1DB12#**	p178
			10pF	±2%	**GQM1875C2E100GB12#**	p178
				±5%	**GQM1875C2E100JB12#**	p178
			11pF	±2%	**GQM1875C2E110GB12#**	p178
				±5%	**GQM1875C2E110JB12#**	p178
			12pF	±2%	**GQM1875C2E120GB12#**	p178
				±5%	**GQM1875C2E120JB12#**	p178
			13pF	±2%	**GQM1875C2E130GB12#**	p178
				±5%	**GQM1875C2E130JB12#**	p178
			15pF	±2%	**GQM1875C2E150GB12#**	p178
				±5%	**GQM1875C2E150JB12#**	p178
			16pF	±2%	**GQM1875C2E160GB12#**	p178
				±5%	**GQM1875C2E160JB12#**	p178
			18pF	±2%	**GQM1875C2E180GB12#**	p178
				±5%	**GQM1875C2E180JB12#**	p178
			20pF	±2%	**GQM1875C2E200GB12#**	p178
				±5%	**GQM1875C2E200JB12#**	p178
			22pF	±2%	**GQM1875C2E220GB12#**	p178
				±5%	**GQM1875C2E220JB12#**	p178
			24pF	±2%	**GQM1875C2E240GB12#**	p178
				±5%	**GQM1875C2E240JB12#**	p178
			27pF	±2%	**GQM1875C2E270GB12#**	p178
				±5%	**GQM1875C2E270JB12#**	p178
			30pF	±2%	**GQM1875C2E300GB12#**	p178
				±5%	**GQM1875C2E300JB12#**	p178
			33pF	±2%	**GQM1875C2E330GB12#**	p178
				±5%	**GQM1875C2E330JB12#**	p178
			36pF	±2%	**GQM1875C2E360GB12#**	p178
				±5%	**GQM1875C2E360JB12#**	p178
			39pF	±2%	**GQM1875C2E390GB12#**	p178
				±5%	**GQM1875C2E390JB12#**	p178
			43pF	±2%	**GQM1875C2E430GB12#**	p178
				±5%	**GQM1875C2E430JB12#**	p178
			47pF	±2%	**GQM1875C2E470GB12#**	p178
				±5%	**GQM1875C2E470JB12#**	p178
		X8G	1.0pF	±0.1pF	**GQM1875G2E1R0BB12#**	p175
				±0.25pF	**GQM1875G2E1R0CB12#**	p175
			1.1pF	±0.1pF	**GQM1875G2E1R1BB12#**	p175

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GQM Series Temperature Compensating Type Part Number List

(→ 1.6×0.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.8mm	250Vdc	X8G	1.1pF	±0.25pF	GQM1875G2E1R1CB12#	p175
			1.2pF	±0.1pF	GQM1875G2E1R2BB12#	p175
				±0.25pF	GQM1875G2E1R2CB12#	p175
			1.3pF	±0.1pF	GQM1875G2E1R3BB12#	p175
				±0.25pF	GQM1875G2E1R3CB12#	p175
			1.5pF	±0.1pF	GQM1875G2E1R5BB12#	p175
				±0.25pF	GQM1875G2E1R5CB12#	p175
			1.6pF	±0.1pF	GQM1875G2E1R6BB12#	p175
				±0.25pF	GQM1875G2E1R6CB12#	p175
			1.8pF	±0.1pF	GQM1875G2E1R8BB12#	p175
				±0.25pF	GQM1875G2E1R8CB12#	p175
			2.0pF	±0.1pF	GQM1875G2E2R0BB12#	p175
				±0.25pF	GQM1875G2E2R0CB12#	p175
			2.2pF	±0.1pF	GQM1875G2E2R2BB12#	p175
				±0.25pF	GQM1875G2E2R2CB12#	p175
			2.4pF	±0.1pF	GQM1875G2E2R4BB12#	p175
				±0.25pF	GQM1875G2E2R4CB12#	p175
			2.7pF	±0.1pF	GQM1875G2E2R7BB12#	p175
				±0.25pF	GQM1875G2E2R7CB12#	p175
			3.0pF	±0.1pF	GQM1875G2E3R0BB12#	p175
				±0.25pF	GQM1875G2E3R0CB12#	p175
			3.3pF	±0.1pF	GQM1875G2E3R3BB12#	p175
				±0.25pF	GQM1875G2E3R3CB12#	p175
			3.6pF	±0.1pF	GQM1875G2E3R6BB12#	p175
				±0.25pF	GQM1875G2E3R6CB12#	p175
			3.9pF	±0.1pF	GQM1875G2E3R9BB12#	p175
				±0.25pF	GQM1875G2E3R9CB12#	p175
			4.0pF	±0.1pF	GQM1875G2E4R0BB12#	p175
				±0.25pF	GQM1875G2E4R0CB12#	p175
			4.3pF	±0.1pF	GQM1875G2E4R3BB12#	p175
				±0.25pF	GQM1875G2E4R3CB12#	p175
			4.7pF	±0.1pF	GQM1875G2E4R7BB12#	p175
				±0.25pF	GQM1875G2E4R7CB12#	p175
			5.0pF	±0.1pF	GQM1875G2E5R0BB12#	p175
				±0.25pF	GQM1875G2E5R0CB12#	p175
			5.1pF	±0.25pF	GQM1875G2E5R1CB12#	p175
				±0.5pF	GQM1875G2E5R1DB12#	p175
			5.6pF	±0.25pF	GQM1875G2E5R6CB12#	p175
				±0.5pF	GQM1875G2E5R6DB12#	p175
			6.0pF	±0.25pF	GQM1875G2E6R0CB12#	p175
				±0.5pF	GQM1875G2E6R0DB12#	p175
			6.2pF	±0.25pF	GQM1875G2E6R2CB12#	p175
				±0.5pF	GQM1875G2E6R2DB12#	p175
			6.8pF	±0.25pF	GQM1875G2E6R8CB12#	p175
				±0.5pF	GQM1875G2E6R8DB12#	p175
			7.0pF	±0.25pF	GQM1875G2E7R0CB12#	p175
				±0.5pF	GQM1875G2E7R0DB12#	p175
			7.5pF	±0.25pF	GQM1875G2E7R5CB12#	p175
				±0.5pF	GQM1875G2E7R5DB12#	p175
			8.0pF	±0.25pF	GQM1875G2E8R0CB12#	p175
				±0.5pF	GQM1875G2E8R0DB12#	p175
			8.2pF	±0.25pF	GQM1875G2E8R2CB12#	p175
				±0.5pF	GQM1875G2E8R2DB12#	p175
			9.0pF	±0.25pF	GQM1875G2E9R0CB12#	p175

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.8mm	250Vdc	X8G	9.0pF	±0.5pF	GQM1875G2E9R0DB12#	p175
			9.1pF	±0.25pF	GQM1875G2E9R1CB12#	p175
				±0.5pF	GQM1875G2E9R1DB12#	p175
			10pF	±2%	GQM1875G2E100GB12#	p175
				±5%	GQM1875G2E100JB12#	p175
			11pF	±2%	GQM1875G2E110GB12#	p175
				±5%	GQM1875G2E110JB12#	p175
			12pF	±2%	GQM1875G2E120GB12#	p175
				±5%	GQM1875G2E120JB12#	p175
			13pF	±2%	GQM1875G2E130GB12#	p175
				±5%	GQM1875G2E130JB12#	p175
			15pF	±2%	GQM1875G2E150GB12#	p175
				±5%	GQM1875G2E150JB12#	p175
			16pF	±2%	GQM1875G2E160GB12#	p175
				±5%	GQM1875G2E160JB12#	p175
			18pF	±2%	GQM1875G2E180GB12#	p175
				±5%	GQM1875G2E180JB12#	p175
			20pF	±2%	GQM1875G2E200GB12#	p175
				±5%	GQM1875G2E200JB12#	p175
			22pF	±2%	GQM1875G2E220GB12#	p175
				±5%	GQM1875G2E220JB12#	p175
			24pF	±2%	GQM1875G2E240GB12#	p175
				±5%	GQM1875G2E240JB12#	p175
			27pF	±2%	GQM1875G2E270GB12#	p175
				±5%	GQM1875G2E270JB12#	p175
			30pF	±2%	GQM1875G2E300GB12#	p175
				±5%	GQM1875G2E300JB12#	p175

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	500Vdc	X8G	1.0pF	±0.1pF	GQM2195G2H1R0BB12#	p175
				±0.25pF	GQM2195G2H1R0CB12#	p175
			1.1pF	±0.1pF	GQM2195G2H1R1BB12#	p175
				±0.25pF	GQM2195G2H1R1CB12#	p175
			1.2pF	±0.1pF	GQM2195G2H1R2BB12#	p175
				±0.25pF	GQM2195G2H1R2CB12#	p175
			1.3pF	±0.1pF	GQM2195G2H1R3BB12#	p175
				±0.25pF	GQM2195G2H1R3CB12#	p175
			1.5pF	±0.1pF	GQM2195G2H1R5BB12#	p175
				±0.25pF	GQM2195G2H1R5CB12#	p175
			1.6pF	±0.1pF	GQM2195G2H1R6BB12#	p175
				±0.25pF	GQM2195G2H1R6CB12#	p175
			1.8pF	±0.1pF	GQM2195G2H1R8BB12#	p175
				±0.25pF	GQM2195G2H1R8CB12#	p175
			2.0pF	±0.1pF	GQM2195G2H2R0BB12#	p175
				±0.25pF	GQM2195G2H2R0CB12#	p175
			2.2pF	±0.1pF	GQM2195G2H2R2BB12#	p175
				±0.25pF	GQM2195G2H2R2CB12#	p175
			2.4pF	±0.1pF	GQM2195G2H2R4BB12#	p175
				±0.25pF	GQM2195G2H2R4CB12#	p175
			2.7pF	±0.1pF	GQM2195G2H2R7BB12#	p175
				±0.25pF	GQM2195G2H2R7CB12#	p175

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GQM Series Temperature Compensating Type Part Number List

(→ 2.0×1.25mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	500Vdc	X8G	3.0pF	±0.1pF	GQM2195G2H3R0BB12#	p175
				±0.25pF	GQM2195G2H3R0CB12#	p175
			3.3pF	±0.1pF	GQM2195G2H3R3BB12#	p175
				±0.25pF	GQM2195G2H3R3CB12#	p175
			3.6pF	±0.1pF	GQM2195G2H3R6BB12#	p175
				±0.25pF	GQM2195G2H3R6CB12#	p175
			3.9pF	±0.1pF	GQM2195G2H3R9BB12#	p175
				±0.25pF	GQM2195G2H3R9CB12#	p175
			4.0pF	±0.1pF	GQM2195G2H4R0BB12#	p175
				±0.25pF	GQM2195G2H4R0CB12#	p175
			4.3pF	±0.1pF	GQM2195G2H4R3BB12#	p175
				±0.25pF	GQM2195G2H4R3CB12#	p175
			4.7pF	±0.1pF	GQM2195G2H4R7BB12#	p175
				±0.25pF	GQM2195G2H4R7CB12#	p175
			5.0pF	±0.1pF	GQM2195G2H5R0BB12#	p175
				±0.25pF	GQM2195G2H5R0CB12#	p175
			5.1pF	±0.25pF	GQM2195G2H5R1CB12#	p175
				±0.5pF	GQM2195G2H5R1DB12#	p175
			5.6pF	±0.25pF	GQM2195G2H5R6CB12#	p175
				±0.5pF	GQM2195G2H5R6DB12#	p175
			6.0pF	±0.25pF	GQM2195G2H6R0CB12#	p175
				±0.5pF	GQM2195G2H6R0DB12#	p175
			6.2pF	±0.25pF	GQM2195G2H6R2CB12#	p175
				±0.5pF	GQM2195G2H6R2DB12#	p175
			6.8pF	±0.25pF	GQM2195G2H6R8CB12#	p175
				±0.5pF	GQM2195G2H6R8DB12#	p175
			7.0pF	±0.25pF	GQM2195G2H7R0CB12#	p175
				±0.5pF	GQM2195G2H7R0DB12#	p175
			7.5pF	±0.25pF	GQM2195G2H7R5CB12#	p175
				±0.5pF	GQM2195G2H7R5DB12#	p175
			8.0pF	±0.25pF	GQM2195G2H8R0CB12#	p175
				±0.5pF	GQM2195G2H8R0DB12#	p175
			8.2pF	±0.25pF	GQM2195G2H8R2CB12#	p175
				±0.5pF	GQM2195G2H8R2DB12#	p175
			9.0pF	±0.25pF	GQM2195G2H9R0CB12#	p175
				±0.5pF	GQM2195G2H9R0DB12#	p175
			9.1pF	±0.25pF	GQM2195G2H9R1CB12#	p175
				±0.5pF	GQM2195G2H9R1DB12#	p175
			10pF	±2%	GQM2195G2H100GB12#	p175
				±5%	GQM2195G2H100JB12#	p175
			11pF	±2%	GQM2195G2H110GB12#	p175
				±5%	GQM2195G2H110JB12#	p175
			12pF	±2%	GQM2195G2H120GB12#	p175
				±5%	GQM2195G2H120JB12#	p175
			13pF	±2%	GQM2195G2H130GB12#	p175
				±5%	GQM2195G2H130JB12#	p175
			15pF	±2%	GQM2195G2H150GB12#	p175
				±5%	GQM2195G2H150JB12#	p175
			16pF	±2%	GQM2195G2H160GB12#	p175
				±5%	GQM2195G2H160JB12#	p175
			18pF	±2%	GQM2195G2H180GB12#	p175
				±5%	GQM2195G2H180JB12#	p175
			20pF	±2%	GQM2195G2H200GB12#	p175
				±5%	GQM2195G2H200JB12#	p175

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	500Vdc	X8G	22pF	±2%	GQM2195G2H220GB12#	p175
				±5%	GQM2195G2H220JB12#	p175
	250Vdc	C0G	1.0pF	±0.1pF	GQM2195C2E1R0BB12#	p178
				±0.25pF	GQM2195C2E1R0CB12#	p178
			1.1pF	±0.1pF	GQM2195C2E1R1BB12#	p178
				±0.25pF	GQM2195C2E1R1CB12#	p178
			1.2pF	±0.1pF	GQM2195C2E1R2BB12#	p178
				±0.25pF	GQM2195C2E1R2CB12#	p178
			1.3pF	±0.1pF	GQM2195C2E1R3BB12#	p178
				±0.25pF	GQM2195C2E1R3CB12#	p178
			1.5pF	±0.1pF	GQM2195C2E1R5BB12#	p178
				±0.25pF	GQM2195C2E1R5CB12#	p178
			1.6pF	±0.1pF	GQM2195C2E1R6BB12#	p178
				±0.25pF	GQM2195C2E1R6CB12#	p178
			1.8pF	±0.1pF	GQM2195C2E1R8BB12#	p178
				±0.25pF	GQM2195C2E1R8CB12#	p178
			2.0pF	±0.1pF	GQM2195C2E2R0BB12#	p178
				±0.25pF	GQM2195C2E2R0CB12#	p178
			2.2pF	±0.1pF	GQM2195C2E2R2BB12#	p178
				±0.25pF	GQM2195C2E2R2CB12#	p178
			2.4pF	±0.1pF	GQM2195C2E2R4BB12#	p178
				±0.25pF	GQM2195C2E2R4CB12#	p178
			2.7pF	±0.1pF	GQM2195C2E2R7BB12#	p178
				±0.25pF	GQM2195C2E2R7CB12#	p178
			3.0pF	±0.1pF	GQM2195C2E3R0BB12#	p178
				±0.25pF	GQM2195C2E3R0CB12#	p178
			3.3pF	±0.1pF	GQM2195C2E3R3BB12#	p178
				±0.25pF	GQM2195C2E3R3CB12#	p178
			3.6pF	±0.1pF	GQM2195C2E3R6BB12#	p178
				±0.25pF	GQM2195C2E3R6CB12#	p178
			3.9pF	±0.1pF	GQM2195C2E3R9BB12#	p178
				±0.25pF	GQM2195C2E3R9CB12#	p178
			4.0pF	±0.1pF	GQM2195C2E4R0BB12#	p178
				±0.25pF	GQM2195C2E4R0CB12#	p178
			4.3pF	±0.1pF	GQM2195C2E4R3BB12#	p178
				±0.25pF	GQM2195C2E4R3CB12#	p178
			4.7pF	±0.1pF	GQM2195C2E4R7BB12#	p178
				±0.25pF	GQM2195C2E4R7CB12#	p178
			5.0pF	±0.1pF	GQM2195C2E5R0BB12#	p178
				±0.25pF	GQM2195C2E5R0CB12#	p178
			5.1pF	±0.25pF	GQM2195C2E5R1CB12#	p178
				±0.5pF	GQM2195C2E5R1DB12#	p178
			5.6pF	±0.25pF	GQM2195C2E5R6CB12#	p178
				±0.5pF	GQM2195C2E5R6DB12#	p178
			6.0pF	±0.25pF	GQM2195C2E6R0CB12#	p178
				±0.5pF	GQM2195C2E6R0DB12#	p178
			6.2pF	±0.25pF	GQM2195C2E6R2CB12#	p178
				±0.5pF	GQM2195C2E6R2DB12#	p178
			6.8pF	±0.25pF	GQM2195C2E6R8CB12#	p178
				±0.5pF	GQM2195C2E6R8DB12#	p178
			7.0pF	±0.25pF	GQM2195C2E7R0CB12#	p178
				±0.5pF	GQM2195C2E7R0DB12#	p178
			7.5pF	±0.25pF	GQM2195C2E7R5CB12#	p178
				±0.5pF	GQM2195C2E7R5DB12#	p178

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GQM Series Temperature Compensating Type Part Number List

(→ 2.0×1.25mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	250Vdc	C0G	8.0pF	±0.25pF	**GQM2195C2E8R0CB12#**	p178
				±0.5pF	**GQM2195C2E8R0DB12#**	p178
			8.2pF	±0.25pF	**GQM2195C2E8R2CB12#**	p178
				±0.5pF	**GQM2195C2E8R2DB12#**	p178
			9.0pF	±0.25pF	**GQM2195C2E9R0CB12#**	p178
				±0.5pF	**GQM2195C2E9R0DB12#**	p178
			9.1pF	±0.25pF	**GQM2195C2E9R1CB12#**	p178
				±0.5pF	**GQM2195C2E9R1DB12#**	p178
			10pF	±2%	**GQM2195C2E100GB12#**	p178
				±5%	**GQM2195C2E100JB12#**	p178
			11pF	±2%	**GQM2195C2E110GB12#**	p178
				±5%	**GQM2195C2E110JB12#**	p178
			12pF	±2%	**GQM2195C2E120GB12#**	p178
				±5%	**GQM2195C2E120JB12#**	p178
			13pF	±2%	**GQM2195C2E130GB12#**	p178
				±5%	**GQM2195C2E130JB12#**	p178
			15pF	±2%	**GQM2195C2E150GB12#**	p178
				±5%	**GQM2195C2E150JB12#**	p178
			16pF	±2%	**GQM2195C2E160GB12#**	p178
				±5%	**GQM2195C2E160JB12#**	p178
			18pF	±2%	**GQM2195C2E180GB12#**	p178
				±5%	**GQM2195C2E180JB12#**	p178
			20pF	±2%	**GQM2195C2E200GB12#**	p178
				±5%	**GQM2195C2E200JB12#**	p178
			22pF	±2%	**GQM2195C2E220GB12#**	p178
				±5%	**GQM2195C2E220JB12#**	p178
			24pF	±2%	**GQM2195C2E240GB12#**	p178
				±5%	**GQM2195C2E240JB12#**	p178
			27pF	±2%	**GQM2195C2E270GB12#**	p178
				±5%	**GQM2195C2E270JB12#**	p178
			30pF	±2%	**GQM2195C2E300GB12#**	p178
				±5%	**GQM2195C2E300JB12#**	p178
			33pF	±2%	**GQM2195C2E330GB12#**	p178
				±5%	**GQM2195C2E330JB12#**	p178
			36pF	±2%	**GQM2195C2E360GB12#**	p178
				±5%	**GQM2195C2E360JB12#**	p178
			39pF	±2%	**GQM2195C2E390GB12#**	p178
				±5%	**GQM2195C2E390JB12#**	p178
			43pF	±2%	**GQM2195C2E430GB12#**	p178
				±5%	**GQM2195C2E430JB12#**	p178
			47pF	±2%	**GQM2195C2E470GB12#**	p178
				±5%	**GQM2195C2E470JB12#**	p178
			51pF	±2%	**GQM2195C2E510GB12#**	p178
				±5%	**GQM2195C2E510JB12#**	p178
			56pF	±2%	**GQM2195C2E560GB12#**	p178
				±5%	**GQM2195C2E560JB12#**	p178
			62pF	±2%	**GQM2195C2E620GB12#**	p178
				±5%	**GQM2195C2E620JB12#**	p178
			68pF	±2%	**GQM2195C2E680GB12#**	p178
				±5%	**GQM2195C2E680JB12#**	p178
			75pF	±2%	**GQM2195C2E750GB12#**	p178
				±5%	**GQM2195C2E750JB12#**	p178
			82pF	±2%	**GQM2195C2E820GB12#**	p178
				±5%	**GQM2195C2E820JB12#**	p178

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	250Vdc	C0G	91pF	±2%	**GQM2195C2E910GB12#**	p178
				±5%	**GQM2195C2E910JB12#**	p178
			100pF	±2%	**GQM2195C2E101GB12#**	p178
				±5%	**GQM2195C2E101JB12#**	p178
		X8G	1.0pF	±0.1pF	**GQM2195G2E1R0BB12#**	p175
				±0.25pF	**GQM2195G2E1R0CB12#**	p175
			1.1pF	±0.1pF	**GQM2195G2E1R1BB12#**	p175
				±0.25pF	**GQM2195G2E1R1CB12#**	p175
			1.2pF	±0.1pF	**GQM2195G2E1R2BB12#**	p175
				±0.25pF	**GQM2195G2E1R2CB12#**	p175
			1.3pF	±0.1pF	**GQM2195G2E1R3BB12#**	p175
				±0.25pF	**GQM2195G2E1R3CB12#**	p175
			1.5pF	±0.1pF	**GQM2195G2E1R5BB12#**	p175
				±0.25pF	**GQM2195G2E1R5CB12#**	p175
			1.6pF	±0.1pF	**GQM2195G2E1R6BB12#**	p175
				±0.25pF	**GQM2195G2E1R6CB12#**	p175
			1.8pF	±0.1pF	**GQM2195G2E1R8BB12#**	p175
				±0.25pF	**GQM2195G2E1R8CB12#**	p175
			2.0pF	±0.1pF	**GQM2195G2E2R0BB12#**	p175
				±0.25pF	**GQM2195G2E2R0CB12#**	p175
			2.2pF	±0.1pF	**GQM2195G2E2R2BB12#**	p175
				±0.25pF	**GQM2195G2E2R2CB12#**	p175
			2.4pF	±0.1pF	**GQM2195G2E2R4BB12#**	p175
				±0.25pF	**GQM2195G2E2R4CB12#**	p175
			2.7pF	±0.1pF	**GQM2195G2E2R7BB12#**	p175
				±0.25pF	**GQM2195G2E2R7CB12#**	p175
			3.0pF	±0.1pF	**GQM2195G2E3R0BB12#**	p175
				±0.25pF	**GQM2195G2E3R0CB12#**	p175
			3.3pF	±0.1pF	**GQM2195G2E3R3BB12#**	p175
				±0.25pF	**GQM2195G2E3R3CB12#**	p175
			3.6pF	±0.1pF	**GQM2195G2E3R6BB12#**	p175
				±0.25pF	**GQM2195G2E3R6CB12#**	p175
			3.9pF	±0.1pF	**GQM2195G2E3R9BB12#**	p175
				±0.25pF	**GQM2195G2E3R9CB12#**	p175
			4.0pF	±0.1pF	**GQM2195G2E4R0BB12#**	p175
				±0.25pF	**GQM2195G2E4R0CB12#**	p175
			4.3pF	±0.1pF	**GQM2195G2E4R3BB12#**	p175
				±0.25pF	**GQM2195G2E4R3CB12#**	p175
			4.7pF	±0.1pF	**GQM2195G2E4R7BB12#**	p175
				±0.25pF	**GQM2195G2E4R7CB12#**	p175
			5.0pF	±0.1pF	**GQM2195G2E5R0BB12#**	p175
				±0.25pF	**GQM2195G2E5R0CB12#**	p175
			5.1pF	±0.25pF	**GQM2195G2E5R1CB12#**	p175
				±0.5pF	**GQM2195G2E5R1DB12#**	p175
			5.6pF	±0.25pF	**GQM2195G2E5R6CB12#**	p175
				±0.5pF	**GQM2195G2E5R6DB12#**	p175
			6.0pF	±0.25pF	**GQM2195G2E6R0CB12#**	p175
				±0.5pF	**GQM2195G2E6R0DB12#**	p175
			6.2pF	±0.25pF	**GQM2195G2E6R2CB12#**	p175
				±0.5pF	**GQM2195G2E6R2DB12#**	p175
			6.8pF	±0.25pF	**GQM2195G2E6R8CB12#**	p175
				±0.5pF	**GQM2195G2E6R8DB12#**	p175
			7.0pF	±0.25pF	**GQM2195G2E7R0CB12#**	p175
				±0.5pF	**GQM2195G2E7R0DB12#**	p175

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GQM Series Temperature Compensating Type Part Number List

(→ 2.0×1.25mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	250Vdc	X8G	7.5pF	±0.25pF	GQM2195G2E7R5CB12#	p175
				±0.5pF	GQM2195G2E7R5DB12#	p175
			8.0pF	±0.25pF	GQM2195G2E8R0CB12#	p175
				±0.5pF	GQM2195G2E8R0DB12#	p175
			8.2pF	±0.25pF	GQM2195G2E8R2CB12#	p175
				±0.5pF	GQM2195G2E8R2DB12#	p175
			9.0pF	±0.25pF	GQM2195G2E9R0CB12#	p175
				±0.5pF	GQM2195G2E9R0DB12#	p175
			9.1pF	±0.25pF	GQM2195G2E9R1CB12#	p175
				±0.5pF	GQM2195G2E9R1DB12#	p175
			10pF	±2%	GQM2195G2E100GB12#	p175
				±5%	GQM2195G2E100JB12#	p175
			11pF	±2%	GQM2195G2E110GB12#	p175
				±5%	GQM2195G2E110JB12#	p175
			12pF	±2%	GQM2195G2E120GB12#	p175
				±5%	GQM2195G2E120JB12#	p175
			13pF	±2%	GQM2195G2E130GB12#	p175
				±5%	GQM2195G2E130JB12#	p175
			15pF	±2%	GQM2195G2E150GB12#	p175
				±5%	GQM2195G2E150JB12#	p175
			16pF	±2%	GQM2195G2E160GB12#	p175
				±5%	GQM2195G2E160JB12#	p175
			18pF	±2%	GQM2195G2E180GB12#	p175
				±5%	GQM2195G2E180JB12#	p175
			20pF	±2%	GQM2195G2E200GB12#	p175
				±5%	GQM2195G2E200JB12#	p175
			22pF	±2%	GQM2195G2E220GB12#	p175
				±5%	GQM2195G2E220JB12#	p175
			24pF	±2%	GQM2195G2E240GB12#	p175
				±5%	GQM2195G2E240JB12#	p175
			27pF	±2%	GQM2195G2E270GB12#	p175
				±5%	GQM2195G2E270JB12#	p175
			30pF	±2%	GQM2195G2E300GB12#	p175
				±5%	GQM2195G2E300JB12#	p175
			33pF	±2%	GQM2195G2E330GB12#	p175
				±5%	GQM2195G2E330JB12#	p175
			36pF	±2%	GQM2195G2E360GB12#	p175
				±5%	GQM2195G2E360JB12#	p175
			39pF	±2%	GQM2195G2E390GB12#	p175
				±5%	GQM2195G2E390JB12#	p175
			43pF	±2%	GQM2195G2E430GB12#	p175
				±5%	GQM2195G2E430JB12#	p175
			47pF	±2%	GQM2195G2E470GB12#	p175
				±5%	GQM2195G2E470JB12#	p175
			51pF	±2%	GQM2195G2E510GB12#	p175
				±5%	GQM2195G2E510JB12#	p175
			56pF	±2%	GQM2195G2E560GB12#	p175
				±5%	GQM2195G2E560JB12#	p175
			62pF	±2%	GQM2195G2E620GB12#	p175
				±5%	GQM2195G2E620JB12#	p175
			68pF	±2%	GQM2195G2E680GB12#	p175
				±5%	GQM2195G2E680JB12#	p175
			75pF	±2%	GQM2195G2E750GB12#	p175
				±5%	GQM2195G2E750JB12#	p175

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	250Vdc	X8G	82pF	±2%	GQM2195G2E820GB12#	p175
				±5%	GQM2195G2E820JB12#	p175

2.8×2.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.35mm	500Vdc	C0G	1.0pF	±0.1pF	GQM22M5C2H1R0BB01#	p181
				±0.25pF	GQM22M5C2H1R0CB01#	p181
			1.1pF	±0.1pF	GQM22M5C2H1R1BB01#	p181
				±0.25pF	GQM22M5C2H1R1CB01#	p181
			1.2pF	±0.1pF	GQM22M5C2H1R2BB01#	p181
				±0.25pF	GQM22M5C2H1R2CB01#	p181
			1.3pF	±0.1pF	GQM22M5C2H1R3BB01#	p181
				±0.25pF	GQM22M5C2H1R3CB01#	p181
			1.5pF	±0.1pF	GQM22M5C2H1R5BB01#	p181
				±0.25pF	GQM22M5C2H1R5CB01#	p181
			1.6pF	±0.1pF	GQM22M5C2H1R6BB01#	p181
				±0.25pF	GQM22M5C2H1R6CB01#	p181
			1.8pF	±0.1pF	GQM22M5C2H1R8BB01#	p181
				±0.25pF	GQM22M5C2H1R8CB01#	p181
			2.0pF	±0.1pF	GQM22M5C2H2R0BB01#	p181
				±0.25pF	GQM22M5C2H2R0CB01#	p181
			2.2pF	±0.1pF	GQM22M5C2H2R2BB01#	p181
				±0.25pF	GQM22M5C2H2R2CB01#	p181
			2.4pF	±0.1pF	GQM22M5C2H2R4BB01#	p181
				±0.25pF	GQM22M5C2H2R4CB01#	p181
			2.7pF	±0.1pF	GQM22M5C2H2R7BB01#	p181
				±0.25pF	GQM22M5C2H2R7CB01#	p181
			3.0pF	±0.1pF	GQM22M5C2H3R0BB01#	p181
				±0.25pF	GQM22M5C2H3R0CB01#	p181
			3.3pF	±0.1pF	GQM22M5C2H3R3BB01#	p181
				±0.25pF	GQM22M5C2H3R3CB01#	p181
			3.6pF	±0.1pF	GQM22M5C2H3R6BB01#	p181
				±0.25pF	GQM22M5C2H3R6CB01#	p181
			3.9pF	±0.1pF	GQM22M5C2H3R9BB01#	p181
				±0.25pF	GQM22M5C2H3R9CB01#	p181
			4.0pF	±0.1pF	GQM22M5C2H4R0BB01#	p181
				±0.25pF	GQM22M5C2H4R0CB01#	p181
			4.3pF	±0.1pF	GQM22M5C2H4R3BB01#	p181
				±0.25pF	GQM22M5C2H4R3CB01#	p181
			4.7pF	±0.1pF	GQM22M5C2H4R7BB01#	p181
				±0.25pF	GQM22M5C2H4R7CB01#	p181
			5.0pF	±0.1pF	GQM22M5C2H5R0BB01#	p181
				±0.25pF	GQM22M5C2H5R0CB01#	p181
			5.1pF	±0.25pF	GQM22M5C2H5R1CB01#	p181
				±0.5pF	GQM22M5C2H5R1DB01#	p181
			5.6pF	±0.25pF	GQM22M5C2H5R6CB01#	p181
				±0.5pF	GQM22M5C2H5R6DB01#	p181
			6.0pF	±0.25pF	GQM22M5C2H6R0CB01#	p181
				±0.5pF	GQM22M5C2H6R0DB01#	p181
			6.2pF	±0.25pF	GQM22M5C2H6R2CB01#	p181
				±0.5pF	GQM22M5C2H6R2DB01#	p181
			6.8pF	±0.25pF	GQM22M5C2H6R8CB01#	p181

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GQM Series Temperature Compensating Type Part Number List

(→ 2.8×2.8mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.35mm	500Vdc	C0G	6.8pF	±0.5pF	**GQM22M5C2H6R8DB01#**	p181
			7.0pF	±0.25pF	**GQM22M5C2H7R0CB01#**	p181
				±0.5pF	**GQM22M5C2H7R0DB01#**	p181
			7.5pF	±0.25pF	**GQM22M5C2H7R5CB01#**	p181
				±0.5pF	**GQM22M5C2H7R5DB01#**	p181
			8.0pF	±0.25pF	**GQM22M5C2H8R0CB01#**	p181
				±0.5pF	**GQM22M5C2H8R0DB01#**	p181
			8.2pF	±0.25pF	**GQM22M5C2H8R2CB01#**	p181
				±0.5pF	**GQM22M5C2H8R2DB01#**	p181
			9.0pF	±0.25pF	**GQM22M5C2H9R0CB01#**	p181
				±0.5pF	**GQM22M5C2H9R0DB01#**	p181
			9.1pF	±0.25pF	**GQM22M5C2H9R1CB01#**	p181
				±0.5pF	**GQM22M5C2H9R1DB01#**	p181
			10pF	±2%	**GQM22M5C2H100GB01#**	p181
				±5%	**GQM22M5C2H100JB01#**	p181
			11pF	±2%	**GQM22M5C2H110GB01#**	p181
				±5%	**GQM22M5C2H110JB01#**	p181
			12pF	±2%	**GQM22M5C2H120GB01#**	p181
				±5%	**GQM22M5C2H120JB01#**	p181
			13pF	±2%	**GQM22M5C2H130GB01#**	p181
				±5%	**GQM22M5C2H130JB01#**	p181
			15pF	±2%	**GQM22M5C2H150GB01#**	p181
				±5%	**GQM22M5C2H150JB01#**	p181
			16pF	±2%	**GQM22M5C2H160GB01#**	p181
				±5%	**GQM22M5C2H160JB01#**	p181
			18pF	±2%	**GQM22M5C2H180GB01#**	p181
				±5%	**GQM22M5C2H180JB01#**	p181
			20pF	±2%	**GQM22M5C2H200GB01#**	p181
				±5%	**GQM22M5C2H200JB01#**	p181
			22pF	±2%	**GQM22M5C2H220GB01#**	p181
				±5%	**GQM22M5C2H220JB01#**	p181
			24pF	±2%	**GQM22M5C2H240GB01#**	p181
				±5%	**GQM22M5C2H240JB01#**	p181
			27pF	±2%	**GQM22M5C2H270GB01#**	p181
				±5%	**GQM22M5C2H270JB01#**	p181
			30pF	±2%	**GQM22M5C2H300GB01#**	p181
				±5%	**GQM22M5C2H300JB01#**	p181
			33pF	±2%	**GQM22M5C2H330GB01#**	p181
				±5%	**GQM22M5C2H330JB01#**	p181
			36pF	±2%	**GQM22M5C2H360GB01#**	p181
				±5%	**GQM22M5C2H360JB01#**	p181
			39pF	±2%	**GQM22M5C2H390GB01#**	p181
				±5%	**GQM22M5C2H390JB01#**	p181
			43pF	±2%	**GQM22M5C2H430GB01#**	p181
				±5%	**GQM22M5C2H430JB01#**	p181
			47pF	±2%	**GQM22M5C2H470GB01#**	p181
				±5%	**GQM22M5C2H470JB01#**	p181
			51pF	±2%	**GQM22M5C2H510GB01#**	p181
				±5%	**GQM22M5C2H510JB01#**	p181
			56pF	±2%	**GQM22M5C2H560GB01#**	p181
				±5%	**GQM22M5C2H560JB01#**	p181
			62pF	±2%	**GQM22M5C2H620GB01#**	p181
				±5%	**GQM22M5C2H620JB01#**	p181
			68pF	±2%	**GQM22M5C2H680GB01#**	p181

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.35mm	500Vdc	C0G	68pF	±5%	**GQM22M5C2H680JB01#**	p181
			75pF	±2%	**GQM22M5C2H750GB01#**	p181
				±5%	**GQM22M5C2H750JB01#**	p181
			82pF	±2%	**GQM22M5C2H820GB01#**	p181
				±5%	**GQM22M5C2H820JB01#**	p181
			91pF	±2%	**GQM22M5C2H910GB01#**	p181
				±5%	**GQM22M5C2H910JB01#**	p181
			100pF	±2%	**GQM22M5C2H101GB01#**	p181
				±5%	**GQM22M5C2H101JB01#**	p181

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GQM Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Applied Time: 1 to 5s Charge/discharge current: 50mA max. Test Voltage: Rated Voltage / Test Voltage 100V / 300% of Rated Voltage 200V / 250% of Rated Voltage
5	Insulation Resistance (I.R.)		More than 10000MΩ	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance / Frequency / Voltage C ≦ 1000pF / 1.0±0.1kHz / 0.5 to 5.0Vrms
7	Q		30pF and over: Q ≧ 1400 30pF and below: Q ≧ 800+20C C: Nominal Capacitance(pF)	
8	Temperature Characteristics of Capacitance		Nominal values of the temperature coefficient is shown in Rated value. But, the Capacitance Change under 25°C is shown in Table A. Capacitance Drift Within ±0.2% or ±0.05pF (Whichever is larger.)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. The capacitance drift is calculated by dividing the differences between the maximum and minimum measured values in the step 1, 3 and 5 by the cap. value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2
9	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate shown in Fig.3. Applied Force: 5N Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
11	Substrate Bending Test	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.1. Pressurization method: Shown in Fig.2 Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
		Capacitance Change	Within ±5% or ±0.5pF (Whichever is larger)	
12	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s
13	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Immersion time: 10±0.5s Exposure Time: 24±2h Preheat: 120 to 150°C for 1min
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

GQM Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±7.5% or ±0.75pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 200 30pF and below: Q ≧ 100+10C/3 C: Nominal Capacitance(pF)	
		I.R.	More than 500MΩ	
16	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±3% or ±0.3pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 350 10pF and over, 30pF and below: Q ≧ 275+5C/2 10pF and below: Q ≧ 200+10C C: Nominal Capacitance (pF)	
		I.R.	More than 1000MΩ	

Table A

Char.	Capacitance Change from 25°C(%)					
	-55°C		-30°C		-10°C	
	Max.	Min.	Max.	Min.	Max.	Min.
5C	0.58	-0.24	0.40	-0.17	0.25	-0.11

Continued on the following page.↗

GQM Series Specifications and Test Methods (1)

Continued from the preceding page.↘

Substrate Bending Test

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 0.8mm
  Copper foil thickness: 0.035mm
  : Solder resist (Coat with heat resistant resin for solder)



Part Number	Dimension (mm)		
	a	b	c
GQM15	0.4	1.5	0.5

Fig.1

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Pressurization Method



Fig.2

Adhesive Strength of Termination, Vibration, Temperature Sudden Change, High Temperature High Humidity (Steady) , Durability

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 1.6mm or 0.8mm
  Copper foil thickness: 0.035mm

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GQM15	0.4	1.5	0.5

Fig.3

2 GQM Series Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage : 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		More than 10000MΩ	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 1min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature :Room Temperature Capacitance: C ≦ 1000pF; Frequency: 1.0±0.1MHz; Voltage: 0.5 to 5.0Vrms
7	Q		30pF and over: Q ≧ 1400 30pF and below: Q ≧ 800+20C C: Nominal Capacitance(pF)	
8	Temperature Characteristics of Capacitance		Nominal values of the temperature coefficient is shown in Rated value. But, the Capacitance Change under 20°C/25°C is shown in Table A. Capacitance Drift Within ±0.2% or ±0.05pF (Whichever is larger.)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. The capacitance drift is calculated by dividing the differences between the maximum and minimum measured values in the step 1, 3 and 5 by the cap. value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2
9	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate shown in Fig.3. GQM18: Applied Force(N) 5 GQM21: Applied Force(N) 10 Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
11	Substrate Bending Test	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.1. Pressurization method: Shown in Fig.2 Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
		Capacitance Change	Within ±5% or ±0.5pF (Whichever is larger)	
12	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s

Continued on the following page.↗

GQM Series Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Immersion time: 10±0.5s Exposure Time: 24±2h Preheat: 120 to 150°C for 1min
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±7.5% or ±0.75pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 200 30pF and below: Q ≧ 100+10C/3 C: Nominal Capacitance(pF)	
		I.R.	More than 500MΩ	
16	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±3% or ±0.3pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 350 10pF and over, 30pF and below: Q ≧ 275+5C/2 10pF and below: Q ≧ 200+10C C: Nominal Capacitance (pF)	
		I.R.	More than 1000MΩ	

Table A

Char.	Capacitance Change from 20°C/25°C (%)							
	-55°C		-30°C		-25°C		-10°C	
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.
2C	0.82	-0.45	-	-	0.49	-0.27	0.33	-0.18
5C/5G	0.58	-0.24	0.40	-0.17	-	-	0.25	-0.11

Continued on the following page.↗

GQM Series Specifications and Test Methods (2)

Continued from the preceding page.↘

Substrate Bending Test

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 1.6mm
  Copper foil thickness: 0.035mm
  : Solder resist (Coat with heat resistant resin for solder)



Part Number	Dimension (mm)		
	a	b	c
GQM18	1.0	3.0	1.2
GQM21	1.2	4.0	1.65

Fig.1

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Pressurization Method



Fig.2

Adhesive Strength of Termination, Vibration, Temperature Sudden Change, High Temperature High Humidity (Steady) , Durability

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 1.6mm or 0.8mm
  Copper foil thickness: 0.035mm

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GQM18	1.0	3.0	1.2
GQM21	1.2	4.0	1.65

Fig.3

3 GQM Series Specifications and Test Methods (3)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		More than 10000MΩ	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance: C ≦ 1000pF; Frequency: 1.0±0.1kHz; Voltage: 0.5 to 5.0Vrms
7	Q		30pF and over: Q ≧ 1400 30pF and below: Q ≧ 800+20C C: Nominal Capacitance (pF)	
8	Temperature Characteristics of Capacitance		Nominal values of the temperature coefficient is shown in Rated value. But, the Capacitance Change under 20°C/25°C is shown in Table A. Capacitance Drift Within ±0.2% or ±0.05pF (Whichever is larger.)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. The capacitance drift is calculated by dividing the differences between the maximum and minimum measured values in the step 1, 3 and 5 by the cap. value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2
9	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate shown in Fig.3. Part Number GQM18: Applied Force(N) 5 Part Number GQM21: Applied Force(N) 10 Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
11	Substrate Bending Test	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.1. Pressurization method: Shown in Fig.2 Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
		Capacitance Change	Within ±5% or ±0.5pF (Whichever is larger)	
12	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s
13	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Immersion time: 10±0.5s Exposure Time: 24±2h Preheat: 120 to 150°C for 1min
		Capacitance Change	Within ±2.5% or ± 0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

GQM Series Specifications and Test Methods (3)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±7.5% or ±0.75pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 200 30pF and below: Q ≧ 100+10C/3 C: Nominal Capacitance(pF)	
		I.R.	More than 500MΩ	
16	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±3% or ±0.3pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 350 10pF and over, 30pF and below: Q ≧ 275+5C/2 10pF and below: Q ≧ 200+10C C: Nominal Capacitance (pF)	
		I.R.	More than 1000MΩ	

Table A

Char.	Capacitance Change from 20°C/25°C (%)							
	-55°C		-30°C		-25°C		-10°C	
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.
2C	0.82	-0.45	-	-	0.49	-0.27	0.33	-0.18
5C/5G	0.58	-0.24	0.40	-0.17	-	-	0.25	-0.11

Continued on the following page.↗

GQM Series Specifications and Test Methods (3)

Continued from the preceding page.↘

Substrate Bending Test

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 1.6mm
  Copper foil thickness: 0.035mm
  : Solder resist (Coat with heat resistant resin for solder)



Part Number	Dimension (mm)		
	a	b	c
GQM18	1.0	3.0	1.2
GQM21	1.2	4.0	1.65

Fig.1

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Pressurization Method



Fig.2

Adhesive Strength of Termination, Vibration, Temperature Sudden Change, High Temperature High Humidity (Steady) , Durability

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 1.6mm or 0.8mm
  Copper foil thickness: 0.035mm

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GQM18	1.0	3.0	1.2
GQM21	1.2	4.0	1.65

Fig.3

4 GQM Series Specifications and Test Methods (4)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		More than 10000MΩ	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance: C ≦ 1000pF; Frequency: 1.0±0.1kHz; Voltage: 0.5 to 5.0Vrms
7	Q		30pF and over: Q ≧ 1400 30pF and below: Q ≧ 800+20C C: Nominal Capacitance(pF)	
8	Temperature Characteristics of Capacitance		Nominal values of the temperature coefficient is shown in Rated value. But, the Capacitance Change under 25°C is shown in Table A. Capacitance Drift Within ±0.2% or ±0.05pF (Whichever is larger.)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. The capacitance drift is calculated by dividing the differences between the maximum and minimum measured values in the step 1, 3 and 5 by the cap. value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2
9	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate shown in Fig.3. Applied Force: 10N Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
11	Substrate Bending Test	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.1. Pressurization method: Shown in Fig.2 Flexure:1mm Holding Time: 5±1s Soldering Method: Reflow soldering
		Capacitance Change	Within ±5% or ±0.5pF (Whichever is larger)	
12	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s
13	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Immersion time: 10±0.5s Exposure Time: 24±2h Preheat: 120 to 150°C for 1min
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

GQM Series Specifications and Test Methods (4)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±7.5% or ±0.75pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 200 30pF and below: Q ≧ 100+10C/3 C: Nominal Capacitance(pF)	
		I.R.	More than 500MΩ	
16	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate shown in Fig.3. Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 150% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±3% or ±0.3pF (Whichever is larger)	
		Q	30pF and over: Q ≧ 350 10pF and over, 30pF and below: Q ≧ 275+5C/2 10pF and below: Q ≧ 200+10C C: Nominal Capacitance (pF)	
		I.R.	More than 1000MΩ	

Table A

Char.	Capacitance Change from 25°C(%)					
	-55°C		-30°C		-10°C	
	Max.	Min.	Max.	Min.	Max.	Min.
5C	0.58	-0.24	0.40	-0.17	0.25	-0.11

Continued on the following page.↗

GQM Series Specifications and Test Methods (4)

Continued from the preceding page.↘

Substrate Bending Test

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 1.6mm
  Copper foil thickness: 0.035mm
  : Solder resist (Coat with heat resistant resin for solder)



Part Number	Dimension (mm)		
	a	b	c
GQM22	2.2	5.0	2.9

Fig.1

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Pressurization Method



Fig.2

Adhesive Strength of Termination, Vibration, Temperature Sudden Change, High Temperature High Humidity (Steady) , Durability

- Test Substrate
  Material: Copper-clad laminated sheets for PCBs (Glass fabric base, epoxy resin)
  Thickness: 1.6mm or 0.8mm
  Copper foil thickness: 0.035mm

- Kind of Solder: Sn-3.0Ag-0.5Cu
- Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GQM22	2.2	5.0	2.9

Fig.3

Based on the Electrical Appliance and Material Safety Law of Japan Chip Multilayer Ceramic Capacitors for General Purpose

GA2 Series

Japanese Safety Law

WEB

This product is for commercial power supplies, compliant with the Electrical Appliance and Material Safety Law of Japan.

Features

1. **Sn plating is applied to the external electrodes, providing excellent solderability.**



<Example of Structure>

2. **Realized large capacitance value and small size while maintaining high withstand voltages by the multilayer structure.**

3. **This product is only for reflow soldering.**

4. **There are types for connections between lines and connections between lines and ground.**

Specifications

Size (mm)	4.5×2.0mm to 5.7×5.0mm
Rated Voltage	250Vac
Capacitance	470pF to 0.10μF
Main Applications	General purpose for Japan

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

GA2 Series High Dielectric Constant Type Part Number List

4.5×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	470pF	±20%	**GA242QR7E2471MW01#**	p186
			1000pF	±20%	**GA242QR7E2102MW01#**	p186

4.5×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	2200pF	±20%	**GA243QR7E2222MW01#**	p186
			3300pF	±20%	**GA243QR7E2332MW01#**	p186
			10000pF	±20%	**GA243QR7E2103MW01#**	p186
			22000pF	±20%	**GA243QR7E2223MW01#**	p186
2.0mm	250Vac	X7R	4700pF	±20%	**GA243DR7E2472MW01#**	p186
			47000pF	±20%	**GA243DR7E2473MW01#**	p186

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
2.0mm	250Vac	X7R	0.10μF	±20%	**GA255DR7E2104MW01#**	p186

*: Refers to the page of the “Specifications and Test Methods”.

Part number # indicates the package specification code.

1 GA2 Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 10000pF min.: AC575V (r.m.s.) less than 10000pF: AC1500V (r.m.s.) Applied Time: 60±1s Charge/discharge current: 50mA max.
4	Insulation Resistance (I.R.)		2000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Measurement Temperature: Room Temperature
5	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
6	Dissipation Factor (D.F.)		0.025 max.	
7	Temperature Characteristics of Capacitance		R7: Within ±15% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 •Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition (*1).
8	Discharge Test (Application: C < 10000pF) C: Nominal Capacitance		No defects or abnormalities.	As in below figure, discharge is made 50 times at 5s intervals from the capacitor (Cd) charged at DC voltage of specified.  Ct: Capacitor under test, Cd: 0.001μF R1: 1000Ω, R2: 100MΩ, R3: Surge resistance
9	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
10	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt) % Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
11	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition (*1). Preheat: GA242 size min.: 100 to 120°C for 1min and 170 to 200°C for 1min • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition (*1).
		Capacitance Change	Within ±10%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

*1 Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA2 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
13	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition (*1). • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition (*1).
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
15	Humidity Insulation	Appearance	No defects or abnormalities.	The capacitor shall be subjected to 40±2°C, relative humidity of 90 to 95% for 8h, and then removed in room condition (*1) for 16h until 5 cycles.
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
16	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h. Applied Voltage: Rated voltage Exposure Time: 24±2h at room condition (*1). • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition (*1).
		Capacitance Change	Within ±15%	
		D.F.	0.05 max.	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
17	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method". Test Temperature: Max. Operating Temp. ±3°C Charge/discharge current: 50mA max. Nominal Capacitance / Test Time / Test Voltage C ≧ 10000pF / 1000+48/-0h / AC300V (r.m.s.) C < 10000pF / 1500+48/-0h (*2) / AC500V (r.m.s.) *2 Except that once each hour the voltage is increased to AC1000V (r.m.s.) for 0.1s. Exposure Time: 24±2h at room condition (*1). • Pretreatment Apply test voltage for 1h±5min at test temperature. Remove and let sit for 24±2h at room condition (*1).
		Capacitance Change	Within ±20%	
		D.F.	0.05 max.	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	

*1 Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA2 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GRM42	3.5	7.0	2.4
GRM43	3.5	7.0	3.7
GRM52	4.5	8.0	3.2
GRM55	4.5	8.0	5.6

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension of Pattern (mm)			
	a	b	c	d
GRM42	3.5	7.0	2.4	1.0
GRM43	3.5	7.0	3.7	1.0
GRM52	4.5	8.0	3.2	1.0
GRM55	4.5	8.0	5.6	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose / IEC60384-14 Class X2

GA3 Series Type GB

Safety standard

WEB

IEC60384-14 X2 Class Certified Product

Features

① **International Standard (IEC60384-14) certified product.**

Please down load Safety Standard Certification (Type GB: X2) from here. WEB

② **Can be used as a Class X2 capacitor.**

Switching Power Supply - Class 1 Equipment



No.	Application	Recommend MLCC Type
C1	X Cap	Type: GB
C2	Y Cap	Type: GF
C3		
C4		
C5	Primary - Secondary Coupling	Type: GF×2

Switching Power Supply - Class 2 Equipment



No.	Application	Recommend MLCC Type
C1	X Cap	Type: GB
C2	Y Cap	Type: GF×2
C3		
C4	Primary - Secondary Coupling	

③ Realized large capacitance value and small size while maintaining high withstand voltages by the multilayer structure.



<Example of Structure>

④ Compared with conventional lead type capacitors, this product realized great reductions in size and height, with a volume of 1/10 or less, and height of 1/4 or less.

⑤ This product is only for reflow soldering.

Specifications

Size (mm)	5.7×5.0mm
Rated Voltage	250Vac
Capacitance	10000pF to 56000pF
Main Applications	AC-DC power supply

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

GA3 Series Type GB High Dielectric Constant Type Safety standard Part Number List

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	10000pF	±10%	**GA355QR7GB103KW01#**	p192
			15000pF	±10%	**GA355QR7GB153KW01#**	p192
2.0mm	250Vac	X7R	22000pF	±10%	**GA355DR7GB223KW01#**	p192
2.5mm	250Vac	X7R	33000pF	±10%	**GA355ER7GB333KW01#**	p192
			47000pF	±10%	**GA355ER7GB473KW01#**	p192
2.9mm	250Vac	X7R	56000pF	±10%	**GA355XR7GB563KW06#**	p192

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GA3 Series Type GB Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: DC1075V Applied Time: 60±1s Charge/discharge current: 50mA max.
4	Insulation Resistance (I.R.)		6000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Measurement Temperature: Room Temperature
5	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
6	Dissipation Factor (D.F.)		0.025 max.	
7	Temperature Characteristics of Capacitance		R7: Within ±15% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h. at room condition*.
8	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
9	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
10	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GA355 size: 100 to 120°C for 1min and 170 to 200°C for 1min • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±10%	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
11	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
12	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GB Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within±15%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
14	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. • No.11 Adhesive Strength of Termination (apply force: 5N) • No.12 Substrate Bending Test Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: Rated voltage Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within±15%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
15	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. • No.11 Adhesive Strength of Termination (apply force: 5N) • No.12 Substrate Bending Test Next, Impulse Voltage test is performed. Each individual capacitor shall be subjected to a 2.5kV Impulse (the voltage value means zero to peak) for 3 times. Then the capacitors are applied to life test.  Front time (T1) = 1.2μs=1.67T Time to half-value (T2) = 50μs Apply voltage as Table for 1000h at 125+2/-0°C , relative humidity 50% max. Applied Voltage AC312.5V (r.m.s.), except that once each hour the voltage is increased to AC1000V (r.m.s.) for 0.1s. Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±20%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GB Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item	Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
16	**Passive Flammability**	The burning time shall not be exceeded the time 30s. The tissue paper shall not ignite.	The capacitor under test shall be held in the flame in the position which best promotes burning. Each specimen shall only be exposed once to the flame. Time of exposure to flame: 30s Length of flame: 12±1mm Gas burner: Length 35mm min. Inside dia: 0.5±0.1mm Outside dia: 0.9mm max. Gas: Butane gas purity 95% min. 
17	**Active Flammability**	The cheesecloth shall not be on fire.	The specimens shall be individually wrapped in at least one but more than two complete layers of cheesecloth. The specimens shall be subjected to 20 discharges. The interval between successive discharges shall be 5s. The UAC shall be maintained for 2min after the last discharge.  C1,C2: Filter capacitor 1μF±10% C3: Capacitor 0.033μF±5% L1 to L4: Rod coa choke 1.5mH±20%, 16A R: Resistor 100Ω±2% Cx < 0.068μF Ct: Tank capacitor 3μF±5% 10kV Cx ≦ 1μF U-: UR±5% UR: Rated voltage Cx: Capacitor under test F: Slow-blow fuse, rated 16A Ut: Voltage to which the tank capacitor Ct is charged 

GA3 Series Type GB Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GA355	4.5	8.0	5.6

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension of Pattern (mm)			
	a	b	c	d
GA355	4.5	8.0	5.6	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



(b) Test State



a: ±2 gap between support stand center and test stand

b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose / Acquired certifications of UL60950-1

GA3 Series Type GD

Safety standard

WEB

UL60950-1 Certified Product

Features

① International Standard (IEC60384-14) certified product.

Please down load Safety Standard Certification (Type GD) from here. WEB

② Can be uesd for UL60950-1 devices.

●DAA Modem - Transformer Less



No.	Application	Recommend MLCC Type
C5	Lighting Surge Absorption	Type: GD / GF
C6	Noise Immunity	
C7	D/A Isolation Barrier	

③ Realized large capacitance value and small size while maintaining high withstand voltages by the multilayer structure.



<Example of Structure>

④ This product is only for reflow soldering.

Specifications

Size (mm)	4.5×2.0mm to 4.5×3.2mm
Rated Voltage	250Vac
Capacitance	10pF to 4700pF
Main Applications	Modem

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

GA3 Series Type GD Temperature Compensating Type Safety standard Part Number List

4.5×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	250Vac	SL	10pF	±5%	**GA342A1XGD100JW31#**	p199
			12pF	±5%	**GA342A1XGD120JW31#**	p199
			15pF	±5%	**GA342A1XGD150JW31#**	p199
			18pF	±5%	**GA342A1XGD180JW31#**	p199
			22pF	±5%	**GA342A1XGD220JW31#**	p199
			27pF	±5%	**GA342A1XGD270JW31#**	p199
			33pF	±5%	**GA342A1XGD330JW31#**	p199
			39pF	±5%	**GA342A1XGD390JW31#**	p199
			47pF	±5%	**GA342A1XGD470JW31#**	p199
			56pF	±5%	**GA342A1XGD560JW31#**	p199
			68pF	±5%	**GA342A1XGD680JW31#**	p199
			82pF	±5%	**GA342A1XGD820JW31#**	p199

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GA3 Series Type GD High Dielectric Constant Type Safety standard Part Number List

4.5×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	100pF	±10%	**GA342QR7GD101KW01#**	p203
			150pF	±10%	**GA342QR7GD151KW01#**	p203
			220pF	±10%	**GA342QR7GD221KW01#**	p203
			330pF	±10%	**GA342QR7GD331KW01#**	p203
			470pF	±10%	**GA342QR7GD471KW01#**	p203
			680pF	±10%	**GA342QR7GD681KW01#**	p203
			1000pF	±10%	**GA342QR7GD102KW01#**	p203
			1500pF	±10%	**GA342QR7GD152KW01#**	p203

4.5×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	1800pF	±10%	**GA343QR7GD182KW01#**	p203
			2200pF	±10%	**GA343QR7GD222KW01#**	p203
2.0mm	250Vac	X7R	4700pF	±10%	**GA343DR7GD472KW01#**	p203

*: Refers to the page of the “Specifications and Test Methods”.

Part number # indicates the package specification code.

1 GA3 Series Type GD Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: AC1500V (r.m.s.) Applied Time: 60±1s Charge/discharge current: 50mA max.
4	Impulse Voltage		No self healing break downs or flash-overs have taken place in the capacitor.	10 impulse of alternating polarity is subjected. (5 impulse for each polarity) The interval between impulse is 60s. Applied Voltage: 2.5kVo-p
5	Insulation Resistance (I.R.)		6000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1MHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
7	Q		C ≧ 30pF: 1000 or more C < 30pF: 400+20C or more C: Nominal Capacitance (pF)	
8	Temperature Characteristics of Capacitance		1X: +350 to -1000 ppm/°C (Temp.Range:+20 to +85°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 However, the capacitance shall be measured at even 85°C between step 3 and step 4.
9	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
10	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
11	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GA342 size: 100 to 120°C for 1min and 170 to 200°C for 1min
		Capacitance Change	Within±2.5% or ±0.25pF (Whichever is larger)	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
12	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
13	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GD Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method" Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*.
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. ▪ No.12 Adhesive Strength of Termination (apply force: 5N) ▪ No.13 Substrate Bending Test Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h. Applied Voltage: Rated voltage Exposure Time:24±2h at room condition*.
		Capacitance Change	Within ±5.0% or ±0.5pF (Whichever is larger)	
		Q	C ≧ 30pF: 350 or more C < 30pF: 275+5/2C or more C: Nominal Capacitance (pF)	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
16	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. ▪ No.12 Adhesive Strength of Termination (apply force: 5N) ▪ No.13 Substrate Bending Test Next, Impulse Voltage test is performed. Each individual capacitor shall be subjected to a 2.5kV Impulse (the voltage value means zero to peak) for 3 times. Then the capacitors are applied to life test.  Front time (T1) = 1.2μs=1.67T Time to half-value (T2) = 50μs Apply voltage as Table for 1000h at 125+2/-0°C , relative humidity 50% max. Applied voltage AC425V (r.m.s.), except that once each hour the voltage is increased to AC1000V (r.m.s.) for 0.1s. Exposure Time: 24±2h at room condition*.
		Capacitance Change	Within ±3.0% or ±0.3pF (Whichever is larger)	
		Q	C ≧ 30pF: 350 or more C < 30pF: 275+5/2C or more C: Nominal Capacitance (pF)	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
17	Passive Flammability		The burning time shall not be exceeded the time 30s. The tissue paper shall not ignite.	The capacitor under test shall be held in the flame in the position which best promotes burning. Each specimen shall only be exposed once to the flame. Time of exposure to flame: 30s Length of flame: 12±1mm Gas burner: Length 35mm min. Inside dia: 0.5±0.1mm Outside dia: 0.9mm max. Gas: Butane gas purity 95% min. 

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GD Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item	Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
18	**Active Flammability**	The cheesecloth shall not be on fire.	The specimens shall be individually wrapped in at least one but more than two complete layers of cheesecloth. The specimens shall be subjected to 20 discharges. The interval between successive discharges shall be 5s. The UAC shall be maintained for 2min after the last discharge.  C1, C2: Filter capacitor 1μF±10% C3: Capacitor 0.033μF±5% L1 to L4: Rod coa choke 1.5mH±20%, 16A R: Resistor 100Ω±2% Cx < 0.068μF Ct: Tank capacitor 3μF±5% 10kV Cx ≦ 1μF U-: UR±5% UR: Rated voltage Cx: Capacitor under test F: Slow-blow fuse, rated 16A Ut: Voltage to which the tank capacitor Ct is charged 

GA3 Series Type GD Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GA342	3.5	7.0	2.4

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension of Pattern (mm)			
	a	b	c	d
GA342	3.5	7.0	2.4	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



2 GA3 Series Type GD Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: AC1500V (r.m.s.) Applied Time: 60±1s Charge/discharge current: 50mA max.
4	Impulse Voltage		No self healing break downs or flash-overs have taken place in the capacitor.	10 impulse of alternating polarity is subjected. (5 impulse for each polarity) The interval between impulse is 60s. Applied Voltage: 2.5kVo-p
5	Insulation Resistance (I.R.)		6000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
7	Dissipation Factor (D.F.)		0.025 max.	
8	Temperature Characteristics of Capacitance		R7: Within ±15% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
9	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
10	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
11	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GA342/43 size: 100 to 120°C for 1min and 170 to 200°C for 1min ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±10%	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
12	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GD Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method" Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*. ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within±15%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. ▪ No.12 Adhesive Strength of Termination (apply force: 5N) ▪ No.13 Substrate Bending Test Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: Rated voltage Exposure Time: 24±2h at room condition*. ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within±15%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
16	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. ▪ No.12 Adhesive Strength of Termination (apply force: 5N) ▪ No.13 Substrate Bending Test Next, Impulse Voltage test is performed. Each individual capacitor shall be subjected to a 2.5kV Impulse (the voltage value means zero to peak) for 3 times. Then the capacitors are applied to life test.  Front time (T1) = 1.2μs=1.67T Time to half-value (T2) = 50μs Apply voltage as Table for 1000h at 125+2/-0°C , relative humidity 50% max. Applied Voltage AC425V (r.m.s.), except that once each hour the voltage is increased to AC1000V (r.m.s.) for 0.1s. Exposure Time: 24±2h at room condition*. ▪ Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±20%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GD Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item	Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
17	**Passive Flammability**	The burning time shall not be exceeded the time 30s. The tissue paper shall not ignite.	The capacitor under test shall be held in the flame in the position which best promotes burning. Each specimen shall only be exposed once to the flame. Time of exposure to flame: 30s Length of flame: 12±1mm Gas burner: Length 35mm min. Inside dia: 0.5±0.1mm Outside dia: 0.9mm max. Gas: Butane gas purity 95% min. 
18	**Active Flammability**	The cheesecloth shall not be on fire.	The specimens shall be individually wrapped in at least one but more than two complete layers of cheesecloth. The specimens shall be subjected to 20 discharges. The interval between successive discharges shall be 5s. The UAC shall be maintained for 2min after the last discharge.  C1, C2: Filter capacitor 1μF±10% C3: Capacitor 0.033μF±5% L1 to L4: Rod coa choke 1.5mH±20%, 16A R: Resistor 100Ω±2% Cx < 0.068μF Ct: Tank capacitor 3μF±5% 10kV Cx ≦ 1μF U-: UR±5% UR: Rated voltage Cx: Capacitor under test F: Slow-blow fuse, rated 16A Ut: Voltage to which the tank capacitor Ct is charged 

GA3 Series Type GD Specifications and Test Methods (2)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GA342	3.5	7.0	2.4
GA343	3.5	7.0	3.7

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension of Pattern (mm)			
	a	b	c	d
GA342	3.5	7.0	2.4	1.0
GA343	3.5	7.0	3.7	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose / Acquired certifications of IEC60384-14 Class X1/Y2 and UL60950-1

GA3 Series Type GF

Safety standard

WEB

Size 4.5x2.0mm: This product is applicable only for the instruments certified by EN/IEC60950-1
Size 5.7x2.8mm or 5.7x5.0mm: This product is applicable as X or Y capacitor

Features

1. **International Standard (IEC60384-14) certified product.**

   Please down load Safety Standard Certification (Type GF: X1/Y2) from here. WEB

2. **Can be used as a Class Y2 capacitor.**

Switching Power Supply - Class 1 Equipment



No.	Application	Recommend MLCC Type
C1	X Cap	Type: GB
C2	Y Cap	Type: GF
C3		
C4		
C5	Primary - Secondary Coupling	Type: GF×2

Switching Power Supply - Class 2 Equipment



No.	Application	Recommend MLCC Type
C1	X Cap	Type: GB
C2	Y Cap	Type: GF×2
C3		
C4	Primary - Secondary Coupling	

③ Realized large capacitance value and small size while maintaining high withstand voltages by the multilayer structure.



<Example of Structure>

④ This product is only for reflow soldering.

Specifications

Size (mm)	4.5×2.0mm to 5.7×5.0mm
Rated Voltage	250Vac
Capacitance	10pF to 4700pF
Main Applications	AC-DC power supply

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

GA3 Series Type GF Temperature Compensating Type Safety standard Part Number List

4.5×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.0mm	250Vac	SL	10pF	±5%	**GA342A1XGF100JW31#**	p211
			12pF	±5%	**GA342A1XGF120JW31#**	p211
			15pF	±5%	**GA342A1XGF150JW31#**	p211
			18pF	±5%	**GA342A1XGF180JW31#**	p211
			22pF	±5%	**GA342A1XGF220JW31#**	p211
			27pF	±5%	**GA342A1XGF270JW31#**	p211
			33pF	±5%	**GA342A1XGF330JW31#**	p211
			39pF	±5%	**GA342A1XGF390JW31#**	p211
			47pF	±5%	**GA342A1XGF470JW31#**	p211
			56pF	±5%	**GA342A1XGF560JW31#**	p211
			68pF	±5%	**GA342A1XGF680JW31#**	p211
			82pF	±5%	**GA342A1XGF820JW31#**	p211

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GA3 Series Type GF High Dielectric Constant Type Safety standard Part Number List

4.5×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	100pF	±10%	**GA342QR7GF101KW01#**	p215
			150pF	±10%	**GA342QR7GF151KW01#**	p215
			470pF	±10%	**GA342QR7GF471KW01#**	p215
			680pF	±10%	**GA342QR7GF681KW01#**	p215
2.2mm	250Vac	X7R	220pF	±10%	**GA342DR7GF221KW02#**	p215
			330pF	±10%	**GA342DR7GF331KW02#**	p215
			1000pF	±10%	**GA342DR7GF102KW02#**	p215

5.7×2.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	100pF	±10%	**GA352QR7GF101KW31#**	p215
			150pF	±10%	**GA352QR7GF151KW31#**	p215
			220pF	±10%	**GA352QR7GF221KW31#**	p215
			330pF	±10%	**GA352QR7GF331KW31#**	p215
			470pF	±10%	**GA352QR7GF471KW01#**	p215
			680pF	±10%	**GA352QR7GF681KW01#**	p215
			1000pF	±10%	**GA352QR7GF102KW01#**	p215
			1500pF	±10%	**GA352QR7GF152KW01#**	p215

5.7×5.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
1.5mm	250Vac	X7R	1800pF	±10%	**GA355QR7GF182KW01#**	p215
			2200pF	±10%	**GA355QR7GF222KW01#**	p215
			3300pF	±10%	**GA355QR7GF332KW01#**	p215
2.0mm	250Vac	X7R	4700pF	±10%	**GA355DR7GF472KW01#**	p215

*: Refers to the page of the “Specifications and Test Methods”.

Part number # indicates the package specification code.

1 GA3 Series Type GF Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: AC2000V (r.m.s.) Applied Time: 60±1s Charge/discharge current: 50mA max.
4	Impulse Voltage		No self healing break downs or flash-overs have taken place in the capacitor.	10 impulse of alternating polarity is subjected. (5 impulse for each polarity) The interval between impulse is 60s. Applied Voltage: 2.5kVo-p
5	Insulation Resistance (I.R.)		6000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1MHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
7	Q		C ≧ 30pF: 1000 or more C < 30pF: 400+20C or more C: Nominal Capacitance (pF)	
8	Temperature Characteristics of Capacitance		1X: +350 to -1000 ppm/°C (Temp.Range:+20 to +85°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 However, the capacitance shall be measured at even 85°C between step 3 and step 4.
9	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		Q	Within the specified initial value.	
10	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
11	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GA342 size: 100 to 120°C for 1min and 170 to 200°C for 1min
		Capacitance Change	Within±2.5% or ±0.25pF (Whichever is larger)	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
12	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
13	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GF Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*.
		Capacitance Change	Within ±2.5% or ±0.25pF (Whichever is larger)	
		Q	Within the specified initial value.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. ▪ No.12 Adhesive Strength of Termination (apply force: 5N) ▪ No.13 Substrate Bending test Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: Rated voltage Exposure Time: 24±2h at room condition*.
		Capacitance Change	Within ±5.0% or ±0.5pF (Whichever is larger)	
		Q	C ≧ 30pF: 350 or more C < 30pF: 275+5/2C or more C: Nominal Capacitance (pF)	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
16	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. ▪ No.12 Adhesive Strength of Termination (apply force: 5N) ▪ No.13 Substrate Bending test Next, Impulse Voltage test is performed. Each individual capacitor shall be subjected to a 5kV Impulse (the voltage value means zero to peak) for 3 times. Then the capacitors are applied to life test.  Front time (T1) = 1.2μs=1.67T Time to half-value (T2) = 50μs Apply voltage as Table for 1000h at 125+2/-0°C , relative humidity 50% max. Applied voltage AC425V (r.m.s.), except that once each hour the voltage is increased to AC1000V (r.m.s.) for 0.1s. Exposure Time: 24±2h at room condition*.
		Capacitance Change	Within ±3.0% or ±0.3pF (Whichever is larger)	
		Q	C ≧ 30pF: 350 or more C < 30pF: 275+5/2C or more C: Nominal Capacitance (pF)	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
17	Passive Flammability		The burning time shall not be exceeded the time 30s. The tissue paper shall not ignite.	The capacitor under test shall be held in the flame in the position which best promotes burning. Each specimen shall only be exposed once to the flame. Time of exposure to flame: 30s Length of flame: 12±1mm Gas burner: Length 35mm min. Inside dia: 0.5±0.1mm Outside dia: 0.9mm max. Gas: Butane gas purity 95% min. 

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GF Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item	Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
18	**Active Flammability**	The cheesecloth shall not be on fire.	The specimens shall be individually wrapped in at least one but more than two complete layers of cheesecloth. The specimens shall be subjected to 20 discharges. The interval between successive discharges shall be 5s. The UAC shall be maintained for 2min after the last discharge.  C1, C2: Filter capacitor 1μF±10% C3: Capacitor 0.033μF±5% L1 to L4: Rod coa choke 1.5mH±20%, 16A R: Resistor 100Ω±2% Cx < 0.068μF Ct: Tank capacitor 3μF±5% 10kV Cx ≦ 1μF U-: UR±5% UR: Rated voltage Cx: Capacitor under test F: Slow-blow fuse, rated 16A Ut: Voltage to which the tank capacitor Ct is charged 

GA3 Series Type GF Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in “Specifications and Test Methods”.
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GA342	3.5	7.0	2.4

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension of Pattern (mm)			
	a	b	c	d
GA342	3.5	7.0	2.4	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



2 GA3 Series Type GF Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Appearance		No defects or abnormalities.	Visual inspection.
2	Dimension		Within the specified dimensions.	Using calipers and micrometers.
3	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: AC2000V (r.m.s.) Applied Time: 60±1s Charge/discharge current: 50mA max.
4	Impulse Voltage		No self healing break downs or flash-overs have taken place in the capacitor.	10 impulse of alternating polarity is subjected. (5 impulse for each polarity) The interval between impulse is 60s. Applied Voltage: 2.5kVo-p
5	Insulation Resistance (I.R.)		6000MΩ or more	Measurement Point: Between the terminations Measurement Voltage: DC500±50V Charging Time: 60±5s Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: AC1.0±0.2V (r.m.s.)
7	Dissipation Factor (D.F.)		0.025 max.	
8	Temperature Characteristics of Capacitance		R7: Within ±15% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) 1 / Reference Temp. ±2 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
9	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate A shown in "Complement of Test Method". Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
10	Solderability		95% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (wt)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 245±5°C Immersion time: 2±0.5s Immersing in speed: 25±2.5mm/s.
11	Resistance to Soldering Heat	Appearance	No defects or abnormalities.	Test Method: Solder bath method Solder: Sn-3.0Ag-0.5Cu (Lead Free Solder) Solder Temp.: 260±5°C Immersion time: 10±1s Immersing in speed: 25±2.5mm/s. Exposure Time: 24±2h at room condition*. Preheat: GA342/52/55 size: 100 to 120°C for 1min and 170 to 200°C for 1min • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±10%	
		I.R.	1000MΩ or more	
		Voltage Proof	No defects.	
12	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate A shown in "Complement of Test Method".  Applied Direction: In parallel with the test substrate and vertical with the capacitor side.

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GF Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Substrate Bending Test		No defects or abnormalities.	Solder the capacitor on the test substrate B shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Substrate Bending Test" of "Complement of Test Method". Flexure: 1mm Holding Time: 5±1s Soldering Method: Reflow soldering
14	Temperature Sudden Change	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate A (glass epoxy board) shown in "Complement of Test Method". Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within±15%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
15	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. • No.12 Adhesive Strength of Termination (apply force: 5N) • No.13 Substrate Bending Test Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500+24/-0h Applied Voltage: Rated voltage Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within±15%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	
16	Durability	Appearance	No defects or abnormalities.	Fix the capacitor to the supporting test substrate B (glass epoxy board) shown in "Complement of Test Method". Before this test, the test shown in the following is performed. • No.12 Adhesive Strength of Termination (apply force: 5N) • No.13 Substrate Bending Test Next, Impulse Voltage test is performed. Each individual capacitor shall be subjected to a 5kV Impulse (the voltage value means zero to peak) for 3 times. Then the capacitors are applied to life test.  Front time (T1) = 1.2μs=1.67T Time to half-value (T2) = 50μs Apply voltage as Table for 1000h at 125+2/-0°C, relative humidity 50% max. Applied Voltage: AC425V (r.m.s.), except that once each hour the voltage is increased to AC1000V (r.m.s.) for 0.1s. Exposure Time: 24±2h at room condition*. • Pretreatment Perform a heat treatment at 150+0/-10°C for 1h±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±20%	
		D.F.	0.05 max.	
		I.R.	3000MΩ or more	
		Voltage Proof	No defects.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

GA3 Series Type GF Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item	Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
17	**Passive Flammability**	The burning time shall not be exceeded the time 30s. The tissue paper shall not ignite.	The capacitor under test shall be held in the flame in the position which best promotes burning. Each specimen shall only be exposed once to the flame. Time of exposure to flame: 30s Length of flame: 12±1mm Gas burner: Length 35mm min. Inside dia: 0.5±0.1mm Outside dia: 0.9mm max. Gas: Butane gas purity 95% min. 
18	**Active Flammability**	The cheesecloth shall not be on fire.	The specimens shall be individually wrapped in at least one but more than two complete layers of cheesecloth. The specimens shall be subjected to 20 discharges. The interval between successive discharges shall be 5s. The UAC shall be maintained for 2min after the last discharge.  C1, C2: Filter capacitor 1μF±10% C3: Capacitor 0.033μF±5% L1 to L4: Rod coa choke 1.5mH±20%, 16A R: Resistor 100Ω±2% Cx < 0.068μF Ct: Tank capacitor 3μF±5% 10kV Cx ≦ 1μF U-: UR±5% UR: Rated voltage Cx: Capacitor under test F: Slow-blow fuse, rated 16A Ut: Voltage to which the tank capacitor Ct is charged 

GA3 Series Type GF Specifications and Test Methods (2)

Continued from the preceding page.↘

Complement of Test Method

1. Test Substrate

The test substrate should be Substrate A or Substrate B as described in "Specifications and Test Methods".
The specimen should be soldered by the conditions as described below.
Soldering Method: Reflow soldering
Solder: Sn-3.0Ag-0.5Cu

(1) Test Substrate A

▪ Land Dimensions



Part Number	Dimension (mm)		
	a	b	c
GA342	3.5	7.0	2.4
GA352	4.5	8.0	3.2
GA355	4.5	8.0	5.6

▪ Material: Glass Epoxy Board
▪ Thickness: 1.6mm
▪ Thickness of Copper Foil: 0.035mm

(2) Test Substrate B



Part Number	Dimension of Pattern (mm)			
	a	b	c	d
GA342	3.5	7.0	2.4	1.0
GA352	4.5	8.0	3.2	1.0
GA355	4.5	8.0	5.6	1.0

▪ Material: Glass Epoxy Board
▪ Thickness of Copper Foil: 0.035mm

2. Test Method of Substrate Bending Test

(a) Support State



a: ±2 gap between support stand center and test stand

(b) Test State



b: ±5 gap between support stand center and test stand center

▪ Material of Test Stand and Pressure Stick
The material shoud be a metal where a remarkable transformation and the distortion are not caused even if it is pressurized.
▪ Pressurizing Speed
The pressurizing speed is pressurized at the speed of about 1mm/s until the flexure reaches a regulated value.



LW Reversed Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLL Series

Low ESL

WEB

This low ESL capacitor is ideal for power supply decoupling of high-speed operation electronic equipment.

Features

① Low ESL

Since the equivalent series inductance (ESL) is low and excellent in high frequency characteristics, this capacitor is suitable for power supply decoupling of high-speed operation electronic equipment.



<Example of Structure>

② Contributes to a reduction in the number of components.

The number of components can be reduced by using low ESL capacitors, while maintaining functions equivalent to general purpose capacitors (GRM Series).

Murata proposes the use of the LLL series to reduce the number of components and high costs. Simulation is also possible.

› Proposal for Cost Reductions

WEB



③ A maximum operating temperature up to 125°C

We also offer an abundant lineup of X7* characteristics that can be used in high temperature locations, such as IC packages.

Specifications

Size (mm)	0.5×1.0mm to 1.6×3.2mm
Rated Voltage	2.5Vdc to 50Vdc
Capacitance	2200pF to 10μF
Main Applications	Application processor/CPU/GPU



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

LLL Series High Dielectric Constant Type LOW ESL Part Number List

0.5×1.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.35mm	6.3Vdc	X6S	0.10μF	±20%	LLL153C80J104ME01#	
			0.22μF	±20%	LLL153C80J224ME14#	
	4Vdc	X7S	0.47μF	±20%	LLL153C70G474ME17#	
		X6S	1.0μF	±20%	LLL153C80G105ME21#	

0.6×1.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.45mm	4Vdc	X5R	4.3μF	±20%	LLL1U4R60G435ME22#	D1

0.8×1.6mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.5mm	25Vdc	X7R	10000pF	±20%	LLL185R71E103MA11#	
	16Vdc	X7R	22000pF	±20%	LLL185R71C223MA11#	
			47000pF	±20%	LLL185R71C473MA11#	
	10Vdc	X7R	0.10μF	±20%	LLL185R71A104MA11#	
	4Vdc	X7S	0.22μF	±20%	LLL185C70G224MA11#	
0.55mm	4Vdc	X7S	2.2μF	±20%	LLL185C70G225ME01#	
0.6mm	50Vdc	X7R	2200pF	±20%	LLL185R71H222MA01#	
			4700pF	±20%	LLL185R71H472MA01#	
	25Vdc	X7R	10000pF	±20%	LLL185R71E103MA01#	
			22000pF	±20%	LLL185R71E223MA01#	
	16Vdc	X7R	47000pF	±20%	LLL185R71C473MA01#	
	10Vdc	X7R	0.10μF	±20%	LLL185R71A104MA01#	
			0.22μF	±20%	LLL185R71A224MA01#	
	4Vdc	X7S	0.47μF	±20%	LLL185C70G474MA01#	

1.25×2.0mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.5mm	50Vdc	X7R	10000pF	±20%	LLL215R71H103MA11#	
	25Vdc	X7R	22000pF	±20%	LLL215R71E223MA11#	
	16Vdc	X7R	47000pF	±20%	LLL215R71C473MA11#	
			0.10μF	±20%	LLL215R71C104MA11#	
	10Vdc	X7R	0.22μF	±20%	LLL215R71A224MA11#	
	6.3Vdc	X7R	0.47μF	±20%	LLL215R70J474MA11#	
	4Vdc	X7S	1.0μF	±20%	LLL215C70G105MA11#	
0.7mm	50Vdc	X7R	10000pF	±20%	LLL216R71H103MA01#	
			22000pF	±20%	LLL216R71H223MA01#	
	25Vdc	X7R	47000pF	±20%	LLL216R71E473MA01#	
			0.10μF	±20%	LLL216R71E104MA01#	
	10Vdc	X7R	0.22μF	±20%	LLL216R71A224MA01#	
0.95mm	16Vdc	X7R	0.22μF	±20%	LLL219R71C224MA01#	
	10Vdc	X7R	0.47μF	±20%	LLL219R71A474MA01#	
			1.0μF	±20%	LLL219R71A105MA01#	
	4Vdc	X7S	2.2μF	±20%	LLL219C70G225MA01#	

1.6×3.2mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
0.5mm	50Vdc	X7R	10000pF	±20%	LLL315R71H103MA11#	
			22000pF	±20%	LLL315R71H223MA11#	
	25Vdc	X7R	47000pF	±20%	LLL315R71E473MA11#	
			0.10μF	±20%	LLL315R71E104MA11#	
	16Vdc	X7R	0.22μF	±20%	LLL315R71C224MA11#	
	10Vdc	X7R	0.47μF	±20%	LLL315R71A474MA11#	
0.8mm	50Vdc	X7R	10000pF	±20%	LLL317R71H103MA01#	
			22000pF	±20%	LLL317R71H223MA01#	
			47000pF	±20%	LLL317R71H473MA01#	
	25Vdc	X7R	0.10μF	±20%	LLL317R71E104MA01#	
	16Vdc	X7R	0.22μF	±20%	LLL317R71C224MA01#	
			0.47μF	±20%	LLL317R71C474MA01#	
	10Vdc	X7R	1.0μF	±20%	LLL317R71A105MA01#	
	6.3Vdc	X7R	2.2μF	±20%	LLL317R70J225MA01#	
1.25mm	50Vdc	X7R	0.10μF	±20%	LLL31MR71H104MA01#	
	25Vdc	X7R	0.22μF	±20%	LLL31MR71E224MA01#	
			0.47μF	±20%	LLL31MR71E474MA01#	
	16Vdc	X7R	1.0μF	±20%	LLL31MR71C105MA01#	
	10Vdc	X7R	2.2μF	±20%	LLL31MR71A225MA01#	
	6.3Vdc	X7R	4.7μF	±20%	LLL31MR70J475MA01#	
		X5R	10μF	±20%	LLL31MR60J106ME01#	

Part number # indicates the package specification code.

LLL Series Specifications and Test Methods

Specifications and Test Methods, please refer to the search web page.
https://www.murata.com/en-global/products/capacitor



Links are provided to the product detail pages on the web, and are shown below in the product number table from the PDF version of the catalog which is available on the web.



Detailed Specifications Sheet

- Rated value
- Specifications and Test Methods
- Package
- Caution, Notice



■ **Specifications and Test Methods**

No	Item		Specification	Test Method (Ref. Standard:JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage proof		No defects or abnormalities.	Measurement Point : Between the terminations Test Voltage : 250% of the rated voltage Applied Time : 1 to 5 s Charge/discharge current : 50mA max.
5	Insulation Resistance(I.R.)		More than 2000MΩ or 50Ω・F (Whichever is smaller)	Measurement Point : Between the terminations Measurement Voltage : DC Rated Voltage Charging Time : 1 min (LLL153C70E474M only 2 min) Charge/discharge current : 50mA max. Measurement Temperature Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature Room Temperature Capacitance / Frequency / Voltage C≦10μF (10V min.) / 1.0+/-0.1kHz / 1.0+/-0.2Vrms C≦10μF (6.3V max.) / 1.0+/-0.1kHz / 0.5+/-0.1Vrms C＞10μF / 120+/-24Hz / 0.5+/-0.1Vrms
7	Dissipation Factor (D.F.)		0.120 max.	
8	Temperature Characteristics of Capacitance	No bias	R6 : Within +/-15% (-55°C to +85°C) C7 : Within +/-22% (-55°C to +125°C) C8 : Within +/-22% (-55°C to +105°C) D7 : Within +22/-33% (-55°C to +125°C) D8 : Within +22/-33% (-55°C to +105°C)	The capacitance change should be measured after 5 min. at each specified temp. stage. Capacitance value as a reference is the value in step 3. ・Measurement Voltage : LLL153 D7 0E/0G 224M only : 0.25+/-0.05Vrms LLL153 C7 0E/0G 104M only : 0.30+/-0.05Vrms LLL152R60G105M , LLL152D80E105M only : 0.10+/-0.03Vrms Step / Temperature(°C) / Applying Voltage(VDC) 1 / Reference Temp.+/-2 2 / Min.Operating Temp. +/-3 3 / Reference Temp. +/-2 No bias

8 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLA Series

Low ESL

WEB

8-Terminal Type Low ESL Capacitor Ideal for Power Supply Decoupling of High-speed Operation IC

Features

1 Ultra-low ESL

Since the equivalent series inductance (ESL) is very low with excellent high frequency characteristics due to the design structure, this capacitor is ideal for power supply decoupling of high-speed operation IC.



<Example of Structure>



<Effectiveness of Cancelling Out Inductance by Mutual Inductance>



<Effectiveness of Suppressing Inductance when Mounting a Multi-terminal Capacitor>

The inductance for the boards also becomes lower, not only the capacitor.

2 A maximum operating temperature up to 125°C

This product is applicable to high temperatures (X7* characteristics); however, Murata also offers numerous thin type products, which are ideal as decoupling capacitors on IC package.

Specifications

Size (mm)	1.6×0.8mm to 2.0×1.25mm
Rated Voltage	4Vdc to 25Vdc
Capacitance	10000pF to 4.7μF
Main Applications	Application processor/CPU/GPU

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

LLA Series High Dielectric Constant Type Low ESL Part Number List

1.6×0.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	4Vdc	X7S	0.10μF	±20%	**LLA185C70G104MA01#**	p224
			0.22μF	±20%	**LLA185C70G224MA01#**	p224
			0.47μF	±20%	**LLA185C70G474MA01#**	p224
			2.2μF	±20%	**LLA185C70G225ME16#**	p226

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	25Vdc	X7R	10000pF	±20%	**LLA215R71E103MA14#**	p224
			22000pF	±20%	**LLA215R71E223MA14#**	p224
	16Vdc	X7R	47000pF	±20%	**LLA215R71C473MA14#**	p224
			0.10μF	±20%	**LLA215R71C104MA14#**	p224
	10Vdc	X7R	0.22μF	±20%	**LLA215R71A224MA14#**	p224
	6.3Vdc	X7R	0.47μF	±20%	**LLA215R70J474MA14#**	p224
	4Vdc	X7S	1.0μF	±20%	**LLA215C70G105MA14#**	p224
			4.7μF	±20%	**LLA215C70G475ME19#**	p226
0.95mm	25Vdc	X7R	10000pF	±20%	**LLA219R71E103MA01#**	p224
			22000pF	±20%	**LLA219R71E223MA01#**	p224
			47000pF	±20%	**LLA219R71E473MA01#**	p224
	16Vdc	X7R	0.10μF	±20%	**LLA219R71C104MA01#**	p224
			0.22μF	±20%	**LLA219R71C224MA01#**	p224
	10Vdc	X7R	0.47μF	±20%	**LLA219R71A474MA01#**	p224
	6.3Vdc	X7R	1.0μF	±20%	**LLA219R70J105MA01#**	p224
	4Vdc	X7S	2.2μF	±20%	**LLA219C70G225MA01#**	p224

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 LLA Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		C ≦ 0.047μF:More than 10000MΩ C > 0.047μF:More than 500Ω • F C: Nominal Capacitance	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance: C ≦ 10μF; Frequency: 1.0±0.1kHz; Voltage: 1.0±0.2Vrms * * For item LLA185 C7 0G 274 to 474, the capacitance should be measured using a voltage of 0.5±0.1Vrms. For item LLA185/215 C7 0G 473, the capacitance should be measured using a voltage of 0.5±0.2Vrms.
7	Dissipation Factor (D.F.)		W.V.:25Vdc min.: 0.025max. W.V.:16/10Vdc: 0.035max. W.V.:6.3Vdc max.: 0.05max.	
8	Temperature Characteristics of Capacitance	No Bias	R7: Within ±15% (-55 to +125°C) R6: Within ±15% (-55 to +85°C) C7: Within ±22% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2 Applying Voltage(VDC): No bias ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
9	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate (glass epoxy board). Applied Force: 5N Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Solderability		75% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s
12	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Perform the 5 cycles according to the four heat treatments shown in the following table. Step 1: Min. Operating Temp. +0/-3; 30±3 Step 2: Room Temp.; 2 to 3 Step 3: Max. Operating Temp. +3/-0; 30±3 Step 4: Room Temp.; 2 to 3 Exposure Time: 24±2h ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

LLA Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±12.5%	
		D.F.	W.V.: 10Vdc min.: 0.05max. W.V.: 6.3Vdc max.: 0.075max.	
		I.R.	More than 500MΩ or 25Ω • F (Whichever is smaller)	
14	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h • Initial measurement Apply 200% of the rated DC voltage at the max. operating temp. ±3°C for 1h. Remove and set for 24±2h at room temperature. Perform initial measurement.
		Capacitance Change	Within ±12.5%	
		D.F.	W.V.:10Vdc min.: 0.05max. W.V.:6.3Vdc max.: 0.075max.	
		I.R.	More than 1000MΩ or 50Ω • F (Whichever is smaller)	

2 LLA Series Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		More than 2000MΩ or 50Ω • F (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 1min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature
7	Dissipation Factor (D.F.)		0.120max.	Capacitance / Frequency / Voltage C ≦ 10μF (10V min.) / 1.0±0.1kHz / 1.0±0.2Vrms C ≦ 10μF (6.3V max.) / 1.0±0.1kHz / 0.5±0.1Vrms C > 10μF / 120±24Hz / 0.5±0.1Vrms
8	Temperature Characteristics of Capacitance	No Bias	C7: Within ±22% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) / Applying Voltage(VDC) 1 / Reference Temp. ±2 / No bias 2 / Min. Operating Temp. ±3 3 / Reference Temp. ±2 4 / Max. Operating Temp. ±3 5 / Reference Temp. ±2 • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
9	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate (glass epoxy board). Applied Force: 5N Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Solderability		75% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s
12	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 EExposure Time: 24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

LLA Series Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. • Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 500MΩ or 12.5Ω • F (Whichever is smaller)	
14	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 150% of the rated voltage Charge/discharge current: 50mA max. • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. • Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature,then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 1000MΩ or 25Ω • F (Whichever is smaller)	

10 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLM Series

Low ESL

WEB

10-Terminal Type Low ESL Capacitor Ideal for Power Supply Decoupling of High-speed Operation IC

Features

1 This is the lowest ESL LW reversed type capacitor.

Since the equivalent series inductance (ESL) of this product is even lower than the LLA series (8-terminal product) with excellent high frequency characteristics, this capacitor is ideal for power supply decoupling of high-speed operation IC.



<Example of Structure>



<Effectiveness of Cancelling Out Inductance by Mutual Inductance>



<Effectiveness of Suppressing Inductance when Mounting a Multi-terminal Capacitor>

The inductance for the boards also becomes lower, not only the capacitor.

2 A maximum operating temperature up to 125°C

This product is applicable to high temperatures (X7* characteristics); however, Murata also offers numerous thin type products, which are ideal as decoupling capacitors on IC package.

Specifications

Size (mm)	2.0×1.25mm
Rated Voltage	4Vdc to 25Vdc
Capacitance	0.22μF to 1.0μF
Main Applications	Application processor/CPU/GPU

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

LLM Series High Dielectric Constant Type LOW ESL Part Number List

2.0×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	6.3Vdc	X7R	0.22μF	±20%	**LLM215R70J224MA11#**	p230
			0.47μF	±20%	**LLM215R70J474MA11#**	p230
	4Vdc	X7S	1.0μF	±20%	**LLM215C70G105MA11#**	p230

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 LLM Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		C ≦ 0.047μF: More than 10000MΩ C > 0.047μF: More than 500Ω • F C: Nominal Capacitance	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance: C ≦ 10μF; Frequency: 1.0±0.1kHz; Voltage: 1.0±0.2Vrms * * For item LLA185 C7 0G 274 to 474, the capacitance should be measured using a voltage of 0.5±0.1Vrms. For item LLA185/215 C7 0G 473, the capacitance should be measured using a voltage of 0.5±0.2Vrms.
7	Dissipation Factor (D.F.)		W.V.:25Vdc min.: 0.025max. W.V.:16/10Vdc: 0.035max. W.V.:6.3Vdc max.: 0.05max.	
8	Temperature Characteristics of Capacitance	No Bias	R7: Within ±15% (-55 to +125°C) R6: Within ±15% (-55 to +85°C) C7: Within ±22% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2 Applying Voltage(VDC): No bias • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature,then measure.
9	Adhesive Strength of Termination		No removal of the terminations or other defect should occur.	Solder the capacitor on the test substrate (glass epoxy board). Applied Force: 5N Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side.
10	Vibration	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Solderability		75% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s
12	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Perform the 5 cycles according to the four heat treatments shown in the following table. Step 1: Min. Operating Temp. +0/-3; 30±3 Step 2: Room Temp.; 2 to 3 Step 3: Max. Operating Temp. +3/-0; 30±3 Step 4: Room Temp.; 2 to 3 Exposure Time: 24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

LLM Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±12.5%	
		D.F.	W.V.: 10Vdc min.: 0.05max. W.V.: 6.3Vdc max.: 0.075max.	
		I.R.	More than 500MΩ or 25Ω • F (Whichever is smaller)	
14	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h • Initial measurement Apply 200% of the rated DC voltage at the max. operating temp. ±3°C for 1h. Remove and set for 24±2h at room temperature. Perform initial measurement.
		Capacitance Change	Within ±12.5%	
		D.F.	W.V.:10Vdc min.: 0.05max. W.V.:6.3Vdc max.: 0.075max.	
		I.R.	More than 1000MΩ or 50Ω • F (Whichever is smaller)	

LW Reversed Controlled ESR Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLR Series

Low ESL

WEB

ESR Controlled Type Low ESL Capacitors Equipped with Anti-resonance Control Function

Features

1 Reduces Anti-resonance

This capacitor is controlled so that the equivalent series resistance (ESR) becomes slightly higher, and is effective in reducing the anti-resonance that occurs when capacitor arrays are used.



2 Lineup of capacitors with ESR values from 100-1,000mΩ.

According to the conditions of the anti-resonance, the most suitable ESR value can be selected from 4 types.

3 Low ESL

This ESR controlled type capacitor has excellent high frequency characteristics, with low equivalent series inductance (ESL). This is also ideal as a decoupling component.

Specifications

Size (mm)	0.8×1.6mm
Rated Voltage	4Vdc
Capacitance	1.0μF
Main Applications	Network processor/ASIC/PMIC



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

LLR Series High Dielectric Constant Type LOW ESL Part Number List

0.8×1.6mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	4Vdc	X7S	1.0μF	±20%	**LLR185C70G105ME01#**	p234
				±20%	**LLR185C70G105ME03#**	p234
				±20%	**LLR185C70G105ME05#**	p234
				±20%	**LLR185C70G105ME07#**	p234

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 LLR Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	**Rated Voltage**		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	**Appearance**		No defects or abnormalities.	Visual inspection.
3	**Dimension**		Within the specified dimensions.	Using Measuring instrument of dimension.
4	**Voltage Proof**		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	**Insulation Resistance (I.R.)**		More than 2000MΩ or 50Ω • F (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 1min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	**Capacitance**		Shown in Rated value.	Measurement Temperature: Room Temperature
7	**Dissipation Factor (D.F.)**		0.120 max.	<table><tr><th>Capacitance</th><th>Frequency</th><th>Voltage</th></tr><tr><td>C ≦ 10μF (10V min.)</td><td>1.0±0.1kHz</td><td>1.0±0.2Vrms</td></tr><tr><td>C ≦ 10μF (6.3V max.)</td><td>1.0±0.1kHz</td><td>0.5±0.1Vrms</td></tr></table>
8	**Temperature Characteristics of Capacitance**	**No Bias**	C7: Within ±22% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. <table><tr><th>Step</th><th>Temperature (°C)</th><th>Applying Voltage(VDC)</th></tr><tr><td>1</td><td>Reference Temp. ±2</td><td rowspan="5">No bias</td></tr><tr><td>2</td><td>Min. Operating Temp. ±3</td></tr><tr><td>3</td><td>Reference Temp. ±2</td></tr><tr><td>4</td><td>Max. Operating Temp. ±3</td></tr><tr><td>5</td><td>Reference Temp. ±2</td></tr></table>• Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature,then measure.
9	**Adhesive Strength of Termination**		No removal of the terminations or other defect should occur. Land Dimensions  Fig.1	Solder the capacitor on the test substrate (glass epoxy board). Applied Force: 5N Holding Time: 10±1s Applied Direction: In parallel with the test substrate and vertical with the capacitor side. <table><tr><th rowspan="2">Part Number</th><th colspan="3">Dimension (mm)</th></tr><tr><th>a</th><th>b</th><th>c</th></tr><tr><td>**LLR18**</td><td>0.3</td><td>1.2</td><td>2.0</td></tr></table>
10	**Vibration**	**Appearance**	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). (Refer to No.9) Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	**Solderability**		75% of the terminations is to be soldered evenly and continuously.	Test Method: Solder bath method Flux: Solution of rosin ethanol 25 (mass)% Preheat: 80 to 120°C for 10 to 30s Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 245±5°C Immersion time: 2±0.5s
12	**Resistance to Soldering Heat**	**Appearance**	No defects or abnormalities.	Test Method: Solder bath Method Solder: Sn-3.0Ag-0.5Cu Solder Temp.: 270±5°C Immersion time: 10±0.5s Exposure Time: 24±2h Preheat: 120 to 150°C for 1min • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

LLR Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
13	Temperature Sudden Change	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). (Refer to No.9) Perform the 5 cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. +0/-3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. +3/-0 / 30±3 4 / Room Temp. / 2 to 3 Exposure Time:24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature,then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	
14	High Temperature High Humidity (Steady)	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). (Refer to No.9) Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. • Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 500MΩ or 12.5Ω • F (Whichever is smaller)	
15	Durability	Appearance	No defects or abnormalities.	Solder the capacitor on the test substrate (glass epoxy board). (Refer to No.9) Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 150% of the rated voltage Charge/discharge current: 50mA max. • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. • Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 1000MΩ or 25Ω • F (Whichever is smaller)	
16	ESR		Murata's Control Code / Specification E01 / 100mΩ±30% E03 / 220mΩ±30% E05 / 470mΩ±30% E07 / 1000mΩ±30%	Measurement Frequency: 10±0.1MHz Measurement Temperature: Room Temperature Measurement Equivalent: HP4294A

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

NFM Series

Low ESL EMI FIL® WEB

This is the most suitable Low ESL capacitors for noise measurement and power decoupling of highspeed electrical devices.

Features

① Low ESL

Since the equivalent series inductance (ESL) is low and excellent in high frequency characteristics, this capacitor is suitable for power supply decoupling of high-speed operation electronic equipment.

Realizes Ultra low ESL by using a extremely shorter high frequency current path

▪ 2-terminal Capacitor

× long current distance
× Narrow wiring width

▪ 3-terminal capacitor



○ Short current distance
○ Wide wiring width
○ Four routes formed in parallel

② Contributes to a reduction in the number of components.

The number of components can be reduced by using low ESL capacitors, while maintaining functions equivalent to 2-terminal capacitor.



2-terminal capacitor
100pcs

3-terminal capacitor
32pcs

③ Contributes to noise suppression

Example of noise suppression effect WEB

Specifications

Size (mm)	1.0×0.5mm to 4.5×1.6mm
Rated Voltage	2.5Vdc to 100Vdc
Capacitance	100pF to 27μF
Main Applications	For decoupling and smoothing circuits, For noise suppression



<Dimensions>

NFM Series Low ESL EMI FIL® Part Number List

1.0×0.5mm

T max.	Rated Voltage	Cap.	Tol.	Part Number	
0.35mm	6.3Vdc	0.47μF	±20%	NFM15PC474R0J3#	
	4Vdc	0.47μF	±20%	NFM15PC474D0G3#	
		1.0μF	±20%	NFM15PC105R0G3#	
0.5mm	16Vdc	2200pF	±20%	NFM15CC222D1C3#	
		22000pF	±20%	NFM15CC223C1C3#	
		47000pF	±20%	NFM15PC473C1C3#	
	10Vdc	2200pF	±20%	NFM15CC222D1A3#	
		22000pF	±20%	NFM15CC223C1A3#	
		47000pF	±20%	NFM15PC473C1A3#	
		0.10μF	±20%	NFM15PC104R1A3#	
		0.22μF	±20%	NFM15PC224R1A3#	
	6.3Vdc	0.10μF	±20%	NFM15PC104D0J3#	
		0.22μF	±20%	NFM15PC224D0J3#	
	2.5Vdc	4.3μF	±20%	NFM15PC435R0E3#	
0.65mm	2.5Vdc	7.5μF	±20%	NFM15PC755R0E3#	
0.7mm	2.5Vdc	9.1μF	±20%	NFM15PC915R0E3#	

1.6×0.8mm

T max.	Rated Voltage	Cap.	Tol.	Part Number	
0.7mm	16Vdc	100pF	±20%	NFM18CC101R1C3#	
		220pF	±20%	NFM18CC221R1C3#	
		470pF	±20%	NFM18CC471R1C3#	
		1000pF	±20%	NFM18CC102R1C3#	
		2200pF	±20%	NFM18CC222R1C3#	
		22000pF	±20%	NFM18CC223R1C3#	
		0.10μF	±20%	NFM18PC104R1C3#	
	6.3Vdc	0.22μF	±20%	NFM18PC224R0J3#	
		0.47μF	±20%	NFM18PC474R0J3#	
			±20%	NFM18PS474R0J3#	
		1.0μF	±20%	NFM18PS105D0J3#	
			±20%	NFM18PS105R0J3#	
		2.2μF	±20%	NFM18PC225B0J3#	
0.9mm	10Vdc	2.2μF	±20%	NFM18PC225B1A3#	
	6.3Vdc	1.0μF	±20%	NFM18PC105R0J3#	

2.0×1.25mm

T max.	Rated Voltage	Cap.	Tol.	Part Number	
0.95mm	50Vdc	220pF	±20%	NFM21CC221R1H3#	
		470pF	±20%	NFM21CC471R1H3#	
		1000pF	±20%	NFM21CC102R1H3#	
		2200pF	±20%	NFM21CC222R1H3#	
		22000pF	±20%	NFM21CC223R1H3#	
	25Vdc	0.10μF	±20%	NFM21PC104R1E3#	
	16Vdc	0.22μF	±20%	NFM21PC224R1C3#	
		0.47μF	±20%	NFM21PC474R1C3#	
		1.0μF	±20%	NFM21PC105B1C3#	
	10Vdc	1.0μF	±20%	NFM21PC105B1A3#	
		4.7μF	±20%	NFM21PC475B1A3#	
0.95mm	6.3Vdc	2.2μF	±20%	NFM21PC225B0J3#	
		10μF	±20%	NFM21PS106B0J3#	

3.2×1.25mm

T max.	Rated Voltage	Cap.	Tol.	Part Number	
0.9mm	50Vdc	220pF	+50/-20%	NFM3DCC221R1H3#	
		470pF	+50/-20%	NFM3DCC471R1H3#	
		1000pF	+50/-20%	NFM3DCC102R1H3#	
		2200pF	+50/-20%	NFM3DCC222R1H3#	
		22000pF	+50/-20%	NFM3DCC223R1H3#	
			±20%	NFM3DPC223R1H3#	D3

3.2×1.6mm

T max.	Rated Voltage	Cap.	Tol.	Part Number	
1.5mm	100Vdc	10000pF	±20%	NFM31KC103R2A3#	D3
		15000pF	±20%	NFM31KC153R2A3#	
		22000pF	±20%	NFM31KC223R2A3#	
		0.10μF	±20%	NFM31KC104R2A3#	
	50Vdc	10000pF	±20%	NFM31KC103R1H3#	D3
		15000pF	±20%	NFM31KC153R1H3#	D3
		22000pF	±20%	NFM31KC223R1H3#	D3
		0.10μF	±20%	NFM31KC104R1H3#	
	6.3Vdc	27μF	±20%	NFM31PC276B0J3#	

4.5×1.6mm

T max.	Rated Voltage	Cap.	Tol.	Part Number	
1.2mm	100Vdc	470pF	+50/-20%	NFM41CC471R2A3#	
		1000pF	+50/-20%	NFM41CC102R2A3#	
		2200pF	+50/-20%	NFM41CC222R2A3#	
		22000pF	+50/-20%	NFM41CC223R2A3#	
	50Vdc	1.5μF	±20%	NFM41PC155B1H3#	
	25Vdc	1.5μF	±20%	NFM41PC155B1E3#	

Part number # indicates the package specification code.

NFM Series Specifications and Test Methods

Specifications and Test Methods, please refer to the search web page.
https://www.murata.com/en-global/products/capacitor



T max.	Rated Voltage	Cap.	Tol.	Part Number
0.35mm	6.3Vdc	0.47μF	±20%	NFM15PC474R0J3#
	4Vdc	0.47μF	±20%	NFM15PC474D0G3#
		1.0μF	±20%	NFM1[illegible]G3#
0.5mm	16Vdc	2200pF	±20%	NFM15[illegible]C3#
		22000pF	±20%	NFM15CC223C1C3#
		47000pF	±20%	NFM15PC473C1C3#
	10Vdc	2200pF	±20%	NFM15CC222D1A3#
		22000pF	±20%	NFM15CC223C1A3#

Links are provided to the product detail pages on the web, and are shown below in the product number table from the PDF version of the catalog which is available on the web.

Detailed Specifications Sheet

- Rated value
- Specifications and Test Methods
- Package
- Caution, Notice

muRata

■SPECIFICATIONS AND TEST METHODS

Mechanical Performance

No	Item	Specification	Test Method
1	Appearance and Dimensions	Appearance:No defects or abnormalities. Dimensions:Within the specified dimensions.	Appearance:Visual inspection. Dimensions:Using calipers.
2	Solderability	Electrodes shall be at least 90% covered with new solder coating.	Flux : Ethanol solution of rosin, 25(wt)% Pre-heat : 150±10°C, 60 to 90s Solder : Sn-3.0Ag-0.5Cu Solder Temperature : 240 ± 3°C Immersion Time : 3±1 s Immersion and emersion rates : 25mm / s
3	Resistance to soldering heat	Meet Table 1. Table 1 Appearance: No damaged Cap. Change: Within ±7.5% I.R.: Meet the initial rated value. DC Resistance: 0.05Ω max.	Flux : Ethanol solution of rosin, 25(wt)% Pre-heat : 150±10°C, 60 to 90s Solder : Sn-3.0Ag-0.5Cu Solder Temperature : 270 ± 5°C Immersion Time : 10 ± 1 s Immersion and emersion rates : 25mm / s Initial values : measured after heat treatment (150+0 / -10 °C,1hour) and exposure in the room condition for 48±4 hours. Then measured after exposure in the room condition for 48±4 hours.
4	Bending Strength	Meet Table 2. Table 2 Appearance: No damaged Cap. Change: Within ±7.5% DC Resistance: 0.05Ω max.	It shall be soldered on the glass-epoxy substrate (100×40×0.8mm). Deflection : 1.0 mm Keeping Time : 5 s Pressure jig, R340, F, Deflection, 45, 45, Product (in mm)
5	Drop	Products shall be no failure after tested.	It shall be dropped on concrete or steel board. Height : 1m Method : Free fall Attitude from which the product is dropped : 3 directions The Number of Time : 3 times for each direction (Total 9 times)

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose

KRM Series

Anti-noise | Deflecting crack | Soldering crack | WEB

Bonding the metal terminals to external electrodes solves design issues by mounting large size MLCC!

Features

① Bond metal terminals to the external electrodes of chips.

The stress applied to the chip is relieved by the elastic action of the metal terminal.



② Substantially reduces noise, board deflection cracks and soldering cracks.

This product is not damaged even with a board deflection of 6 mm.
Solder cracks do not occur even with 2,000 cycles of heat stress.

Acoustic Noise is Reduced with Metal Terminals



Reduces Stress Caused by Board Deflection



Suppresses Solder Cracks Caused by Heat Stress

Chip Size	Chip Only (5750 (in mm)/2220 (in inch) size)		Metal Terminal Type (5750 (in mm)/2220 (in inch) size)	
1000 Cycle		⇧Solder Crack		
2000 Cycle		 ⇧Solder Crack		

Compared with chips only, this product is excellent in solder cracking resistance.

Test Condition: -55 to +125°C, 5min.,(Liquid Phase)
Board Used: Glass Epoxy Board (FR-4)

Demonstrates replacement value of low noise capacitors Experience the effectiveness of the KRM Series.

› Examples of Noise Countermeasures

WEB

③ 2 chips can be stacked.

Realize large capacity by stacking 2 capacitors.

Specifications

Size (mm)	2.2×1.25mm to 6.1×5.3mm
Rated Voltage	16Vdc to 1000Vdc
Capacitance	68000pF to 100μF
Main Applications	For smoothing and noise suppression of DC-DC converters

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

KRM Series High Dielectric Constant Type Anti-noise Deflecting crack Soldering crack Part Number List

2.2×1.25mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
1.9mm	25Vdc	X5R	10μF	±10%	KRM21ER61E106KFA1#	
	16Vdc	X5R	10μF	±10%	KRM21ER61C106KFA1#	
2.0mm	25Vdc	X7S	10μF	±10%	KRM21FC71E106KFA1#	D1
		X6S	10μF	±10%	KRM21FC81E106KFA1#	D1
		X5R	22μF	±20%	KRM21FR61E226MFA1#	

3.5×1.7mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
2.0mm	25Vdc	X5R	10μF	±10%	KRM31FR61E106KH01#	
2.9mm	100Vdc	X7R	1.0μF	±10%	KRM31KR72A105KH01#	
	50Vdc	X7R	4.7μF	±10%	KRM31KR71H475KH01#	
	35Vdc	X6S	10μF	±10%	KRM31KC8YA106KH01#	
	25Vdc	X6S	10μF	±10%	KRM31KC81E106KH01#	

3.6×1.7mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
2.9mm	50Vdc	X7R	2.2μF	±10%	KRM31KR71H225KH01#	

3.7×1.85mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
2.9mm	100Vdc	X7R	2.2μF	±10%	KRM31KR72A225KH01#	

6.1×5.3mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	
3.0mm	1000Vdc	X7R	68000pF	±10%	KRM55LR73A683KH01#	
			0.10μF	±10%	KRM55LR73A104KH01#	
	630Vdc	X7R	0.15μF	±10%	KRM55LR72J154KH01#	
			0.22μF	±10%	KRM55LR72J224KH01#	
	450Vdc	X7R	0.33μF	±10%	KRM55LR72W334KH01#	
			0.47μF	±10%	KRM55LR72W474KH01#	
	250Vdc	X7R	0.68μF	±10%	KRM55LR72E684KH01#	
			1.0μF	±10%	KRM55LR72E105KH01#	
	100Vdc	X7R	4.7μF	±10%	KRM55LR72A475KH01#	
	63Vdc	X7R	4.7μF	±10%	KRM55LR71J475KH01#	
	50Vdc	X7R	4.7μF	±10%	KRM55LR71H475KH01#	
			10μF	±10%	KRM55LR71H106KH01#	
	35Vdc	X7R	10μF	±10%	KRM55LR7YA106KH01#	
			15μF	±10%	KRM55LR7YA156KH01#	
	25Vdc	X7R	15μF	±10%	KRM55LR71E156KH01#	
3.9mm	100Vdc	X7R	6.8μF	±10%	KRM55QR72A685KH01#	
			10μF	±10%	KRM55QR72A106KH01#	
	63Vdc	X7R	10μF	±10%	KRM55QR71J106KH01#	
	50Vdc	X7R	17μF	±10%	KRM55QR71H176KH01#	
	35Vdc	X7R	17μF	±10%	KRM55QR7YA176KH01#	
3.9mm	35Vdc	X7R	22μF	±10%	KRM55QR7YA226KH01#	
	25Vdc	X7R	22μF	±10%	KRM55QR71E226KH01#	
			33μF	±10%	KRM55QR71E336KH01#	
		X7S	47μF	±10%	KRM55QC71E476KH13#	
5.0mm	1000Vdc	X7R	0.15μF	±20%	KRM55TR73A154MH01#	
			0.22μF	±20%	KRM55TR73A224MH01#	
	630Vdc	X7R	0.33μF	±20%	KRM55TR72J334MH01#	
			0.47μF	±20%	KRM55TR72J474MH01#	
	450Vdc	X7R	0.68μF	±20%	KRM55TR72W684MH01#	
			1μF	±20%	KRM55TR72W105MH01#	
	250Vdc	X7R	1.5μF	±20%	KRM55TR72E155MH01#	
			2.2μF	±20%	KRM55TR72E225MH01#	
	100Vdc	X7R	10μF	±20%	KRM55TR72A106MH01#	
	50Vdc	X7R	22μF	±20%	KRM55TR71H226MH01#	
	35Vdc	X7R	22μF	±20%	KRM55TR7YA226MH01#	
			33μF	±20%	KRM55TR7YA336MH01#	
	25Vdc	X7R	33μF	±20%	KRM55TR71E336MH01#	
6.7mm	100Vdc	X7R	15μF	±20%	KRM55WR72A156MH01#	
			22μF	±20%	KRM55WR72A226MH01#	
	63Vdc	X7R	22μF	±20%	KRM55WR71J226MH01#	
	50Vdc	X7R	33μF	±20%	KRM55WR71H336MH01#	
	35Vdc	X7R	47μF	±20%	KRM55WR7YA476MH01#	
	25Vdc	X7R	47μF	±20%	KRM55WR71E476MH01#	
			68μF	±20%	KRM55WR71E686MH01#	
		X7S	100μF	±20%	KRM55WC71E107MH13#	

Part number # indicates the package specification code.

KRM Series Specifications and Test Methods

Specifications and Test Methods, please refer to the search web page.
https://www.murata.com/en-global/products/capacitor



Links are provided to the product detail pages on the web, and are shown below in the product number table from the PDF version of the catalog which is available on the web.

Detailed Specifications Sheet

- Rated value
- Specifications and Test Methods
- Package
- Caution, Notice

Reference only

4. Specifications and test methods

No.	Item	Specifications	Test method
1	Operating temperature range	Char. X5R : -55 to +85°C Char. X6S : -55 to +105°C Char. X7R : -55 to +125°C	
2	Appearance	No defects or abnormalities	Visual inspection.
3	Dimensions	Within the specified dimension.	Using calipers and micrometers.
4	Dielectric strength	No defects or abnormalities.	No failure should be observed when voltage in the table is applied between the trminations for 1 to 5 s, provided the charge/discharge current is less than 50mA. Rated Voltage: DC25V, DC35V, DC50V — Test Voltage: 250% of the rated voltage Rated Voltage: DC100V — Test Voltage: 200% of the rated voltage
5	Insulation resistance(I.R.)	Rated Voltage: DC25V, DC35V — I.R.: 50MΩ·μF or more Rated Voltage: DC50V , DC100V — I.R.: 500MΩ·μF or more	The insulation resistance should be measured with rated voltage and within 60±5 s of charging.
6	Capacitance	Within the specified tolerance.	The capacicance/D.F.should be measured at reference temperature at the meaning frequency and voltage shown in the table. Nominal capacitance: C＞10μF — Measuring frequency: 120±24Hz — Measuring volgate: AC0.5±0.1V (r.m.s.) Nominal capacitance: C≦10μF — Measuring frequency: 1±0.2kHz — Measuring volgate: AC1.0±0.2V (r.m.s.)
7	Dissipation Factor (D.F.)	Rated Voltage: DC25V, DC35V — D.F.: 0.15 max. Rated Voltage: DC50V — D.F.: 0.025 max. Rated Voltage: DC100V — D.F.: 0.05 max.	
8	Capacitance Temperature Characteristics	Char. X5R : within ±15% (Temp.Range:-55 to +85°C) Char. X6S : within ±22% (Temp.Range:-55 to +105°C) Char. X7R : within ±15% (Temp.Range:-55 to +125°C)	The capacitance measurement should be made at each step specified in the table. •Pretreatment Perform the heat treatment at 150+0/-10°C for 60±5 min and then let sit for 24±2 h at room condition*.
9	Vibration resistance — Appearance	No defects or abnormalities.	Solder the capacitor to the Test Jig A (glass epoxy board) shown in “Complement of test
	Vibration resistance — Capacitance	Within the specified tolerance.	

Step	1	2	3	4	5
Temp.(°C)	25±2	Min. Operating Temp. ±3	25±2	Max. Operating Temp. ±2	25±2

High Effective Capacitance & High Allowable Ripple Current Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose

KR3 Series

Anti-noise | Deflecting crack | Soldering crack | WEB

Bonding the metal terminals to external electrodes solves design issues by mounting large size MLCC!

Features

① Bond Metal Terminals to External Electrodes of Chips

This product has high resistance to heat and mechanical impact and greatly reduces acoustic noise of boards by ceramics.



② Stacking of Chips

Achieve high capacity by stacking 2 capacitors.

Comparison of Noise Reduction Effects



Evaluation Items: 5750 (in mm)/2220 (in inch) size/DC630V/220nF
Test Method: DC50V, AC10Vp-p/3kHz
Test Board: Glass Epoxy Board (T=1.6mm)
Test Quantity: 3pc
Distance Between Microphone and Board: 3mm

Note: Results Using Murata's Evaluation Board

Reduces Stress Caused by Board Deflection



Suppresses Solder Cracks Caused by Heat Stress

Chip Size	Chip Only (5750 (in mm)/2220 (in inch) size)		Metal Terminal Type (5750 (in mm)/2220 (in inch) size)	
1000 Cycle		⇧Solder Crack		
2000 Cycle		 ⇧Solder Crack		

Compared with chips only, this product is excellent in solder cracking resistance.

Test Condition: -55 to +125°C, 5min., (Liquid Phase)
Board Used: Glass Epoxy Board (FR-4)

③ Adopted Low Dielectric Constant Materials

Improved effective capacity and ripple resistant performance, compared to conventional products (X7R characteristics).



Specifications

Size (mm)	6.1×5.3mm
Rated Voltage	250Vdc to 630Vdc
Capacitance	0.10μF to 2.2μF
Main Applications	For DC-DC converters of general electronic equipment

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

KR3 Series High Dielectric Constant Type Anti-noise Deflecting crack Soldering crack Part Number List

6.1×5.3mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
3.0mm	630Vdc	X7T	0.10μF	±10%	**KR355LD72J104KH01#**	p246
			0.15μF	±10%	**KR355LD72J154KH01#**	p246
	450Vdc	X7T	0.22μF	±10%	**KR355LD72W224KH01#**	p246
			0.33μF	±10%	**KR355LD72W334KH01#**	p246
			0.47μF	±10%	**KR355LD72W474KH01#**	p246
	250Vdc	X7T	0.47μF	±10%	**KR355LD72E474KH01#**	p246
			0.68μF	±10%	**KR355LD72E684KH01#**	p246
3.9mm	630Vdc	X7T	0.22μF	±10%	**KR355QD72J224KH01#**	p246
			0.27μF	±10%	**KR355QD72J274KH01#**	p246
	450Vdc	X7T	0.56μF	±10%	**KR355QD72W564KH01#**	p246
	250Vdc	X7T	1.0μF	±10%	**KR355QD72E105KH01#**	p246
5.0mm	450Vdc	X7T	0.68μF	±20%	**KR355TD72W684MH01#**	p246
			1.0μF	±20%	**KR355TD72W105MH01#**	p246
	250Vdc	X7T	1.5μF	±20%	**KR355TD72E155MH01#**	p246
6.7mm	630Vdc	X7T	0.47μF	±20%	**KR355WD72J474MH01#**	p246
			0.56μF	±20%	**KR355WD72J564MH01#**	p246
	450Vdc	X7T	1.2μF	±20%	**KR355WD72W125MH01#**	p246
	250Vdc	X7T	2.2μF	±20%	**KR355WD72E225MH01#**	p246

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 KR3 Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Operating Temperature		-55 to +125°C	
2	Appearance		No defects or abnormalities	Visual inspection.
3	Dimension		Within the specified dimension.	Using calipers and micrometers.
4	Dielectric Strength		No defects or abnormalities.	No failure should be observed when voltage in the table is applied between the terminations for 1 to 5s, provided the charge/discharge current is less than 50mA. Rated Voltage / Test Voltage DC250V / 200% of the rated voltage DC450V / 150% of the rated voltage DC630V / 120% of the rated voltage
5	Insulation Resistance (I.R.)		More than 10000MΩ or 100MΩ ▪ μF (Whichever is smaller)	The insulation resistance should be measured with DC500±50V (DC250±25V in case of rated voltage: DC250V, DC450V) andwithin 60±5s of charging.
6	Capacitance		Within the specified tolerance.	Capacitance should be measured at the frequency of 1±0.2kHz and a voltage of AC1.0±0.2V (r.m.s.).
7	Dissipation Factor (D.F.)		0.01 max.	D.F. should be measured at the frequency of 1±0.2kHz and a voltage of AC1.0±0.2V (r.m.s.).
8	Capacitance Temperature Characteristics		Cap. change within +22/-33% (Temp.Range: -55 to +125°C)	The capacitance measurement should be made at each step specified in the table. ▪ Pretreatment Perform the heat treatment at 150+0/-10°C for 60±5min and then let sit for 24±2h at room condition*. Step / Temperature (°C) 1 / 25±2 2 / Min. Operating Temp. ±3 3 / 25±2 4 / Max. Operating Temp. ±3 5 / 25±2
9	Vibration Resistance	Appearance	No defects or abnormalities.	Solder the capacitor to the Test Jig A (glass epoxy board) shown in "Complement of Test Method". The capacitor should be subjected to a simple harmonic motion having a total amplitude of 1.5mm, the frequency being varied uniformly between the approximate limits of 10 and 55Hz . The frequency range, from 10 to 55Hz and return to 10Hz, should be traversed in approximately 1min. This motion should be applied for a period of 2h in each of 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified tolerance.	
		D.F.	Pass the item No.7.	
10	Solderability of Termination		The metal surface is soldered well.	Reflow Soldering: Peak 260+0/-5°C The area of soldering 230°C min., 20 to 40s Let sit for 24±2h at room condition*, then measure. ▪ Pretreatment Perform the heat treatment at 150+0/-10°C for 60±5min and then let sit for 24±2h at room condition*. 
11	Resistance to Soldering Heat	Appearance	No marking defects.	Reflow Soldering ▪ See Item 10 Solderability of termination In a soldering iron case Temp. of solder: 350±10°C Solder time: 4+1/-0 s Let sit for 24±2h at room condition*, then measure. Please refer to "⚠Caution 4-3. Correction of Soldered Portion"
		Capacitance Change	Within ±10%	
		D.F.	Pass the item No.7.	
		I.R.	Pass the item No.5.	
		Dielectric Strength	Pass the item No.4.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

KR3 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard:JIS C 5101, IEC60384)
12	Adhesive Strength of Termination		No removal of the terminations or other defects should occur.	Solder the capacitor to the Test Jig A (glass epoxy board) shown in "Complement of Test Method". Then apply 10N force in the direction of the arrow. 
13	Deflection		No marking defects.	Solder the capacitor to the Test Jig B (glass epoxy board) shown in "Complement of Test Method". Then apply the force in the direction shown in "Test Method of Deflection" of "Complement of Test Method". ▪ Flexure: 5mm ▪ Hold time: 5s
14	Strength of metal Terminal		Termination not to be broken or loosened.	A static load of 10N using a pressure jig should be applied to the center in the direction of the arrow and held for 10s 
15	Temperature Cycle	Appearance	No marking defects.	Fix the capacitor to the supporting Test Jig A (glass epoxy board) shown in "Complement of Test Method". Perform the 100 cycles according to the 4 heat treatments listed the following table. Step / Temp. (°C) / Time (min) 1 / Min. Operating Temp. ±3 / 30±3 2 / Room Temp. / 2 to 3 3 / Max. Operating Temp. ±2 / 30±3 4 / Room Temp. / 2 to 3 Let sit for 24±2h at room condition*, then measure. ▪ Pretreatment Perform the heat treatment at 150+0/-10°C for 60±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±7.5%	
		D.F.	Pass the item No.7.	
		I.R.	Pass the item No.5.	
		Dielectric Strength	Pass the item No.4.	
16	Humidity (Steady State)	Appearance	No marking defects.	Sit the capacitor at 40±2°C and relative humidity 90 to 95% for 500+24/-0h. Remove and let sit for 24±2h at room condition*, then measure. ▪ Pretreatment Perform the heat treatment at 150+0/-10°C for 60±5min and then let sit for 24±2h at room condition*.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000 MΩ or 10 MΩ ▪ μF (Whichever is smaller)	
		Dielectric Strength	Pass the item No.4.	
17	Life	Appearance	No marking defects.	Apply voltage as in the table for 1000+48/-0h at maximum operating temperature±3°C. Remove and let sit for 24±2h at room condition*, then measure. Rated Voltage / Applied Voltage DC250V / 150% of the rated voltage DC450V / 130% of the rated voltage DC630V / 120% of the rated voltage The charge/discharge current is less than 50mA. ▪ Pretreatment Apply test voltage for 60±5min at test temperature.
		Capacitance Change	Within ±12.5%	
		D.F.	0.02 max.	
		I.R.	More than 1000 MΩ or 10 MΩ ▪ μF (Whichever is smaller)	
		Dielectric Strength	Pass the item No.4.	

* Room Condition: Temperature: 15 to 35°C, Relative humidity: 45 to 75%, Atmosphere pressure: 86 to 106kPa

Continued on the following page.↗

KR3 Series Specifications and Test Methods (1)

Continued from the preceding page.↘

Complement of Test Method

Test Jig

The test jig should be Jig A or Jig B as described in "Specifications and Test Methods".

The specimen should be soldered by the conditions as described below.

Soldering Method: Reflow soldering
Thickness of Metal-mask: 200μm
Solder: Sn-3.0Ag-0.5Cu

(1) Test Jig A



Dimension (mm)		
a	b	c
4.5	8.0	5.6

- Material: Glass Epoxy Board
- Thickness: 1.6mm
- Thickness of copper foil: 0.035mm

(2) Test Jig B



Dimension (mm)			
a	b	c	d
4.5	8.0	5.6	1.0

- Material: Glass Epoxy Board
- Thickness of copper foil: 0.035mm

Wire Bonding Mount Multilayer Microchip Capacitors for General Purpose

GMA Series

Bonding

WEB

These capacitors have gold-plated electrodes and are designed specifically for wire bonding.

Features

① Allows for high density mounting.

Noise can be reduced by eliminating the routing of the wire, and high efficiency can be achieved with a built-in capacitor in a package, such as IC. Miniaturization of the set is also possible.



<Example of Structure>



<Mounting Example>

② Achieved small size and high capacitance with a multilayer structure.

Small size, high capacitance	Minimum 0.38mm×0.38mm Achieved 0.1μF in 0.5mm×0.5mm size

Lineup comparison table with competitor's is provided in my Murata Capacitor Site (need to sign in & approval from the site) WEB

③ Ideal for bypass applications

Especially for optical communication related devices such as TOSA/ROSA.

④ Excellent in high frequency characteristics.

Since the capacitor consists of an upper/lower electrode structure, the current path becomes shorter and lowers the ESL. Compared with the general purpose GRM series of the same capacity, the impedance of this product becomes lower at high frequencies.



<Comparison between Impedance - Frequency Characteristics>

Specifications

Size (mm)	0.38×0.38mm to 0.8×0.8mm
Rated Voltage	6.3Vdc to 100Vdc
Capacitance	100pF to 0.47μF
Main Applications	1. Optical communication related devices such as TOSA/ROSA. 2. Various device related, such as GaAsIC (mounted in IC packages) 3. Measuring instruments, other ultra compact/thin devices



<Dimensions>

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.

GMA Series High Dielectric Constant Type Part Number List

0.38×0.38mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.35mm	10Vdc	X7R	1000pF	±20%	**GMA0D3R71A102MA01#**	p254
			1500pF	±20%	**GMA0D3R71A152MA01#**	p254
			1800pF	±20%	**GMA0D3R71A182MA01#**	p254
			10000pF	±20%	**GMA0D3R71A103MA01#**	p254
		R	1000pF	±20%	**GMA0D3R11A102MA01#**	p254
			1500pF	±20%	**GMA0D3R11A152MA01#**	p254
			1800pF	±20%	**GMA0D3R11A182MA01#**	p254
			10000pF	±20%	**GMA0D3R11A103MA01#**	p254
		B	1000pF	±20%	**GMA0D3B11A102MA01#**	p254
			1500pF	±20%	**GMA0D3B11A152MA01#**	p254
			1800pF	±20%	**GMA0D3B11A182MA01#**	p254

0.5×0.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.4mm	100Vdc	X7R	100pF	±20%	**GMA05XR72A101MA01#**	p254
			150pF	±20%	**GMA05XR72A151MA01#**	p254
			220pF	±20%	**GMA05XR72A221MA01#**	p254
			330pF	±20%	**GMA05XR72A331MA01#**	p254
			470pF	±20%	**GMA05XR72A471MA01#**	p254
			680pF	±20%	**GMA05XR72A681MA01#**	p254
			1000pF	±20%	**GMA05XR72A102MA01#**	p254
	25Vdc	X7R	1500pF	±20%	**GMA05XR71E152MA11#**	p254
			2200pF	±20%	**GMA05XR71E222MA11#**	p254
			3300pF	±20%	**GMA05XR71E332MA11#**	p254
			4700pF	±20%	**GMA05XR71E472MA11#**	p254
		B	1500pF	±20%	**GMA05XB31E152MA11#**	p254
			2200pF	±20%	**GMA05XB31E222MA11#**	p254
			3300pF	±20%	**GMA05XB31E332MA11#**	p254
			4700pF	±20%	**GMA05XB31E472MA11#**	p254
	10Vdc	X7R	6800pF	±20%	**GMA05XR71A682MA01#**	p254
			10000pF	±20%	**GMA05XR71A103MA01#**	p254
			15000pF	±20%	**GMA05XR71A153MA01#**	p254
			22000pF	±20%	**GMA05XR71A223MA01#**	p254
		R	6800pF	±20%	**GMA05XR11A682MA01#**	p254
			10000pF	±20%	**GMA05XR11A103MA01#**	p254
			15000pF	±20%	**GMA05XR11A153MA01#**	p254
			22000pF	±20%	**GMA05XR11A223MA01#**	p254
		B	6800pF	±20%	**GMA05XB11A682MA01#**	p254
			10000pF	±20%	**GMA05XB11A103MA01#**	p254
			15000pF	±20%	**GMA05XB11A153MA01#**	p254
			22000pF	±20%	**GMA05XB11A223MA01#**	p254
	6.3Vdc	X5R	0.10μF	±20%	**GMA05XR60J104ME12#**	p252
		B	0.10μF	±20%	**GMA05XB30J104ME12#**	p252

0.8×0.8mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.6mm	100Vdc	X7R	1500pF	±20%	**GMA085R72A152MA01#**	p254
			2200pF	±20%	**GMA085R72A222MA01#**	p254
			3300pF	±20%	**GMA085R72A332MA01#**	p254
			4700pF	±20%	**GMA085R72A472MA01#**	p254
			6800pF	±20%	**GMA085R72A682MA01#**	p254
	25Vdc	X7R	10000pF	±20%	**GMA085R71E103MA11#**	p254
			15000pF	±20%	**GMA085R71E153MA11#**	p254
			22000pF	±20%	**GMA085R71E223MA11#**	p254
		B	10000pF	±20%	**GMA085B31E103MA11#**	p254
			15000pF	±20%	**GMA085B31E153MA11#**	p254
			22000pF	±20%	**GMA085B31E223MA11#**	p254
	10Vdc	X7R	33000pF	±20%	**GMA085R71A333MA01#**	p254
			47000pF	±20%	**GMA085R71A473MA01#**	p254
			68000pF	±20%	**GMA085R71A683MA01#**	p254
			0.10μF	±20%	**GMA085R71A104MA01#**	p254
		R	33000pF	±20%	**GMA085R11A333MA01#**	p254
			47000pF	±20%	**GMA085R11A473MA01#**	p254
			68000pF	±20%	**GMA085R11A683MA01#**	p254
			0.10μF	±20%	**GMA085R11A104MA01#**	p254
		B	33000pF	±20%	**GMA085B11A333MA01#**	p254
			47000pF	±20%	**GMA085B11A473MA01#**	p254
			68000pF	±20%	**GMA085B11A683MA01#**	p254
			0.10μF	±20%	**GMA085B11A104MA01#**	p254
	6.3Vdc	X5R	0.47μF	±20%	**GMA085R60J474ME12#**	p252
		B	0.47μF	±20%	**GMA085B30J474ME12#**	p252

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GMA Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		More than 2000MΩ or 50Ω • F (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 1min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Capacitance: C ≦ 10μF (6.3V max.); Frequency: 1.0±0.1kHz; Voltage: 0.5±0.1Vrms
7	Dissipation Factor (D.F.)		0.1 max.	
8	Temperature Characteristics of Capacitance	No Bias	B3: Within ±10% (-25 to +85°C) R6: Within ±15% (-55 to +85°C) C8: Within ±22% (-55 to +105°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step 1: Reference Temp. ±2 Step 2: Min. Operating Temp. ±3 Step 3: Reference Temp. ±2 Step 4: Max. Operating Temp. ±3 Step 5: Reference Temp. ±2 Applying Voltage (VDC): No bias • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
9	Adhesive Strength of Termination	Bond Strength	Pull force: 0.03N min.	MIL-STD-883 Method 2011 Condition D Mount the capacitor on a gold metalized alumina substrate with Au-20Sn and bond a ø25μm (ø0.001 inch) gold wire to the capacitor terminal using an ultrasonic ball bond. Then, pull wire.
		Die Shear Strength	Die Shear force: 2N min.	MIL-STD-883 Method 2019 Mount the capacitor on a gold metalized alumina substrate with Au-20Sn. Apply the force parallel to the substrate.
10	Vibration *	Appearance	No defects or abnormalities.	Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Temperature Sudden Change *	Appearance	No defects or abnormalities.	Perform the five cycles according to the four heat treatments shown in the following table. Step 1: Min. Operating Temp. +0/-3; 30±3 Step 2: Room Temp.; 2 to 3 Step 3: Max. Operating Temp. +3/-0; 30±3 Step 4: Room Temp.; 2 to 3 Exposure Time: 24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

GMA Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	High Temperature High Humidity (Steady) *	Appearance	No defects or abnormalities.	Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. ▪ Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 500MΩ or 12.5Ω ▪ F (Whichever is smaller)	
13	Durability *	Appearance	No defects or abnormalities.	Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 150% of the rated voltage Charge/discharge current: 50mA max. ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. ▪ Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 1000MΩ or 25Ω ▪ F (Whichever is smaller)	

* Mounting for testing: The capacitors should be mounted on the substrate as shown below using die bonding and wire bonding when tests No.10 to 13 are performed.





2 GMA Series Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		C ≦ 0.047μF: More than 10000MΩ C > 0.047μF: More than 500Ω • F C: Nominal Capacitance	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: 1.0±0.2Vrms
7	Dissipation Factor (D.F.)		W.V.: 25Vdc min.: 0.025max. W.V.: 16/10Vdc: 0.035max. W.V.: 6.3Vdc: 0.05max.	
8	Temperature Characteristics of Capacitance	No Bias	B1, B3: Within ±10% (-25 to +85°C) R1, R7: Within ±15% (-55 to +125°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. In case of applying voltage, the capacitance change should be measured after 1min with applying voltage in equilibration of each temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) / Applying Voltage (VDC) 1 Reference Temp. ±2 — No bias 2 Min.Operating Temp. ±3 3 Reference Temp. ±2 4 Max.Operating Temp. ±3 5 Reference Temp. ±2 — 50% of the rated voltage (For B1, R1) 6 Min.Operating Temp. ±3 7 Reference Temp. ±2 8 Max.Operating Temp. ±3 • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		50% of the Rated Voltage	B1: Within +10/-30% R1: Within +15/-40%	
9	Adhesive Strength of Termination	Bond Strength	Pull force: 0.03N min.	MIL-STD-883 Method 2011 Condition D Mount the capacitor on a gold metalized alumina substrate with Au-20Sn and bond a ø25μm (ø0.001 inch) gold wire to the capacitor terminal using an ultrasonic ball bond. Then, pull wire.
		Die Shear Strength	Die Shear force: 2N min.	MIL-STD-883 Method 2019 Mount the capacitor on a gold metalized alumina substrate with Au-20Sn. Apply the force parallel to the substrate.
10	Vibration *	Appearance	No defects or abnormalities.	Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Temperature Sudden Change *	Appearance	No defects or abnormalities.	Perform the five cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min) 1 Min. Operating Temp. +0/-3 30±3 2 Room Temp. 2 to 3 3 Max. Operating Temp. +3/-0 30±3 4 Room Temp. 2 to 3 Exposure Time: 24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

GMA Series Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	High Temperature High Humidity (Steady) *	Appearance	No defects or abnormalities.	Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±12.5%	
		D.F.	W.V.: 25Vdc min.: 0.05max. W.V.: 16/10Vdc: 0.05max. W.V.: 6.3Vdc: 0.075max.	
		I.R.	More than 500MΩ or 25Ω • F (Whichever is smaller)	
13	Durability *	Appearance	No defects or abnormalities.	Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h • Initial measurement Apply 200% of the rated DC voltage at the max. operating temp. ±3°C for 1h. Remove and set for 24±2h at room temperature. Perform initial measurement.
		Capacitance Change	Within ±12.5%	
		D.F.	W.V.: 25Vdc min.: 0.05max. W.V.: 16/10Vdc: 0.05max. W.V.: 6.3Vdc: 0.075max.	
		I.R.	More than 1000MΩ or 50Ω • F (Whichever is smaller)	

* Mounting for testing: The capacitors should be mounted on the substrate as shown below using die bonding and wire bonding when tests No.10 to 13 are performed.





Wire Bonding/AuSn Soldering Mount Chip Multilayer Ceramic Capacitors for General Purpose

GMD Series

Bonding

WEB

These capacitors have gold-plated electrodes and are designed specifically for wire bonding and use of gold-tin (AuSn) solder.

Features

1 Designed specifically for wire bonding and use of gold-tin (AuSn) solder.

The gold-plated external electrodes make these devices suitable for wire bonding or use of gold tin (AuSn) solder.



<Example of Structure>



<Mounting Example>

*This product is suitable only for wire bonding or use of gold-tin (AuSn) solder. Other mounting methods should not be used.

2 Ideal for mounting in packages, such as optical communication related devices, IC and etc.

Noise can be reduced by eliminating the routing of the wire, and high efficiency can be achieved with a built-in capacitor in the package, such as TO-CAN, IC and etc. by wire bonding mounting.

3 Contributes to the miniaturization of the set.

Murata offers a lineup of small size products, such as the 0603 (0201) and 1005 (0402) in mm (inch).

Specifications

Size (mm)	0.6×0.3mm to 1.0×0.5mm
Rated Voltage	6.3Vdc to 50Vdc
Capacitance	100pF to 1.0μF
Main Applications	Various device related, such as GaAsIC (mounted in IC packages)

This catalog contains only a portion of the product lineup.
Please refer to the capacitor search tool on the Murata Web site for details.



<Dimensions>

GMD Series High Dielectric Constant Type Part Number List

0.6×0.3mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.33mm	25Vdc	X7R	100pF	±10%	GMD033R71E101KA01#	p259
			120pF	±10%	GMD033R71E121KA01#	p259
			150pF	±10%	GMD033R71E151KA01#	p259
			180pF	±10%	GMD033R71E181KA01#	p259
			220pF	±10%	GMD033R71E221KA01#	p259
			270pF	±10%	GMD033R71E271KA01#	p259
			330pF	±10%	GMD033R71E331KA01#	p259
			390pF	±10%	GMD033R71E391KA01#	p259
			470pF	±10%	GMD033R71E471KA01#	p259
			560pF	±10%	GMD033R71E561KA01#	p259
			680pF	±10%	GMD033R71E681KA01#	p259
			820pF	±10%	GMD033R71E821KA01#	p259
			1000pF	±10%	GMD033R71E102KA01#	p259
			1200pF	±10%	GMD033R71E122KA01#	p259
			1500pF	±10%	GMD033R71E152KA01#	p259
		R	100pF	±10%	GMD033R11E101KA01#	p259
			120pF	±10%	GMD033R11E121KA01#	p259
			150pF	±10%	GMD033R11E151KA01#	p259
			180pF	±10%	GMD033R11E181KA01#	p259
			220pF	±10%	GMD033R11E221KA01#	p259
			270pF	±10%	GMD033R11E271KA01#	p259
			330pF	±10%	GMD033R11E331KA01#	p259
			390pF	±10%	GMD033R11E391KA01#	p259
			470pF	±10%	GMD033R11E471KA01#	p259
			560pF	±10%	GMD033R11E561KA01#	p259
			680pF	±10%	GMD033R11E681KA01#	p259
			820pF	±10%	GMD033R11E821KA01#	p259
			1000pF	±10%	GMD033R11E102KA01#	p259
			1200pF	±10%	GMD033R11E122KA01#	p259
			1500pF	±10%	GMD033R11E152KA01#	p259
		B	100pF	±10%	GMD033B11E101KA01#	p259
			120pF	±10%	GMD033B11E121KA01#	p259
			150pF	±10%	GMD033B11E151KA01#	p259
			180pF	±10%	GMD033B11E181KA01#	p259
			220pF	±10%	GMD033B11E221KA01#	p259
			270pF	±10%	GMD033B11E271KA01#	p259
			330pF	±10%	GMD033B11E331KA01#	p259
			390pF	±10%	GMD033B11E391KA01#	p259
			470pF	±10%	GMD033B11E471KA01#	p259
			560pF	±10%	GMD033B11E561KA01#	p259
			680pF	±10%	GMD033B11E681KA01#	p259
			820pF	±10%	GMD033B11E821KA01#	p259
			1000pF	±10%	GMD033B11E102KA01#	p259
			1200pF	±10%	GMD033B11E122KA01#	p259
			1500pF	±10%	GMD033B11E152KA01#	p259
	16Vdc	X7R	1800pF	±10%	GMD033R71C182KA11#	p259
			2200pF	±10%	GMD033R71C222KA11#	p259
			2700pF	±10%	GMD033R71C272KA11#	p259
			3300pF	±10%	GMD033R71C332KA11#	p259
		R	1800pF	±10%	GMD033R11C182KA11#	p259
			2200pF	±10%	GMD033R11C222KA11#	p259
			2700pF	±10%	GMD033R11C272KA11#	p259
0.33mm	16Vdc	R	3300pF	±10%	GMD033R11C332KA11#	p259
		B	1800pF	±10%	GMD033B31C182KA11#	p259
			2200pF	±10%	GMD033B31C222KA11#	p259
			2700pF	±10%	GMD033B31C272KA11#	p259
			3300pF	±10%	GMD033B31C332KA11#	p259
	10Vdc	X7R	3900pF	±10%	GMD033R71A392KA01#	p259
			4700pF	±10%	GMD033R71A472KA01#	p259
			5600pF	±10%	GMD033R71A562KA01#	p259
			6800pF	±10%	GMD033R71A682KA01#	p259
			8200pF	±10%	GMD033R71A822KA01#	p259
			10000pF	±10%	GMD033R71A103KA01#	p259
		R	3900pF	±10%	GMD033R11A392KA01#	p259
			4700pF	±10%	GMD033R11A472KA01#	p259
			5600pF	±10%	GMD033R11A562KA01#	p259
			6800pF	±10%	GMD033R11A682KA01#	p259
			8200pF	±10%	GMD033R11A822KA01#	p259
			10000pF	±10%	GMD033R11A103KA01#	p259
		B	3900pF	±10%	GMD033B11A392KA01#	p259
			4700pF	±10%	GMD033B11A472KA01#	p259
			5600pF	±10%	GMD033B11A562KA01#	p259
			6800pF	±10%	GMD033B11A682KA01#	p259
			8200pF	±10%	GMD033B11A822KA01#	p259
			10000pF	±10%	GMD033B11A103KA01#	p259
	6.3Vdc	X5R	56000pF	±10%	GMD033R60J563KE11#	p261
			68000pF	±10%	GMD033R60J683KE11#	p261
			82000pF	±10%	GMD033R60J823KE11#	p261
			0.10μF	±10%	GMD033R60J104KE11#	p261
		B	56000pF	±10%	GMD033B30J563KE11#	p261
			68000pF	±10%	GMD033B30J683KE11#	p261
			82000pF	±10%	GMD033B30J823KE11#	p261
			0.10μF	±10%	GMD033B30J104KE11#	p261

1.0×0.5mm

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	X7R	220pF	±10%	GMD155R71H221KA01#	p259
			270pF	±10%	GMD155R71H271KA01#	p259
			330pF	±10%	GMD155R71H331KA01#	p259
			390pF	±10%	GMD155R71H391KA01#	p259
			470pF	±10%	GMD155R71H471KA01#	p259
			560pF	±10%	GMD155R71H561KA01#	p259
			680pF	±10%	GMD155R71H681KA01#	p259
			820pF	±10%	GMD155R71H821KA01#	p259
			1000pF	±10%	GMD155R71H102KA01#	p259
			1200pF	±10%	GMD155R71H122KA01#	p259
			1500pF	±10%	GMD155R71H152KA01#	p259
			1800pF	±10%	GMD155R71H182KA01#	p259
			2200pF	±10%	GMD155R71H222KA01#	p259
			2700pF	±10%	GMD155R71H272KA01#	p259
			3300pF	±10%	GMD155R71H332KA01#	p259
			3900pF	±10%	GMD155R71H392KA01#	p259
			4700pF	±10%	GMD155R71H472KA01#	p259
		R	220pF	±10%	GMD155R11H221KA01#	p259

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

GMD Series High Dielectric Constant Type Part Number List

(→ 1.0×0.5mm)

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	50Vdc	R	270pF	±10%	**GMD155R11H271KA01#**	p259
			330pF	±10%	**GMD155R11H331KA01#**	p259
			390pF	±10%	**GMD155R11H391KA01#**	p259
			470pF	±10%	**GMD155R11H471KA01#**	p259
			560pF	±10%	**GMD155R11H561KA01#**	p259
			680pF	±10%	**GMD155R11H681KA01#**	p259
			820pF	±10%	**GMD155R11H821KA01#**	p259
			1000pF	±10%	**GMD155R11H102KA01#**	p259
			1200pF	±10%	**GMD155R11H122KA01#**	p259
			1500pF	±10%	**GMD155R11H152KA01#**	p259
			1800pF	±10%	**GMD155R11H182KA01#**	p259
			2200pF	±10%	**GMD155R11H222KA01#**	p259
			2700pF	±10%	**GMD155R11H272KA01#**	p259
			3300pF	±10%	**GMD155R11H332KA01#**	p259
			3900pF	±10%	**GMD155R11H392KA01#**	p259
			4700pF	±10%	**GMD155R11H472KA01#**	p259
		B	220pF	±10%	**GMD155B11H221KA01#**	p259
			270pF	±10%	**GMD155B11H271KA01#**	p259
			330pF	±10%	**GMD155B11H331KA01#**	p259
			390pF	±10%	**GMD155B11H391KA01#**	p259
			470pF	±10%	**GMD155B11H471KA01#**	p259
			560pF	±10%	**GMD155B11H561KA01#**	p259
			680pF	±10%	**GMD155B11H681KA01#**	p259
			820pF	±10%	**GMD155B11H821KA01#**	p259
			1000pF	±10%	**GMD155B11H102KA01#**	p259
			1200pF	±10%	**GMD155B11H122KA01#**	p259
			1500pF	±10%	**GMD155B11H152KA01#**	p259
			1800pF	±10%	**GMD155B11H182KA01#**	p259
			2200pF	±10%	**GMD155B11H222KA01#**	p259
			2700pF	±10%	**GMD155B11H272KA01#**	p259
			3300pF	±10%	**GMD155B11H332KA01#**	p259
			3900pF	±10%	**GMD155B11H392KA01#**	p259
			4700pF	±10%	**GMD155B11H472KA01#**	p259
	25Vdc	X7R	5600pF	±10%	**GMD155R71E562KA01#**	p259
			6800pF	±10%	**GMD155R71E682KA01#**	p259
			8200pF	±10%	**GMD155R71E822KA01#**	p259
			10000pF	±10%	**GMD155R71E103KA01#**	p259
			12000pF	±10%	**GMD155R71E123KA01#**	p259
			15000pF	±10%	**GMD155R71E153KA01#**	p259
			18000pF	±10%	**GMD155R71E183KA01#**	p259
			22000pF	±10%	**GMD155R71E223KA01#**	p259
			27000pF	±10%	**GMD155R71E273KA11#**	p259
			33000pF	±10%	**GMD155R71E333KA11#**	p259
			39000pF	±10%	**GMD155R71E393KA11#**	p259
			47000pF	±10%	**GMD155R71E473KA11#**	p259
		R	5600pF	±10%	**GMD155R11E562KA01#**	p259
			6800pF	±10%	**GMD155R11E682KA01#**	p259
			8200pF	±10%	**GMD155R11E822KA01#**	p259
			10000pF	±10%	**GMD155R11E103KA01#**	p259
			12000pF	±10%	**GMD155R11E123KA01#**	p259
			15000pF	±10%	**GMD155R11E153KA01#**	p259
			18000pF	±10%	**GMD155R11E183KA01#**	p259
			22000pF	±10%	**GMD155R11E223KA01#**	p259
			27000pF	±10%	**GMD155R11E273KA11#**	p259

T max.	Rated Voltage	TC Code	Cap.	Tol.	Part Number	p*
0.55mm	25Vdc	R	33000pF	±10%	**GMD155R11E333KA11#**	p259
			39000pF	±10%	**GMD155R11E393KA11#**	p259
			47000pF	±10%	**GMD155R11E473KA11#**	p259
		B	5600pF	±10%	**GMD155B11E562KA01#**	p259
			6800pF	±10%	**GMD155B11E682KA01#**	p259
			8200pF	±10%	**GMD155B11E822KA01#**	p259
			10000pF	±10%	**GMD155B11E103KA01#**	p259
			12000pF	±10%	**GMD155B11E123KA01#**	p259
			15000pF	±10%	**GMD155B11E153KA01#**	p259
			18000pF	±10%	**GMD155B11E183KA01#**	p259
			22000pF	±10%	**GMD155B11E223KA01#**	p259
			27000pF	±10%	**GMD155B31E273KA11#**	p259
			33000pF	±10%	**GMD155B31E333KA11#**	p259
			39000pF	±10%	**GMD155B31E393KA11#**	p259
			47000pF	±10%	**GMD155B31E473KA11#**	p259
	16Vdc	X7R	56000pF	±10%	**GMD155R71C563KA11#**	p259
			68000pF	±10%	**GMD155R71C683KA11#**	p259
			82000pF	±10%	**GMD155R71C823KA11#**	p259
			0.10μF	±10%	**GMD155R71C104KA11#**	p259
		R	56000pF	±10%	**GMD155R11C563KA11#**	p259
			68000pF	±10%	**GMD155R11C683KA11#**	p259
			82000pF	±10%	**GMD155R11C823KA11#**	p259
			0.10μF	±10%	**GMD155R11C104KA11#**	p259
		B	56000pF	±10%	**GMD155B31C563KA11#**	p259
			68000pF	±10%	**GMD155B31C683KA11#**	p259
			82000pF	±10%	**GMD155B31C823KA11#**	p259
			0.10μF	±10%	**GMD155B31C104KA11#**	p259
	10Vdc	X5R	0.12μF	±10%	**GMD155R61A124KE12#**	p261
			0.15μF	±10%	**GMD155R61A154KE12#**	p261
			0.18μF	±10%	**GMD155R61A184KE12#**	p261
			0.22μF	±10%	**GMD155R61A224KE12#**	p261
			0.27μF	±10%	**GMD155R61A274KE11#**	p263
			0.33μF	±10%	**GMD155R61A334KE11#**	p263
			0.39μF	±10%	**GMD155R61A394KE11#**	p263
			0.47μF	±10%	**GMD155R61A474KE11#**	p263
		B	0.12μF	±10%	**GMD155B31A124KE12#**	p261
			0.15μF	±10%	**GMD155B31A154KE12#**	p261
			0.18μF	±10%	**GMD155B31A184KE12#**	p261
			0.22μF	±10%	**GMD155B31A224KE12#**	p261
			0.27μF	±10%	**GMD155B31A274KE11#**	p263
			0.33μF	±10%	**GMD155B31A334KE11#**	p263
			0.39μF	±10%	**GMD155B31A394KE11#**	p263
			0.47μF	±10%	**GMD155B31A474KE11#**	p263

*: Refers to the page of the "Specifications and Test Methods".

Part number # indicates the package specification code.

1 GMD Series Specifications and Test Methods (1)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		C ≦ 0.047μF: More than 10000MΩ C > 0.047μF: More than 500Ω • F C: Nominal Capacitance	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 2min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature Measurement Frequency: 1.0±0.1kHz Measurement Voltage: 1.0±0.2Vrms
7	Dissipation Factor (D.F.)		W.V.: 25Vdc min.: 0.025max. W.V.: 16/10Vdc: 0.035max.	
8	Temperature Characteristics of Capacitance	No Bias	B1, B3: Within ±10% (-25 to +85°C) R1, R7: Within ±15% (-55 to +125°C) R6: Within ±15% (-55 to +85°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. In case of applying voltage, the capacitance change should be measured after 1 minute with applying voltage in equilibration of each temp. stage. Capacitance value as a reference is the value in step 3. • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		50% of the Rated Voltage	B1: Within +10/-30% R1: Within +15/-40%	

Step	Temperature (°C)	Applying Voltage (VDC)
1	Reference Temp. ±2	No bias
2	Min.Operating Temp. ±3	
3	Reference Temp. ±2	
4	Max.Operating Temp. ±3	
5	Reference Temp. ±2	50% of the rated voltage (For B1, R1)
6	Min.Operating Temp. ±3	
7	Reference Temp. ±2	
8	Max.Operating Temp. ±3	

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
9	Adhesive Strength of Termination	Bond Strength	Pull force: 0.03N min.	MIL-STD-883 Method 2011 Condition D Mount the capacitor on a gold metalized alumina substrate with Au-20Sn and bond a ø25μm (ø0.001 inch) gold wire to the capacitor terminal using an ultrasonic ball bond. Then, pull wire.
		Die Shear Strength	Die Shear force: 2N min.	MIL-STD-883 Method 2019 Mount the capacitor on a gold metalized alumina substrate with Au-20Sn. Apply the force parallel to the substrate.
10	Vibration *	Appearance	No defects or abnormalities.	Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Temperature Sudden Change *	Appearance	No defects or abnormalities.	Perform the five cycles according to the four heat treatments shown in the following table. Exposure Time: 24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Step	Temp. (°C)	Time (min)
1	Min. Operating Temp. +0/-3	30±3
2	Room Temp.	2 to 3
3	Max. Operating Temp. +3/-0	30±3
4	Room Temp.	2 to 3

Continued on the following page.↗

GMD Series Specifications and Test Methods (1)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	High Temperature High Humidity (Steady) *	Appearance	No defects or abnormalities.	Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h
		Capacitance Change	Within ±12.5%	
		D.F.	0.05max.	
		I.R.	More than 500MΩ or 25Ω • F (Whichever is smaller)	
13	Durability *	Appearance	No defects or abnormalities.	Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 200% of the rated voltage Charge/discharge current: 50mA max. Exposure Time: 24±2h • Initial measurement Apply 200% of the rated DC voltage at the max. operating temp. ±3°C for 1h. Remove and set for 24±2h at room temperature. Perform initial measurement.
		Capacitance Change	Within ±12.5%	
		D.F.	0.05max.	
		I.R.	More than 1000MΩ or 50Ω • F (Whichever is smaller)	

* Mounting for testing: The capacitors should be mounted on the substrate as shown below using die bonding and wire bonding when tests No.10 to 13 are performed.





2 GMD Series Specifications and Test Methods (2)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		More than 2000MΩ or 50Ω • F (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 1min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature
7	Dissipation Factor (D.F.)		0.1 max.	Capacitance / Frequency / Voltage: *1 C ≦ 10μF (10V min.): 1.0±0.1kHz, 1.0±0.2Vrms C ≦ 10μF (6.3V max.): 1.0±0.1kHz, 0.5±0.1Vrms *1 GMD155 B3/R6 1A 124 to 224 are applied to 0.5±0.1Vrms
8	Temperature Characteristics of Capacitance	No Bias	B3: Within ±10% (-25 to +85°C) R6: Within ±15% (-55 to +85°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) / Applying Voltage (VDC): 1 Reference Temp. ±2 2 Min. Operating Temp. ±3 3 Reference Temp. ±2 4 Max. Operating Temp. ±3 5 Reference Temp. ±2 No bias • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature,then measure.
9	Adhesive Strength of Termination	Bond Strength	Pull force: 0.03N min.	MIL-STD-883 Method 2011 Condition D Mount the capacitor on a gold metalized alumina substrate with Au-20Sn and bond a ø25μm (ø0.001 inch) gold wire to the capacitor terminal using an ultrasonic ball bond. Then, pull wire.
		Die Shear Strength	Die Shear force: 2N min.	MIL-STD-883 Method 2019 Mount the capacitor on a gold metalized alumina substrate with Au-20Sn. Apply the force parallel to the substrate.
10	Vibration *2	Appearance	No defects or abnormalities.	Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Temperature Sudden Change *2	Appearance	No defects or abnormalities.	Perform the five cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min): 1 Min. Operating Temp. +0/-3 30±3 2 Room Temp. 2 to 3 3 Max. Operating Temp. +3/-0 30±3 4 Room Temp. 2 to 3 Exposure Time: 24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

GMD Series Specifications and Test Methods (2)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	High Temperature High Humidity (Steady) *2	Appearance	No defects or abnormalities.	Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. ▪ Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 500MΩ or 12.5Ω ▪ F (Whichever is smaller)	
13	Durability *2	Appearance	No defects or abnormalities.	Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 150% of the rated voltage Charge/discharge current: 50mA max. ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature,then measure. ▪ Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 1000MΩ or 25Ω ▪ F (Whichever is smaller)	

*2 Mounting for testing: The capacitors should be mounted on the substrate as shown below using die bonding and wire bonding when tests No.10 to 13 are performed.





3 GMD Series Specifications and Test Methods (3)

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
1	Rated Voltage		Shown in Rated value.	The rated voltage is defined as the maximum voltage which may be applied continuously to the capacitor. When AC voltage is superimposed on DC voltage, V^{P-P} or V^{O-P}, whichever is larger, should be maintained within the rated voltage range.
2	Appearance		No defects or abnormalities.	Visual inspection.
3	Dimension		Within the specified dimensions.	Using Measuring instrument of dimension.
4	Voltage Proof		No defects or abnormalities.	Measurement Point: Between the terminations Test Voltage: 250% of the rated voltage Applied Time: 1 to 5s Charge/discharge current: 50mA max.
5	Insulation Resistance (I.R.)		More than 2000MΩ or 50Ω • F (Whichever is smaller)	Measurement Point: Between the terminations Measurement Voltage: DC Rated Voltage Charging Time: 1min Charge/discharge current: 50mA max. Measurement Temperature: Room Temperature
6	Capacitance		Shown in Rated value.	Measurement Temperature: Room Temperature
7	Dissipation Factor (D.F.)		0.1 max.	Capacitance / Frequency / Voltage: *1 C ≦ 10μF (10V min.): 1.0±0.1kHz, 1.0±0.2Vrms C ≦ 10μF (6.3V max.): 1.0±0.1kHz, 0.5±0.1Vrms *1 GMD155 B3/R6 1A 124 to 224 are applied to 0.5±0.1Vrms
8	Temperature Characteristics of Capacitance	No Bias	B3: Within ±10% (-25 to +85°C) R6: Within ±15% (-55 to +85°C)	The capacitance change should be measured after 5 minutes at each specified temp. stage. Capacitance value as a reference is the value in step 3. Step / Temperature (°C) / Applying Voltage (VDC): 1 Reference Temp. ±2 2 Min. Operating Temp. ±3 3 Reference Temp. ±2 4 Max. Operating Temp. ±3 5 Reference Temp. ±2 No bias • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
9	Adhesive Strength of Termination	Bond Strength	Pull force: 0.03N min.	MIL-STD-883 Method 2011 Condition D Mount the capacitor on a gold metalized alumina substrate with Au-20Sn and bond a ø25μm (ø0.001 inch) gold wire to the capacitor terminal using an ultrasonic ball bond. Then, pull wire.
		Die Shear Strength	Die Shear force: 2N min.	MIL-STD-883 Method 2019 Mount the capacitor on a gold metalized alumina substrate with Au-20Sn. Apply the force parallel to the substrate.
10	Vibration *2	Appearance	No defects or abnormalities.	Kind of Vibration: A simple harmonic motion 10Hz to 55Hz to 10Hz (1min) Total amplitude: 1.5mm This motion should be applied for a period of 2h in each 3 mutually perpendicular directions (total of 6h).
		Capacitance	Within the specified initial value.	
		D.F.	Within the specified initial value.	
11	Temperature Sudden Change *2	Appearance	No defects or abnormalities.	Perform the five cycles according to the four heat treatments shown in the following table. Step / Temp. (°C) / Time (min): 1 Min. Operating Temp. +0/-3 30±3 2 Room Temp. 2 to 3 3 Max. Operating Temp. +3/-0 30±3 4 Room Temp. 2 to 3 Exposure Time: 24±2h • Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±7.5%	
		D.F.	Within the specified initial value.	
		I.R.	Within the specified initial value.	
		Voltage Proof	No defects.	

Continued on the following page.↗

GMD Series Specifications and Test Methods (3)

Continued from the preceding page.↘

No	Item		Specification	Test Method (Ref. Standard: JIS C 5101, IEC60384)
12	High Temperature High Humidity (Steady) *2	Appearance	No defects or abnormalities.	Test Temperature: 40±2°C Test Humidity: 90 to 95%RH Test Time: 500±12h Applied Voltage: DC Rated Voltage Charge/discharge current: 50mA max. ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure. ▪ Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 500MΩ or 12.5Ω ▪ F (Whichever is smaller)	
13	Durability *2	Appearance	No defects or abnormalities.	Test Temperature: Max. Operating Temp. ±3°C Test Time: 1000±12h Applied Voltage: 120% of the rated voltage Charge/discharge current: 50mA max. ▪ Initial measurement Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature,then measure. ▪ Measurement after test Perform a heat treatment at 150+0/-10°C for 1h and then let sit for 24±2h at room temperature, then measure.
		Capacitance Change	Within ±12.5%	
		D.F.	0.2 max.	
		I.R.	More than 1000MΩ or 25Ω ▪ F (Whichever is smaller)	

*2 Mounting for testing: The capacitors should be mounted on the substrate as shown below using die bonding and wire bonding when tests No.10 to 13 are performed.





Recommended derating conditions on voltage and temperature



These Part Numbers are designed for use in the circuits where continuous applied voltage to the capacitor is derated than rated voltage, and guarantee Durability Test with 120% × rated voltage as testing voltage at the maximum operating temperature.
The voltage and temperature derating conditions on the upside are recommended for use to ensure the same reliability level as normal specification.

GRM, GR3, GRJ, GR4, GR7, GJM, GQM, GA2, GA3, LLL, LLA, LLM, LLR, NFM, KRM, KR3, GMA, GMD ⚠Caution/Notice

WEB

⚠Caution

Storage and Operation Conditions 266

Rating 266
1. Temperature Dependent Characteristics 266
2. Measurement of Capacitance 266
3. Applied Voltage and Applied Current 267
4. Type of Applied Voltage and Self-heating Temperature 267
5. DC Voltage and AC Voltage Characteristics 270
6. Capacitance Aging 270
7. Vibration and Shock 271

Soldering and Mounting 271
1. Mounting Position 271
2. Information before Mounting 272
3. Maintenance of the Mounting (pick and place) Machine 272
4-1. Reflow Soldering 273
4-2. Flow Soldering 275
4-3. Correction of Soldered Portion 276
5. Washing 277
6. Electrical Test on Printed Circuit Board 277
7. Printed Circuit Board Cropping 277
8. Assembly 280
9. Die Bonding/Wire Bonding 281

Other 281
1. Under Operation of Equipment 281
2. Other 282

Notice

Rating 283
1. Operating Temperature 283
2. Atmosphere Surroundings (gaseous and liquid) 283
3. Piezo-electric Phenomenon 283

Soldering and Mounting 283
1. PCB Design 283
1. Notice for Pattern Forms 283
2. Land Dimensions 284
3. Board Design 288
2. Adhesive Application 288
3. Adhesive Curing 289
4. Flux for Flow Soldering 289
5. Flow Soldering 289
6. Reflow Soldering 289
7. Washing 290
8. Coating 290

Other 290
1. Transportation 290
2. Characteristics Evaluation in the Actual System 290

⚠Caution

Storage and Operation Conditions

1. The performance of chip multilayer ceramic capacitors and chip EMIFIL NFM series (henceforth just "capacitors") may be affected by the storage conditions.
   Please use them promptly after delivery.
   1-1. Maintain appropriate storage for the capacitors using the following conditions: Room Temperature of +5 to +40°C and a Relative Humidity of 20 to 70%.
   High temperature and humidity conditions and/or prolonged storage may cause deterioration of the packaging materials. If more than six months have elapsed since delivery, check packaging, mounting, etc. before use.
   In addition, this may cause oxidation of the electrodes. If more than one year has elapsed since delivery, also check the solderability before use.
   1-2. Corrosive gas can react with the termination (external) electrodes or lead wires of capacitors, and result in poor solderability. Do not store the capacitors in an atmosphere consisting of corrosive gas (e.g., hydrogen sulfide, sulfur dioxide, chlorine, ammonia gas, etc.).
   1-3. Due to moisture condensation caused by rapid humidity changes, or the photochemical change caused by direct sunlight on the terminal electrodes and/or the resin/epoxy coatings, the solderability and electrical performance may deteriorate. Do not store capacitors under direct sunlight or in high humidity conditions.

Rating

1. Temperature Dependent Characteristics

1. The electrical characteristics of a capacitor can change with temperature.
   1-1. For capacitors having larger temperature dependency, the capacitance may change with temperature changes.
   The following actions are recommended in order to ensure suitable capacitance values.
   (1) Select a suitable capacitance for the operating temperature range.
   (2) The capacitance may change within the rated temperature.
   When you use a high dielectric constant type capacitor in a circuit that needs a tight (narrow) capacitance tolerance (e.g., a time-constant circuit), please carefully consider the temperature characteristics, and carefully confirm the various characteristics in actual use conditions and the actual system.

[Example of Temperature Characteristics X7R (R7)]
Sample: 0.1μF, Rated Voltage 50VDC



[Example of Temperature Characteristics X5R (R6)]
Sample: 22μF, Rated Voltage 4VDC



2. Measurement of Capacitance

1. Measure capacitance with the voltage and frequency specified in the product specifications.
   1-1. The output voltage of the measuring equipment may decrease occasionally when capacitance is high.
   Please confirm whether a prescribed measured voltage is impressed to the capacitor.
   1-2. The capacitance values of high dielectric constant type capacitors change depending on the AC voltage applied. Please consider the AC voltage characteristics when selecting a capacitor to be used in an AC circuit.

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

3. Applied Voltage and Applied Current

1. Do not apply a voltage to the capacitor that exceeds the rated voltage as called out in the specifications.
   1-1. Applied voltage between the terminals of a capacitor shall be less than or equal to the rated voltage.
   (1) When AC voltage is superimposed on DC voltage, the zero-to-peak voltage shall not exceed the rated DC voltage.
   When AC voltage or pulse voltage is applied, the peak-to-peak voltage shall not exceed the rated DC voltage.
   (2) Abnormal voltages (surge voltage, static electricity, pulse voltage, etc.) shall not exceed the rated DC voltage.

Typical Voltage Applied to the DC Capacitor

DC Voltage	DC Voltage+AC	AC Voltage	Pulse Voltage
			

(E: Maximum possible applied voltage.)

   1-2. Influence of over voltage
   Over voltage that is applied to the capacitor may result in an electrical short circuit caused by the breakdown of the internal dielectric layers.
   The time duration until breakdown depends on the applied voltage and the ambient temperature.
2. Use a safety standard certified capacitor in a power supply input circuit (AC filter), as it is also necessary to consider the withstand voltage and impulse withstand voltage defined for each device.

<Applicable to NFM Series>

3. The capacitors also have rated currents.
   The current flowing between the terminals of a capacitor shall be less than or equal to the rated current. Using the capacitor beyond this range could lead to excessive heat.

4. Type of Applied Voltage and Self-heating Temperature

1. Confirm the operating conditions to make sure that no large current is flowing into the capacitor due to the continuous application of an AC voltage or pulse voltage.
   When a DC rated voltage product is used in an AC voltage circuit or a pulse voltage circuit, the AC current or pulse current will flow into the capacitor; therefore check the self-heating condition.
   Please confirm the surface temperature of the capacitor so that the temperature remains within the upper limits of the operating temperature, including the rise in temperature due to self-heating. When the capacitor is used with a high-frequency voltage or pulse voltage, heat may be generated by dielectric loss.
   <Applicable to Rated Voltage of less than 100VDC>
   1-1. The load should be contained so that the self-heating of the capacitor body remains below 20°C, when measuring at an ambient temperature of 25°C.

[Example of Temperature Rise (Heat Generation) in Chip Multilayer Ceramic Capacitors in Contrast to Ripple Current]
Sample: R (R1) characteristics 10μF,
Rated voltage: DC10V



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

<Applicable to Temperature Characteristics X7R (R7), X7T (D7), X7T (W0) beyond Rated Voltage of 200VDC>

1-2. The load should be contained so that the self-heating of the capacitor body remains below 20°C, when measuring at an ambient temperature of 25°C. In addition, use a K thermocouple of ø0.1mm with less heat capacity when measuring, and measure in a condition where there is no effect from the radiant heat of other components or air flow caused by convection. Excessive generation of heat may cause deterioration of the characteristics and reliability of the capacitor. (Absolutely do not perform measurements while the cooling fan is operating, as an accurate measurement may not be performed.)

<Applicable to Temperature Characteristics U2J (7U), C0G (5C) beyond Rated Voltage of 200VDC>

1-3. Since the self-heating is low in the low loss series, the allowable power becomes extremely high compared to the common X7R (R7) characteristics.
However, when a load with self-heating of 20°C is applied at the rated voltage, the allowable power may be exceeded. When the capacitor is used in a high-frequency voltage circuit of 1kHz or more, the frequency of the applied voltage should be less than 500kHz sine wave (less than 100kHz for a product with rated voltage of DC3.15kV), to limit the voltage load so that the load remains within the derating shown in the following figure. In the case of non-sine wave, high-frequency components exceeding the fundamental frequency may be included. In such a case, please contact Murata. The excessive generation of heat may cause deterioration of the characteristics and reliability of the capacitor.
(Absolutely do not perform measurements while the cooling fan is operating, as an accurate measurement may not be performed.)

[The sine-wave frequency VS allowable voltage]

The surface temperature of the capacitor: 125°C or less
(including self-heating)



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

[The sine-wave frequency VS allowable voltage]

The surface temperature of the capacitor: 125°C or less
(including self-heating)

U2J (7U) char., Rated Voltage: DC200V



U2J (7U) char., Rated Voltage: DC250V



U2J (7U) char., Rated Voltage: DC500V



U2J (7U) char., Rated Voltage: DC630V



U2J (7U) char., Rated Voltage: DC1kV



U2J (7U) char., Rated Voltage: DC2kV



U2J (7U) char., Rated Voltage: DC3.15kV



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

5. DC Voltage and AC Voltage Characteristics

1. The capacitance value of a high dielectric constant type capacitor changes depending on the DC voltage applied. Please consider the DC voltage characteristics when a capacitor is selected for use in a DC circuit.
   1-1. The capacitance of ceramic capacitors may change sharply depending on the applied voltage (see figure). Please confirm the following in order to secure the capacitance.
   (1) Determine whether the capacitance change caused by the applied voltage is within the allowed range.
   (2) In the DC voltage characteristics, the rate of capacitance change becomes larger as voltage increases, even if the applied voltage is below the rated voltage. When a high dielectric constant type capacitor is used in a circuit that requires a tight (narrow) capacitance tolerance (e.g., a time constant circuit), please carefully consider the voltage characteristics, and confirm the various characteristics in the actual operating conditions of the system.

[Example of DC Voltage Characteristics]
Sample: X7R (R7) Characteristics 0.1μF,
Rated Voltage 50VDC



2. The capacitance values of high dielectric constant type capacitors changes depending on the AC voltage applied. Please consider the AC voltage characteristics when selecting a capacitor to be used in an AC circuit.

[Example of AC Voltage Characteristics]
Sample: X7R (R7) Characteristics 10μF,
Rated Voltage 6.3VDC



6. Capacitance Aging

1. The high dielectric constant type capacitors have an Aging characteristic in which the capacitance value decreases with the passage of time.
   When you use high dielectric constant type capacitors in a circuit that needs a tight (narrow) capacitance tolerance (e.g., a time-constant circuit), please carefully consider the characteristics of these capacitors, such as their aging, voltage, and temperature characteristics. In addition, check capacitors using your actual appliances at the intended environment and operating conditions.

[Example of Change Over Time (Aging Characteristics)]



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

7. Vibration and Shock

1. Please confirm the kind of vibration and/or shock, its condition, and any generation of resonance.
   Please mount the capacitor so as not to generate resonance, and do not allow any impact on the terminals.
2. Mechanical shock due to being dropped may cause damage or a crack in the dielectric material of the capacitor.
   Do not use a dropped capacitor because the quality and reliability may be deteriorated.



3. When printed circuit boards are piled up or handled, the corner of another printed circuit board should not be allowed to hit the capacitor, in order to avoid a crack or other damage to the capacitor.



Soldering and Mounting

1. Mounting Position

1. Confirm the best mounting position and direction that minimizes the stress imposed on the capacitor during flexing or bending the printed circuit board.
   1-1. Choose a mounting position that minimizes the stress imposed on the chip during flexing or bending of the board.

<Applicable to NFM Series>

2. If you mount the capacitor near components that generate heat, take note of the heat from the other components and carefully check the self-heating of the capacitor before using.
   If there is significant heat radiation from other components, it could lower the insulation resistance of the capacitor or produce excessive heat.

[Component Direction]



Locate chip horizontal to the direction in which stress acts.

[Chip Mounting Close to Board Separation Point]

It is effective to implement the following measures, to reduce stress in separating the board.
It is best to implement all of the following three measures; however, implement as many measures as possible to reduce stress.

Contents of Measures	Stress Level
(1) Turn the mounting direction of the component parallel to the board separation surface.	A > D *1
(2) Add slits in the board separation part.	A > B
(3) Keep the mounting position of the component away from the board separation surface.	A > C



*1 A > D is valid when stress is added vertically to the perforation as with Hand Separation.
If a Cutting Disc is used, stress will be diagonal to the PCB, therefore A > D is invalid.

[Mounting Capacitors Near Screw Holes]

When a capacitor is mounted near a screw hole, it may be affected by the board deflection that occurs during the tightening of the screw. Mount the capacitor in a position as far away from the screw holes as possible.



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

2. Information before Mounting

1. Do not re-use capacitors that were removed from the equipment.
2. Confirm capacitance characteristics under actual applied voltage.
3. Confirm the mechanical stress under actual process and equipment use.
4. Confirm the rated capacitance, rated voltage and other electrical characteristics before assembly.
5. Prior to use, confirm the solderability of capacitors that were in long-term storage.
6. Prior to measuring capacitance, carry out a heat treatment for capacitors that were in long-term storage.
7. The use of Sn-Zn based solder will deteriorate the reliability of the MLCC.
   Please contact our sales representative or product engineers on the use of Sn-Zn based solder in advance.
8. We have also produced a DVD which shows a summary of our recommendations, regarding the precautions for mounting. Please contact our sales representative to request the DVD.

3. Maintenance of the Mounting (pick and place) Machine

1. Make sure that the following excessive forces are not applied to the capacitors. Check the mounting in the actual device under actual use conditions ahead of time.
   1-1. In mounting the capacitors on the printed circuit board, any bending force against them shall be kept to a minimum to prevent them from any damage or cracking. Please take into account the following precautions and recommendations for use in your process.
   (1) Adjust the lowest position of the pickup nozzle so as not to bend the printed circuit board.



2. Dirt particles and dust accumulated in the suction nozzle and suction mechanism prevent the nozzle from moving smoothly. This creates excessive force on the capacitor during mounting, causing cracked chips. Also, the locating claw, when worn out, imposes uneven forces on the chip when positioning, causing cracked chips. The suction nozzle and the locating claw must be maintained, checked, and replaced periodically.

<Applicable to ZRB Series>

3. To adjust the inspection tolerance for automated appearance sorting machine of mounting position, because ZRB series are easier to shift the mounting position than standard MLCC.
4. To check the overturn and reverse of chip.
5. To control mounting speed carefully, because ZRB series is heavier than standard MLCC.

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

4-1. Reflow Soldering

1. When sudden heat is applied to the components, the mechanical strength of the components will decrease because a sudden temperature change causes deformation inside the components. In order to prevent mechanical damage to the components, preheating is required for both the components and the PCB. Preheating conditions are shown in table 1. It is required to keep the temperature differential between the solder and the components surface (ΔT) as small as possible.
2. When components are immersed in solvent after mounting, be sure to maintain the temperature difference (ΔT) between the component and the solvent within the range shown in table 1.

Table 1

Series	Chip Dimension Code (L/W)	Temperature Differential
GRM/GJM/GQM/GR3/ GRJ/KRM/LLR/NFM/GR7	02/03/15/18/21/31	ΔT≦190°C
LLL	02/03/15/18/1U/21/31	
ZRB	15/18	
GR3/GRJ/GRM/KR3/KRM GA2/GA3/GR4	32/42/43/52/55	ΔT≦130°C
LLA/LLM	18/21/31	
GQM	22	

Recommended Conditions

	Pb-Sn Solder	Lead Free Solder
Peak Temperature	230 to 250°C	240 to 260°C
Atmosphere	Air	Air or N_2

Pb-Sn Solder: Sn-37Pb
Lead Free Solder: Sn-3.0Ag-0.5Cu

3. When a capacitor is mounted at a temperature lower than the peak reflow temperature recommended by the solder manufacturer, the following quality problems can occur. Consider factors such as the placement of peripheral components and the reflow temperature setting to prevent the capacitor's reflow temperature from dropping below the peak temperature specified. Be sure to evaluate the mounting situation beforehand and verify that none of the following problems occur.
   - Drop in solder wettability
   - Solder voids
   - Possible occurrence of whiskering
   - Drop in bonding strength
   - Drop in self-alignment properties
   - Possible occurrence of tombstones and/or shifting on the land patterns of the circuit board

[Example of Temperature Conditions for Reflow Soldering]



Temperature
Incase of Lead Free Solder
( ): In case of Pb-Sn Solder

[Allowable Reflow Soldering Temperature and Time]



In the case of repeated soldering, the accumulated soldering time must be within the range shown above.

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

4. Optimum Solder Amount for Reflow Soldering
   4-1. Overly thick application of solder paste results in a excessive solder fillet height.
   This makes the chip more susceptible to mechanical and thermal stress on the board and may cause the chips to crack.
   4-2. Too little solder paste results in a lack of adhesive strength on the termination, which may result in chips breaking loose from the PCB.
   4-3. Please confirm that solder has been applied smoothly to the termination.

<Applicable to NFM Series>

[Guideline of solder paste thickness]
100-150μm: NFM15/18/21/3D/31
100-200μm: NFM41

NFM15CC/15PC



NFM18CC/18PC



NFM18PS



NFM21CC/21PC



NFM21PS



NFM3DCC/3DPC



NFM31PC/31KC



NFM41CC/41PC



Inverting the PCB

Make sure not to impose any abnormal mechanical shocks to the PCB.

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

4-2. Flow Soldering

1. Do not apply flow soldering to chips not listed in table 2.

Table 2

Series	Chip Dimension Code (L/W)	Temperature Differential
GR3/GRM	**18/21/31**	ΔT≦150°C
GQM	**18/21**	
LLL	**21/31**	
GRJ	**18/21/31**	
NFM	**3D/31/41**	

2. When sudden heat is applied to the components, the mechanical strength of the components will decrease because a sudden temperature change causes deformation inside the components. In order to prevent mechanical damage to the components, preheating is required for both of the components and the PCB. Preheating conditions are shown in table 2. It is required to keep the temperature differential between the solder and the components surface (ΔT) as low as possible.
3. Excessively long soldering time or high soldering temperature can result in leaching of the terminations, causing poor adhesion or a reduction in capacitance value due to loss of contact between the inner electrodes and terminations.
4. When components are immersed in solvent after mounting, be sure to maintain the temperature differential (ΔT) between the component and solvent within the range shown in the table 2.

Recommended Conditions

	Pb-Sn Solder	Lead Free Solder
Preheating Peak Temperature	90 to 110°C	100 to 120°C 140 to 160°C (**NFM**)
Soldering Peak Temperature	240 to 250°C	250 to 260°C
Atmosphere	Air	Air or N_2

Pb-Sn Solder: Sn-37Pb
Lead Free Solder: Sn-3.0Ag-0.5Cu

5. Optimum Solder Amount for Flow Soldering
   5-1. The top of the solder fillet should be lower than the thickness of the components. If the solder amount is excessive, the risk of cracking is higher during board bending or any other stressful condition.



[Example of Temperature Conditions for Flow Soldering]



[Allowable Flow Soldering Temperature and Time]



In the case of repeated soldering, the accumulated soldering time must be within the range shown above.

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

4-3. Correction of Soldered Portion

When sudden heat is applied to the capacitor, distortion caused by the large temperature difference occurs internally, and can be the cause of cracks. Capacitors also tend to be affected by mechanical and thermal stress depending on the board preheating temperature or the soldering fillet shape, and can be the cause of cracks. Please refer to "1. PCB Design" or "3. Optimum solder amount" for the solder amount and the fillet shapes.
Do not correct with a soldering iron for ZRB series.
Correction with a soldering iron for ZRB series may cause loss suppress acoustic noise, because the solder amount become excessive.

1. Correction with a Soldering Iron
   1-1. In order to reduce damage to the capacitor, be sure to preheat the capacitor and the mounting board. Preheat to the temperature range shown in Table 3. A hot plate, hot air type preheater, etc. can be used for preheating.
   1-2. After soldering, do not allow the component/PCB to cool down rapidly.
   1-3. Perform the corrections with a soldering iron as quickly as possible. If the soldering iron is applied too long, there is a possibility of causing solder leaching on the terminal electrodes, which will cause deterioration of the adhesive strength and other problems.

Table 3

Series	Chip Dimension Code (L/W)	Temperature of Soldering Iron Tip	Preheating Temperature	Temperature Differential (ΔT)	Atmosphere
GJM/GQM/GR3/GRJ/GRM/GR7	**03/15/18/21/31**	350°C max.	150°C min.	ΔT≦190°C	Air
GRJ/GRM/GR4/GA2/GA3	**32/42/43/52/55**	280°C max.	150°C min.	ΔT≦130°C	Air
GQM	**22**				
NFM	**3D/41**	350°C max.	150°C min.	ΔT≦190°C	Air
	15	340°C max.			

*Applicable for both Pb-Sn and Lead Free Solder.
Pb-Sn Solder: Sn-37Pb
Lead Free Solder: Sn-3.0Ag-0.5Cu
*Please manage ΔT in the temperature of soldering iron and the preheating temperature.

2. Correction with Spot Heater
   Compared to local heating with a soldering iron, hot air heating by a spot heater heats the overall component and board, therefore, it tends to lessen the thermal shock. In the case of a high density mounted board, a spot heater can also prevent concerns of the soldering iron making direct contact with the component.
   2-1. If the distance from the hot air outlet of the spot heater to the component is too close, cracks may occur due to thermal shock. To prevent this problem, follow the conditions shown in Table 4.
   2-2. In order to create an appropriate solder fillet shape, it is recommended that hot air be applied at the angle shown in Figure 1.

Table 4

Distance	5mm or more
Hot Air Application Angle	45° *Figure 1
Hot Air Temperature Nozzle Outlet	400°C max.
Application Time	Less than 10 seconds (1206 (3216M) size or smaller)
	Less than 30 seconds (1210 (3225M) size or larger)

[*Figure 1]



3. Optimum solder amount when re-working with a soldering iron
   3-1. If the solder amount is excessive, the risk of cracking is higher during board bending or any other stressful condition.
   Too little solder amount results in a lack of adhesive strength on the termination, which may result in chips breaking loose from the PCB.
   Please confirm that solder has been applied smoothly and rising to the end surface of the chip.



in section

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

3-2. A soldering iron with a tip of ø3mm or smaller should be used. It is also necessary to keep the soldering iron from touching the components during the re-work.

3-3. Solder wire with ø0.5mm or smaller is required for soldering.

<Applicable to KR3/KRM Series>

4. For the shape of the soldering iron tip, refer to the figure on the right.
Regarding the type of solder, use a wire diameter of ø0.5mm or less (rosin core wire solder).

4-1. How to Apply the Soldering Iron
Apply the tip of the soldering iron against the lower end of the metal terminal.
1) In order to prevent cracking caused by sudden heating of the ceramic device, do not touch the ceramic base directly.
2) In order to prevent deviations and dislocating of the chip, do not touch the junction of the chip and the metal terminal, and the metal portion on the outside directly.

4-2. Appropriate Amount of Solder
The amount of solder for corrections by soldering iron, should be lower than the height of the lower side of the chip.





5. Washing

Excessive ultrasonic oscillation during cleaning can cause the PCBs to resonate, resulting in cracked chips or broken solder joints. Before starting your production process, test your cleaning equipment/process to insure it does not degrade the capacitors.

6. Electrical Test on Printed Circuit Board

1. Confirm position of the support pin or specific jig, when inspecting the electrical performance of a capacitor after mounting on the printed circuit board.

1-1. Avoid bending the printed circuit board by the pressure of a test-probe, etc.
The thrusting force of the test probe can flex the PCB, resulting in cracked chips or open solder joints.
Provide support pins on the back side of the PCB to prevent warping or flexing. Install support pins as close to the test-probe as possible.

1-2. Avoid vibration of the board by shock when a test-probe contacts a printed circuit board.



7. Printed Circuit Board Cropping

1. After mounting a capacitor on a printed circuit board, do not apply any stress to the capacitor that causes bending or twisting the board.

1-1. In cropping the board, the stress as shown at right may cause the capacitor to crack.
Cracked capacitors may cause deterioration of the insulation resistance, and result in a short.
Avoid this type of stress to a capacitor.



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

2. Check the cropping method for the printed circuit board in advance.
   2-1. Printed circuit board cropping shall be carried out by using a jig or an apparatus (Disc separator, router type separator, etc.) to prevent the mechanical stress that can occur to the board.

Board Separation Method	Hand Separation Nipper Separation	(1) Board Separation Jig	Board Separation Apparatus	
			(2) Disc Separator	(3) Router Type Separator
Level of stress on board	High	Medium	Medium	Low
Recommended	×	△*	△*	○
Notes	Hand and nipper separation apply a high level of stress. Use another method.	· Board handling · Board bending direction · Layout of capacitors	· Board handling · Layout of slits · Design of V groove · Arrangement of blades · Controlling blade life	Board handling

* When a board separation jig or disc separator is used, if the following precautions are not observed, a large board deflection stress will occur and the capacitors may crack. Use router type separator if at all possible.

(1) Example of a suitable jig
[In the case of Single-side Mounting]
An outline of the board separation jig is shown as follows. Recommended example: Stress on the component mounting position can be minimized by holding the portion close to the jig, and bend in the direction towards the side where the capacitors are mounted. Not recommended example: The risk of cracks occurring in the capacitors increases due to large stress being applied to the component mounting position, if the portion away from the jig is held and bent in the direction opposite the side where the capacitors are mounted.

[Outline of Jig]



Hand Separation

Recommended	Not Recommended
	

[In the case of Double-sided Mounting]
Since components are mounted on both sides of the board, the risk of cracks occurring can not be avoided with the above method.
Therefore, implement the following measures to prevent stress from being applied to the components.

(Measures)
(1) Consider introducing a router type separator.
If it is difficult to introduce a router type separator, implement the following measures. (Refer to item 1. Mounting Position)
(2) Mount the components parallel to the board separation surface.
(3) When mounting components near the board separation point, add slits in the separation position near the component.
(4) Keep the mounting position of the components away from the board separation point.

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

(2) Example of a Disc Separator

An outline of a disc separator is shown as follows. As shown in the Principle of Operation, the top blade and bottom blade are aligned with the V-grooves on the printed circuit board to separate the board.

In the following case, board deflection stress will be applied and cause cracks in the capacitors.

(1) When the adjustment of the top and bottom blades are misaligned, such as deviating in the top-bottom, left-right or front-rear directions

(2) The angle of the V groove is too low, depth of the V groove is too shallow, or the V groove is misaligned top-bottom

IF V groove is too deep, it is possible to brake when you handle and carry it. Carefully design depth of the V groove with consideration about strength of material of the printed circuit board.



Disc Separator

Recommended	Not Recommended		
	Top-bottom Misalignment	Left-right Misalignment	Front-rear Misalignment
			

V-groove Design

Example of Recommended V-groove Design	Not Recommended			
	Left-right Misalignment	Low-Angle	Depth too Shallow	Depth too Deep
				

(3) Example of Router Type Separator

The router type separator performs cutting by a router rotating at a high speed. Since the board does not bend in the cutting process, stress on the board can be suppressed during board separation.

When attaching or removing boards to/from the router type separator, carefully handle the boards to prevent bending.



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

8. Assembly

1. Handling

If a board mounted with capacitors is held with one hand, the board may bend. Firmly hold the edges of the board with both hands when handling.
If a board mounted with capacitors is dropped, cracks may occur in the capacitors.
Do not use dropped boards, as there is a possibility that the quality of the capacitors may be impaired.

2. Attachment of Other Components

2-1. Mounting of Other Components

Pay attention to the following items, when mounting other components on the back side of the board after capacitors have been mounted on the opposite side.
When the bottom dead point of the suction nozzle is set too low, board deflection stress may be applied to the capacitors on the back side (bottom side), and cracks may occur in the capacitors.

· After the board is straightened, set the bottom dead point of the nozzle on the upper surface of the board.
· Periodically check and adjust the bottom dead point.



2-2. Inserting Components with Leads into Boards

When inserting components (transformers, IC, etc.) into boards, bending the board may cause cracks in the capacitors or cracks in the solder.
Pay attention to the following.

· Increase the size of the holes to insert the leads, to reduce the stress on the board during insertion.
· Fix the board with support pins or a dedicated jig before insertion.
· Support below the board so that the board does not bend. When using support pins on the board, periodically confirm that there is no difference in the height of each support pin.



2-3. Attaching/Removing Sockets and/or Connectors

Insertion and removal of sockets and connectors, etc., might cause the board to bend. Please insure that the board does not warp during insertion and removal of sockets and connectors, etc., or the bending may damage mounted components on the board.



2-4. Tightening Screws

The board may be bent, when tightening screws, etc. during the attachment of the board to a shield or chassis.
Pay attention to the following items before performing the work.

· Plan the work to prevent the board from bending.
· Use a torque screwdriver, to prevent over-tightening of the screws.
· The board may bend after mounting by reflow soldering, etc. Please note, as stress may be applied to the chips by forcibly flattening the board when tightening the screws.



Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

<Applicable to GMA or GMD Series>

9. Die Bonding/Wire Bonding

1. Die Bonding of Capacitors
   1-1. Use the following materials for the Brazing alloys:
   Au-Sn (80/20) 300 to 320 °C in N_2 atmosphere
   1-2. Mounting
   (1) Control the temperature of the substrate so it matches the temperature of the brazing alloy.
   (2) Place the brazing alloy on the substrate and place the capacitor on the alloy. Hold the capacitor and gently apply the load. Be sure to complete the operation within 1 minute.
2. Wire Bonding
   2-1. Wire
   Gold wire: 25 micro m (0.001 inch) diameter
   2-2. Bonding
   (1) Thermo compression, ultrasonic ball bonding.
   (2) Required stage temperature: 150 to 200 °C
   (3) Required wedge or capillary weight: 0.2N to 0.5N
   (4) Bond the capacitor and base substrate or other devices with gold wire.

Other

1. Under Operation of Equipment

1-1. Do not touch a capacitor directly with bare hands during operation in order to avoid the danger of an electric shock.

1-2. Do not allow the terminals of a capacitor to come in contact with any conductive objects (short-circuit). Do not expose a capacitor to a conductive liquid, including any acid or alkali solutions.

1-3. Confirm the environment in which the equipment will operate is under the specified conditions.
Do not use the equipment under the following environments.
(1) Being spattered with water or oil.
(2) Being exposed to direct sunlight.
(3) Being exposed to ozone, ultraviolet rays, or radiation.
(4) Being exposed to toxic gas (e.g., hydrogen sulfide, sulfur dioxide, chlorine, ammonia gas, etc.)
(5) Any vibrations or mechanical shocks exceeding the specified limits.
(6) Moisture condensing environments.

1-4. Use damp proof countermeasures if using under any conditions that can cause condensation.

Continued on the following page.↗

⚠Caution

Continued from the preceding page.↘

2. Other

2-1. In an Emergency

(1) If the equipment should generate smoke, fire, or smell, immediately turn off or unplug the equipment.
If the equipment is not turned off or unplugged, the hazards may be worsened by supplying continuous power.

(2) In this type of situation, do not allow face and hands to come in contact with the capacitor or burns may be caused by the capacitor's high temperature.

2-2. Disposal of Waste

When capacitors are disposed of, they must be burned or buried by an industrial waste vendor with the appropriate licenses.

2-3. Circuit Design

(1) Addition of Fail Safe Function
Capacitors that are cracked by dropping or bending of the board may cause deterioration of the insulation resistance, and result in a short.
If the circuit being used may cause an electrical shock, smoke or fire when a capacitor is shorted, be sure to install fail-safe functions, such as a fuse, to prevent secondary accidents.

(2) Capacitors used to prevent electromagnetic interference in the primary AC side circuit, or as a connection/insulation, must be a safety standard certified product, or satisfy the contents stipulated in the Electrical Appliance and Material Safety Law.
Install a fuse for each line in case of a short.

(3) The GJM, GMA, GMD, GQM, GR3, GRJ, GRM, KR3, KRM, LLA, LLL, LLM, LLR, NFM and ZRB series are not safety standard certified products.

2-4. Test Condition for AC Withstanding Voltage

(1) Test Equipment
Test equipment for AC withstanding voltage should be made with equipment capable of creating a wave similar to a 50/60Hz sine wave.

(2) Voltage Applied Method
The capacitor's lead or terminal should be firmly connected to the output of the withstanding voltage test equipment, and then the voltage should be raised from near zero to the test voltage.
If the test voltage is applied directly to the capacitor without raising it from near zero, it should be applied with the zero cross. *At the end of the test time, the test voltage should be reduced to near zero, and then capacitor's lead or terminals should be taken off the output of the withstanding voltage test equipment.
If the test voltage applied directly to the capacitor without raising it from near zero, surge voltage may occur and cause a defect.

*ZERO CROSS is the point where voltage sine wave passes 0V. - See the figure at right -



2-5. Remarks

Failure to follow the cautions may result, worst case, in a short circuit and smoking when the product is used.
The above notices are for standard applications and conditions. Contact us when the products are used in special mounting conditions.
Select optimum conditions for operation as they determine the reliability of the product after assembly.
The data herein are given in typical values, not guaranteed ratings.

Notice

Rating

1. Operating Temperature

1. The operating temperature limit depends on the capacitor.
   1-1. Do not apply temperatures exceeding the maximum operating temperature.
   It is necessary to select a capacitor with a suitable rated temperature that will cover the operating temperature range.
   It is also necessary to consider the temperature distribution in equipment and the seasonal temperature variable factor.
   1-2. Consider the self-heating factor of the capacitor.
   The surface temperature of the capacitor shall not exceed the maximum operating temperature including self-heating.

2. Atmosphere Surroundings (gaseous and liquid)

1. Restriction on the operating environment of capacitors.
   1-1. Capacitors, when used in the above, unsuitable, operating environments may deteriorate due to the corrosion of the terminations and the penetration of moisture into the capacitor.
   1-2. The same phenomenon as the above may occur when the electrodes or terminals of the capacitor are subject to moisture condensation.
   1-3. The deterioration of characteristics and insulation resistance due to the oxidization or corrosion of terminal electrodes may result in breakdown when the capacitor is exposed to corrosive or volatile gases or solvents for long periods of time.

3. Piezo-electric Phenomenon

1. When using high dielectric constant type capacitors in AC or pulse circuits, the capacitor itself vibrates at specific frequencies and noise may be generated.
   Moreover, when the mechanical vibration or shock is added to the capacitor, noise may occur.

Soldering and Mounting

1. PCB Design

1. Notice for Pattern Forms
   1-1. Unlike leaded components, chip components are susceptible to flexing stresses since they are mounted directly on the substrate.
   They are also more sensitive to mechanical and thermal stresses than leaded components.
   Excess solder fillet height can multiply these stresses and cause chip cracking. When designing substrates, take land patterns and dimensions into consideration to eliminate the possibility of excess solder fillet height.
   1-2. There is a possibility of chip cracking caused by PCB expansion/contraction with heat, because stress on a chip is different depending on PCB material and structure. When the thermal expansion coefficient greatly differs between the board used for mounting and the chip, it will cause cracking of the chip due to the thermal expansion and contraction.
   When capacitors are mounted on a fluorine resin printed circuit board or on a single-layered glass epoxy board, it may also cause cracking of the chip for the same reason.

<Applicable to NFM Series>

   1-3. Because noise is suppressed by shunting unwanted high-frequency components to the ground, when designing a land for the NFM series, design the ground pattern to be as large as possible in order to better bring out this characteristic.
   As shown in the figure below, noise countermeasures can be made more effective by using a via to connect the ground pattern on the chip mounting surface to a larger ground pattern on the inner layer.

Continued on the following page.↗

Notice

Continued from the preceding page.↘

Pattern Forms

	Prohibited	Correct
Placing Close to Chassis	 in section	 in section
Placing of Chip Components and Leaded Components	 in section	 in section
Placing of Leaded Components after Chip Component	 in section	 in section
Lateral Mounting		

2. Land Dimensions

2-1. Please refer to the land dimensions in table 1 for flow soldering, table 2 for reflow soldering, table 3 for reflow soldering for ZRB Series, table 4 for reflow soldering for LLA Series, table 5 for reflow soldering for LLM Series.
Please confirm the suitable land dimension by evaluating of the actual SET / PCB.



Table 1 Flow Soldering Method

Series	Chip Dimension Code (L/W)	Chip (L×W)	a	b	c
GQM/GR3/GRJ/GRM	**18**	1.6×0.8	0.6 to 1.0	0.8 to 0.9	0.6 to 0.8
GQM/GR3/GRJ/GRM	**21**	2.0×1.25	1.0 to 1.2	0.9 to 1.0	0.8 to 1.1
GR3/GRJ/GRM	**31**	3.2×1.6	2.2 to 2.6	1.0 to 1.1	1.0 to 1.4
LLL	**21**	1.25×2.0	0.4 to 0.7	0.5 to 0.7	1.4 to 1.8
LLL	**31**	1.6×3.2	0.6 to 1.0	0.8 to 0.9	2.6 to 2.8

Flow soldering can only be used for products with a chip size from 1.6x0.8mm to 3.2x1.6mm.

(in mm)

Continued on the following page.↗

Notice

Continued from the preceding page.↘

Table 2 Reflow Soldering Method

Series	Chip Dimension Code (L/W)	Chip (L×W)	a	b	c
GJM/GRM	02	0.4×0.2	0.16 to 0.2	0.12 to 0.18	0.2 to 0.23
GJM/GRM	03	0.6×0.3 (±0.03)	0.2 to 0.25	0.2 to 0.3	0.25 to 0.35
		0.6×0.3 (±0.05)	0.2 to 0.25	0.25 to 0.35	0.3 to 0.4
		0.6×0.3 (±0.09)	0.23 to 0.3	0.25 to 0.35	0.3 to 0.4
GJM/GRM	15	1.0×0.5 (within ±0.10)	0.3 to 0.5	0.35 to 0.45	0.4 to 0.6
		1.0×0.5 (±0.15/±0.20)	0.4 to 0.6	0.4 to 0.5	0.5 to 0.7
GQM/GR3/GRJ/GRM	18	1.6×0.8 (within ±0.10)	0.6 to 0.8	0.6 to 0.7	0.6 to 0.8
		1.6×0.8 (±0.15/±0.20)	0.7 to 0.9	0.7 to 0.8	0.8 to 1.0
GQM	21	2.0×1.25	1.0 to 1.2	0.6 to 0.7	0.8 to 1.1
GR3/GRJ/GRM/GR7	21	2.0×1.25 (within ±0.10)	1.2	0.6	1.25
		2.0×1.25 (±0.15)	1.2	0.6 to 0.8	1.2 to 1.4
		2.0×1.25 (±0.20)	1.0 to 1.4	0.6 to 0.8	1.2 to 1.4
GQM	22	2.8×2.8	2.2 to 2.5	0.8 to 1.0	1.9 to 2.3
GR3/GRJ/GRM/GR7	31	3.2×1.6 (within ±0.20)	1.8 to 2.0	0.9 to 1.2	1.5 to 1.7
		3.2×1.6 (±0.30)	1.9 to 2.1	1.0 to 1.3	1.7 to 1.9
GR3/GRJ/GRM	32	3.2×2.5	2.0 to 2.4	1.0 to 1.2	1.8 to 2.3
GA2/GA3/GR4	42	4.5×2.0	2.8 to 3.4	1.2 to 1.4	1.4 to 1.8
GR3/GRJ/GRM/GA2/GA3/GR4	43	4.5×3.2	3.0 to 3.5	1.2 to 1.4	2.3 to 3.0
GA2/GA3	52	5.7×2.8	4.0 to 4.6	1.4 to 1.6	2.1 to 2.6
GR3/GRJ/GRM/GA2/GA3/GR4	55	5.7×5.0	4.0 to 4.6	1.4 to 1.6	3.5 to 4.8
LLL	15	0.5×1.0	0.15 to 0.2	0.2 to 0.25	0.7 to 1.0
LLL	1U	0.6×1.0	0.20 to 0.25	0.25 to 0.35	0.7 to 1.0
LLL/LLR	18	0.8×1.6	0.2 to 0.3	0.3 to 0.4	1.4 to 1.6
LLL	21	1.25×2.0	0.4 to 0.5	0.4 to 0.5	1.4 to 1.8
LLL	31	1.6×3.2	0.6 to 0.8	0.6 to 0.7	2.6 to 2.8

(in mm)

<Applicable to Part Number KR3/KRM>

Series	Chip Dimension Code (L/W)	Chip (L×W)	a	b	c
KRM	21	2.0×1.25	1.0 to 1.2	0.6 to 0.7	0.8 to 1.1
KRM	31	3.2×1.6	2.2 to 2.4	0.8 to 0.9	1.0 to 1.4
KR3/KRM	55	5.7×5.0	2.6	2.7	5.6

(in mm)

Table 3 ZRB Series Reflow Soldering Method

Series	Chip Dimension Code (L/W)	Chip (L×W)	a	b	c
ZRB	15	1.0×0.5	0.4 to 0.6	0.4 to 0.5	0.5 to 0.7
ZRB	18*	1.6×0.8	0.7 to 0.9	0.7 to 0.8	0.8 to 1.0

(in mm)

*If distance between parts is too short, there is risk to cause electrical short. Please confirm the mounting pitch (distance between centers of parts) has 1.275mm or more. (ZRB18 only)

[Land for ZRB Series]



Table 4 LLA Series Reflow Soldering Method

Series	Chip Dimension Code (L/W)	Chip (L×W)	a	b	c	p
LLA	18	1.6×0.8	0.3 to 0.4	0.25 to 0.35	0.15 to 0.25	0.4
LLA	21	2.0×1.25	0.5 to 0.7	0.35 to 0.6	0.2 to 0.3	0.5

(in mm)

Continued on the following page.↗

Notice

Continued from the preceding page.↘

Table 5 LLM Series Reflow Soldering Method

Series	Chip Dimension Code (L/W)	Chip (L×W)	a	b, b'	c, c'	d	e	f	p
LLM	**21**	2.0×1.25	0.6 to 0.8	(0.3 to 0.5)	0.3	2.0 to 2.6	1.3 to 1.8	1.4 to 1.6	0.5

b=(c-e)/2, b'=(d-f)/2

(in mm)

[Land for LLA Series]



[Land for LLM Series]



<Applicable to beyond Rated Voltage of 200VDC>

2-2. Dimensions of Slit (Example)

Preparing the slit helps flux cleaning and resin coating on the back of the capacitor.
However, the length of the slit design should be as short as possible to prevent mechanical damage in the capacitor.
A longer slit design might receive more severe mechanical stress from the PCB.
Recommended slit design is shown in the Table.



L×W	d	e
1.6×0.8	–	–
2.0×1.25	–	–
3.2×1.6	1.0 to 2.0	3.2 to 3.7
3.2×2.5	1.0 to 2.0	4.1 to 4.6
4.5×2.0	1.0 to 2.8	3.6 to 4.1
4.5×3.2	1.0 to 2.8	4.8 to 5.3
5.7×2.8	1.0 to 4.0	4.4 to 4.9
5.7×5.0	1.0 to 4.0	6.6 to 7.1

(in mm)

Continued on the following page.↗

Notice

Continued from the preceding page.↘

<Applicable to NFM Series>

Land Pattern + Solder Resist | Land Pattern | Solder Resist

(in mm)

Series	Land Dimensions
NFM15CC **NFM15PC** **NFM18CC** **NFM18PC** **NFM18PS** **NFM21CC** **NFM21PC** **NFM21PS**	● Reflow Soldering

NFM15CC/NFM15PC



NFM18CC/NFM18PC



NFM18PS



NFM21CC/NFM21PC



NFM21PS



Series	Land Dimensions
NFM3DCC **NFM3DPC** **NFM31PC** **NFM31KC** **NFM41CC** **NFM41PC**	● Reflow Soldering Chip mounting side ● Flow Soldering Chip mounting side

NFM3DCC/NFM3DPC/NFM31PC/NFM41CC/NFM41PC



Part Number	Size (mm)						
	a	b	c	d	e	f	g
NFM3DCC **NFM3DPC**	1.0	1.4	2.5	4.4	1.0	2.0	2.4
NFM31PC	1.0	1.4	2.5	4.4	1.2	2.6	3.0
NFM41CC **NFM41PC**	1.5	2.0	3.5	6.0	1.2	2.6	3.0



Part Number	Size (mm)						
	a	b	c	d	e	f	g
NFM3DCC **NFM3DPC**	1.0	1.4	2.5	4.4	1.0	2.0	2.4
NFM31PC	1.0	1.4	2.5	4.4	1.2	2.6	3.0
NFM41CC **NFM41PC**	1.5	2.0	3.5	6.0	1.2	2.6	3.0

NFM31KC*1



*1 For large current design, width of signal land pattern should be wider not less than 1mm per 1A (1mm/A).
For example, in case of 10A, signal land pattern width should be 10mm or more.
(1mm/A*10A=10mm)

NFM31KC*1



*1 For large current design, width of signal land pattern should be wider not less than 1mm per 1A (1mm/A).
For example, in case of 10A, signal land pattern width should be 10mm or more.
(1mm/A*10A=10mm)

Continued on the following page.↗

Notice

Continued from the preceding page.↘

3. Board Design

When designing the board, keep in mind that the amount of strain which occurs will increase depending on the size and material of the board.

[Relationship with amount of strain to the board thickness, length, width, etc.]

$$\varepsilon = \frac{3PL}{2Ewh^2}$$ Relationship between load and strain

ε: Strain on center of board (μst)
L: Distance between supporting points (mm)
w: Board width (mm)
h: Board thickness (mm)
E: Elastic modulus of board (N/m^2=Pa)
Y: Deflection (mm)
P: Load (N)



When the load is constant, the following relationship can be established.
· As the distance between the supporting points (L) increases, the amount of strain also increases.
→Reduce the distance between the supporting points.
· As the elastic modulus (*E*) decreases, the amount of strain increases.
→Increase the elastic modulus.
· As the board width (*w*) decreases, the amount of strain increases.
→Increase the width of the board.
· As the board thickness (*h*) decreases, the amount of strain increases.
→Increase the thickness of the board.
Since the board thickness is squared, the effect on the amount of strain becomes even greater.

2. Adhesive Application

If you want to temporarily attach the capacitor to the board using an adhesive agent before soldering the capacitor, first be sure that the conditions are appropriate for affixing the capacitor. If the dimensions of the land, the type of adhesive, the amount of coating, the contact surface area, the curing temperature, or other conditions are inappropriate, the characteristics of the capacitor may deteriorate.

1. Selection of Adhesive

1-1. Depending on the type of adhesive, there may be a decrease in insulation resistance. In addition, there is a chance that the capacitor might crack from contractile stress due to the difference in the contraction rate of the capacitor and the adhesive.

1-2. If there is not enough adhesive, the contact surface area is too small, or the curing temperature or curing time are inadequate, the adhesive strength will be insufficient and the capacitor may loosen or become disconnected during transportation or soldering.
If there is too much adhesive, for example if it overflows onto the land, the result could be soldering defects, loss of electrical connection, insufficient curing, or slippage after the capacitor is mounted.
Furthermore, if the curing temperature is too high or the curing time is too long, not only will the adhesive strength be reduced, but solderability may also suffer due to the effects of oxidation on the terminations (outer electrodes) of the capacitor and the land surface on the board.

(1) Selection of Adhesive

Epoxy resins are a typical class of adhesive.
To select the proper adhesive, consider the following points.

1) There must be enough adhesive strength to prevent the component from loosening or slipping during the mounting process.
2) The adhesive strength must not decrease when exposed to moisture during soldering.
3) The adhesive must have good coatability and shape retention properties.
4) The adhesive must have a long pot life.
5) The curing time must be short.
6) The adhesive must not be corrosive to the exterior of the capacitor or the board.
7) The adhesive must have good insulation properties.
8) The adhesive must not emit toxic gases or otherwise be harmful to health.
9) The adhesive must be free of halogenated compounds.

Continued on the following page.↗

Notice

Continued from the preceding page.↘

(2) Use the following illustration as a guide to the amount of adhesive to apply.

[Sizes: 0603(1608M) / 0805(2012M) / 1206(3216M)]



<Applicable to NFM Series>

[Sizes: 1205(3212M) / 1206(3216M) / 1806(4516M)]



3. Adhesive Curing

1. Insufficient curing of the adhesive can cause chips to disconnect during flow soldering and causes deterioration in the insulation resistance between the terminations due to moisture absorption.

Control curing temperature and time in order to prevent insufficient hardening.

4. Flux for Flow Soldering

1. An excessive amount of flux generates a large quantity of flux gas, which can cause a deterioration of solderability, so apply flux thinly and evenly throughout. (A foaming system is generally used for flow soldering.)
2. Flux containing too high a percentage of halide may cause corrosion of the terminations unless there is sufficient cleaning. Use flux with a halide content of 0.1% max.
3. Strong acidic flux can corrode the capacitor and degrade its performance.
   Please check the quality of capacitor after mounting.

5. Flow Soldering

● Set temperature and time to ensure that leaching of the terminations does not exceed 25% of the chip end area as a single chip (full length of the edge A-B-C-D shown at right) and 25% of the length A-B shown as mounted on substrate.

[As a Single Chip]



[As Mounted on Substrate]



6. Reflow Soldering

The flux in the solder paste contains halogen-based substances and organic acids as activators.
Strong acidic flux can corrode the capacitor and degrade its performance.

Please check the quality after mounting, please use.

Continued on the following page.↗

Notice

Continued from the preceding page.↘

7. Washing

1. Please evaluate the capacitor using actual cleaning equipment and conditions to confirm the quality, and select the solvent for cleaning.
2. Unsuitable cleaning may leave residual flux or other foreign substances, causing deterioration of electrical characteristics and the reliability of the capacitors.

8. Coating

1. A crack may be caused in the capacitor due to the stress of the thermal contraction of the resin during curing process.
   The stress is affected by the amount of resin and curing contraction.
   Select a resin with low curing contraction.
   The difference in the thermal expansion coefficient between a coating resin or a molding resin and the capacitor may cause the destruction and deterioration of the capacitor such as a crack or peeling, and lead to the deterioration of insulation resistance or dielectric breakdown.
   Select a resin for which the thermal expansion coefficient is as close to that of the capacitor as possible.
   A silicone resin can be used as an under-coating to buffer against the stress.
2. Select a resin that is less hygroscopic.
   Using hygroscopic resins under high humidity conditions may cause the deterioration of the insulation resistance of a capacitor.
   An epoxy resin can be used as a less hygroscopic resin.
3. The halogen system substance and organic acid are included in coating material, and a chip corrodes by the kind of Coating material.
   Do not use strong acid type.

<Applicable to ZRB Series>

4. Loss suppress acoustic noise may be caused in ZRB series due to the resin during curing process. Please contact our sales representative or product engineers on the apply to resin during curing process.

Other

1. Transportation

1. The performance of a capacitor may be affected by the conditions during transportation.
   1-1. The capacitors shall be protected against excessive temperature, humidity, and mechanical force during transportation.
   (1) Climatic condition
   ▪ low air temperature: -40°C
   ▪ change of temperature air/air: -25°C/+25°C
   ▪ low air pressure: 30 kPa
   ▪ change of air pressure: 6 kPa/min.
   (2) Mechanical condition
   Transportation shall be done in such a way that the boxes are not deformed and forces are not directly passed on to the inner packaging.
   1-2. Do not apply excessive vibration, shock, or pressure to the capacitor.
   (1) When excessive mechanical shock or pressure is applied to a capacitor, chipping or cracking may occur in the ceramic body of the capacitor.
   (2) When the sharp edge of an air driver, a soldering iron, tweezers, a chassis, etc. impacts strongly on the surface of the capacitor, the capacitor may crack and short-circuit.
   1-3. Do not use a capacitor to which excessive shock was applied by dropping, etc.
   A capacitor dropped accidentally during processing may be damaged.

2. Characteristics Evaluation in the Actual System

1. Evaluate the capacitor in the actual system, to confirm that there is no problem with the performance and specification values in a finished product before using.
2. Since a voltage dependency and temperature dependency exists in the capacitance of high dielectric type ceramic capacitors, the capacitance may change depending on the operating conditions in the actual system. Therefore, be sure to evaluate the various characteristics, such as the leakage current and noise absorptivity, which will affect the capacitance value of the capacitor.
3. In addition, voltages exceeding the predetermined surge may be applied to the capacitor by the inductance in the actual system. Evaluate the surge resistance in the actual system as required.

<Applicable to NFM Series>

4. The effects of noise suppression can vary depending on the usage conditions, including differences in the circuit or IC to be used, the type of noise, the shape of the pattern to be mounted, and the mounting location. Be sure to verify the effect on the actual device in advance.

Design Support Tool "SimSurfing"

https://www.murata.com/simsurfing/

This is the latest tool to get the electrical characteristics for Capacitors, Inductors, and EMI Suppression Filters, and to simulate Thermistors' behavior !

■Characteristics viewer

You can easily search and download the following data for Multilayer Ceramic Capacitors, Polymer Capacitors, EMI Suppression Filters (Three-terminal Capacitors, Ferrite Beads) and Power/RF Inductors.

■Components performance simulator

You can search by the simulation on simple circuits for Thermistors.

■Selection tool

You can select Medium voltage Capacitors and Power Inductors according to conditions of use.
* Medium voltage: Rated Voltage 250V and over

■Search tool

You can search the Murata timing device (CERALOCK® and crystal units) that is most suitable for your IC and access information about the recommended circuit constant setting.

If you register as a "my Murata" user (https://my.murata.com/en/web/mymurata/), you can use Enhanced SimSurfing.

■ Usage example of "Multilayer Ceramic Capacitors"

1 Select the products

(1) By performance/type
(2) By part number

2 Show graph

Click each button on each tab of [Basic], [S-parameter] and [Detailed].

3 Data download

- Click each purple button in this area.
- Click "CSV output" button.



* Images are as of October 2015. Be assured that this software will be updated frequently.

https://www.murata.com/simsurfing/

Web page Introduction



1 Search by Part Number
http://psearch.en.murata.com/capacitor/partnumber/

You can search for capacitors by specifying the alphanumeric characters in the part number. The packing codes shown contain the substitute character "#". If you enter the official packing code, part numbers that contain that packing code will be matched.

2 Search by Specifications
http://psearch.en.murata.com/capacitor/spec/smd/

You can search for SMD, lead type, or screw termination type capacitors by indicating specifications such as application, capacitance, rated voltage, or temperature characteristics.

You can narrow your search by entering values of ranges, and by specifying product characteristics.

The items for narrowing searches are linked, so specifying one condition causes selectable options for the other items to allow input only of conditions that match the relevant part numbers.

3 Search in the Lineups
http://psearch.en.murata.com/capacitor/lineup/

You can search for capacitors by specifying the series lineup.

You can also confirm items such as characteristics and applications on each series page.



Capacitance chart in Series page.



[Search result]



Compares the characteristics of the checked ☑ part numbers.

Displays the number of hits for the current search conditions in real time.

Clicking on each search condition button brings up a menu, allowing you to narrow the search results to match the selected condition in real time.

Click "Current search terms" to display a menu, from which you can confirm the current conditions for narrowing the search results.

Click the ▲ mark for each item to switch between ascending and descending display.

Click a product name to display a details page listing more in-depth information (→ P39).

You can download detailed spec sheets.

Icons enable you to check the status and characteristics of products at a glance.

Global Locations

For details please visit www.murata.com

⚠Note

1 Export Control

For customers outside Japan:

No Murata products should be used or sold, through any channels, for use in the design, development, production, utilization, maintenance or operation of, or otherwise contribution to (1) any weapons (Weapons of Mass Destruction [nuclear, chemical or biological weapons or missiles] or conventional weapons) or (2) goods or systems specially designed or intended for military end-use or utilization by military end-users.

For customers in Japan:

For products which are controlled items subject to the "Foreign Exchange and Foreign Trade Law" of Japan, the export license specified by the law is required for export.

2 Please contact our sales representatives or product engineers before using the products in this catalog for the applications listed below, which require especially high reliability for the prevention of defects which might directly damage a third party's life, body or property, or when one of our products is intended for use in applications other than those specified in this catalog.

1. *Aircraft equipment*
2. *Aerospace equipment*
3. *Undersea equipment*
4. *Power plant equipment*
5. *Medical equipment*
6. *Transportation equipment (vehicles, trains, ships, etc.)*
7. *Traffic signal equipment*
8. *Disaster prevention / crime prevention equipment*
9. *Data-processing equipment*
10. *Application of similar complexity and/or reliability requirements to the applications listed above*

3 Product specifications in this catalog are as of September 2017. They are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. If there are any questions, please contact our sales representatives or product engineers.

4 Please read rating and ⚠CAUTION (for storage, operating, rating, soldering, mounting and handling) in this catalog to prevent smoking and/or burning, etc.

5 This catalog has only typical specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

6 Please note that unless otherwise specified, we shall assume no responsibility whatsoever for any conflict or dispute that may occur in connection with the effect of our and/or a third party's intellectual property rights and other related rights in consideration of your use of our products and/or information described or contained in our catalogs. In this connection, no representation shall be made to the effect that any third parties are authorized to use the rights mentioned above under licenses without our consent.

7 No ozone depleting substances (ODS) under the Montreal Protocol are used in our manufacturing process.

Murata Manufacturing Co., Ltd.

www.murata.com

muRata
INNOVATOR IN ELECTRONICS