



## Main

|                             |                                                    |
|-----------------------------|----------------------------------------------------|
| Product or component type   | Circuit breaker                                    |
| Range of product            | PowerPact P                                        |
| Current sensor rating range | 400 A                                              |
| Line Rated Current          | 400 A                                              |
| Breaking capacity           | 65 kA 240 V AC<br>50 kA 480 V AC<br>50 kA 600 V AC |
| Trip unit technology        | Electronic, power, Micrologic 5.0 P, LSI           |

## Complementary

|                                |                                                                                                    |
|--------------------------------|----------------------------------------------------------------------------------------------------|
| Product certifications         | UL Listed<br>CSA<br>IEC                                                                            |
| [Ue] rated operational voltage | 600 V AC                                                                                           |
| Module type                    | P-Frame                                                                                            |
| Mounting location              | Busbar                                                                                             |
| Mounting mode                  | Unit mount                                                                                         |
| Poles description              | 3P                                                                                                 |
| Breaking capacity code         | K                                                                                                  |
| Electrical connection          | Busbar connection line<br>Busbar connection load                                                   |
| Continuous current rating      | 80 %                                                                                               |
| Device short name              | A                                                                                                  |
| Communication interface        | Modbus                                                                                             |
| Maximum Height                 | 12.86 in (326.64 mm)                                                                               |
| Maximum Depth                  | 8.05 in (204.47 mm)                                                                                |
| Maximum Width                  | 8.27 in (210.06 mm)                                                                                |
| Tightening torque              | 442.54 lbf.in (50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 3/0...500 kcmil |

8.85...11.51 lbf.in (1.0...1.3 N.m)

Ordering and shipping details

|                     |                          |
|---------------------|--------------------------|
| Package weight(Lbs) | 32.00 lb(US) (14.515 kg) |
|---------------------|--------------------------|