



Nut Torque: 5 ~ 14Nm  
 Operating Pressure: 500gf ±200gf  
 Operating Stroke: 1.9mm ±0.5mm  
 Protection Grade: IP65  
 Function: (ON)-OFF  
 Contact: Silver Alloy  
 Base: PBT  
 Shell: Brass, Ni Plating  
 Button: SUS  
 Terminal: Brass, silver  
 Rating (Resistive load): 3A 250V AC  
 Contact Resistance: 50mΩ Max  
 Insulation Resistance: 100MΩ Min  
 Dielectric Strength: 1500V AC 1 minute  
 Electrical life: 50,000 cycles  
 Mechanical life: 200,000 cycles  
 Operating Temperature: -20°C~80°C  
 Relative Air Humidity: 45%~85%  
 Safety Approval:



公差 TOLERANCES .X±0.5 .XX±0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECON NO.	版本 VERSION	核准 APPROVED BY	比例尺 SCALE	核对 CHECKED BY	日期 DATE	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
				A0		1:1		2021.04.27	孙成	PBM-16M11-F-S-N-NN-B8S-A3	PBM-16M11-F-S-N-NN-B8S-A3_A0