


Features


- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDTA)
- Built-In Biasing Resistor, R1 only
- **Lead Free/RoHS Compliant (Note 2)**
- "Green" Device, Note 3 and 4

Mechanical Data

- Case: SC-59
- Case Material: Molded Plastic, "Green" Molding Compound, Note 4. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Copper leadframe).
- Terminal Connections: See Diagram
- Marking: Date Code and Type Code (See Diagrams & Page 2)
- Ordering Information (See Page 2)
- Weight: 0.008 grams (approximate)



SC-59		
Dim	Min	Max
A	0.35	0.50
B	1.50	1.70
C	2.70	3.00
D	0.95	
G	1.90	
H	2.90	3.10
J	0.013	0.10
K	1.00	1.30
L	0.35	0.55
M	0.10	0.20
	0°	8°
All Dimensions in mm		



SCHEMATIC DIAGRAM

P/N	R1 (NOM)	Type Code
DDTC113TKA	1K	N01
DDTC123TKA	2.2K	N03
DDTC143TKA	4.7K	N07
DDTC114TKA	10K	N12
DDTC124TKA	22K	N16
DDTC144TKA	47K	N19
DDTC115TKA	100K	N23
DDTC125TKA	200K	N25

Maximum Ratings @ T_A = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V _{CBO}	50	V
Collector-Emitter Voltage	V _{CEO}	50	V
Emitter-Base Voltage	V _{EBO}	5	V
Collector Current	I _C (Max)	100	mA
Power Dissipation	P _d	200	mW
Thermal Resistance, Junction to Ambient Air (Note 1)	R _{JA}	625	°C/W
Operating and Storage and Temperature Range	T _j , T _{STG}	-55 to +150	°C

- Note:
1. Mounted on FR4 PC Board with recommended pad layout at <http://www.diodes.com/datasheets/ap02001.pdf>
 2. No purposefully added lead.
 3. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
 4. Product manufactured with Date Code 0609 (week 9, 2006) and newer are built with Green Molding Compound. Product manufactured prior to Date Code 0609 are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.

Electrical Characteristics @ T_A = 25°C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Collector-Base Breakdown Voltage	BV _{CBO}	50			V	I _C = 50μA
Collector-Emitter Breakdown Voltage	BV _{CEO}	50			V	I _C = 1mA
Emitter-Base Breakdown Voltage	BV _{EBO}	5			V	I _E = 50μA
Collector Cutoff Current	I _{CBO}			0.5	μA	V _{CB} = 50V
Emitter Cutoff Current	I _{EBO}			0.5	μA	V _{EB} = 4V
Collector-Emitter Saturation Voltage	V _{CE(sat)}			0.3	V	I _C /I _B = 10mA/1mA DDTC113TKA I _C /I _B = 5mA/0.5mA DDTC123TKA I _C /I _B = 2.5mA/.25mA DDTC143TKA I _C /I _B = 1mA/.1mA DDTC114TKA I _C /I _B = 5mA/0.5mA DDTC124TKA I _C /I _B = 2.5mA/.25mA DDTC144TKA I _C /I _B = 1mA/0.1mA DDTC115TKA I _C /I _B = .5mA/.05mA DDTC125TKA
DC Current Transfer Ratio	h _{FE}	100	250	600		I _C = 1mA, V _{CE} = 5V
Input Resistor (R ₁) Tolerance	R ₁	-30		+30	%	
Gain-Bandwidth Product*	f _T		250		MHz	V _{CE} = 10V, I _E = -5mA, f = 100MHz


* Transistor - For Reference Only

Ordering Information (Note 4 & 5)

Device	Packaging	Shipping
DDTC113TKA-7-F	SC-59	3000/Tape & Reel
DDTC123TKA-7-F	SC-59	3000/Tape & Reel
DDTC143TKA-7-F	SC-59	3000/Tape & Reel
DDTC114TKA-7-F	SC-59	3000/Tape & Reel
DDTC124TKA-7-F	SC-59	3000/Tape & Reel
DDTC144TKA-7-F	SC-59	3000/Tape & Reel
DDTC115TKA-7-F	SC-59	3000/Tape & Reel
DDTC125TKA-7-F	SC-59	3000/Tape & Reel

- Notes: 4. Product manufactured with Date Code 0609 (week 9, 2006) and newer are built with Green Molding Compound. Product manufactured prior to Date Code 0609 are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.
5. For Packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



XXX = Product Type Marking Code, See Table on Page 1
 YM = Date Code Marking
 Y = Year ex: N = 2002
 M = Month ex: 9 = September


Date Code Key

Year	2002	2003	2004	2005	2006	2007	2008	2009
Code	N	P	R	S	T	U	V	W


Month	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

TYPICAL CURVES - DDT114TKA


NEW PRODUCT




T_A , AMBIENT TEMPERATURE ($^{\circ}C$)
Fig. 1 Derating Curve




$V_{CE(SAT)}$, MAXIMUM COLLECTOR VOLTAGE (V)
 I_C , COLLECTOR CURRENT (mA)
Fig. 2 $V_{CE(SAT)}$ vs. I_C




h_{FE} , DC CURRENT GAIN (NORMALIZED)
 I_C , COLLECTOR CURRENT (mA)
Fig. 3 DC Current Gain



C_{OB} , CAPACITANCE (pF)
 V_R , REVERSE BIAS VOLTAGE (V)
Fig. 4 Output Capacitance



I_C , COLLECTOR CURRENT (mA)
 V_{in} , INPUT VOLTAGE (V)
Fig. 5 Collector Current Vs. Input Voltage



V_{in} , INPUT VOLTAGE (V)
 I_C , COLLECTOR CURRENT (mA)
Fig. 6 Input Voltage vs. Collector Current

IMPORTANT NOTICE

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

The products located on our website at www.diodes.com are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the express written approval of Diodes Incorporated.