

Clip, 5 x 20 mm, Version 2



250 VAC

**Description**

- Through hole mounting

**References**

General Product Information

**Weblinks**

Approvals, RoHS, CHINA-RoHS, e-Store, Distributor-Stock-Check, Accessories, Product Change Notification (PCN)

**Technical Data**

|                          |                            |
|--------------------------|----------------------------|
| Fuse-Link                | 5 x 20 mm                  |
| Mounting                 | PCB                        |
| Terminal                 | Solder THT                 |
| Rated Voltage            | 250 VAC                    |
| Rated Current            | 6.3 A                      |
| Degree of Protection     | IP 00                      |
| Material: Terminals      | see variants               |
| Unit Weight (Socket/Cap) | 0.7 g                      |
| Storage Conditions       | 0°C to 60°C, max. 70% r.h. |
| Product Marking          | none                       |

|                              |  |
|------------------------------|--|
| Soldering Methods            | Wave   |
| Solderability                | 235°C / 2 sec acc. to IEC 60068-2-20,<br>Test Ta, method 1   |
| Resistance to Soldering Heat | 260°C / 10 sec acc. to IEC 60068-2-20,<br>Test Tb, method 1A |

**Abmessungen**

7.1 mm



Drilling diagram

**Variants**

| Clip | Terminal | Material: Terminals | Order Number |
|------|----------|---------------------|--------------|
| ●    | Straight | Tin-Plated Bronze   | 7141.2001    |

**Packaging Unit**

Bulk (100 pcs.)