NSS60600MZ4

60 V, 6.0 A, Low $V_{CE(sat)}$ PNP Transistor

ON Semiconductor's e^2PowerEdge family of low $V_{CE(sat)}$ transistors are surface mount devices featuring ultra low saturation voltage ($V_{CE(sat)}$) and high current gain capability. These are designed for use in low voltage, high speed switching applications where affordable efficient energy control is important.

Typical applications are DC−DC converters and power management in portable and battery powered products such as cellular and cordless phones, PDAs, computers, printers, digital cameras and MP3 players. Other applications are low voltage motor controls in mass storage products such as disc drives and tape drives. In the automotive industry they can be used in air bag deployment and in the instrument cluster. The high current gain allows e^2PowerEdge devices to be driven directly from PMU's control outputs, and the Linear Gain (Beta) makes them ideal components in analog amplifiers.

Features

- Complementary to NSS60601MZ4
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant*

MAXIMUM RATINGS (T_A = 25°C)

Rating	Symbol	Max	Unit
Collector-Emitter Voltage	V_{CEO}	−60	Vdc
Collector-Base Voltage	V_{CBO}	−100	Vdc
Emitter-Base Voltage	V_{EBO}	−6.0	Vdc
Collector Current − Continuous	I_C	−6.0	A
Collector Current − Peak	I_{CM}	−12.0	A


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


ON Semiconductor®

www.onsemi.com


−60 VOLTS, 6.0 AMPS
2.0 WATTS
PNP LOW $V_{CE(sat)}$ TRANSISTOR
EQUIVALENT $R_{DS(on)}$ 50 mΩ



SOT−223
CASE 318E
STYLE 1




MARKING DIAGRAM



A = Assembly Location
Y = Year
W = Work Week
60600 = Specific Device Code
▪ = Pb−Free Package

PIN ASSIGNMENT



Top View Pinout

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2016

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation T_A = 25°C Derate above 25°C	P_D (Note 1)	 800 6.5	 mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$ (Note 1)	 155	°C/W
Total Device Dissipation T_A = 25°C Derate above 25°C	P_D (Note 2)	 2 15.6	 W mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$ (Note 2)	 64	°C/W
Total Device Dissipation (Single Pulse < 10 sec.)	$P_{Dsingle}$ (Note 3)	 710	mW
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C

1. FR−4 @ 7.6 mm^2, 1 oz. copper traces.
2. FR−4 @ 645 mm^2, 1 oz. copper traces.
3. Thermal response.

ORDERING INFORMATION

Device	Package	Shipping†
NSS60600MZ4T1G	SOT−223 (Pb−Free)	1,000 / Tape & Reel
NSV60600MZ4T1G	SOT−223 (Pb−Free)	1,000 / Tape & Reel
NSS60600MZ4T3G	SOT−223 (Pb−Free)	4,000 / Tape & Reel
NSV60600MZ4T3G	SOT−223 (Pb−Free)	4,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Breakdown Voltage (I_C = −10 mAdc, I_B = 0)	$V_{(BR)CEO}$	−60	−	−	Vdc
Collector−Base Breakdown Voltage (I_C = −0.1 mAdc, I_E = 0)	$V_{(BR)CBO}$	−100	−	−	Vdc
Emitter−Base Breakdown Voltage (I_E = −0.1 mAdc, I_C = 0)	$V_{(BR)EBO}$	−6.0	−	−	Vdc
Collector Cutoff Current (V_{CB} = −100 Vdc, I_E = 0)	I_{CBO}	−	−	−0.1	μAdc
Emitter Cutoff Current (V_{EB} = −6.0 Vdc)	I_{EBO}	−	−	−0.1	μAdc
ON CHARACTERISTICS					
DC Current Gain (Note 4) (I_C = −500 mA, V_{CE} = −2.0 V) (I_C = −1.0 A, V_{CE} = −2.0 V) (I_C = −2.0 A, V_{CE} = −2.0 V) (I_C = −6.0 A, V_{CE} = −2.0 V)	h_{FE}	 150 120 100 70	 − − − −	 − 360 − −	−
Collector−Emitter Saturation Voltage (Note 4) (I_C = −0.1 A, I_B = −2.0 mA) (I_C = −1.0 A, I_B = −0.100 A) (I_C = −2.0 A, I_B = −0.200 A) (I_C = −3.0 A, I_B = −60 mA) (I_C = −6.0 A, I_B = −0.6 A)	$V_{CE(sat)}$	 − − − − −	 − −0.050 −0.100 − −	 −0.050 −0.070 −0.120 −0.250 −0.350	V
Base−Emitter Saturation Voltage (Note 4) (I_C = −1.0 A, I_B = −0.1 A)	$V_{BE(sat)}$	 −	 −	 −1.0	V
Base−Emitter Turn−on Voltage (Note 4) (I_C = −1.0 A, V_{CE} = −2.0 V)	$V_{BE(on)}$	 −	 −	 −0.900	V
Cutoff Frequency (I_C = −500 mA, V_{CE} = −10 V, f = 1.0 MHz)	f_T	 100	 −	 −	MHz
Input Capacitance (V_{EB} = 5.0 V, f = 1.0 MHz)	Cibo	−	360	−	pF
Output Capacitance (V_{CB} = 10 V, f = 1.0 MHz)	Cobo	−	60	−	pF
SWITCHING CHARACTERISTICS					
Delay (V_{CC} = −30 V, I_C = 750 mA, I_{B1} = 15 mA)	t_d	−	100	−	ns
Rise (V_{CC} = −30 V, I_C = 750 mA, I_{B1} = 15 mA)	t_r	−	180	−	ns
Storage (V_{CC} = −30 V, I_C = 750 mA, I_{B1} = 15 mA)	t_s	−	540	−	ns
Fall (V_{CC} = −30 V, I_C = 750 mA, I_{B1} = 15 mA)	t_f	−	145	−	ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulsed Condition: Pulse Width = 300 msec, Duty Cycle ≤ 2%.




Figure 1. Power Derating

TYPICAL CHARACTERISTICS




Figure 2. DC Current Gain




Figure 3. DC Current Gain




Figure 4. Collector−Emitter Saturation Voltage




Figure 5. Collector−Emitter Saturation Voltage




Figure 6. Collector Saturation Region




Figure 7. $V_{BE(on)}$ Voltage

TYPICAL CHARACTERISTICS




Figure 8. Base−Emitter Saturation Voltage




Figure 9. Base−Emitter Saturation Voltage




Figure 10. Input Capacitance




Figure 11. Output Capacitance




Figure 12. Current−Gain Bandwidth Product





Figure 13. Safe Operating Area

PACKAGE DIMENSIONS

SOT−223 (TO−261)
CASE 318E−04
ISSUE N




NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCH.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	1.50	1.63	1.75	0.060	0.064	0.068
A1	0.02	0.06	0.10	0.001	0.002	0.004
b	0.60	0.75	0.89	0.024	0.030	0.035
b1	2.90	3.06	3.20	0.115	0.121	0.126
c	0.24	0.29	0.35	0.009	0.012	0.014
D	6.30	6.50	6.70	0.249	0.256	0.263
E	3.30	3.50	3.70	0.130	0.138	0.145
e	2.20	2.30	2.40	0.087	0.091	0.094
e1	0.85	0.94	1.05	0.033	0.037	0.041
L	0.20	−−−	−−−	0.008	−−−	−−−
L1	1.50	1.75	2.00	0.060	0.069	0.078
H_E	6.70	7.00	7.30	0.264	0.276	0.287
θ	0°	−	10°	0°	−	10°

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

SOLDERING FOOTPRINT*



*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative