NPN SILICON PLANAR MEDIUM POWER HIGH GAIN TRANSISTOR

ZTX1051A


ISSUE 3 – FEBRUARY 95

FEATURES

* B_{CEV}=150V
* Very Low Saturation Voltage
* High Gain
* Inherently Low Noise

APPLICATIONS

* Emergency Lighting
* Low Noise Audio



E-Line
TO92 Compatible

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	150	V
Collector-Emitter Voltage	V_{CEO}	40	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	10	A
Continuous Collector Current	I_C	4	A
Base Current	I_B	500	mA
Power Dissipation at T_{amb}=25°C	P_{tot}	1	W
Operating and Storage Temperature Range	T_j:T_{stg}	-55 to +200	°C


ZTX1051A

ELECTRICAL CHARACTERISTICS (at T_{amb} = 25°C unless otherwise stated).


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	150	190		V	I_C=100μA
Collector-Emitter Breakdown Voltage	V_{CES}	150	190		V	IC=100μA
Collector-Emitter Breakdown Voltage	V_{CEO}	40	60		V	IC=10mA
Collector-Emitter Breakdown Voltage	V_{CEV}	150	190		V	IC=100μA, V_{EB}=1V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	5	8.8		V	I_E=100μA
Collector Cut-Off Current	I_{CBO}		0.3	10	nA	V_{CB}=120V
Emitter Cut-Off Current	I_{EBO}		0.3	10	nA	V_{EB}=4V
Collector Emitter Cut-Off Current	I_{CES}		0.3	10	nA	VCES=120V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		17 75 165	25 110 210	mV mV mV	I_C=0.2A, I_B=10mA* I_C=1A, I_B=10mA* I_C=4A, I_B=100mA*
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		920	1000	mV	I_C=4A, I_B=100mA*
Base-Emitter Turn-On Voltage	$V_{BE(on)}$		825	950	mV	IC=4A, V_{CE}=2V*
Static Forward Current Transfer Ratio	h_{FE}	290 300 190 45	440 450 310 70	1200		I_C=10mA, V_{CE}=2V* I_C=1A, V_{CE}=2V* I_C=4A, V_{CE}=2V* I_C=10A, V_{CE}=2V*
Transition Frequency	f_T		155		MHz	I_C=50mA, V_{CE}=10V f=100MHz
Output Capacitance	C_{obo}		27	40	pF	V_{CB}=10V, f=1MHz
Switching Times	t_{on}		100		ns	I_C=4A, I_B=40mA, V_{CC}=10V
	t_{off}		300		ns	I_C=4A, I_B=±40mA, V_{CC}=10V

*Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤ 2%


TYPICAL CHARACTERISTICS




VCE(sat) v IC




VCE(sat) v IC




hFE v IC



VBE(sat) v IC




VBE(on) v IC




Safe Operating Area

ZTX1051A



Transient Thermal Resistance



Derating curve

SPICE PARAMETERS

```
*ZETEX  ZTX1051A Spice model   Last revision 16/12/94
*
.MODEL   ZTX1051A  NPN IS=1.35E-12  NF=1.0  BF=600  IKF=5.0  VAF=120
+            ISE=0.6E-13  NE=1.25  NR=1.0  BR=150  IKR=3  VAR=15
+            ISC=1.0E-10  NC=1.7  RB=0.1  RE=0.023  RC=0.010
+            CJC=90.36E-12  CJE=547.5E-12  MJC=0.385  MJE=0.357
+            VJC=0.5 VJE=0.741  TF=600E-12  TR=8E-9
*
```

© 1995 ZETEX PLC
The copyright in this model and the design embodied belong to Zetex PLC ("Zetex"). It is supplied free of charge by Zetex for the purpose of research and design and may be used or copied intact (including this notice) for that purpose only. All other rights are reserved. The model is believed accurate but no condition or warranty as to its merchantability or fitness for purpose is given and no liability in respect of any use is accepted by Zetex PLC, its distributors or agents.

Zetex plc.
Fields New Road, Chadderton, Oldham, OL9-8NP, United Kingdom.
Telephone: (44)161-627 5105 (Sales), (44)161-627 4963 (General Enquiries)
Facsimile: (44)161-627 5467

Zetex GmbH
Streitfeldstraße 19
D-81673 München
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49

Zetex Inc.
87 Modular Avenue
Commack NY11725
Telephone: (516) 543-7100
Fax: (516) 864-7630

Zetex (Asia) Ltd.
3510 Metroplaza, Tower 2
Hing Fong Road, Kwai Fong
Telephone:(852) 26100 611
Fax: (852) 24250 494

These are supported by agents and distributors in major countries world-wide
©Zetex plc 1995

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.