

FEATURES :

- 15 Watt Package
- 4:1Wide Input Voltage
- 100% Burned In
- High Efficiency To 86%
- Customized Solutions Available
- Remote Control:On/Off
- UL94V-0 Package Material
- Operating Temperature:-40°C TO +85°C
- 3 Years Warranty

Specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified

Part Number	Input Voltage	Input Current		Output Voltage	Output Current	Efficiency	Capacitor Load
	Vdc	No-Load (mA TYP)	Full Load (mA TYP)	Vdc	Full Load (mA)	%TYP	uF MAX
67DW-24S03R3	9-36	60	663	3.3	4000	83	3300
67DW-24S05R3	9-36	60	727	5	3000	86	3300
67DW-24S12R3	9-36	40	727	12	1250	86	330
67DW-24S15R3	9-36	20	727	15	1000	86	330
67DW-24D05R3	9-36	70	754	±5	±1500	83	±2000
67DW-24D12R3	9-36	40	726	±12	±625	86	±330
67DW-24D15R3	9-36	40	726	±15	±500	86	±330
67DW-48S03R3	18-75	30	331	3.3	4000	83	5600
67DW-48S05R3	18-75	30	363	5	3000	86	5600
67DW-48S12R3	18-75	30	363	12	1250	86	680
67DW-48S15R3	18-75	30	363	15	1000	86	680
67DW-48D05R3	18-75	30	377	±5	±1500	83	±3300
67DW-48D12R3	18-75	30	363	±12	±625	86	±220
67DW-48D15R3	18-75	30	363	±15	±500	86	±220

Input Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Types				4:1	
Filter	Pi TYPE				

Output Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	Full load@Vin(nom.)			±2	%
Short Circuit Protection	Hiccup, automatic recovery				
Line Regulation				±0.5	%
Load Regulation	Single Dual(Balance Load)			±0.5 ±1.0	%
Cross Regulation	Dual (25% to 100% Load)			±5	%
Ripple & Noise	Output:3-15V TYPES BW=DC To 20MHz			100	mVp-p
	Output > 15V TYPES BW=DC To 20MHz		1% of Vout		mVp-p
Transient response setting time	25% load step change		300		us

YUAN DEAN SCIENTIFIC



DC-DC Converter


67DW-R3 SERIES

15Watt 1.5KV Isolated


4 : 1 Input Voltage Range

Single & Dual Output

2" x 1"



Temperature Derating Graph



www.yds.com.tw




TEL : 886-6-3842899 FAX : 886-6-3843288
E-MAIL : ydsweb@yds.com.tw

Rev:o 2018/10/31

General Specifications

Parameters	Conditions	Min	Typ	Max	Units
Isolation Voltage			1500		Vdc
Isolation Resistance	500Vdc	1000			MΩ
Switching Frequency			300		KHz
Operating Temperature	With derating	-40		85	°C
Storage Temperature		-55		125	°C
Humidity	Non Condensing	5		95	%
Cooling	Natural Convection (20LFM)				
Case material	Nickel coated copper with no-conductive base				
MTBF	MIL-HDBK-217F @25°C	2.43x10 ⁶			Hours
Weight			32.6		g
Dimensions			50.8x25.4x10.6		mm

Dimensions



UNIT : mm

Tolerances : XX.X ±0.5, XX.XX±0.25

Part Number

67DW - $\frac{24}{A}$ $\frac{S}{B}$ $\frac{03}{C}$ $\frac{R}{D}$ $\frac{3}{E}$ $\frac{3}{F}$

A: Series

B: Input Voltage


C: Single Output(S), Dual (D)

D: Output Voltage


E: Regulated(R)

F: Package

Recommended Test Circuit



24V & 48V : Cin 10uF, 100V



24V & 40V : Cin 10uF, 100V

PIN Assignment

Pin	1	2	3	4	5	6
Single	+Vin	-Vin	+Vout	Trim	-Vout	Remote On/Off
Dual	+Vin	-Vin	+Vout	Com	-Vout	Remote On/Off