
This document was generated on 04/16/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0510151400

Status: Active

Description: 2.00mm (.079") Pitch Board-In Crimp Housing, Low Profile, 14 Circuits



Series image - Reference only

Documents:

3D Model
Drawing (PDF)
Product Specification PS-51015-001 (PDF)
Product Specification PS-51015-002 (PDF)
RoHS Certificate of Compliance (PDF)

Agency Certification

UL	E29179

General

Product Family	Crimp Housings
Series	51015
Product Name	Board-In

Physical

Circuits (maximum)	14
Color - Resin	Natural
Flammability	94V-0
Gender	Male
Glow-Wire Compliant	No
Material - Resin	Nylon
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.079 In
Pitch - Mating Interface (mm)	2.00 mm
Stackable	No
Temperature Range - Operating	-40°C to +105°C

Material Info

Reference - Drawing Numbers

Product Specification	PS-51015-001, PS-51015-002, RPS-51015-001, RPS-51015-003, RPS-51015-004, RPS-51015-006
Sales Drawing	SD-51015-**00

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free Status
Not Halogen-Free

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.


Search Parts in this Series
51015Series


Use With
50034


This document was generated on 04/16/2010


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

DWG. NO. SD-51015-**00









基板取付穴推奨寸法

(基板厚：t＝1～1。6mm)
RECOMMENDED PC BOARD
HOLE DIMENSION
(THICKNESS:t=1～1.6mm)

注記
NOTE

⚠1 適合ターミナル：50034－8＊00
APPLICABLE TERMINAL:50034-8*00

28	30.4	51015-1500	15
26	28.4	-1400	14
24	26.4	-1300	13
22	24.4	-1200	12
20	22.4	-1100	11
18	20.4	-1000	10
16	18.4	-0900	9
14	16.4	-0800	8
12	14.4	-0700	7
10	12.4	-0600	6
8	10.4	-0500	5
6	8.4	-0400	4
4	6.4	-0300	3
2	4.4	51015-0200	2
B	A	ENG.NO.	極数 NO. OF CKT

角度 ANGLE	±3°					
30 以上 OVER	±0.3					
10 以上 OVER 30 未満 UNDER	±0.25					
10 未満 UNDER	±0.2	B	再作図 REDRAWN (JC70310)	h.i	M.F	'96/05/20
一般公差 GENERAL TOLERANCES		記号 LTR	変更内容 REVISION RECORD	DR.	CHK.	日付 DATE

材料 MATERIAL
ナイロン66、UL94V-0
NYLON66,UL94V-0

仕上げ FINISH

適用電線範囲 WIRE RANGE

被覆外径 INS. RANGE

DRAWN BY '96/05/28 H.IIJIMA
CHK'D BY '96/05/28 M.FUKUSHIMA
APP'D BY '96/05/28 M.ENOMOTO
尺度 SCALE 8 : 1

MOLEX-JAPAN CO.,LTD.
日本モレックス株式会社

REVISE ONLY ON CAD SYSTEM

TITLE 名称
2.0 BOARD IN CONN. HSG.

DWG. NO. SD-51015-**00
REV B

:MM DIMENSIONS IN METRIC DO NOT SCALE DRAWING

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX(JAPAN) AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
本図面は日本モレックス（株）の所有する情報を含むもので当社の許可なく複製を禁止する。