SPECIFICATIONS

RF-7850A-PS001 Power Supply





The RF-7850A-PS001 is a very low-profile, ruggedized solution supporting deployment of the RF-7850A-UA Unmanned Aircraft Networking Radio in platforms using MIL-STD-704 compliant VDC power. This high-efficiency DC/DC-mounted power supply converts 28 VDC to 12 VDC for the UA. It includes EMI filters, input/output isolation capabilities, zero voltage switching technology and over-voltage and over-temperature shutdowns with auto recovery.

GENERAL	
Part Number	RF-7850A-PS001
Supports Product	RF-7850A-UA001
TRANSMITTER	
Power Output	12 VDC/5A
POWER	
Power Input	18-48 VDC
EMI / EMC	
MIL-STD-461E	CE101, CE102, CS101, CS114, CS115, CS116, RE102, RS103
PHYSICAL	
Dimensions	0.42 H x 5.3 W x 3.0 D in (1.6 H x 13.46 W x 7.62 D cm)
Weight	0.40 lbs (~ 180 gm)
Heat Dissipation Area	15.16 in ²

ENVIRONMENTAL	
Temperature	Operating: -67° F to +185° F (-55° C to +85° C) Storage: -67° F to +257° F (-55° C to +125° C)
Altitude Shock & Vibration Sand/Dust/Salt Fog/Rain Humidity	MIL-STD 810G
OPTIONAL ACCESSORIES	
12178-5610-01	Integration Kit
12178-5620-01	Bench-top Cable Kit
TECHNICAL PUBLICATIONS	
10515-0532-4100	Quick Reference Guide

About Harris Corporation

Harris Corporation is a leading technology innovator, solving customers' toughest mission-critical challenges by providing solutions that connect, inform and protect. Harris supports government and commercial customers around the world.

Learn more at harris.com

FLORIDA NEW YORK VIRGINIA BRAZIL UNITED KINGDOM UAE SINGAPORE

