

TX25SA Series

TCXO, 2.5 x 2.0mm, Clipped sine wave




From ±0.5ppm stability over -30°C to 85°C



Parameters		Specification		Remarks
Frequency range		F_nom	8.0MHz ~ 50.0MHz	Limited frequencies available
Supply voltage		Vcc	1.8V, 2.4V, 2.8V, 3.0V	±5% tolerance
Initial frequency tolerance		F_tol	±1.0ppm max	At +25°C
Frequency stability	vs Temperature	F_stb	±0.5ppm max	Table 1
	vs Load	F_load	±0.2ppm max.	±10% load condition change
	vs Voltage	F_Vcc	±0.2ppm max.	±5% input voltage change
	vs Aging	F_age	±1.0ppm max	1 year
	vs Reflow		±1.0ppm max.	2 times
Frequency stability slope (-20°C ~ +70°C)			±0.1ppm/°C max	Every +2°C
Frequency stability slope (-30°C ~ -20°C)			±0.2ppm/°C max	Every +2°C
Frequency stability slope (+70°C ~ +85°C)			±0.2ppm/°C max	Every +2°C
Operating temperature range (°C)		Topr	-30°C ~ +85°C	Table 1
Storage temperature (°C)		Tstg	-40°C ~ +85°C	
Output wave form			Clipped sine wave	DC coupled
Output voltage level			0.8V p-p (min.)	
Output Load			10KΩ//10pF	±10% tolerance
Current consumption		Icc	1.5mA max.	10KΩ//10pF±10%
Start-up time		T_str	2.0ms max.	Reach 90% amplitude at +25°C
Moisture sensitive level		MSL	1	
ESD sensitive device			Yes	

Please leave product at room temperature for 2 hrs or more after reflow.

Temp. (°C)	Stability in ppm					
	±0.5	±1.0	±1.5	±2.0	±2.5	±3.0
0°C to 50°C	✓	✓	✓	✓	✓	✓
-10°C to 60°C	✓	✓	✓	✓	✓	✓
-20°C to 70°C	✓	✓	✓	✓	✓	✓
-30°C to 75°C	✓	✓	✓	✓	✓	✓
-30°C to 85°C	✓	✓	✓	✓	✓	✓



- Pad 1 : Ground
- Pad 2 : NC
- Pad 3 : Ground
- Pad 4 : Output
- Pad 5 : NC
- Pad 6 : Supply voltage

TX25SA Series

TCXO, 2.5 x 2.0mm, Clipped sine wave




TCXO/VC-TCXO part number generation


TX25SA	2600	M	E	X	B	X	Z	L	-PF
ACT series Code	Frequency (MHz) Ex. 26.00MHz = 2600 8.00MHz = 0800 14.7456MHz = 1474	Temp. stability (\pm ppm)	Supply voltage (V)	Operating temp. range ($^{\circ}$ C)	Output wave	Electrical tuning (\pm ppm)	Duty Cycle	Tape & Reel	RoHS Code
TCXO = TX25SA	< 100MHz First 4 digit of frequency > 100MHz First 5 digit of frequency	0.5 = R 1.0 = P 1.5 = O 2.0 = N 2.5 = M 3.0 = L	1.8V = D 2.4V = J 2.8V = H 3.0V = E	0 ~ 50 = D -10 ~ +60 = F -20 ~ +70 = B -30 ~ +75 = W -30 ~ +85 = X	CSW = B	None = X	Not specified = Z	Loose = L 1000 = C 3000 = D	-PF

Note: It is important to suffix the above part number with full frequency required to give a completed part number as illustrated below.
Full Example part number : **TX25SA2600MEXBXZL-PF [26MHz]**, **TX25SA1474MEXBXZL-PF [14.7456MHz]**


Test circuit




Clipped sine waveform



Solder reflow profile



TCXO construction



Drawing control: (Internal use only)
Commodity code: 854370 90 99
Issue number : 1
Date : 24062016
Internal reference : C1f

Advanced Crystal Technology (A wholly owned Acal BFi Company)
Tel: +44 (0) 118 978 8878 Email info@actcrystals.com / www.actcrystals.com

ISO9001 Registered

Specifications subject to change without notification