



P.C.B LAYOUT
TOLERANCE:±0.05



Ordering Information:

A2005WV-N-2xXP-A - **
1 2

1.Part NO.

2.Material:

(blank): Nylon 6T,UL94V-0

9T: Nylon 9T,UL94V-0

SPECIFICATIONS:

Current Rating: 2A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 1000MΩ Min.

Withstanding Voltage: 500V AC/minute

Pin Material: Brass/Gold over Nickel

Material: Nylon 6T,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x2P	2.00	6.65	5.00	2x14P	26.00	30.65	29.00
2x3P	4.00	8.65	7.00	2x15P	28.00	32.65	31.00
2x4P	6.00	10.65	9.00	2x16P	30.00	34.65	33.00
2x5P	8.00	12.65	11.00	2x17P	32.00	36.65	35.00
2x6P	10.00	14.65	13.00	2x18P	34.00	38.65	37.00
2x7P	12.00	16.65	15.00	2x19P	36.00	40.65	39.00
2x8P	14.00	18.65	17.00	2x20P	38.00	42.65	41.00
2x9P	16.00	20.65	19.00	2x21P	40.00	44.65	43.00
2x10P	18.00	22.65	21.00	2x22P	42.00	46.65	45.00
2x11P	20.00	24.65	23.00	2x23P	44.00	48.65	47.00
2x12P	22.00	26.65	25.00	2x24P	46.00	50.65	49.00
2x13P	24.00	28.65	27.00	2x25P	48.00	52.65	51.00

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit mm Scale 2.5:1 Sheet 1 of 1

DRWN DENGCHUN YI CHK'D DANKUI WAN APPR JACK YIN

General Tolerances
A1 ADD THE SIZE 2020.08.31
A0 NEW RELEASE 2011.12.15
REV DESCRIPTION DATE
x.xx±0.25
x.xxx±0.20
x.xxxx±0.15
ANGLES ±1°

TITLE
2.00mm PITCH
180° DUAL ROW BOX HEADER
- A TYPE

DRAWING NO. A2005WV-N-2xXP-A
REV A1