
ZDX080N50

Nch 500V 8A Power MOSFET Datasheet

V_{DSS}	500V
$R_{DS(on)}$ (Max.)	0.85Ω
I_D	8A
P_D	40W

●Outline

TO-220FM



●Features

1) Low on-resistance.

2) Fast switching speed.


3) Gate-source voltage (V_{GSS}) guaranteed to be ±30V.

4) Drive circuits can be simple.

5) Parallel use is easy.

6) Pb-free lead plating ; RoHS compliant

●Inner circuit



(1) Gate
(2) Drain
(3) Source

∗1 BODY DIODE

●Application

Switching Power Supply

●Packaging specifications

Type	Packaging	Bulk
	Reel size (mm)	-
	Tape width (mm)	-
	Basic ordering unit (pcs)	500
	Taping code	-
	Marking	ZDX080N50

●Absolute maximum ratings(T_a = 25°C)

Parameter		Symbol	Value	Unit
Drain - Source voltage		V_{DSS}	500	V
Continuous drain current	T_c = 25°C	I_D *1	±8	A
Pulsed drain current		$I_{D,pulse}$ *2	±24	A
Gate - Source voltage		V_{GSS}	±30	V
Power dissipation (T_c = 25°C)		P_D	40	W
Junction temperature		T_j	150	°C
Range of storage temperature		T_{stg}	−55 to +150	°C

Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●Thermal resistance

Parameter	Symbol	Values			Unit
		Min.	Typ.	Max.	
Thermal resistance, junction - ambient	R_{thJA}	-	-	3.125	°C/W

●Electrical characteristics(T_a = 25°C)

Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Drain - Source breakdown voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = 1mA	500	-	-	V
Zero gate voltage drain current	I_{DSS}	V_{DS} = 500V, V_{GS} = 0V	-		100	μA
Gate - Source leakage current	I_{GSS}	V_{GS} = ±30V, V_{DS} = 0V	-	-	±100	nA
Gate threshold voltage	$V_{GS\ (th)}$	V_{DS} = 10V, I_D = 1mA	2.0	-	4.0	V
Static drain - source on - state resistance	$R_{DS(on)}$ *3	V_{GS} = 10V, I_D = 4A	-	0.65	0.85	Ω

Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●**Electrical characteristics**(T_a = 25°C)

Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Transconductance	g_{fs} *3	V_{DS} = 10V, I_D = 4A	2	6	-	S
Input capacitance	C_{iss}	V_{GS} = 0V	-	1120	-	pF
Output capacitance	C_{oss}	V_{DS} = 25V	-	98	-	
Reverse transfer capacitance	C_{rss}	f = 1MHz	-	7.5	-	
Turn - on delay time	$t_{d(on)}$ *3	V_{DD} ≃ 264V, V_{GS} = 10V	-	38	-	ns
Rise time	t_r *3	I_D = 8A	-	30	-	
Turn - off delay time	$t_{d(off)}$ *3	R_L = 33Ω	-	40	-	
Fall time	t_f *3	R_G = 10Ω	-	20	-	

●**Gate Charge characteristics**(T_a = 25°C)

Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Total gate charge	Q_g *3	V_{DD} ≃ 250V	-	23	-	nC
Gate - Source charge	Q_{gs} *3	I_D = 8A	-	7	-	
Gate - Drain charge	Q_{gd} *3	V_{GS} = 10V	-	9	-	
Gate plateau voltage	$V_{(plateau)}$	V_{DD} ≃ 250V, I_D = 8A	-	6	-	V

*1 Limited only by maximum temperature allowed.

*2 Pw ≤ 10μs, Duty cycle ≤ 1%

*3 Pulsed

Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●**Body diode electrical characteristics** (Source-Drain)(T_a = 25°C)

Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Inverse diode continuous, forward current	I_S *1	T_c = 25°C	-	-	8	A
Inverse diode direct current, pulsed	I_{SM} *2		-	-	24	A
Forward voltage	V_{SD} *3	V_{GS} = 0V, I_S = 4A	-	-	1.2	V

Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●Electrical characteristic curves

Fig.1 Power Dissipation Derating Curve




Fig.2 Maximum Safe Operating Area





Fig.3 Normalized Transient Thermal Resistance vs. Pulse Width



Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●Electrical characteristic curves

Fig.4 Typical Output Characteristics(I)




Fig.5 Typical Output Characteristics(II)




Fig.6 Breakdown Voltage vs. Channel Temperature





Fig.7 Typical Transfer Characteristics



Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●Electrical characteristic curves

Fig.8 Gate Threshold Voltage vs. Channel Temperature




Fig.9 Transconductance vs. Drain Current





Fig.10 Static Drain - Source On - State Resistance vs. Gate Source Voltage



Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●Electrical characteristic curves

Fig.11 Static Drain - Source On - State Resistance vs. Drain Current(II)





Fig.12 Static Drain - Source On - State Resistance vs. Junction Temperature



Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●Electrical characteristic curves

Fig.13 Typical Capacitance vs. Drain - Source Voltage




Fig.14 Switching Characteristics




Fig.15 Dynamic Input Characteristics





Fig.16 Inverse Diode Forward Current vs. Source - Drain Voltage



Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●Measurement circuits

Fig.1-1 Switching Time Measurement Circuit




Fig.1-2 Switching Waveforms




Fig.2-1 Gate Charge Measurement Circuit





Fig.2-2 Gate Charge Waveform




Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

●**Dimensions** (Unit : mm)

TO-220FM



DIM	MILIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	16.60	17.60	0.654	0.693
A1	1.80	2.20	0.071	0.087
A2	14.80	15.40	0.583	0.606
A4	6.80	7.20	0.268	0.283
b	0.70	0.85	0.028	0.033
b1	1.10	1.50	0.043	0.059
c	0.70	0.85	0.028	0.033
D	9.90	10.30	0.39	0.406
E	4.40	4.80	0.173	0.189
e	2.54		0.10	
E1	2.70	3.00	0.106	0.118
F	2.80	3.20	0.11	0.126
L	11.50	12.50	0.453	0.492
p	3.00	3.40	0.118	0.134
Q	2.10	3.10	0.083	0.122
x	−	0.381	−	0.015

Dimension in mm/inches

Not Recommended for New Designs

© 2012 ROHM Co., Ltd. All rights reserved.

Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.

Not Recommended for New Designs

ROHM SEMICONDUCTOR

Thank you for your accessing to ROHM product informations.
More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/

© 2012 ROHM Co., Ltd. All rights reserved.