1.75x3.9mm RECTANGULAR LED LAMP

WP1773HD BRIGHT RED


Features

- ●LOW POWER CONSUMPTION.
- ●I.C. COMPATIBLE.
- ●ROUNDED END RECTANGULAR SHAPE.
- ●LONG LIFE-SOLID STATE RELIABILITY.
- ●RoHS COMPLIANT

Description

The Bright Red source color devices are made with Gallium Phosphide Red Light Emitting Diode.

Package Dimensions



Notes:
1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25(0.01") unless otherwise noted.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

Kingbright

Selection Guide

Part No.	Dice	Lens Type	Iv (mcd) @ 10mA		Viewing Angle
			Min.	Typ.	2 θ 1/2
WP1773HD	BRIGHT RED (GaP)	RED DIFFUSED	0.7	2	100°

Note:
1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.


Electrical / Optical Characteristics at T_A=25°C

Symbol	Parameter	Device	Typ.	Max.	Units	Test Conditions
λpeak	Peak Wavelength	Bright Red	700		nm	I_F=20mA
λD	Dominant Wavelength	Bright Red	660		nm	I_F=20mA
Δλ1/2	Spectral Line Half-width	Bright Red	45		nm	I_F=20mA
C	Capacitance	Bright Red	40		pF	V_F=0V;f=1MHz
V_F	Forward Voltage	Bright Red	2.25	2.5	V	I_F=20mA
I_R	Reverse Current	Bright Red		10	uA	V_R = 5V

Absolute Maximum Ratings at T_A=25°C


Parameter	Bright Red	Units
Power dissipation	120	mW
DC Forward Current	25	mA
Peak Forward Current [1]	130	mA
Reverse Voltage	5	V
Operating / Storage Temperature	-40°C To +85°C	
Lead Solder Temperature [2]	260°C For 3 Seconds	
Lead Solder Temperature [3]	260°C For 5 Seconds	

Notes:
1. 1/10 Duty Cycle, 0.1ms Pulse Width.
2. 2mm below package base.
3. 5mm below package base.




RELATIVE INTENSITY Vs. WAVELENGTH


Bright Red **WP1773HD**




FORWARD CURRENT Vs. FORWARD VOLTAGE




LUMINOUS INTENSITY Vs. FORWARD CURRENT



FORWARD CURRENT DERATING CURVE



LUMINOUS INTENSITY Vs. AMBIENT TEMPERATURE



SPATIAL DISTRIBUTION

Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity, or wavelength), the typical accuracy of the sorting process is as follows:

1. Wavelength: +/-1nm
2. Luminous Intensity: +/-15%
3. Forward Voltage: +/-0.1V

Note: Accuracy may depend on the sorting parameters.