

NOTES:

MATERIAL

1. Insulator Material: PBT+30%GF(UL94V-0)
2. Contact Material : Brass
3. Contact Plating :
 - AWP xx-7240-T : Gold flash over Ni
 - AWP xx-7540-T : Tin over Ni


ELECTRICAL

1. Current Rating : 3AMP
2. Withstand Voltage : 1000V AC/DC
3. Contact Resistance : 20mΩ max
4. Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

1. Operation Temperature: -40°C to +105°C
2. Packing: Tray

- (4) 6P-8P Without Slot "M" and "N"
- 10P-12P With Slot "M" , Without Slot "N"
- 14P-64P With Slot "M" and "N"
- (6) Wire Spec: AWG28



Section A-A

RoHS compliant



File No.: E198287 (5)

Scale	Free	(6)	Add wire spec	14.02.2014	Amy	Date	Name	Customer-No.
TOLERANCE		(5)	Add the UL-File No	13.12.2013	Winnie	Drawn	25.01.2006	Alex
X.X	±0.40	(4)	Update	27.03.2013	Winnie	Approved	14.02.2014	Amy
X.XX	±0.25	(3)	New p/n added	21.12.2009	Dean			
X.XXX	±0.15	(2)	Redraw	13.03.2009	Dean			
Angle	±3°	(1)	Drawn	25.01.2006	Alex			
		Id.	Modification	Date	Name			



ASSMANN WSW-No.
AWP xx-7x40-T

Drawing-No.
ASS 1194C CO rev06

Replace Sheet