

3A, 50V - 1000V Surface Mount Fast Recovery Rectifier

FEATURES

- Glass passivated chip junction
- Ideal for automated placement
- Fast switching for high efficiency
- Moisture sensitivity level: level 1, per J-STD-020
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- Lighting application
- Converter

MECHANICAL DATA

- Case: DO-214AB (SMC)
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1A whisker test
- Polarity: As marked
- Weight: 0.21 g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	3	A
V_{RRM}	50 - 1000	V
I_{FSM}	100	A
T_{JMAX}	150	°C
Package	DO-214AB (SMC)	



DO-214AB (SMC)

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)									
PARAMETER	SYMBOL	RS 3A-K	RS 3B-K	RS 3D-K	RS 3G-K	RS 3J-K	RS 3K-K	RS 3M-K	UNIT
Marking code on the device		RS3A	RS3B	RS3D	RS3G	RS3J	RS3K	RS3M	
Repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Reverse voltage, total rms value	$V_{R(RMS)}$	35	70	140	280	420	560	700	V
Forward current	I_F	3							A
Surge peak forward current, 8.3 ms single half sine-wave superimposed on rated load per diode	I_{FSM}	100							A
Junction temperature	T_J	- 55 to +150							°C
Storage temperature	T_{STG}	- 55 to +150							°C

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	TYP.	UNIT
Junction-to-lead thermal resistance per diode	$R_{\theta JL}$	10	$^{\circ}C/W$
Junction-to-ambient thermal resistance per diode	$R_{\theta JA}$	56	$^{\circ}C/W$
Junction-to-case thermal resistance per diode	$R_{\theta JC}$	11	$^{\circ}C/W$

Thermal Performance Note: Units mounted on PCB (16mm x 16mm Cu pad test board)

ELECTRICAL SPECIFICATIONS ($T_A = 25^{\circ}C$ unless otherwise noted)						
PARAMETER	CONDITIONS	SYMBOL	TYP.	MAX.	UNIT	
Forward voltage per diode ⁽¹⁾	$I_F = 1.5A, T_J = 25^{\circ}C$	V_F	0.99	-	V	
	$I_F = 3.0A, T_J = 25^{\circ}C$		1.10	1.30	V	
	$I_F = 1.5A, T_J = 125^{\circ}C$		0.81	-	V	
	$I_F = 3.0A, T_J = 125^{\circ}C$		0.91	1.05	V	
Reverse current @ rated V_R per diode ⁽²⁾	$T_J = 25^{\circ}C$	I_R	-	10	μA	
	$T_J = 125^{\circ}C$		-	250	μA	
Junction capacitance	1 MHz, $V_R = 4.0V$	C_J	24	-	pF	
Reverse recovery time	RS3A-K RS3B-K RS3D-K RS3G-K	$I_F = 0.5A, I_R = 1.0A$ $I_{RR} = 0.25A$	t_{rr}	-	150	ns
	RS3J-K			-	250	ns
	RS3K-K RS3M-K			-	500	ns

Notes:

1. Pulse test with $PW = 0.3$ ms
2. Pulse test with $PW = 30$ ms

ORDERING INFORMATION		
ORDERING CODE	PACKAGE	PACKING
RS3A-K R7G	SMC	850 / 7" Plastic reel
RS3A-K M6G	SMC	3,000 / 13" Plastic reel
RS3B-K R7G	SMC	850 / 7" Plastic reel
RS3B-K M6G	SMC	3,000 / 13" Plastic reel
RS3D-K R7G	SMC	850 / 7" Plastic reel
RS3D-K M6G	SMC	3,000 / 13" Plastic reel
RS3G-K R7G	SMC	850 / 7" Plastic reel
RS3G-K M6G	SMC	3,000 / 13" Plastic reel
RS3J-K R7G	SMC	850 / 7" Plastic reel
RS3J-K M6G	SMC	3,000 / 13" Plastic reel
RS3K-K R7G	SMC	850 / 7" Plastic reel
RS3K-K M6G	SMC	3,000 / 13" Plastic reel
RS3M-K R7G	SMC	850 / 7" Plastic reel
RS3M-K M6G	SMC	3,000 / 13" Plastic reel

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics






Fig.4 Typical Forward Characteristics




PACKAGE OUTLINE DIMENSIONS

DO-214AB (SMC)




DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	2.90	3.20	0.114	0.126
B	6.60	7.11	0.260	0.280
C	5.59	6.22	0.220	0.245
D	2.00	2.62	0.079	0.103
E	1.00	1.60	0.039	0.063
F	7.75	8.13	0.305	0.320
G	0.10	0.20	0.004	0.008
H	0.15	0.31	0.006	0.012

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	3.30	0.130
B	2.50	0.098
C	6.80	0.268
D	4.40	0.173
E	9.40	0.370

MARKING DIAGRAM



- P/N =Marking Code
- G =Green Compound
- YW =Date Code
- F =Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.