

## PENTEK WPX-BB SERIES POLYPROPYLENE STRING-WOUND CARTRIDGES

DESIGNED FOR A VARIETY OF APPLICATIONS REQUIRING SEDIMENT REDUCTION



**Pentair<sup>†</sup> Pentek<sup>‡</sup> WPX-BB Series Cartridges are manufactured in 10" and 20" lengths and in 4.5" diameters from a durable polypropylene string that is wound around a rigid polypropylene core. The WPX-BB Cartridges are an economical solution to reduce fine sediment including rust, sand and scale particles.**

**The material in the WPX-BB Cartridges is a fibrillated polypropylene media wound in a precise pattern around a polypropylene core, providing greater surface area to maintaining high flow rates. The WPX-BB Cartridges are manufactured without any anti-static agent.**

**These string-wound cartridges are capable of withstanding temperatures up to 165°F (73.9°C), and will accommodate flow rates between 10 and 65 GPM with minimal pressure drop.**

**WPX-BB Series Cartridges are suitable for a wide range of sediment applications including municipal and well water, and are bacteria and chemical resistant so they can be used with many industrial fluids. WPX-BB Cartridges are recommended when foaming is an application issue.**

### FEATURES/BENEFITS

String-wound design reduces fine sediment from a variety of fluids

Bacteria and chemical resistant

Economically priced

Nominal 5, 10, 25, 50, 100 micron rating

Lengths: 10", 20"

### SPECIFICATIONS

Filter Media – fibrillated polypropylene fiber cord

Temperature Rating – 40-165°F (4.4-73.9°C)

## SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	RATING (NOMINAL)*	INITIAL ΔP (PSI) @ FLOW RATE (GPM)*
WPX5BB97P	355217-43	4.5" x 9.88" (114 mm x 251 mm)	5 micron	<16 psi @ 10 gpm (<1.1 bar @ 38 Lpm)
WPX10BB97P	355218-43	4.5" x 9.88" (114 mm x 251 mm)	10 micron	<12 psi @ 15 gpm (<0.8 bar @ 57 Lpm)
WPX25BB97P	355219-43	4.5" x 9.88" (114 mm x 251 mm)	25 micron	<10 psi @ 20 gpm (<0.7 bar @ 76 Lpm)
WPX50BB97P	355220-43	4.5" x 9.88" (114 mm x 251 mm)	50 micron	<8 psi @ 30 gpm (<0.6 bar @ 114 Lpm)
WPX100BB97P	355221-43	4.5" x 9.88" (114 mm x 251 mm)	100 micron	<8 psi @ 40 gpm (<0.6 bar @ 151 Lpm)
WPX100BB20P	355226-43	4.5" x 20" (114 mm x 508 mm)	100 micron	<8 psi @ 65 gpm (<0.6 bar @ 246 Lpm)

\*Based on manufacturer's internal testing.

**WARNING:** Do not use where water is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system.



### WATER QUALITY SYSTEMS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2015 Pentair Residential Filtration, LLC. All rights reserved.

†For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com](http://waterpurification.pentair.com).

Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

247670 REV B MY15