


RWS1000B-12/S<sup>New</sup>  
Product



<b>Sales Region</b>	Worldwide
<b>Series</b>	RWS-B
<b>Status</b>	 Production
<b>Feature</b>	
<b>Option</b>	Remote ON/OFF control Standby supply
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 340V
Efficiency	85% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	10.2 to 13.8V
Maximum Output Current	84A
Maximum Output Power	1008W

Cases Shape & Size	
Case'□ shape	Unit
Width(W)	127mm Nom.
Height(H)	63mm Nom.
Depth(D)	198mm Nom.
Weight	2000g Typ.

Other	
Operating Temp. Range	-20 to 60°C
Cooling	Blower fan cooling UL60950-1
Safety Standard(Certified)	CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	Den-an Appendix 12
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.