


| | |
|----------------------|--|
| Sales Region | Worldwide (except Japan) |
| Series | ALE |
| Model | ALE-Rack mount |
| Status |  Production |
| Option | Negative polarity |
| Option Lineup | Please refer to here. |
| Accessories | Please refer to the catalog |



Electrical Characteristics

| | |
|----------------------------------|---------------|
| Input | 3-phase |
| Input Voltage Range[AC] | 180 to 264VAC |
| Input Frequency Range | 47 to 63Hz |
| Rated Output Voltage[DC] | 10000Vdc |
| Output Voltage Range[DC] | 0 to 10000V |
| Average Capacitor Charging Power | 8000J/sec |
| Peak Capacitor Charging Power | 9000J/sec |
| Charge Current | 1.8A |
| Continuous DC Current | 800mA |
| Continuous DC Power | 8kW |
| Polarity | Negative |
| Power Factor | 0.85 |
| Efficiency | 85% Typ. |

Package Type & Size

| | |
|--------------------|---------------------------|
| Package / Mounting | Rack mount |
| Width(W) | 482mm Nom. (18.98in Nom.) |
| Height(H) | 222mm Nom. (8.74in Nom.) |
| Depth(D) | 432mm Nom. (17.01in Nom.) |
| Weight | 37kg Typ. (81.6lbs Typ.) |

Other

| | |
|----------------------------|-------------|
| Operating Temp. Range | -20 to 45°C |
| Storage Temp. Range | -40 to 85°C |
| Cooling | Forced air |
| Safety Standard(Certified) | |
| Safety Standard(Conformed) | |

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.