# Panel feed-through terminal block - HDFKV 25-VP-DP - 0708975

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



The figure shows a similar product

Panel feed-through terminal block, Connection method: Screw connection, Screw connection, Load current : 125 A, Cross section: 6 mm² - 35 mm², AWG 8 - 3, Width: 15.1 mm, Color: gray

## Key commercial data

| | |
|---|---|
| Packing unit | 1 1 |
| Weight per Piece (excluding packing) | 50.33 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Greece |

## Technical data

### General

| | |
|---|---|
| Number of levels | 1 |
| Number of connections | 2 |
| Color | gray |
| Insulating material | PA |
| Inflammability class according to UL 94 | V2 |
| Rated surge voltage | 6 kV |
| Pollution degree | 3 |
| Surge voltage category | III |
| Insulating material group | I |
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal current $I_N$ | 101 A |
| Nominal voltage $U_N$ | 500 V |
| Open side panel | nein |
| Number of positions | 1 |

### Dimensions

| | |
|---|---|
| Width | 15.1 mm |

### Connection data

# Panel feed-through terminal block - HDFKV 25-VP-DP - 0708975

## Technical data

### Connection data

| | |
|---|---|
| Note | Terminal sleeve |
| Connection side | Level 1 ext. 1 |
| Connection method | Screw connection |
| Conductor cross section solid min. | 6 mm² |
| Conductor cross section solid max. | 35 mm² |
| Conductor cross section stranded min. | 10 mm² |
| Conductor cross section stranded max. | 25 mm² |
| Conductor cross section AWG/kcmil min. | 10 |
| Conductor cross section AWG/kcmil max | 2 |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 4 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 25 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 4 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 25 mm² |
| 2 conductors with same cross section, solid min. | 2.5 mm² |
| 2 conductors with same cross section, solid max. | 10 mm² |
| 2 conductors with same cross section, stranded min. | 4 mm² |
| 2 conductors with same cross section, stranded max. | 10 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 2.5 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 10 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 2.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 10 mm² |
| Stripping length | 19 mm |
| Internal cylindrical gage | B8 |
| Screw thread | M5 |
| Tightening torque, min | 4 Nm |
| Tightening torque max | 4.5 Nm |
| Connection side | Level 1 int. 1 |
| Connection method | Screw connection |
| Conductor cross section solid min. | 6 mm² |
| Conductor cross section solid max. | 35 mm² |
| Conductor cross section stranded min. | 10 mm² |
| Conductor cross section stranded max. | 25 mm² |
| Conductor cross section AWG/kcmil min. | 10 |
| Conductor cross section AWG/kcmil max | 2 |

# Panel feed-through terminal block - HDFKV 25-VP-DP - 0708975

## Technical data

### Connection data

| | |
|---|---|
| Internal cylindrical gage | B8 |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141134 |
| eCl@ss 5.1 | 27141134 |
| eCl@ss 6.0 | 27141134 |
| eCl@ss 7.0 | 27141134 |
| eCl@ss 8.0 | 27141134 |

### ETIM

| | |
|---|---|
| ETIM 2.0 | EC001283 |
| ETIM 3.0 | EC001283 |
| ETIM 4.0 | EC001283 |
| ETIM 5.0 | EC001283 |

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

## Approvals

### Approvals

Approvals

UL Recognized / GOST / GOST

Ex Approvals

Approvals submitted

# Panel feed-through terminal block - HDFKV 25-VP-DP - 0708975

## Approvals

### Approval details

UL Recognized

| | B | C |
|---|---|---|
| mm²/AWG/kcmil | 8-2 | 8-2 |
| Nominal current IN | 115 A | 115 A |
| Nominal voltage UN | 600 V | 600 V |

GOST

GOST

© Phoenix Contact 2013 - all rights reserved
http://www.phoenixcontact.com