



特性: Specifications;
 电器: Electrical;
 接触阻抗: Contact Resistance
 30 millionms MAX

耐电压: Dielectric Withstanding Voltage:
 500v AC AT Sea Level
 绝缘阻抗: Insulation Resistance:
 1000 MEGA ohms MLN

机构: Mechanical;
 接合为: Mating Force;
 4.0 KG MAX 最大4Kg

拔出力: Unmating Force;
 0.7KG MIN.最少0.7KG

PART NO	H
U-A-24DD-Y-7	13.00
U-A-24DD-Y-8	13.70
U-A-24DD-Y-9	15.00

Recommended PCB Layout

③	Base	—	1	NYLON	White
②	Terminal	—	4	Phosphor Bronze	Ag Plated
①	Housing	—	1	SPCC/Phosphor Bronze	Ni Plated
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING

APPROVALS		DATE	TITLE:	
DRAWN	JIANKUN LU	2015.03.18	USB CONNECTOR	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	PROJ:
	A		NEW				30~以上 ±0.30 10~30 ±0.25 5~10 ±0.20 ~5 ±0.15	±2°	mm	1:1	PROJ: 1 OF 1