

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 124.17 USD



### Main

Range	Spacial
Product name	Spacial SBM
Device application	Multi-purpose
Category	Industrial box
Device short name	SBM
Enclosure type	Flat face box
Enclosure nominal height	11.81 in (300 mm)
Enclosure nominal width	23.62 in (600 mm)
Enclosure nominal depth	4.72 in (120 mm)
Enclosure mounting	Wall mounted
Device composition	1 cover 1 body 6 cover screw
Body type	Single piece body folded and welded
Type of front cover	Plain door
Cover fixing	Half turn metal screw
Lock type	Captive screw PZ2 outside sealed area
Removable parts	Cover by captive screws

### Complementary

Material	Sheet steel
Surface finish	Polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product certifications	LR DNV-GL

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

UL  
BV

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 IEC 62262
Ambient air temperature for storage	-31...140 °F (-35...60 °C)
Operating temperature	-31...176 °F (-35...80 °C)
Net Weight	14.82 lb(US) (6.724 kg)

### Ordering and shipping details

Category	80033 - ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	03606480520235
Nbr. of units in pkg.	1
Package weight(Lbs)	14.82 lb(US) (6.72 kg)
Returnability	No
Country of origin	IN

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	24.61 in (62.5 cm)
Package 1 width	12.40 in (31.5 cm)
Package 1 Length	5.91 in (15 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.

### Contractual warranty

Warranty	18 months
----------	-----------