



FCS-3096 Version: 1

**!** Power supply unit is to be ordered separately.

## Fixed Dome IP Network Camera, 8-Megapixel, H.265, 802.3af PoE, IR LEDs, two-way audio, Indoor/Outdoor, Vandalproof

The LevelOne FCS-3096 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP67 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3096 offers 8-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

### Key Features

- 8-Megapixel high-definition resolution
- Video compression: H.264, H.265
- Weatherproof IP67-rated housing
- Vandal-proof IK10-rated housing
- Built-in infrared LEDs for night viewing up to 50m
- Dual power support: 12V DC/PoE (IEEE 802.3af)
- Free surveillance and CMS (Central Management System) software packages with 64-channel license

### Specifications

#### System Specifications

##### Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6

##### Image Sensor:

1/2.5" Progressive Scan CMOS

##### Lens:

Fixed-focal, f=4mm, F2.0

##### Port:

1 x RJ-45 10/100 Mbps PoE port

Power Connector

Audio:In/Out

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

**Button/Knob:**

Reset Button

**Indicator:**

Power

**IR Cut Filter:**

Removable infrared-cut filter for day & night function

**IR LED:**

IR LEDs for illumination up to 30m

**Shutter Time:**

1/3 ~ 1/10,000 sec

**Angle of View:**

79°

**Video Compression:**

H.265, H.264

**Resolution:**

50Hz: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

**Output Video Format:**

AVI

**Audio Compression:**

G.711/G.722.1/G.726/MP2L2

64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-128Kbps(MP2L2)

**Power Input:**

12 VDC ± 25%, 6.2W

PoE(802.3af, class 3), 9W

**Power Consumption:**

6.2-9W

**Data Rate:**

32 Kbps to 16 Mbps

**Storage Capacity:**

Built-in microSD/SDHC/SDXC slot, up to 128 GB

## Features

**General:**

rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser.

**PoE:**

PoE(802.3af, class 3)

**Security:**

One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter

**Management:**

Behavior Analysis: Line crossing detection, intrusion detection, unattended baggage detection, object removal detection

Line Crossing Detection: Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported

Intrusion Detection: Enter and loiter in a pre-defined virtual region, up to 1 pre-defined virtual regions supported

Object Removal Detection: Objects removed from the pre-defined region, such as the exhibits on display.

Unattended Baggage Detection: Objects left over in the pre-defined region such as the baggage, purse, dangerous materials

Face Detection: Human face appears in the image can be detected and trigger linkage method.

**Video:**

Support 1 fixed region for mainstream and sub stream separately

**Audio:**

1 audio input (line in), 1 audio output

## Performance

**Number of Clients:**

16

**Frame Rate (fps):**

50Hz: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

**Minimum illumination:**

Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR

## Environment

**Operating Temperature (°C):**

-30 °C to +60 °C (-22 °F to +140 °F)

**Operating Humidity (Non-condensing):**

Humidity 95% or less

## Physical Specifications

**Dimensions (W x D x H mm):**

? 111 × 82.4 mm (? 4.4? × 3.2?)

**Weight (g):**

500

**Color:**

White

## Approval and Compliance

**EMI/EMS:**

CF/FCC

**Environmental Test:**

IP67, IK10

**Others:**

ONVIF

## Others

**Supported Browsers:**

Internet Explorer 9.0 or above

---

## Order Information

FCS-3096

---

## Package Contents

FCS-3096

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit



## Optional Accessory



**CAS-7301**  
Wall Mount Bracket



**CAS-7302**  
Wall mount bracket with Junction Box



**CAS-7303**  
Pole Mount Bracket, Clamping Range 2.6"-5"



**CAS-7304**  
Inclined Ceiling Mount Bracket




**CAS-7306**  
Pendant Mount Bracket



**CAS-7307**  
Corner Mount Bracket



**CAS-7309**  
Weather Shield



**CAS-7310**  
Junction box for Dome Camera

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.