
SHEET 1 OF 1




RECOMMENDED PANEL MOUNTING


PANEL THICKNESS	X
0.75-1.25	30.0-30.2
1.25-2.00	30.2-30.4
2.00-3.00	30.6-30.8


SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
OFF	NONE	(ON)
OPEN	N/A	1-1a, 2-2a


MOMENTARY = (ON)




CIRCUIT: DPST









NOTES:
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
▲4. RATING: 20A @125VAC 3/4HP UL APPROVED
   16A @250VAC 1HP UL APPROVED
   16A @ 250VAC 1HP VDE APPROVED (C)
5. ELECTRICAL LIFE: 10,000 CYCLES
6. MECHANICAL LIFE: 30,000 CYCLES
7. CONTACT RESISTANCE: <20 MILLI-OHMS INITIAL
8. DIELECTRIC STRENGTH: >1,500V AC 1MIN
9. INSULATION RESISTANCE: >1000MOHMS
10. OPERATING TEMP: TERMINAL SIDE: -20°C to 85°C
    ROCKER SIDE: -20°C to 55°C
12. ▲DENOTES CRITICAL PARAMETER.
13. 2002/95/EC (ROHS) COMPLIANT

REV	PCR NO	DESCRIPTION	DATE	BY
C	20139	ADD HP RATING	09/08/11	BMA
B	19784	UPDATE DRAWING	03/22/11	BMA
A	17388	RELEASED FOR PRODUCTION	06/20/07	TN

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E•SWITCH®

TITLE R5FBLKBLKEF0

SCALE	DATE	DR	DWG	REV
1:1	6/20/2007	TN	M050254	C