

Data Sheet

FUJITSU Desktop ESPRIMO P910-L

Combines Longevity with Highest Reliability

FUJITSU ESPRIMO P910-L PCs give you maximum expandability to satisfy your ultimate upgradeability needs. With extended Windows XP driver support this PC facilitates long-term projects and prolonged product lifecycle. Its sophisticated product concept ensures reliable 24/7 operations and the lowest failure rates. Intel® vPro™ technology lowers your TCO. The 90%-efficient integrated power supply cuts your energy bill. Plus, EraseDisk ensures secure system retirement.

Long lifecycle

Continuity and availability for long-term projects

- Microsoft® Windows XP driver support extends the lifecycle up to 24 months

Extended usage scenarios

Highest PC reliability and extended capabilities

- Selected components are optimized for 24/7 operations and the PC supports an extended temperature range of up to 40°C

Expandability

Microtower chassis for optimum expandability

- High-quality microtower, 7 drive bays, 1 PCI legacy interface/ 3 PCI express interfaces

Green technology

Fujitsu's contribution to environmental protection and sustainability

- Halogen-free mainboard and highly energy-efficient power supply, sophisticated product concept supporting a stable lifecycle

System management

Simple system administration for complex IT infrastructures

- Intel® vPro™ technology (depending on processor) combined with the DeskView manageability suite



Components

Processor	Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) * Intel® Core™ i5-3550s processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.7 GHz, 6 MB, Intel® HD Graphics 4600) * Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500) Intel® Pentium® processor G2120 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics) Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
Operating systems	
Operating system	Windows 8.1 Pro Windows 8.1 Windows 7 Professional 64-bit Windows 7 Professional 32-bit
Operating system compatible	Windows 10 Pro (license + recovery media only) openSUSE Linux Windows® XP Citrix XenClient™ 2
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM 8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
Hard disk drives (internal)	SSD SATA III Premium, 256 GB, 2.5-inch SSD SATA III Premium, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch, SED SSD SATA III, 128 GB, 2.5-inch, SED SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch HDD SATA II, 5,400 rpm, 320 GB, 2.5-inch
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
Graphics	NVIDIA® NVS™ 315, 1 GB NVIDIA® GeForce® GTX 745 2 GB FH, 2 GB NVIDIA® GeForce® GT630 DisplayPort 2GB FH "0-Watt", 2 GB NVIDIA® GeForce® 605 DisplayPort 1GB FH, 1 GB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DVI-I to VGA Adapter DP to DVI-D (single link) Adapter Cable AMD® Radeon R9 255 FH, 2 GB

Drives (optional)	BD Triple Writer SATA slim (tray)
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 24in1 USB 2.0 3.5"

Interface add on cards/components (optional)

Parallel Interface
Gigabit Ethernet PCIe x1, DS
eSATA Interface
Dual serial card PCIe x1

Base unit

Base unit	ESPRIMO P910-L
-----------	----------------

Mainboard

Mainboard type	D3162
Formfactor	µATX
Chipset	Intel® Q77
Processor socket	LGA 1155
Processor quantity maximum	1
Supported capacity RAM (max.)	32 GB
Memory slots	4 DIMM (DDR3)
Memory frequency	1,600 MHz
Memory notes	Dual channel support For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.

LAN	10/100/1,000 MBit/s Intel® 82579 LM
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound

I/O controller on board

Serial ATA total	6
thereof SATA III	2
thereof eSATA	2
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10 (Windows XP not supported) Intel® Smart Response Technology (depending on CPU)

Interfaces

Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	10

Interfaces

USB 3.0 total	4
USB front	2x 2.0/ 2x 3.0
USB rear	6x 2.0 / 2x 3.0
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	2 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO

Drive bays

Drive bays total	7
2.5-inch internal bays	1
3.5-inch internal bays	2
3.5-inch external bays	2
5.25-inch external bays	2

Slots

PCI-Express 3.0 x16	1 x (312 mm / 12.29 inch) Full height
PCI-Express 2.0 x4 (mech. x16)	1 x (312 mm / 12.29 inch) Full height
PCI-Express x1	1 x (312 mm / 12.29 inch) Full height
PCI (32-bit / 33 MHz)	1 x (170 mm / 6.7 inch) Full height

Graphics on board

Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
Shared video memory	up to 1,759 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DVI)	1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel

Graphics on board

Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.3 (depending on CPU) Open CL® 1.1 (depending on CPU) For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows® 7 or Windows 8)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 88% / 92% / 91%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=4496ccf5-f069-47f9-b185-4dd60e0997c7

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Core i5-3770
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise operation mode: CPU 50% load	3.6 B / 22 dB(A) Bystander; 26 dB(A) Operator position
Standard noise operation mode: HDD load	3.6 B / 23 dB(A) Bystander; 25 dB(A) Operator position
Standard noise operation mode: Idle mode	3.3 B / 19 dB(A) Bystander; 22 dB(A) Operator position
Standard noise operation mode: ODD load	4.6 B / 32 dB(A) Bystander; 37 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.4 B / 19 dB(A) Bystander; 22 dB(A) Operator position
Blue angel noise emission according certification	for max. possible configuration According to ISO 7779:2010, ECMA-74
Blue angel noise notes / description	Bystander position
Blue angel noise operation mode: HDD load	4.0 B = 40 dB
Blue angel noise operation mode: Idle mode	3.7 B = 37 dB
Blue angel noise operation mode: ODD load	4.6 B = 46 dB

Dimensions / Weight / Environmental

Dimensions (W x D x H)	175 x 419 x 395 mm 6.89 x 16.5 x 15.56 inch
Operating position	Vertical
Weight	11 kg

Dimensions / Weight / Environmental

Weight (lbs)	24.25 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 40 °C (50 - 104 °F)

Compliance

Product	ESPRIMO P910-L
Model	M15W
Germany	TÜV GS Blauer Engel / Blue Angel
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 in progress EPEAT® in progress (dedicated regions)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates

Compatibility (references)

DMI 2.0
PC 2001
WMI 1.5
USB 2.0
SMBIOS

Additional Software

Additional software (preinstalled)	Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT 8.0 (depending on CPU) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Manageability link	http://www.fujitsu.com/fts/manageability

Security

Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
--------------------------	--

Security	
System and BIOS Security	EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)



Miscellaneous	
	Extended lifetime 24/7 (limited configurations) Keyboard on (Special Fujitsu keyboard required) Thermal management

Serviceability	
	EasyFix EasyChange for 3.5" HDD EasyChange for optical drives

Packaging information	
Packaging dimension (mm)	516 x 278 x 562 mm
Packaging dimension (inch)	20.31 x 10.94 x 22.13 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1280 g
Material - Weight (lbs) Carton	2.82 lbs
Material - Weight (g) EPS / PS	190 g
Material - Weight (lbs) EPS / PS	0.42 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty	
Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Mouse M440 ECO		Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.	Order Code: S26381-K450-L200
SOUNDSYSTEM DS E2000 Air		The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600

Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The S26381-K341-L1** (**: keyboard is made out of 45% renewable raw material and comes with a PVC country specific variation) free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Desktop ESPRIMO P910-L, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO P910-L, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions GmbH
Website: www.fujitsu.com/fts
2016-07-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH