
2016-11-09
Product version 00
Document revision 0

Data sheet

Order No.: 1848710

Type: SDDC 1,5/ 9-PV-3,5

Plug component, Push-in spring connection



The illustration shows the 5-pos. version

1 Main features



- Number of positions 9
- Conductor cross section 1.5 mm²
- Color green
- Pitch 3.50 mm
- Connection method Push-in spring connection
- Nominal current 8 A
- Nominal voltage 160 V
- Connection direction 0 °
- Type of packaging packed in cardboard

2 Your advantages

- SKEDD direct plug-in technology enables flexible positioning on the PCB
- Reduced component and process costs: simple insertion by hand and vibration-resistant connection
- Time saving push-in connection, tools not required
- Intuitive use through colour coded actuation lever
- Quick and convenient testing using integrated test option

Make sure you always use the latest documentation.
It can be downloaded at: phoenixcontact.net/product/1848710

© PHOENIX CONTACT 2016

3 Table of contents

1 Main features ... 1
2 Your advantages ... 1
3 Table of contents ... 2
4 3D model in PDF can be activated (Acrobat Reader only) ... 3
5 Item properties ... 4
5.1 Material data ... 4
5.2 Dimensions ... 4
6 Series drawing ... 5
7 Packaging information ... 6
8 Application ... 6
8.1 Temperature limit values ... 6
9 Mechanical tests ... 7
9.1 Pull-out test ... 7
10 Electrical tests ... 8
10.1 Electrical data ... 8
10.2 Air and creepage distances ... 8
10.3 Electrical function ... 8
10.4 Temperature cycles ... 8
11 Current carrying capacity/derating curves ... 9
12 Environmental and durability tests ... 10
12.1 Vibration test ... 10
13 Classification for connectors ... 10
14 Approvals ... 10
15 Commercial data ... 10
16 Project documentation ... 10
17 Accessories ... 10
17.1 Combination tests ... 12

© PHOENIX CONTACT 2016

4 3D model in PDF can be activated (Acrobat Reader only)



© PHOENIX CONTACT 2016

5 Item properties

Order No.	1848710
Type	SDDC 1,5/ 9-PV-3,5
Range of articles	SDDC 1,5/..-PV
Pitch	3.50 mm
Number of positions	9
Connection method	Push-in spring connection
Mounting type	SKEDD - Direct plug-in technology
Pin layout	Linear double pinning

5.1 Material data

Material of metal parts		
Note	WEEE/RoHS-compliant, whisker-free acc. to IEC 60068-2-82/JEDEC JESD 201	
Contact material	Cu alloy	
Terminal point surface	Sn 4 µm ... 8 µm	
Surface contact area	Sn 4 µm ... 8 µm	
Surface characteristics	hot-dip tin-plated	


Insulating material data	Housing	
Insulating material	PA	PBT
CTI according to IEC 60112	600	600
Flammability rating according to UL 94	V0	V0
Color	green (6021)	
Glow wire flammability index GWFI according to EN 60695-2-12	850	
Glow wire ignition temperature GWIT according to EN 60695-2-13	775	
Temperature for the ball pressure test according to EN 60695-10-2	125 °C	

5.2 Dimensions

Dimension a	28 mm
Length	13.5 mm
Width	38.8 mm
Total height	17.6 mm
Pin dimensions	0,9 x 2,0 mm
Pin spacing	7.00 mm
Hole diameter	1.6 mm

© PHOENIX CONTACT 2016

6 Series drawing



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless expressed consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.

© PHOENIX CONTACT 2016

7 Packaging information

Type of packaging	packed in cardboard
Pieces per package	100

8 Application

8.1 Temperature limit values

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C

© PHOENIX CONTACT 2016

9 Mechanical tests

9.1 Pull-out test

Termination and connection method: pull-out test	
Specification	IEC 60999-1:1999-11
Result	Test passed
Conductor cross section/conductor type/tractive force actual value	0.2 mm² / solid / > 10 N
Conductor cross section/conductor type/tractive force actual value	0.2 mm² / stranded / > 10 N
Conductor cross section/conductor type/tractive force actual value	1.5 mm² / solid / > 40 N
Conductor cross section/conductor type/tractive force actual value	1.5 mm² / stranded / > 40 N
Conductor cross section/conductor type/tractive force actual value	AWG 16 / stranded / > 40 N

© PHOENIX CONTACT 2016

10 Electrical tests

10.1 Electrical data

Rated current / conductor cross section	8 A / 1.5 mm²
Rated insulation voltage (III/2)	160 V
Rated surge voltage (III/2)	2.5 kV
Contact resistance	1.4 mΩ
Degree of pollution	2

10.2 Air and creepage distances

Component	Plug component		
Specification	IEC 60664-1:2007-04		
Mains type	unearthed mains		
Insulating material group	I		
Comparative tracking index (IEC 60112:2003-01)	CTI 600		
Rated insulation voltage	160 V	160 V	400 V
Rated surge voltage	2.5 kV	2.5 kV	2.5 kV
Degree of pollution	3	2	2
Overvoltage category	III	III	II
Minimum clearance case A (inhomogeneous field)	1.5 mm	1.5 mm	1.5 mm
Minimum value of the creepage path requirement in acc. with table	2 mm	0.8 mm	2 mm

10.3 Electrical function

Specification	IEC 60999-1:1999-11
Result	Test passed
Voltage drop	Voltage drop (U) after the load ≤ 15 mV
Conductor cross section, flexible	
Conductor cross section, solid	

10.4 Temperature cycles

Specification	IEC 60999-1:1999-11
Result	Test passed
Voltage drop	Voltage drop (U) after the load ≤ 22.5 mV or 1.5 x $U_{\text{after 24 h}}$ The small value is to be used.
Test current	4 A DC
Temperature cycles	
Conductor cross section, flexible	
Conductor cross section, solid	

© PHOENIX CONTACT 2016

11 Current carrying capacity/derating curves

Specification	IEC 61984:2008-10
Note	Representation based on IEC 60512-5-2:2002-02
Reduction factor	0.8
Number of positions	See diagram
Conductor cross section	1.5 mm²

Type: SDDC 1,5/...-PV-3,5

© PHOENIX CONTACT 2016

12 Environmental and durability tests

12.1 Vibration test

Specification	IEC 60068-2-6:2007-12
Result	Test passed
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 - 60.1 Hz)
Acceleration	5 g (60.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis
Requirements	
Note	

13 Classification for connectors

Specification	IEC 61984:2008-10
Main features	Connectors without switching capacity (COC)
Construction form	Fixed connectors
Strain relief elements	without strain relief
Connection method	Can be reconnected
Protection against electric shock	Not encapsulated - touch-proof when inserted
Protective conductor	without PE
Lock	no
Connection method	Screwless terminal points

14 Approvals

15 Commercial data

Order No.	1848710
Type	SDDC 1,5/ 9-PV-3,5
Pieces per package	100
Net weight	2.22 g
GTIN	4055626307183
Customs tariff number	Information that applies locally, see link on page 1
Country of origin	Information that applies locally, see link on page 1

16 Project documentation

Project documentation	M6

17 Accessories

Description	Order No.	Type
Coding profile, is inserted into the hole in the plug, red insulating material	1985564	CP-PT 1,5
	0804073	SK 3,5/2,8:FORTL.ZAHLEN
	0825121	SK 2,8 REEL P3,5 WH CUS
	0803883	SK U/2,8 WH:UNBEDRUCKT


© PHOENIX CONTACT 2016

1848710 SDDC 1,5/ 9-PV-3,5

Description	Order No.	Type
	0805205	SK 2,8 WH:REEL
	1944372	MPS-MT 1-S
	1982800	MPS-MT 1-S4-B RD
Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm² ... 6.0 mm², lateral entry, trapezoidal crimp	1212034	CRIMPFOX 6
	3203037	AI 0,25- 8 YE
	3200014	AI 0,5 - 8 WH
	3200881	AI 0,5 - 8 WH -1000
	3201275	AI 0,5 -10 WH
	3201288	AI 0,75-10 GY
	3200182	AI 1 -10 RD
	3202481	A 0,5 - 8
	3202494	A 0,5 -10
	3202504	A 0,75- 8
	3200234	A 0,75-10
	3202517	A 1 - 8
	3200250	A 1 -10

© PHOENIX CONTACT 2016

17.1 Combination tests



SDDC 1,5/..-PV

Specification	IEC 61984			
Mechanical tests (A)				
Insertion/withdrawal force per position	approx. 8 N / 6 N			
Polarization when inserted Requirement > 20 N	Test passed			
Contact holder in insert Requirements > 20 N				
Endurance tests (B)				
Contact resistance R_1	1.4 mΩ			
Insertion/withdrawal cycles	25			
Contact resistance R_2	1.5 mΩ			
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 µs)	2.95 kV			
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	1.39 kV			
Insulation resistance Requirements > 5 MΩ	> 0.2 TΩ			
Thermal tests (C)				
Tested number of positions	16			
Tested conductor cross section	1.5 mm^2			
Test current	8 A			
Upper limiting temperature Requirements < 100°C	Test passed			
Climatic tests (D)				
Test sequence 1: low temperature storage	-40 °C/2 h			
Test sequence 2: heat storage	100 °C/168 h			
Test sequence 3: noxious gas storage (ISO 6988)	0.2 dm^3 SO_2 on 300 dm^3/ 40 °C/1 cycle			
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 µs)	2.95 kV			
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	1.39 kV			
Environmental and endurance tests (E)				
Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08			
Type of protection (when plugged in)	Finger safety with IP20 test finger			

© PHOENIX CONTACT 2016