

## Electronic housing - ME 22,5 UT BUS/10+2 GN - 2915232

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Component housing with vents, Lower part, Cross connection: integrated bus connector, Color: green, Width: 22.5 mm, Constructional height: 114.5 mm, Number of positions cross connector: 10+2

### Why buy this product

- Item is from the ME product range
- Tool-free mounting
- Available in overall widths from 12.5 mm to 90 mm, modular extension is possible
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail
- Optional bus connector that is either integrated or mounted on the DIN rail

### Key Commercial Data

Packing unit	1 STK
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Environmental Product Compliance

China RoHS	No hazardous substances above threshold values
------------	--

#### General

Housing type	Component housing
Housing material	Polyamide
Color	green

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

## Electronic housing - ME 22,5 UT BUS/10+2 GN - 2915232

### Technical data

#### Dimensions

Length	99 mm
Constructional height	114.5 mm
Width	22.5 mm

#### Technical data

Flammability rating according to UL 94	V0
Number of positions	16
	24
	4

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Classifications

#### eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

#### ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Electronic housing - ME 22,5 UT BUS/10+2 GN - 2915232

### Approvals

Approvals

---

Approvals


UL Recognized

---

Ex Approvals

---

### Approval details

UL Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 240868

### Accessories

Accessories

Filler plug

Electronic housing - ME B-KA - 2854173



Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS terminal opening, (male side)

---

Electronic housing - ME B-SA/NS 35 - 2935959

Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS male side, (female side)



## Electronic housing - ME 22,5 UT BUS/10+2 GN - 2915232

### Accessories

Electronic housing - ME B-SA/NS 35 - 2935959

Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS male side, (female side)



---

### Mounting material

Electronic housing - ME DH27 NS 35 - 2908760

Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 27 mm



Electronic housing - ME DH36 NS 35 - 2909895

Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 36 mm



Electronic housing - ME LPZS - 2906911



Component housing

Printed-circuit board connector - MCVR 1,5/10-ST-3,81 AU - 1893216



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 10, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Gold

## Electronic housing - ME 22,5 UT BUS/10+2 GN - 2915232

### Accessories

Printed-circuit board connector - MC 1,5/10-ST-3,81 AU - 1879599



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 10, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Gold

Printed-circuit board connector - IMC 1,5/10-ST-3,81 AU - 1943289



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 10, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Gold

Printed-circuit board connector - MCVR 1,5/ 2-ST-3,81 AU - 1940680



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 2, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Gold

Plug - MC 1,5/ 2-ST-3,81 AU - 1851999



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 2, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Gold

Printed-circuit board connector - IMC 1,5/ 2-ST-3,81 AU - 1943263



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 2, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Gold

### Necessary add-on products

## Electronic housing - ME 22,5 UT BUS/10+2 GN - 2915232

### Accessories

Electronic housing - ME 22,5 OT-1MSTBO GN - 2709558



Component housing, Upper part, Color: green, Width: 22.5 mm, Constructional height: 38.5 mm

---

Electronic housing - ME 22,5 OT-MSTBO GN - 2907169



Component housing, Upper part, Color: green, Width: 22.5 mm, Constructional height: 38.5 mm

---

Electronic housing - ME 22,5 OT-MKDSO GN - 2907172



Component housing, Upper part, Color: green, Width: 22.5 mm, Constructional height: 38.5 mm

---

---