Creation Date : September 17, 2020 (GMT)

AC-DC Power Supplies

QS70004B

RoHS

Sales Region	Worldwide (except Japan)
Series	QS
Model	QS7
Status	Production
Feature	Medical for Medical instruments 2MOPP 2MOPP MIL-STD MIL-STD-810G Vibration and Shock
Options	Product is fully configurable
Option Lineup	
Recommended EMC Filter	
Accessories	Please refer to the catalog

Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac 180 to 264Vac
Input Voltage Range[DC]	
Efficiency	91% Typ.
Rated Output Voltage[DC]	48Vdc
Output Voltage Range[DC]	48 to 52.8Vdc
Maximum Output Current	25A
Maximum Output Power	1200W

Package Type & Size	
Package / Mounting	Enclosed / Unit type
Width(W)	270mm Nom. (10.63in Nom.)
Height(H)	63.3mm Nom. (2.49in Nom.)
Depth(D)	176mm Nom. (6.93in Nom.)
Weight	

Other	
Operating Temp. Range	-20 to 70°C
Cooling	Forced air

Safety Standard(Certified)	IEC60601-1 CSA60601-1 EN60601-1 ES60601-1 UL60601-1 IEC60950-1 CSA60950-1 EN60950-1 UL60950-1 IEC61010-1 EN61010-1 IEC62368-1 CSA62368-1 EN62368-1 UL62368-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.