



2~5A

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material:Wafer Nylon46,UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-XA-2AW	2.50	7.50
HC-XA-3AW	5.00	10.00
HC-XA-4AW	7.50	12.50
HC-XA-5AW	10.00	15.00
HC-XA-6AW	12.50	17.50
HC-XA-7AW	15.00	20.00
HC-XA-8AW	17.50	22.50
HC-XA-9AW	20.00	25.00
HC-XA-10AW	22.50	27.50
HC-XA-11AW	25.00	30.00
HC-XA-12AW	27.50	32.50

PCB LAYOUT

GENERAL TOLERANCE		制 图 DRAWING 2013、07、01	料 号	HC-XA-NAW		版 本	A
X.±0.25	X.'±2'		PART NO.	XA-AW		REV.	
.X±0.20	.X'±1'		审 核	WAFER DIP TYPE		页 次	1/1
.XX±0.15	.XX'±0.5'		CHECK	客 户 料 号			SHEET
.XXX±0.10	.XXX'±0.5'	核 准 APPROVAL	CUTM. NO.				
		单 位 UNITS	深 圳 市 华 灿 天 禄 电 子 有 限 公 司				
		MM	比 例 SCALE	1:1			