



PART NO.	DIM. "A"	DIM. "B"	DIM. "C"	THREAD "S"/"I"	DIM. "F"
NTS-7	.28 (7.0)	.24 (6.0)	.25 (6.3)	M3/M3	.24 (6.0)
NTS-8	.31 (8.0)				
NTS-9	.35 (9.0)		.24 (6.0)		
NTS-10	.39 (10.0)		.24 (6.1)		
NTS-11	.43 (11.0)		.25 (6.4)		
NTS-12	.50 (12.7)		.24 (6.1)		
NTS-16	.63 (16.0)		.24 (6.0)		
NTS-17.5	.69 (17.5)		.24 (6.1)		
NTS-20	.79 (20.0)		.26 (6.5)		
NTS-25	.98 (25.0)		.24 (6.0)		
NTS-15A	.59 (15.0)	.31 (8.0)	.22 (5.5)	M4/M4	.31 (8.0)
NTS-19	.75 (19.1)				
NTS-37	1.46 (37.1)				

NOTES:

- MATERIAL: NYLON 6/6.  
FLAME RETARDANT NYLON (RMS-146),  
AVAILABLE BY SPECIAL ORDER.  
TO ORDER ADD "-146" AS SUFFIX.
- COLOR: NATURAL.

D SEE CO 200041 FOR CHANGES SK 09.28.07			TITLE: NYLON THREADED SPACERS			DWG IN IN (MM) FINAL			
C SEE ECN #522 FOR CHANGES SM 11.14.02			FILE # NTS			DWN: P.B.		APP:	
B CHANGED FILE NO. SM 06.07.02			MAT'L: SEE NOTES			DT: 07-24-95		DT:	
A REMOVED RMS-01 SM 02.09.01			RE: RICHCO, INC.			RICHCO INC.		PART #	
REV DESCRIPTION ENGR DATE			TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1°			PO BOX 804238, CHICAGO, 60680 (773) 539-4060		SEE TABLE	
								PRINT TYPE CA	