
CW INDUSTRIES
130 James Way
Southampton, PA 18966
Phone: 215-355-7080 • **Fax:** 215-355-1088
Email: info@cwind.com • **Website:** http://www.cwind.com



Item # GRB258GSERIES, GRB Series Full Size Sealed Rocker Switches

Specifications · Materials · Technical Information

Specifications

Circuitry	SPDT
Switch Function	(ON)-OFF-(ON)
Electrical Ratings	10 A @ 24 VAC 10 A @ 250 VAC 20 A @ 125 VAC 20 A @ 14 VAC 3/4 HP @ 125 VAC 3/4 HP @ 250 VAC
IP Level	56
Mounting	36.8 x 15.3
Actuator Color	Amber Black Green Red
Housing Color	Black
C1	N
Polarization	N
Actuator Legend	Various
Illumination	Non Illuminated
Terminal	0.250 Quick Connect (SQ)
Fitting	Snap-In
Options	 Reference Lamp Chart larger image
Optional Connector	Not Available
Compliance	.

Materials

Frame Material	Nylon (UL: 94V-2)
Actuator Material	Nylon (UL: 94V-2) PC (UL: 94V-2)
Terminal Material	Copper Alloy Silver Plated

Technical Information

Operating Temperature	-20 to 85 ºC
Maximum Contact Resistance	50m ohm
Minimum Insulation Resistance	DC 500VM 100M OHM
Dielectric Strength (AC) (1 Minute)	1500 ºC
Mechanical Life	> 100,000 Cycles
Maximum Solderability of Terminals (Per 3 Seconds)	350 ºC