

Null Modem Serial DB9 Serial Cable (DB9 F/F), 10-ft.

MODEL NUMBER: **P450-010**



Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 10FT cable has a DB9 female connector on each end. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

Features

- DB9 female to DB9 female
- Full Handshake Null wiring configuration: 1+6 - 4, 2-3, 3-2, 4 - 1+6, 5-5, 7-8, 8-7.
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity

Specifications

OVERVIEW	
Cable Type	Modem/Null Modem
INPUT	
Cable Length (ft.)	10
Cable Length (m)	3.05
PHYSICAL	
Color	Black
CONNECTIONS	

Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

System Requirements

- Two serial devices with DB9M connectors requiring a null modem (cross-wired) configuration

Package Includes

- 10FT Null Modem Gold Cable DB9F to DB9F



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Connector A	DB9 (FEMALE)
Connector B	DB9 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.